

Autotask API Data Model

for use with Invantive SQL

24.0

invantive
the SQL company

Copyright

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

Important Safety and Usage Information

Intended Use and Limitations: This software, developed by Invantive, is designed to support a variety of business and information technology data processing functions, such as accounting, financial reporting an sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- Nuclear facilities: The software should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.
- Defense and Military Applications: This software is not suitable for use in defense-related applications, including but not limited to weaponry control, military strategy planning, or any other aspects of national defense.
- Aviation: The software is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.
- Healthcare and Medicine Production: This software should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.
- Chemical and Hazardous Material Handling: This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.
- Transportation and Traffic Control Systems: The software should not be used for the control, operation, or management of transportation systems, including railway signal controls, subway systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.
- Energy Grid and Utility Control Systems: This software is not designed for the control or operation of energy grid systems, including electrical substations, renewable energy control systems, or water utility control systems. The failure of software in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.
- Other High-Risk Environments: Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

User Responsibility: Users must ensure that they understand the intended use of the software and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the software for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment.
Disclaimer of Liability: Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this software in prohibited or unintended applications.

Contents

1 SQL Driver for Autotask API 1

2 SQL Driver Attributes for Autotask API 2

3 Schema: ActionTypes 17

3.1 Tables 17
3.1.1 ActionTypes 17
3.1.2 ActionTypesById 17
3.1.3 ActionTypesCount 18

4 Schema: AdditionalInvoiceFieldValues 18

4.1 Tables 18
4.1.1 AdditionalInvoiceFieldValues 18
4.1.2 AdditionalInvoiceFieldValuesById 19
4.1.3 AdditionalInvoiceFieldValuesCount 20

5 Schema: ApiVersion 20

5.1 Tables 20
5.1.1 VersionInformation 20

6 Schema: Appointments 20

6.1 Tables 20
6.1.1 Appointments 20
6.1.2 AppointmentsById 21
6.1.3 AppointmentsCount 22

7 Schema: ArticleAttachments 22

7.1 Tables 22
7.1.1 ArticleAttachments 22
7.1.2 ArticleAttachmentsById 23
7.1.3 ArticleAttachmentsCount 25

8 Schema: ArticleAttachmentsChild 25

8.1 Tables 25
8.1.1 KnowledgeBaseArticlesByParentIdAttachments 25
8.1.2 KnowledgeBaseArticlesByParentIdAttachmentsId 27

9 Schema: ArticleConfigurationItemCategoryAssociations 28

9.1 Tables 28
9.1.1 ArticleConfigurationItemCategoryAssociations 28
9.1.2 ArticleConfigurationItemCategoryAssociationsById 29
9.1.3 ArticleConfigurationItemCategoryAssociationsCount 30

10 Schema: ArticleConfigurationItemCategoryAssociationsChild 30

10.1 Tables 30
10.1.1 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociations 30

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

10.1.2 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsId ... 30

11 Schema: ArticleNotes 31

11.1 Tables ... 31
11.1.1 ArticleNotes ... 31
11.1.2 ArticleNotesById ... 32
11.1.3 ArticleNotesCount ... 33

12 Schema: ArticleNotesChild 34

12.1 Tables ... 34
12.1.1 KnowledgeBaseArticlesByParentIdNotes ... 34
12.1.2 KnowledgeBaseArticlesByParentIdNotesId ... 35

13 Schema: ArticlePlainTextContent 36

13.1 Tables ... 36
13.1.1 ArticlePlainTextContent ... 36
13.1.2 ArticlePlainTextContentById ... 37
13.1.3 ArticlePlainTextContentCount ... 38

14 Schema: ArticlePlainTextContentChild 38

14.1 Tables ... 38
14.1.1 KnowledgeBaseArticlesByParentIdPlainTextContent ... 38
14.1.2 KnowledgeBaseArticlesByParentIdPlainTextContentId ... 39

15 Schema: ArticleTagAssociations 40

15.1 Tables ... 40
15.1.1 ArticleTagAssociations ... 40
15.1.2 ArticleTagAssociationsById ... 41
15.1.3 ArticleTagAssociationsCount ... 42

16 Schema: ArticleTagAssociationsChild 43

16.1 Tables ... 43
16.1.1 KnowledgeBaseArticlesByParentIdTagAssociations ... 43
16.1.2 KnowledgeBaseArticlesByParentIdTagAssociationsId ... 44

17 Schema: ArticleTicketAssociations 45

17.1 Tables ... 45
17.1.1 ArticleTicketAssociations ... 45
17.1.2 ArticleTicketAssociationsById ... 46
17.1.3 ArticleTicketAssociationsCount ... 47

18 Schema: ArticleTicketAssociationsChild 47

18.1 Tables ... 47
18.1.1 KnowledgeBaseArticlesByParentIdTicketAssociations ... 47
18.1.2 KnowledgeBaseArticlesByParentIdTicketAssociationsId ... 48

19 Schema: ArticleToArticleAssociations 49

19.1 Tables ... 49
19.1.1 ArticleToArticleAssociations ... 49
19.1.2 ArticleToArticleAssociationsById ... 50
19.1.3 ArticleToArticleAssociationsCount ... 51

20 Schema: ArticleToArticleAssociationsChild 51

20.1 Tables ... 51
20.1.1 KnowledgeBaseArticlesByParentIdArticleAssociations ... 51

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

20.1.2 KnowledgeBaseArticlesByParentIdArticleAssociationsId ... 52

21 Schema: ArticleToDocumentAssociations 53

21.1 Tables ... 53
21.1.1 ArticleToDocumentAssociations ... 53
21.1.2 ArticleToDocumentAssociationsById ... 54
21.1.3 ArticleToDocumentAssociationsCount ... 55

22 Schema: ArticleToDocumentAssociationsChild 55

22.1 Tables ... 55
22.1.1 KnowledgeBaseArticlesByParentIdDocumentAssociations ... 55
22.1.2 KnowledgeBaseArticlesByParentIdDocumentAssociationsId ... 57

23 Schema: AttachmentInfo 58

23.1 Tables ... 58
23.1.1 AttachmentInfo ... 58
23.1.2 AttachmentInfoById ... 59
23.1.3 AttachmentInfoCount ... 61

24 Schema: AutotaskVersionApiIntegration 61

24.1 Tables ... 61
24.1.1 Version ... 61

25 Schema: BillingCodes 61

25.1 Tables ... 61
25.1.1 BillingCodes ... 61
25.1.2 BillingCodesById ... 62
25.1.3 BillingCodesCount ... 63

26 Schema: BillingItemApprovalLevels 64

26.1 Tables ... 64
26.1.1 BillingItemApprovalLevels ... 64
26.1.2 BillingItemApprovalLevelsById ... 64
26.1.3 BillingItemApprovalLevelsCount ... 65

27 Schema: BillingItems 65

27.1 Tables ... 65
27.1.1 BillingItems ... 65
27.1.2 BillingItemsById ... 67
27.1.3 BillingItemsCount ... 69

28 Schema: ChangeOrderCharges 70

28.1 Tables ... 70
28.1.1 ChangeOrderCharges ... 70
28.1.2 ChangeOrderChargesById ... 71
28.1.3 ChangeOrderChargesCount ... 72

29 Schema: ChangeRequestLinks 73

29.1 Tables ... 73
29.1.1 ChangeRequestLinks ... 73
29.1.2 ChangeRequestLinksById ... 73
29.1.3 ChangeRequestLinksCount ... 74

30 Schema: ChecklistLibraries 74

30.1 Tables ... 74

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

30.1.1 ChecklistLibraries ... 74
30.1.2 ChecklistLibrariesById ... 75
30.1.3 ChecklistLibrariesCount ... 76

31 Schema: ChecklistLibraryChecklistItems 76

31.1 Tables ... 76
31.1.1 ChecklistLibraryChecklistItems ... 76
31.1.2 ChecklistLibraryChecklistItemsById ... 77
31.1.3 ChecklistLibraryChecklistItemsCount ... 78

32 Schema: ChecklistLibraryChecklistItemsChild 78

32.1 Tables ... 78
32.1.1 ChecklistLibrariesByParentIdChecklistItems ... 78
32.1.2 ChecklistLibrariesByParentIdChecklistItemsId ... 79

33 Schema: ClassificationIcons 81

33.1 Tables ... 81
33.1.1 ClassificationIcons ... 81
33.1.2 ClassificationIconsById ... 81
33.1.3 ClassificationIconsCount ... 82

34 Schema: ClientPortalUsers 82

34.1 Tables ... 82
34.1.1 ClientPortalUsers ... 82
34.1.2 ClientPortalUsersById ... 83
34.1.3 ClientPortalUsersCount ... 84

35 Schema: ComanagedAssociations 84

35.1 Tables ... 84
35.1.1 ComanagedAssociations ... 84
35.1.2 ComanagedAssociationsById ... 85
35.1.3 ComanagedAssociationsCount ... 86

36 Schema: Companies 86

36.1 Tables ... 86
36.1.1 Companies ... 86
36.1.2 Companies_ItemsUserDefinedFields ... 88
36.1.3 CompaniesById ... 90
36.1.4 CompaniesCount ... 92

37 Schema: CompanyAlerts 93

37.1 Tables ... 93
37.1.1 CompanyAlerts ... 93
37.1.2 CompanyAlertsById ... 93
37.1.3 CompanyAlertsCount ... 94

38 Schema: CompanyAlertsChild 95

38.1 Tables ... 95
38.1.1 CompaniesByParentIdAlerts ... 95
38.1.2 CompaniesByParentIdAlertsId ... 96

39 Schema: CompanyAttachments 97

39.1 Tables ... 97
39.1.1 CompanyAttachments ... 97
39.1.2 CompanyAttachmentsById ... 98

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

39.1.3 CompanyAttachmentsCount ... 100

40 Schema: CompanyAttachmentsChild 100

40.1 Tables ... 100
40.1.1 CompaniesByParentIdAttachments ... 100
40.1.2 CompaniesByParentIdAttachmentsId ... 102

41 Schema: CompanyCategories 103

41.1 Tables ... 103
41.1.1 CompanyCategories ... 103
41.1.2 CompanyCategoriesById ... 104
41.1.3 CompanyCategoriesCount ... 105

42 Schema: CompanyContactsChild 105

42.1 Tables ... 105
42.1.1 CompaniesByParentId_ItemsUserDefinedFieldsContacts ... 105
42.1.2 CompaniesByParentIdContacts ... 107
42.1.3 CompaniesByParentIdContactsId ... 109

43 Schema: CompanyLocations 111

43.1 Tables ... 111
43.1.1 CompanyLocations ... 111
43.1.2 CompanyLocationsById ... 112
43.1.3 CompanyLocationsCount ... 114

44 Schema: CompanyLocationsChild 114

44.1 Tables ... 114
44.1.1 CompaniesByParentIdLocations ... 114
44.1.2 CompaniesByParentIdLocationsId ... 116

45 Schema: CompanyNoteAttachments 117

45.1 Tables ... 117
45.1.1 CompanyNoteAttachments ... 117
45.1.2 CompanyNoteAttachmentsById ... 118
45.1.3 CompanyNoteAttachmentsCount ... 120

46 Schema: CompanyNoteAttachmentsChild 120

46.1 Tables ... 120
46.1.1 CompanyNotesByParentIdAttachments ... 120
46.1.2 CompanyNotesByParentIdAttachmentsId ... 122

47 Schema: CompanyNotes 123

47.1 Tables ... 123
47.1.1 CompanyNotes ... 123
47.1.2 CompanyNotesById ... 124
47.1.3 CompanyNotesCount ... 126

48 Schema: CompanyNotesChild 126

48.1 Tables ... 126
48.1.1 CompaniesByParentIdNotes ... 126
48.1.2 CompaniesByParentIdNotesId ... 127

49 Schema: CompanySiteConfigurations 129

49.1 Tables ... 129
49.1.1 CompanySiteConfigurations ... 129

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

49.1.2 CompanySiteConfigurations_ItemsUserDefinedFields ... 130
49.1.3 CompanySiteConfigurationsById ... 130
49.1.4 CompanySiteConfigurationsCount ... 131

50 Schema: CompanySiteConfigurationsChild 132

50.1 Tables ... 132
50.1.1 CompaniesByParentId_ItemsUserDefinedFieldsSiteConfigurations ... 132
50.1.2 CompaniesByParentIdSiteConfigurations ... 133
50.1.3 CompaniesByParentIdSiteConfigurationsId ... 134

51 Schema: CompanyTeams 135

51.1 Tables ... 135
51.1.1 CompanyTeams ... 135
51.1.2 CompanyTeamsById ... 136
51.1.3 CompanyTeamsCount ... 137

52 Schema: CompanyTeamsChild 137

52.1 Tables ... 137
52.1.1 CompaniesByParentIdTeams ... 137
52.1.2 CompaniesByParentIdTeamsId ... 138

53 Schema: CompanyToDos 139

53.1 Tables ... 139
53.1.1 CompanyToDos ... 139
53.1.2 CompanyToDosById ... 140
53.1.3 CompanyToDosCount ... 142

54 Schema: CompanyToDosChild 142

54.1 Tables ... 142
54.1.1 CompaniesByParentIdToDos ... 142
54.1.2 CompaniesByParentIdToDosId ... 144

55 Schema: CompanyWebhookExcludedResources 145

55.1 Tables ... 145
55.1.1 CompanyWebhookExcludedResources ... 145
55.1.2 CompanyWebhookExcludedResourcesById ... 146
55.1.3 CompanyWebhookExcludedResourcesCount ... 147

56 Schema: CompanyWebhookExcludedResourcesCh 147

56.1 Tables ... 147
56.1.1 CompanyWebhooksByParentIdExcludedResources ... 147
56.1.2 CompanyWebhooksByParentIdExcludedResourcesId ... 148

57 Schema: CompanyWebhookFields 149

57.1 Tables ... 149
57.1.1 CompanyWebhookFields ... 149
57.1.2 CompanyWebhookFieldsById ... 150
57.1.3 CompanyWebhookFieldsCount ... 151

58 Schema: CompanyWebhookFieldsChild 151

58.1 Tables ... 151
58.1.1 CompanyWebhooksByParentIdFields ... 151
58.1.2 CompanyWebhooksByParentIdFieldsId ... 153

59 Schema: CompanyWebhooks 154

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

59.1 Tables 154
59.1.1 CompanyWebhooks 154
59.1.2 CompanyWebhooksById 154
59.1.3 CompanyWebhooksCount 156

60 Schema: CompanyWebhookUdfFields 156

60.1 Tables 156
60.1.1 CompanyWebhookUdfFields 156
60.1.2 CompanyWebhookUdfFieldsById 157
60.1.3 CompanyWebhookUdfFieldsCount 158

61 Schema: CompanyWebhookUdfFieldsChild 158

61.1 Tables 158
61.1.1 CompanyWebhooksByParentIdUdfFields 158
61.1.2 CompanyWebhooksByParentIdUdfFieldsId 159

62 Schema: ConfigurationItemAttachments 160

62.1 Tables 160
62.1.1 ConfigurationItemAttachments 160
62.1.2 ConfigurationItemAttachmentsById 162
62.1.3 ConfigurationItemAttachmentsCount 163

63 Schema: ConfigurationItemAttachmentsChild 163

63.1 Tables 163
63.1.1 ConfigurationItemsByParentIdAttachments 163
63.1.2 ConfigurationItemsByParentIdAttachmentsId 165

64 Schema: ConfigurationItemBillingProductAssociatic 167

64.1 Tables 167
64.1.1 ConfigurationItemBillingProductAssociations 167
64.1.2 ConfigurationItemBillingProductAssociationsById 167
64.1.3 ConfigurationItemBillingProductAssociationsCount 168

65 Schema: ConfigurationItemBillingProductAssociationsChild 169

65.1 Tables 169
65.1.1 ConfigurationItemsByParentIdBillingProductAssociations 169
65.1.2 ConfigurationItemsByParentIdBillingProductAssociationsId 169

66 Schema: ConfigurationItemCategories 170

66.1 Tables 170
66.1.1 ConfigurationItemCategories 170
66.1.2 ConfigurationItemCategoriesById 170
66.1.3 ConfigurationItemCategoriesCount 171

67 Schema: ConfigurationItemCategoryUdfAssociation 172

67.1 Tables 172
67.1.1 ConfigurationItemCategoryUdfAssociations 172
67.1.2 ConfigurationItemCategoryUdfAssociationsById 172
67.1.3 ConfigurationItemCategoryUdfAssociationsCount 173

68 Schema: ConfigurationItemCategoryUdfAssociationsChild 174

68.1 Tables 174
68.1.1 ConfigurationItemCategoriesByParentIdUdfAssociations 174

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

68.1.2 ConfigurationItemCategoriesByParentIdUdfAssociationsId ... 174

69 Schema: ConfigurationItemDnsRecords 175

69.1 Tables ... 175
69.1.1 ConfigurationItemDnsRecords ... 175
69.1.2 ConfigurationItemDnsRecordsById ... 176
69.1.3 ConfigurationItemDnsRecordsCount ... 176

70 Schema: ConfigurationItemDnsRecordsChild 177

70.1 Tables ... 177
70.1.1 ConfigurationItemsByParentIdDnsRecords ... 177
70.1.2 ConfigurationItemsByParentIdDnsRecordsId ... 178

71 Schema: ConfigurationItemNoteAttachments 179

71.1 Tables ... 179
71.1.1 ConfigurationItemNoteAttachments ... 179
71.1.2 ConfigurationItemNoteAttachmentsById ... 180
71.1.3 ConfigurationItemNoteAttachmentsCount ... 181

72 Schema: ConfigurationItemNoteAttachmentsChild 182

72.1 Tables ... 182
72.1.1 ConfigurationItemNotesByParentIdAttachments ... 182
72.1.2 ConfigurationItemNotesByParentIdAttachmentsId ... 183

73 Schema: ConfigurationItemNotes 185

73.1 Tables ... 185
73.1.1 ConfigurationItemNotes ... 185
73.1.2 ConfigurationItemNotesById ... 186
73.1.3 ConfigurationItemNotesCount ... 187

74 Schema: ConfigurationItemNotesChild 187

74.1 Tables ... 187
74.1.1 ConfigurationItemsByParentIdNotes ... 187
74.1.2 ConfigurationItemsByParentIdNotesId ... 189

75 Schema: ConfigurationItemRelatedItems 190

75.1 Tables ... 190
75.1.1 ConfigurationItemRelatedItems ... 190
75.1.2 ConfigurationItemRelatedItemsById ... 191
75.1.3 ConfigurationItemRelatedItemsCount ... 192

76 Schema: ConfigurationItemRelatedItemsChild 192

76.1 Tables ... 192
76.1.1 ConfigurationItemsByParentIdRelatedItems ... 192
76.1.2 ConfigurationItemsByParentIdRelatedItemsId ... 193

77 Schema: ConfigurationItems 194

77.1 Tables ... 194
77.1.1 ConfigurationItems ... 194
77.1.2 ConfigurationItems_ItemsUserDefinedFields ... 198
77.1.3 ConfigurationItemsById ... 202
77.1.4 ConfigurationItemsCount ... 206

78 Schema: ConfigurationItemSslSubjectAlternativeNames 206

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

78.1 Tables ... 206
78.1.1 ConfigurationItemSslSubjectAlternativeNames ... 206
78.1.2 ConfigurationItemSslSubjectAlternativeNamesById ... 207
78.1.3 ConfigurationItemSslSubjectAlternativeNamesCount ... 207

79 Schema: ConfigurationItemSslSubjectAlternativeNamesChild 208

79.1 Tables ... 208
79.1.1 ConfigurationItemsByParentIdSslSubjectAlternativeNames ... 208
79.1.2 ConfigurationItemsByParentIdSslSubjectAlternativeNamesId ... 208

80 Schema: ConfigurationItemTypes 209

80.1 Tables ... 209
80.1.1 ConfigurationItemTypes ... 209
80.1.2 ConfigurationItemTypesById ... 209
80.1.3 ConfigurationItemTypesCount ... 210

81 Schema: ConfigurationItemWebhookExcludedResources 210

81.1 Tables ... 210
81.1.1 ConfigurationItemWebhookExcludedResources ... 210
81.1.2 ConfigurationItemWebhookExcludedResourcesById ... 211
81.1.3 ConfigurationItemWebhookExcludedResourcesCount ... 212

82 Schema: ConfigurationItemWebhookExcludedResourcesChil 212

82.1 Tables ... 212
82.1.1 ConfigurationItemWebhooksByParentIdExcludedResources ... 212
82.1.2 ConfigurationItemWebhooksByParentIdExcludedResourcesId ... 212

83 Schema: ConfigurationItemWebhookFields 214

83.1 Tables ... 214
83.1.1 ConfigurationItemWebhookFields ... 214
83.1.2 ConfigurationItemWebhookFieldsById ... 214
83.1.3 ConfigurationItemWebhookFieldsCount ... 215

84 Schema: ConfigurationItemWebhookFieldsChild 216

84.1 Tables ... 216
84.1.1 ConfigurationItemWebhooksByParentIdFields ... 216
84.1.2 ConfigurationItemWebhooksByParentIdFieldsId ... 217

85 Schema: ConfigurationItemWebhooks 218

85.1 Tables ... 218
85.1.1 ConfigurationItemWebhooks ... 218
85.1.2 ConfigurationItemWebhooksById ... 219
85.1.3 ConfigurationItemWebhooksCount ... 220

86 Schema: ConfigurationItemWebhookUdfFields 220

86.1 Tables ... 220
86.1.1 ConfigurationItemWebhookUdfFields ... 220
86.1.2 ConfigurationItemWebhookUdfFieldsById ... 221
86.1.3 ConfigurationItemWebhookUdfFieldsCount ... 222

87 Schema: ConfigurationItemWebhookUdfFieldsChild 223

87.1 Tables ... 223

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

87.1.1 ConfigurationItemWebhooksByParentIdUdfFields ... 223
87.1.2 ConfigurationItemWebhooksByParentIdUdfFieldsId ... 224

88 Schema: ContactBillingProductAssociations 225

88.1 Tables ... 225
88.1.1 ContactBillingProductAssociations ... 225
88.1.2 ContactBillingProductAssociationsById ... 226
88.1.3 ContactBillingProductAssociationsCount ... 227

89 Schema: ContactBillingProductAssociationsChild 227

89.1 Tables ... 227
89.1.1 ContactsByParentIdBillingProductAssociations ... 227
89.1.2 ContactsByParentIdBillingProductAssociationsId ... 228

90 Schema: ContactGroupContacts 229

90.1 Tables ... 229
90.1.1 ContactGroupContacts ... 229
90.1.2 ContactGroupContactsById ... 230
90.1.3 ContactGroupContactsCount ... 231

91 Schema: ContactGroupContactsChild 231

91.1 Tables ... 231
91.1.1 ContactGroupsByParentIdContacts ... 231
91.1.2 ContactGroupsByParentIdContactsId ... 232

92 Schema: ContactGroups 234

92.1 Tables ... 234
92.1.1 ContactGroups ... 234
92.1.2 ContactGroupsById ... 234
92.1.3 ContactGroupsCount ... 235

93 Schema: Contacts 235

93.1 Tables ... 235
93.1.1 Contacts ... 235
93.1.2 Contacts_ItemsUserDefinedFields ... 237
93.1.3 ContactsById ... 239
93.1.4 ContactsCount ... 241

94 Schema: ContactWebhookExcludedResources 241

94.1 Tables ... 241
94.1.1 ContactWebhookExcludedResources ... 241
94.1.2 ContactWebhookExcludedResourcesById ... 242
94.1.3 ContactWebhookExcludedResourcesCount ... 243

95 Schema: ContactWebhookExcludedResourcesChild 243

95.1 Tables ... 243
95.1.1 ContactWebhooksByParentIdExcludedResources ... 243
95.1.2 ContactWebhooksByParentIdExcludedResourcesId ... 244

96 Schema: ContactWebhookFields 245

96.1 Tables ... 245
96.1.1 ContactWebhookFields ... 245
96.1.2 ContactWebhookFieldsById ... 246
96.1.3 ContactWebhookFieldsCount ... 247

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

97 Schema: ContactWebhookFieldsChild 247

97.1 Tables ... 247
97.1.1 ContactWebhooksByParentIdFields ... 247
97.1.2 ContactWebhooksByParentIdFieldsId ... 249

98 Schema: ContactWebhooks 250

98.1 Tables ... 250
98.1.1 ContactWebhooks ... 250
98.1.2 ContactWebhooksById ... 250
98.1.3 ContactWebhooksCount ... 252

99 Schema: ContactWebhookUdfFields 252

99.1 Tables ... 252
99.1.1 ContactWebhookUdfFields ... 252
99.1.2 ContactWebhookUdfFieldsById ... 253
99.1.3 ContactWebhookUdfFieldsCount ... 254

100 Schema: ContactWebhookUdfFieldsChild 254

100.1 Tables ... 254
100.1.1 ContactWebhooksByParentIdUdfFields ... 254
100.1.2 ContactWebhooksByParentIdUdfFieldsId ... 255

101 Schema: ContractBillingRules 256

101.1 Tables ... 256
101.1.1 ContractBillingRules ... 256
101.1.2 ContractBillingRulesById ... 257
101.1.3 ContractBillingRulesCount ... 259

102 Schema: ContractBillingRulesChild 259

102.1 Tables ... 259
102.1.1 ContractsByParentIdBillingRules ... 259
102.1.2 ContractsByParentIdBillingRulesId ... 261

103 Schema: ContractBlockHourFactors 262

103.1 Tables ... 262
103.1.1 ContractBlockHourFactors ... 262
103.1.2 ContractBlockHourFactorsById ... 263
103.1.3 ContractBlockHourFactorsCount ... 264

104 Schema: ContractBlockHourFactorsChild 264

104.1 Tables ... 264
104.1.1 ContractsByParentIdBlockHourFactors ... 264
104.1.2 ContractsByParentIdBlockHourFactorsId ... 265

105 Schema: ContractBlocks 267

105.1 Tables ... 267
105.1.1 ContractBlocks ... 267
105.1.2 ContractBlocksById ... 267
105.1.3 ContractBlocksCount ... 269

106 Schema: ContractBlocksChild 269

106.1 Tables ... 269
106.1.1 ContractsByParentIdBlocks ... 269
106.1.2 ContractsByParentIdBlocksId ... 270

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

107 Schema: ContractCharges 272

107.1 Tables ... 272
107.1.1 ContractCharges ... 272
107.1.2 ContractChargesById ... 273
107.1.3 ContractChargesCount ... 275

108 Schema: ContractChargesChild 275

108.1 Tables ... 275
108.1.1 ContractsByParentIdCharges ... 275
108.1.2 ContractsByParentIdChargesId ... 277

109 Schema: ContractExclusionBillingCodes 279

109.1 Tables ... 279
109.1.1 ContractExclusionBillingCodes ... 279
109.1.2 ContractExclusionBillingCodesById ... 280
109.1.3 ContractExclusionBillingCodesCount ... 281

110 Schema: ContractExclusionBillingCodesChild 281

110.1 Tables ... 281
110.1.1 ContractsByParentIdExclusionBillingCodes ... 281
110.1.2 ContractsByParentIdExclusionBillingCodesId ... 282

111 Schema: ContractExclusionRoles 283

111.1 Tables ... 283
111.1.1 ContractExclusionRoles ... 283
111.1.2 ContractExclusionRolesById ... 284
111.1.3 ContractExclusionRolesCount ... 285

112 Schema: ContractExclusionRolesChild 285

112.1 Tables ... 285
112.1.1 ContractsByParentIdExclusionRoles ... 285
112.1.2 ContractsByParentIdExclusionRolesId ... 286

113 Schema: ContractExclusionSetExcludedRoles 287

113.1 Tables ... 287
113.1.1 ContractExclusionSetExcludedRoles ... 287
113.1.2 ContractExclusionSetExcludedRolesById ... 288
113.1.3 ContractExclusionSetExcludedRolesCount ... 289

114 Schema: ContractExclusionSetExcludedRolesChild 290

114.1 Tables ... 290
114.1.1 ContractExclusionSetsByParentIdExcludedRoles ... 290
114.1.2 ContractExclusionSetsByParentIdExcludedRolesId ... 291

115 Schema: ContractExclusionSetExcludedWorkTypes 292

115.1 Tables ... 292
115.1.1 ContractExclusionSetExcludedWorkTypes ... 292
115.1.2 ContractExclusionSetExcludedWorkTypesById ... 292
115.1.3 ContractExclusionSetExcludedWorkTypesCount ... 294

116 Schema: ContractExclusionSetExcludedWorkTypesChild 294

116.1 Tables ... 294
116.1.1 ContractExclusionSetsByParentIdExcludedWorkTypes ... 294

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

116.1.2 ContractExclusionSetsByParentIdExcludedWorkTypesId ... 295

117 Schema: ContractExclusionSets 296

117.1 Tables ... 296
117.1.1 ContractExclusionSets ... 296
117.1.2 ContractExclusionSetsById ... 297
117.1.3 ContractExclusionSetsCount ... 297

118 Schema: ContractMilestones 298

118.1 Tables ... 298
118.1.1 ContractMilestones ... 298
118.1.2 ContractMilestonesById ... 299
118.1.3 ContractMilestonesCount ... 300

119 Schema: ContractMilestonesChild 300

119.1 Tables ... 300
119.1.1 ContractsByParentIdMilestones ... 300
119.1.2 ContractsByParentIdMilestonesId ... 302

120 Schema: ContractNoteAttachments 303

120.1 Tables ... 303
120.1.1 ContractNoteAttachments ... 303
120.1.2 ContractNoteAttachmentsById ... 304
120.1.3 ContractNoteAttachmentsCount ... 306

121 Schema: ContractNoteAttachmentsChild 306

121.1 Tables ... 306
121.1.1 ContractNotesByParentIdAttachments ... 306
121.1.2 ContractNotesByParentIdAttachmentsId ... 308

122 Schema: ContractNotes 309

122.1 Tables ... 309
122.1.1 ContractNotes ... 309
122.1.2 ContractNotesById ... 310
122.1.3 ContractNotesCount ... 311

123 Schema: ContractNotesChild 312

123.1 Tables ... 312
123.1.1 ContractsByParentIdNotes ... 312
123.1.2 ContractsByParentIdNotesId ... 313

124 Schema: ContractRates 314

124.1 Tables ... 314
124.1.1 ContractRates ... 314
124.1.2 ContractRatesById ... 315
124.1.3 ContractRatesCount ... 316

125 Schema: ContractRatesChild 316

125.1 Tables ... 316
125.1.1 ContractsByParentIdRates ... 316
125.1.2 ContractsByParentIdRatesId ... 318

126 Schema: ContractRetainers 319

126.1 Tables ... 319
126.1.1 ContractRetainers ... 319

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

126.1.2 ContractRetainersById ... 320
126.1.3 ContractRetainersCount ... 321

127 Schema: ContractRetainersChild 321

127.1 Tables ... 321
127.1.1 ContractsByParentIdRetainers ... 321
127.1.2 ContractsByParentIdRetainersId ... 323

128 Schema: ContractRoleCosts 324

128.1 Tables ... 324
128.1.1 ContractRoleCosts ... 324
128.1.2 ContractRoleCostsById ... 325
128.1.3 ContractRoleCostsCount ... 326

129 Schema: ContractRoleCostsChild 326

129.1 Tables ... 326
129.1.1 ContractsByParentIdRoleCosts ... 326
129.1.2 ContractsByParentIdRoleCostsId ... 327

130 Schema: Contracts 329

130.1 Tables ... 329
130.1.1 Contracts ... 329
130.1.2 Contracts_ItemsUserDefinedFields ... 330
130.1.3 ContractsById ... 331
130.1.4 ContractsCount ... 333

131 Schema: ContractServiceBundles 333

131.1 Tables ... 333
131.1.1 ContractServiceBundles ... 333
131.1.2 ContractServiceBundlesById ... 334
131.1.3 ContractServiceBundlesCount ... 335

132 Schema: ContractServiceBundlesChild 336

132.1 Tables ... 336
132.1.1 ContractsByParentIdServiceBundles ... 336
132.1.2 ContractsByParentIdServiceBundlesId ... 337

133 Schema: ContractServiceBundleUnits 338

133.1 Tables ... 338
133.1.1 ContractServiceBundleUnits ... 338
133.1.2 ContractServiceBundleUnitsById ... 339
133.1.3 ContractServiceBundleUnitsCount ... 340

134 Schema: ContractServiceBundleUnitsChild 341

134.1 Tables ... 341
134.1.1 ContractsByParentIdServiceBundleUnits ... 341
134.1.2 ContractsByParentIdServiceBundleUnitsId ... 342

135 Schema: ContractServices 343

135.1 Tables ... 343
135.1.1 ContractServices ... 343
135.1.2 ContractServicesById ... 344
135.1.3 ContractServicesCount ... 345

136 Schema: ContractServicesChild 345

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

136.1 Tables ... 345
136.1.1 ContractsByParentIdServices ... 345
136.1.2 ContractsByParentIdServicesId ... 347

137 Schema: ContractServiceUnits 348

137.1 Tables ... 348
137.1.1 ContractServiceUnits ... 348
137.1.2 ContractServiceUnitsById ... 349
137.1.3 ContractServiceUnitsCount ... 350

138 Schema: ContractServiceUnitsChild 350

138.1 Tables ... 350
138.1.1 ContractsByParentIdServiceUnits ... 350
138.1.2 ContractsByParentIdServiceUnitsId ... 351

139 Schema: ContractTicketPurchases 352

139.1 Tables ... 352
139.1.1 ContractTicketPurchases ... 352
139.1.2 ContractTicketPurchasesById ... 353
139.1.3 ContractTicketPurchasesCount ... 355

140 Schema: ContractTicketPurchasesChild 355

140.1 Tables ... 355
140.1.1 ContractsByParentIdTicketPurchases ... 355
140.1.2 ContractsByParentIdTicketPurchasesId ... 356

141 Schema: Countries 358

141.1 Tables ... 358
141.1.1 Countries ... 358
141.1.2 CountriesById ... 358
141.1.3 CountriesCount ... 359

142 Schema: Currencies 359

142.1 Tables ... 359
142.1.1 Currencies ... 359
142.1.2 CurrenciesById ... 360
142.1.3 CurrenciesCount ... 361

143 Schema: DeletedTaskActivityLogs 361

143.1 Tables ... 361
143.1.1 DeletedTaskActivityLogs ... 361
143.1.2 DeletedTaskActivityLogsById ... 362
143.1.3 DeletedTaskActivityLogsCount ... 363

144 Schema: DeletedTicketActivityLogs 364

144.1 Tables ... 364
144.1.1 DeletedTicketActivityLogs ... 364
144.1.2 DeletedTicketActivityLogsById ... 364
144.1.3 DeletedTicketActivityLogsCount ... 365

145 Schema: DeletedTicketLogs 366

145.1 Tables ... 366
145.1.1 DeletedTicketLogs ... 366
145.1.2 DeletedTicketLogsById ... 366
145.1.3 DeletedTicketLogsCount ... 367

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

146 Schema: Departments 367

146.1 Tables ... 367
146.1.1 Departments ... 367
146.1.2 DepartmentsById ... 368
146.1.3 DepartmentsCount ... 369

147 Schema: DocumentAttachments 369

147.1 Tables ... 369
147.1.1 DocumentAttachments ... 369
147.1.2 DocumentAttachmentsById ... 370
147.1.3 DocumentAttachmentsCount ... 372

148 Schema: DocumentAttachmentsChild 372

148.1 Tables ... 372
148.1.1 DocumentsByParentIdAttachments ... 372
148.1.2 DocumentsByParentIdAttachmentsId ... 374

149 Schema: DocumentCategories 375

149.1 Tables ... 375
149.1.1 DocumentCategories ... 375
149.1.2 DocumentCategoriesById ... 376
149.1.3 DocumentCategoriesCount ... 376

150 Schema: DocumentChecklistItems 377

150.1 Tables ... 377
150.1.1 DocumentChecklistItems ... 377
150.1.2 DocumentChecklistItemsById ... 377
150.1.3 DocumentChecklistItemsCount ... 378

151 Schema: DocumentChecklistItemsChild 379

151.1 Tables ... 379
151.1.1 DocumentsByParentIdChecklistItems ... 379
151.1.2 DocumentsByParentIdChecklistItemsId ... 380

152 Schema: DocumentConfigurationItemAssociations 381

152.1 Tables ... 381
152.1.1 DocumentConfigurationItemAssociations ... 381
152.1.2 DocumentConfigurationItemAssociationsById ... 382
152.1.3 DocumentConfigurationItemAssociationsCount ... 383

153 Schema: DocumentConfigurationItemAssociationsChild 383

153.1 Tables ... 383
153.1.1 DocumentsByParentIdConfigurationItemAssociations ... 383
153.1.2 DocumentsByParentIdConfigurationItemAssociationsId ... 384

154 Schema: DocumentConfigurationItemCategoryAssociations 386

154.1 Tables ... 386
154.1.1 DocumentConfigurationItemCategoryAssociations ... 386
154.1.2 DocumentConfigurationItemCategoryAssociationsById ... 386
154.1.3 DocumentConfigurationItemCategoryAssociationsCount ... 387

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

155 Schema: DocumentConfigurationItemCategoryAssociationsChild 388

155.1 Tables ... 388
155.1.1 DocumentsByParentIdConfigurationItemCategoryAssociations ... 388
155.1.2 DocumentsByParentIdConfigurationItemCategoryAssociationsId ... 388

156 Schema: DocumentNotes 389

156.1 Tables ... 389
156.1.1 DocumentNotes ... 389
156.1.2 DocumentNotesById ... 390
156.1.3 DocumentNotesCount ... 391

157 Schema: DocumentNotesChild 391

157.1 Tables ... 391
157.1.1 DocumentsByParentIdNotes ... 391
157.1.2 DocumentsByParentIdNotesId ... 393

158 Schema: DocumentPlainTextContent 394

158.1 Tables ... 394
158.1.1 DocumentPlainTextContent ... 394
158.1.2 DocumentPlainTextContentById ... 394
158.1.3 DocumentPlainTextContentCount ... 395

159 Schema: DocumentPlainTextContentChild 396

159.1 Tables ... 396
159.1.1 DocumentsByParentIdPlainTextContent ... 396
159.1.2 DocumentsByParentIdPlainTextContentId ... 397

160 Schema: Documents 398

160.1 Tables ... 398
160.1.1 Documents ... 398
160.1.2 DocumentsById ... 399
160.1.3 DocumentsCount ... 400

161 Schema: DocumentsChild 401

161.1 Tables ... 401
161.1.1 DocumentCategoriesByParentIdDocuments ... 401
161.1.2 DocumentCategoriesByParentIdDocumentsId ... 402

162 Schema: DocumentTagAssociations 403

162.1 Tables ... 403
162.1.1 DocumentTagAssociations ... 403
162.1.2 DocumentTagAssociationsById ... 404
162.1.3 DocumentTagAssociationsCount ... 405

163 Schema: DocumentTagAssociationsChild 405

163.1 Tables ... 405
163.1.1 DocumentsByParentIdTagAssociations ... 405
163.1.2 DocumentsByParentIdTagAssociationsId ... 407

164 Schema: DocumentTicketAssociations 408

164.1 Tables ... 408

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

164.1.1 DocumentTicketAssociations ... 408
164.1.2 DocumentTicketAssociationsById ... 408
164.1.3 DocumentTicketAssociationsCount ... 409

165 Schema: DocumentTicketAssociationsChild 410

165.1 Tables ... 410
165.1.1 DocumentsByParentIdTicketAssociations ... 410
165.1.2 DocumentsByParentIdTicketAssociationsId ... 411

166 Schema: DocumentToArticleAssociations 412

166.1 Tables ... 412
166.1.1 DocumentToArticleAssociations ... 412
166.1.2 DocumentToArticleAssociationsById ... 413
166.1.3 DocumentToArticleAssociationsCount ... 414

167 Schema: DocumentToArticleAssociationsChild 414

167.1 Tables ... 414
167.1.1 DocumentsByParentIdArticleAssociations ... 414
167.1.2 DocumentsByParentIdArticleAssociationsId ... 415

168 Schema: DocumentToDocumentAssociations 416

168.1 Tables ... 416
168.1.1 DocumentToDocumentAssociations ... 416
168.1.2 DocumentToDocumentAssociationsById ... 417
168.1.3 DocumentToDocumentAssociationsCount ... 418

169 Schema: DocumentToDocumentAssociationsChild 418

169.1 Tables ... 418
169.1.1 DocumentsByParentIdDocumentAssociations ... 418
169.1.2 DocumentsByParentIdDocumentAssociationsId ... 419

170 Schema: DomainRegistrars 421

170.1 Tables ... 421
170.1.1 DomainRegistrars ... 421
170.1.2 DomainRegistrarsById ... 421
170.1.3 DomainRegistrarsCount ... 422

171 Schema: ExpenseItemAttachments 422

171.1 Tables ... 422
171.1.1 ExpenseItemAttachments ... 422
171.1.2 ExpenseItemAttachmentsById ... 423
171.1.3 ExpenseItemAttachmentsCount ... 425

172 Schema: ExpenseItemAttachmentsChild 425

172.1 Tables ... 425
172.1.1 ExpenseItemsByParentIdAttachments ... 425
172.1.2 ExpenseItemsByParentIdAttachmentsId ... 427

173 Schema: ExpenseItems 428

173.1 Tables ... 428
173.1.1 ExpenseItems ... 428
173.1.2 ExpenseItemsById ... 429
173.1.3 ExpenseItemsCount ... 431

174 Schema: ExpenseItemsChild 432

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

174.1 Tables ... 432
174.1.1 ExpensesByParentIdItems ... 432
174.1.2 ExpensesByParentIdItemsId ... 433

175 Schema: ExpenseReportAttachments 435

175.1 Tables ... 435
175.1.1 ExpenseReportAttachments ... 435
175.1.2 ExpenseReportAttachmentsById ... 436
175.1.3 ExpenseReportAttachmentsCount ... 438

176 Schema: ExpenseReportAttachmentsChild 438

176.1 Tables ... 438
176.1.1 ExpenseReportsByParentIdAttachments ... 438
176.1.2 ExpenseReportsByParentIdAttachmentsId ... 440

177 Schema: ExpenseReports 441

177.1 Tables ... 441
177.1.1 ExpenseReports ... 441
177.1.2 ExpenseReportsById ... 442
177.1.3 ExpenseReportsCount ... 443

178 Schema: Holidays 444

178.1 Tables ... 444
178.1.1 Holidays ... 444
178.1.2 HolidaysById ... 444
178.1.3 HolidaysCount ... 445

179 Schema: HolidaysChild 446

179.1 Tables ... 446
179.1.1 HolidaySetsByParentIdHolidays ... 446
179.1.2 HolidaySetsByParentIdHolidaysId ... 447

180 Schema: HolidaySets 448

180.1 Tables ... 448
180.1.1 HolidaySets ... 448
180.1.2 HolidaySetsById ... 448
180.1.3 HolidaySetsCount ... 449

181 Schema: IntegrationVendorInsights 450

181.1 Tables ... 450
181.1.1 IntegrationVendorInsights ... 450
181.1.2 IntegrationVendorInsightsById ... 450
181.1.3 IntegrationVendorInsightsCount ... 451

182 Schema: IntegrationVendorWidgets 452

182.1 Tables ... 452
182.1.1 IntegrationVendorWidgets ... 452
182.1.2 IntegrationVendorWidgetsById ... 452
182.1.3 IntegrationVendorWidgetsCount ... 453

183 Schema: InternalLocations 454

183.1 Tables ... 454
183.1.1 InternalLocations ... 454
183.1.2 InternalLocationsById ... 454
183.1.3 InternalLocationsCount ... 455

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

184 Schema: InternalLocationWithBusinessHours 456

184.1 Tables ... 456
184.1.1 InternalLocationWithBusinessHours ... 456
184.1.2 InternalLocationWithBusinessHoursById ... 458
184.1.3 InternalLocationWithBusinessHoursCount ... 460

185 Schema: InventoryItems 461

185.1 Tables ... 461
185.1.1 InventoryItems ... 461
185.1.2 InventoryItemsById ... 461
185.1.3 InventoryItemsCount ... 462

186 Schema: InventoryItemSerialNumbers 463

186.1 Tables ... 463
186.1.1 InventoryItemSerialNumbers ... 463
186.1.2 InventoryItemSerialNumbersById ... 463
186.1.3 InventoryItemSerialNumbersCount ... 464

187 Schema: InventoryItemSerialNumbersChild 465

187.1 Tables ... 465
187.1.1 InventoryItemsByParentIdSerialNumbers ... 465
187.1.2 InventoryItemsByParentIdSerialNumbersId ... 466

188 Schema: InventoryLocations 467

188.1 Tables ... 467
188.1.1 InventoryLocations ... 467
188.1.2 InventoryLocationsById ... 467
188.1.3 InventoryLocationsCount ... 468

189 Schema: InventoryProducts 469

189.1 Tables ... 469
189.1.1 InventoryProducts ... 469
189.1.2 InventoryProductsById ... 469
189.1.3 InventoryProductsCount ... 471

190 Schema: InventoryStockedItems 471

190.1 Tables ... 471
190.1.1 InventoryStockedItems ... 471
190.1.2 InventoryStockedItemsById ... 472
190.1.3 InventoryStockedItemsCount ... 474

191 Schema: InventoryStockedItemsChild 475

191.1 Tables ... 475
191.1.1 InventoryProductsByParentIdStockedItems ... 475
191.1.2 InventoryProductsByParentIdStockedItemsId ... 476

192 Schema: InventoryTransfers 478

192.1 Tables ... 478
192.1.1 InventoryTransfers ... 478
192.1.2 InventoryTransfersById ... 479
192.1.3 InventoryTransfersCount ... 480

193 Schema: InvoiceMarkupApiIntegration 480

193.1 Tables ... 480

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

193.1.1 InvoicesByIdInvoiceMarkupHtml ... 480
193.1.2 InvoicesByIdInvoiceMarkupXml ... 481

194 Schema: Invoices 482

194.1 Tables ... 482
194.1.1 Invoices ... 482
194.1.2 InvoicesById ... 483
194.1.3 InvoicesCount ... 484

195 Schema: InvoiceTemplates 484

195.1 Tables ... 484
195.1.1 InvoiceTemplates ... 484
195.1.2 InvoiceTemplatesById ... 486
195.1.3 InvoiceTemplatesCount ... 487

196 Schema: KnowledgeBaseArticles 488

196.1 Tables ... 488
196.1.1 KnowledgeBaseArticles ... 488
196.1.2 KnowledgeBaseArticlesById ... 488
196.1.3 KnowledgeBaseArticlesCount ... 490

197 Schema: KnowledgeBaseArticlesChild 490

197.1 Tables ... 490
197.1.1 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticles ... 490
197.1.2 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesId ... 491

198 Schema: KnowledgeBaseCategories 493

198.1 Tables ... 493
198.1.1 KnowledgeBaseCategories ... 493
198.1.2 KnowledgeBaseCategoriesById ... 493
198.1.3 KnowledgeBaseCategoriesCount ... 494

199 Schema: Metadata 495

199.1 Tables ... 495
199.1.1 ActionTypesEntityInformation ... 495
199.1.2 ActionTypesEntityInformation_FieldsPicklistValuesFields ... 495
199.1.3 ActionTypesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 496
199.1.4 ActionTypesEntityInformationFields ... 497
199.1.5 ActionTypesEntityInformationUserDefinedFields ... 497
199.1.6 AdditionalInvoiceFieldValuesEntityInformation ... 498
199.1.7 AdditionalInvoiceFieldValuesEntityInformation_FieldsPicklistValuesFields ... 499
199.1.8 AdditionalInvoiceFieldValuesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 500
199.1.9 AdditionalInvoiceFieldValuesEntityInformationFields ... 500
199.1.10 AdditionalInvoiceFieldValuesEntityInformationUserDefinedFields ... 501
199.1.11 AppointmentsEntityInformation ... 502
199.1.12 AppointmentsEntityInformation_FieldsPicklistValuesFields ... 502
199.1.13 AppointmentsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 503
199.1.14 AppointmentsEntityInformationFields ... 504
199.1.15 AppointmentsEntityInformationUserDefinedFields ... 505
199.1.16 ArticleAttachmentsEntityInformation ... 505
199.1.17 ArticleAttachmentsEntityInformation_FieldsPicklistValuesFields ... 506
199.1.18 ArticleAttachmentsEntityInformationFields ... 507
199.1.19 ArticleConfigurationItemCategoryAssociationsEntityInformation ... 507
199.1.20 ArticleConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields ... 508
199.1.21 ArticleConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 509
199.1.22 ArticleConfigurationItemCategoryAssociationsEntityInformationFields ... 510
199.1.23 ArticleConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields ... 510

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.24 ArticleNotesEntityInformation ... 511
199.1.25 ArticleNotesEntityInformation_FieldsPicklistValuesFields ... 511
199.1.26 ArticleNotesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 512
199.1.27 ArticleNotesEntityInformationFields ... 513
199.1.28 ArticleNotesEntityInformationUserDefinedFields ... 514
199.1.29 ArticlePlainTextContentEntityInformation ... 514
199.1.30 ArticlePlainTextContentEntityInformation_FieldsPicklistValuesFields ... 515
199.1.31 ArticlePlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields ... 516
199.1.32 ArticlePlainTextContentEntityInformationFields ... 517
199.1.33 ArticlePlainTextContentEntityInformationUserDefinedFields ... 517
199.1.34 ArticleTagAssociationsEntityInformation ... 518
199.1.35 ArticleTagAssociationsEntityInformation_FieldsPicklistValuesFields ... 518
199.1.36 ArticleTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 519
199.1.37 ArticleTagAssociationsEntityInformationFields ... 520
199.1.38 ArticleTagAssociationsEntityInformationUserDefinedFields ... 521
199.1.39 ArticleTicketAssociationsEntityInformation ... 521
199.1.40 ArticleTicketAssociationsEntityInformation_FieldsPicklistValuesFields ... 522
199.1.41 ArticleTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 523
199.1.42 ArticleTicketAssociationsEntityInformationFields ... 524
199.1.43 ArticleTicketAssociationsEntityInformationUserDefinedFields ... 524
199.1.44 ArticleToArticleAssociationsEntityInformation ... 525
199.1.45 ArticleToArticleAssociationsEntityInformation_FieldsPicklistValuesFields ... 525
199.1.46 ArticleToArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 526
199.1.47 ArticleToArticleAssociationsEntityInformationFields ... 527
199.1.48 ArticleToArticleAssociationsEntityInformationUserDefinedFields ... 528
199.1.49 ArticleToDocumentAssociationsEntityInformation ... 528
199.1.50 ArticleToDocumentAssociationsEntityInformation_FieldsPicklistValuesFields ... 529
199.1.51 ArticleToDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 530
199.1.52 ArticleToDocumentAssociationsEntityInformationFields ... 531
199.1.53 ArticleToDocumentAssociationsEntityInformationUserDefinedFields ... 531
199.1.54 AttachmentInfoEntityInformation ... 532
199.1.55 AttachmentInfoEntityInformation_FieldsPicklistValuesFields ... 533
199.1.56 AttachmentInfoEntityInformation_FieldsPicklistValuesUserDefinedFields ... 533
199.1.57 AttachmentInfoEntityInformationFields ... 534
199.1.58 AttachmentInfoEntityInformationUserDefinedFields ... 535
199.1.59 BillingCodesEntityInformation ... 535
199.1.60 BillingCodesEntityInformation_FieldsPicklistValuesFields ... 536
199.1.61 BillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 537
199.1.62 BillingCodesEntityInformationFields ... 538
199.1.63 BillingCodesEntityInformationUserDefinedFields ... 538
199.1.64 BillingItemApprovalLevelsEntityInformation ... 539
199.1.65 BillingItemApprovalLevelsEntityInformation_FieldsPicklistValuesFields ... 540
199.1.66 BillingItemApprovalLevelsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 540
199.1.67 BillingItemApprovalLevelsEntityInformationFields ... 541
199.1.68 BillingItemApprovalLevelsEntityInformationUserDefinedFields ... 542
199.1.69 BillingItemsEntityInformation ... 542
199.1.70 BillingItemsEntityInformation_FieldsPicklistValuesFields ... 543
199.1.71 BillingItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 544
199.1.72 BillingItemsEntityInformationFields ... 545
199.1.73 BillingItemsEntityInformationUserDefinedFields ... 545
199.1.74 ChangeOrderChargesEntityInformation ... 546
199.1.75 ChangeOrderChargesEntityInformation_FieldsPicklistValuesFields ... 547
199.1.76 ChangeOrderChargesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 547
199.1.77 ChangeOrderChargesEntityInformationFields ... 548
199.1.78 ChangeOrderChargesEntityInformationUserDefinedFields ... 549
199.1.79 ChangeRequestLinksEntityInformation ... 549
199.1.80 ChangeRequestLinksEntityInformation_FieldsPicklistValuesFields ... 550
199.1.81 ChangeRequestLinksEntityInformation_FieldsPicklistValuesUserDefinedFields ... 551
199.1.82 ChangeRequestLinksEntityInformationFields ... 552

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.83 ChangeRequestLinksEntityInformationUserDefinedFields ... 552
199.1.84 ChecklistLibrariesByParentIdChecklistItemsEntityInformation ... 553
199.1.85 ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields ... 554
199.1.86 ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 555
199.1.87 ChecklistLibrariesByParentIdChecklistItemsEntityInformationFields ... 556
199.1.88 ChecklistLibrariesByParentIdChecklistItemsEntityInformationUserDefinedFields ... 558
199.1.89 ChecklistLibrariesEntityInformation ... 559
199.1.90 ChecklistLibrariesEntityInformation_FieldsPicklistValuesFields ... 559
199.1.91 ChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 560
199.1.92 ChecklistLibrariesEntityInformationFields ... 561
199.1.93 ChecklistLibrariesEntityInformationUserDefinedFields ... 562
199.1.94 ChecklistLibraryChecklistItemsEntityInformation ... 562
199.1.95 ChecklistLibraryChecklistItemsEntityInformation_FieldsPicklistValuesFields ... 563
199.1.96 ChecklistLibraryChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 564
199.1.97 ChecklistLibraryChecklistItemsEntityInformationFields ... 565
199.1.98 ChecklistLibraryChecklistItemsEntityInformationUserDefinedFields ... 565
199.1.99 ClassificationIconsEntityInformation ... 566
199.1.100 ClassificationIconsEntityInformation_FieldsPicklistValuesFields ... 566
199.1.101 ClassificationIconsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 567
199.1.102 ClassificationIconsEntityInformationFields ... 568
199.1.103 ClassificationIconsEntityInformationUserDefinedFields ... 569
199.1.104 ClientPortalUsersEntityInformation ... 569
199.1.105 ClientPortalUsersEntityInformation_FieldsPicklistValuesFields ... 570
199.1.106 ClientPortalUsersEntityInformation_FieldsPicklistValuesUserDefinedFields ... 571
199.1.107 ClientPortalUsersEntityInformationFields ... 572
199.1.108 ClientPortalUsersEntityInformationUserDefinedFields ... 572
199.1.109 ComanagedAssociationsEntityInformation ... 573
199.1.110 ComanagedAssociationsEntityInformation_FieldsPicklistValuesFields ... 573
199.1.111 ComanagedAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 574
199.1.112 ComanagedAssociationsEntityInformationFields ... 575
199.1.113 ComanagedAssociationsEntityInformationUserDefinedFields ... 576
199.1.114 CompaniesByParentIdAlertsEntityInformation ... 576
199.1.115 CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesFields ... 577
199.1.116 CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 579
199.1.117 CompaniesByParentIdAlertsEntityInformationFields ... 580
199.1.118 CompaniesByParentIdAlertsEntityInformationUserDefinedFields ... 581
199.1.119 CompaniesByParentIdContactsEntityInformation ... 582
199.1.120 CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesFields ... 583
199.1.121 CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 584
199.1.122 CompaniesByParentIdContactsEntityInformationFields ... 586
199.1.123 CompaniesByParentIdContactsEntityInformationUserDefinedFields ... 587
199.1.124 CompaniesByParentIdLocationsEntityInformation ... 588
199.1.125 CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesFields ... 589
199.1.126 CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 590
199.1.127 CompaniesByParentIdLocationsEntityInformationFields ... 591
199.1.128 CompaniesByParentIdLocationsEntityInformationUserDefinedFields ... 592
199.1.129 CompaniesByParentIdNotesEntityInformation ... 593
199.1.130 CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesFields ... 594
199.1.131 CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 596
199.1.132 CompaniesByParentIdNotesEntityInformationFields ... 597
199.1.133 CompaniesByParentIdNotesEntityInformationUserDefinedFields ... 598
199.1.134 CompaniesByParentIdSiteConfigurationsEntityInformation ... 599
199.1.135 CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesFields ... 600
199.1.136 CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 601
199.1.137 CompaniesByParentIdSiteConfigurationsEntityInformationFields ... 603
199.1.138 CompaniesByParentIdSiteConfigurationsEntityInformationUserDefinedFields ... 604
199.1.139 CompaniesByParentIdTeamsEntityInformation ... 605
199.1.140 CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesFields ... 606
199.1.141 CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 607

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.142 CompaniesByParentIdTeamsEntityInformationFields ... 608
199.1.143 CompaniesByParentIdTeamsEntityInformationUserDefinedFields ... 609
199.1.144 CompaniesByParentIdToDosEntityInformation ... 610
199.1.145 CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesFields ... 611
199.1.146 CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesUserDefinedFields ... 613
199.1.147 CompaniesByParentIdToDosEntityInformationFields ... 614
199.1.148 CompaniesByParentIdToDosEntityInformationUserDefinedFields ... 615
199.1.149 CompaniesEntityInformation ... 616
199.1.150 CompaniesEntityInformation_FieldsPicklistValuesFields ... 617
199.1.151 CompaniesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 617
199.1.152 CompaniesEntityInformationFields ... 618
199.1.153 CompaniesEntityInformationUserDefinedFields ... 619
199.1.154 CompanyAlertsEntityInformation ... 619
199.1.155 CompanyAlertsEntityInformation_FieldsPicklistValuesFields ... 620
199.1.156 CompanyAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 621
199.1.157 CompanyAlertsEntityInformationFields ... 622
199.1.158 CompanyAlertsEntityInformationUserDefinedFields ... 622
199.1.159 CompanyAttachmentsEntityInformation ... 623
199.1.160 CompanyAttachmentsEntityInformation_FieldsPicklistValuesFields ... 624
199.1.161 CompanyAttachmentsEntityInformationFields ... 624
199.1.162 CompanyCategoriesEntityInformation ... 625
199.1.163 CompanyCategoriesEntityInformation_FieldsPicklistValuesFields ... 626
199.1.164 CompanyCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 626
199.1.165 CompanyCategoriesEntityInformationFields ... 627
199.1.166 CompanyCategoriesEntityInformationUserDefinedFields ... 628
199.1.167 CompanyLocationsEntityInformation ... 628
199.1.168 CompanyLocationsEntityInformation_FieldsPicklistValuesFields ... 629
199.1.169 CompanyLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 630
199.1.170 CompanyLocationsEntityInformationFields ... 631
199.1.171 CompanyLocationsEntityInformationUserDefinedFields ... 631
199.1.172 CompanyNoteAttachmentsEntityInformation ... 632
199.1.173 CompanyNoteAttachmentsEntityInformation_FieldsPicklistValuesFields ... 633
199.1.174 CompanyNoteAttachmentsEntityInformationFields ... 633
199.1.175 CompanyNotesEntityInformation ... 634
199.1.176 CompanyNotesEntityInformation_FieldsPicklistValuesFields ... 635
199.1.177 CompanyNotesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 635
199.1.178 CompanyNotesEntityInformationFields ... 636
199.1.179 CompanyNotesEntityInformationUserDefinedFields ... 637
199.1.180 CompanySiteConfigurationsEntityInformation ... 637
199.1.181 CompanySiteConfigurationsEntityInformation_FieldsPicklistValuesFields ... 638
199.1.182 CompanySiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 639
199.1.183 CompanySiteConfigurationsEntityInformationFields ... 640
199.1.184 CompanySiteConfigurationsEntityInformationUserDefinedFields ... 640
199.1.185 CompanyTeamsEntityInformation ... 641
199.1.186 CompanyTeamsEntityInformation_FieldsPicklistValuesFields ... 642
199.1.187 CompanyTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 642
199.1.188 CompanyTeamsEntityInformationFields ... 643
199.1.189 CompanyTeamsEntityInformationUserDefinedFields ... 644
199.1.190 CompanyToDosEntityInformation ... 644
199.1.191 CompanyToDosEntityInformation_FieldsPicklistValuesFields ... 645
199.1.192 CompanyToDosEntityInformation_FieldsPicklistValuesUserDefinedFields ... 646
199.1.193 CompanyToDosEntityInformationFields ... 647
199.1.194 CompanyToDosEntityInformationUserDefinedFields ... 647
199.1.195 CompanyWebhookExcludedResourcesEntityInformation ... 648
199.1.196 CompanyWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields ... 649
199.1.197 CompanyWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 649
199.1.198 CompanyWebhookExcludedResourcesEntityInformationFields ... 650
199.1.199 CompanyWebhookExcludedResourcesEntityInformationUserDefinedFields ... 651
199.1.200 CompanyWebhookFieldsEntityInformation ... 652

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.201 CompanyWebhookFieldsEntityInformation_FieldsPicklistValuesFields 652
199.1.202 CompanyWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 653
199.1.203 CompanyWebhookFieldsEntityInformationFields 654
199.1.204 CompanyWebhookFieldsEntityInformationUserDefinedFields 654
199.1.205 CompanyWebhooksByParentIdExcludedResourcesEntityInformation 655
199.1.206 CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 656
199.1.207 CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.208 CompanyWebhooksByParentIdExcludedResourcesEntityInformationFields 659
199.1.209 CompanyWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 660
199.1.210 CompanyWebhooksByParentIdFieldsEntityInformation 661
199.1.211 CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 662
199.1.212 CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 663
199.1.213 CompanyWebhooksByParentIdFieldsEntityInformationFields 664
199.1.214 CompanyWebhooksByParentIdFieldsEntityInformationUserDefinedFields 665
199.1.215 CompanyWebhooksByParentIdUdfFieldsEntityInformation 667
199.1.216 CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields 668
199.1.217 CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 669
199.1.218 CompanyWebhooksByParentIdUdfFieldsEntityInformationFields 670
199.1.219 CompanyWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields 671
199.1.220 CompanyWebhooksEntityInformation 672
199.1.221 CompanyWebhooksEntityInformation_FieldsPicklistValuesFields 673
199.1.222 CompanyWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 674
199.1.223 CompanyWebhooksEntityInformationFields 675
199.1.224 CompanyWebhooksEntityInformationUserDefinedFields 675
199.1.225 CompanyWebhookUdfFieldsEntityInformation 676
199.1.226 CompanyWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields 676
199.1.227 CompanyWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 677
199.1.228 CompanyWebhookUdfFieldsEntityInformationFields 678
199.1.229 CompanyWebhookUdfFieldsEntityInformationUserDefinedFields 679
199.1.230 ConfigurationItemAttachmentsEntityInformation 679
199.1.231 ConfigurationItemAttachmentsEntityInformation_FieldsPicklistValuesFields 680
199.1.232 ConfigurationItemAttachmentsEntityInformationFields 681
199.1.233 ConfigurationItemBillingProductAssociationsEntityInformation 681
199.1.234 ConfigurationItemBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields 682
199.1.235 ConfigurationItemBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 683
199.1.236 ConfigurationItemBillingProductAssociationsEntityInformationFields 684
199.1.237 ConfigurationItemBillingProductAssociationsEntityInformationUserDefinedFields 684
199.1.238 ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation 685
199.1.239 ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation_FieldsPicklistValuesFields 686
199.1.240 ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.241 ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationFields 687
199.1.242 ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationUserDefinedFields 688
199.1.243 ConfigurationItemCategoriesEntityInformation 690
199.1.244 ConfigurationItemCategoriesEntityInformation_FieldsPicklistValuesFields 690
199.1.245 ConfigurationItemCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 691
199.1.246 ConfigurationItemCategoriesEntityInformationFields 692
199.1.247 ConfigurationItemCategoriesEntityInformationUserDefinedFields 692
199.1.248 ConfigurationItemCategoryUdfAssociationsEntityInformation 693
199.1.249 ConfigurationItemCategoryUdfAssociationsEntityInformation_FieldsPicklistValuesFields 694
199.1.250 ConfigurationItemCategoryUdfAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 695
199.1.251 ConfigurationItemCategoryUdfAssociationsEntityInformationFields 695
199.1.252 ConfigurationItemCategoryUdfAssociationsEntityInformationUserDefinedFields 696
199.1.253 ConfigurationItemDnsRecordsEntityInformation 697
199.1.254 ConfigurationItemDnsRecordsEntityInformation_FieldsPicklistValuesFields 697
199.1.255 ConfigurationItemDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields 698
199.1.256 ConfigurationItemDnsRecordsEntityInformationFields 699
199.1.257 ConfigurationItemDnsRecordsEntityInformationUserDefinedFields 700
199.1.258 ConfigurationItemNoteAttachmentsEntityInformation 700
199.1.259 ConfigurationItemNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 701

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.260 ConfigurationItemNoteAttachmentsEntityInformationFields ... 702
199.1.261 ConfigurationItemNotesEntityInformation ... 702
199.1.262 ConfigurationItemNotesEntityInformation_FieldsPicklistValuesFields ... 703
199.1.263 ConfigurationItemNotesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 704
199.1.264 ConfigurationItemNotesEntityInformationFields ... 705
199.1.265 ConfigurationItemNotesEntityInformationUserDefinedFields ... 705
199.1.266 ConfigurationItemRelatedItemsEntityInformation ... 706
199.1.267 ConfigurationItemRelatedItemsEntityInformation_FieldsPicklistValuesFields ... 706
199.1.268 ConfigurationItemRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 707
199.1.269 ConfigurationItemRelatedItemsEntityInformationFields ... 708
199.1.270 ConfigurationItemRelatedItemsEntityInformationUserDefinedFields ... 709
199.1.271 ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation ... 709
199.1.272 ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields ... 710
199.1.273 ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.274 ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationFields ... 712
199.1.275 ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields ... 713
199.1.276 ConfigurationItemsByParentIdDnsRecordsEntityInformation ... 714
199.1.277 ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesFields ... 715
199.1.278 ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 716
199.1.279 ConfigurationItemsByParentIdDnsRecordsEntityInformationFields ... 717
199.1.280 ConfigurationItemsByParentIdDnsRecordsEntityInformationUserDefinedFields ... 719
199.1.281 ConfigurationItemsByParentIdNotesEntityInformation ... 720
199.1.282 ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesFields ... 721
199.1.283 ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 722
199.1.284 ConfigurationItemsByParentIdNotesEntityInformationFields ... 723
199.1.285 ConfigurationItemsByParentIdNotesEntityInformationUserDefinedFields ... 724
199.1.286 ConfigurationItemsByParentIdRelatedItemsEntityInformation ... 725
199.1.287 ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesFields ... 726
199.1.288 ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 728
199.1.289 ConfigurationItemsByParentIdRelatedItemsEntityInformationFields ... 729
199.1.290 ConfigurationItemsByParentIdRelatedItemsEntityInformationUserDefinedFields ... 730
199.1.291 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation ... 731
199.1.292 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields . 732
199.1.293 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.294 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationFields ... 733
199.1.295 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationUserDefinedFields ... 734
199.1.296 ConfigurationItemsEntityInformation ... 736
199.1.297 ConfigurationItemsEntityInformation_FieldsPicklistValuesFields ... 736
199.1.298 ConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 737
199.1.299 ConfigurationItemsEntityInformationFields ... 738
199.1.300 ConfigurationItemsEntityInformationUserDefinedFields ... 738
199.1.301 ConfigurationItemSslSubjectAlternativeNamesEntityInformation ... 739
199.1.302 ConfigurationItemSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields ... 740
199.1.303 ConfigurationItemSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesUserDefinedFields 741
199.1.304 ConfigurationItemSslSubjectAlternativeNamesEntityInformationFields ... 741
199.1.305 ConfigurationItemSslSubjectAlternativeNamesEntityInformationUserDefinedFields ... 742
199.1.306 ConfigurationItemTypesEntityInformation ... 743
199.1.307 ConfigurationItemTypesEntityInformation_FieldsPicklistValuesFields ... 743
199.1.308 ConfigurationItemTypesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 744
199.1.309 ConfigurationItemTypesEntityInformationFields ... 745
199.1.310 ConfigurationItemTypesEntityInformationUserDefinedFields ... 746
199.1.311 ConfigurationItemWebhookExcludedResourcesEntityInformation ... 746
199.1.312 ConfigurationItemWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields ... 747
199.1.313 ConfigurationItemWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 748
199.1.314 ConfigurationItemWebhookExcludedResourcesEntityInformationFields ... 749
199.1.315 ConfigurationItemWebhookExcludedResourcesEntityInformationUserDefinedFields ... 749
199.1.316 ConfigurationItemWebhookFieldsEntityInformation ... 750
199.1.317 ConfigurationItemWebhookFieldsEntityInformation_FieldsPicklistValuesFields ... 751
199.1.318 ConfigurationItemWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 751

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.319 ConfigurationItemWebhookFieldsEntityInformationFields ... 752
199.1.320 ConfigurationItemWebhookFieldsEntityInformationUserDefinedFields ... 753
199.1.321 ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation ... 754
199.1.322 ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 755
199.1.323 ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.324 ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationFields ... 756
199.1.325 ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields ... 757
199.1.326 ConfigurationItemWebhooksByParentIdFieldsEntityInformation ... 758
199.1.327 ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields ... 759
199.1.328 ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields .. 760
199.1.329 ConfigurationItemWebhooksByParentIdFieldsEntityInformationFields ... 762
199.1.330 ConfigurationItemWebhooksByParentIdFieldsEntityInformationUserDefinedFields ... 763
199.1.331 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation ... 764
199.1.332 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields ... 765
199.1.333 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 36
199.1.334 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationFields ... 767
199.1.335 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields ... 768
199.1.336 ConfigurationItemWebhooksEntityInformation ... 770
199.1.337 ConfigurationItemWebhooksEntityInformation_FieldsPicklistValuesFields ... 770
199.1.338 ConfigurationItemWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields ... 771
199.1.339 ConfigurationItemWebhooksEntityInformationFields ... 772
199.1.340 ConfigurationItemWebhooksEntityInformationUserDefinedFields ... 772
199.1.341 ConfigurationItemWebhookUdfFieldsEntityInformation ... 773
199.1.342 ConfigurationItemWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields ... 774
199.1.343 ConfigurationItemWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 774
199.1.344 ConfigurationItemWebhookUdfFieldsEntityInformationFields ... 775
199.1.345 ConfigurationItemWebhookUdfFieldsEntityInformationUserDefinedFields ... 776
199.1.346 ContactBillingProductAssociationsEntityInformation ... 777
199.1.347 ContactBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields ... 777
199.1.348 ContactBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 778
199.1.349 ContactBillingProductAssociationsEntityInformationFields ... 779
199.1.350 ContactBillingProductAssociationsEntityInformationUserDefinedFields ... 779
199.1.351 ContactGroupContactsEntityInformation ... 780
199.1.352 ContactGroupContactsEntityInformation_FieldsPicklistValuesFields ... 781
199.1.353 ContactGroupContactsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 781
199.1.354 ContactGroupContactsEntityInformationFields ... 782
199.1.355 ContactGroupContactsEntityInformationUserDefinedFields ... 783
199.1.356 ContactGroupsByParentIdContactsEntityInformation ... 784
199.1.357 ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesFields ... 785
199.1.358 ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 786
199.1.359 ContactGroupsByParentIdContactsEntityInformationFields ... 787
199.1.360 ContactGroupsByParentIdContactsEntityInformationUserDefinedFields ... 788
199.1.361 ContactGroupsEntityInformation ... 789
199.1.362 ContactGroupsEntityInformation_FieldsPicklistValuesFields ... 790
199.1.363 ContactGroupsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 791
199.1.364 ContactGroupsEntityInformationFields ... 791
199.1.365 ContactGroupsEntityInformationUserDefinedFields ... 792
199.1.366 ContactsByParentIdBillingProductAssociationsEntityInformation ... 793
199.1.367 ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields ... 794
199.1.368 ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 795
199.1.369 ContactsByParentIdBillingProductAssociationsEntityInformationFields ... 796
199.1.370 ContactsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields ... 797
199.1.371 ContactsEntityInformation ... 798
199.1.372 ContactsEntityInformation_FieldsPicklistValuesFields ... 799
199.1.373 ContactsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 800
199.1.374 ContactsEntityInformationFields ... 801
199.1.375 ContactsEntityInformationUserDefinedFields ... 801
199.1.376 ContactWebhookExcludedResourcesEntityInformation ... 802
199.1.377 ContactWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields ... 803

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.378 ContactWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 803
199.1.379 ContactWebhookExcludedResourcesEntityInformationFields 804
199.1.380 ContactWebhookExcludedResourcesEntityInformationUserDefinedFields 805
199.1.381 ContactWebhookFieldsEntityInformation 806
199.1.382 ContactWebhookFieldsEntityInformation_FieldsPicklistValuesFields 806
199.1.383 ContactWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 807
199.1.384 ContactWebhookFieldsEntityInformationFields 808
199.1.385 ContactWebhookFieldsEntityInformationUserDefinedFields 808
199.1.386 ContactWebhooksByParentIdExcludedResourcesEntityInformation 809
199.1.387 ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 810
199.1.388 ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields I
199.1.389 ContactWebhooksByParentIdExcludedResourcesEntityInformationFields 813
199.1.390 ContactWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 814
199.1.391 ContactWebhooksByParentIdFieldsEntityInformation 815
199.1.392 ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 816
199.1.393 ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 817
199.1.394 ContactWebhooksByParentIdFieldsEntityInformationFields 818
199.1.395 ContactWebhooksByParentIdFieldsEntityInformationUserDefinedFields 819
199.1.396 ContactWebhooksByParentIdUdfFieldsEntityInformation 821
199.1.397 ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields 822
199.1.398 ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 823
199.1.399 ContactWebhooksByParentIdUdfFieldsEntityInformationFields 824
199.1.400 ContactWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields 825
199.1.401 ContactWebhooksEntityInformation 826
199.1.402 ContactWebhooksEntityInformation_FieldsPicklistValuesFields 827
199.1.403 ContactWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 828
199.1.404 ContactWebhooksEntityInformationFields 828
199.1.405 ContactWebhooksEntityInformationUserDefinedFields 829
199.1.406 ContactWebhookUdfFieldsEntityInformation 830
199.1.407 ContactWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields 830
199.1.408 ContactWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 831
199.1.409 ContactWebhookUdfFieldsEntityInformationFields 832
199.1.410 ContactWebhookUdfFieldsEntityInformationUserDefinedFields 833
199.1.411 ContractBillingRulesEntityInformation 833
199.1.412 ContractBillingRulesEntityInformation_FieldsPicklistValuesFields 834
199.1.413 ContractBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields 835
199.1.414 ContractBillingRulesEntityInformationFields 836
199.1.415 ContractBillingRulesEntityInformationUserDefinedFields 836
199.1.416 ContractBlockHourFactorsEntityInformation 837
199.1.417 ContractBlockHourFactorsEntityInformation_FieldsPicklistValuesFields 837
199.1.418 ContractBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields 838
199.1.419 ContractBlockHourFactorsEntityInformationFields 839
199.1.420 ContractBlockHourFactorsEntityInformationUserDefinedFields 840
199.1.421 ContractBlocksEntityInformation 840
199.1.422 ContractBlocksEntityInformation_FieldsPicklistValuesFields 841
199.1.423 ContractBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields 842
199.1.424 ContractBlocksEntityInformationFields 843
199.1.425 ContractBlocksEntityInformationUserDefinedFields 843
199.1.426 ContractChargesEntityInformation 844
199.1.427 ContractChargesEntityInformation_FieldsPicklistValuesFields 845
199.1.428 ContractChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 845
199.1.429 ContractChargesEntityInformationFields 846
199.1.430 ContractChargesEntityInformationUserDefinedFields 847
199.1.431 ContractExclusionBillingCodesEntityInformation 847
199.1.432 ContractExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields 848
199.1.433 ContractExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields 849
199.1.434 ContractExclusionBillingCodesEntityInformationFields 850
199.1.435 ContractExclusionBillingCodesEntityInformationUserDefinedFields 850
199.1.436 ContractExclusionRolesEntityInformation 851

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.437 ContractExclusionRolesEntityInformation_FieldsPicklistValuesFields ... 852
199.1.438 ContractExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 852
199.1.439 ContractExclusionRolesEntityInformationFields ... 853
199.1.440 ContractExclusionRolesEntityInformationUserDefinedFields ... 854
199.1.441 ContractExclusionSetExcludedRolesEntityInformation ... 854
199.1.442 ContractExclusionSetExcludedRolesEntityInformation_FieldsPicklistValuesFields ... 855
199.1.443 ContractExclusionSetExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 856
199.1.444 ContractExclusionSetExcludedRolesEntityInformationFields ... 857
199.1.445 ContractExclusionSetExcludedRolesEntityInformationUserDefinedFields ... 857
199.1.446 ContractExclusionSetExcludedWorkTypesEntityInformation ... 858
199.1.447 ContractExclusionSetExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields ... 859
199.1.448 ContractExclusionSetExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 860
199.1.449 ContractExclusionSetExcludedWorkTypesEntityInformationFields ... 860
199.1.450 ContractExclusionSetExcludedWorkTypesEntityInformationUserDefinedFields ... 861
199.1.451 ContractExclusionSetsByParentIdExcludedRolesEntityInformation ... 862
199.1.452 ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesFields ... 863
199.1.453 ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 864
199.1.454 ContractExclusionSetsByParentIdExcludedRolesEntityInformationFields ... 865
199.1.455 ContractExclusionSetsByParentIdExcludedRolesEntityInformationUserDefinedFields ... 866
199.1.456 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation ... 868
199.1.457 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields ... 869
199.1.458 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.459 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationFields ... 871
199.1.460 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationUserDefinedFields ... 872
199.1.461 ContractExclusionSetsEntityInformation ... 873
199.1.462 ContractExclusionSetsEntityInformation_FieldsPicklistValuesFields ... 874
199.1.463 ContractExclusionSetsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 875
199.1.464 ContractExclusionSetsEntityInformationFields ... 876
199.1.465 ContractExclusionSetsEntityInformationUserDefinedFields ... 876
199.1.466 ContractMilestonesEntityInformation ... 877
199.1.467 ContractMilestonesEntityInformation_FieldsPicklistValuesFields ... 877
199.1.468 ContractMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 878
199.1.469 ContractMilestonesEntityInformationFields ... 879
199.1.470 ContractMilestonesEntityInformationUserDefinedFields ... 880
199.1.471 ContractNoteAttachmentsEntityInformation ... 880
199.1.472 ContractNoteAttachmentsEntityInformation_FieldsPicklistValuesFields ... 881
199.1.473 ContractNoteAttachmentsEntityInformationFields ... 882
199.1.474 ContractNotesEntityInformation ... 882
199.1.475 ContractNotesEntityInformation_FieldsPicklistValuesFields ... 883
199.1.476 ContractNotesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 884
199.1.477 ContractNotesEntityInformationFields ... 885
199.1.478 ContractNotesEntityInformationUserDefinedFields ... 885
199.1.479 ContractRatesEntityInformation ... 886
199.1.480 ContractRatesEntityInformation_FieldsPicklistValuesFields ... 886
199.1.481 ContractRatesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 887
199.1.482 ContractRatesEntityInformationFields ... 888
199.1.483 ContractRatesEntityInformationUserDefinedFields ... 889
199.1.484 ContractRetainersEntityInformation ... 889
199.1.485 ContractRetainersEntityInformation_FieldsPicklistValuesFields ... 890
199.1.486 ContractRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields ... 891
199.1.487 ContractRetainersEntityInformationFields ... 892
199.1.488 ContractRetainersEntityInformationUserDefinedFields ... 892
199.1.489 ContractRoleCostsEntityInformation ... 893
199.1.490 ContractRoleCostsEntityInformation_FieldsPicklistValuesFields ... 893
199.1.491 ContractRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 894
199.1.492 ContractRoleCostsEntityInformationFields ... 895
199.1.493 ContractRoleCostsEntityInformationUserDefinedFields ... 896
199.1.494 ContractsByParentIdBillingRulesEntityInformation ... 896
199.1.495 ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesFields ... 897

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.496 ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 899
199.1.497 ContractsByParentIdBillingRulesEntityInformationFields ... 900
199.1.498 ContractsByParentIdBillingRulesEntityInformationUserDefinedFields ... 901
199.1.499 ContractsByParentIdBlockHourFactorsEntityInformation ... 902
199.1.500 ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesFields ... 903
199.1.501 ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 904
199.1.502 ContractsByParentIdBlockHourFactorsEntityInformationFields ... 906
199.1.503 ContractsByParentIdBlockHourFactorsEntityInformationUserDefinedFields ... 907
199.1.504 ContractsByParentIdBlocksEntityInformation ... 908
199.1.505 ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesFields ... 909
199.1.506 ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields ... 910
199.1.507 ContractsByParentIdBlocksEntityInformationFields ... 911
199.1.508 ContractsByParentIdBlocksEntityInformationUserDefinedFields ... 912
199.1.509 ContractsByParentIdChargesEntityInformation ... 913
199.1.510 ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesFields ... 914
199.1.511 ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 916
199.1.512 ContractsByParentIdChargesEntityInformationFields ... 917
199.1.513 ContractsByParentIdChargesEntityInformationUserDefinedFields ... 918
199.1.514 ContractsByParentIdExclusionBillingCodesEntityInformation ... 919
199.1.515 ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields ... 920
199.1.516 ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 921
199.1.517 ContractsByParentIdExclusionBillingCodesEntityInformationFields ... 923
199.1.518 ContractsByParentIdExclusionBillingCodesEntityInformationUserDefinedFields ... 924
199.1.519 ContractsByParentIdExclusionRolesEntityInformation ... 925
199.1.520 ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesFields ... 926
199.1.521 ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 927
199.1.522 ContractsByParentIdExclusionRolesEntityInformationFields ... 928
199.1.523 ContractsByParentIdExclusionRolesEntityInformationUserDefinedFields ... 929
199.1.524 ContractsByParentIdMilestonesEntityInformation ... 930
199.1.525 ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesFields ... 931
199.1.526 ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 933
199.1.527 ContractsByParentIdMilestonesEntityInformationFields ... 934
199.1.528 ContractsByParentIdMilestonesEntityInformationUserDefinedFields ... 935
199.1.529 ContractsByParentIdNotesEntityInformation ... 936
199.1.530 ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesFields ... 937
199.1.531 ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 938
199.1.532 ContractsByParentIdNotesEntityInformationFields ... 940
199.1.533 ContractsByParentIdNotesEntityInformationUserDefinedFields ... 941
199.1.534 ContractsByParentIdRatesEntityInformation ... 942
199.1.535 ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesFields ... 943
199.1.536 ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 944
199.1.537 ContractsByParentIdRatesEntityInformationFields ... 945
199.1.538 ContractsByParentIdRatesEntityInformationUserDefinedFields ... 946
199.1.539 ContractsByParentIdRetainersEntityInformation ... 947
199.1.540 ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesFields ... 948
199.1.541 ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields ... 950
199.1.542 ContractsByParentIdRetainersEntityInformationFields ... 951
199.1.543 ContractsByParentIdRetainersEntityInformationUserDefinedFields ... 952
199.1.544 ContractsByParentIdRoleCostsEntityInformation ... 953
199.1.545 ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesFields ... 954
199.1.546 ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 955
199.1.547 ContractsByParentIdRoleCostsEntityInformationFields ... 956
199.1.548 ContractsByParentIdRoleCostsEntityInformationUserDefinedFields ... 957
199.1.549 ContractsByParentIdServiceAdjustmentsEntityInformation ... 959
199.1.550 ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields ... 960
199.1.551 ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 961
199.1.552 ContractsByParentIdServiceAdjustmentsEntityInformationFields ... 962
199.1.553 ContractsByParentIdServiceAdjustmentsEntityInformationUserDefinedFields ... 963
199.1.554 ContractsByParentIdServiceBundleAdjustmentsEntityInformation ... 964

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.555 ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields 965
199.1.556 ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 67
199.1.557 ContractsByParentIdServiceBundleAdjustmentsEntityInformationFields 968
199.1.558 ContractsByParentIdServiceBundleAdjustmentsEntityInformationUserDefinedFields 969
199.1.559 ContractsByParentIdServiceBundlesEntityInformation 970
199.1.560 ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesFields 971
199.1.561 ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields 972
199.1.562 ContractsByParentIdServiceBundlesEntityInformationFields 974
199.1.563 ContractsByParentIdServiceBundlesEntityInformationUserDefinedFields 975
199.1.564 ContractsByParentIdServiceBundleUnitsEntityInformation 976
199.1.565 ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields 977
199.1.566 ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields 978
199.1.567 ContractsByParentIdServiceBundleUnitsEntityInformationFields 979
199.1.568 ContractsByParentIdServiceBundleUnitsEntityInformationUserDefinedFields 980
199.1.569 ContractsByParentIdServicesEntityInformation 982
199.1.570 ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesFields 983
199.1.571 ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 984
199.1.572 ContractsByParentIdServicesEntityInformationFields 985
199.1.573 ContractsByParentIdServicesEntityInformationUserDefinedFields 986
199.1.574 ContractsByParentIdServiceUnitsEntityInformation 987
199.1.575 ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesFields 988
199.1.576 ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields 989
199.1.577 ContractsByParentIdServiceUnitsEntityInformationFields 991
199.1.578 ContractsByParentIdServiceUnitsEntityInformationUserDefinedFields 992
199.1.579 ContractsByParentIdTicketPurchasesEntityInformation 993
199.1.580 ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesFields 994
199.1.581 ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields 995
199.1.582 ContractsByParentIdTicketPurchasesEntityInformationFields 996
199.1.583 ContractsByParentIdTicketPurchasesEntityInformationUserDefinedFields 997
199.1.584 ContractsEntityInformation 999
199.1.585 ContractsEntityInformation_FieldsPicklistValuesFields 999
199.1.586 ContractsEntityInformation_FieldsPicklistValuesUserDefinedFields 1000
199.1.587 ContractsEntityInformationFields 1001
199.1.588 ContractsEntityInformationUserDefinedFields 1001
199.1.589 ContractServiceAdjustmentsEntityInformation 1002
199.1.590 ContractServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields 1003
199.1.591 ContractServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1003
199.1.592 ContractServiceAdjustmentsEntityInformationFields 1004
199.1.593 ContractServiceAdjustmentsEntityInformationUserDefinedFields 1005
199.1.594 ContractServiceBundleAdjustmentsEntityInformation 1006
199.1.595 ContractServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields 1006
199.1.596 ContractServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1007
199.1.597 ContractServiceBundleAdjustmentsEntityInformationFields 1008
199.1.598 ContractServiceBundleAdjustmentsEntityInformationUserDefinedFields 1008
199.1.599 ContractServiceBundlesEntityInformation 1009
199.1.600 ContractServiceBundlesEntityInformation_FieldsPicklistValuesFields 1010
199.1.601 ContractServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields 1011
199.1.602 ContractServiceBundlesEntityInformationFields 1011
199.1.603 ContractServiceBundlesEntityInformationUserDefinedFields 1012
199.1.604 ContractServiceBundleUnitsEntityInformation 1013
199.1.605 ContractServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields 1013
199.1.606 ContractServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields 1014
199.1.607 ContractServiceBundleUnitsEntityInformationFields 1015
199.1.608 ContractServiceBundleUnitsEntityInformationUserDefinedFields 1016
199.1.609 ContractServicesEntityInformation 1016
199.1.610 ContractServicesEntityInformation_FieldsPicklistValuesFields 1017
199.1.611 ContractServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1018
199.1.612 ContractServicesEntityInformationFields 1018
199.1.613 ContractServicesEntityInformationUserDefinedFields 1019

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.614 ContractServiceUnitsEntityInformation ... 1020
199.1.615 ContractServiceUnitsEntityInformation_FieldsPicklistValuesFields ... 1020
199.1.616 ContractServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1021
199.1.617 ContractServiceUnitsEntityInformationFields ... 1022
199.1.618 ContractServiceUnitsEntityInformationUserDefinedFields ... 1023
199.1.619 ContractTicketPurchasesEntityInformation ... 1023
199.1.620 ContractTicketPurchasesEntityInformation_FieldsPicklistValuesFields ... 1024
199.1.621 ContractTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1025
199.1.622 ContractTicketPurchasesEntityInformationFields ... 1026
199.1.623 ContractTicketPurchasesEntityInformationUserDefinedFields ... 1026
199.1.624 CountriesEntityInformation ... 1027
199.1.625 CountriesEntityInformation_FieldsPicklistValuesFields ... 1027
199.1.626 CountriesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1028
199.1.627 CountriesEntityInformationFields ... 1029
199.1.628 CountriesEntityInformationUserDefinedFields ... 1030
199.1.629 CurrenciesEntityInformation ... 1030
199.1.630 CurrenciesEntityInformation_FieldsPicklistValuesFields ... 1031
199.1.631 CurrenciesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1032
199.1.632 CurrenciesEntityInformationFields ... 1033
199.1.633 CurrenciesEntityInformationUserDefinedFields ... 1033
199.1.634 DeletedTaskActivityLogsEntityInformation ... 1034
199.1.635 DeletedTaskActivityLogsEntityInformation_FieldsPicklistValuesFields ... 1034
199.1.636 DeletedTaskActivityLogsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1035
199.1.637 DeletedTaskActivityLogsEntityInformationFields ... 1036
199.1.638 DeletedTaskActivityLogsEntityInformationUserDefinedFields ... 1037
199.1.639 DeletedTicketActivityLogsEntityInformation ... 1037
199.1.640 DeletedTicketActivityLogsEntityInformation_FieldsPicklistValuesFields ... 1038
199.1.641 DeletedTicketActivityLogsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1039
199.1.642 DeletedTicketActivityLogsEntityInformationFields ... 1040
199.1.643 DeletedTicketActivityLogsEntityInformationUserDefinedFields ... 1040
199.1.644 DeletedTicketLogsEntityInformation ... 1041
199.1.645 DeletedTicketLogsEntityInformation_FieldsPicklistValuesFields ... 1042
199.1.646 DeletedTicketLogsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1042
199.1.647 DeletedTicketLogsEntityInformationFields ... 1043
199.1.648 DeletedTicketLogsEntityInformationUserDefinedFields ... 1044
199.1.649 DepartmentsEntityInformation ... 1044
199.1.650 DepartmentsEntityInformation_FieldsPicklistValuesFields ... 1045
199.1.651 DepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1046
199.1.652 DepartmentsEntityInformationFields ... 1047
199.1.653 DepartmentsEntityInformationUserDefinedFields ... 1047
199.1.654 DocumentAttachmentsEntityInformation ... 1048
199.1.655 DocumentAttachmentsEntityInformation_FieldsPicklistValuesFields ... 1049
199.1.656 DocumentAttachmentsEntityInformationFields ... 1049
199.1.657 DocumentCategoriesByParentIdDocumentsEntityInformation ... 1050
199.1.658 DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesFields ... 1051
199.1.659 DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1052
199.1.660 DocumentCategoriesByParentIdDocumentsEntityInformationFields ... 1053
199.1.661 DocumentCategoriesByParentIdDocumentsEntityInformationUserDefinedFields ... 1055
199.1.662 DocumentCategoriesEntityInformation ... 1056
199.1.663 DocumentCategoriesEntityInformation_FieldsPicklistValuesFields ... 1056
199.1.664 DocumentCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1057
199.1.665 DocumentCategoriesEntityInformationFields ... 1058
199.1.666 DocumentCategoriesEntityInformationUserDefinedFields ... 1059
199.1.667 DocumentChecklistItemsEntityInformation ... 1059
199.1.668 DocumentChecklistItemsEntityInformation_FieldsPicklistValuesFields ... 1060
199.1.669 DocumentChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1061
199.1.670 DocumentChecklistItemsEntityInformationFields ... 1062
199.1.671 DocumentChecklistItemsEntityInformationUserDefinedFields ... 1062
199.1.672 DocumentChecklistLibrariesEntityInformation ... 1063

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.673 DocumentChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 1063
199.1.674 DocumentChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 1064
199.1.675 DocumentChecklistLibrariesEntityInformationFields 1065
199.1.676 DocumentChecklistLibrariesEntityInformationUserDefinedFields 1066
199.1.677 DocumentConfigurationItemAssociationsEntityInformation 1066
199.1.678 DocumentConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields 1067
199.1.679 DocumentConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1068
199.1.680 DocumentConfigurationItemAssociationsEntityInformationFields 1069
199.1.681 DocumentConfigurationItemAssociationsEntityInformationUserDefinedFields 1069
199.1.682 DocumentConfigurationItemCategoryAssociationsEntityInformation 1070
199.1.683 DocumentConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields 1071
199.1.684 DocumentConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields I
199.1.685 DocumentConfigurationItemCategoryAssociationsEntityInformationFields 1072
199.1.686 DocumentConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields 1073
199.1.687 DocumentNotesEntityInformation 1074
199.1.688 DocumentNotesEntityInformation_FieldsPicklistValuesFields 1074
199.1.689 DocumentNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1075
199.1.690 DocumentNotesEntityInformationFields 1076
199.1.691 DocumentNotesEntityInformationUserDefinedFields 1076
199.1.692 DocumentPlainTextContentEntityInformation 1077
199.1.693 DocumentPlainTextContentEntityInformation_FieldsPicklistValuesFields 1078
199.1.694 DocumentPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields 1078
199.1.695 DocumentPlainTextContentEntityInformationFields 1079
199.1.696 DocumentPlainTextContentEntityInformationUserDefinedFields 1080
199.1.697 DocumentsByParentIdArticleAssociationsEntityInformation 1081
199.1.698 DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields 1082
199.1.699 DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1083
199.1.700 DocumentsByParentIdArticleAssociationsEntityInformationFields 1084
199.1.701 DocumentsByParentIdArticleAssociationsEntityInformationUserDefinedFields 1085
199.1.702 DocumentsByParentIdChecklistItemsEntityInformation 1086
199.1.703 DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields 1087
199.1.704 DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1089
199.1.705 DocumentsByParentIdChecklistItemsEntityInformationFields 1090
199.1.706 DocumentsByParentIdChecklistItemsEntityInformationUserDefinedFields 1091
199.1.707 DocumentsByParentIdChecklistLibrariesEntityInformation 1092
199.1.708 DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 1093
199.1.709 DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 1094
199.1.710 DocumentsByParentIdChecklistLibrariesEntityInformationFields 1096
199.1.711 DocumentsByParentIdChecklistLibrariesEntityInformationUserDefinedFields 1097
199.1.712 DocumentsByParentIdConfigurationItemAssociationsEntityInformation 1098
199.1.713 DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields 1099
199.1.714 DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.715 DocumentsByParentIdConfigurationItemAssociationsEntityInformationFields 1101
199.1.716 DocumentsByParentIdConfigurationItemAssociationsEntityInformationUserDefinedFields 1102
199.1.717 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation 1104
199.1.718 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields 5
199.1.719 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.720 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationFields 1106
199.1.721 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields 1107
199.1.722 DocumentsByParentIdDocumentAssociationsEntityInformation 1108
199.1.723 DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields 1109
199.1.724 DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1110
199.1.725 DocumentsByParentIdDocumentAssociationsEntityInformationFields 1112
199.1.726 DocumentsByParentIdDocumentAssociationsEntityInformationUserDefinedFields 1113
199.1.727 DocumentsByParentIdNotesEntityInformation 1114
199.1.728 DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1115
199.1.729 DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1116
199.1.730 DocumentsByParentIdNotesEntityInformationFields 1117
199.1.731 DocumentsByParentIdNotesEntityInformationUserDefinedFields 1118

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.732 DocumentsByParentIdPlainTextContentEntityInformation 1120
199.1.733 DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields 1121
199.1.734 DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields 1122
199.1.735 DocumentsByParentIdPlainTextContentEntityInformationFields 1123
199.1.736 DocumentsByParentIdPlainTextContentEntityInformationUserDefinedFields 1124
199.1.737 DocumentsByParentIdTagAssociationsEntityInformation 1125
199.1.738 DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields 1126
199.1.739 DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1128
199.1.740 DocumentsByParentIdTagAssociationsEntityInformationFields 1129
199.1.741 DocumentsByParentIdTagAssociationsEntityInformationUserDefinedFields 1130
199.1.742 DocumentsByParentIdTicketAssociationsEntityInformation 1131
199.1.743 DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields 1132
199.1.744 DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1133
199.1.745 DocumentsByParentIdTicketAssociationsEntityInformationFields 1135
199.1.746 DocumentsByParentIdTicketAssociationsEntityInformationUserDefinedFields 1136
199.1.747 DocumentsEntityInformation 1137
199.1.748 DocumentsEntityInformation_FieldsPicklistValuesFields 1137
199.1.749 DocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1138
199.1.750 DocumentsEntityInformationFields 1139
199.1.751 DocumentsEntityInformationUserDefinedFields 1140
199.1.752 DocumentTagAssociationsEntityInformation 1140
199.1.753 DocumentTagAssociationsEntityInformation_FieldsPicklistValuesFields 1141
199.1.754 DocumentTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1142
199.1.755 DocumentTagAssociationsEntityInformationFields 1143
199.1.756 DocumentTagAssociationsEntityInformationUserDefinedFields 1143
199.1.757 DocumentTicketAssociationsEntityInformation 1144
199.1.758 DocumentTicketAssociationsEntityInformation_FieldsPicklistValuesFields 1144
199.1.759 DocumentTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1145
199.1.760 DocumentTicketAssociationsEntityInformationFields 1146
199.1.761 DocumentTicketAssociationsEntityInformationUserDefinedFields 1147
199.1.762 DocumentToArticleAssociationsEntityInformation 1147
199.1.763 DocumentToArticleAssociationsEntityInformation_FieldsPicklistValuesFields 1148
199.1.764 DocumentToArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1149
199.1.765 DocumentToArticleAssociationsEntityInformationFields 1150
199.1.766 DocumentToArticleAssociationsEntityInformationUserDefinedFields 1150
199.1.767 DocumentToDocumentAssociationsEntityInformation 1151
199.1.768 DocumentToDocumentAssociationsEntityInformation_FieldsPicklistValuesFields 1152
199.1.769 DocumentToDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1152
199.1.770 DocumentToDocumentAssociationsEntityInformationFields 1153
199.1.771 DocumentToDocumentAssociationsEntityInformationUserDefinedFields 1154
199.1.772 DomainRegistrarsEntityInformation 1155
199.1.773 DomainRegistrarsEntityInformation_FieldsPicklistValuesFields 1155
199.1.774 DomainRegistrarsEntityInformation_FieldsPicklistValuesUserDefinedFields 1156
199.1.775 DomainRegistrarsEntityInformationFields 1157
199.1.776 DomainRegistrarsEntityInformationUserDefinedFields 1157
199.1.777 ExpenseItemAttachmentsEntityInformation 1158
199.1.778 ExpenseItemAttachmentsEntityInformation_FieldsPicklistValuesFields 1159
199.1.779 ExpenseItemAttachmentsEntityInformationFields 1159
199.1.780 ExpenseItemsEntityInformation 1160
199.1.781 ExpenseItemsEntityInformation_FieldsPicklistValuesFields 1161
199.1.782 ExpenseItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1161
199.1.783 ExpenseItemsEntityInformationFields 1162
199.1.784 ExpenseItemsEntityInformationUserDefinedFields 1163
199.1.785 ExpenseReportAttachmentsEntityInformation 1164
199.1.786 ExpenseReportAttachmentsEntityInformation_FieldsPicklistValuesFields 1164
199.1.787 ExpenseReportAttachmentsEntityInformationFields 1165
199.1.788 ExpenseReportsEntityInformation 1166
199.1.789 ExpenseReportsEntityInformation_FieldsPicklistValuesFields 1166
199.1.790 ExpenseReportsEntityInformation_FieldsPicklistValuesUserDefinedFields 1167

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.791 ExpenseReportsEntityInformationFields ... 1168
199.1.792 ExpenseReportsEntityInformationUserDefinedFields ... 1168
199.1.793 ExpensesByParentIdItemsEntityInformation ... 1169
199.1.794 ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesFields ... 1170
199.1.795 ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1171
199.1.796 ExpensesByParentIdItemsEntityInformationFields ... 1173
199.1.797 ExpensesByParentIdItemsEntityInformationUserDefinedFields ... 1174
199.1.798 HolidaysEntityInformation ... 1175
199.1.799 HolidaysEntityInformation_FieldsPicklistValuesFields ... 1175
199.1.800 HolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1176
199.1.801 HolidaysEntityInformationFields ... 1177
199.1.802 HolidaysEntityInformationUserDefinedFields ... 1177
199.1.803 HolidaySetsByParentIdHolidaysEntityInformation ... 1178
199.1.804 HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesFields ... 1179
199.1.805 HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1180
199.1.806 HolidaySetsByParentIdHolidaysEntityInformationFields ... 1182
199.1.807 HolidaySetsByParentIdHolidaysEntityInformationUserDefinedFields ... 1183
199.1.808 HolidaySetsEntityInformation ... 1184
199.1.809 HolidaySetsEntityInformation_FieldsPicklistValuesFields ... 1184
199.1.810 HolidaySetsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1185
199.1.811 HolidaySetsEntityInformationFields ... 1186
199.1.812 HolidaySetsEntityInformationUserDefinedFields ... 1187
199.1.813 IntegrationVendorInsightsEntityInformation ... 1187
199.1.814 IntegrationVendorInsightsEntityInformation_FieldsPicklistValuesFields ... 1188
199.1.815 IntegrationVendorInsightsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1189
199.1.816 IntegrationVendorInsightsEntityInformationFields ... 1190
199.1.817 IntegrationVendorInsightsEntityInformationUserDefinedFields ... 1190
199.1.818 IntegrationVendorWidgetsEntityInformation ... 1191
199.1.819 IntegrationVendorWidgetsEntityInformation_FieldsPicklistValuesFields ... 1191
199.1.820 IntegrationVendorWidgetsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1192
199.1.821 IntegrationVendorWidgetsEntityInformationFields ... 1193
199.1.822 IntegrationVendorWidgetsEntityInformationUserDefinedFields ... 1194
199.1.823 InternalLocationsEntityInformation ... 1194
199.1.824 InternalLocationsEntityInformation_FieldsPicklistValuesFields ... 1195
199.1.825 InternalLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1196
199.1.826 InternalLocationsEntityInformationFields ... 1197
199.1.827 InternalLocationsEntityInformationUserDefinedFields ... 1197
199.1.828 InternalLocationWithBusinessHoursEntityInformation ... 1198
199.1.829 InternalLocationWithBusinessHoursEntityInformation_FieldsPicklistValuesFields ... 1199
199.1.830 InternalLocationWithBusinessHoursEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1199
199.1.831 InternalLocationWithBusinessHoursEntityInformationFields ... 1200
199.1.832 InternalLocationWithBusinessHoursEntityInformationUserDefinedFields ... 1201
199.1.833 InventoryItemsByParentIdSerialNumbersEntityInformation ... 1202
199.1.834 InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesFields ... 1203
199.1.835 InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1204
199.1.836 InventoryItemsByParentIdSerialNumbersEntityInformationFields ... 1205
199.1.837 InventoryItemsByParentIdSerialNumbersEntityInformationUserDefinedFields ... 1206
199.1.838 InventoryItemsEntityInformation ... 1207
199.1.839 InventoryItemsEntityInformation_FieldsPicklistValuesFields ... 1208
199.1.840 InventoryItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1209
199.1.841 InventoryItemsEntityInformationFields ... 1210
199.1.842 InventoryItemsEntityInformationUserDefinedFields ... 1210
199.1.843 InventoryItemSerialNumbersEntityInformation ... 1211
199.1.844 InventoryItemSerialNumbersEntityInformation_FieldsPicklistValuesFields ... 1211
199.1.845 InventoryItemSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1212
199.1.846 InventoryItemSerialNumbersEntityInformationFields ... 1213
199.1.847 InventoryItemSerialNumbersEntityInformationUserDefinedFields ... 1214
199.1.848 InventoryLocationsEntityInformation ... 1214
199.1.849 InventoryLocationsEntityInformation_FieldsPicklistValuesFields ... 1215

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.850 InventoryLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1216
199.1.851 InventoryLocationsEntityInformationFields ... 1217
199.1.852 InventoryLocationsEntityInformationUserDefinedFields ... 1217
199.1.853 InventoryProductsByParentIdStockedItemsAddEntityInformation ... 1218
199.1.854 InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesFields ... 1219
199.1.855 InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields 220
199.1.856 InventoryProductsByParentIdStockedItemsAddEntityInformationFields ... 1221
199.1.857 InventoryProductsByParentIdStockedItemsAddEntityInformationUserDefinedFields ... 1223
199.1.858 InventoryProductsByParentIdStockedItemsEntityInformation ... 1224
199.1.859 InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesFields ... 1225
199.1.860 InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1226
199.1.861 InventoryProductsByParentIdStockedItemsEntityInformationFields ... 1227
199.1.862 InventoryProductsByParentIdStockedItemsEntityInformationUserDefinedFields ... 1228
199.1.863 InventoryProductsByParentIdStockedItemsRemoveEntityInformation ... 1229
199.1.864 InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields ... 1230
199.1.865 InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.866 InventoryProductsByParentIdStockedItemsRemoveEntityInformationFields ... 1233
199.1.867 InventoryProductsByParentIdStockedItemsRemoveEntityInformationUserDefinedFields ... 1234
199.1.868 InventoryProductsByParentIdStockedItemsTransferEntityInformation ... 1235
199.1.869 InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesFields ... 1236
199.1.870 InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.871 InventoryProductsByParentIdStockedItemsTransferEntityInformationFields ... 1239
199.1.872 InventoryProductsByParentIdStockedItemsTransferEntityInformationUserDefinedFields ... 1240
199.1.873 InventoryProductsEntityInformation ... 1241
199.1.874 InventoryProductsEntityInformation_FieldsPicklistValuesFields ... 1242
199.1.875 InventoryProductsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1242
199.1.876 InventoryProductsEntityInformationFields ... 1243
199.1.877 InventoryProductsEntityInformationUserDefinedFields ... 1244
199.1.878 InventoryStockedItemsAddEntityInformation ... 1244
199.1.879 InventoryStockedItemsAddEntityInformation_FieldsPicklistValuesFields ... 1245
199.1.880 InventoryStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1246
199.1.881 InventoryStockedItemsAddEntityInformationFields ... 1247
199.1.882 InventoryStockedItemsAddEntityInformationUserDefinedFields ... 1247
199.1.883 InventoryStockedItemsEntityInformation ... 1248
199.1.884 InventoryStockedItemsEntityInformation_FieldsPicklistValuesFields ... 1249
199.1.885 InventoryStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1249
199.1.886 InventoryStockedItemsEntityInformationFields ... 1250
199.1.887 InventoryStockedItemsEntityInformationUserDefinedFields ... 1251
199.1.888 InventoryStockedItemsRemoveEntityInformation ... 1251
199.1.889 InventoryStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields ... 1252
199.1.890 InventoryStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1253
199.1.891 InventoryStockedItemsRemoveEntityInformationFields ... 1254
199.1.892 InventoryStockedItemsRemoveEntityInformationUserDefinedFields ... 1254
199.1.893 InventoryStockedItemsTransferEntityInformation ... 1255
199.1.894 InventoryStockedItemsTransferEntityInformation_FieldsPicklistValuesFields ... 1256
199.1.895 InventoryStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1256
199.1.896 InventoryStockedItemsTransferEntityInformationFields ... 1257
199.1.897 InventoryStockedItemsTransferEntityInformationUserDefinedFields ... 1258
199.1.898 InventoryTransfersEntityInformation ... 1258
199.1.899 InventoryTransfersEntityInformation_FieldsPicklistValuesFields ... 1259
199.1.900 InventoryTransfersEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1260
199.1.901 InventoryTransfersEntityInformationFields ... 1261
199.1.902 InventoryTransfersEntityInformationUserDefinedFields ... 1261
199.1.903 InvoicesEntityInformation ... 1262
199.1.904 InvoicesEntityInformation_FieldsPicklistValuesFields ... 1263
199.1.905 InvoicesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1263
199.1.906 InvoicesEntityInformationFields ... 1264
199.1.907 InvoicesEntityInformationUserDefinedFields ... 1265
199.1.908 InvoiceTemplatesEntityInformation ... 1265

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.909 InvoiceTemplatesEntityInformation_FieldsPicklistValuesFields 1266
199.1.910 InvoiceTemplatesEntityInformation_FieldsPicklistValuesUserDefinedFields 1267
199.1.911 InvoiceTemplatesEntityInformationFields 1268
199.1.912 InvoiceTemplatesEntityInformationUserDefinedFields 1268
199.1.913 KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation 1269
199.1.914 KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields 1270
199.1.915 KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.916 KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationFields 1271
199.1.917 KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationUserDefinedFields 1272
199.1.918 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation 1273
199.1.919 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields
199.1.920 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.921 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationFields 1276
199.1.922 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields
199.1.923 KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation 1278
199.1.924 KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields 1279
199.1.925 KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.926 KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationFields 1280
199.1.927 KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationUserDefinedFields 1281
199.1.928 KnowledgeBaseArticlesByParentIdNotesEntityInformation 1282
199.1.929 KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1283
199.1.930 KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1285
199.1.931 KnowledgeBaseArticlesByParentIdNotesEntityInformationFields 1286
199.1.932 KnowledgeBaseArticlesByParentIdNotesEntityInformationUserDefinedFields 1287
199.1.933 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation 1288
199.1.934 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields 1289
199.1.935 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.936 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationFields 1292
199.1.937 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationUserDefinedFields 1293
199.1.938 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation 1294
199.1.939 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields 1295
199.1.940 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.941 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationFields 1298
199.1.942 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationUserDefinedFields 1299
199.1.943 KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation 1300
199.1.944 KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields 1301
199.1.945 KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.946 KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationFields 1302
199.1.947 KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationUserDefinedFields 1303
199.1.948 KnowledgeBaseArticlesEntityInformation 1304
199.1.949 KnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields 1305
199.1.950 KnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesUserDefinedFields 1306
199.1.951 KnowledgeBaseArticlesEntityInformationFields 1307
199.1.952 KnowledgeBaseArticlesEntityInformationUserDefinedFields 1307
199.1.953 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation 1308
199.1.954 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields
199.1.955 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.956 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationFields 1310
199.1.957 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationUserDefinedFields 1311
199.1.958 KnowledgeBaseCategoriesEntityInformation 1312
199.1.959 KnowledgeBaseCategoriesEntityInformation_FieldsPicklistValuesFields 1313
199.1.960 KnowledgeBaseCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1314
199.1.961 KnowledgeBaseCategoriesEntityInformationFields 1315
199.1.962 KnowledgeBaseCategoriesEntityInformationUserDefinedFields 1315
199.1.963 NotificationHistoryEntityInformation 1316
199.1.964 NotificationHistoryEntityInformation_FieldsPicklistValuesFields 1316
199.1.965 NotificationHistoryEntityInformation_FieldsPicklistValuesUserDefinedFields 1317
199.1.966 NotificationHistoryEntityInformationFields 1318
199.1.967 NotificationHistoryEntityInformationUserDefinedFields 1319

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.968 OpportunitiesByParentIdSalesOrdersEntityInformation ... 1319
199.1.969 OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesFields ... 1320
199.1.970 OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1322
199.1.971 OpportunitiesByParentIdSalesOrdersEntityInformationFields ... 1323
199.1.972 OpportunitiesByParentIdSalesOrdersEntityInformationUserDefinedFields ... 1324
199.1.973 OpportunitiesEntityInformation ... 1325
199.1.974 OpportunitiesEntityInformation_FieldsPicklistValuesFields ... 1326
199.1.975 OpportunitiesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1326
199.1.976 OpportunitiesEntityInformationFields ... 1327
199.1.977 OpportunitiesEntityInformationUserDefinedFields ... 1328
199.1.978 OpportunityAttachmentsEntityInformation ... 1329
199.1.979 OpportunityAttachmentsEntityInformation_FieldsPicklistValuesFields ... 1329
199.1.980 OpportunityAttachmentsEntityInformationFields ... 1330
199.1.981 OrganizationalLevel1sEntityInformation ... 1331
199.1.982 OrganizationalLevel1sEntityInformation_FieldsPicklistValuesFields ... 1331
199.1.983 OrganizationalLevel1sEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1332
199.1.984 OrganizationalLevel1sEntityInformationFields ... 1333
199.1.985 OrganizationalLevel1sEntityInformationUserDefinedFields ... 1333
199.1.986 OrganizationalLevel2sEntityInformation ... 1334
199.1.987 OrganizationalLevel2sEntityInformation_FieldsPicklistValuesFields ... 1335
199.1.988 OrganizationalLevel2sEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1335
199.1.989 OrganizationalLevel2sEntityInformationFields ... 1336
199.1.990 OrganizationalLevel2sEntityInformationUserDefinedFields ... 1337
199.1.991 OrganizationalLevelAssociationsByParentIdResourcesEntityInformation ... 1338
199.1.992 OrganizationalLevelAssociationsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields ... 1339
199.1.993 OrganizationalLevelAssociationsByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.994 OrganizationalLevelAssociationsByParentIdResourcesEntityInformationFields ... 1340
199.1.995 OrganizationalLevelAssociationsByParentIdResourcesEntityInformationUserDefinedFields ... 1341
199.1.996 OrganizationalLevelAssociationsEntityInformation ... 1342
199.1.997 OrganizationalLevelAssociationsEntityInformation_FieldsPicklistValuesFields ... 1343
199.1.998 OrganizationalLevelAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1343
199.1.999 OrganizationalLevelAssociationsEntityInformationFields ... 1344
199.1.1000 OrganizationalLevelAssociationsEntityInformationUserDefinedFields ... 1345
199.1.1001 OrganizationalResourcesEntityInformation ... 1346
199.1.1002 OrganizationalResourcesEntityInformation_FieldsPicklistValuesFields ... 1346
199.1.1003 OrganizationalResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1347
199.1.1004 OrganizationalResourcesEntityInformationFields ... 1348
199.1.1005 OrganizationalResourcesEntityInformationUserDefinedFields ... 1348
199.1.1006 PaymentTermsEntityInformation ... 1349
199.1.1007 PaymentTermsEntityInformation_FieldsPicklistValuesFields ... 1350
199.1.1008 PaymentTermsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1350
199.1.1009 PaymentTermsEntityInformationFields ... 1351
199.1.1010 PaymentTermsEntityInformationUserDefinedFields ... 1352
199.1.1011 PhasesEntityInformation ... 1353
199.1.1012 PhasesEntityInformation_FieldsPicklistValuesFields ... 1353
199.1.1013 PhasesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1354
199.1.1014 PhasesEntityInformationFields ... 1355
199.1.1015 PhasesEntityInformationUserDefinedFields ... 1355
199.1.1016 PriceListMaterialCodesEntityInformation ... 1356
199.1.1017 PriceListMaterialCodesEntityInformation_FieldsPicklistValuesFields ... 1357
199.1.1018 PriceListMaterialCodesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1357
199.1.1019 PriceListMaterialCodesEntityInformationFields ... 1358
199.1.1020 PriceListMaterialCodesEntityInformationUserDefinedFields ... 1359
199.1.1021 PriceListProductsEntityInformation ... 1360
199.1.1022 PriceListProductsEntityInformation_FieldsPicklistValuesFields ... 1360
199.1.1023 PriceListProductsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1361
199.1.1024 PriceListProductsEntityInformationFields ... 1362
199.1.1025 PriceListProductsEntityInformationUserDefinedFields ... 1362
199.1.1026 PriceListProductTiersEntityInformation ... 1363

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1027 PriceListProductTiersEntityInformation_FieldsPicklistValuesFields 1364
199.1.1028 PriceListProductTiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1364
199.1.1029 PriceListProductTiersEntityInformationFields 1365
199.1.1030 PriceListProductTiersEntityInformationUserDefinedFields 1366
199.1.1031 PriceListRolesEntityInformation 1367
199.1.1032 PriceListRolesEntityInformation_FieldsPicklistValuesFields 1367
199.1.1033 PriceListRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1368
199.1.1034 PriceListRolesEntityInformationFields 1369
199.1.1035 PriceListRolesEntityInformationUserDefinedFields 1369
199.1.1036 PriceListServiceBundlesEntityInformation 1370
199.1.1037 PriceListServiceBundlesEntityInformation_FieldsPicklistValuesFields 1371
199.1.1038 PriceListServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields 1371
199.1.1039 PriceListServiceBundlesEntityInformationFields 1372
199.1.1040 PriceListServiceBundlesEntityInformationUserDefinedFields 1373
199.1.1041 PriceListServicesEntityInformation 1374
199.1.1042 PriceListServicesEntityInformation_FieldsPicklistValuesFields 1374
199.1.1043 PriceListServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1375
199.1.1044 PriceListServicesEntityInformationFields 1376
199.1.1045 PriceListServicesEntityInformationUserDefinedFields 1376
199.1.1046 PriceListWorkTypeModifiersEntityInformation 1377
199.1.1047 PriceListWorkTypeModifiersEntityInformation_FieldsPicklistValuesFields 1378
199.1.1048 PriceListWorkTypeModifiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1378
199.1.1049 PriceListWorkTypeModifiersEntityInformationFields 1379
199.1.1050 PriceListWorkTypeModifiersEntityInformationUserDefinedFields 1380
199.1.1051 ProductNotesEntityInformation 1381
199.1.1052 ProductNotesEntityInformation_FieldsPicklistValuesFields 1381
199.1.1053 ProductNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1382
199.1.1054 ProductNotesEntityInformationFields 1383
199.1.1055 ProductNotesEntityInformationUserDefinedFields 1383
199.1.1056 ProductsByParentIdNotesEntityInformation 1384
199.1.1057 ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1385
199.1.1058 ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1386
199.1.1059 ProductsByParentIdNotesEntityInformationFields 1388
199.1.1060 ProductsByParentIdNotesEntityInformationUserDefinedFields 1389
199.1.1061 ProductsByParentIdTiersEntityInformation 1390
199.1.1062 ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesFields 1391
199.1.1063 ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1392
199.1.1064 ProductsByParentIdTiersEntityInformationFields 1393
199.1.1065 ProductsByParentIdTiersEntityInformationUserDefinedFields 1394
199.1.1066 ProductsByParentIdVendorsEntityInformation 1395
199.1.1067 ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesFields 1396
199.1.1068 ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields 1398
199.1.1069 ProductsByParentIdVendorsEntityInformationFields 1399
199.1.1070 ProductsByParentIdVendorsEntityInformationUserDefinedFields 1400
199.1.1071 ProductsEntityInformation 1401
199.1.1072 ProductsEntityInformation_FieldsPicklistValuesFields 1402
199.1.1073 ProductsEntityInformation_FieldsPicklistValuesUserDefinedFields 1402
199.1.1074 ProductsEntityInformationFields 1403
199.1.1075 ProductsEntityInformationUserDefinedFields 1404
199.1.1076 ProductTiersEntityInformation 1404
199.1.1077 ProductTiersEntityInformation_FieldsPicklistValuesFields 1405
199.1.1078 ProductTiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1406
199.1.1079 ProductTiersEntityInformationFields 1407
199.1.1080 ProductTiersEntityInformationUserDefinedFields 1407
199.1.1081 ProductVendorsEntityInformation 1408
199.1.1082 ProductVendorsEntityInformation_FieldsPicklistValuesFields 1409
199.1.1083 ProductVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields 1409
199.1.1084 ProductVendorsEntityInformationFields 1410
199.1.1085 ProductVendorsEntityInformationUserDefinedFields 1411

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1086 ProjectAttachmentsEntityInformation 1411
199.1.1087 ProjectAttachmentsEntityInformation_FieldsPicklistValuesFields 1412
199.1.1088 ProjectAttachmentsEntityInformationFields 1413
199.1.1089 ProjectChargesEntityInformation 1413
199.1.1090 ProjectChargesEntityInformation_FieldsPicklistValuesFields 1414
199.1.1091 ProjectChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 1415
199.1.1092 ProjectChargesEntityInformationFields 1416
199.1.1093 ProjectChargesEntityInformationUserDefinedFields 1416
199.1.1094 ProjectNoteAttachmentsEntityInformation 1417
199.1.1095 ProjectNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 1417
199.1.1096 ProjectNoteAttachmentsEntityInformationFields 1418
199.1.1097 ProjectNotesEntityInformation 1419
199.1.1098 ProjectNotesEntityInformation_FieldsPicklistValuesFields 1419
199.1.1099 ProjectNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1420
199.1.1100 ProjectNotesEntityInformationFields 1421
199.1.1101 ProjectNotesEntityInformationUserDefinedFields 1422
199.1.1102 ProjectsByParentIdChargesEntityInformation 1422
199.1.1103 ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesFields 1423
199.1.1104 ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 1425
199.1.1105 ProjectsByParentIdChargesEntityInformationFields 1426
199.1.1106 ProjectsByParentIdChargesEntityInformationUserDefinedFields 1427
199.1.1107 ProjectsByParentIdNotesEntityInformation 1428
199.1.1108 ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1429
199.1.1109 ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1430
199.1.1110 ProjectsByParentIdNotesEntityInformationFields 1431
199.1.1111 ProjectsByParentIdNotesEntityInformationUserDefinedFields 1432
199.1.1112 ProjectsByParentIdPhasesEntityInformation 1434
199.1.1113 ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesFields 1435
199.1.1114 ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesUserDefinedFields 1436
199.1.1115 ProjectsByParentIdPhasesEntityInformationFields 1437
199.1.1116 ProjectsByParentIdPhasesEntityInformationUserDefinedFields 1438
199.1.1117 ProjectsByParentIdTasksEntityInformation 1439
199.1.1118 ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesFields 1440
199.1.1119 ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields 1441
199.1.1120 ProjectsByParentIdTasksEntityInformationFields 1443
199.1.1121 ProjectsByParentIdTasksEntityInformationUserDefinedFields 1444
199.1.1122 ProjectsEntityInformation 1445
199.1.1123 ProjectsEntityInformation_FieldsPicklistValuesFields 1445
199.1.1124 ProjectsEntityInformation_FieldsPicklistValuesUserDefinedFields 1446
199.1.1125 ProjectsEntityInformationFields 1447
199.1.1126 ProjectsEntityInformationUserDefinedFields 1448
199.1.1127 PurchaseApprovalsEntityInformation 1448
199.1.1128 PurchaseApprovalsEntityInformation_FieldsPicklistValuesFields 1449
199.1.1129 PurchaseApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields 1450
199.1.1130 PurchaseApprovalsEntityInformationFields 1451
199.1.1131 PurchaseApprovalsEntityInformationUserDefinedFields 1451
199.1.1132 PurchaseOrderItemReceivingEntityInformation 1452
199.1.1133 PurchaseOrderItemReceivingEntityInformation_FieldsPicklistValuesFields 1452
199.1.1134 PurchaseOrderItemReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields 1453
199.1.1135 PurchaseOrderItemReceivingEntityInformationFields 1454
199.1.1136 PurchaseOrderItemReceivingEntityInformationUserDefinedFields 1455
199.1.1137 PurchaseOrderItemsByParentIdReceivingEntityInformation 1455
199.1.1138 PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesFields 1456
199.1.1139 PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields 1458
199.1.1140 PurchaseOrderItemsByParentIdReceivingEntityInformationFields 1459
199.1.1141 PurchaseOrderItemsByParentIdReceivingEntityInformationUserDefinedFields 1460
199.1.1142 PurchaseOrderItemsEntityInformation 1461
199.1.1143 PurchaseOrderItemsEntityInformation_FieldsPicklistValuesFields 1462
199.1.1144 PurchaseOrderItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1463

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1145 PurchaseOrderItemsEntityInformationFields ... 1463
199.1.1146 PurchaseOrderItemsEntityInformationUserDefinedFields ... 1464
199.1.1147 PurchaseOrdersByParentIdItemsEntityInformation ... 1465
199.1.1148 PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesFields ... 1466
199.1.1149 PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1467
199.1.1150 PurchaseOrdersByParentIdItemsEntityInformationFields ... 1468
199.1.1151 PurchaseOrdersByParentIdItemsEntityInformationUserDefinedFields ... 1469
199.1.1152 PurchaseOrdersEntityInformation ... 1470
199.1.1153 PurchaseOrdersEntityInformation_FieldsPicklistValuesFields ... 1471
199.1.1154 PurchaseOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1472
199.1.1155 PurchaseOrdersEntityInformationFields ... 1473
199.1.1156 PurchaseOrdersEntityInformationUserDefinedFields ... 1473
199.1.1157 QuoteItemsEntityInformation ... 1474
199.1.1158 QuoteItemsEntityInformation_FieldsPicklistValuesFields ... 1474
199.1.1159 QuoteItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1475
199.1.1160 QuoteItemsEntityInformationFields ... 1476
199.1.1161 QuoteItemsEntityInformationUserDefinedFields ... 1477
199.1.1162 QuoteLocationsEntityInformation ... 1477
199.1.1163 QuoteLocationsEntityInformation_FieldsPicklistValuesFields ... 1478
199.1.1164 QuoteLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1479
199.1.1165 QuoteLocationsEntityInformationFields ... 1480
199.1.1166 QuoteLocationsEntityInformationUserDefinedFields ... 1480
199.1.1167 QuotesByParentIdItemsEntityInformation ... 1481
199.1.1168 QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesFields ... 1482
199.1.1169 QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1483
199.1.1170 QuotesByParentIdItemsEntityInformationFields ... 1484
199.1.1171 QuotesByParentIdItemsEntityInformationUserDefinedFields ... 1485
199.1.1172 QuotesEntityInformation ... 1486
199.1.1173 QuotesEntityInformation_FieldsPicklistValuesFields ... 1487
199.1.1174 QuotesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1488
199.1.1175 QuotesEntityInformationFields ... 1489
199.1.1176 QuotesEntityInformationUserDefinedFields ... 1489
199.1.1177 QuoteTemplatesEntityInformation ... 1490
199.1.1178 QuoteTemplatesEntityInformation_FieldsPicklistValuesFields ... 1491
199.1.1179 QuoteTemplatesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1491
199.1.1180 QuoteTemplatesEntityInformationFields ... 1492
199.1.1181 QuoteTemplatesEntityInformationUserDefinedFields ... 1493
199.1.1182 ResourceAttachmentsEntityInformation ... 1493
199.1.1183 ResourceAttachmentsEntityInformation_FieldsPicklistValuesFields ... 1494
199.1.1184 ResourceAttachmentsEntityInformationFields ... 1495
199.1.1185 ResourceRoleDepartmentsEntityInformation ... 1495
199.1.1186 ResourceRoleDepartmentsEntityInformation_FieldsPicklistValuesFields ... 1496
199.1.1187 ResourceRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1497
199.1.1188 ResourceRoleDepartmentsEntityInformationFields ... 1498
199.1.1189 ResourceRoleDepartmentsEntityInformationUserDefinedFields ... 1498
199.1.1190 ResourceRoleQueuesEntityInformation ... 1499
199.1.1191 ResourceRoleQueuesEntityInformation_FieldsPicklistValuesFields ... 1499
199.1.1192 ResourceRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1500
199.1.1193 ResourceRoleQueuesEntityInformationFields ... 1501
199.1.1194 ResourceRoleQueuesEntityInformationUserDefinedFields ... 1502
199.1.1195 ResourceRolesEntityInformation ... 1502
199.1.1196 ResourceRolesEntityInformation_FieldsPicklistValuesFields ... 1503
199.1.1197 ResourceRolesEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1504
199.1.1198 ResourceRolesEntityInformationFields ... 1505
199.1.1199 ResourceRolesEntityInformationUserDefinedFields ... 1505
199.1.1200 ResourcesByParentIdRoleDepartmentsEntityInformation ... 1506
199.1.1201 ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesFields ... 1507
199.1.1202 ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields ... 1508
199.1.1203 ResourcesByParentIdRoleDepartmentsEntityInformationFields ... 1509

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1204 ResourcesByParentIdRoleDepartmentsEntityInformationUserDefinedFields 1510
199.1.1205 ResourcesByParentIdRoleQueuesEntityInformation 1512
199.1.1206 ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesFields 1513
199.1.1207 ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields 1514
199.1.1208 ResourcesByParentIdRoleQueuesEntityInformationFields 1515
199.1.1209 ResourcesByParentIdRoleQueuesEntityInformationUserDefinedFields 1516
199.1.1210 ResourcesByParentIdRolesEntityInformation 1517
199.1.1211 ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesFields 1518
199.1.1212 ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1519
199.1.1213 ResourcesByParentIdRolesEntityInformationFields 1521
199.1.1214 ResourcesByParentIdRolesEntityInformationUserDefinedFields 1522
199.1.1215 ResourcesByParentIdServiceDeskRolesEntityInformation 1523
199.1.1216 ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesFields 1524
199.1.1217 ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1525
199.1.1218 ResourcesByParentIdServiceDeskRolesEntityInformationFields 1526
199.1.1219 ResourcesByParentIdServiceDeskRolesEntityInformationUserDefinedFields 1527
199.1.1220 ResourcesByParentIdSkillsEntityInformation 1529
199.1.1221 ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesFields 1530
199.1.1222 ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields 1531
199.1.1223 ResourcesByParentIdSkillsEntityInformationFields 1532
199.1.1224 ResourcesByParentIdSkillsEntityInformationUserDefinedFields 1533
199.1.1225 ResourcesByParentIdTimeOffRequestsEntityInformation 1534
199.1.1226 ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesFields 1535
199.1.1227 ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields 1536
199.1.1228 ResourcesByParentIdTimeOffRequestsEntityInformationFields 1538
199.1.1229 ResourcesByParentIdTimeOffRequestsEntityInformationUserDefinedFields 1539
199.1.1230 ResourcesEntityInformation 1540
199.1.1231 ResourcesEntityInformation_FieldsPicklistValuesFields 1540
199.1.1232 ResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1541
199.1.1233 ResourcesEntityInformationFields 1542
199.1.1234 ResourcesEntityInformationUserDefinedFields 1543
199.1.1235 ResourceServiceDeskRolesEntityInformation 1543
199.1.1236 ResourceServiceDeskRolesEntityInformation_FieldsPicklistValuesFields 1544
199.1.1237 ResourceServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1545
199.1.1238 ResourceServiceDeskRolesEntityInformationFields 1546
199.1.1239 ResourceServiceDeskRolesEntityInformationUserDefinedFields 1546
199.1.1240 ResourceSkillsEntityInformation 1547
199.1.1241 ResourceSkillsEntityInformation_FieldsPicklistValuesFields 1547
199.1.1242 ResourceSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields 1548
199.1.1243 ResourceSkillsEntityInformationFields 1549
199.1.1244 ResourceSkillsEntityInformationUserDefinedFields 1550
199.1.1245 RolesEntityInformation 1550
199.1.1246 RolesEntityInformation_FieldsPicklistValuesFields 1551
199.1.1247 RolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1552
199.1.1248 RolesEntityInformationFields 1553
199.1.1249 RolesEntityInformationUserDefinedFields 1553
199.1.1250 SalesOrderAttachmentsEntityInformation 1554
199.1.1251 SalesOrderAttachmentsEntityInformation_FieldsPicklistValuesFields 1554
199.1.1252 SalesOrderAttachmentsEntityInformationFields 1555
199.1.1253 SalesOrdersEntityInformation 1556
199.1.1254 SalesOrdersEntityInformation_FieldsPicklistValuesFields 1556
199.1.1255 SalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields 1557
199.1.1256 SalesOrdersEntityInformationFields 1558
199.1.1257 SalesOrdersEntityInformationUserDefinedFields 1559
199.1.1258 ServiceBundlesByParentIdServicesEntityInformation 1559
199.1.1259 ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesFields 1560
199.1.1260 ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1562
199.1.1261 ServiceBundlesByParentIdServicesEntityInformationFields 1563
199.1.1262 ServiceBundlesByParentIdServicesEntityInformationUserDefinedFields 1564

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1263 ServiceBundlesEntityInformation 1565
199.1.1264 ServiceBundlesEntityInformation_FieldsPicklistValuesFields 1566
199.1.1265 ServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields 1566
199.1.1266 ServiceBundlesEntityInformationFields 1567
199.1.1267 ServiceBundlesEntityInformationUserDefinedFields 1568
199.1.1268 ServiceBundleServicesEntityInformation 1569
199.1.1269 ServiceBundleServicesEntityInformation_FieldsPicklistValuesFields 1569
199.1.1270 ServiceBundleServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1570
199.1.1271 ServiceBundleServicesEntityInformationFields 1571
199.1.1272 ServiceBundleServicesEntityInformationUserDefinedFields 1571
199.1.1273 ServiceCallsByParentIdTasksEntityInformation 1572
199.1.1274 ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesFields 1573
199.1.1275 ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields 1574
199.1.1276 ServiceCallsByParentIdTasksEntityInformationFields 1576
199.1.1277 ServiceCallsByParentIdTasksEntityInformationUserDefinedFields 1577
199.1.1278 ServiceCallsByParentIdTicketsEntityInformation 1578
199.1.1279 ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesFields 1579
199.1.1280 ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields 1580
199.1.1281 ServiceCallsByParentIdTicketsEntityInformationFields 1581
199.1.1282 ServiceCallsByParentIdTicketsEntityInformationUserDefinedFields 1582
199.1.1283 ServiceCallsEntityInformation 1583
199.1.1284 ServiceCallsEntityInformation_FieldsPicklistValuesFields 1584
199.1.1285 ServiceCallsEntityInformation_FieldsPicklistValuesUserDefinedFields 1585
199.1.1286 ServiceCallsEntityInformationFields 1586
199.1.1287 ServiceCallsEntityInformationUserDefinedFields 1586
199.1.1288 ServiceCallTaskResourcesEntityInformation 1587
199.1.1289 ServiceCallTaskResourcesEntityInformation_FieldsPicklistValuesFields 1587
199.1.1290 ServiceCallTaskResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1588
199.1.1291 ServiceCallTaskResourcesEntityInformationFields 1589
199.1.1292 ServiceCallTaskResourcesEntityInformationUserDefinedFields 1590
199.1.1293 ServiceCallTasksByParentIdResourcesEntityInformation 1590
199.1.1294 ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesFields 1591
199.1.1295 ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1593
199.1.1296 ServiceCallTasksByParentIdResourcesEntityInformationFields 1594
199.1.1297 ServiceCallTasksByParentIdResourcesEntityInformationUserDefinedFields 1595
199.1.1298 ServiceCallTasksEntityInformation 1596
199.1.1299 ServiceCallTasksEntityInformation_FieldsPicklistValuesFields 1597
199.1.1300 ServiceCallTasksEntityInformation_FieldsPicklistValuesUserDefinedFields 1598
199.1.1301 ServiceCallTasksEntityInformationFields 1598
199.1.1302 ServiceCallTasksEntityInformationUserDefinedFields 1599
199.1.1303 ServiceCallTicketResourcesEntityInformation 1600
199.1.1304 ServiceCallTicketResourcesEntityInformation_FieldsPicklistValuesFields 1600
199.1.1305 ServiceCallTicketResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1601
199.1.1306 ServiceCallTicketResourcesEntityInformationFields 1602
199.1.1307 ServiceCallTicketResourcesEntityInformationUserDefinedFields 1603
199.1.1308 ServiceCallTicketsByParentIdResourcesEntityInformation 1603
199.1.1309 ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields 1604
199.1.1310 ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1605
199.1.1311 ServiceCallTicketsByParentIdResourcesEntityInformationFields 1607
199.1.1312 ServiceCallTicketsByParentIdResourcesEntityInformationUserDefinedFields 1608
199.1.1313 ServiceCallTicketsEntityInformation 1609
199.1.1314 ServiceCallTicketsEntityInformation_FieldsPicklistValuesFields 1610
199.1.1315 ServiceCallTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields 1610
199.1.1316 ServiceCallTicketsEntityInformationFields 1611
199.1.1317 ServiceCallTicketsEntityInformationUserDefinedFields 1612
199.1.1318 ServiceLevelAgreementResultsEntityInformation 1612
199.1.1319 ServiceLevelAgreementResultsEntityInformation_FieldsPicklistValuesFields 1613
199.1.1320 ServiceLevelAgreementResultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1614
199.1.1321 ServiceLevelAgreementResultsEntityInformationFields 1615

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1322 ServiceLevelAgreementResultsEntityInformationUserDefinedFields 1615
199.1.1323 ServiceLevelAgreementsByParentIdResultsEntityInformation 1616
199.1.1324 ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesFields 1617
199.1.1325 ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1618
199.1.1326 ServiceLevelAgreementsByParentIdResultsEntityInformationFields 1620
199.1.1327 ServiceLevelAgreementsByParentIdResultsEntityInformationUserDefinedFields 1621
199.1.1328 ServicesEntityInformation 1622
199.1.1329 ServicesEntityInformation_FieldsPicklistValuesFields 1622
199.1.1330 ServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1623
199.1.1331 ServicesEntityInformationFields 1624
199.1.1332 ServicesEntityInformationUserDefinedFields 1624
199.1.1333 ShippingTypesEntityInformation 1625
199.1.1334 ShippingTypesEntityInformation_FieldsPicklistValuesFields 1626
199.1.1335 ShippingTypesEntityInformation_FieldsPicklistValuesUserDefinedFields 1627
199.1.1336 ShippingTypesEntityInformationFields 1627
199.1.1337 ShippingTypesEntityInformationUserDefinedFields 1628
199.1.1338 SkillsEntityInformation 1629
199.1.1339 SkillsEntityInformation_FieldsPicklistValuesFields 1629
199.1.1340 SkillsEntityInformation_FieldsPicklistValuesUserDefinedFields 1630
199.1.1341 SkillsEntityInformationFields 1631
199.1.1342 SkillsEntityInformationUserDefinedFields 1631
199.1.1343 SubscriptionPeriodsEntityInformation 1632
199.1.1344 SubscriptionPeriodsEntityInformation_FieldsPicklistValuesFields 1633
199.1.1345 SubscriptionPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields 1634
199.1.1346 SubscriptionPeriodsEntityInformationFields 1634
199.1.1347 SubscriptionPeriodsEntityInformationUserDefinedFields 1635
199.1.1348 SubscriptionsByParentIdPeriodsEntityInformation 1636
199.1.1349 SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesFields 1637
199.1.1350 SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields 1638
199.1.1351 SubscriptionsByParentIdPeriodsEntityInformationFields 1639
199.1.1352 SubscriptionsByParentIdPeriodsEntityInformationUserDefinedFields 1640
199.1.1353 SubscriptionsEntityInformation 1641
199.1.1354 SubscriptionsEntityInformation_FieldsPicklistValuesFields 1642
199.1.1355 SubscriptionsEntityInformation_FieldsPicklistValuesUserDefinedFields 1643
199.1.1356 SubscriptionsEntityInformationFields 1644
199.1.1357 SubscriptionsEntityInformationUserDefinedFields 1644
199.1.1358 SurveyResultsEntityInformation 1645
199.1.1359 SurveyResultsEntityInformation_FieldsPicklistValuesFields 1645
199.1.1360 SurveyResultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1646
199.1.1361 SurveyResultsEntityInformationFields 1647
199.1.1362 SurveyResultsEntityInformationUserDefinedFields 1648
199.1.1363 SurveysEntityInformation 1648
199.1.1364 SurveysEntityInformation_FieldsPicklistValuesFields 1649
199.1.1365 SurveysEntityInformation_FieldsPicklistValuesUserDefinedFields 1650
199.1.1366 SurveysEntityInformationFields 1651
199.1.1367 SurveysEntityInformationUserDefinedFields 1651
199.1.1368 TagAliasesEntityInformation 1652
199.1.1369 TagAliasesEntityInformation_FieldsPicklistValuesFields 1652
199.1.1370 TagAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields 1653
199.1.1371 TagAliasesEntityInformationFields 1654
199.1.1372 TagAliasesEntityInformationUserDefinedFields 1655
199.1.1373 TagGroupsEntityInformation 1655
199.1.1374 TagGroupsEntityInformation_FieldsPicklistValuesFields 1656
199.1.1375 TagGroupsEntityInformation_FieldsPicklistValuesUserDefinedFields 1657
199.1.1376 TagGroupsEntityInformationFields 1658
199.1.1377 TagGroupsEntityInformationUserDefinedFields 1658
199.1.1378 TagsByParentIdAliasesEntityInformation 1659
199.1.1379 TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesFields 1660
199.1.1380 TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields 1661

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1381 TagsByParentIdAliasesEntityInformationFields 1662
199.1.1382 TagsByParentIdAliasesEntityInformationUserDefinedFields 1663
199.1.1383 TagsEntityInformation 1664
199.1.1384 TagsEntityInformation_FieldsPicklistValuesFields 1665
199.1.1385 TagsEntityInformation_FieldsPicklistValuesUserDefinedFields 1666
199.1.1386 TagsEntityInformationFields 1667
199.1.1387 TagsEntityInformationUserDefinedFields 1667
199.1.1388 TaskAttachmentsEntityInformation 1668
199.1.1389 TaskAttachmentsEntityInformation_FieldsPicklistValuesFields 1669
199.1.1390 TaskAttachmentsEntityInformationFields 1669
199.1.1391 TaskNoteAttachmentsEntityInformation 1670
199.1.1392 TaskNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 1671
199.1.1393 TaskNoteAttachmentsEntityInformationFields 1671
199.1.1394 TaskNotesEntityInformation 1672
199.1.1395 TaskNotesEntityInformation_FieldsPicklistValuesFields 1673
199.1.1396 TaskNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1673
199.1.1397 TaskNotesEntityInformationFields 1674
199.1.1398 TaskNotesEntityInformationUserDefinedFields 1675
199.1.1399 TaskPredecessorsEntityInformation 1675
199.1.1400 TaskPredecessorsEntityInformation_FieldsPicklistValuesFields 1676
199.1.1401 TaskPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields 1677
199.1.1402 TaskPredecessorsEntityInformationFields 1678
199.1.1403 TaskPredecessorsEntityInformationUserDefinedFields 1678
199.1.1404 TasksByParentIdNotesEntityInformation 1679
199.1.1405 TasksByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1680
199.1.1406 TasksByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1681
199.1.1407 TasksByParentIdNotesEntityInformationFields 1682
199.1.1408 TasksByParentIdNotesEntityInformationUserDefinedFields 1683
199.1.1409 TasksByParentIdPredecessorsEntityInformation 1684
199.1.1410 TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesFields 1685
199.1.1411 TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields 1687
199.1.1412 TasksByParentIdPredecessorsEntityInformationFields 1688
199.1.1413 TasksByParentIdPredecessorsEntityInformationUserDefinedFields 1689
199.1.1414 TasksByParentIdSecondaryResourcesEntityInformation 1690
199.1.1415 TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields 1691
199.1.1416 TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1692
199.1.1417 TasksByParentIdSecondaryResourcesEntityInformationFields 1694
199.1.1418 TasksByParentIdSecondaryResourcesEntityInformationUserDefinedFields 1695
199.1.1419 TaskSecondaryResourcesEntityInformation 1696
199.1.1420 TaskSecondaryResourcesEntityInformation_FieldsPicklistValuesFields 1696
199.1.1421 TaskSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1697
199.1.1422 TaskSecondaryResourcesEntityInformationFields 1698
199.1.1423 TaskSecondaryResourcesEntityInformationUserDefinedFields 1699
199.1.1424 TasksEntityInformation 1699
199.1.1425 TasksEntityInformation_FieldsPicklistValuesFields 1700
199.1.1426 TasksEntityInformation_FieldsPicklistValuesUserDefinedFields 1701
199.1.1427 TasksEntityInformationFields 1702
199.1.1428 TasksEntityInformationUserDefinedFields 1702
199.1.1429 TaxCategoriesEntityInformation 1703
199.1.1430 TaxCategoriesEntityInformation_FieldsPicklistValuesFields 1703
199.1.1431 TaxCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1704
199.1.1432 TaxCategoriesEntityInformationFields 1705
199.1.1433 TaxCategoriesEntityInformationUserDefinedFields 1706
199.1.1434 TaxesEntityInformation 1706
199.1.1435 TaxesEntityInformation_FieldsPicklistValuesFields 1707
199.1.1436 TaxesEntityInformation_FieldsPicklistValuesUserDefinedFields 1708
199.1.1437 TaxesEntityInformationFields 1709
199.1.1438 TaxesEntityInformationUserDefinedFields 1709
199.1.1439 TaxRegionsEntityInformation 1710

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1440 TaxRegionsEntityInformation_FieldsPicklistValuesFields 1710
199.1.1441 TaxRegionsEntityInformation_FieldsPicklistValuesUserDefinedFields 1711
199.1.1442 TaxRegionsEntityInformationFields 1712
199.1.1443 TaxRegionsEntityInformationUserDefinedFields 1713
199.1.1444 TicketAdditionalConfigurationItemsEntityInformation 1713
199.1.1445 TicketAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields 1714
199.1.1446 TicketAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1715
199.1.1447 TicketAdditionalConfigurationItemsEntityInformationFields 1716
199.1.1448 TicketAdditionalConfigurationItemsEntityInformationUserDefinedFields 1716
199.1.1449 TicketAdditionalContactsEntityInformation 1717
199.1.1450 TicketAdditionalContactsEntityInformation_FieldsPicklistValuesFields 1718
199.1.1451 TicketAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields 1718
199.1.1452 TicketAdditionalContactsEntityInformationFields 1719
199.1.1453 TicketAdditionalContactsEntityInformationUserDefinedFields 1720
199.1.1454 TicketAttachmentsEntityInformation 1720
199.1.1455 TicketAttachmentsEntityInformation_FieldsPicklistValuesFields 1721
199.1.1456 TicketAttachmentsEntityInformationFields 1722
199.1.1457 TicketCategoriesByParentIdFieldDefaultsEntityInformation 1722
199.1.1458 TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesFields 1724
199.1.1459 TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1725
199.1.1460 TicketCategoriesByParentIdFieldDefaultsEntityInformationFields 1726
199.1.1461 TicketCategoriesByParentIdFieldDefaultsEntityInformationUserDefinedFields 1727
199.1.1462 TicketCategoriesEntityInformation 1728
199.1.1463 TicketCategoriesEntityInformation_FieldsPicklistValuesFields 1729
199.1.1464 TicketCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1730
199.1.1465 TicketCategoriesEntityInformationFields 1731
199.1.1466 TicketCategoriesEntityInformationUserDefinedFields 1731
199.1.1467 TicketCategoryFieldDefaultsEntityInformation 1732
199.1.1468 TicketCategoryFieldDefaultsEntityInformation_FieldsPicklistValuesFields 1732
199.1.1469 TicketCategoryFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1733
199.1.1470 TicketCategoryFieldDefaultsEntityInformationFields 1734
199.1.1471 TicketCategoryFieldDefaultsEntityInformationUserDefinedFields 1735
199.1.1472 TicketChangeRequestApprovalsEntityInformation 1735
199.1.1473 TicketChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields 1736
199.1.1474 TicketChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields 1737
199.1.1475 TicketChangeRequestApprovalsEntityInformationFields 1738
199.1.1476 TicketChangeRequestApprovalsEntityInformationUserDefinedFields 1738
199.1.1477 TicketChargesEntityInformation 1739
199.1.1478 TicketChargesEntityInformation_FieldsPicklistValuesFields 1740
199.1.1479 TicketChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 1740
199.1.1480 TicketChargesEntityInformationFields 1741
199.1.1481 TicketChargesEntityInformationUserDefinedFields 1742
199.1.1482 TicketChecklistItemsEntityInformation 1742
199.1.1483 TicketChecklistItemsEntityInformation_FieldsPicklistValuesFields 1743
199.1.1484 TicketChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1744
199.1.1485 TicketChecklistItemsEntityInformationFields 1745
199.1.1486 TicketChecklistItemsEntityInformationUserDefinedFields 1745
199.1.1487 TicketChecklistLibrariesEntityInformation 1746
199.1.1488 TicketChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 1747
199.1.1489 TicketChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 1747
199.1.1490 TicketChecklistLibrariesEntityInformationFields 1748
199.1.1491 TicketChecklistLibrariesEntityInformationUserDefinedFields 1749
199.1.1492 TicketHistoryEntityInformation 1749
199.1.1493 TicketHistoryEntityInformation_FieldsPicklistValuesFields 1750
199.1.1494 TicketHistoryEntityInformation_FieldsPicklistValuesUserDefinedFields 1751
199.1.1495 TicketHistoryEntityInformationFields 1752
199.1.1496 TicketHistoryEntityInformationUserDefinedFields 1752
199.1.1497 TicketNoteAttachmentsEntityInformation 1753
199.1.1498 TicketNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 1754

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1499 TicketNoteAttachmentsEntityInformationFields 1754
199.1.1500 TicketNotesEntityInformation 1755
199.1.1501 TicketNotesEntityInformation_FieldsPicklistValuesFields 1756
199.1.1502 TicketNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1756
199.1.1503 TicketNotesEntityInformationFields 1757
199.1.1504 TicketNotesEntityInformationUserDefinedFields 1758
199.1.1505 TicketNoteWebhookExcludedResourcesEntityInformation 1758
199.1.1506 TicketNoteWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields 1759
199.1.1507 TicketNoteWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1760
199.1.1508 TicketNoteWebhookExcludedResourcesEntityInformationFields 1761
199.1.1509 TicketNoteWebhookExcludedResourcesEntityInformationUserDefinedFields 1761
199.1.1510 TicketNoteWebhookFieldsEntityInformation 1762
199.1.1511 TicketNoteWebhookFieldsEntityInformation_FieldsPicklistValuesFields 1763
199.1.1512 TicketNoteWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1763
199.1.1513 TicketNoteWebhookFieldsEntityInformationFields 1764
199.1.1514 TicketNoteWebhookFieldsEntityInformationUserDefinedFields 1765
199.1.1515 TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation 1765
199.1.1516 TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 1767
199.1.1517 TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields
199.1.1518 TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationFields 1769
199.1.1519 TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 1770
199.1.1520 TicketNoteWebhooksByParentIdFieldsEntityInformation 1771
199.1.1521 TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 1772
199.1.1522 TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1774
199.1.1523 TicketNoteWebhooksByParentIdFieldsEntityInformationFields 1775
199.1.1524 TicketNoteWebhooksByParentIdFieldsEntityInformationUserDefinedFields 1776
199.1.1525 TicketNoteWebhooksEntityInformation 1777
199.1.1526 TicketNoteWebhooksEntityInformation_FieldsPicklistValuesFields 1778
199.1.1527 TicketNoteWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 1778
199.1.1528 TicketNoteWebhooksEntityInformationFields 1779
199.1.1529 TicketNoteWebhooksEntityInformationUserDefinedFields 1780
199.1.1530 TicketRmaCreditsEntityInformation 1781
199.1.1531 TicketRmaCreditsEntityInformation_FieldsPicklistValuesFields 1781
199.1.1532 TicketRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields 1782
199.1.1533 TicketRmaCreditsEntityInformationFields 1783
199.1.1534 TicketRmaCreditsEntityInformationUserDefinedFields 1783
199.1.1535 TicketsByParentIdAdditionalConfigurationItemsEntityInformation 1784
199.1.1536 TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields 1785
199.1.1537 TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 786
199.1.1538 TicketsByParentIdAdditionalConfigurationItemsEntityInformationFields 1788
199.1.1539 TicketsByParentIdAdditionalConfigurationItemsEntityInformationUserDefinedFields 1789
199.1.1540 TicketsByParentIdAdditionalContactsEntityInformation 1790
199.1.1541 TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesFields 1791
199.1.1542 TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields 1792
199.1.1543 TicketsByParentIdAdditionalContactsEntityInformationFields 1793
199.1.1544 TicketsByParentIdAdditionalContactsEntityInformationUserDefinedFields 1794
199.1.1545 TicketsByParentIdChangeRequestApprovalsEntityInformation 1796
199.1.1546 TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields 1797
199.1.1547 TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields 1798
199.1.1548 TicketsByParentIdChangeRequestApprovalsEntityInformationFields 1799
199.1.1549 TicketsByParentIdChangeRequestApprovalsEntityInformationUserDefinedFields 1800
199.1.1550 TicketsByParentIdChargesEntityInformation 1801
199.1.1551 TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesFields 1802
199.1.1552 TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 1804
199.1.1553 TicketsByParentIdChargesEntityInformationFields 1805
199.1.1554 TicketsByParentIdChargesEntityInformationUserDefinedFields 1806
199.1.1555 TicketsByParentIdChecklistItemsEntityInformation 1807
199.1.1556 TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields 1808
199.1.1557 TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1809

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1558 TicketsByParentIdChecklistItemsEntityInformationFields 1810
199.1.1559 TicketsByParentIdChecklistItemsEntityInformationUserDefinedFields 1811
199.1.1560 TicketsByParentIdChecklistLibrariesEntityInformation 1813
199.1.1561 TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 1814
199.1.1562 TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 1815
199.1.1563 TicketsByParentIdChecklistLibrariesEntityInformationFields 1816
199.1.1564 TicketsByParentIdChecklistLibrariesEntityInformationUserDefinedFields 1817
199.1.1565 TicketsByParentIdNotesEntityInformation 1818
199.1.1566 TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1819
199.1.1567 TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1820
199.1.1568 TicketsByParentIdNotesEntityInformationFields 1822
199.1.1569 TicketsByParentIdNotesEntityInformationUserDefinedFields 1823
199.1.1570 TicketsByParentIdRmaCreditsEntityInformation 1824
199.1.1571 TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesFields 1825
199.1.1572 TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields 1826
199.1.1573 TicketsByParentIdRmaCreditsEntityInformationFields 1827
199.1.1574 TicketsByParentIdRmaCreditsEntityInformationUserDefinedFields 1828
199.1.1575 TicketsByParentIdSecondaryResourcesEntityInformation 1829
199.1.1576 TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields 1831
199.1.1577 TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1832
199.1.1578 TicketsByParentIdSecondaryResourcesEntityInformationFields 1833
199.1.1579 TicketsByParentIdSecondaryResourcesEntityInformationUserDefinedFields 1834
199.1.1580 TicketsByParentIdTagAssociationsEntityInformation 1835
199.1.1581 TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields 1836
199.1.1582 TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1838
199.1.1583 TicketsByParentIdTagAssociationsEntityInformationFields 1839
199.1.1584 TicketsByParentIdTagAssociationsEntityInformationUserDefinedFields 1840
199.1.1585 TicketSecondaryResourcesEntityInformation 1841
199.1.1586 TicketSecondaryResourcesEntityInformation_FieldsPicklistValuesFields 1842
199.1.1587 TicketSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1842
199.1.1588 TicketSecondaryResourcesEntityInformationFields 1843
199.1.1589 TicketSecondaryResourcesEntityInformationUserDefinedFields 1844
199.1.1590 TicketsEntityInformation 1844
199.1.1591 TicketsEntityInformation_FieldsPicklistValuesFields 1845
199.1.1592 TicketsEntityInformation_FieldsPicklistValuesUserDefinedFields 1846
199.1.1593 TicketsEntityInformationFields 1847
199.1.1594 TicketsEntityInformationUserDefinedFields 1847
199.1.1595 TicketTagAssociationsEntityInformation 1848
199.1.1596 TicketTagAssociationsEntityInformation_FieldsPicklistValuesFields 1849
199.1.1597 TicketTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1849
199.1.1598 TicketTagAssociationsEntityInformationFields 1850
199.1.1599 TicketTagAssociationsEntityInformationUserDefinedFields 1851
199.1.1600 TicketWebhookExcludedResourcesEntityInformation 1851
199.1.1601 TicketWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields 1852
199.1.1602 TicketWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1853
199.1.1603 TicketWebhookExcludedResourcesEntityInformationFields 1854
199.1.1604 TicketWebhookExcludedResourcesEntityInformationUserDefinedFields 1854
199.1.1605 TicketWebhookFieldsEntityInformation 1855
199.1.1606 TicketWebhookFieldsEntityInformation_FieldsPicklistValuesFields 1856
199.1.1607 TicketWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1856
199.1.1608 TicketWebhookFieldsEntityInformationFields 1857
199.1.1609 TicketWebhookFieldsEntityInformationUserDefinedFields 1858
199.1.1610 TicketWebhooksByParentIdExcludedResourcesEntityInformation 1858
199.1.1611 TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 1859
199.1.1612 TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 61
199.1.1613 TicketWebhooksByParentIdExcludedResourcesEntityInformationFields 1862
199.1.1614 TicketWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 1863
199.1.1615 TicketWebhooksByParentIdFieldsEntityInformation 1864
199.1.1616 TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 1865

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1617 TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1866
199.1.1618 TicketWebhooksByParentIdFieldsEntityInformationFields 1868
199.1.1619 TicketWebhooksByParentIdFieldsEntityInformationUserDefinedFields 1869
199.1.1620 TicketWebhooksByParentIdUdfFieldsEntityInformation 1870
199.1.1621 TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields 1871
199.1.1622 TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1872
199.1.1623 TicketWebhooksByParentIdUdfFieldsEntityInformationFields 1873
199.1.1624 TicketWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields 1874
199.1.1625 TicketWebhooksEntityInformation 1876
199.1.1626 TicketWebhooksEntityInformation_FieldsPicklistValuesFields 1876
199.1.1627 TicketWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 1877
199.1.1628 TicketWebhooksEntityInformationFields 1878
199.1.1629 TicketWebhooksEntityInformationUserDefinedFields 1878
199.1.1630 TicketWebhookUdfFieldsEntityInformation 1879
199.1.1631 TicketWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields 1880
199.1.1632 TicketWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1880
199.1.1633 TicketWebhookUdfFieldsEntityInformationFields 1881
199.1.1634 TicketWebhookUdfFieldsEntityInformationUserDefinedFields 1882
199.1.1635 TimeEntriesEntityInformation 1883
199.1.1636 TimeEntriesEntityInformation_FieldsPicklistValuesFields 1883
199.1.1637 TimeEntriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1884
199.1.1638 TimeEntriesEntityInformationFields 1885
199.1.1639 TimeEntriesEntityInformationUserDefinedFields 1885
199.1.1640 TimeEntryAttachmentsEntityInformation 1886
199.1.1641 TimeEntryAttachmentsEntityInformation_FieldsPicklistValuesFields 1887
199.1.1642 TimeEntryAttachmentsEntityInformationFields 1887
199.1.1643 TimeOffRequestsEntityInformation 1888
199.1.1644 TimeOffRequestsEntityInformation_FieldsPicklistValuesFields 1889
199.1.1645 TimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields 1889
199.1.1646 TimeOffRequestsEntityInformationFields 1890
199.1.1647 TimeOffRequestsEntityInformationUserDefinedFields 1891
199.1.1648 UserDefinedFieldDefinitionsEntityInformation 1892
199.1.1649 UserDefinedFieldDefinitionsEntityInformation_FieldsPicklistValuesFields 1892
199.1.1650 UserDefinedFieldDefinitionsEntityInformation_FieldsPicklistValuesUserDefinedFields 1893
199.1.1651 UserDefinedFieldDefinitionsEntityInformationFields 1894
199.1.1652 UserDefinedFieldDefinitionsEntityInformationUserDefinedFields 1894
199.1.1653 UserDefinedFieldListItemsEntityInformation 1895
199.1.1654 UserDefinedFieldListItemsEntityInformation_FieldsPicklistValuesFields 1896
199.1.1655 UserDefinedFieldListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1896
199.1.1656 UserDefinedFieldListItemsEntityInformationFields 1897
199.1.1657 UserDefinedFieldListItemsEntityInformationUserDefinedFields 1898
199.1.1658 UserDefinedFieldsByParentIdListItemsEntityInformation 1899
199.1.1659 UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesFields 1900
199.1.1660 UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1901
199.1.1661 UserDefinedFieldsByParentIdListItemsEntityInformationFields 1902
199.1.1662 UserDefinedFieldsByParentIdListItemsEntityInformationUserDefinedFields 1903
199.1.1663 WebhookEventErrorLogsEntityInformation 1904
199.1.1664 WebhookEventErrorLogsEntityInformation_FieldsPicklistValuesFields 1905
199.1.1665 WebhookEventErrorLogsEntityInformation_FieldsPicklistValuesUserDefinedFields 1906
199.1.1666 WebhookEventErrorLogsEntityInformationFields 1907
199.1.1667 WebhookEventErrorLogsEntityInformationUserDefinedFields 1907
199.1.1668 WorkTypeModifiersEntityInformation 1908
199.1.1669 WorkTypeModifiersEntityInformation_FieldsPicklistValuesFields 1908
199.1.1670 WorkTypeModifiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1909
199.1.1671 WorkTypeModifiersEntityInformationFields 1910
199.1.1672 WorkTypeModifiersEntityInformationUserDefinedFields 1911

200 Schema: MetadataApiIntegration 1911

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

200.1 Tables ... 1911
200.1.1 EntityInformation ... 1911

201 Schema: ModuleAccessApiIntegration 1912

201.1 Tables ... 1912
201.1.1 Modules ... 1912

202 Schema: Native 1912

202.1 Tables ... 1912
202.1.1 NATIVEPLATFORMSCALARREQUESTS: Autotask Native Platform Scalar Requests ... 1912

203 Schema: NotificationHistory 1914

203.1 Tables ... 1914
203.1.1 NotificationHistory ... 1914
203.1.2 NotificationHistoryById ... 1915
203.1.3 NotificationHistoryCount ... 1916

204 Schema: Opportunities 1917

204.1 Tables ... 1917
204.1.1 Opportunities ... 1917
204.1.2 Opportunities_ItemsUserDefinedFields ... 1918
204.1.3 OpportunitiesById ... 1920
204.1.4 OpportunitiesCount ... 1923

205 Schema: OpportunityAttachments 1923

205.1 Tables ... 1923
205.1.1 OpportunityAttachments ... 1923
205.1.2 OpportunityAttachmentsById ... 1924
205.1.3 OpportunityAttachmentsCount ... 1926

206 Schema: OpportunityAttachmentsChild 1926

206.1 Tables ... 1926
206.1.1 OpportunitiesByParentIdAttachments ... 1926
206.1.2 OpportunitiesByParentIdAttachmentsId ... 1927

207 Schema: OrganizationalLevel1 1929

207.1 Tables ... 1929
207.1.1 OrganizationalLevel1s ... 1929
207.1.2 OrganizationalLevel1sById ... 1929
207.1.3 OrganizationalLevel1sCount ... 1930

208 Schema: OrganizationalLevel2 1930

208.1 Tables ... 1930
208.1.1 OrganizationalLevel2s ... 1930
208.1.2 OrganizationalLevel2sById ... 1931
208.1.3 OrganizationalLevel2sCount ... 1932

209 Schema: OrganizationalLevelAssociation 1932

209.1 Tables ... 1932
209.1.1 OrganizationalLevelAssociations ... 1932
209.1.2 OrganizationalLevelAssociationsById ... 1933
209.1.3 OrganizationalLevelAssociationsCount ... 1933

210 Schema: OrganizationalResources 1934

210.1 Tables ... 1934

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

210.1.1 OrganizationalResources ... 1934
210.1.2 OrganizationalResourcesById ... 1934
210.1.3 OrganizationalResourcesCount ... 1935

211 Schema: OrganizationalResourcesChild 1935

211.1 Tables ... 1935
211.1.1 OrganizationalLevelAssociationsByParentIdResources ... 1935
211.1.2 OrganizationalLevelAssociationsByParentIdResourcesId ... 1936

212 Schema: PaymentTerms 1937

212.1 Tables ... 1937
212.1.1 PaymentTerms ... 1937
212.1.2 PaymentTermsById ... 1938
212.1.3 PaymentTermsCount ... 1939

213 Schema: Phases 1939

213.1 Tables ... 1939
213.1.1 Phases ... 1939
213.1.2 PhasesById ... 1940
213.1.3 PhasesCount ... 1941

214 Schema: PhasesChild 1942

214.1 Tables ... 1942
214.1.1 ProjectsByParentIdPhases ... 1942
214.1.2 ProjectsByParentIdPhasesId ... 1943

215 Schema: PriceListMaterialCodes 1944

215.1 Tables ... 1944
215.1.1 PriceListMaterialCodes ... 1944
215.1.2 PriceListMaterialCodesById ... 1945
215.1.3 PriceListMaterialCodesCount ... 1946

216 Schema: PriceListProducts 1946

216.1 Tables ... 1946
216.1.1 PriceListProducts ... 1946
216.1.2 PriceListProductsById ... 1946
216.1.3 PriceListProductsCount ... 1947

217 Schema: PriceListProductTiers 1948

217.1 Tables ... 1948
217.1.1 PriceListProductTiers ... 1948
217.1.2 PriceListProductTiersById ... 1948
217.1.3 PriceListProductTiersCount ... 1949

218 Schema: PriceListRoles 1950

218.1 Tables ... 1950
218.1.1 PriceListRoles ... 1950
218.1.2 PriceListRolesById ... 1950
218.1.3 PriceListRolesCount ... 1951

219 Schema: PriceListServiceBundles 1952

219.1 Tables ... 1952
219.1.1 PriceListServiceBundles ... 1952
219.1.2 PriceListServiceBundlesById ... 1952
219.1.3 PriceListServiceBundlesCount ... 1953

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

220 Schema: PriceListServices 1953

220.1 Tables ... 1953
220.1.1 PriceListServices ... 1953
220.1.2 PriceListServicesById ... 1954
220.1.3 PriceListServicesCount ... 1955

221 Schema: PriceListWorkTypeModifiers 1955

221.1 Tables ... 1955
221.1.1 PriceListWorkTypeModifiers ... 1955
221.1.2 PriceListWorkTypeModifiersById ... 1955
221.1.3 PriceListWorkTypeModifiersCount ... 1956

222 Schema: ProductNotes 1957

222.1 Tables ... 1957
222.1.1 ProductNotes ... 1957
222.1.2 ProductNotesById ... 1958
222.1.3 ProductNotesCount ... 1959

223 Schema: ProductNotesChild 1959

223.1 Tables ... 1959
223.1.1 ProductsByParentIdNotes ... 1959
223.1.2 ProductsByParentIdNotesId ... 1960

224 Schema: Products 1962

224.1 Tables ... 1962
224.1.1 Products ... 1962
224.1.2 Products_ItemsUserDefinedFields ... 1963
224.1.3 ProductsById ... 1964
224.1.4 ProductsCount ... 1965

225 Schema: ProductTiers 1966

225.1 Tables ... 1966
225.1.1 ProductTiers ... 1966
225.1.2 ProductTiersById ... 1966
225.1.3 ProductTiersCount ... 1967

226 Schema: ProductTiersChild 1968

226.1 Tables ... 1968
226.1.1 ProductsByParentIdTiers ... 1968
226.1.2 ProductsByParentIdTiersId ... 1969

227 Schema: ProductVendors 1970

227.1 Tables ... 1970
227.1.1 ProductVendors ... 1970
227.1.2 ProductVendorsById ... 1971
227.1.3 ProductVendorsCount ... 1972

228 Schema: ProductVendorsChild 1972

228.1 Tables ... 1972
228.1.1 ProductsByParentIdVendors ... 1972
228.1.2 ProductsByParentIdVendorsId ... 1973

229 Schema: ProjectAttachments 1975

229.1 Tables ... 1975

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

229.1.1 ProjectAttachments ... 1975
229.1.2 ProjectAttachmentsById ... 1976
229.1.3 ProjectAttachmentsCount ... 1977

230 Schema: ProjectAttachmentsChild 1978

230.1 Tables ... 1978
230.1.1 ProjectsByParentIdAttachments ... 1978
230.1.2 ProjectsByParentIdAttachmentsId ... 1979

231 Schema: ProjectCharges 1981

231.1 Tables ... 1981
231.1.1 ProjectCharges ... 1981
231.1.2 ProjectChargesById ... 1982
231.1.3 ProjectChargesCount ... 1984

232 Schema: ProjectChargesChild 1984

232.1 Tables ... 1984
232.1.1 ProjectsByParentIdCharges ... 1984
232.1.2 ProjectsByParentIdChargesId ... 1986

233 Schema: ProjectNoteAttachments 1988

233.1 Tables ... 1988
233.1.1 ProjectNoteAttachments ... 1988
233.1.2 ProjectNoteAttachmentsById ... 1989
233.1.3 ProjectNoteAttachmentsCount ... 1991

234 Schema: ProjectNoteAttachmentsChild 1991

234.1 Tables ... 1991
234.1.1 ProjectNotesByParentIdAttachments ... 1991
234.1.2 ProjectNotesByParentIdAttachmentsId ... 1992

235 Schema: ProjectNotes 1994

235.1 Tables ... 1994
235.1.1 ProjectNotes ... 1994
235.1.2 ProjectNotesById ... 1995
235.1.3 ProjectNotesCount ... 1996

236 Schema: ProjectNotesChild 1997

236.1 Tables ... 1997
236.1.1 ProjectsByParentIdNotes ... 1997
236.1.2 ProjectsByParentIdNotesId ... 1998

237 Schema: Projects 1999

237.1 Tables ... 1999
237.1.1 Projects ... 1999
237.1.2 Projects_ItemsUserDefinedFields ... 2001
237.1.3 ProjectsById ... 2003
237.1.4 ProjectsCount ... 2005

238 Schema: PurchaseApprovals 2005

238.1 Tables ... 2005
238.1.1 PurchaseApprovals ... 2005
238.1.2 PurchaseApprovalsById ... 2005
238.1.3 PurchaseApprovalsCount ... 2006

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

239 Schema: PurchaseOrderItemReceiving 2007

239.1 Tables ... 2007
239.1.1 PurchaseOrderItemReceiving ... 2007
239.1.2 PurchaseOrderItemReceivingById ... 2007
239.1.3 PurchaseOrderItemReceivingCount ... 2009

240 Schema: PurchaseOrderItemReceivingChild 2009

240.1 Tables ... 2009
240.1.1 PurchaseOrderItemsByParentIdReceiving ... 2009
240.1.2 PurchaseOrderItemsByParentIdReceivingId ... 2010

241 Schema: PurchaseOrderItems 2012

241.1 Tables ... 2012
241.1.1 PurchaseOrderItems ... 2012
241.1.2 PurchaseOrderItemsById ... 2013
241.1.3 PurchaseOrderItemsCount ... 2014

242 Schema: PurchaseOrderItemsChild 2014

242.1 Tables ... 2014
242.1.1 PurchaseOrdersByParentIdItems ... 2014
242.1.2 PurchaseOrdersByParentIdItemsId ... 2016

243 Schema: PurchaseOrders 2017

243.1 Tables ... 2017
243.1.1 PurchaseOrders ... 2017
243.1.2 PurchaseOrdersById ... 2018
243.1.3 PurchaseOrdersCount ... 2020

244 Schema: QuoteItems 2020

244.1 Tables ... 2020
244.1.1 QuoteItems ... 2020
244.1.2 QuoteItemsById ... 2022
244.1.3 QuoteItemsCount ... 2024

245 Schema: QuoteItemsChild 2024

245.1 Tables ... 2024
245.1.1 QuotesByParentIdItems ... 2024
245.1.2 QuotesByParentIdItemsId ... 2026

246 Schema: QuoteLocations 2027

246.1 Tables ... 2027
246.1.1 QuoteLocations ... 2027
246.1.2 QuoteLocationsById ... 2028
246.1.3 QuoteLocationsCount ... 2029

247 Schema: Quotes 2029

247.1 Tables ... 2029
247.1.1 Quotes ... 2029
247.1.2 QuotesById ... 2031
247.1.3 QuotesCount ... 2033

248 Schema: QuoteTemplates 2033

248.1 Tables ... 2033
248.1.1 QuoteTemplates ... 2033

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

248.1.2 QuoteTemplatesById ... 2034
248.1.3 QuoteTemplatesCount ... 2035

249 Schema: ResourceAttachments 2036

249.1 Tables ... 2036
249.1.1 ResourceAttachments ... 2036
249.1.2 ResourceAttachmentsById ... 2037
249.1.3 ResourceAttachmentsCount ... 2038

250 Schema: ResourceAttachmentsChild 2038

250.1 Tables ... 2038
250.1.1 ResourcesByParentIdAttachments ... 2038
250.1.2 ResourcesByParentIdAttachmentsId ... 2040

251 Schema: ResourceRoleDepartments 2041

251.1 Tables ... 2041
251.1.1 ResourceRoleDepartments ... 2041
251.1.2 ResourceRoleDepartmentsById ... 2042
251.1.3 ResourceRoleDepartmentsCount ... 2043

252 Schema: ResourceRoleDepartmentsChild 2044

252.1 Tables ... 2044
252.1.1 ResourcesByParentIdRoleDepartments ... 2044
252.1.2 ResourcesByParentIdRoleDepartmentsId ... 2045

253 Schema: ResourceRoleQueues 2046

253.1 Tables ... 2046
253.1.1 ResourceRoleQueues ... 2046
253.1.2 ResourceRoleQueuesById ... 2047
253.1.3 ResourceRoleQueuesCount ... 2048

254 Schema: ResourceRoleQueuesChild 2048

254.1 Tables ... 2048
254.1.1 ResourcesByParentIdRoleQueues ... 2048
254.1.2 ResourcesByParentIdRoleQueuesId ... 2049

255 Schema: ResourceRoles 2050

255.1 Tables ... 2050
255.1.1 ResourceRoles ... 2050
255.1.2 ResourceRolesById ... 2051
255.1.3 ResourceRolesCount ... 2052

256 Schema: ResourceRolesChild 2052

256.1 Tables ... 2052
256.1.1 ResourcesByParentIdRoles ... 2052
256.1.2 ResourcesByParentIdRolesId ... 2053

257 Schema: Resources 2054

257.1 Tables ... 2054
257.1.1 Resources ... 2054
257.1.2 ResourcesById ... 2055
257.1.3 ResourcesCount ... 2057

258 Schema: ResourceServiceDeskRoles 2057

258.1 Tables ... 2057

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

258.1.1 ResourceServiceDeskRoles ... 2057
258.1.2 ResourceServiceDeskRolesById ... 2058
258.1.3 ResourceServiceDeskRolesCount ... 2059

259 Schema: ResourceServiceDeskRolesChild 2059

259.1 Tables ... 2059
259.1.1 ResourcesByParentIdServiceDeskRoles ... 2059
259.1.2 ResourcesByParentIdServiceDeskRolesId ... 2060

260 Schema: ResourceSkills 2062

260.1 Tables ... 2062
260.1.1 ResourceSkills ... 2062
260.1.2 ResourceSkillsById ... 2062
260.1.3 ResourceSkillsCount ... 2063

261 Schema: ResourceSkillsChild 2064

261.1 Tables ... 2064
261.1.1 ResourcesByParentIdSkills ... 2064
261.1.2 ResourcesByParentIdSkillsId ... 2065

262 Schema: Roles 2066

262.1 Tables ... 2066
262.1.1 Roles ... 2066
262.1.2 RolesById ... 2067
262.1.3 RolesCount ... 2068

263 Schema: SalesOrderAttachments 2068

263.1 Tables ... 2068
263.1.1 SalesOrderAttachments ... 2068
263.1.2 SalesOrderAttachmentsById ... 2069
263.1.3 SalesOrderAttachmentsCount ... 2070

264 Schema: SalesOrderAttachmentsChild 2071

264.1 Tables ... 2071
264.1.1 SalesOrdersByParentIdAttachments ... 2071
264.1.2 SalesOrdersByParentIdAttachmentsId ... 2072

265 Schema: SalesOrders 2074

265.1 Tables ... 2074
265.1.1 SalesOrders ... 2074
265.1.2 SalesOrders_ItemsUserDefinedFields ... 2075
265.1.3 SalesOrdersById ... 2076
265.1.4 SalesOrdersCount ... 2078

266 Schema: SalesOrdersChild 2078

266.1 Tables ... 2078
266.1.1 OpportunitiesByParentId_ItemsUserDefinedFieldsSalesOrders ... 2078
266.1.2 OpportunitiesByParentIdSalesOrders ... 2080
266.1.3 OpportunitiesByParentIdSalesOrdersId ... 2082

267 Schema: ServiceBundles 2084

267.1 Tables ... 2084
267.1.1 ServiceBundles ... 2084
267.1.2 ServiceBundlesById ... 2084
267.1.3 ServiceBundlesCount ... 2085

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

268 Schema: ServiceBundleServices 2086

268.1 Tables ... 2086
268.1.1 ServiceBundleServices ... 2086
268.1.2 ServiceBundleServicesById ... 2086
268.1.3 ServiceBundleServicesCount ... 2087

269 Schema: ServiceBundleServicesChild 2088

269.1 Tables ... 2088
269.1.1 ServiceBundlesByParentIdServices ... 2088
269.1.2 ServiceBundlesByParentIdServicesId ... 2089

270 Schema: ServiceCalls 2090

270.1 Tables ... 2090
270.1.1 ServiceCalls ... 2090
270.1.2 ServiceCallsById ... 2091
270.1.3 ServiceCallsCount ... 2092

271 Schema: ServiceCallTaskResources 2092

271.1 Tables ... 2092
271.1.1 ServiceCallTaskResources ... 2092
271.1.2 ServiceCallTaskResourcesById ... 2093
271.1.3 ServiceCallTaskResourcesCount ... 2094

272 Schema: ServiceCallTaskResourcesChild 2094

272.1 Tables ... 2094
272.1.1 ServiceCallTasksByParentIdResources ... 2094
272.1.2 ServiceCallTasksByParentIdResourcesId ... 2095

273 Schema: ServiceCallTasks 2097

273.1 Tables ... 2097
273.1.1 ServiceCallTasks ... 2097
273.1.2 ServiceCallTasksById ... 2097
273.1.3 ServiceCallTasksCount ... 2098

274 Schema: ServiceCallTasksChild 2099

274.1 Tables ... 2099
274.1.1 ServiceCallsByParentIdTasks ... 2099
274.1.2 ServiceCallsByParentIdTasksId ... 2100

275 Schema: ServiceCallTicketResources 2101

275.1 Tables ... 2101
275.1.1 ServiceCallTicketResources ... 2101
275.1.2 ServiceCallTicketResourcesById ... 2101
275.1.3 ServiceCallTicketResourcesCount ... 2103

276 Schema: ServiceCallTicketResourcesChild 2103

276.1 Tables ... 2103
276.1.1 ServiceCallTicketsByParentIdResources ... 2103
276.1.2 ServiceCallTicketsByParentIdResourcesId ... 2104

277 Schema: ServiceCallTickets 2105

277.1 Tables ... 2105
277.1.1 ServiceCallTickets ... 2105
277.1.2 ServiceCallTicketsById ... 2106

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

277.1.3 ServiceCallTicketsCount ... 2107

278 Schema: ServiceCallTicketsChild 2107

278.1 Tables ... 2107
278.1.1 ServiceCallsByParentIdTickets ... 2107
278.1.2 ServiceCallsByParentIdTicketsId ... 2108

279 Schema: ServiceLevelAgreementResults 2109

279.1 Tables ... 2109
279.1.1 ServiceLevelAgreementResults ... 2109
279.1.2 ServiceLevelAgreementResultsById ... 2110
279.1.3 ServiceLevelAgreementResultsCount ... 2111

280 Schema: ServiceLevelAgreementResultsChild 2112

280.1 Tables ... 2112
280.1.1 ServiceLevelAgreementsByParentIdResults ... 2112
280.1.2 ServiceLevelAgreementsByParentIdResultsId ... 2113

281 Schema: Services 2114

281.1 Tables ... 2114
281.1.1 Services ... 2114
281.1.2 ServicesById ... 2115
281.1.3 ServicesCount ... 2116

282 Schema: ShippingTypes 2116

282.1 Tables ... 2116
282.1.1 ShippingTypes ... 2116
282.1.2 ShippingTypesById ... 2117
282.1.3 ShippingTypesCount ... 2118

283 Schema: Skills 2118

283.1 Tables ... 2118
283.1.1 Skills ... 2118
283.1.2 SkillsById ... 2118
283.1.3 SkillsCount ... 2119

284 Schema: SubscriptionPeriods 2120

284.1 Tables ... 2120
284.1.1 SubscriptionPeriods ... 2120
284.1.2 SubscriptionPeriodsById ... 2120
284.1.3 SubscriptionPeriodsCount ... 2121

285 Schema: SubscriptionPeriodsChild 2122

285.1 Tables ... 2122
285.1.1 SubscriptionsByParentIdPeriods ... 2122
285.1.2 SubscriptionsByParentIdPeriodsId ... 2123

286 Schema: Subscriptions 2124

286.1 Tables ... 2124
286.1.1 Subscriptions ... 2124
286.1.2 Subscriptions_ItemsUserDefinedFields ... 2124
286.1.3 SubscriptionsById ... 2125
286.1.4 SubscriptionsCount ... 2126

287 Schema: SurveyResults 2127

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

287.1 Tables ... 2127
287.1.1 SurveyResults ... 2127
287.1.2 SurveyResultsById ... 2127
287.1.3 SurveyResultsCount ... 2128

288 Schema: Surveys 2129

288.1 Tables ... 2129
288.1.1 Surveys ... 2129
288.1.2 SurveysById ... 2129
288.1.3 SurveysCount ... 2130

289 Schema: TagAliases 2130

289.1 Tables ... 2130
289.1.1 TagAliases ... 2130
289.1.2 TagAliasesById ... 2131
289.1.3 TagAliasesCount ... 2132

290 Schema: TagAliasesChild 2132

290.1 Tables ... 2132
290.1.1 TagsByParentIdAliases ... 2132
290.1.2 TagsByParentIdAliasesId ... 2133

291 Schema: TagGroups 2134

291.1 Tables ... 2134
291.1.1 TagGroups ... 2134
291.1.2 TagGroupsById ... 2135
291.1.3 TagGroupsCount ... 2136

292 Schema: Tags 2136

292.1 Tables ... 2136
292.1.1 Tags ... 2136
292.1.2 TagsById ... 2137
292.1.3 TagsCount ... 2138

293 Schema: TaskAttachments 2138

293.1 Tables ... 2138
293.1.1 TaskAttachments ... 2138
293.1.2 TaskAttachmentsById ... 2139
293.1.3 TaskAttachmentsCount ... 2141

294 Schema: TaskAttachmentsChild 2141

294.1 Tables ... 2141
294.1.1 TasksByParentIdAttachments ... 2141
294.1.2 TasksByParentIdAttachmentsId ... 2142

295 Schema: TaskNoteAttachments 2144

295.1 Tables ... 2144
295.1.1 TaskNoteAttachments ... 2144
295.1.2 TaskNoteAttachmentsById ... 2145
295.1.3 TaskNoteAttachmentsCount ... 2147

296 Schema: TaskNoteAttachmentsChild 2147

296.1 Tables ... 2147
296.1.1 TaskNotesByParentIdAttachments ... 2147
296.1.2 TaskNotesByParentIdAttachmentsId ... 2148

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

297 Schema: TaskNotes 2150

297.1 Tables ... 2150
297.1.1 TaskNotes ... 2150
297.1.2 TaskNotesById ... 2151
297.1.3 TaskNotesCount ... 2152

298 Schema: TaskNotesChild 2152

298.1 Tables ... 2152
298.1.1 TasksByParentIdNotes ... 2152
298.1.2 TasksByParentIdNotesId ... 2154

299 Schema: TaskPredecessors 2155

299.1 Tables ... 2155
299.1.1 TaskPredecessors ... 2155
299.1.2 TaskPredecessorsById ... 2156
299.1.3 TaskPredecessorsCount ... 2157

300 Schema: TaskPredecessorsChild 2157

300.1 Tables ... 2157
300.1.1 TasksByParentIdPredecessors ... 2157
300.1.2 TasksByParentIdPredecessorsId ... 2158

301 Schema: Tasks 2159

301.1 Tables ... 2159
301.1.1 Tasks ... 2159
301.1.2 Tasks_ItemsUserDefinedFields ... 2161
301.1.3 TasksById ... 2163
301.1.4 TasksCount ... 2164

302 Schema: TasksChild 2165

302.1 Tables ... 2165
302.1.1 ProjectsByParentId_ItemsUserDefinedFieldsTasks ... 2165
302.1.2 ProjectsByParentIdTasks ... 2167
302.1.3 ProjectsByParentIdTasksId ... 2169

303 Schema: TaskSecondaryResources 2171

303.1 Tables ... 2171
303.1.1 TaskSecondaryResources ... 2171
303.1.2 TaskSecondaryResourcesById ... 2172
303.1.3 TaskSecondaryResourcesCount ... 2173

304 Schema: TaskSecondaryResourcesChild 2173

304.1 Tables ... 2173
304.1.1 TasksByParentIdSecondaryResources ... 2173
304.1.2 TasksByParentIdSecondaryResourcesId ... 2174

305 Schema: TaxCategories 2175

305.1 Tables ... 2175
305.1.1 TaxCategories ... 2175
305.1.2 TaxCategoriesById ... 2176
305.1.3 TaxCategoriesCount ... 2176

306 Schema: Taxes 2177

306.1 Tables ... 2177

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

306.1.1 Taxes ... 2177
306.1.2 TaxesById ... 2177
306.1.3 TaxesCount ... 2178

307 Schema: TaxRegions 2178

307.1 Tables ... 2178
307.1.1 TaxRegions ... 2178
307.1.2 TaxRegionsById ... 2179
307.1.3 TaxRegionsCount ... 2180

308 Schema: ThresholdApiIntegration 2180

308.1 Tables ... 2180
308.1.1 ThresholdInformation ... 2180

309 Schema: TicketAdditionalConfigurationItems 2180

309.1 Tables ... 2180
309.1.1 TicketAdditionalConfigurationItems ... 2180
309.1.2 TicketAdditionalConfigurationItemsById ... 2181
309.1.3 TicketAdditionalConfigurationItemsCount ... 2182

310 Schema: TicketAdditionalConfigurationItemsChild 2182

310.1 Tables ... 2182
310.1.1 TicketsByParentIdAdditionalConfigurationItems ... 2182
310.1.2 TicketsByParentIdAdditionalConfigurationItemsId ... 2184

311 Schema: TicketAdditionalContacts 2185

311.1 Tables ... 2185
311.1.1 TicketAdditionalContacts ... 2185
311.1.2 TicketAdditionalContactsById ... 2185
311.1.3 TicketAdditionalContactsCount ... 2186

312 Schema: TicketAdditionalContactsChild 2187

312.1 Tables ... 2187
312.1.1 TicketsByParentIdAdditionalContacts ... 2187
312.1.2 TicketsByParentIdAdditionalContactsId ... 2188

313 Schema: TicketAttachments 2189

313.1 Tables ... 2189
313.1.1 TicketAttachments ... 2189
313.1.2 TicketAttachmentsById ... 2190
313.1.3 TicketAttachmentsCount ... 2192

314 Schema: TicketAttachmentsChild 2192

314.1 Tables ... 2192
314.1.1 TicketsByParentIdAttachments ... 2192
314.1.2 TicketsByParentIdAttachmentsId ... 2193

315 Schema: TicketCategories 2195

315.1 Tables ... 2195
315.1.1 TicketCategories ... 2195
315.1.2 TicketCategoriesById ... 2196
315.1.3 TicketCategoriesCount ... 2196

316 Schema: TicketCategoryFieldDefaults 2197

316.1 Tables ... 2197

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

316.1.1 TicketCategoryFieldDefaults ... 2197
316.1.2 TicketCategoryFieldDefaultsById ... 2198
316.1.3 TicketCategoryFieldDefaultsCount ... 2199

317 Schema: TicketCategoryFieldDefaultsChild 2199

317.1 Tables ... 2199
317.1.1 TicketCategoriesByParentIdFieldDefaults ... 2199
317.1.2 TicketCategoriesByParentIdFieldDefaultsId ... 2200

318 Schema: TicketChangeRequestApprovals 2202

318.1 Tables ... 2202
318.1.1 TicketChangeRequestApprovals ... 2202
318.1.2 TicketChangeRequestApprovalsById ... 2203
318.1.3 TicketChangeRequestApprovalsCount ... 2204

319 Schema: TicketChangeRequestApprovalsChild 2204

319.1 Tables ... 2204
319.1.1 TicketsByParentIdChangeRequestApprovals ... 2204
319.1.2 TicketsByParentIdChangeRequestApprovalsId ... 2205

320 Schema: TicketCharges 2206

320.1 Tables ... 2206
320.1.1 TicketCharges ... 2206
320.1.2 TicketChargesById ... 2208
320.1.3 TicketChargesCount ... 2210

321 Schema: TicketChargesChild 2210

321.1 Tables ... 2210
321.1.1 TicketsByParentIdCharges ... 2210
321.1.2 TicketsByParentIdChargesId ... 2212

322 Schema: TicketChecklistItems 2214

322.1 Tables ... 2214
322.1.1 TicketChecklistItems ... 2214
322.1.2 TicketChecklistItemsById ... 2214
322.1.3 TicketChecklistItemsCount ... 2216

323 Schema: TicketChecklistItemsChild 2216

323.1 Tables ... 2216
323.1.1 TicketsByParentIdChecklistItems ... 2216
323.1.2 TicketsByParentIdChecklistItemsId ... 2217

324 Schema: TicketHistory 2219

324.1 Tables ... 2219
324.1.1 TicketHistory ... 2219
324.1.2 TicketHistoryById ... 2220
324.1.3 TicketHistoryCount ... 2220

325 Schema: TicketNoteAttachments 2221

325.1 Tables ... 2221
325.1.1 TicketNoteAttachments ... 2221
325.1.2 TicketNoteAttachmentsById ... 2222
325.1.3 TicketNoteAttachmentsCount ... 2223

326 Schema: TicketNoteAttachmentsChild 2224

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

326.1 Tables ... 2224
326.1.1 TicketNotesByParentIdAttachments ... 2224
326.1.2 TicketNotesByParentIdAttachmentsId ... 2225

327 Schema: TicketNotes 2227

327.1 Tables ... 2227
327.1.1 TicketNotes ... 2227
327.1.2 TicketNotesById ... 2228
327.1.3 TicketNotesCount ... 2229

328 Schema: TicketNotesChild 2229

328.1 Tables ... 2229
328.1.1 TicketsByParentIdNotes ... 2229
328.1.2 TicketsByParentIdNotesId ... 2231

329 Schema: TicketNoteWebhookExcludedResources 2232

329.1 Tables ... 2232
329.1.1 TicketNoteWebhookExcludedResources ... 2232
329.1.2 TicketNoteWebhookExcludedResourcesById ... 2233
329.1.3 TicketNoteWebhookExcludedResourcesCount ... 2234

330 Schema: TicketNoteWebhookExcludedResourcesC 2234

330.1 Tables ... 2234
330.1.1 TicketNoteWebhooksByParentIdExcludedResources ... 2234
330.1.2 TicketNoteWebhooksByParentIdExcludedResourcesId ... 2235

331 Schema: TicketNoteWebhookFields 2236

331.1 Tables ... 2236
331.1.1 TicketNoteWebhookFields ... 2236
331.1.2 TicketNoteWebhookFieldsById ... 2237
331.1.3 TicketNoteWebhookFieldsCount ... 2238

332 Schema: TicketNoteWebhookFieldsChild 2238

332.1 Tables ... 2238
332.1.1 TicketNoteWebhooksByParentIdFields ... 2238
332.1.2 TicketNoteWebhooksByParentIdFieldsId ... 2240

333 Schema: TicketNoteWebhooks 2241

333.1 Tables ... 2241
333.1.1 TicketNoteWebhooks ... 2241
333.1.2 TicketNoteWebhooksById ... 2241
333.1.3 TicketNoteWebhooksCount ... 2243

334 Schema: TicketRmaCredits 2243

334.1 Tables ... 2243
334.1.1 TicketRmaCredits ... 2243
334.1.2 TicketRmaCreditsById ... 2244
334.1.3 TicketRmaCreditsCount ... 2245

335 Schema: TicketRmaCreditsChild 2245

335.1 Tables ... 2245
335.1.1 TicketsByParentIdRmaCredits ... 2245
335.1.2 TicketsByParentIdRmaCreditsId ... 2246

336 Schema: Tickets 2247

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

336.1 Tables ... 2247
336.1.1 Tickets ... 2247
336.1.2 Tickets_ItemsUserDefinedFields ... 2250
336.1.3 TicketsById ... 2253
336.1.4 TicketsCount ... 2256

337 Schema: TicketSecondaryResources 2256

337.1 Tables ... 2256
337.1.1 TicketSecondaryResources ... 2256
337.1.2 TicketSecondaryResourcesById ... 2257
337.1.3 TicketSecondaryResourcesCount ... 2258

338 Schema: TicketSecondaryResourcesChild 2259

338.1 Tables ... 2259
338.1.1 TicketsByParentIdSecondaryResources ... 2259
338.1.2 TicketsByParentIdSecondaryResourcesId ... 2260

339 Schema: TicketTagAssociations 2261

339.1 Tables ... 2261
339.1.1 TicketTagAssociations ... 2261
339.1.2 TicketTagAssociationsById ... 2261
339.1.3 TicketTagAssociationsCount ... 2263

340 Schema: TicketTagAssociationsChild 2263

340.1 Tables ... 2263
340.1.1 TicketsByParentIdTagAssociations ... 2263
340.1.2 TicketsByParentIdTagAssociationsId ... 2264

341 Schema: TicketWebhookExcludedResources 2265

341.1 Tables ... 2265
341.1.1 TicketWebhookExcludedResources ... 2265
341.1.2 TicketWebhookExcludedResourcesById ... 2266
341.1.3 TicketWebhookExcludedResourcesCount ... 2267

342 Schema: TicketWebhookExcludedResourcesChild 2267

342.1 Tables ... 2267
342.1.1 TicketWebhooksByParentIdExcludedResources ... 2267
342.1.2 TicketWebhooksByParentIdExcludedResourcesId ... 2268

343 Schema: TicketWebhookFields 2269

343.1 Tables ... 2269
343.1.1 TicketWebhookFields ... 2269
343.1.2 TicketWebhookFieldsById ... 2270
343.1.3 TicketWebhookFieldsCount ... 2271

344 Schema: TicketWebhookFieldsChild 2271

344.1 Tables ... 2271
344.1.1 TicketWebhooksByParentIdFields ... 2271
344.1.2 TicketWebhooksByParentIdFieldsId ... 2273

345 Schema: TicketWebhooks 2274

345.1 Tables ... 2274
345.1.1 TicketWebhooks ... 2274
345.1.2 TicketWebhooksById ... 2274
345.1.3 TicketWebhooksCount ... 2276

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

346 Schema: TicketWebhookUdfFields 2276

346.1 Tables ... 2276
346.1.1 TicketWebhookUdfFields ... 2276
346.1.2 TicketWebhookUdfFieldsById ... 2277
346.1.3 TicketWebhookUdfFieldsCount ... 2278

347 Schema: TicketWebhookUdfFieldsChild 2278

347.1 Tables ... 2278
347.1.1 TicketWebhooksByParentIdUdfFields ... 2278
347.1.2 TicketWebhooksByParentIdUdfFieldsId ... 2279

348 Schema: TimeEntries 2280

348.1 Tables ... 2280
348.1.1 TimeEntries ... 2280
348.1.2 TimeEntriesById ... 2282
348.1.3 TimeEntriesCount ... 2283

349 Schema: TimeEntryAttachments 2284

349.1 Tables ... 2284
349.1.1 TimeEntryAttachments ... 2284
349.1.2 TimeEntryAttachmentsById ... 2285
349.1.3 TimeEntryAttachmentsCount ... 2286

350 Schema: TimeEntryAttachmentsChild 2287

350.1 Tables ... 2287
350.1.1 TimeEntriesByParentIdAttachments ... 2287
350.1.2 TimeEntriesByParentIdAttachmentsId ... 2288

351 Schema: TimeOffRequests 2290

351.1 Tables ... 2290
351.1.1 TimeOffRequests ... 2290
351.1.2 TimeOffRequestsById ... 2291
351.1.3 TimeOffRequestsCount ... 2292

352 Schema: TimeOffRequestsChild 2293

352.1 Tables ... 2293
352.1.1 ResourcesByParentIdTimeOffRequests ... 2293
352.1.2 ResourcesByParentIdTimeOffRequestsId ... 2294

353 Schema: UserDefinedFieldDefinitions 2295

353.1 Tables ... 2295
353.1.1 UserDefinedFieldDefinitions ... 2295
353.1.2 UserDefinedFieldDefinitionsById ... 2296
353.1.3 UserDefinedFieldDefinitionsCount ... 2297

354 Schema: UserDefinedFieldListItems 2298

354.1 Tables ... 2298
354.1.1 UserDefinedFieldListItems ... 2298
354.1.2 UserDefinedFieldListItemsById ... 2299
354.1.3 UserDefinedFieldListItemsCount ... 2300

355 Schema: UserDefinedFieldListItemsChild 2300

355.1 Tables ... 2300
355.1.1 UserDefinedFieldsByParentIdListItems ... 2300

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

355.1.2 UserDefinedFieldsByParentIdListItemsId 2301

356 Schema: WebhookEventErrorLogs 2302

356.1 Tables 2302
356.1.1 WebhookEventErrorLogs 2302
356.1.2 WebhookEventErrorLogsById 2303
356.1.3 WebhookEventErrorLogsCount 2304

357 Schema: WorkTypeModifiers 2304

357.1 Tables 2304
357.1.1 WorkTypeModifiers 2304
357.1.2 WorkTypeModifiersById 2305
357.1.3 WorkTypeModifiersCount 2305

358 Schema: ZoneInformationApiIntegration 2306

358.1 Tables 2306
358.1.1 ZoneInformation 2306

Index 2307

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

1 SQL Driver for Autotask API

Invantive UniversalSQL is the fastest, easiest and most reliable way to exchange data with the Autotask API.

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the user community. Invantive Support or other users will try to help you.

datto Autotask service management.

The Autotask driver covers 2609 tables and 38275 columns.

Autotask API Clients

Invantive UniversalSQL is available on many user interfaces ("clients" in traditional server-client paradigma). All Invantive UniversalSQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

The Autotask Power BI connector is based on the Invantive UniversalSQL driver for Autotask, completed by a high-performance OData connector which works straight on Power BI without any add-on. The OData protocol is always version 4, independent whether the backing platform uses OData, SOAP or another protocol.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL. High-volume replication of data taken from the Autotask API into traditional databases such as SQL Server (on-premises and Azure), MySQL, PostgreSQL and Oracle is possible using Invantive Data Replicator. Invantive Data Replicator automatically creates and maintains Autotask datawarehouses, possibly in combination with data from over 75 other (cloud) platforms. Invantive Data Replicator supports data volumes up to over 1 TB and over 5.000 companies. The on-premise edition of Invantive Bridge offers an Autotask ADO.net provider.

Finally, online web apps can be build for Autotask using App Online of Invantive Cloud.

Monitor API Calls

When a query or DML-statement has been executed on Invantive UniversalSQL a developer can evaluate the actual calls made to the Autotask API using a query on sessionios@DataDictionary. As an alternative, extensive request and response logging can be enabled by setting log-native-calls-to-disk to true. In the %USERPROFILE% \Invantive\NativeLog folder Invantive UniversalSQL will create log files per Autotask API request and response.

Specifications

The SQL driver for Autotask does not support partitioning. Define one data container in a database for each company in Autotask to enable parallel access for data from multiple companies.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

An introduction into the concepts of Invantive UniversalSQL such as databases, data containers and partitioning can be found in the Invantive UniversalSQL grammar.

The configuration can be changed using various attributes from the database definition, on log on and during use. A full list of configuration options is listed in the driver attributes 2.

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On Autotask the comparison of two texts is case sensitive by default.

Changes and bug fixes on the Autotask SQL driver can be found in the release notes. Get access to the community through the Autotask section of the Invantive forums.

Driver code for use in settings.xml: `Autotask`

Alias: `autotask`

Recommended alias: `at`

Driver code for use in settings.xml

General documentation on Autotask is available at https://www.autotask.net/help.

Autotask is Professional Services Automation (PSA) software from Datto. Autotask provides a cloud-based PSA platform for businesses.

Updated 10-06-2024 18:39 using Invantive UniversalSQL version 24.1.3-BETA+4689.

2 SQL Driver Attributes for Autotask API

The SQL driver for Autotask has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the API server of Autotask or high volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The Autotask driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for Autotask can be found in the settings*.xml file used for the database. The reference manuals contain instructions how to relocate the settings*.xml files. Settings*.xml files are typically located in the `%USERPROFILE%\invantive` folder in most deployment scenarios. Each data container of a database in the connection string can have a `connectionString` element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: `set NAME VALUE`, or for a distributed database: `set NAME@ALIAS VALUE`. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance when a reserved SQL keyword is part of the name. The new value takes effect straight after

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The Autotask driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
add-odata-mandatory-filters	Whether to automatically add OData filters deemed necessary by the platform.	OData	False	✓	✓	✓	
analysis-enforce-row-uniqueness	Enforce rows to be unique for software analysis. A fingerprint is calculated from the whole row of data when the primary key column is unknown.	Shared	False	✓	✓	✓	
api-access-token	Access Token is a security token for multiple OAuth2 Flows. With an Access Token you can access protected resources. An Access Token must be stored securely since once compromised allows access to your protected resources.	OData		✓	✓	✓	✓
api-client-id	The client ID is a unique identifier of your application. It is generated by registering an application.	OData		✓		✓	✓
api-client-secret	The client secret is to be kept confidential. Such as a password for a logon code, the client secret is the confidential part of an app identified by a client ID. It is needed during the OAuth2 Code Grant Flow together with the refresh token to get access.	OData		✓		✓	✓
api-integration-code	The integration code uniquely identifies the Autotask application and vendor.	Autotask		✓		✓	✓
api-pre-expiry-refresh-sec	The number of seconds before the token expires to acquire a new token.	OData		✓	✓	✓	
api-redirect-url	The redirect URI is the website a browser session is redirected to after the OAuth2 authentication process has been completed.	OData		✓		✓	✓
api-refresh-token	Refresh Token is a security token for the OAuth2 Code Grant Flow. With a Refresh Token and client secret you can retrieve a renewed access token to access protected resources. A Refresh Token and client secret must be stored securely since once compromised	OData		✓		✓	✓

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
	allows access to your protected resources.						
api-scope	The authorization scope(s) to request an OAuth token for.	OData		✓		✓	
api-token-url	The token URI is the OAuth2 endpoint to exchange tokens with.	OData		✓		✓	
api-url	URL of web service.	OData		✓		✓	
bulk-delete-page-size-rows	Number of rows to delete per batch when bulk deleting.	Shared	10000	✓	✓	✓	
bulk-insert-page-size-bytes	Approximate maximum size in bytes of batch when bulk inserting.	Shared	10000000	✓	✓	✓	
bulk-insert-page-size-rows	Number of rows to insert per batch when bulk inserting.	Shared	250	✓	✓	✓	
download-error-400-bad-request-max-tries	Maximum number of tries when HTTP server reports bad format during retrieval of data.		3	✓	✓	✓	
download-error-400-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when HTTP server reports that the API server is unavailable during retrieval of data.		500	✓	✓	✓	
download-error-400-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when HTTP server reports that the API server is unavailable during retrieval of data.		5000	✓	✓	✓	
download-error-400-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries HTTP server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
download-error-408-request-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 408.		10	✓	✓	✓	
download-error-408-request-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 408.		10000	✓	✓	✓	
download-error-408-request-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 408.		300000	✓	✓	✓	
download-error-408-request-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 408.		2	✓	✓	✓	
download-error-422-bad-request-max-tries	Maximum number of tries when HTTP server reports unprocessable entity during retrieval of data.		30	✓	✓	✓	
download-error-422-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when HTTP server reports unprocessable entity during retrieval of data.		10000	✓	✓	✓	
download-error-422-bad-request-	Maximum sleep in milliseconds between retries when HTTP server		300000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
sleep-max-ms	reports unprocessable entity during retrieval of data.						
download-error-422-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries HTTP server reports unprocessable entity during retrieval of data.		2	✓	✓	✓	
download-error-429-too-many-requests-max-tries	Maximum number of tries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10	✓	✓	✓	
download-error-429-too-many-requests-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10000	✓	✓	✓	
download-error-429-too-many-requests-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		300000	✓	✓	✓	
download-error-429-too-many-requests-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		2	✓	✓	✓	
download-error-500-internal-server-error-max-tries	itgen_pae_download_error_500_internal_server_error_max_tries		10	✓	✓	✓	
download-error-500-internal-server-error-sleep-initial-ms	itgen_pae_download_error_500_internal_server_error_sleep_initial_ms		10000	✓	✓	✓	
download-error-500-internal-server-error-sleep-max-ms	itgen_pae_download_error_500_internal_server_error_sleep_max_ms		300000	✓	✓	✓	
download-error-500-internal-server-error-sleep-multiplicator	itgen_pae_download_error_500_internal_server_error_sleep_multiplicator		2	✓	✓	✓	
download-error-502-server-unavailable-max-tries	Maximum number of tries when HTTP server reports a bad gateway during retrieval of data.		30	✓	✓	✓	
download-error-502-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when HTTP server reports a bad gateway during retrieval of data.		10000	✓	✓	✓	
download-error-502-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when HTTP server reports that a bad gateway during retrieval of data.		300000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
download-error-502-server-unavailable-sleep-multiplicator	Multiplication factor for sleep between retries HTTP server reports a bad gateway during retrieval of data.		2	✓	✓	✓	
download-error-503-server-unavailable-max-tries	Maximum number of tries when HTTP server reports that the API server is unavailable during retrieval of data.		30	✓	✓	✓	
download-error-503-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when HTTP server reports that the API server is unavailable during retrieval of data.		10000	✓	✓	✓	
download-error-503-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when HTTP server reports that the API server is unavailable during retrieval of data.		300000	✓	✓	✓	
download-error-503-server-unavailable-sleep-multiplicator	Multiplication factor for sleep between retries HTTP server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
download-error-504-gateway-timeout-max-tries	Maximum number of tries when the website reports a gateway timeout.		10	✓	✓	✓	
download-error-504-gateway-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a gateway timeout.		10000	✓	✓	✓	
download-error-504-gateway-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a gateway timeout.		300000	✓	✓	✓	
download-error-504-gateway-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a gateway timeout.		2	✓	✓	✓	
download-error-590-network-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 590.		10	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 590.		10000	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 590.		300000	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 590.		2	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
download-error-599-network-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 599.		10	✓	✓	✓	
download-error-599-network-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 599.		10000	✓	✓	✓	
download-error-599-network-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 599.		300000	✓	✓	✓	
download-error-599-network-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 599.		2	✓	✓	✓	
download-error-argument-exception-max-tries	Maximum number of tries when an argument exception is returned when downloading a blob.		10	✓	✓	✓	
download-error-argument-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		10000	✓	✓	✓	
download-error-argument-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		300000	✓	✓	✓	
download-error-argument-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an argument exception is returned when downloading a blob.		2	✓	✓	✓	
download-error-internet-down-max-tries	Maximum number of tries when the Internet connection seems down during retrieval of data.		10	✓	✓	✓	
download-error-internet-down-sleep-initial-ms	Initial sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		10000	✓	✓	✓	
download-error-internet-down-sleep-max-ms	Maximum sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		300000	✓	✓	✓	
download-error-internet-down-sleep-multiplicator	Multiplication factor for sleep between retries when the Internet connection seems down during retrieval of data.		2	✓	✓	✓	
download-error-io-exception-max-tries	Maximum number of tries when a network I/O connection failure occurs during retrieval of data.		10	✓	✓	✓	
download-error-io-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a network I/O		10000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
	connection failure occurs during retrieval of data.						
download-error-io-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		300000	✓	✓	✓	
download-error-io-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a network I/O connection failure occurs during retrieval of data.		2	✓	✓	✓	
download-error-json-exception-max-tries	Maximum number of tries when an invalid JSON body is returned.		3	✓	✓	✓	
download-error-json-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an invalid JSON body is returned.		1000	✓	✓	✓	
download-error-json-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an invalid JSON body is returned.		10000	✓	✓	✓	
download-error-json-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an invalid JSON body is returned.		2	✓	✓	✓	
download-error-name-resolution-failure-max-tries	Maximum number of tries when the host name could not be resolved during retrieval of data.		5	✓	✓	✓	
download-error-name-resolution-failure-sleep-initial-ms	Initial sleep in milliseconds between retries when the host name could not be resolved during retrieval of data.		5000	✓	✓	✓	
download-error-name-resolution-failure-sleep-max-ms	Maximum sleep in milliseconds between retries when the host name could not be resolved during retrieval of data.		5000	✓	✓	✓	
download-error-name-resolution-failure-sleep-multiplicator	itgen_pae_download_error_iname_resolution_failure_sleep_multiplicator		1	✓	✓	✓	
download-error-other-exception-max-tries	Maximum number of tries when an unqualified error occurs during retrieval of data.		3	✓	✓	✓	
download-error-other-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an unqualified error ocurrs during retrieval of data.		10000	✓	✓	✓	
download-error-other-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an unqualified error ocurrs during retrieval of data.		300000	✓	✓	✓	
download-error-other-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an unqualified error ocurrs during retrieval of data.		2	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
download-error-socket-exception-max-tries	Maximum number of tries when the network connection is forcible dropped during retrieval of data.		10	✓	✓	✓	
download-error-socket-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when the network connection is forcible dropped during retrieval of data.		10000	✓	✓	✓	
download-error-socket-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when the network connection is forcible dropped during retrieval of data.		300000	✓	✓	✓	
download-error-socket-exception-sleep-multiplicator	Multiplication factor for sleep between retries when the network connection is forcible dropped during retrieval of data.		2	✓	✓	✓	
download-error-web-exception-max-tries	Maximum number of tries when a web connection failure occurs during retrieval of data.		10	✓	✓	✓	
download-error-web-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		10000	✓	✓	✓	
download-error-web-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		300000	✓	✓	✓	
download-error-web-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a web connection failure occurs during retrieval of data.		2	✓	✓	✓	
download-error-web-not-found-max-tries	itgen_pae_download_error_web_not_found_max_tries		1	✓	✓	✓	
download-error-web-not-found-sleep-initial-ms	itgen_pae_download_error_web_not_found_sleep_initial_ms		10000	✓	✓	✓	
download-error-web-not-found-sleep-max-ms	itgen_pae_download_error_web_not_found_sleep_max_ms		300000	✓	✓	✓	
download-error-web-not-found-sleep-multiplicator	itgen_pae_download_error_web_not_found_sleep_multiplicator		2	✓	✓	✓	
download-error-web-not-implemented-max-tries	Maximum number of tries when the connection reports not implemented.		1	✓	✓	✓	
download-error-web-not-implemented-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports not implemented.		10000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
download-error-web-not-implemented-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports not implemented.		300000	✓	✓	✓	
download-error-web-not-implemented-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports not implemented.		2	✓	✓	✓	
download-error-web-timeout-max-tries	Maximum number of tries when the connection reports a timeout.		10	✓	✓	✓	
download-error-web-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports a timeout.		1000	✓	✓	✓	
download-error-web-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports a timeout.		30000	✓	✓	✓	
download-error-web-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports a timeout.		2	✓	✓	✓	
download-error-web-unauthorized-max-tries	Maximum number of tries when the connection reports an unauthorized error.		1	✓	✓	✓	
download-error-web-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports an unauthorized error.		10000	✓	✓	✓	
download-error-web-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports an unauthorized error.		300000	✓	✓	✓	
download-error-web-unauthorized-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports an unauthorized error.		2	✓	✓	✓	
duplicate-row-mode	Configure behaviour when multiple rows are discovered during a limited search based upon a fingerprint generated from the primary key value, or all column values when no primary key is known.. The following values can be used: "error" to raise error on duplicate fingerprint values in an API-page of rows, "keep" to ignore duplicate fingerprint values silently, "skip" like "keep" but with logging to trace of duplicate values or "null" for default behaviour (typically "error")..			✓	✓	✓	✓
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	Shared	False	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
forced-casing-identifiers	Forced casing of identifiers. Choose from: Unset, Lower, Upper and Mixed.	Shared		✓	✓	✓	
http-disk-cache-compression-level	Compression level for the HTTP disk cache, ranging from 1 (little) to 9 (intense). Default is 5.	Shared	5	✓	✓	✓	
http-disk-cache-directory	Directory where HTTP cache is stored.	Shared	C:\Users\guido\Invantive\Cache\http\guido\shared	✓	✓	✓	
http-disk-cache-ignore-write-errors	Whether to ignore write errors to disk cache.	Shared	False	✓	✓	✓	
http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP disk cache.	Shared	2592000	✓	✓	✓	
http-get-timeout-max-ms	HTTP GET maximum timeout on retry (ms).		24000	✓	✓	✓	
http-get-timeout-ms	HTTP GET timeout (ms).		298000	✓	✓	✓	
http-memory-cache-compression-level	Compression level for the HTTP memory cache, ranging from 1 (little) to 9 (intense). Default is 5.	OData	5	✓	✓	✓	
http-memory-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP memory cache.	OData	14400	✓	✓	✓	
http-post-timeout-max-ms	HTTP POST maximum timeout on retry (ms).		58000	✓	✓	✓	
http-post-timeout-ms	HTTP POST timeout (ms).		57000	✓	✓	✓	
ignore-http-400-errors	Ignore HTTP 400 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-http-401-errors	Ignore HTTP 401 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-http-402-errors	Ignore HTTP 402 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-http-403-errors	Ignore HTTP 403 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-http-404-errors	Ignore HTTP 404 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-http-422-errors	Ignore HTTP 422 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-http-429-errors	Ignore HTTP 429 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
ignore-http-500-errors	Ignore HTTP 500 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-http-502-errors	Ignore HTTP 502 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-http-503-errors	Ignore HTTP 503 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
ignore-unknown-path-type	Whether to ignore path types not yet supported. An error will be generated when an unsupported type occurs.		True	✓	✓	✓	✓
ignore-values-unknown-path	Whether to ignore values outside of processed paths. An error will be generated when a value occurs outside a path otherwise.		True	✓	✓	✓	✓
invalid-json-on-get-max-tries	Maximum number of tries when the JSON received on GET is invalid.		1	✓	✓	✓	
invalid-json-on-get-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on GET is invalid.		1000	✓	✓	✓	
invalid-json-on-get-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on GET is invalid.		10000	✓	✓	✓	
invalid-json-on-get-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on GET is invalid.		2	✓	✓	✓	
invalid-json-on-post-max-tries	Maximum number of tries when the JSON received on POST is invalid.		1	✓	✓	✓	
invalid-json-on-post-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on POST is invalid.		1000	✓	✓	✓	
invalid-json-on-post-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on POST is invalid.		10000	✓	✓	✓	
invalid-json-on-post-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on POST is invalid.		2	✓	✓	✓	
invantive-sql-compress-sparse-arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753.	SQL Engine V1	False	✓	✓	✓	
invantive-sql-execution-profile-disk-path	itgen_pae_invantive_sql_execution_profile_disk_path	SQL Engine V1	c:\temp\profiles	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
invantive-sql-execution-profile-to-disk	itgen_pae_invantive_sql_execution_profile_to_disk	SQL Engine V1	True	✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-shuffle-fetch-results-data-containers	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	✓	✓	✓	
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	✓	✓	✓	
join-set-points-per-request	Maximum number of values in a request when executing a join set.	OData	60	✓	✓	✓	
limit-partition-calls-left	Minimum number of remaining API calls on a partition towards a hard limit. When below, an error is raised.	OData	500	✓	✓	✓	
log-native-calls-to-disk-max-events	Maximum number of call events to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-max-seconds	Maximum number of seconds to register calls from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-on-error	Registers native calls to data container backend as disk files when the call raised an error.	Shared	False	✓	✓	✓	
log-native-calls-to-disk-on-success	Registers native calls to data container backend as disk files when the call raised no error.	Shared	False	✓	✓	✓	
log-native-calls-to-trace	Log native calls to data container backend on the trace.	Shared	False	✓	✓	✓	
max-odata-filters	Maximum number of OData filter elements.	OData	100	✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	Shared	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	Shared	8000	✓	✓	✓	
maximum-discovered-column-count	Maximum number of discovered columns. An error will be generated when the column exceeds this value.		250	✓	✓	✓	✓
maximum-length-identifiers	Non-default maximum length in characters of identifier names.	Shared		✓	✓	✓	
maximum-url-length	Maximum URL Length			✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
metadata-cache-max-age-sec	Maximum acceptable age in seconds for re-use of metadata.	OData		✓	✓	✓	
oauth-unauthorized-max-tries	Maximum number of tries when an OAuth exception occurs.	OData	2	✓	✓	✓	
oauth-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between OAuth reauthentication tries when the OAuth authentication fails.	OData	10000	✓	✓	✓	
oauth-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between OAuth reauthentication tries when the OAuth authentication fails.	OData	1000	✓	✓	✓	
oauth-unauthorized-sleep-multiplicator	Multiplication factor for sleep between OAuth reauthentication tries when the OAuth authentication fails.	OData	2	✓	✓	✓	
partition-slot-based-rate-limit-length-ms	Total length in milliseconds across all slots of a partition-based rate limit.	Shared	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit.	Shared		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	Shared	0	✓	✓	✓	
requested-page-size	Preferred number of rows to exchange per round trip; only effective on limited platforms such as AFAS Online.	Shared		✓	✓	✓	
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	Shared	32	✓	✓	✓	
simulate-http-400-errors-percentage	Percentage of simulated HTTP 400 errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	
simulate-http-400-errors	Simulate HTTP 400 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-401-errors-percentage	Percentage of simulated HTTP 401 errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	
simulate-http-401-errors	Simulate HTTP 401 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-403-errors-percentage	Percentage of simulated HTTP 403 errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	
simulate-http-403-errors	Simulate HTTP 403 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-408-errors-percentage	Percentage of simulated HTTP 408 errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
simulate-http-408-errors	Simulate HTTP 408 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-429-errors-percentage	Percentage of simulated HTTP 429 errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	
simulate-http-429-errors	Simulate HTTP 429 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-500-errors-percentage	Percentage of simulated HTTP 500 errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	
simulate-http-500-errors	Simulate HTTP 500 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-502-errors-percentage	Percentage of simulated HTTP 502 errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	
simulate-http-502-errors	Simulate HTTP 502 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-503-errors-percentage	Percentage of simulated HTTP 503 errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	
simulate-http-503-errors	Simulate HTTP 503 errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-504-errors-percentage	itgen_pae_simulate_http_504_errors_percentage		0	✓	✓	✓	
simulate-http-504-errors	itgen_pae_simulate_http_504_errors		False	✓	✓	✓	
simulate-http-522-errors-percentage	itgen_pae_simulate_http_522_errors_percentage		0	✓	✓	✓	
simulate-http-522-errors	itgen_pae_simulate_http_522_errors		False	✓	✓	✓	
simulate-http-524-errors-percentage	itgen_pae_simulate_http_524_errors_percentage		0	✓	✓	✓	
simulate-http-524-errors	itgen_pae_simulate_http_524_errors		False	✓	✓	✓	
simulate-http-protocol-errors-percentage	Percentage of simulated HTTP protocol errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	
simulate-http-protocol-errors	Simulate HTTP protocol errors when exchanging results with the HTTP endpoint.		False	✓	✓	✓	
simulate-http-timeout-errors-percentage	Percentage of simulated HTTP timeout errors when exchanging results with the HTTP endpoint.		0	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
simulate-http-timeout-errors	Simulate HTTP timeout errors when exchanging results with the HTTP endpoint..		False	✓	✓	✓	
slot-based-rate-limit-length-ms	Total length in milliseconds across all slots of a slot-based rate limit.	Shared	3600000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit.	Shared	10000	✓		✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	Shared	True	✓	✓	✓	
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	✓	✓	✓	
swagger-specification-download-tries	Specification Download Tries		5	✓	✓	✓	
swagger-specification-file	The Swagger file path, such as C:\temp\swagger.json.			✓	✓	✓	✓
swagger-specification-http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of Swagger specification data in the HTTP disk cache.		86400	✓	✓	✓	
swagger-specification-url	The Swagger URL such as https://example.org/rest/swagger.json.			✓	✓	✓	✓
use-batch-insert	Whether to use batch insert.	OData	True	✓	✓	✓	
use-http-disk-cache-read	Whether to use HTTP responses from previous queries stored on disk to answer the current query.	Shared	False	✓	✓	✓	
use-http-disk-cache-write	Whether to memorize HTTP responses on disk.	Shared	False	✓	✓	✓	
use-http-memory-cache-read	Whether to use HTTP responses from previous queries stored in memory that can answer the current query.	OData	True	✓	✓	✓	
use-http-memory-cache-write	Whether to memorize HTTP responses from previous queries for use by future queries.	OData	True	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

3 Schema: ActionTypes

3.1 Tables

3.1.1 ActionTypes

Catalog: Autotask

Schema: ActionTypes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ActionTypes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isSystemActionType	boolean	Is System Action Type	☐	
name	string	Name	☐	
view	int32	View	☐	

3.1.2 ActionTypesById

Catalog: Autotask

Schema: ActionTypes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ActionTypesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ActionTypesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isSystemActionType	boolean	Is System Action Type	☐	
name	string	Name	☐	
view	int32	View	☐	

3.1.3 ActionTypesCount

Catalog: Autotask

Schema: ActionTypes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ActionTypesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

4 Schema: AdditionalInvoiceFieldValues

4.1 Tables

4.1.1 AdditionalInvoiceFieldValues

Catalog: Autotask

Schema: AdditionalInvoiceFieldValues

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AdditionalInvoiceFieldValues are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalInvoiceFieldID	int64	Additional Invoice Field ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fieldValue	string	Field Value	☐	
id	int64	ID	☐	
invoiceBatchID	int64	Invoice Batch ID	☐	

4.1.2 AdditionalInvoiceFieldValuesById

Catalog: Autotask

Schema: AdditionalInvoiceFieldValues

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function AdditionalInvoiceFieldValuesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function AdditionalInvoiceFieldValuesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalInvoiceFieldID	int64	Additional Invoice Field ID	☐	
fieldValue	string	Field Value	☐	
id	int64	ID	☐	
invoiceBatchID	int64	Invoice Batch ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

4.1.3 AdditionalInvoiceFieldValuesCount

Catalog: Autotask

Schema: AdditionalInvoiceFieldValues

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AdditionalInvoiceFieldValuesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

5 Schema: ApiVersion

5.1 Tables

5.1.1 VersionInformation

Catalog: Autotask

Schema: ApiVersion

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table VersionInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
TEXT	string		☐	

6 Schema: Appointments

6.1 Tables

6.1.1 Appointments

Catalog: Autotask

Schema: Appointments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Appointments are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
startDateTime	datetime	Start Date/Time	☐	
title	string	Title	☐	
updateDateTime	datetime	Update Date/Time	☐	

6.1.2 AppointmentsById

Catalog: Autotask

Schema: Appointments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function AppointmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function AppointmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
startDateTime	datetime	Start Date/Time	☐	
title	string	Title	☐	
updateDateTime	datetime	Update Date/Time	☐	

6.1.3 AppointmentsCount

Catalog: Autotask

Schema: Appointments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AppointmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

7 Schema: ArticleAttachments

7.1 Tables

7.1.1 ArticleAttachments

Catalog: Autotask

Schema: ArticleAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

7.1.2 ArticleAttachmentsById

Catalog: Autotask

Schema: ArticleAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticleAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ArticleAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

7.1.3 ArticleAttachmentsCount

Catalog: Autotask

Schema: ArticleAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

8 Schema: ArticleAttachmentsChild

8.1 Tables

8.1.1 KnowledgeBaseArticlesByParentIdAttachments

Catalog: Autotask

Schema: ArticleAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

8.1.2 KnowledgeBaseArticlesByParentIdAttachmentsId

Catalog: Autotask

Schema: ArticleAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

9 Schema: ArticleConfigurationItemCategoryAssociations

9.1 Tables

9.1.1 ArticleConfigurationItemCategoryAssociations

Catalog: Autotask

Schema: ArticleConfigurationItemCategoryAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleConfigurationItemCategoryAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
id	int64	ID	☐	
installedProductCategoryID	int32	Installed Product Category ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

9.1.2 ArticleConfigurationItemCategoryAssociationsById

Catalog: Autotask

Schema: ArticleConfigurationItemCategoryAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticleConfigurationItemCategoryAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ArticleConfigurationItemCategoryAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
id	int64	ID	☐	
installedProductCategoryID	int32	Installed Product Category ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

9.1.3 ArticleConfigurationItemCategoryAssociationsCount

Catalog: Autotask

Schema: ArticleConfigurationItemCategoryAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleConfigurationItemCategoryAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

10 Schema: ArticleConfigurationItemCategoryAssociationsChild

10.1 Tables

10.1.1 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociations

Catalog: Autotask

Schema: ArticleConfigurationItemCategoryAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
id	int64	ID	☐	
installedProductCategoryID	int32	Installed Product Category ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

11 Schema: ArticleNotes

11.1 Tables

11.1.1 ArticleNotes

Catalog: Autotask

Schema: ArticleNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ArticleNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
description	string	Description	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

11.1.2 ArticleNotesById

Catalog: Autotask

Schema: ArticleNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticleNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ArticleNotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
description	string	Description	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

11.1.3 ArticleNotesCount

Catalog: Autotask

Schema: ArticleNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleNotesCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

12 Schema: ArticleNotesChild

12.1 Tables

12.1.1 KnowledgeBaseArticlesByParentIdNotes

Catalog: Autotask

Schema: ArticleNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
description	string	Description	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
lastModifiedDateTime	datetime	Last Modified	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

12.1.2 KnowledgeBaseArticlesByParentIdNotesId

Catalog: Autotask

Schema: ArticleNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function KnowledgeBaseArticlesByParentIdNotesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
description	string	Description	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

13 Schema: ArticlePlainTextContent

13.1 Tables

13.1.1 ArticlePlainTextContent

Catalog: Autotask

Schema: ArticlePlainTextContent

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticlePlainTextContent are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contentData	string	Content Data	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

13.1.2 ArticlePlainTextContentById

Catalog: Autotask

Schema: ArticlePlainTextContent

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticlePlainTextContentById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ArticlePlainTextContentById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contentData	string	Content Data	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

13.1.3 ArticlePlainTextContentCount

Catalog: Autotask

Schema: ArticlePlainTextContent

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticlePlainTextContentCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

14 Schema: ArticlePlainTextContentChild

14.1 Tables

14.1.1 KnowledgeBaseArticlesByParentIdPlainTextContent

Catalog: Autotask

Schema: ArticlePlainTextContentChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdPlainTextContent. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdPlainTextContent are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contentData	string	Content Data	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

14.1.2 KnowledgeBaseArticlesByParentIdPlainTextContentId

Catalog: Autotask

Schema: ArticlePlainTextContentChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdPlainTextContentId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdPlainTextContentId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contentData	string	Content Data	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

15 Schema: ArticleTagAssociations

15.1 Tables

15.1.1 ArticleTagAssociations

Catalog: Autotask

Schema: ArticleTagAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ArticleTagAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

15.1.2 ArticleTagAssociationsById

Catalog: Autotask

Schema: ArticleTagAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticleTagAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ArticleTagAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

15.1.3 ArticleTagAssociationsCount

Catalog: Autotask

Schema: ArticleTagAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTagAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

16 Schema: ArticleTagAssociationsChild

16.1 Tables

16.1.1 KnowledgeBaseArticlesByParentIdTagAssociations

Catalog: Autotask

Schema: ArticleTagAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTagAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTagAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

16.1.2 KnowledgeBaseArticlesByParentIdTagAssociationsId

Catalog: Autotask

Schema: ArticleTagAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTagAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTagAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

17 Schema: ArticleTicketAssociations

17.1 Tables

17.1.1 ArticleTicketAssociations

Catalog: Autotask

Schema: ArticleTicketAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTicketAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

17.1.2 ArticleTicketAssociationsById

Catalog: Autotask

Schema: ArticleTicketAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticleTicketAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ArticleTicketAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

17.1.3 ArticleTicketAssociationsCount

Catalog: Autotask

Schema: ArticleTicketAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTicketAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

18 Schema: ArticleTicketAssociationsChild

18.1 Tables

18.1.1 KnowledgeBaseArticlesByParentIdTicketAssociations

Catalog: Autotask

Schema: ArticleTicketAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTicketAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function KnowledgeBaseArticlesByParentIdTicketAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

18.1.2 KnowledgeBaseArticlesByParentIdTicketAssociationsId

Catalog: Autotask

Schema: ArticleTicketAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

19 Schema: ArticleToArticleAssociations

19.1 Tables

19.1.1 ArticleToArticleAssociations

Catalog: Autotask

Schema: ArticleToArticleAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToArticleAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
associatedArticleID	int32	Associated Article ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

19.1.2 ArticleToArticleAssociationsById

Catalog: Autotask

Schema: ArticleToArticleAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticleToArticleAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ArticleToArticleAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
associatedArticleID	int32	Associated Article ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

19.1.3 ArticleToArticleAssociationsCount

Catalog: Autotask

Schema: ArticleToArticleAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToArticleAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

20 Schema: ArticleToArticleAssociationsChild

20.1 Tables

20.1.1 KnowledgeBaseArticlesByParentIdArticleAssociations

Catalog: Autotask

Schema: ArticleToArticleAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdArticleAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdArticleAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
associatedArticleID	int32	Associated Article ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

20.1.2 KnowledgeBaseArticlesByParentIdArticleAssociationsId

Catalog: Autotask

Schema: ArticleToArticleAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
associatedArticleID	int32	Associated Article ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

21 Schema: ArticleToDocumentAssociations

21.1 Tables

21.1.1 ArticleToDocumentAssociations

Catalog: Autotask

Schema: ArticleToDocumentAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ArticleToDocumentAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
associatedDocumentID	int32	Associated Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

21.1.2 ArticleToDocumentAssociationsById

Catalog: Autotask

Schema: ArticleToDocumentAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticleToDocumentAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ArticleToDocumentAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
associatedDocumentID	int32	Associated Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

21.1.3 ArticleToDocumentAssociationsCount

Catalog: Autotask

Schema: ArticleToDocumentAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToDocumentAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

22 Schema: ArticleToDocumentAssociationsChild

22.1 Tables

22.1.1 KnowledgeBaseArticlesByParentIdDocumentAssociations

Catalog: Autotask

Schema: ArticleToDocumentAssociationsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdDocumentAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdDocumentAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
associatedDocumentID	int32	Associated Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

22.1.2 KnowledgeBaseArticlesByParentIdDocumentAssociationsId

Catalog: Autotask

Schema: ArticleToDocumentAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
associatedDocumentID	int32	Associated Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

23 Schema: AttachmentInfo

23.1 Tables

23.1.1 AttachmentInfo

Catalog: Autotask

Schema: AttachmentInfo

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AttachmentInfo are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
contractID	int32	Contract ID	☐	
contractNoteID	int32	Contract Note ID	☐	
creatorType	int32	Creator Type	☐	
documentID	int32	Document ID	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
opportunityID	int64	Opportunity ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
resourceID	int32	Resource ID	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

23.1.2 AttachmentInfoById

Catalog: Autotask

Schema: AttachmentInfo

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function AttachmentInfoById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function AttachmentInfoById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleID	int32	Article ID	☐	
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
contractID	int32	Contract ID	☐	
contractNoteID	int32	Contract Note ID	☐	
creatorType	int32	Creator Type	☐	
documentID	int32	Document ID	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
resourceID	int32	Resource ID	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

23.1.3 AttachmentInfoCount

Catalog: Autotask

Schema: AttachmentInfo

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AttachmentInfoCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

24 Schema: AutotaskVersionApiIntegration

24.1 Tables

24.1.1 Version

Catalog: Autotask

Schema: AutotaskVersionApiIntegration

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Version are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
build	string	Build	☐	
majorVersion	string	Major Version	☐	
minorVersion	string	Minor Version	☐	

25 Schema: BillingCodes

25.1 Tables

25.1.1 BillingCodes

Catalog: Autotask

Schema: BillingCodes

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
afterHoursWorkType	int32	After Hours Work Type	☐	
billingCodeType	int32	Billing Code Type	☐	
department	int32	Department	☐	
description	string	Description	☐	
externalNumber	string	External Number	☐	
generalLedgerAccount	int32	General Ledger Account	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isExcludedFromNew Contracts	boolean	Is Excluded from New Contracts	☐	
markupRate	double	Mark-up Rate	☐	
name	string	Name	☐	
taxCategoryID	int32	Tax Category ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
useType	int32	Use Type	☐	

25.1.2 BillingCodesById

Catalog: Autotask

Schema: BillingCodes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function BillingCodesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function BillingCodesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
afterHoursWorkType	int32	After Hours Work Type	☐	
billingCodeType	int32	Billing Code Type	☐	
department	int32	Department	☐	
description	string	Description	☐	
externalNumber	string	External Number	☐	
generalLedgerAccount	int32	General Ledger Account	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isExcludedFromNew Contracts	boolean	Is Excluded from New Contracts	☐	
markupRate	double	Mark-up Rate	☐	
name	string	Name	☐	
taxCategoryID	int32	Tax Category ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
useType	int32	Use Type	☐	

25.1.3 BillingCodesCount

Catalog: Autotask

Schema: BillingCodes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingCodesCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

26 Schema: BillingItemApprovalLevels

26.1 Tables

26.1.1 BillingItemApprovalLevels

Catalog: Autotask

Schema: BillingItemApprovalLevels

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemApprovalLevels are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approvalDateTime	datetime	Approval Date/Time	☐	
approvalLevel	int32	Approval Level	☐	
approvalResourceID	int32	Approval Resource ID	☐	
id	int64	ID	☐	
timeEntryID	int32	Time Entry ID	☐	

26.1.2 BillingItemApprovalLevelsById

Catalog: Autotask

Schema: BillingItemApprovalLevels

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function BillingItemApprovalLevelsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function BillingItemApprovalLevelsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approvalDateTime	datetime	Approval Date/Time	☐	
approvalLevel	int32	Approval Level	☐	
approvalResourceID	int32	Approval Resource ID	☐	
id	int64	ID	☐	
timeEntryID	int32	Time Entry ID	☐	

26.1.3 BillingItemApprovalLevelsCount

Catalog: Autotask

Schema: BillingItemApprovalLevels

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemApprovalLevelsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

27 Schema: BillingItems

27.1 Tables

27.1.1 BillingItems

Catalog: Autotask

Schema: BillingItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItems are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
accountManagerWhenApprovedID	int32	Account Manager When Approved ID	☐	
billingCodeID	int32	Billing Code ID	☐	
billingItemType	int32	Billing Item Type	☐	
companyID	int32	Company ID	☐	
configurationItemID	int64	Configuration Item ID	☐	
contractChargeID	int64	Contract Charge ID	☐	
contractID	int32	Contract ID	☐	
contractServiceAdjustmentID	int32	Contract Service Adjustment ID	☐	
contractServiceBundleAdjustmentID	int32	Contract Service Bundle Adjustment ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
contractServiceBundlePeriodID	int32	Contract Service Bundle Period ID	☐	
contractServiceID	int32	Contract Service ID	☐	
contractServicePeriodID	int32	Contract Service Period ID	☐	
description	string	Description	☐	
expenseItemID	int32	Expense Item ID	☐	
extendedPrice	double	Extended Price	☐	
id	int64	ID	☐	
internalCurrencyExtendedPrice	double	Internal Currency Extended Price	☐	
internalCurrencyRate	double	Internal Currency Rate	☐	
internalCurrencyTaxDollars	double	Internal Currency Tax Dollars	☐	
internalCurrencyTotalAmount	double	Internal Currency Total Amount	☐	
invoiceID	int32	Invoice ID	☐	
itemApproverID	int32	Item Approver ID	☐	
itemDate	datetime	Item Date	☐	
itemName	string	Item Name	☐	
lineItemFullDescription	string	Line Item Full Description	☐	
lineItemGroupDescription	string	Line Item Group Description	☐	
milestoneID	int64	Milestone ID	☐	
nonBillable	int32	Non-billable	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ourCost	double	Our Cost	☐	
postedDate	datetime	Posted	☐	
postedOnTime	datetime	Posted on-time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
projectChargeID	int64	Project Charge ID	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
quantity	double	Quantity	☐	
rate	double	Rate	☐	
roleID	int32	Role ID	☐	
serviceBundleID	int64	Service Bundle ID	☐	
serviceID	int64	Service ID	☐	
sortOrderID	int64	Sort Order ID	☐	
subType	int32	Sub-type	☐	
taskID	int32	Task ID	☐	
taxDollars	double	Tax Dollars	☐	
ticketChargeID	int64	Ticket Charge ID	☐	
ticketID	int32	Ticket ID	☐	
timeEntryID	int32	Time Entry ID	☐	
totalAmount	double	Total Amount	☐	
vendorID	int64	Vendor ID	☐	
w ebServiceDate	datetime	Webservice Date	☐	

27.1.2 BillingItemsById

Catalog: Autotask

Schema: BillingItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function BillingItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function BillingItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountManagerWhenApprovedID	int32	Account Manager When Approved ID	☐	
billingCodeID	int32	Billing Code ID	☐	
billingItemType	int32	Billing Item Type	☐	
companyID	int32	Company ID	☐	
configurationItemID	int64	Configuration Item ID	☐	
contractChargeID	int64	Contract Charge ID	☐	
contractID	int32	Contract ID	☐	
contractServiceAdjustmentID	int32	Contract Service Adjustment ID	☐	
contractServiceBundleAdjustmentID	int32	Contract Service Bundle Adjustment ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
contractServiceBundlePeriodID	int32	Contract Service Bundle Period ID	☐	
contractServiceID	int32	Contract Service ID	☐	
contractServicePeriodID	int32	Contract Service Period ID	☐	
description	string	Description	☐	
expenseItemID	int32	Expense Item ID	☐	
extendedPrice	double	Extended Price	☐	
id	int64	ID	☐	
internalCurrencyExtendedPrice	double	Internal Currency Extended Price	☐	
internalCurrencyRate	double	Internal Currency Rate	☐	
internalCurrencyTaxDollars	double	Internal Currency Tax Dollars	☐	
internalCurrencyTotalAmount	double	Internal Currency Total Amount	☐	
invoiceID	int32	Invoice ID	☐	
itemApproverID	int32	Item Approver ID	☐	
itemDate	datetime	Item Date	☐	
itemName	string	Item Name	☐	
lineItemFullDescription	string	Line Item Full Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
lineItemGroupDescription	string	Line Item Group Description	☐	
milestoneID	int64	Milestone ID	☐	
nonBillable	int32	Non-billable	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ourCost	double	Our Cost	☐	
postedDate	datetime	Posted	☐	
postedOnTime	datetime	Posted on-time	☐	
projectChargeID	int64	Project Charge ID	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
quantity	double	Quantity	☐	
rate	double	Rate	☐	
roleID	int32	Role ID	☐	
serviceBundleID	int64	Service Bundle ID	☐	
serviceID	int64	Service ID	☐	
sortOrderID	int64	Sort Order ID	☐	
subType	int32	Sub-type	☐	
taskID	int32	Task ID	☐	
taxDollars	double	Tax Dollars	☐	
ticketChargeID	int64	Ticket Charge ID	☐	
ticketID	int32	Ticket ID	☐	
timeEntryID	int32	Time Entry ID	☐	
totalAmount	double	Total Amount	☐	
vendorID	int64	Vendor ID	☐	
w ebServiceDate	datetime	Webservice Date	☐	

27.1.3 BillingItemsCount

Catalog: Autotask

Schema: BillingItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

28 Schema: ChangeOrderCharges

28.1 Tables

28.1.1 ChangeOrderCharges

Catalog: Autotask

Schema: ChangeOrderCharges

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeOrderCharges are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int32	Billing Code ID	☐	
changeOrderHours	double	Change Order Hours	☐	
chargeType	int32	Charge Type	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
contractServiceID	int32	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int32	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
status	int32	Status	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
statusLastModifiedBy	int32	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
taskID	int32	Task ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

28.1.2 ChangeOrderChargesById

Catalog: Autotask

Schema: ChangeOrderCharges

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChangeOrderChargesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ChangeOrderChargesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int32	Billing Code ID	☐	
changeOrderHours	double	Change Order Hours	☐	
chargeType	int32	Charge Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
contractServiceID	int32	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int32	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
status	int32	Status	☐	
statusLastModifiedBy	int32	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
taskID	int32	Task ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

28.1.3 ChangeOrderChargesCount

Catalog: Autotask

Schema: ChangeOrderCharges

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ChangeOrderChargesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

29 Schema: ChangeRequestLinks

29.1 Tables

29.1.1 ChangeRequestLinks

Catalog: Autotask

Schema: ChangeRequestLinks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeRequestLinks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
changeRequestTicketID	int32	Change Request Ticket ID	☐	
id	int64	ID	☐	
problemOrIncidentTicketID	int32	Project or Incident Ticket ID	☐	

29.1.2 ChangeRequestLinksById

Catalog: Autotask

Schema: ChangeRequestLinks

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChangeRequestLinksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ChangeRequestLinksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
changeRequestTicketID	int32	Change Request Ticket ID	☐	
id	int64	ID	☐	
problemOrIncidentTicketID	int32	Project or Incident Ticket ID	☐	

29.1.3 ChangeRequestLinksCount

Catalog: Autotask

Schema: ChangeRequestLinks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeRequestLinksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

30 Schema: ChecklistLibraries

30.1 Tables

30.1.1 ChecklistLibraries

Catalog: Autotask

Schema: ChecklistLibraries

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ChecklistLibraries are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
entityType	int32	Entity Type	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

30.1.2 ChecklistLibrariesById

Catalog: Autotask

Schema: ChecklistLibraries

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibrariesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ChecklistLibrariesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
entityType	int32	Entity Type	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	

30.1.3 ChecklistLibrariesCount

Catalog: Autotask

Schema: ChecklistLibraries

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibrariesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

31 Schema: ChecklistLibraryChecklistItems

31.1 Tables

31.1.1 ChecklistLibraryChecklistItems

Catalog: Autotask

Schema: ChecklistLibraryChecklistItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibraryChecklistItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
checklistLibraryID	int32	Checklist Library ID	☐	
id	int64	ID	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
knowledgebaseArticleID	int32	Knowledgebase Article ID	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

31.1.2 ChecklistLibraryChecklistItemsById

Catalog: Autotask

Schema: ChecklistLibraryChecklistItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibraryChecklistItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ChecklistLibraryChecklistItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
checklistLibraryID	int32	Checklist Library ID	☐	
id	int64	ID	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
knowledgebaseArticleID	int32	Knowledgebase Article ID	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

31.1.3 ChecklistLibraryChecklistItemsCount

Catalog: Autotask

Schema: ChecklistLibraryChecklistItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibraryChecklistItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

32 Schema: ChecklistLibraryChecklistItemsChild

32.1 Tables

32.1.1 ChecklistLibrariesByParentIdChecklistItems

Catalog: Autotask

Schema: ChecklistLibraryChecklistItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibrariesByParentIdChecklistItems. A value must be provided at all times for

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ChecklistLibrariesByParentIdChecklistItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
checklistLibraryID	int32	Checklist Library ID	☐	
id	int64	ID	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
knowledgebaseArticleID	int32	Knowledgebase Article ID	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

32.1.2 ChecklistLibrariesByParentIdChecklistItemsId

Catalog: Autotask

Schema: ChecklistLibraryChecklistItemsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibrariesByParentIdChecklistItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ChecklistLibrariesByParentIdChecklistItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
checklistLibraryID	int32	Checklist Library ID	☐	
id	int64	ID	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
knowledgebaseArticleID	int32	Knowledgebase Article ID	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	

33 Schema: ClassificationIcons

33.1 Tables

33.1.1 ClassificationIcons

Catalog: Autotask

Schema: ClassificationIcons

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClassificationIcons are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isSystem	boolean	Is System	☐	
name	string	Name	☐	
relativeUrl	string	Relative URL	☐	

33.1.2 ClassificationIconsById

Catalog: Autotask

Schema: ClassificationIcons

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ClassificationIconsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ClassificationIconsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isSystem	boolean	Is System	☐	
name	string	Name	☐	
relativeUrl	string	Relative URL	☐	

33.1.3 ClassificationIconsCount

Catalog: Autotask

Schema: ClassificationIcons

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClassificationIconsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

34 Schema: ClientPortalUsers

34.1 Tables

34.1.1 ClientPortalUsers

Catalog: Autotask

Schema: ClientPortalUsers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ClientPortalUsers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactID	int32	Contact ID	☐	
dateFormat	int32	Date Format	☐	
id	int64	ID	☐	
isClientPortalActive	boolean	Is Client Portal Active	☐	
numberFormat	int32	Number Format	☐	
password	string	Password	☐	
securityLevel	int32	Security Level	☐	
timeFormat	int32	Time Format	☐	
userName	string	User Name	☐	

34.1.2 ClientPortalUsersById

Catalog: Autotask

Schema: ClientPortalUsers

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ClientPortalUsersById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ClientPortalUsersById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contactID	int32	Contact ID	☐	
dateFormat	int32	Date Format	☐	
id	int64	ID	☐	
isClientPortalActive	boolean	Is Client Portal Active	☐	
numberFormat	int32	Number Format	☐	
password	string	Password	☐	
securityLevel	int32	Security Level	☐	
timeFormat	int32	Time Format	☐	
userName	string	User Name	☐	

34.1.3 ClientPortalUsersCount

Catalog: Autotask

Schema: ClientPortalUsers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClientPortalUsersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

35 Schema: ComanagedAssociations

35.1 Tables

35.1.1 ComanagedAssociations

Catalog: Autotask

Schema: ComanagedAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ComanagedAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPrimaryComanagedResource	boolean	Is Primary Co-managed Resource	☐	
resourceID	int32	Resource ID	☐	

35.1.2 ComanagedAssociationsById

Catalog: Autotask

Schema: ComanagedAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ComanagedAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ComanagedAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
id	int64	ID	☐	
isPrimaryComanagedResource	boolean	Is Primary Co-managed Resource	☐	
resourceID	int32	Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

35.1.3 ComanagedAssociationsCount

Catalog: Autotask

Schema: ComanagedAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ComanagedAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

36 Schema: Companies

36.1 Tables

36.1.1 Companies

Catalog: Autotask

Schema: Companies

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Companies are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
address1	string	Address 1	☐	
address2	string	Address 2	☐	
alternatePhone1	string	Alternate Phone 1	☐	
alternatePhone2	string	Alternate Phone 2	☐	
apiVendorID	int32	API Vendor ID	☐	
assetValue	double	Asset Value	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToAdditionalAddressInformation	string	Bill-to Additional Address Information	☐	
billToAddressToUse	int32	Bill-to Address to Use	☐	
billToAttention	string	Bill-to Attention	☐	
billToCity	string	Bill-to City	☐	
billToCompanyLocationID	int32	Bill-to Company Location ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
billToCountryID	int32	Bill-to Country ID	☐	
billToState	string	Bill-to State	☐	
billToZipCode	string	Bill-to ZIP Code	☐	
city	string	City	☐	
classification	int32	Classification	☐	
companyCategoryID	int32	Company Category ID	☐	
companyName	string	Company Name	☐	
companyNumber	string	Company Number	☐	
companyType	int32	Company Type	☐	
competitorID	int32	Competitor ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
currencyID	int32	Currency ID	☐	
fax	string	Fax	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
invoiceEmailMessageID	int32	Invoice Email Message ID	☐	
invoiceMethod	int32	Invoice Method	☐	
invoiceNonContractItemsToParentCompany	boolean	Invoice Non-contract Items to Parent Company	☐	
invoiceTemplateID	int32	Invoice Template ID	☐	
isActive	boolean	Is Active	☐	
isClientPortalActive	boolean	Is Client Portal Active	☐	
isEnabledForComanaged	boolean	Is Enabled for Co-managed	☐	
isSample	boolean	Is Sample	☐	
isTaskFireActive	boolean	Is Task Fire Active	☐	
isTaxExempt	boolean	Is Tax Exempt	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastTrackedModifiedDateTime	datetime	Last Tracked Modified Date/Time	☐	
marketSegmentID	int32	Market Segment ID	☐	
ownerResourceID	int32	Owner Resource ID	☐	
parentCompanyID	int32	Parent Company ID	☐	
phone	string	Phone	☐	
postalCode	string	Postal Code	☐	
purchaseOrderTemplateID	int32	Purchase Order Template ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
quoteEmailMessageID	int32	Quote Email Message ID	☐	
quoteTemplateID	int32	Quote Template ID	☐	
sicCode	string	SIC Code	☐	
state	string	State	☐	
stockMarket	string	Stock Market	☐	
stockSymbol	string	Stock Symbol	☐	
surveyCompanyRating	double	Survey Company Rating	☐	
taxID	string	Tax ID	☐	
taxRegionID	int32	Tax Region ID	☐	
territoryID	int32	Territory ID	☐	
w ebAddress	string	Web Address	☐	

36.1.2 Companies_ItemsUserDefinedFields

Catalog: Autotask

Schema: Companies

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Companies_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
address1	string	Address 1	☐	
address2	string	Address 2	☐	
alternatePhone1	string	Alternate Phone 1	☐	
alternatePhone2	string	Alternate Phone 2	☐	
apiVendorID	int32	API Vendor ID	☐	
assetValue	double	Asset Value	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToAdditionalAddressInformation	string	Bill-to Additional Address Information	☐	
billToAddressToUse	int32	Bill-to Address to Use	☐	
billToAttention	string	Bill-to Attention	☐	
billToCity	string	Bill-to City	☐	
billToCompanyLocationID	int32	Bill-to Company Location ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
billToCountryID	int32	Bill-to Country ID	☐	
billToState	string	Bill-to State	☐	
billToZipCode	string	Bill-to ZIP Code	☐	
city	string	City	☐	
classification	int32	Classification	☐	
companyCategoryID	int32	Company Category ID	☐	
companyName	string	Company Name	☐	
companyNumber	string	Company Number	☐	
companyType	int32	Company Type	☐	
competitorID	int32	Competitor ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
currencyID	int32	Currency ID	☐	
fax	string	Fax	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
invoiceEmailMessageID	int32	Invoice Email Message ID	☐	
invoiceMethod	int32	Invoice Method	☐	
invoiceNonContractItemsToParentCompany	boolean	Invoice Non-contract Items to Parent Company	☐	
invoiceTemplateID	int32	Invoice Template ID	☐	
isActive	boolean	Is Active	☐	
isClientPortalActive	boolean	Is Client Portal Active	☐	
isEnabledForComanaged	boolean	Is Enabled for Co-managed	☐	
isSample	boolean	Is Sample	☐	
isTaskFireActive	boolean	Is Task Fire Active	☐	
isTaxExempt	boolean	Is Tax Exempt	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastTrackedModifiedDateTime	datetime	Last Tracked Modified Date/Time	☐	
marketSegmentID	int32	Market Segment ID	☐	
name	string	Name	☐	
ownerResourceID	int32	Owner Resource ID	☐	
parentCompanyID	int32	Parent Company ID	☐	
phone	string	Phone	☐	
postalCode	string	Postal Code	☐	
purchaseOrderTemplateID	int32	Purchase Order Template ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
quoteEmailMessageID	int32	Quote Email Message ID	☐	
quoteTemplateID	int32	Quote Template ID	☐	
sicCode	string	SIC Code	☐	
state	string	State	☐	
stockMarket	string	Stock Market	☐	
stockSymbol	string	Stock Symbol	☐	
surveyCompanyRating	double	Survey Company Rating	☐	
taxID	string	Tax ID	☐	
taxRegionID	int32	Tax Region ID	☐	
territoryID	int32	Territory ID	☐	
value	string	Value	☐	
w ebAddress	string	Web Address	☐	

36.1.3 CompaniesById

Catalog: Autotask

Schema: Companies

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function CompaniesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
address1	string	Address 1	☐	
address2	string	Address 2	☐	
alternatePhone1	string	Alternate Phone 1	☐	
alternatePhone2	string	Alternate Phone 2	☐	
apiVendorID	int32	API Vendor ID	☐	
assetValue	double	Asset Value	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToAdditionalAddressInformation	string	Bill-to Additional Address Information	☐	
billToAddressToUse	int32	Bill-to Address to Use	☐	
billToAttention	string	Bill-to Attention	☐	
billToCity	string	Bill-to City	☐	
billToCompanyLocationID	int32	Bill-to Company Location ID	☐	
billToCountryID	int32	Bill-to Country ID	☐	
billToState	string	Bill-to State	☐	
billToZipCode	string	Bill-to ZIP Code	☐	
city	string	City	☐	
classification	int32	Classification	☐	
companyCategoryID	int32	Company Category ID	☐	
companyName	string	Company Name	☐	
companyNumber	string	Company Number	☐	
companyType	int32	Company Type	☐	
competitorID	int32	Competitor ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
currencyID	int32	Currency ID	☐	
fax	string	Fax	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
invoiceEmailMessageID	int32	Invoice Email Message ID	☐	
invoiceMethod	int32	Invoice Method	☐	
invoiceNonContractItemsToParentCompany	boolean	Invoice Non-contract Items to Parent Company	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
invoiceTemplateID	int32	Invoice Template ID	☐	
isActive	boolean	Is Active	☐	
isClientPortalActive	boolean	Is Client Portal Active	☐	
isEnabledForComanaged	boolean	Is Enabled for Co-managed	☐	
isSample	boolean	Is Sample	☐	
isTaskFireActive	boolean	Is Task Fire Active	☐	
isTaxExempt	boolean	Is Tax Exempt	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastTrackedModifiedDateTime	datetime	Last Tracked Modified Date/Time	☐	
marketSegmentID	int32	Market Segment ID	☐	
ownerResourceID	int32	Owner Resource ID	☐	
parentCompanyID	int32	Parent Company ID	☐	
phone	string	Phone	☐	
postalCode	string	Postal Code	☐	
purchaseOrderTemplateID	int32	Purchase Order Template ID	☐	
quoteEmailMessageID	int32	Quote Email Message ID	☐	
quoteTemplateID	int32	Quote Template ID	☐	
sicCode	string	SIC Code	☐	
state	string	State	☐	
stockMarket	string	Stock Market	☐	
stockSymbol	string	Stock Symbol	☐	
surveyCompanyRating	double	Survey Company Rating	☐	
taxID	string	Tax ID	☐	
taxRegionID	int32	Tax Region ID	☐	
territoryID	int32	Territory ID	☐	
webAddress	string	Web Address	☐	

36.1.4 CompaniesCount

Catalog: Autotask

Schema: Companies

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompaniesCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

37 Schema: CompanyAlerts

37.1 Tables

37.1.1 CompanyAlerts

Catalog: Autotask

Schema: CompanyAlerts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAlerts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
alertText	string	Alert Text	☐	
alertTypeID	int32	Alert Type ID	☐	
companyID	int32	Company ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

37.1.2 CompanyAlertsById

Catalog: Autotask

Schema: CompanyAlerts

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function CompanyAlertsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyAlertsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
alertText	string	Alert Text	☐	
alertTypeID	int32	Alert Type ID	☐	
companyID	int32	Company ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

37.1.3 CompanyAlertsCount

Catalog: Autotask

Schema: CompanyAlerts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table CompanyAlertsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

38 Schema: CompanyAlertsChild

38.1 Tables

38.1.1 CompaniesByParentIdAlerts

Catalog: Autotask

Schema: CompanyAlertsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAlerts. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdAlerts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
alertText	string	Alert Text	☐	
alertTypeID	int32	Alert Type ID	☐	
companyID	int32	Company ID	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

38.1.2 CompaniesByParentIdAlertsId

Catalog: Autotask

Schema: CompanyAlertsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAlertsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdAlertsId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
alertText	string	Alert Text	☐	
alertTypeID	int32	Alert Type ID	☐	
companyID	int32	Company ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

39 Schema: CompanyAttachments

39.1 Tables

39.1.1 CompanyAttachments

Catalog: Autotask

Schema: CompanyAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

39.1.2 CompanyAttachmentsById

Catalog: Autotask

Schema: CompanyAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

39.1.3 CompanyAttachmentsCount

Catalog: Autotask

Schema: CompanyAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

40 Schema: CompanyAttachmentsChild

40.1 Tables

40.1.1 CompaniesByParentIdAttachments

Catalog: Autotask

Schema: CompanyAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

40.1.2 CompaniesByParentIdAttachmentsId

Catalog: Autotask

Schema: CompanyAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

41 Schema: CompanyCategories

41.1 Tables

41.1.1 CompanyCategories

Catalog: Autotask

Schema: CompanyCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyCategories are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
displayColorRGB	int32	Display Color RGB	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isApiOnly	boolean	Is API Only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isGlobalDefault	boolean	Is Global Default	☐	
name	string	Name	☐	
nickname	string	Nickname	☐	

41.1.2 CompanyCategoriesById

Catalog: Autotask

Schema: CompanyCategories

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyCategoriesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyCategoriesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
displayColorRGB	int32	Display Color RGB	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isApiOnly	boolean	Is API Only	☐	
isGlobalDefault	boolean	Is Global Default	☐	
name	string	Name	☐	
nickname	string	Nickname	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

41.1.3 CompanyCategoriesCount

Catalog: Autotask

Schema: CompanyCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyCategoriesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

42 Schema: CompanyContactsChild

42.1 Tables

42.1.1 CompaniesByParentId_ItemsUserDefinedFieldsContacts

Catalog: Autotask

Schema: CompanyContactsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentId_ItemsUserDefinedFieldsContacts. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function CompaniesByParentId_ItemsUserDefinedFieldsContacts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
addressLine	string	Address Line	☐	
addressLine1	string	Address Line 1	☐	
alternatePhone	string	Alternate Phone	☐	
apiVendorID	int32	API Vendor ID	☐	
bulkEmailOptOutTime	datetime	Bulk Email Opt-out Time	☐	
city	string	City	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
emailAddress	string	Email Address	☐	
emailAddress2	string	Email Address 2	☐	
emailAddress3	string	Email Address 3	☐	
extension	string	Extension	☐	
externalID	string	External ID	☐	
facebookUrl	string	Facebook URL	☐	
faxNumber	string	Fax Number	☐	
firstName	string	First Name	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	int32	Is Active	☐	
isOptedOutFromBulkEmail	boolean	Is Opted Out from Bulk Email	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastModifiedDate	datetime	Last Modified	☐	
lastName	string	Last Name	☐	
linkedInUrl	string	LinkedIn URL	☐	
middleInitial	string	Middle Initial	☐	
mobilePhone	string	Mobile Phone	☐	
name	string	Name	☐	
namePrefix	int32	Name Prefix	☐	
nameSuffix	int32	Name Suffix	☐	
note	string	Note	☐	
phone	string	Phone	☐	
primaryContact	boolean	Primary Contact	☐	
receivesEmailNotifications	boolean	Receives Email Notification	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
roomNumber	string	Room Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
solicitationOptOut	boolean	Sollicitation Opt-out	☐	
solicitationOptOutTime	datetime	Sollicitation Opt-out Time	☐	
state	string	State	☐	
surveyOptOut	boolean	Survey Opt-out	☐	
title	string	Title	☐	
twitterUrl	string	Twitter URL	☐	
value	string	Value	☐	
zipCode	string	ZIP Code	☐	

42.1.2 CompaniesByParentIdContacts

Catalog: Autotask

Schema: CompanyContactsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdContacts. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdContacts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
addressLine	string	Address Line	☐	
addressLine1	string	Address Line 1	☐	
alternatePhone	string	Alternate Phone	☐	
apiVendorID	int32	API Vendor ID	☐	
bulkEmailOptOutTime	datetime	Bulk Email Opt-out Time	☐	
city	string	City	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
emailAddress	string	Email Address	☐	
emailAddress2	string	Email Address 2	☐	
emailAddress3	string	Email Address 3	☐	
extension	string	Extension	☐	
externalID	string	External ID	☐	
facebookUrl	string	Facebook URL	☐	
faxNumber	string	Fax Number	☐	
firstName	string	First Name	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	int32	Is Active	☐	
isOptedOutFromBulkEmail	boolean	Is Opted Out from Bulk Email	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastModifiedDate	datetime	Last Modified	☐	
lastName	string	Last Name	☐	
linkedInUrl	string	LinkedIn URL	☐	
middleInitial	string	Middle Initial	☐	
mobilePhone	string	Mobile Phone	☐	
namePrefix	int32	Name Prefix	☐	
nameSuffix	int32	Name Suffix	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
note	string	Note	☐	
phone	string	Phone	☐	
primaryContact	boolean	Primary Contact	☐	
receivesEmailNotifications	boolean	Receives Email Notification	☐	
roomNumber	string	Room Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
solicitationOptOut	boolean	Sollicitation Opt-out	☐	
solicitationOptOutTime	datetime	Sollicitation Opt-out Time	☐	
state	string	State	☐	
surveyOptOut	boolean	Survey Opt-out	☐	
title	string	Title	☐	
twitterUrl	string	Twitter URL	☐	
zipCode	string	ZIP Code	☐	

42.1.3 CompaniesByParentIdContactsId

Catalog: Autotask

Schema: CompanyContactsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdContactsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdContactsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
addressLine	string	Address Line	☐	
addressLine1	string	Address Line 1	☐	
alternatePhone	string	Alternate Phone	☐	
apiVendorID	int32	API Vendor ID	☐	
bulkEmailOptOutTime	datetime	Bulk Email Opt-out Time	☐	
city	string	City	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
emailAddress	string	Email Address	☐	
emailAddress2	string	Email Address 2	☐	
emailAddress3	string	Email Address 3	☐	
extension	string	Extension	☐	
externalID	string	External ID	☐	
facebookUrl	string	Facebook URL	☐	
faxNumber	string	Fax Number	☐	
firstName	string	First Name	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	int32	Is Active	☐	
isOptedOutFromBulkEmail	boolean	Is Opted Out from Bulk Email	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastModifiedDate	datetime	Last Modified	☐	
lastName	string	Last Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
linkedInUrl	string	LinkedIn URL	☐	
middleInitial	string	Middle Initial	☐	
mobilePhone	string	Mobile Phone	☐	
namePrefix	int32	Name Prefix	☐	
nameSuffix	int32	Name Suffix	☐	
note	string	Note	☐	
phone	string	Phone	☐	
primaryContact	boolean	Primary Contact	☐	
receivesEmailNotifications	boolean	Receives Email Notification	☐	
roomNumber	string	Room Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
solicitationOptOut	boolean	Sollicitation Opt-out	☐	
solicitationOptOutTime	datetime	Sollicitation Opt-out Time	☐	
state	string	State	☐	
surveyOptOut	boolean	Survey Opt-out	☐	
title	string	Title	☐	
twitterUrl	string	Twitter URL	☐	
zipCode	string	ZIP Code	☐	

43 Schema: CompanyLocations

43.1 Tables

43.1.1 CompanyLocations

Catalog: Autotask

Schema: CompanyLocations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table CompanyLocations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
address1	string	Address 1	☐	
address2	string	Address 2	☐	
alternatePhone1	string	Alternate Phone 1	☐	
alternatePhone2	string	Alternate Phone 2	☐	
city	string	City	☐	
companyID	int32	Company ID	☐	
countryID	int32	Country ID	☐	
description	string	Description	☐	
fax	string	Fax	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isPrimary	boolean	Is Primary	☐	
isTaxExempt	boolean	Is Tax Exempt	☐	
name	string	Name	☐	
overrideCompanyTaxSettings	boolean	Override Company Tax Settings	☐	
phone	string	Phone	☐	
postalCode	string	Postal Code	☐	
roundtripDistance	double	Roundtrip Distance	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
state	string	State	☐	
taxRegionID	int32	Tax Region ID	☐	

43.1.2 CompanyLocationsById

Catalog: Autotask

Schema: CompanyLocations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyLocationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyLocationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
address1	string	Address 1	☐	
address2	string	Address 2	☐	
alternatePhone1	string	Alternate Phone 1	☐	
alternatePhone2	string	Alternate Phone 2	☐	
city	string	City	☐	
companyID	int32	Company ID	☐	
countryID	int32	Country ID	☐	
description	string	Description	☐	
fax	string	Fax	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isPrimary	boolean	Is Primary	☐	
isTaxExempt	boolean	Is Tax Exempt	☐	
name	string	Name	☐	
overrideCompanyTaxSettings	boolean	Override Company Tax Settings	☐	
phone	string	Phone	☐	
postalCode	string	Postal Code	☐	
roundtripDistance	double	Roundtrip Distance	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
state	string	State	☐	
taxRegionID	int32	Tax Region ID	☐	

43.1.3 CompanyLocationsCount

Catalog: Autotask

Schema: CompanyLocations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyLocationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

44 Schema: CompanyLocationsChild

44.1 Tables

44.1.1 CompaniesByParentIdLocations

Catalog: Autotask

Schema: CompanyLocationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdLocations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdLocations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
address1	string	Address 1	☐	
address2	string	Address 2	☐	
alternatePhone1	string	Alternate Phone 1	☐	
alternatePhone2	string	Alternate Phone 2	☐	
city	string	City	☐	
companyID	int32	Company ID	☐	
countryID	int32	Country ID	☐	
description	string	Description	☐	
fax	string	Fax	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isPrimary	boolean	Is Primary	☐	
isTaxExempt	boolean	Is Tax Exempt	☐	
name	string	Name	☐	
overrideCompanyTaxSettings	boolean	Override Company Tax Settings	☐	
phone	string	Phone	☐	
postalCode	string	Postal Code	☐	
roundtripDistance	double	Roundtrip Distance	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
state	string	State	☐	
taxRegionID	int32	Tax Region ID	☐	

44.1.2 CompaniesByParentIdLocationsId

Catalog: Autotask

Schema: CompanyLocationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdLocationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdLocationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
address1	string	Address 1	☐	
address2	string	Address 2	☐	
alternatePhone1	string	Alternate Phone 1	☐	
alternatePhone2	string	Alternate Phone 2	☐	
city	string	City	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
countryID	int32	Country ID	☐	
description	string	Description	☐	
fax	string	Fax	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isPrimary	boolean	Is Primary	☐	
isTaxExempt	boolean	Is Tax Exempt	☐	
name	string	Name	☐	
overrideCompanyTaxSettings	boolean	Override Company Tax Settings	☐	
phone	string	Phone	☐	
postalCode	string	Postal Code	☐	
roundtripDistance	double	Roundtrip Distance	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
state	string	State	☐	
taxRegionID	int32	Tax Region ID	☐	

45 Schema: CompanyNoteAttachments

45.1 Tables

45.1.1 CompanyNoteAttachments

Catalog: Autotask

Schema: CompanyNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNoteAttachments are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

45.1.2 CompanyNoteAttachmentsById

Catalog: Autotask

Schema: CompanyNoteAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyNoteAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyNoteAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

45.1.3 CompanyNoteAttachmentsCount

Catalog: Autotask

Schema: CompanyNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNoteAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

46 Schema: CompanyNoteAttachmentsChild

46.1 Tables

46.1.1 CompanyNotesByParentIdAttachments

Catalog: Autotask

Schema: CompanyNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyNotesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompanyNotesByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

46.1.2 CompanyNotesByParentIdAttachmentsId

Catalog: Autotask

Schema: CompanyNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyNotesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompanyNotesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
companyID	int32	Company ID	☐	
companyNoteID	int32	Company Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

47 Schema: CompanyNotes

47.1 Tables

47.1.1 CompanyNotes

Catalog: Autotask

Schema: CompanyNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table CompanyNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actionType	int32	Action Type	☐	
assignedResourceID	int32	Assigned Resource ID	☐	
companyID	int32	Company ID	☐	
completedDateTime	datetime	Completed	☐	
contactID	int32	Contact ID	☐	
createDateTime	datetime	Created	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastModifiedDate	datetime	Last Modified	☐	
name	string	Name	☐	
note	string	Note	☐	
opportunityID	int32	Opportunity ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	

47.1.2 CompanyNotesById

Catalog: Autotask

Schema: CompanyNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function CompanyNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyNotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actionType	int32	Action Type	☐	
assignedResourceID	int32	Assigned Resource ID	☐	
companyID	int32	Company ID	☐	
completedDateTime	datetime	Completed	☐	
contactID	int32	Contact ID	☐	
createDateTime	datetime	Created	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastModifiedDate	datetime	Last Modified	☐	
name	string	Name	☐	
note	string	Note	☐	
opportunityID	int32	Opportunity ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	

47.1.3 CompanyNotesCount

Catalog: Autotask

Schema: CompanyNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

48 Schema: CompanyNotesChild

48.1 Tables

48.1.1 CompaniesByParentIdNotes

Catalog: Autotask

Schema: CompanyNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actionType	int32	Action Type	☐	
assignedResourceID	int32	Assigned Resource ID	☐	
companyID	int32	Company ID	☐	
completedDateTime	datetime	Completed	☐	
contactID	int32	Contact ID	☐	
createDateTime	datetime	Created	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastModifiedDate	datetime	Last Modified	☐	
name	string	Name	☐	
note	string	Note	☐	
opportunityID	int32	Opportunity ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	

48.1.2 CompaniesByParentIdNotesId

Catalog: Autotask

Schema: CompanyNotesChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdNotesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actionType	int32	Action Type	☐	
assignedResourceID	int32	Assigned Resource ID	☐	
companyID	int32	Company ID	☐	
completedDateTime	datetime	Completed	☐	
contactID	int32	Contact ID	☐	
createDateTime	datetime	Created	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastModifiedDate	datetime	Last Modified	☐	
name	string	Name	☐	
note	string	Note	☐	
opportunityID	int32	Opportunity ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	

49 Schema: CompanySiteConfigurations

49.1 Tables

49.1.1 CompanySiteConfigurations

Catalog: Autotask

Schema: CompanySiteConfigurations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanySiteConfigurations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
id	int64	ID	☐	
locationName	string	Location Name	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

49.1.2 CompanySiteConfigurations_ItemsUserDefinedFields

Catalog: Autotask

Schema: CompanySiteConfigurations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanySiteConfigurations_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
id	int64	ID	☐	
locationName	string	Location Name	☐	
name	string	Name	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
value	string	Value	☐	

49.1.3 CompanySiteConfigurationsById

Catalog: Autotask

Schema: CompanySiteConfigurations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanySiteConfigurationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanySiteConfigurationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
id	int64	ID	☐	
locationName	string	Location Name	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

49.1.4 CompanySiteConfigurationsCount

Catalog: Autotask

Schema: CompanySiteConfigurations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanySiteConfigurationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

50 Schema: CompanySiteConfigurationsChild

50.1 Tables

50.1.1 CompaniesByParentId_ItemsUserDefinedFieldsSiteConfigurations

Catalog: Autotask

Schema: CompanySiteConfigurationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentId_ItemsUserDefinedFieldsSiteConfigurations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentId_ItemsUserDefinedFieldsSiteConfigurations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
id	int64	ID	☐	
locationName	string	Location Name	☐	
name	string	Name	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
value	string	Value	☐	

50.1.2 CompaniesByParentIdSiteConfigurations

Catalog: Autotask

Schema: CompanySiteConfigurationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdSiteConfigurations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdSiteConfigurations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
id	int64	ID	☐	
locationName	string	Location Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

50.1.3 CompaniesByParentIdSiteConfigurationsId

Catalog: Autotask

Schema: CompanySiteConfigurationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdSiteConfigurationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdSiteConfigurationsId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
id	int64	ID	☐	
locationName	string	Location Name	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

51 Schema: CompanyTeams

51.1 Tables

51.1.1 CompanyTeams

Catalog: Autotask

Schema: CompanyTeams

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyTeams are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int64	Company ID	☐	
id	int64	ID	☐	
isAssociatedAsComanaged	boolean	Is Associated as Co-managed	☐	
resourceID	int64	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

51.1.2 CompanyTeamsById

Catalog: Autotask

Schema: CompanyTeams

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyTeamsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyTeamsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int64	Company ID	☐	
id	int64	ID	☐	
isAssociatedAsComanaged	boolean	Is Associated as Co-managed	☐	
resourceID	int64	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

51.1.3 CompanyTeamsCount

Catalog: Autotask

Schema: CompanyTeams

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyTeamsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

52 Schema: CompanyTeamsChild

52.1 Tables

52.1.1 CompaniesByParentIdTeams

Catalog: Autotask

Schema: CompanyTeamsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdTeams. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdTeams are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int64	Company ID	☐	
id	int64	ID	☐	
isAssociatedAsComanaged	boolean	Is Associated as Co-managed	☐	
resourceID	int64	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

52.1.2 CompaniesByParentIdTeamsId

Catalog: Autotask

Schema: CompanyTeamsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdTeamsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdTeamsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int64	Company ID	☐	
id	int64	ID	☐	
isAssociatedAsComanaged	boolean	Is Associated as Co-managed	☐	
resourceID	int64	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

53 Schema: CompanyToDos

53.1 Tables

53.1.1 CompanyToDos

Catalog: Autotask

Schema: CompanyToDos

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table CompanyToDos are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actionType	int32	Action Type	☐	
activityDescription	string	Activity Description	☐	
assignedToResourceID	int64	Assigned to Resource ID	☐	
companyID	int64	Company ID	☐	
completedDate	datetime	Completion Date	☐	
contactID	int64	Contact ID	☐	
contractID	int64	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
lastModifiedDate	datetime	Last Modified	☐	
opportunityID	int64	Opportunity ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
ticketID	int64	Ticket ID	☐	

53.1.2 CompanyToDosById

Catalog: Autotask

Schema: CompanyToDos

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function CompanyToDosById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyToDosById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actionType	int32	Action Type	☐	
activityDescription	string	Activity Description	☐	
assignedToResourceID	int64	Assigned to Resource ID	☐	
companyID	int64	Company ID	☐	
completedDate	datetime	Completion Date	☐	
contactID	int64	Contact ID	☐	
contractID	int64	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
lastModifiedDate	datetime	Last Modified	☐	
opportunityID	int64	Opportunity ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
ticketID	int64	Ticket ID	☐	

53.1.3 CompanyToDosCount

Catalog: Autotask

Schema: CompanyToDos

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyToDosCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

54 Schema: CompanyToDosChild

54.1 Tables

54.1.1 CompaniesByParentIdToDos

Catalog: Autotask

Schema: CompanyToDosChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdToDos. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdToDos are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actionType	int32	Action Type	☐	
activityDescription	string	Activity Description	☐	
assignedToResourceID	int64	Assigned to Resource ID	☐	
companyID	int64	Company ID	☐	
completedDate	datetime	Completion Date	☐	
contactID	int64	Contact ID	☐	
contractID	int64	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
lastModifiedDate	datetime	Last Modified	☐	
opportunityID	int64	Opportunity ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
ticketID	int64	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

54.1.2 CompaniesByParentIdToDosId

Catalog: Autotask

Schema: CompanyToDosChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdToDosId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdToDosId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actionType	int32	Action Type	☐	
activityDescription	string	Activity Description	☐	
assignedToResourceID	int64	Assigned to Resource ID	☐	
companyID	int64	Company ID	☐	
completedDate	datetime	Completion Date	☐	
contactID	int64	Contact ID	☐	
contractID	int64	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
lastModifiedDate	datetime	Last Modified	☐	
opportunityID	int64	Opportunity ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
ticketID	int64	Ticket ID	☐	

55 Schema: CompanyWebhookExcludedResources

55.1 Tables

55.1.1 CompanyWebhookExcludedResources

Catalog: Autotask

Schema: CompanyWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
w ebhookID	int32	Webhook ID	☐	

55.1.2 CompanyWebhookExcludedResourcesById

Catalog: Autotask

Schema: CompanyWebhookExcludedResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhookExcludedResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhookExcludedResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

55.1.3 CompanyWebhookExcludedResourcesCount

Catalog: Autotask

Schema: CompanyWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookExcludedResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

56 Schema: CompanyWebhookExcludedResourcesChild

56.1 Tables

56.1.1 CompanyWebhooksByParentIdExcludedResources

Catalog: Autotask

Schema: CompanyWebhookExcludedResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdExcludedResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

56.1.2 CompanyWebhooksByParentIdExcludedResourcesId

Catalog: Autotask

Schema: CompanyWebhookExcludedResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdExcludedResourcesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdExcludedResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

57 Schema: CompanyWebhookFields

57.1 Tables

57.1.1 CompanyWebhookFields

Catalog: Autotask

Schema: CompanyWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

57.1.2 CompanyWebhookFieldsById

Catalog: Autotask

Schema: CompanyWebhookFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhookFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function CompanyWebhookFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

57.1.3 CompanyWebhookFieldsCount

Catalog: Autotask

Schema: CompanyWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

58 Schema: CompanyWebhookFieldsChild

58.1 Tables

58.1.1 CompanyWebhooksByParentIdFields

Catalog: Autotask

Schema: CompanyWebhookFieldsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

58.1.2 CompanyWebhooksByParentIdFieldsId

Catalog: Autotask

Schema: CompanyWebhookFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

59 Schema: CompanyWebhooks

59.1 Tables

59.1.1 CompanyWebhooks

Catalog: Autotask

Schema: CompanyWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhooks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

59.1.2 CompanyWebhooksById

Catalog: Autotask

Schema: CompanyWebhooks

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

59.1.3 CompanyWebhooksCount

Catalog: Autotask

Schema: CompanyWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhooksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

60 Schema: CompanyWebhookUdfFields

60.1 Tables

60.1.1 CompanyWebhookUdfFields

Catalog: Autotask

Schema: CompanyWebhookUdfFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookUdfFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

60.1.2 CompanyWebhookUdfFieldsById

Catalog: Autotask

Schema: CompanyWebhookUdfFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhookUdfFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhookUdfFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

60.1.3 CompanyWebhookUdfFieldsCount

Catalog: Autotask

Schema: CompanyWebhookUdfFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookUdfFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

61 Schema: CompanyWebhookUdfFieldsChild

61.1 Tables

61.1.1 CompanyWebhooksByParentIdUdfFields

Catalog: Autotask

Schema: CompanyWebhookUdfFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdUdfFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdUdfFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

61.1.2 CompanyWebhooksByParentIdUdfFieldsId

Catalog: Autotask

Schema: CompanyWebhookUdfFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdUdfFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdUdfFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

62 Schema: ConfigurationItemAttachments

62.1 Tables

62.1.1 ConfigurationItemAttachments

Catalog: Autotask

Schema: ConfigurationItemAttachments

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

62.1.2 ConfigurationItemAttachmentsById

Catalog: Autotask

Schema: ConfigurationItemAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

62.1.3 ConfigurationItemAttachmentsCount

Catalog: Autotask

Schema: ConfigurationItemAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

63 Schema: ConfigurationItemAttachmentsChild

63.1 Tables

63.1.1 ConfigurationItemsByParentIdAttachments

Catalog: Autotask

Schema: ConfigurationItemAttachmentsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

63.1.2 ConfigurationItemsByParentIdAttachmentsId

Catalog: Autotask

Schema: ConfigurationItemAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

64 Schema: ConfigurationItemBillingProductAssociations

64.1 Tables

64.1.1 ConfigurationItemBillingProductAssociations

Catalog: Autotask

Schema: ConfigurationItemBillingProductAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemBillingProductAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingProductID	int32	Billing Product ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

64.1.2 ConfigurationItemBillingProductAssociationsById

Catalog: Autotask

Schema: ConfigurationItemBillingProductAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemBillingProductAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemBillingProductAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingProductID	int32	Billing Product ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

64.1.3 ConfigurationItemBillingProductAssociationsCount

Catalog: Autotask

Schema: ConfigurationItemBillingProductAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ConfigurationItemBillingProductAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

65 Schema: ConfigurationItemBillingProductAssociationsChild

65.1 Tables

65.1.1 ConfigurationItemsByParentIdBillingProductAssociations

Catalog: Autotask

Schema: ConfigurationItemBillingProductAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdBillingProductAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdBillingProductAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingProductID	int32	Billing Product ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

66 Schema: ConfigurationItemCategories

66.1 Tables

66.1.1 ConfigurationItemCategories

Catalog: Autotask

Schema: ConfigurationItemCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategories are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
displayColorRGB	int32	Display Color RGB	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isClientPortalDefault	boolean	Is Client Portal Default	☐	
isGlobalDefault	boolean	Is Global Default	☐	
name	string	Name	☐	
nickname	string	Nickname	☐	

66.1.2 ConfigurationItemCategoriesById

Catalog: Autotask

Schema: ConfigurationItemCategories

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemCategoriesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemCategoriesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
displayColorRGB	int32	Display Color RGB	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isClientPortalDefault	boolean	Is Client Portal Default	☐	
isGlobalDefault	boolean	Is Global Default	☐	
name	string	Name	☐	
nickname	string	Nickname	☐	

66.1.3 ConfigurationItemCategoriesCount

Catalog: Autotask

Schema: ConfigurationItemCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoriesCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

67 Schema: ConfigurationItemCategoryUdfAssociations

67.1 Tables

67.1.1 ConfigurationItemCategoryUdfAssociations

Catalog: Autotask

Schema: ConfigurationItemCategoryUdfAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoryUdfAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemCategoryID	int32	Configuration Item Category ID	☐	
id	int64	ID	☐	
isRequired	boolean	Is Required	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
userDefinedFieldDefinitionID	int32	User-defined Field Definition ID	☐	

67.1.2 ConfigurationItemCategoryUdfAssociationsById

Catalog: Autotask

Schema: ConfigurationItemCategoryUdfAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ConfigurationItemCategoryUdfAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemCategoryUdfAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemCategoryID	int32	Configuration Item Category ID	☐	
id	int64	ID	☐	
isRequired	boolean	Is Required	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
userDefinedFieldDefinitionID	int32	User-defined Field Definition ID	☐	

67.1.3 ConfigurationItemCategoryUdfAssociationsCount

Catalog: Autotask

Schema: ConfigurationItemCategoryUdfAssociations

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoryUdfAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

68 Schema: ConfigurationItemCategoryUdfAssociationsChild

68.1 Tables

68.1.1 ConfigurationItemCategoriesByParentIdUdfAssociations

Catalog: Autotask

Schema: ConfigurationItemCategoryUdfAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemCategoriesByParentIdUdfAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemCategoriesByParentIdUdfAssociations are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
configurationItemCategoryID	int32	Configuration Item Category ID	☐	
id	int64	ID	☐	
isRequired	boolean	Is Required	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
userDefinedFieldDefinitionID	int32	User-defined Field Definition ID	☐	

69 Schema: ConfigurationItemDnsRecords

69.1 Tables

69.1.1 ConfigurationItemDnsRecords

Catalog: Autotask

Schema: ConfigurationItemDnsRecords

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemDnsRecords are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
data	string	Data	☐	
dnsType	string	DNS Type	☐	
id	int64	ID	☐	
installedProductID	int32	Installed Product ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
timeToLiveSeconds	int32	Time-to-live Seconds	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

69.1.2 ConfigurationItemDnsRecordsById

Catalog: Autotask

Schema: ConfigurationItemDnsRecords

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemDnsRecordsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemDnsRecordsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
data	string	Data	☐	
dnsType	string	DNS Type	☐	
id	int64	ID	☐	
installedProductID	int32	Installed Product ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
timeToLiveSeconds	int32	Time-to-live Seconds	☐	

69.1.3 ConfigurationItemDnsRecordsCount

Catalog: Autotask

Schema: ConfigurationItemDnsRecords

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemDnsRecordsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

70 Schema: ConfigurationItemDnsRecordsChild

70.1 Tables

70.1.1 ConfigurationItemsByParentIdDnsRecords

Catalog: Autotask

Schema: ConfigurationItemDnsRecordsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdDnsRecords. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdDnsRecords are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
data	string	Data	☐	
dnsType	string	DNS Type	☐	
id	int64	ID	☐	
installedProductID	int32	Installed Product ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
timeToLiveSeconds	int32	Time-to-live Seconds	☐	

70.1.2 ConfigurationItemsByParentIdDnsRecordsId

Catalog: Autotask

Schema: ConfigurationItemDnsRecordsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdDnsRecordsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdDnsRecordsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
data	string	Data	☐	
dnsType	string	DNS Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
installedProductID	int32	Installed Product ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
timeToLiveSeconds	int32	Time-to-live Seconds	☐	

71 Schema: ConfigurationItemNoteAttachments

71.1 Tables

71.1.1 ConfigurationItemNoteAttachments

Catalog: Autotask

Schema: ConfigurationItemNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNoteAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

71.1.2 ConfigurationItemNoteAttachmentsById

Catalog: Autotask

Schema: ConfigurationItemNoteAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemNoteAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemNoteAttachmentsById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

71.1.3 ConfigurationItemNoteAttachmentsCount

Catalog: Autotask

Schema: ConfigurationItemNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemNoteAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

72 Schema: ConfigurationItemNoteAttachmentsChild

72.1 Tables

72.1.1 ConfigurationItemNotesByParentIdAttachments

Catalog: Autotask

Schema: ConfigurationItemNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemNotesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemNotesByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachmentType	string	Attachment Type	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

72.1.2 ConfigurationItemNotesByParentIdAttachmentsId

Catalog: Autotask

Schema: ConfigurationItemNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemNotesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemNotesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
configurationItemID	int32	Configuration Item ID	☐	
configurationItemNoteID	int32	Configuration Item Note ID	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

73 Schema: ConfigurationItemNotes

73.1 Tables

73.1.1 ConfigurationItemNotes

Catalog: Autotask

Schema: ConfigurationItemNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

73.1.2 ConfigurationItemNotesById

Catalog: Autotask

Schema: ConfigurationItemNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemNotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

73.1.3 ConfigurationItemNotesCount

Catalog: Autotask

Schema: ConfigurationItemNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

74 Schema: ConfigurationItemNotesChild

74.1 Tables

74.1.1 ConfigurationItemsByParentIdNotes

Catalog: Autotask

Schema: ConfigurationItemNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
title	string	Title	☐	

74.1.2 ConfigurationItemsByParentIdNotesId

Catalog: Autotask

Schema: ConfigurationItemNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdNotesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
noteType	int32	Note Type	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

75 Schema: ConfigurationItemRelatedItems

75.1 Tables

75.1.1 ConfigurationItemRelatedItems

Catalog: Autotask

Schema: ConfigurationItemRelatedItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemRelatedItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
relatedConfigurationItemID	int32	Related Configuration Item ID	☐	
relationship	int32	Relationship	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

75.1.2 ConfigurationItemRelatedItemsById

Catalog: Autotask

Schema: ConfigurationItemRelatedItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemRelatedItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemRelatedItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
relatedConfigurationItemID	int32	Related Configuration Item ID	☐	
relationship	int32	Relationship	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

75.1.3 ConfigurationItemRelatedItemsCount

Catalog: Autotask

Schema: ConfigurationItemRelatedItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemRelatedItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

76 Schema: ConfigurationItemRelatedItemsChild

76.1 Tables

76.1.1 ConfigurationItemsByParentIdRelatedItems

Catalog: Autotask

Schema: ConfigurationItemRelatedItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdRelatedItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdRelatedItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
relatedConfigurationItemID	int32	Related Configuration Item ID	☐	
relationship	int32	Relationship	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

76.1.2 ConfigurationItemsByParentIdRelatedItemsId

Catalog: Autotask

Schema: ConfigurationItemRelatedItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdRelatedItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdRelatedItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
relatedConfigurationItemID	int32	Related Configuration Item ID	☐	
relationship	int32	Relationship	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

77 Schema: ConfigurationItems

77.1 Tables

77.1.1 ConfigurationItems

Catalog: Autotask

Schema: ConfigurationItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
apiVendorID	int32	API Vendor ID	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
configurationItemCategoryID	int32	Configuration Item Category ID	☐	
configurationItemType	int32	Configuration Item Type	☐	
contactID	int32	Contact ID	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
contractServiceID	int32	Contract Service ID	☐	
createDate	datetime	Created	☐	
createdByPersonID	int32	Created by Person ID	☐	
dailyCost	double	Daily Cost	☐	
dattoAvailableKilobytes	int64	Available Kilobytes	☐	
dattoDeviceMemoryMegabytes	int32	Device Memory Megabytes	☐	
dattoDrivesErrors	boolean	Drives Errors	☐	
dattoHostname	string	Hostname	☐	
dattoInternalIP	string	Internal IP	☐	
dattoKernelVersionID	int32	Kernel Version ID	☐	
dattoLastCheckInDateTime	datetime	Last Check-in Date/Time	☐	
dattoNICSpeedKilobitsPerSecond	int32	Speed Kilobits per Second	☐	
dattoNumberOfAgents	int32	Number of Agents	☐	
dattoNumberOfDrives	int32	Number of Drives	☐	
dattoNumberOfVolumes	int32	Number of Volumes	☐	
dattoOffsiteUsedBytes	int64	Off-site Used Bytes	☐	
dattoOSVersionID	int32	OS Version ID	☐	
dattoPercentageUsed	double	Percentage Used	☐	
dattoProtectedKilobytes	int64	Protected Kilobytes	☐	
dattoRemoteIP	string	Remote IP	☐	
dattoSerialNumber	string	Serial Number	☐	
dattoUptimeSeconds	int32	Up-time (seconds)	☐	
dattoUsedKilobytes	int64	Used (Kilobytes)	☐	
dattoZFSVersionID	int32	OZFS Version ID	☐	
deviceNetworkingID	string	Device Networking ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
domain	string	Domain	☐	
domainExpirationDateTime	datetime	Domain Expiration Date/Time	☐	
domainLastUpdatedDateTime	datetime	Domain Last Updated Date/Time	☐	
domainRegistrarID	int32	Domain Registrar ID	☐	
domainRegistrationDateTime	datetime	Domain Registration Date/Time	☐	
hourlyCost	double	Hourly Cost	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
installDate	datetime	Install Date	☐	
installedByContactID	int32	Installed by Contact ID	☐	
installedByID	int32	Installed by ID	☐	
isActive	boolean	Is Active	☐	
lastActivityPersonID	int32	Last Activity Person ID	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastModifiedTime	datetime	Last Modified Time	☐	
location	string	Location	☐	
monthlyCost	double	Monthly Cost	☐	
notes	string	Notes	☐	
numberOfUsers	double	Number of Users	☐	
parentConfigurationItemID	int32	Parent Configuration Item ID	☐	
perUseCost	double	Per Use Cost	☐	
productID	int32	Product ID	☐	
referenceNumber	string	Reference Number	☐	
referenceTitle	string	Reference Title	☐	
rmmDeviceAuditAntivirusStatusID	int32	Device Audit Anti-virus Status ID	☐	
rmmDeviceAuditArchitectureID	int32	Device Audit Architecture ID	☐	
rmmDeviceAuditBackupStatusID	int32	Device Audit Backup Status ID	☐	
rmmDeviceAuditDescription	string	Device Audit Description	☐	
rmmDeviceAuditDeviceTypeID	int32	Device Audit Device Type ID	☐	
rmmDeviceAuditDisplayAdaptorID	int32	Device Audit Display Adaptor ID	☐	
rmmDeviceAuditDomainID	int32	Device Audit Domain ID	☐	
rmmDeviceAuditExternalIPAddress	string	Device Audit External IP Address	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
rmmDeviceAuditHostname	string	Device Audit Hostname	☐	
rmmDeviceAuditIPAddress	string	Devuce Audit IP-address	☐	
rmmDeviceAuditLastUser	string	Device Audit Last User	☐	
rmmDeviceAuditMacAddress	string	Device Audit MAC Address	☐	
rmmDeviceAuditManufacturerID	int32	Device Audit Manufacturer ID	☐	
rmmDeviceAuditMemoryBytes	int64	Device Audit Memory Bytes	☐	
rmmDeviceAuditMissingPatchCount	int32	Device Audit Missing Patch Count	☐	
rmmDeviceAuditMobileNetw orkOperatorID	int32	Device Audit Mobile Netw ork Operator ID	☐	
rmmDeviceAuditMobileNumber	string	Device Audit Mobile Number	☐	
rmmDeviceAuditModelID	int32	Device Audit Model ID	☐	
rmmDeviceAuditMotherboardID	int32	Device Audit Motherboard ID	☐	
rmmDeviceAuditOperatingSystem	string	Device Audit Operating System	☐	
rmmDeviceAuditPatchStatusID	int32	Device Audit Patch Status ID	☐	
rmmDeviceAuditProcessorID	int32	Device Audit Processor ID	☐	
rmmDeviceAuditServicePackID	int32	Device Audit Service Pack ID	☐	
rmmDeviceAuditSNMPContact	string	Device Audit SNMP Contact	☐	
rmmDeviceAuditSNMPLocation	string	Device Audit SNMP Location	☐	
rmmDeviceAuditSNMPName	string	Device Audit SNMP Name	☐	
rmmDeviceAuditSoftw areStatusID	int32	Device Audit Softw are Status ID	☐	
rmmDeviceAuditStorageBytes	int64	Device Audit Storage Bytes	☐	
rmmDeviceID	int64	Device ID	☐	
rmmDeviceUID	string	Device UID	☐	
rmmOpenAlertCount	int32	Open Alert Count	☐	
serialNumber	string	Serial Number	☐	
serviceBundleID	int32	Service Bundle ID	☐	
serviceID	int32	Service ID	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
setupFee	double	Setup Fee	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sourceChargeID	int32	Source Charge ID	☐	
sourceChargeType	int32	Source Charge Type	☐	
sslCommonName	string	SSL Common Name	☐	
sslIssuedBy	string	SSL Issued by	☐	
sslLocation	string	SSL Location	☐	
sslOrganization	string	SSL Organization	☐	
sslOrganizationUnit	string	SSL Organization Unit	☐	
sslSerialNumber	string	SSL Serial Number	☐	
sslSignatureAlgorithm	string	SSL Signature Algorithm	☐	
sslSource	string	SSL Source	☐	
sslValidFromDateTime	datetime	SSL Valid from Date/Time	☐	
sslValidUntilDateTime	datetime	SSL Valid until Date/Time	☐	
vendorID	int32	Vendor ID	☐	
warrantyExpirationDate	datetime	Warranty Expiration Date	☐	

77.1.2 ConfigurationItems_ItemsUserDefinedFields

Catalog: Autotask

Schema: ConfigurationItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItems_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
apiVendorID	int32	API Vendor ID	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
configurationItemCategoryID	int32	Configuration Item Category ID	☐	
configurationItemType	int32	Configuration Item Type	☐	
contactID	int32	Contact ID	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
contractServiceID	int32	Contract Service ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
createdByPersonID	int32	Created by Person ID	☐	
dailyCost	double	Daily Cost	☐	
dattoAvailableKilobytes	int64	Available Kilobytes	☐	
dattoDeviceMemoryMegabytes	int32	Device Memory Megabytes	☐	
dattoDrivesErrors	boolean	Drives Errors	☐	
dattoHostname	string	Hostname	☐	
dattoInternalIP	string	Internal IP	☐	
dattoKernelVersionID	int32	Kernel Version ID	☐	
dattoLastCheckInDateTime	datetime	Last Check-in Date/Time	☐	
dattoNICSpeedKilobitsPerSecond	int32	Speed Kilobits per Second	☐	
dattoNumberOfAgents	int32	Number of Agents	☐	
dattoNumberOfDrives	int32	Number of Drives	☐	
dattoNumberOfVolumes	int32	Number of Volumes	☐	
dattoOffsiteUsedBytes	int64	Off-site Used Bytes	☐	
dattoOSVersionID	int32	OS Version ID	☐	
dattoPercentageUsed	double	Percentage Used	☐	
dattoProtectedKilobytes	int64	Protected Kilobytes	☐	
dattoRemoteIP	string	Remote IP	☐	
dattoSerialNumber	string	Serial Number	☐	
dattoUptimeSeconds	int32	Up-time (seconds)	☐	
dattoUsedKilobytes	int64	Used (Kilobytes)	☐	
dattoZFSVersionID	int32	OZFS Version ID	☐	
deviceNetworkingID	string	Device Networking ID	☐	
domain	string	Domain	☐	
domainExpirationDateTime	datetime	Domain Expiration Date/Time	☐	
domainLastUpdatedDateTime	datetime	Domain Last Updated Date/Time	☐	
domainRegistrarID	int32	Domain Registrar ID	☐	
domainRegistrationDateTime	datetime	Domain Registration Date/Time	☐	
hourlyCost	double	Hourly Cost	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
installDate	datetime	Install Date	☐	
installedByContactID	int32	Installed by Contact ID	☐	
installedByID	int32	Installed by ID	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
lastActivityPersonID	int32	Last Activity Person ID	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastModifiedTime	datetime	Last Modified Time	☐	
location	string	Location	☐	
monthlyCost	double	Monthly Cost	☐	
name	string	Name	☐	
notes	string	Notes	☐	
numberOfUsers	double	Number of Users	☐	
parentConfigurationItemID	int32	Parent Configuration Item ID	☐	
perUseCost	double	Per Use Cost	☐	
productID	int32	Product ID	☐	
referenceNumber	string	Reference Number	☐	
referenceTitle	string	Reference Title	☐	
rmmDeviceAuditAntivirusStatusID	int32	Device Audit Anti-virus Status ID	☐	
rmmDeviceAuditArchitectureID	int32	Device Audit Architecture ID	☐	
rmmDeviceAuditBackupStatusID	int32	Device Audit Backup Status ID	☐	
rmmDeviceAuditDescription	string	Device Audit Description	☐	
rmmDeviceAuditDeviceTypeID	int32	Device Audit Device Type ID	☐	
rmmDeviceAuditDisplayAdaptorID	int32	Device Audit Display Adaptor ID	☐	
rmmDeviceAuditDomainID	int32	Device Audit Domain ID	☐	
rmmDeviceAuditExternalIPAddress	string	Device Audit External IP Address	☐	
rmmDeviceAuditHostname	string	Device Audit Hostname	☐	
rmmDeviceAuditIPAddress	string	Devuce Audit IP-address	☐	
rmmDeviceAuditLastUser	string	Device Audit Last User	☐	
rmmDeviceAuditMacAddress	string	Device Audit MAC Address	☐	
rmmDeviceAuditManufacturerID	int32	Device Audit Manufacturer ID	☐	
rmmDeviceAuditMemoryBytes	int64	Device Audit Memory Bytes	☐	
rmmDeviceAuditMissingPatchCount	int32	Device Audit Missing Patch Count	☐	
rmmDeviceAuditMobileNetw orkOperatorID	int32	Device Audit Mobile Netw ork Operator ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
rmmDeviceAuditMobileNumber	string	Device Audit Mobile Number	☐	
rmmDeviceAuditModelID	int32	Device Audit Model ID	☐	
rmmDeviceAuditMotherboardID	int32	Device Audit Motherboard ID	☐	
rmmDeviceAuditOperatingSystem	string	Device Audit Operating System	☐	
rmmDeviceAuditPatchStatusID	int32	Device Audit Patch Status ID	☐	
rmmDeviceAuditProcessorID	int32	Device Audit Processor ID	☐	
rmmDeviceAuditServicePackID	int32	Device Audit Service Pack ID	☐	
rmmDeviceAuditSNMPContact	string	Device Audit SNMP Contact	☐	
rmmDeviceAuditSNMPLocation	string	Device Audit SNMP Location	☐	
rmmDeviceAuditSNMPName	string	Device Audit SNMP Name	☐	
rmmDeviceAuditSoftwareStatusID	int32	Device Audit Software Status ID	☐	
rmmDeviceAuditStorageBytes	int64	Device Audit Storage Bytes	☐	
rmmDeviceID	int64	Device ID	☐	
rmmDeviceUID	string	Device UID	☐	
rmmOpenAlertCount	int32	Open Alert Count	☐	
serialNumber	string	Serial Number	☐	
serviceBundleID	int32	Service Bundle ID	☐	
serviceID	int32	Service ID	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
setupFee	double	Setup Fee	☐	
sourceChargeID	int32	Source Charge ID	☐	
sourceChargeType	int32	Source Charge Type	☐	
sslCommonName	string	SSL Common Name	☐	
sslIssuedBy	string	SSL Issued by	☐	
sslLocation	string	SSL Location	☐	
sslOrganization	string	SSL Organization	☐	
sslOrganizationUnit	string	SSL Organization Unit	☐	
sslSerialNumber	string	SSL Serial Number	☐	
sslSignatureAlgorithm	string	SSL Signature Algorithm	☐	
sslSource	string	SSL Source	☐	
sslValidFromDateTime	datetime	SSL Valid from Date/Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sslValidUntilDateTime	datetime	SSL Valid until Date/Time	☐	
value	string	Value	☐	
vendorID	int32	Vendor ID	☐	
warrantyExpirationDate	datetime	Warranty Expiration Date	☐	

77.1.3 ConfigurationItemsById

Catalog: Autotask

Schema: ConfigurationItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
apiVendorID	int32	API Vendor ID	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
configurationItemCategoryID	int32	Configuration Item Category ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
configurationItemType	int32	Configuration Item Type	☐	
contactID	int32	Contact ID	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
contractServiceID	int32	Contract Service ID	☐	
createDate	datetime	Created	☐	
createdByPersonID	int32	Created by Person ID	☐	
dailyCost	double	Daily Cost	☐	
dattoAvailableKilobytes	int64	Available Kilobytes	☐	
dattoDeviceMemoryMegabytes	int32	Device Memory Megabytes	☐	
dattoDrivesErrors	boolean	Drives Errors	☐	
dattoHostname	string	Hostname	☐	
dattoInternalIP	string	Internal IP	☐	
dattoKernelVersionID	int32	Kernel Version ID	☐	
dattoLastCheckInDateTime	datetime	Last Check-in Date/Time	☐	
dattoNICSpeedKilobitsPerSecond	int32	Speed Kilobits per Second	☐	
dattoNumberOfAgents	int32	Number of Agents	☐	
dattoNumberOfDrives	int32	Number of Drives	☐	
dattoNumberOfVolumes	int32	Number of Volumes	☐	
dattoOffsiteUsedBytes	int64	Off-site Used Bytes	☐	
dattoOSVersionID	int32	OS Version ID	☐	
dattoPercentageUsed	double	Percentage Used	☐	
dattoProtectedKilobytes	int64	Protected Kilobytes	☐	
dattoRemoteIP	string	Remote IP	☐	
dattoSerialNumber	string	Serial Number	☐	
dattoUptimeSeconds	int32	Up-time (seconds)	☐	
dattoUsedKilobytes	int64	Used (Kilobytes)	☐	
dattoZFSVersionID	int32	OZFS Version ID	☐	
deviceNetworkingID	string	Device Networking ID	☐	
domain	string	Domain	☐	
domainExpirationDateTime	datetime	Domain Expiration Date/Time	☐	
domainLastUpdatedDateTime	datetime	Domain Last Updated Date/Time	☐	
domainRegistrarID	int32	Domain Registrar ID	☐	
domainRegistrationDateTime	datetime	Domain Registration Date/Time	☐	
hourlyCost	double	Hourly Cost	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
installDate	datetime	Install Date	☐	
installedByContactID	int32	Installed by Contact ID	☐	
installedByID	int32	Installed by ID	☐	
isActive	boolean	Is Active	☐	
lastActivityPersonID	int32	Last Activity Person ID	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastModifiedTime	datetime	Last Modified Time	☐	
location	string	Location	☐	
monthlyCost	double	Monthly Cost	☐	
notes	string	Notes	☐	
numberOfUsers	double	Number of Users	☐	
parentConfigurationItemID	int32	Parent Configuration Item ID	☐	
perUseCost	double	Per Use Cost	☐	
productID	int32	Product ID	☐	
referenceNumber	string	Reference Number	☐	
referenceTitle	string	Reference Title	☐	
rmmDeviceAuditAntivirusStatusID	int32	Device Audit Anti-virus Status ID	☐	
rmmDeviceAuditArchitectureID	int32	Device Audit Architecture ID	☐	
rmmDeviceAuditBackupStatusID	int32	Device Audit Backup Status ID	☐	
rmmDeviceAuditDescription	string	Device Audit Description	☐	
rmmDeviceAuditDeviceTypeID	int32	Device Audit Device Type ID	☐	
rmmDeviceAuditDisplayAdaptorID	int32	Device Audit Display Adaptor ID	☐	
rmmDeviceAuditDomainID	int32	Device Audit Domain ID	☐	
rmmDeviceAuditExternalIPAddress	string	Device Audit External IP Address	☐	
rmmDeviceAuditHostname	string	Device Audit Hostname	☐	
rmmDeviceAuditIPAddress	string	Devuce Audit IP-address	☐	
rmmDeviceAuditLastUser	string	Device Audit Last User	☐	
rmmDeviceAuditMacAddress	string	Device Audit MAC Address	☐	
rmmDeviceAuditManufacturerID	int32	Device Audit Manufacturer ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
rmmDeviceAuditMemoryBytes	int64	Device Audit Memory Bytes	☐	
rmmDeviceAuditMissingPatchCount	int32	Device Audit Missing Patch Count	☐	
rmmDeviceAuditMobileNetworkOperatorID	int32	Device Audit Mobile Network Operator ID	☐	
rmmDeviceAuditMobileNumber	string	Device Audit Mobile Number	☐	
rmmDeviceAuditModelID	int32	Device Audit Model ID	☐	
rmmDeviceAuditMotherboardID	int32	Device Audit Motherboard ID	☐	
rmmDeviceAuditOperatingSystem	string	Device Audit Operating System	☐	
rmmDeviceAuditPatchStatusID	int32	Device Audit Patch Status ID	☐	
rmmDeviceAuditProcessorID	int32	Device Audit Processor ID	☐	
rmmDeviceAuditServicePackID	int32	Device Audit Service Pack ID	☐	
rmmDeviceAuditSNMPContact	string	Device Audit SNMP Contact	☐	
rmmDeviceAuditSNMPLocation	string	Device Audit SNMP Location	☐	
rmmDeviceAuditSNMPName	string	Device Audit SNMP Name	☐	
rmmDeviceAuditSoftwareStatusID	int32	Device Audit Software Status ID	☐	
rmmDeviceAuditStorageBytes	int64	Device Audit Storage Bytes	☐	
rmmDeviceID	int64	Device ID	☐	
rmmDeviceUID	string	Device UID	☐	
rmmOpenAlertCount	int32	Open Alert Count	☐	
serialNumber	string	Serial Number	☐	
serviceBundleID	int32	Service Bundle ID	☐	
serviceID	int32	Service ID	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
setupFee	double	Setup Fee	☐	
sourceChargeID	int32	Source Charge ID	☐	
sourceChargeType	int32	Source Charge Type	☐	
sslCommonName	string	SSL Common Name	☐	
sslIssuedBy	string	SSL Issued by	☐	
sslLocation	string	SSL Location	☐	
sslOrganization	string	SSL Organization	☐	
sslOrganizationUnit	string	SSL Organization Unit	☐	
sslSerialNumber	string	SSL Serial Number	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sslSignatureAlgorithm	string	SSL Signature Algorithm	☐	
sslSource	string	SSL Source	☐	
sslValidFromDateTime	datetime	SSL Valid from Date/Time	☐	
sslValidUntilDateTime	datetime	SSL Valid until Date/Time	☐	
vendorID	int32	Vendor ID	☐	
warrantyExpirationDate	datetime	Warranty Expiration Date	☐	

77.1.4 ConfigurationItemsCount

Catalog: Autotask

Schema: ConfigurationItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

78 Schema: ConfigurationItemSslSubjectAlternativeNames

78.1 Tables

78.1.1 ConfigurationItemSslSubjectAlternativeNames

Catalog: Autotask

Schema: ConfigurationItemSslSubjectAlternativeNames

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemSslSubjectAlternativeNames are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

78.1.2 ConfigurationItemSslSubjectAlternativeNamesById

Catalog: Autotask

Schema: ConfigurationItemSslSubjectAlternativeNames

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemSslSubjectAlternativeNamesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemSslSubjectAlternativeNamesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
name	string	Name	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

78.1.3 ConfigurationItemSslSubjectAlternativeNamesCount

Catalog: Autotask

Schema: ConfigurationItemSslSubjectAlternativeNames

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemSslSubjectAlternativeNamesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

79 Schema: ConfigurationItemSslSubjectAlternativeNamesChild

79.1 Tables

79.1.1 ConfigurationItemsByParentIdSslSubjectAlternativeNames

Catalog: Autotask

Schema: ConfigurationItemSslSubjectAlternativeNamesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNames. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNames are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
name	string	Name	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

80 Schema: ConfigurationItemTypes

80.1 Tables

80.1.1 ConfigurationItemTypes

Catalog: Autotask

Schema: ConfigurationItemTypes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemTypes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

80.1.2 ConfigurationItemTypesById

Catalog: Autotask

Schema: ConfigurationItemTypes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemTypesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemTypesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

80.1.3 ConfigurationItemTypesCount

Catalog: Autotask

Schema: ConfigurationItemTypes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemTypesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

81 Schema: ConfigurationItemWebhookExcludedResources

81.1 Tables

81.1.1 ConfigurationItemWebhookExcludedResources

Catalog: Autotask

Schema: ConfigurationItemWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ConfigurationItemWebhookExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

81.1.2 ConfigurationItemWebhookExcludedResourcesById

Catalog: Autotask

Schema: ConfigurationItemWebhookExcludedResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhookExcludedResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ConfigurationItemWebhookExcludedResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

81.1.3 ConfigurationItemWebhookExcludedResourcesCount

Catalog: Autotask

Schema: ConfigurationItemWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookExcludedResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

82 Schema: ConfigurationItemWebhookExcludedResourcesChild

82.1 Tables

82.1.1 ConfigurationItemWebhooksByParentIdExcludedResources

Catalog: Autotask

Schema: ConfigurationItemWebhookExcludedResourcesChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdExcludedResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

83 Schema: ConfigurationItemWebhookFields

83.1 Tables

83.1.1 ConfigurationItemWebhookFields

Catalog: Autotask

Schema: ConfigurationItemWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

83.1.2 ConfigurationItemWebhookFieldsById

Catalog: Autotask

Schema: ConfigurationItemWebhookFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhookFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhookFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

83.1.3 ConfigurationItemWebhookFieldsCount

Catalog: Autotask

Schema: ConfigurationItemWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemWebhookFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

84 Schema: ConfigurationItemWebhookFieldsChild

84.1 Tables

84.1.1 ConfigurationItemWebhooksByParentIdFields

Catalog: Autotask

Schema: ConfigurationItemWebhookFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

84.1.2 ConfigurationItemWebhooksByParentIdFieldsId

Catalog: Autotask

Schema: ConfigurationItemWebhookFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ConfigurationItemWebhooksByParentIdFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

85 Schema: ConfigurationItemWebhooks

85.1 Tables

85.1.1 ConfigurationItemWebhooks

Catalog: Autotask

Schema: ConfigurationItemWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhooks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

85.1.2 ConfigurationItemWebhooksById

Catalog: Autotask

Schema: ConfigurationItemWebhooks

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

85.1.3 ConfigurationItemWebhooksCount

Catalog: Autotask

Schema: ConfigurationItemWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhooksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

86 Schema: ConfigurationItemWebhookUdfFields

86.1 Tables

86.1.1 ConfigurationItemWebhookUdfFields

Catalog: Autotask

Schema: ConfigurationItemWebhookUdfFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemWebhookUdfFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

86.1.2 ConfigurationItemWebhookUdfFieldsById

Catalog: Autotask

Schema: ConfigurationItemWebhookUdfFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhookUdfFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhookUdfFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

86.1.3 ConfigurationItemWebhookUdfFieldsCount

Catalog: Autotask

Schema: ConfigurationItemWebhookUdfFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookUdfFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

87 Schema: ConfigurationItemWebhookUdfFieldsChild

87.1 Tables

87.1.1 ConfigurationItemWebhooksByParentIdUdfFields

Catalog: Autotask

Schema: ConfigurationItemWebhookUdfFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdUdfFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdUdfFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

87.1.2 ConfigurationItemWebhooksByParentIdUdfFieldsId

Catalog: Autotask

Schema: ConfigurationItemWebhookUdfFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdUdfFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdUdfFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

88 Schema: ContactBillingProductAssociations

88.1 Tables

88.1.1 ContactBillingProductAssociations

Catalog: Autotask

Schema: ContactBillingProductAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactBillingProductAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingProductID	int32	Billing Product ID	☐	
contactID	int32	Contact ID	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

88.1.2 ContactBillingProductAssociationsById

Catalog: Autotask

Schema: ContactBillingProductAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactBillingProductAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContactBillingProductAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingProductID	int32	Billing Product ID	☐	
contactID	int32	Contact ID	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

88.1.3 ContactBillingProductAssociationsCount

Catalog: Autotask

Schema: ContactBillingProductAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactBillingProductAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

89 Schema: ContactBillingProductAssociationsChild

89.1 Tables

89.1.1 ContactsByParentIdBillingProductAssociations

Catalog: Autotask

Schema: ContactBillingProductAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactsByParentIdBillingProductAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactsByParentIdBillingProductAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingProductID	int32	Billing Product ID	☐	
contactID	int32	Contact ID	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

89.1.2 ContactsByParentIdBillingProductAssociationsId

Catalog: Autotask

Schema: ContactBillingProductAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactsByParentIdBillingProductAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactsByParentIdBillingProductAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingProductID	int32	Billing Product ID	☐	
contactID	int32	Contact ID	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

90 Schema: ContactGroupContacts

90.1 Tables

90.1.1 ContactGroupContacts

Catalog: Autotask

Schema: ContactGroupContacts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupContacts are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contactGroupId	int32	Contact Group ID	☐	
contactId	int32	Contact ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

90.1.2 ContactGroupContactsById

Catalog: Autotask

Schema: ContactGroupContacts

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactGroupContactsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContactGroupContactsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactGroupId	int32	Contact Group ID	☐	
contactId	int32	Contact ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

90.1.3 ContactGroupContactsCount

Catalog: Autotask

Schema: ContactGroupContacts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupContactsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

91 Schema: ContactGroupContactsChild

91.1 Tables

91.1.1 ContactGroupsByParentIdContacts

Catalog: Autotask

Schema: ContactGroupContactsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContactGroupsByParentIdContacts. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactGroupsByParentIdContacts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactGroupId	int32	Contact Group ID	☐	
contactId	int32	Contact ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

91.1.2 ContactGroupsByParentIdContactsId

Catalog: Autotask

Schema: ContactGroupContactsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactGroupsByParentIdContactsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactGroupsByParentIdContactsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactGroupId	int32	Contact Group ID	☐	
contactId	int32	Contact ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

92 Schema: ContactGroups

92.1 Tables

92.1.1 ContactGroups

Catalog: Autotask

Schema: ContactGroups

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroups are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

92.1.2 ContactGroupsById

Catalog: Autotask

Schema: ContactGroups

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactGroupsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContactGroupsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

92.1.3 ContactGroupsCount

Catalog: Autotask

Schema: ContactGroups

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

93 Schema: Contacts

93.1 Tables

93.1.1 Contacts

Catalog: Autotask

Schema: Contacts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Contacts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
addressLine	string	Address Line	☐	
addressLine1	string	Address Line 1	☐	
alternatePhone	string	Alternate Phone	☐	
apiVendorID	int32	API Vendor ID	☐	
bulkEmailOptOutTime	datetime	Bulk Email Opt-out Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
city	string	City	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
emailAddress	string	Email Address	☐	
emailAddress2	string	Email Address 2	☐	
emailAddress3	string	Email Address 3	☐	
extension	string	Extension	☐	
externalID	string	External ID	☐	
facebookUrl	string	Facebook URL	☐	
faxNumber	string	Fax Number	☐	
firstName	string	First Name	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	int32	Is Active	☐	
isOptedOutFromBulkEmail	boolean	Is Opted Out from Bulk Email	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastModifiedDate	datetime	Last Modified	☐	
lastName	string	Last Name	☐	
linkedInUrl	string	LinkedIn URL	☐	
middleInitial	string	Middle Initial	☐	
mobilePhone	string	Mobile Phone	☐	
namePrefix	int32	Name Prefix	☐	
nameSuffix	int32	Name Suffix	☐	
note	string	Note	☐	
phone	string	Phone	☐	
primaryContact	boolean	Primary Contact	☐	
receivesEmailNotifications	boolean	Receives Email Notification	☐	
roomNumber	string	Room Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
solicitationOptOut	boolean	Sollicitation Opt-out	☐	
solicitationOptOutTime	datetime	Sollicitation Opt-out Time	☐	
state	string	State	☐	
surveyOptOut	boolean	Survey Opt-out	☐	
title	string	Title	☐	
twitterUrl	string	Twitter URL	☐	
zipCode	string	ZIP Code	☐	

93.1.2 Contacts_ItemsUserDefinedFields

Catalog: Autotask

Schema: Contacts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Contacts_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
addressLine	string	Address Line	☐	
addressLine1	string	Address Line 1	☐	
alternatePhone	string	Alternate Phone	☐	
apiVendorID	int32	API Vendor ID	☐	
bulkEmailOptOutTime	datetime	Bulk Email Opt-out Time	☐	
city	string	City	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
emailAddress	string	Email Address	☐	
emailAddress2	string	Email Address 2	☐	
emailAddress3	string	Email Address 3	☐	
extension	string	Extension	☐	
externalID	string	External ID	☐	
facebookUrl	string	Facebook URL	☐	
faxNumber	string	Fax Number	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
firstName	string	First Name	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	int32	Is Active	☐	
isOptedOutFromBulkEmail	boolean	Is Opted Out from Bulk Email	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastModifiedDate	datetime	Last Modified	☐	
lastName	string	Last Name	☐	
linkedInUrl	string	LinkedIn URL	☐	
middleInitial	string	Middle Initial	☐	
mobilePhone	string	Mobile Phone	☐	
name	string	Name	☐	
namePrefix	int32	Name Prefix	☐	
nameSuffix	int32	Name Suffix	☐	
note	string	Note	☐	
phone	string	Phone	☐	
primaryContact	boolean	Primary Contact	☐	
receivesEmailNotifications	boolean	Receives Email Notification	☐	
roomNumber	string	Room Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
solicitationOptOut	boolean	Sollicitation Opt-out	☐	
solicitationOptOutTime	datetime	Sollicitation Opt-out Time	☐	
state	string	State	☐	
surveyOptOut	boolean	Survey Opt-out	☐	
title	string	Title	☐	
twitterUrl	string	Twitter URL	☐	
value	string	Value	☐	
zipCode	string	ZIP Code	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

93.1.3 ContactsById

Catalog: Autotask

Schema: Contacts

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContactsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInformation	string	Additional Address Information	☐	
addressLine	string	Address Line	☐	
addressLine1	string	Address Line 1	☐	
alternatePhone	string	Alternate Phone	☐	
apiVendorID	int32	API Vendor ID	☐	
bulkEmailOptOutTime	datetime	Bulk Email Opt-out Time	☐	
city	string	City	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
countryID	int32	Country ID	☐	
createDate	datetime	Created	☐	
emailAddress	string	Email Address	☐	
emailAddress2	string	Email Address 2	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
emailAddress3	string	Email Address 3	☐	
extension	string	Extension	☐	
externalID	string	External ID	☐	
facebookUrl	string	Facebook URL	☐	
faxNumber	string	Fax Number	☐	
firstName	string	First Name	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	int32	Is Active	☐	
isOptedOutFromBulkEmail	boolean	Is Opted Out from Bulk Email	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastModifiedDate	datetime	Last Modified	☐	
lastName	string	Last Name	☐	
linkedInUrl	string	LinkedIn URL	☐	
middleInitial	string	Middle Initial	☐	
mobilePhone	string	Mobile Phone	☐	
namePrefix	int32	Name Prefix	☐	
nameSuffix	int32	Name Suffix	☐	
note	string	Note	☐	
phone	string	Phone	☐	
primaryContact	boolean	Primary Contact	☐	
receivesEmailNotifications	boolean	Receives Email Notification	☐	
roomNumber	string	Room Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
solicitationOptOut	boolean	Sollicitation Opt-out	☐	
solicitationOptOutTime	datetime	Sollicitation Opt-out Time	☐	
state	string	State	☐	
surveyOptOut	boolean	Survey Opt-out	☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
twitterUrl	string	Twitter URL	☐	
zipCode	string	ZIP Code	☐	

93.1.4 ContactsCount

Catalog: Autotask

Schema: Contacts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

94 Schema: ContactWebhookExcludedResources

94.1 Tables

94.1.1 ContactWebhookExcludedResources

Catalog: Autotask

Schema: ContactWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
w ebhookID	int32	Webhook ID	☐	

94.1.2 ContactWebhookExcludedResourcesById

Catalog: Autotask

Schema: ContactWebhookExcludedResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhookExcludedResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhookExcludedResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

94.1.3 ContactWebhookExcludedResourcesCount

Catalog: Autotask

Schema: ContactWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookExcludedResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

95 Schema: ContactWebhookExcludedResourcesChild

95.1 Tables

95.1.1 ContactWebhooksByParentIdExcludedResources

Catalog: Autotask

Schema: ContactWebhookExcludedResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdExcludedResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

95.1.2 ContactWebhooksByParentIdExcludedResourcesId

Catalog: Autotask

Schema: ContactWebhookExcludedResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdExcludedResourcesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdExcludedResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

96 Schema: ContactWebhookFields

96.1 Tables

96.1.1 ContactWebhookFields

Catalog: Autotask

Schema: ContactWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

96.1.2 ContactWebhookFieldsById

Catalog: Autotask

Schema: ContactWebhookFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhookFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContactWebhookFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

96.1.3 ContactWebhookFieldsCount

Catalog: Autotask

Schema: ContactWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

97 Schema: ContactWebhookFieldsChild

97.1 Tables

97.1.1 ContactWebhooksByParentIdFields

Catalog: Autotask

Schema: ContactWebhookFieldsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

97.1.2 ContactWebhooksByParentIdFieldsId

Catalog: Autotask

Schema: ContactWebhookFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

98 Schema: ContactWebhooks

98.1 Tables

98.1.1 ContactWebhooks

Catalog: Autotask

Schema: ContactWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhooks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

98.1.2 ContactWebhooksById

Catalog: Autotask

Schema: ContactWebhooks

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhooksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

98.1.3 ContactWebhooksCount

Catalog: Autotask

Schema: ContactWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhooksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

99 Schema: ContactWebhookUdfFields

99.1 Tables

99.1.1 ContactWebhookUdfFields

Catalog: Autotask

Schema: ContactWebhookUdfFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookUdfFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

99.1.2 ContactWebhookUdfFieldsById

Catalog: Autotask

Schema: ContactWebhookUdfFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhookUdfFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhookUdfFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

99.1.3 ContactWebhookUdfFieldsCount

Catalog: Autotask

Schema: ContactWebhookUdfFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookUdfFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

100 Schema: ContactWebhookUdfFieldsChild

100.1 Tables

100.1.1 ContactWebhooksByParentIdUdfFields

Catalog: Autotask

Schema: ContactWebhookUdfFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdUdfFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdUdfFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

100.1.2 ContactWebhooksByParentIdUdfFieldsId

Catalog: Autotask

Schema: ContactWebhookUdfFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdUdfFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdUdfFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

101 Schema: ContractBillingRules

101.1 Tables

101.1.1 ContractBillingRules

Catalog: Autotask

Schema: ContractBillingRules

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBillingRules are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
createChargesAsBillable	boolean	Create Charges as Billable	☐	
dailyProratedCost	double	Daily Pro-rated Cost	☐	
dailyProratedPrice	double	Daily Pro-rated Price	☐	
determineUnits	int32	Determine Unit	☐	
endDate	datetime	End Date	☐	
executionMethod	int32	Execution Method	☐	
id	int64	ID	☐	
includeItemsInChargeDescription	boolean	Include Items in Charge Description	☐	
invoiceDescription	string	Invoice Description	☐	
isActive	boolean	Is Active	☐	
isDailyProrationEnabled	boolean	Is Daily Pro-ration Enabled	☐	
maximumUnits	int32	Maximum Units	☐	
minimumUnits	int32	Minimum Units	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	

101.1.2 ContractBillingRulesById

Catalog: Autotask

Schema: ContractBillingRules

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractBillingRulesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractBillingRulesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
createChargesAsBillable	boolean	Create Charges as Billable	☐	
dailyProratedCost	double	Daily Pro-rated Cost	☐	
dailyProratedPrice	double	Daily Pro-rated Price	☐	
determineUnits	int32	Determine Unit	☐	
endDate	datetime	End Date	☐	
executionMethod	int32	Execution Method	☐	
id	int64	ID	☐	
includeItemsInChargeDescription	boolean	Include Items in Charge Description	☐	
invoiceDescription	string	Invoice Description	☐	
isActive	boolean	Is Active	☐	
isDailyProrationEnabled	boolean	Is Daily Pro-ration Enabled	☐	
maximumUnits	int32	Maximum Units	☐	
minimumUnits	int32	Minimum Units	☐	
productID	int32	Product ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	

101.1.3 ContractBillingRulesCount

Catalog: Autotask

Schema: ContractBillingRules

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBillingRulesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

102 Schema: ContractBillingRulesChild

102.1 Tables

102.1.1 ContractsByParentIdBillingRules

Catalog: Autotask

Schema: ContractBillingRulesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBillingRules. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBillingRules are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
createChargesAsBillable	boolean	Create Charges as Billable	☐	
dailyProratedCost	double	Daily Pro-rated Cost	☐	
dailyProratedPrice	double	Daily Pro-rated Price	☐	
determineUnits	int32	Determine Unit	☐	
endDate	datetime	End Date	☐	
executionMethod	int32	Execution Method	☐	
id	int64	ID	☐	
includeItemsInChargeDescription	boolean	Include Items in Charge Description	☐	
invoiceDescription	string	Invoice Description	☐	
isActive	boolean	Is Active	☐	
isDailyProrationEnabled	boolean	Is Daily Pro-ration Enabled	☐	
maximumUnits	int32	Maximum Units	☐	
minimumUnits	int32	Minimum Units	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	

102.1.2 ContractsByParentIdBillingRulesId

Catalog: Autotask

Schema: ContractBillingRulesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBillingRulesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBillingRulesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
createChargesAsBillable	boolean	Create Charges as Billable	☐	
dailyProratedCost	double	Daily Pro-rated Cost	☐	
dailyProratedPrice	double	Daily Pro-rated Price	☐	
determineUnits	int32	Determine Unit	☐	
endDate	datetime	End Date	☐	
executionMethod	int32	Execution Method	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
includeItemsInChargeDescription	boolean	Include Items in Charge Description	☐	
invoiceDescription	string	Invoice Description	☐	
isActive	boolean	Is Active	☐	
isDailyProrationEnabled	boolean	Is Daily Pro-ration Enabled	☐	
maximumUnits	int32	Maximum Units	☐	
minimumUnits	int32	Minimum Units	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	

103 Schema: ContractBlockHourFactors

103.1 Tables

103.1.1 ContractBlockHourFactors

Catalog: Autotask

Schema: ContractBlockHourFactors

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlockHourFactors are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
blockHourMultiplier	double	Block Hour Multiplier	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
roleID	int32	Role ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

103.1.2 ContractBlockHourFactorsById

Catalog: Autotask

Schema: ContractBlockHourFactors

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractBlockHourFactorsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractBlockHourFactorsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
blockHourMultiplier	double	Block Hour Multiplier	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

103.1.3 ContractBlockHourFactorsCount

Catalog: Autotask

Schema: ContractBlockHourFactors

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlockHourFactorsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

104 Schema: ContractBlockHourFactorsChild

104.1 Tables

104.1.1 ContractsByParentIdBlockHourFactors

Catalog: Autotask

Schema: ContractBlockHourFactorsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlockHourFactors. A value must be provided at all times for required

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlockHourFactors are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
blockHourMultiplier	double	Block Hour Multiplier	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

104.1.2 ContractsByParentIdBlockHourFactorsId

Catalog: Autotask

Schema: ContractBlockHourFactorsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlockHourFactorsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlockHourFactorsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
blockHourMultiplier	double	Block Hour Multiplier	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

105 Schema: ContractBlocks

105.1 Tables

105.1.1 ContractBlocks

Catalog: Autotask

Schema: ContractBlocks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlocks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
hourlyRate	double	Hourly Rate	☐	
hours	double	Hours	☐	
hoursApproved	double	Hours Approved	☐	
id	int64	ID	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentNumber	string	Payment Number	☐	
paymentType	int32	Payment Type	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	

105.1.2 ContractBlocksById

Catalog: Autotask

Schema: ContractBlocks

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractBlocksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractBlocksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
hourlyRate	double	Hourly Rate	☐	
hours	double	Hours	☐	
hoursApproved	double	Hours Approved	☐	
id	int64	ID	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentNumber	string	Payment Number	☐	
paymentType	int32	Payment Type	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	

105.1.3 ContractBlocksCount

Catalog: Autotask

Schema: ContractBlocks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlocksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

106 Schema: ContractBlocksChild

106.1 Tables

106.1.1 ContractsByParentIdBlocks

Catalog: Autotask

Schema: ContractBlocksChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlocks. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlocks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
hourlyRate	double	Hourly Rate	☐	
hours	double	Hours	☐	
hoursApproved	double	Hours Approved	☐	
id	int64	ID	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentNumber	string	Payment Number	☐	
paymentType	int32	Payment Type	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	

106.1.2 ContractsByParentIdBlocksId

Catalog: Autotask

Schema: ContractBlocksChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlocksId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlocksId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
hourlyRate	double	Hourly Rate	☐	
hours	double	Hours	☐	
hoursApproved	double	Hours Approved	☐	
id	int64	ID	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentNumber	string	Payment Number	☐	
paymentType	int32	Payment Type	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	

107 Schema: ContractCharges

107.1 Tables

107.1.1 ContractCharges

Catalog: Autotask

Schema: ContractCharges

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractCharges are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractID	int64	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

107.1.2 ContractChargesById

Catalog: Autotask

Schema: ContractCharges

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractChargesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractChargesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractID	int64	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

107.1.3 ContractChargesCount

Catalog: Autotask

Schema: ContractCharges

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractChargesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

108 Schema: ContractChargesChild

108.1 Tables

108.1.1 ContractsByParentIdCharges

Catalog: Autotask

Schema: ContractChargesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdCharges. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdCharges are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractID	int64	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

108.1.2 ContractsByParentIdChargesId

Catalog: Autotask

Schema: ContractChargesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdChargesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdChargesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractID	int64	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

109 Schema: ContractExclusionBillingCodes

109.1 Tables

109.1.1 ContractExclusionBillingCodes

Catalog: Autotask

Schema: ContractExclusionBillingCodes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionBillingCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int64	Billing Code ID	☐	
contractID	int64	Contract ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

109.1.2 ContractExclusionBillingCodesById

Catalog: Autotask

Schema: ContractExclusionBillingCodes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionBillingCodesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractExclusionBillingCodesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int64	Billing Code ID	☐	
contractID	int64	Contract ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

109.1.3 ContractExclusionBillingCodesCount

Catalog: Autotask

Schema: ContractExclusionBillingCodes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionBillingCodesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

110 Schema: ContractExclusionBillingCodesChild

110.1 Tables

110.1.1 ContractsByParentIdExclusionBillingCodes

Catalog: Autotask

Schema: ContractExclusionBillingCodesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionBillingCodes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionBillingCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int64	Billing Code ID	☐	
contractID	int64	Contract ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

110.1.2 ContractsByParentIdExclusionBillingCodesId

Catalog: Autotask

Schema: ContractExclusionBillingCodesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionBillingCodesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionBillingCodesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int64	Billing Code ID	☐	
contractID	int64	Contract ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

111 Schema: ContractExclusionRoles

111.1 Tables

111.1.1 ContractExclusionRoles

Catalog: Autotask

Schema: ContractExclusionRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionRoles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int64	Contract ID	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
roleID	int64	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

111.1.2 ContractExclusionRolesById

Catalog: Autotask

Schema: ContractExclusionRoles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionRolesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractExclusionRolesById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contractID	int64	Contract ID	☐	
id	int64	ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

111.1.3 ContractExclusionRolesCount

Catalog: Autotask

Schema: ContractExclusionRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionRolesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

112 Schema: ContractExclusionRolesChild

112.1 Tables

112.1.1 ContractsByParentIdExclusionRoles

Catalog: Autotask

Schema: ContractExclusionRolesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionRoles. A value must be provided at all times for required

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionRoles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int64	Contract ID	☐	
id	int64	ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

112.1.2 ContractsByParentIdExclusionRolesId

Catalog: Autotask

Schema: ContractExclusionRolesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionRolesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionRolesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int64	Contract ID	☐	
id	int64	ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

113 Schema: ContractExclusionSetExcludedRoles

113.1 Tables

113.1.1 ContractExclusionSetExcludedRoles

Catalog: Autotask

Schema: ContractExclusionSetExcludedRoles

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedRoles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
excludedRoleID	int32	Excluded Role ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

113.1.2 ContractExclusionSetExcludedRolesById

Catalog: Autotask

Schema: ContractExclusionSetExcludedRoles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetExcludedRolesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetExcludedRolesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
excludedRoleID	int32	Excluded Role ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

113.1.3 ContractExclusionSetExcludedRolesCount

Catalog: Autotask

Schema: ContractExclusionSetExcludedRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedRolesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

114 Schema: ContractExclusionSetExcludedRolesChild

114.1 Tables

114.1.1 ContractExclusionSetsByParentIdExcludedRoles

Catalog: Autotask

Schema: ContractExclusionSetExcludedRolesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedRoles. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedRoles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
excludedRoleID	int32	Excluded Role ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

114.1.2 ContractExclusionSetsByParentIdExcludedRolesId

Catalog: Autotask

Schema: ContractExclusionSetExcludedRolesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedRolesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedRolesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
excludedRoleID	int32	Excluded Role ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

115 Schema: ContractExclusionSetExcludedWorkTypes

115.1 Tables

115.1.1 ContractExclusionSetExcludedWorkTypes

Catalog: Autotask

Schema: ContractExclusionSetExcludedWorkTypes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedWorkTypes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
excludedWorkTypeID	int32	Excluded Work Type ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

115.1.2 ContractExclusionSetExcludedWorkTypesById

Catalog: Autotask

Schema: ContractExclusionSetExcludedWorkTypes

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetExcludedWorkTypesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetExcludedWorkTypesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
excludedWorkTypeID	int32	Excluded Work Type ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

115.1.3 ContractExclusionSetExcludedWorkTypesCount

Catalog: Autotask

Schema: ContractExclusionSetExcludedWorkTypes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedWorkTypesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

116 Schema: ContractExclusionSetExcludedWorkTypesChild

116.1 Tables

116.1.1 ContractExclusionSetsByParentIdExcludedWorkTypes

Catalog: Autotask

Schema: ContractExclusionSetExcludedWorkTypesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedWorkTypes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContractExclusionSetsByParentIdExcludedWorkTypes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
excludedWorkTypeID	int32	Excluded Work Type ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

116.1.2 ContractExclusionSetsByParentIdExcludedWorkTypesId

Catalog: Autotask

Schema: ContractExclusionSetExcludedWorkTypesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedWorkTypesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedWorkTypesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
excludedWorkTypeID	int32	Excluded Work Type ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

117 Schema: ContractExclusionSets

117.1 Tables

117.1.1 ContractExclusionSets

Catalog: Autotask

Schema: ContractExclusionSets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSets are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

117.1.2 ContractExclusionSetsById

Catalog: Autotask

Schema: ContractExclusionSets

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

117.1.3 ContractExclusionSetsCount

Catalog: Autotask

Schema: ContractExclusionSets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractExclusionSetsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

118 Schema: ContractMilestones

118.1 Tables

118.1.1 ContractMilestones

Catalog: Autotask

Schema: ContractMilestones

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractMilestones are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amount	double	Amount	☐	
billingCodeID	int32	Billing Code ID	☐	
contractID	int32	Contract ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
dateDue	datetime	Date Due	☐	
description	string	Description	☐	
id	int64	ID	☐	
internalCurrencyAmount	double	Internal Currency Amount	☐	
isInitialPayment	boolean	Is Initial Payment	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	

118.1.2 ContractMilestonesById

Catalog: Autotask

Schema: ContractMilestones

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractMilestonesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractMilestonesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amount	double	Amount	☐	
billingCodeID	int32	Billing Code ID	☐	
contractID	int32	Contract ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
dateDue	datetime	Date Due	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
internalCurrencyAmount	double	Internal Currency Amount	☐	
isInitialPayment	boolean	Is Initial Payment	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	

118.1.3 ContractMilestonesCount

Catalog: Autotask

Schema: ContractMilestones

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractMilestonesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

119 Schema: ContractMilestonesChild

119.1 Tables

119.1.1 ContractsByParentIdMilestones

Catalog: Autotask

Schema: ContractMilestonesChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdMilestones. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdMilestones are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amount	double	Amount	☐	
billingCodeID	int32	Billing Code ID	☐	
contractID	int32	Contract ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
dateDue	datetime	Date Due	☐	
description	string	Description	☐	
id	int64	ID	☐	
internalCurrencyAmount	double	Internal Currency Amount	☐	
isInitialPayment	boolean	Is Initial Payment	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	

119.1.2 ContractsByParentIdMilestonesId

Catalog: Autotask

Schema: ContractMilestonesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdMilestonesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdMilestonesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amount	double	Amount	☐	
billingCodeID	int32	Billing Code ID	☐	
contractID	int32	Contract ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
dateDue	datetime	Date Due	☐	
description	string	Description	☐	
id	int64	ID	☐	
internalCurrencyAmount	double	Internal Currency Amount	☐	
isInitialPayment	boolean	Is Initial Payment	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	

120 Schema: ContractNoteAttachments

120.1 Tables

120.1.1 ContractNoteAttachments

Catalog: Autotask

Schema: ContractNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNoteAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
contractID	int32	Contract ID	☐	
contractNoteID	int32	Contract Note ID	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

120.1.2 ContractNoteAttachmentsById

Catalog: Autotask

Schema: ContractNoteAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractNoteAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractNoteAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
contractID	int32	Contract ID	☐	
contractNoteID	int32	Contract Note ID	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

120.1.3 ContractNoteAttachmentsCount

Catalog: Autotask

Schema: ContractNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNoteAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

121 Schema: ContractNoteAttachmentsChild

121.1 Tables

121.1.1 ContractNotesByParentIdAttachments

Catalog: Autotask

Schema: ContractNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractNotesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractNotesByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
contractID	int32	Contract ID	☐	
contractNoteID	int32	Contract Note ID	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

121.1.2 ContractNotesByParentIdAttachmentsId

Catalog: Autotask

Schema: ContractNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractNotesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractNotesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
contractID	int32	Contract ID	☐	
contractNoteID	int32	Contract Note ID	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

122 Schema: ContractNotes

122.1 Tables

122.1.1 ContractNotes

Catalog: Autotask

Schema: ContractNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

122.1.2 ContractNotesById

Catalog: Autotask

Schema: ContractNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContractNotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

122.1.3 ContractNotesCount

Catalog: Autotask

Schema: ContractNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

123 Schema: ContractNotesChild

123.1 Tables

123.1.1 ContractsByParentIdNotes

Catalog: Autotask

Schema: ContractNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

123.1.2 ContractsByParentIdNotesId

Catalog: Autotask

Schema: ContractNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdNotesId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

124 Schema: ContractRates

124.1 Tables

124.1.1 ContractRates

Catalog: Autotask

Schema: ContractRates

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRates are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractHourlyRate	double	Contract Hourly Rate	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyContractHourlyRate	double	Internal Currency Contract Hourly Rate	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

124.1.2 ContractRatesById

Catalog: Autotask

Schema: ContractRates

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractRatesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractRatesById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contractHourlyRate	double	Contract Hourly Rate	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyContractHourlyRate	double	Internal Currency Contract Hourly Rate	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

124.1.3 ContractRatesCount

Catalog: Autotask

Schema: ContractRates

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRatesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

125 Schema: ContractRatesChild

125.1 Tables

125.1.1 ContractsByParentIdRates

Catalog: Autotask

Schema: ContractRatesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRates. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRates are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractHourlyRate	double	Contract Hourly Rate	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyContractHourlyRate	double	Internal Currency Contract Hourly Rate	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

125.1.2 ContractsByParentIdRatesId

Catalog: Autotask

Schema: ContractRatesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRatesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRatesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractHourlyRate	double	Contract Hourly Rate	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyContractHourlyRate	double	Internal Currency Contract Hourly Rate	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

126 Schema: ContractRetainers

126.1 Tables

126.1.1 ContractRetainers

Catalog: Autotask

Schema: ContractRetainers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRetainers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amount	double	Amount	☐	
amountApproved	double	Amount Approved	☐	
contractID	int32	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyAmount	double	Internal Currency Amount	☐	
internalCurrencyAmountApproved	double	Internal Currency Amount Approved	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentID	int32	Payment ID	☐	
paymentNumber	string	Payment Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	

126.1.2 ContractRetainersById

Catalog: Autotask

Schema: ContractRetainers

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractRetainersById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractRetainersById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amount	double	Amount	☐	
amountApproved	double	Amount Approved	☐	
contractID	int32	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyAmount	double	Internal Currency Amount	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
internalCurrencyAmountApproved	double	Internal Currency Amount Approved	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentID	int32	Payment ID	☐	
paymentNumber	string	Payment Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	

126.1.3 ContractRetainersCount

Catalog: Autotask

Schema: ContractRetainers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRetainersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

127 Schema: ContractRetainersChild

127.1 Tables

127.1.1 ContractsByParentIdRetainers

Catalog: Autotask

Schema: ContractRetainersChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRetainers. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRetainers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amount	double	Amount	☐	
amountApproved	double	Amount Approved	☐	
contractID	int32	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyAmount	double	Internal Currency Amount	☐	
internalCurrencyAmountApproved	double	Internal Currency Amount Approved	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentID	int32	Payment ID	☐	
paymentNumber	string	Payment Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	

127.1.2 ContractsByParentIdRetainersId

Catalog: Autotask

Schema: ContractRetainersChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRetainersId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRetainersId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amount	double	Amount	☐	
amountApproved	double	Amount Approved	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyAmount	double	Internal Currency Amount	☐	
internalCurrencyAmountApproved	double	Internal Currency Amount Approved	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentID	int32	Payment ID	☐	
paymentNumber	string	Payment Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	

128 Schema: ContractRoleCosts

128.1 Tables

128.1.1 ContractRoleCosts

Catalog: Autotask

Schema: ContractRoleCosts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRoleCosts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
rate	double	Rate	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

128.1.2 ContractRoleCostsById

Catalog: Autotask

Schema: ContractRoleCosts

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractRoleCostsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContractRoleCostsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
rate	double	Rate	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

128.1.3 ContractRoleCostsCount

Catalog: Autotask

Schema: ContractRoleCosts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRoleCostsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

129 Schema: ContractRoleCostsChild

129.1 Tables

129.1.1 ContractsByParentIdRoleCosts

Catalog: Autotask

Schema: ContractRoleCostsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRoleCosts. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRoleCosts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
rate	double	Rate	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

129.1.2 ContractsByParentIdRoleCostsId

Catalog: Autotask

Schema: ContractRoleCostsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRoleCostsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRoleCostsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
rate	double	Rate	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

130 Schema: Contracts

130.1 Tables

130.1.1 Contracts

Catalog: Autotask

Schema: Contracts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Contracts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingPreference	int32	Billing Preference	☐	
billToCompanyContactID	int32	Bill-to Company Contact ID	☐	
billToCompanyID	int32	Bill-to Company ID	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
contactName	string	Contact Name	☐	
contractCategory	int32	Contract Category	☐	
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
contractName	string	Contract Name	☐	
contractNumber	string	Contract Number	☐	
contractPeriodType	int32	Contract Period Type	☐	
contractType	int32	Contract Type	☐	
description	string	Description	☐	
endDate	datetime	End Date	☐	
estimatedCost	double	Estimated Cost	☐	
estimatedHours	double	Estimated Hours	☐	
estimatedRevenue	double	Estimated Revenue	☐	
exclusionContractID	int64	Exclusion Contract ID	☐	
id	int64	ID	☐	
internalCurrencyOverageBillingRate	double	Internal Currency Overage Billing Rate	☐	
internalCurrencySetupFee	double	Internal Currency Setup Fee	☐	
isCompliant	boolean	Is Compliant	☐	
isDefaultContract	boolean	Is Default Contract	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
overageBillingRate	double	Overage Billing Rate	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
purchaseOrderNumber	string	Purchase Order Number	☐	
renewedContractID	int64	Renewed Contract ID	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
setupFee	double	Setup Fee	☐	
setupFeeBillingCodeID	int64	Setup Fee Billing Code ID	☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
timeReportingRequiresStartAndStopTimes	int32	Time Reporting Requires Start and Stop Times	☐	

130.1.2 Contracts_ItemsUserDefinedFields

Catalog: Autotask

Schema: Contracts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Contracts_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingPreference	int32	Billing Preference	☐	
billToCompanyContactID	int32	Bill-to Company Contact ID	☐	
billToCompanyID	int32	Bill-to Company ID	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
contactName	string	Contact Name	☐	
contractCategory	int32	Contract Category	☐	
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
contractName	string	Contract Name	☐	
contractNumber	string	Contract Number	☐	
contractPeriodType	int32	Contract Period Type	☐	
contractType	int32	Contract Type	☐	
description	string	Description	☐	
endDate	datetime	End Date	☐	
estimatedCost	double	Estimated Cost	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimatedHours	double	Estimated Hours	☐	
estimatedRevenue	double	Estimated Revenue	☐	
exclusionContractID	int64	Exclusion Contract ID	☐	
id	int64	ID	☐	
internalCurrencyOverageBillingRate	double	Internal Currency Overage Billing Rate	☐	
internalCurrencySetupFee	double	Internal Currency Setup Fee	☐	
isCompliant	boolean	Is Compliant	☐	
isDefaultContract	boolean	Is Default Contract	☐	
name	string	Name	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
overageBillingRate	double	Overage Billing Rate	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
renewedContractID	int64	Renewed Contract ID	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
setupFee	double	Setup Fee	☐	
setupFeeBillingCodeID	int64	Setup Fee Billing Code ID	☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
timeReportingRequiresStartAndStopTimes	int32	Time Reporting Requires Start and Stop Times	☐	
value	string	Value	☐	

130.1.3 ContractsById

Catalog: Autotask

Schema: Contracts

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingPreference	int32	Billing Preference	☐	
billToCompanyContactID	int32	Bill-to Company Contact ID	☐	
billToCompanyID	int32	Bill-to Company ID	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
contactName	string	Contact Name	☐	
contractCategory	int32	Contract Category	☐	
contractExclusionSetID	int32	Contract Exclusion Set ID	☐	
contractName	string	Contract Name	☐	
contractNumber	string	Contract Number	☐	
contractPeriodType	int32	Contract Period Type	☐	
contractType	int32	Contract Type	☐	
description	string	Description	☐	
endDate	datetime	End Date	☐	
estimatedCost	double	Estimated Cost	☐	
estimatedHours	double	Estimated Hours	☐	
estimatedRevenue	double	Estimated Revenue	☐	
exclusionContractID	int64	Exclusion Contract ID	☐	
id	int64	ID	☐	
internalCurrencyOverageBillingRate	double	Internal Currency Overage Billing Rate	☐	
internalCurrencySetupFee	double	Internal Currency Setup Fee	☐	
isCompliant	boolean	Is Compliant	☐	
isDefaultContract	boolean	Is Default Contract	☐	
opportunityID	int32	Opportunity ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
overageBillingRate	double	Overage Billing Rate	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
renew edContractID	int64	Renew ed Contract ID	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
setupFee	double	Setup Fee	☐	
setupFeeBillingCodeID	int64	Setup Fee Billing Code ID	☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
timeReportingRequiresStartAndStopTimes	int32	Time Reporting Requires Start and Stop Times	☐	

130.1.4 ContractsCount

Catalog: Autotask

Schema: Contracts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

131 Schema: ContractServiceBundles

131.1 Tables

131.1.1 ContractServiceBundles

Catalog: Autotask

Schema: ContractServiceBundles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContractServiceBundles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
adjustedPrice	double	Adjusted Price	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyAdjustedPrice	double	Internal Currency Adjusted Price	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalDescription	string	Internal Description	☐	
invoiceDescription	string	Invoice Description	☐	
quoteItemID	int64	Quote Item ID	☐	
serviceBundleID	int32	Service Bundle ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitPrice	double	Unit Price	☐	

131.1.2 ContractServiceBundlesById

Catalog: Autotask

Schema: ContractServiceBundles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractServiceBundlesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractServiceBundlesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
adjustedPrice	double	Adjusted Price	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyAdjustedPrice	double	Internal Currency Adjusted Price	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalDescription	string	Internal Description	☐	
invoiceDescription	string	Invoice Description	☐	
quoteItemID	int64	Quote Item ID	☐	
serviceBundleID	int32	Service Bundle ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitPrice	double	Unit Price	☐	

131.1.3 ContractServiceBundlesCount

Catalog: Autotask

Schema: ContractServiceBundles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractServiceBundlesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

132 Schema: ContractServiceBundlesChild

132.1 Tables

132.1.1 ContractsByParentIdServiceBundles

Catalog: Autotask

Schema: ContractServiceBundlesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundles. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
adjustedPrice	double	Adjusted Price	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
internalCurrencyAdjustedPrice	double	Internal Currency Adjusted Price	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalDescription	string	Internal Description	☐	
invoiceDescription	string	Invoice Description	☐	
quoteItemID	int64	Quote Item ID	☐	
serviceBundleID	int32	Service Bundle ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitPrice	double	Unit Price	☐	

132.1.2 ContractsByParentIdServiceBundlesId

Catalog: Autotask

Schema: ContractServiceBundlesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundlesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundlesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
adjustedPrice	double	Adjusted Price	☐	
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyAdjustedPrice	double	Internal Currency Adjusted Price	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalDescription	string	Internal Description	☐	
invoiceDescription	string	Invoice Description	☐	
quoteItemID	int64	Quote Item ID	☐	
serviceBundleID	int32	Service Bundle ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitPrice	double	Unit Price	☐	

133 Schema: ContractServiceBundleUnits

133.1 Tables

133.1.1 ContractServiceBundleUnits

Catalog: Autotask

Schema: ContractServiceBundleUnits

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractServiceBundleUnits are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveAndPostDate	datetime	Approve and Post Date	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
cost	double	Cost	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyPrice	double	Internal Currency Price	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
price	double	Price	☐	
serviceBundleID	int32	Service Bundle ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
startDate	datetime	Start Date	☐	
units	int32	Units	☐	

133.1.2 ContractServiceBundleUnitsById

Catalog: Autotask

Schema: ContractServiceBundleUnits

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractServiceBundleUnitsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractServiceBundleUnitsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveAndPostDate	datetime	Approve and Post Date	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
cost	double	Cost	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyPrice	double	Internal Currency Price	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
price	double	Price	☐	
serviceBundleID	int32	Service Bundle ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
startDate	datetime	Start Date	☐	
units	int32	Units	☐	

133.1.3 ContractServiceBundleUnitsCount

Catalog: Autotask

Schema: ContractServiceBundleUnits

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleUnitsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

134 Schema: ContractServiceBundleUnitsChild

134.1 Tables

134.1.1 ContractsByParentIdServiceBundleUnits

Catalog: Autotask

Schema: ContractServiceBundleUnitsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleUnits. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleUnits are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveAndPostDate	datetime	Approve and Post Date	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
cost	double	Cost	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyPrice	double	Internal Currency Price	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
price	double	Price	☐	
serviceBundleID	int32	Service Bundle ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
startDate	datetime	Start Date	☐	
units	int32	Units	☐	

134.1.2 ContractsByParentIdServiceBundleUnitsId

Catalog: Autotask

Schema: ContractServiceBundleUnitsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleUnitsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleUnitsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveAndPostDate	datetime	Approve and Post Date	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int32	Contract Service Bundle ID	☐	
cost	double	Cost	☐	
endDate	datetime	End Date	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
internalCurrencyPrice	double	Internal Currency Price	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
price	double	Price	☐	
serviceBundleID	int32	Service Bundle ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
startDate	datetime	Start Date	☐	
units	int32	Units	☐	

135 Schema: ContractServices

135.1 Tables

135.1.1 ContractServices

Catalog: Autotask

Schema: ContractServices

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServices are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyAdjustedPrice	double	Internal Currency Adjusted Price	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalDescription	string	Internal Description	☐	
invoiceDescription	string	Invoice Description	☐	
quoteItemID	int64	Quote Item ID	☐	
serviceID	int32	Service ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	

135.1.2 ContractServicesById

Catalog: Autotask

Schema: ContractServices

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractServicesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractServicesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyAdjustedPrice	double	Internal Currency Adjusted Price	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalDescription	string	Internal Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
invoiceDescription	string	Invoice Description	☐	
quoteItemID	int64	Quote Item ID	☐	
serviceID	int32	Service ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	

135.1.3 ContractServicesCount

Catalog: Autotask

Schema: ContractServices

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServicesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

136 Schema: ContractServicesChild

136.1 Tables

136.1.1 ContractsByParentIdServices

Catalog: Autotask

Schema: ContractServicesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServices. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServices are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyAdjustedPrice	double	Internal Currency Adjusted Price	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalDescription	string	Internal Description	☐	
invoiceDescription	string	Invoice Description	☐	
quoteItemID	int64	Quote Item ID	☐	
serviceID	int32	Service ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

136.1.2 ContractsByParentIdServicesId

Catalog: Autotask

Schema: ContractServicesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServicesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServicesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int32	Contract ID	☐	
id	int64	ID	☐	
internalCurrencyAdjustedPrice	double	Internal Currency Adjusted Price	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalDescription	string	Internal Description	☐	
invoiceDescription	string	Invoice Description	☐	
quoteItemID	int64	Quote Item ID	☐	
serviceID	int32	Service ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	

137 Schema: ContractServiceUnits

137.1 Tables

137.1.1 ContractServiceUnits

Catalog: Autotask

Schema: ContractServiceUnits

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceUnits are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveAndPostDate	datetime	Approve and Post Date	☐	
contractID	int32	Contract ID	☐	
contractServiceID	int32	Contract Service ID	☐	
cost	double	Cost	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyPrice	double	Internal Currency Price	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
price	double	Price	☐	
serviceID	int32	Service ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
startDate	datetime	Start Date	☐	
units	int32	Units	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
vendorCompanyID	int32	Vendor Company ID	☐	

137.1.2 ContractServiceUnitsById

Catalog: Autotask

Schema: ContractServiceUnits

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractServiceUnitsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractServiceUnitsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveAndPostDate	datetime	Approve and Post Date	☐	
contractID	int32	Contract ID	☐	
contractServiceID	int32	Contract Service ID	☐	
cost	double	Cost	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyPrice	double	Internal Currency Price	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
price	double	Price	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
serviceID	int32	Service ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
startDate	datetime	Start Date	☐	
units	int32	Units	☐	
vendorCompanyID	int32	Vendor Company ID	☐	

137.1.3 ContractServiceUnitsCount

Catalog: Autotask

Schema: ContractServiceUnits

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceUnitsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

138 Schema: ContractServiceUnitsChild

138.1 Tables

138.1.1 ContractsByParentIdServiceUnits

Catalog: Autotask

Schema: ContractServiceUnitsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceUnits. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceUnits are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveAndPostDate	datetime	Approve and Post Date	☐	
contractID	int32	Contract ID	☐	
contractServiceID	int32	Contract Service ID	☐	
cost	double	Cost	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyPrice	double	Internal Currency Price	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
price	double	Price	☐	
serviceID	int32	Service ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
startDate	datetime	Start Date	☐	
units	int32	Units	☐	
vendorCompanyID	int32	Vendor Company ID	☐	

138.1.2 ContractsByParentIdServiceUnitsId

Catalog: Autotask

Schema: ContractServiceUnitsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceUnitsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceUnitsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveAndPostDate	datetime	Approve and Post Date	☐	
contractID	int32	Contract ID	☐	
contractServiceID	int32	Contract Service ID	☐	
cost	double	Cost	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
internalCurrencyPrice	double	Internal Currency Price	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
price	double	Price	☐	
serviceID	int32	Service ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
startDate	datetime	Start Date	☐	
units	int32	Units	☐	
vendorCompanyID	int32	Vendor Company ID	☐	

139 Schema: ContractTicketPurchases

139.1 Tables

139.1.1 ContractTicketPurchases

Catalog: Autotask

Schema: ContractTicketPurchases

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractTicketPurchases are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int64	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentNumber	string	Payment Number	☐	
paymentType	int32	Payment Type	☐	
perTicketRate	double	Per Ticket Rate	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
ticketsPurchased	double	Tickets Purchased	☐	
ticketsUsed	double	Tickets Used	☐	

139.1.2 ContractTicketPurchasesById

Catalog: Autotask

Schema: ContractTicketPurchases

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractTicketPurchasesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ContractTicketPurchasesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int64	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentNumber	string	Payment Number	☐	
paymentType	int32	Payment Type	☐	
perTicketRate	double	Per Ticket Rate	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
ticketsPurchased	double	Tickets Purchased	☐	
ticketsUsed	double	Tickets Used	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

139.1.3 ContractTicketPurchasesCount

Catalog: Autotask

Schema: ContractTicketPurchases

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractTicketPurchasesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

140 Schema: ContractTicketPurchasesChild

140.1 Tables

140.1.1 ContractsByParentIdTicketPurchases

Catalog: Autotask

Schema: ContractTicketPurchasesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdTicketPurchases. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdTicketPurchases are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contractID	int64	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentNumber	string	Payment Number	☐	
paymentType	int32	Payment Type	☐	
perTicketRate	double	Per Ticket Rate	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
ticketsPurchased	double	Tickets Purchased	☐	
ticketsUsed	double	Tickets Used	☐	

140.1.2 ContractsByParentIdTicketPurchasesId

Catalog: Autotask

Schema: ContractTicketPurchasesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdTicketPurchasesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdTicketPurchasesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contractID	int64	Contract ID	☐	
datePurchased	datetime	Purchase Date	☐	
endDate	datetime	End Date	☐	
id	int64	ID	☐	
invoiceNumber	string	Invoice Number	☐	
isPaid	boolean	Is Paid	☐	
paymentNumber	string	Payment Number	☐	
paymentType	int32	Payment Type	☐	
perTicketRate	double	Per Ticket Rate	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
ticketsPurchased	double	Tickets Purchased	☐	
ticketsUsed	double	Tickets Used	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

141 Schema: Countries

141.1 Tables

141.1.1 Countries

Catalog: Autotask

Schema: Countries

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Countries are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
addressFormatID	int64	Address Format ID	☐	
countryCode	string	Country Code	☐	
displayName	string	Display Name	☐	
id	int64	ID	☐	
invoiceTemplateID	int32	Invoice Template ID	☐	
isActive	boolean	Is Active	☐	
isDefaultCountry	boolean	Is Default Country	☐	
name	string	Name	☐	
purchaseOrderTemplateID	int32	Purchase Order Template ID	☐	
quoteTemplateID	int32	Quote Template ID	☐	

141.1.2 CountriesById

Catalog: Autotask

Schema: Countries

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CountriesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CountriesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
addressFormatID	int64	Address Format ID	☐	
countryCode	string	Country Code	☐	
displayName	string	Display Name	☐	
id	int64	ID	☐	
invoiceTemplateID	int32	Invoice Template ID	☐	
isActive	boolean	Is Active	☐	
isDefaultCountry	boolean	Is Default Country	☐	
name	string	Name	☐	
purchaseOrderTemplateID	int32	Purchase Order Template ID	☐	
quoteTemplateID	int32	Quote Template ID	☐	

141.1.3 CountriesCount

Catalog: Autotask

Schema: Countries

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CountriesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

142 Schema: Currencies

142.1 Tables

142.1.1 Currencies

Catalog: Autotask

Schema: Currencies

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Currencies are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyNegativeFormat	string	Currency Negative Format	☐	
currencyPositiveFormat	string	Currency Positive Format	☐	
description	string	Description	☐	
displaySymbol	int32	Display Symbol	☐	
exchangeRate	double	Exchange Rate	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isInternalCurrency	boolean	Is Internal Currency	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
name	string	Name	☐	
updateResourceId	int32	Update Resource ID	☐	

142.1.2 CurrenciesById

Catalog: Autotask

Schema: Currencies

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CurrenciesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function CurrenciesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyNegativeFormat	string	Currency Negative Format	☐	
currencyPositiveFormat	string	Currency Positive Format	☐	
description	string	Description	☐	
displaySymbol	int32	Display Symbol	☐	
exchangeRate	double	Exchange Rate	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isInternalCurrency	boolean	Is Internal Currency	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
name	string	Name	☐	
updateResourceId	int32	Update Resource ID	☐	

142.1.3 CurrenciesCount

Catalog: Autotask

Schema: Currencies

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CurrenciesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

143 Schema: DeletedTaskActivityLogs

143.1 Tables

143.1.1 DeletedTaskActivityLogs

Catalog: Autotask

Schema: DeletedTaskActivityLogs

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTaskActivityLogs are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
activityDateTime	datetime	Activity Date Time	☐	
createdByResourceID	int32	Created by Resource ID	☐	
deletedByResourceID	int32	Deleted by Resource ID	☐	
deletedDateTime	datetime	Deleted Date/Time	☐	
endDateTime	datetime	End Date/Time	☐	
hoursWorked	double	Hours Worked	☐	
id	int64	ID	☐	
noteOrAttachmentTitle	string	Note or Attachment Title	☐	
startDateTime	datetime	Start Date/Time	☐	
taskID	int32	Task ID	☐	
taskNumber	string	Task Number	☐	
typeID	int32	Type ID	☐	

143.1.2 DeletedTaskActivityLogsById

Catalog: Autotask

Schema: DeletedTaskActivityLogs

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DeletedTaskActivityLogsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DeletedTaskActivityLogsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
activityDateTime	datetime	Activity Date Time	☐	
createdByResourceID	int32	Created by Resource ID	☐	
deletedByResourceID	int32	Deleted by Resource ID	☐	
deletedDateTime	datetime	Deleted Date/Time	☐	
endDateTime	datetime	End Date/Time	☐	
hoursWorked	double	Hours Worked	☐	
id	int64	ID	☐	
noteOrAttachmentTitle	string	Note or Attachment Title	☐	
startDateTime	datetime	Start Date/Time	☐	
taskID	int32	Task ID	☐	
taskNumber	string	Task Number	☐	
typeID	int32	Type ID	☐	

143.1.3 DeletedTaskActivityLogsCount

Catalog: Autotask

Schema: DeletedTaskActivityLogs

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTaskActivityLogsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

144 Schema: DeletedTicketActivityLogs

144.1 Tables

144.1.1 DeletedTicketActivityLogs

Catalog: Autotask

Schema: DeletedTicketActivityLogs

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketActivityLogs are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
activityDateTime	datetime	Activity Date Time	☐	
createdByResourceID	int32	Created by Resource ID	☐	
deletedByResourceID	int32	Deleted by Resource ID	☐	
deletedDateTime	datetime	Deleted Date/Time	☐	
endDateTime	datetime	End Date/Time	☐	
hoursWorked	double	Hours Worked	☐	
id	int64	ID	☐	
noteOrAttachmentTitle	string	Note or Attachment Title	☐	
startDateTime	datetime	Start Date/Time	☐	
ticketID	int32	Ticket ID	☐	
ticketNumber	string	Ticket Number	☐	
typeID	int32	Type ID	☐	

144.1.2 DeletedTicketActivityLogsById

Catalog: Autotask

Schema: DeletedTicketActivityLogs

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DeletedTicketActivityLogsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DeletedTicketActivityLogsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
activityDateTime	datetime	Activity Date Time	☐	
createdByResourceID	int32	Created by Resource ID	☐	
deletedByResourceID	int32	Deleted by Resource ID	☐	
deletedDateTime	datetime	Deleted Date/Time	☐	
endDateTime	datetime	End Date/Time	☐	
hoursWorked	double	Hours Worked	☐	
id	int64	ID	☐	
noteOrAttachmentTitle	string	Note or Attachment Title	☐	
startDateTime	datetime	Start Date/Time	☐	
ticketID	int32	Ticket ID	☐	
ticketNumber	string	Ticket Number	☐	
typeID	int32	Type ID	☐	

144.1.3 DeletedTicketActivityLogsCount

Catalog: Autotask

Schema: DeletedTicketActivityLogs

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketActivityLogsCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

145 Schema: DeletedTicketLogs

145.1 Tables

145.1.1 DeletedTicketLogs

Catalog: Autotask

Schema: DeletedTicketLogs

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketLogs are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deletedByResourceID	int32	Deleted by Resource ID	☐	
deletedDateTime	datetime	Deleted Date/Time	☐	
id	int64	ID	☐	
ticketID	int32	Ticket ID	☐	
ticketNumber	string	Ticket Number	☐	
ticketTitle	string	Ticket Title	☐	

145.1.2 DeletedTicketLogsById

Catalog: Autotask

Schema: DeletedTicketLogs

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DeletedTicketLogsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DeletedTicketLogsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deletedByResourceID	int32	Deleted by Resource ID	☐	
deletedDateTime	datetime	Deleted Date/Time	☐	
id	int64	ID	☐	
ticketID	int32	Ticket ID	☐	
ticketNumber	string	Ticket Number	☐	
ticketTitle	string	Ticket Title	☐	

145.1.3 DeletedTicketLogsCount

Catalog: Autotask

Schema: DeletedTicketLogs

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketLogsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

146 Schema: Departments

146.1 Tables

146.1.1 Departments

Catalog: Autotask

Schema: Departments

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Departments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
name	string	Name	☐	
number	string	Number	☐	
primaryLocationID	int32	Primary Location ID	☐	

146.1.2 DepartmentsById

Catalog: Autotask

Schema: Departments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DepartmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DepartmentsById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
name	string	Name	☐	
number	string	Number	☐	
primaryLocationID	int32	Primary Location ID	☐	

146.1.3 DepartmentsCount

Catalog: Autotask

Schema: Departments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DepartmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

147 Schema: DocumentAttachments

147.1 Tables

147.1.1 DocumentAttachments

Catalog: Autotask

Schema: DocumentAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
documentID	int32	Document ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

147.1.2 DocumentAttachmentsById

Catalog: Autotask

Schema: DocumentAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
documentID	int32	Document ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

147.1.3 DocumentAttachmentsCount

Catalog: Autotask

Schema: DocumentAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

148 Schema: DocumentAttachmentsChild

148.1 Tables

148.1.1 DocumentsByParentIdAttachments

Catalog: Autotask

Schema: DocumentAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
documentID	int32	Document ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

148.1.2 DocumentsByParentIdAttachmentsId

Catalog: Autotask

Schema: DocumentAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
documentID	int32	Document ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

149 Schema: DocumentCategories

149.1 Tables

149.1.1 DocumentCategories

Catalog: Autotask

Schema: DocumentCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentCategories are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
name	string	Name	☐	
parentCategoryID	int32	Parent Category ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

149.1.2 DocumentCategoriesById

Catalog: Autotask

Schema: DocumentCategories

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentCategoriesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentCategoriesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
name	string	Name	☐	
parentCategoryID	int32	Parent Category ID	☐	

149.1.3 DocumentCategoriesCount

Catalog: Autotask

Schema: DocumentCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table DocumentCategoriesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

150 Schema: DocumentChecklistItems

150.1 Tables

150.1.1 DocumentChecklistItems

Catalog: Autotask

Schema: DocumentChecklistItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

150.1.2 DocumentChecklistItemsById

Catalog: Autotask

Schema: DocumentChecklistItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentChecklistItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentChecklistItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

150.1.3 DocumentChecklistItemsCount

Catalog: Autotask

Schema: DocumentChecklistItems

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

151 Schema: DocumentChecklistItemsChild

151.1 Tables

151.1.1 DocumentsByParentIdChecklistItems

Catalog: Autotask

Schema: DocumentChecklistItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

151.1.2 DocumentsByParentIdChecklistItemsId

Catalog: Autotask

Schema: DocumentChecklistItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

152 Schema: DocumentConfigurationItemAssociations

152.1 Tables

152.1.1 DocumentConfigurationItemAssociations

Catalog: Autotask

Schema: DocumentConfigurationItemAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

152.1.2 DocumentConfigurationItemAssociationsById

Catalog: Autotask

Schema: DocumentConfigurationItemAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentConfigurationItemAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentConfigurationItemAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

152.1.3 DocumentConfigurationItemAssociationsCount

Catalog: Autotask

Schema: DocumentConfigurationItemAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

153 Schema: DocumentConfigurationItemAssociationsChild

153.1 Tables

153.1.1 DocumentsByParentIdConfigurationItemAssociations

Catalog: Autotask

Schema: DocumentConfigurationItemAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

153.1.2 DocumentsByParentIdConfigurationItemAssociationsId

Catalog: Autotask

Schema: DocumentConfigurationItemAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

154 Schema: DocumentConfigurationItemCategoryAssociations

154.1 Tables

154.1.1 DocumentConfigurationItemCategoryAssociations

Catalog: Autotask

Schema: DocumentConfigurationItemCategoryAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemCategoryAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
installedProductCategoryID	int32	Installed Product Category ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

154.1.2 DocumentConfigurationItemCategoryAssociationsById

Catalog: Autotask

Schema: DocumentConfigurationItemCategoryAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentConfigurationItemCategoryAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentConfigurationItemCategoryAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
installedProductCategoryID	int32	Installed Product Category ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

154.1.3 DocumentConfigurationItemCategoryAssociationsCount

Catalog: Autotask

Schema: DocumentConfigurationItemCategoryAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table DocumentConfigurationItemCategoryAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

155 Schema: DocumentConfigurationItemCategoryAssociationsChild

155.1 Tables

155.1.1 DocumentsByParentIdConfigurationItemCategoryAssociations

Catalog: Autotask

Schema: DocumentConfigurationItemCategoryAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemCategoryAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemCategoryAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
installedProductCategoryID	int32	Installed Product Category ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

156 Schema: DocumentNotes

156.1 Tables

156.1.1 DocumentNotes

Catalog: Autotask

Schema: DocumentNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
description	string	Description	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

156.1.2 DocumentNotesById

Catalog: Autotask

Schema: DocumentNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentNotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
description	string	Description	☐	
documentID	int32	Document ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

156.1.3 DocumentNotesCount

Catalog: Autotask

Schema: DocumentNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentNotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

157 Schema: DocumentNotesChild

157.1 Tables

157.1.1 DocumentsByParentIdNotes

Catalog: Autotask

Schema: DocumentNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
description	string	Description	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

157.1.2 DocumentsByParentIdNotesId

Catalog: Autotask

Schema: DocumentNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdNotesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
description	string	Description	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

158 Schema: DocumentPlainTextContent

158.1 Tables

158.1.1 DocumentPlainTextContent

Catalog: Autotask

Schema: DocumentPlainTextContent

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentPlainTextContent are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contentData	string	Content Data	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

158.1.2 DocumentPlainTextContentById

Catalog: Autotask

Schema: DocumentPlainTextContent

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentPlainTextContentById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentPlainTextContentById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contentData	string	Content Data	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

158.1.3 DocumentPlainTextContentCount

Catalog: Autotask

Schema: DocumentPlainTextContent

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table DocumentPlainTextContentCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

159 Schema: DocumentPlainTextContentChild

159.1 Tables

159.1.1 DocumentsByParentIdPlainTextContent

Catalog: Autotask

Schema: DocumentPlainTextContentChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdPlainTextContent. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdPlainTextContent are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contentData	string	Content Data	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

159.1.2 DocumentsByParentIdPlainTextContentId

Catalog: Autotask

Schema: DocumentPlainTextContentChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdPlainTextContentId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdPlainTextContentId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contentData	string	Content Data	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

160 Schema: Documents

160.1 Tables

160.1.1 Documents

Catalog: Autotask

Schema: Documents

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Documents are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
documentCategoryID	int32	Document Category ID	☐	
errorCodes	string	Error Codes	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
keywords	string	Keywords	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
publish	int32	Publish	☐	
referenceLink	string	Reference Link	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

160.1.2 DocumentsById

Catalog: Autotask

Schema: Documents

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
documentCategoryID	int32	Document Category ID	☐	
errorCodes	string	Error Codes	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
keywords	string	Keywords	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
publish	int32	Publish	☐	
referenceLink	string	Reference Link	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

160.1.3 DocumentsCount

Catalog: Autotask

Schema: Documents

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

161 Schema: DocumentsChild

161.1 Tables

161.1.1 DocumentCategoriesByParentIdDocuments

Catalog: Autotask

Schema: DocumentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentCategoriesByParentIdDocuments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentCategoriesByParentIdDocuments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
documentCategoryID	int32	Document Category ID	☐	
errorCodes	string	Error Codes	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
keywords	string	Keywords	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
publish	int32	Publish	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceLink	string	Reference Link	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

161.1.2 DocumentCategoriesByParentIdDocumentsId

Catalog: Autotask

Schema: DocumentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentCategoriesByParentIdDocumentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function DocumentCategoriesByParentIdDocumentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
documentCategoryID	int32	Document Category ID	☐	
errorCodes	string	Error Codes	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
keywords	string	Keywords	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
publish	int32	Publish	☐	
referenceLink	string	Reference Link	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

162 Schema: DocumentTagAssociations

162.1 Tables

162.1.1 DocumentTagAssociations

Catalog: Autotask

Schema: DocumentTagAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTagAssociations are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

162.1.2 DocumentTagAssociationsById

Catalog: Autotask

Schema: DocumentTagAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentTagAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function DocumentTagAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

162.1.3 DocumentTagAssociationsCount

Catalog: Autotask

Schema: DocumentTagAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTagAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

163 Schema: DocumentTagAssociationsChild

163.1 Tables

163.1.1 DocumentsByParentIdTagAssociations

Catalog: Autotask

Schema: DocumentTagAssociationsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTagAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTagAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

163.1.2 DocumentsByParentIdTagAssociationsId

Catalog: Autotask

Schema: DocumentTagAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTagAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTagAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

164 Schema: DocumentTicketAssociations

164.1 Tables

164.1.1 DocumentTicketAssociations

Catalog: Autotask

Schema: DocumentTicketAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTicketAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

164.1.2 DocumentTicketAssociationsById

Catalog: Autotask

Schema: DocumentTicketAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function DocumentTicketAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentTicketAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

164.1.3 DocumentTicketAssociationsCount

Catalog: Autotask

Schema: DocumentTicketAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table DocumentTicketAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

165 Schema: DocumentTicketAssociationsChild

165.1 Tables

165.1.1 DocumentsByParentIdTicketAssociations

Catalog: Autotask

Schema: DocumentTicketAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTicketAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTicketAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

165.1.2 DocumentsByParentIdTicketAssociationsId

Catalog: Autotask

Schema: DocumentTicketAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTicketAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTicketAssociationsId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

166 Schema: DocumentToArticleAssociations

166.1 Tables

166.1.1 DocumentToArticleAssociations

Catalog: Autotask

Schema: DocumentToArticleAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToArticleAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
associatedArticleID	int32	Associated Article ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	

166.1.2 DocumentToArticleAssociationsById

Catalog: Autotask

Schema: DocumentToArticleAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentToArticleAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentToArticleAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
associatedArticleID	int32	Associated Article ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

166.1.3 DocumentToArticleAssociationsCount

Catalog: Autotask

Schema: DocumentToArticleAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToArticleAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

167 Schema: DocumentToArticleAssociationsChild

167.1 Tables

167.1.1 DocumentsByParentIdArticleAssociations

Catalog: Autotask

Schema: DocumentToArticleAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdArticleAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdArticleAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
associatedArticleID	int32	Associated Article ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

167.1.2 DocumentsByParentIdArticleAssociationsId

Catalog: Autotask

Schema: DocumentToArticleAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdArticleAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdArticleAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
associatedArticleID	int32	Associated Article ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

168 Schema: DocumentToDocumentAssociations

168.1 Tables

168.1.1 DocumentToDocumentAssociations

Catalog: Autotask

Schema: DocumentToDocumentAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToDocumentAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
associatedDocumentID	int32	Associated Document ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

168.1.2 DocumentToDocumentAssociationsById

Catalog: Autotask

Schema: DocumentToDocumentAssociations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentToDocumentAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function DocumentToDocumentAssociationsById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
associatedDocumentID	int32	Associated Document ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

168.1.3 DocumentToDocumentAssociationsCount

Catalog: Autotask

Schema: DocumentToDocumentAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToDocumentAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

169 Schema: DocumentToDocumentAssociationsChild

169.1 Tables

169.1.1 DocumentsByParentIdDocumentAssociations

Catalog: Autotask

Schema: DocumentToDocumentAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdDocumentAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdDocumentAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
associatedDocumentID	int32	Associated Document ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

169.1.2 DocumentsByParentIdDocumentAssociationsId

Catalog: Autotask

Schema: DocumentToDocumentAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdDocumentAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdDocumentAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
associatedDocumentID	int32	Associated Document ID	☐	
documentID	int32	Document ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

170 Schema: DomainRegistrars

170.1 Tables

170.1.1 DomainRegistrars

Catalog: Autotask

Schema: DomainRegistrars

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DomainRegistrars are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
name	string	Name	☐	
url	string	URL	☐	

170.1.2 DomainRegistrarsById

Catalog: Autotask

Schema: DomainRegistrars

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DomainRegistrarsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function DomainRegistrarsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
name	string	Name	☐	
url	string	URL	☐	

170.1.3 DomainRegistrarsCount

Catalog: Autotask

Schema: DomainRegistrars

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DomainRegistrarsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

171 Schema: ExpenseItemAttachments

171.1 Tables

171.1.1 ExpenseItemAttachments

Catalog: Autotask

Schema: ExpenseItemAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

171.1.2 ExpenseItemAttachmentsById

Catalog: Autotask

Schema: ExpenseItemAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpenseItemAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ExpenseItemAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

171.1.3 ExpenseItemAttachmentsCount

Catalog: Autotask

Schema: ExpenseItemAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

172 Schema: ExpenseItemAttachmentsChild

172.1 Tables

172.1.1 ExpenseItemsByParentIdAttachments

Catalog: Autotask

Schema: ExpenseItemAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpenseItemsByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ExpenseItemsByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

172.1.2 ExpenseItemsByParentIdAttachmentsId

Catalog: Autotask

Schema: ExpenseItemAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpenseItemsByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ExpenseItemsByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

173 Schema: ExpenseItems

173.1 Tables

173.1.1 ExpenseItems

Catalog: Autotask

Schema: ExpenseItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
description	string	Description	☐	
destination	string	Destination	☐	
entertainmentLocation	string	Entertainment Location	☐	
expenseCategory	int32	Expense Category	☐	
expenseCurrencyExpenseAmount	double	Expense Currency Expense Amount	☐	
expenseCurrencyID	int32	Expense Currency ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
expenseDate	datetime	Expense Date	☐	
expenseReportID	int32	Expense Report ID	☐	
glCode	string	GL Code	☐	
haveReceipt	boolean	Have Receipt	☐	
id	int64	ID	☐	
internalCurrencyExpenseAmount	double	Internal Currency Expense Amount	☐	
internalCurrencyReimbursementAmount	double	Internal Currency Reimbursement Amount	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isReimbursable	boolean	Is Reimbursable	☐	
isRejected	boolean	Is Rejected	☐	
miles	double	Miles	☐	
odometerEnd	double	Odometer End	☐	
odometerStart	double	Odometer Start	☐	
origin	string	Origin	☐	
paymentType	int32	Payment Type	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
reimbursementCurrencyReimbursementAmount	double	Reimbursement Currency and Amount	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	
w orkType	int32	Work Type	☐	

173.1.2 ExpenseItemsById

Catalog: Autotask

Schema: ExpenseItems

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpenseItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ExpenseItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
description	string	Description	☐	
destination	string	Destination	☐	
entertainmentLocation	string	Entertainment Location	☐	
expenseCategory	int32	Expense Category	☐	
expenseCurrencyExpenseAmount	double	Expense Currency Expense Amount	☐	
expenseCurrencyID	int32	Expense Currency ID	☐	
expenseDate	datetime	Expense Date	☐	
expenseReportID	int32	Expense Report ID	☐	
glCode	string	GL Code	☐	
haveReceipt	boolean	Have Receipt	☐	
id	int64	ID	☐	
internalCurrencyExpenseAmount	double	Internal Currency Expense Amount	☐	
internalCurrencyReimbursementAmount	double	Internal Currency Reimbursement Amount	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReimbursable	boolean	Is Reimbursable	☐	
isRejected	boolean	Is Rejected	☐	
miles	double	Miles	☐	
odometerEnd	double	Odometer End	☐	
odometerStart	double	Odometer Start	☐	
origin	string	Origin	☐	
paymentType	int32	Payment Type	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
reimbursementCurrencyReimbursementAmount	double	Reimbursement Currency and Amount	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	
w orkType	int32	Work Type	☐	

173.1.3 ExpenseItemsCount

Catalog: Autotask

Schema: ExpenseItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

174 Schema: ExpenseItemsChild

174.1 Tables

174.1.1 ExpensesByParentIdItems

Catalog: Autotask

Schema: ExpenseItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpensesByParentIdItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ExpensesByParentIdItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
description	string	Description	☐	
destination	string	Destination	☐	
entertainmentLocation	string	Entertainment Location	☐	
expenseCategory	int32	Expense Category	☐	
expenseCurrencyExpenseAmount	double	Expense Currency Expense Amount	☐	
expenseCurrencyID	int32	Expense Currency ID	☐	
expenseDate	datetime	Expense Date	☐	
expenseReportID	int32	Expense Report ID	☐	
glCode	string	GL Code	☐	
haveReceipt	boolean	Have Receipt	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
internalCurrencyExpenseAmount	double	Internal Currency Expense Amount	☐	
internalCurrencyReimbursementAmount	double	Internal Currency Reimbursement Amount	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isReimbursable	boolean	Is Reimbursable	☐	
isRejected	boolean	Is Rejected	☐	
miles	double	Miles	☐	
odometerEnd	double	Odometer End	☐	
odometerStart	double	Odometer Start	☐	
origin	string	Origin	☐	
paymentType	int32	Payment Type	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
reimbursementCurrencyReimbursementAmount	double	Reimbursement Currency and Amount	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	
w orkType	int32	Work Type	☐	

174.1.2 ExpensesByParentIdItemsId

Catalog: Autotask

Schema: ExpenseItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ExpensesByParentIdItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ExpensesByParentIdItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
description	string	Description	☐	
destination	string	Destination	☐	
entertainmentLocation	string	Entertainment Location	☐	
expenseCategory	int32	Expense Category	☐	
expenseCurrencyExpenseAmount	double	Expense Currency Expense Amount	☐	
expenseCurrencyID	int32	Expense Currency ID	☐	
expenseDate	datetime	Expense Date	☐	
expenseReportID	int32	Expense Report ID	☐	
glCode	string	GL Code	☐	
haveReceipt	boolean	Have Receipt	☐	
id	int64	ID	☐	
internalCurrencyExpenseAmount	double	Internal Currency Expense Amount	☐	
internalCurrencyReimbursementAmount	double	Internal Currency Reimbursement Amount	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isReimbursable	boolean	Is Reimbursable	☐	
isRejected	boolean	Is Rejected	☐	
miles	double	Miles	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
odometerEnd	double	Odometer End	☐	
odometerStart	double	Odometer Start	☐	
origin	string	Origin	☐	
paymentType	int32	Payment Type	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
reimbursementCurrencyReimbursementAmount	double	Reimbursement Currency and Amount	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	
w orkType	int32	Work Type	☐	

175 Schema: ExpenseReportAttachments

175.1 Tables

175.1.1 ExpenseReportAttachments

Catalog: Autotask

Schema: ExpenseReportAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

175.1.2 ExpenseReportAttachmentsById

Catalog: Autotask

Schema: ExpenseReportAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpenseReportAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ExpenseReportAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

175.1.3 ExpenseReportAttachmentsCount

Catalog: Autotask

Schema: ExpenseReportAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

176 Schema: ExpenseReportAttachmentsChild

176.1 Tables

176.1.1 ExpenseReportsByParentIdAttachments

Catalog: Autotask

Schema: ExpenseReportAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpenseReportsByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ExpenseReportsByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

176.1.2 ExpenseReportsByParentIdAttachmentsId

Catalog: Autotask

Schema: ExpenseReportAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpenseReportsByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ExpenseReportsByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
expenseItemID	int32	Expense Item ID	☐	
expenseReportID	int32	Expense Report ID	☐	
fileSize	double	File Size	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

177 Schema: ExpenseReports

177.1 Tables

177.1.1 ExpenseReports

Catalog: Autotask

Schema: ExpenseReports

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReports are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amountDue	double	Amount Due	☐	
approvedDate	datetime	Approved Date	☐	
approverID	int32	Approver ID	☐	
departmentNumber	string	Department Number	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
internalCurrencyCashAdvanceAmount	double	Internal Currency Cash Advance Amount	☐	
internalCurrencyExpenseTotal	double	Internal Currency Expense Total	☐	
name	string	Name	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
quickBooksReferenceNumber	string	Quickbooks Reference Number	☐	
reimbursementCurrencyAmountDue	double	Reimbursement Currency Amount Due	☐	
reimbursementCurrencyCashAdvanceAmount	double	Reimbursement Currency Cash Advance Amount	☐	
reimbursementCurrencyID	int32	Reimbursement Currency ID	☐	
rejectionReason	string	Rejection Reason	☐	
status	int32	Status	☐	
submit	boolean	Submit	☐	
submitDate	datetime	Submit Date	☐	
submitterID	int32	Submitter ID	☐	
weekEnding	datetime	Weekending	☐	

177.1.2 ExpenseReportsById

Catalog: Autotask

Schema: ExpenseReports

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpenseReportsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ExpenseReportsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
amountDue	double	Amount Due	☐	
approvedDate	datetime	Approved Date	☐	
approverID	int32	Approver ID	☐	
departmentNumber	string	Department Number	☐	
id	int64	ID	☐	
internalCurrencyCashAdvanceAmount	double	Internal Currency Cash Advance Amount	☐	
internalCurrencyExpenseTotal	double	Internal Currency Expense Total	☐	
name	string	Name	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
quickBooksReferenceNumber	string	Quickbooks Reference Number	☐	
reimbursementCurrencyAmountDue	double	Reimbursement Currency Amount Due	☐	
reimbursementCurrencyCashAdvanceAmount	double	Reimbursement Currency Cash Advance Amount	☐	
reimbursementCurrencyID	int32	Reimbursement Currency ID	☐	
rejectionReason	string	Rejection Reason	☐	
status	int32	Status	☐	
submit	boolean	Submit	☐	
submitDate	datetime	Submit Date	☐	
submitterID	int32	Submitter ID	☐	
w eekEnding	datetime	Weekending	☐	

177.1.3 ExpenseReportsCount

Catalog: Autotask

Schema: ExpenseReports

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ExpenseReportsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

178 Schema: Holidays

178.1 Tables

178.1.1 Holidays

Catalog: Autotask

Schema: Holidays

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Holidays are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
holidayDate	datetime	Holiday Date	☐	
holidayName	string	Holiday Name	☐	
holidaySetID	int32	Holiday Set ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

178.1.2 HolidaysById

Catalog: Autotask

Schema: Holidays

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function HolidaysById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function HolidaysById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
holidayDate	datetime	Holiday Date	☐	
holidayName	string	Holiday Name	☐	
holidaySetID	int32	Holiday Set ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

178.1.3 HolidaysCount

Catalog: Autotask

Schema: Holidays

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaysCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

179 Schema: HolidaysChild

179.1 Tables

179.1.1 HolidaySetsByParentIdHolidays

Catalog: Autotask

Schema: HolidaysChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function HolidaySetsByParentIdHolidays. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function HolidaySetsByParentIdHolidays are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
holidayDate	datetime	Holiday Date	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
holidayName	string	Holiday Name	☐	
holidaySetID	int32	Holiday Set ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

179.1.2 HolidaySetsByParentIdHolidaysId

Catalog: Autotask

Schema: HolidaysChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function HolidaySetsByParentIdHolidaysId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function HolidaySetsByParentIdHolidaysId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
holidayDate	datetime	Holiday Date	☐	
holidayName	string	Holiday Name	☐	
holidaySetID	int32	Holiday Set ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

180 Schema: HolidaySets

180.1 Tables

180.1.1 HolidaySets

Catalog: Autotask

Schema: HolidaySets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaySets are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
holidaySetDescription	string	Holiday Set Description	☐	
holidaySetName	string	Holiday Set Name	☐	
id	int64	ID	☐	

180.1.2 HolidaySetsById

Catalog: Autotask

Schema: HolidaySets

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function HolidaySetsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function HolidaySetsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
holidaySetDescription	string	Holiday Set Description	☐	
holidaySetName	string	Holiday Set Name	☐	
id	int64	ID	☐	

180.1.3 HolidaySetsCount

Catalog: Autotask

Schema: HolidaySets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaySetsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

181 Schema: IntegrationVendorInsights

181.1 Tables

181.1.1 IntegrationVendorInsights

Catalog: Autotask

Schema: IntegrationVendorInsights

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorInsights are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
description	string	Description	☐	
height	int32	Height	☐	
id	int64	ID	☐	
insightCategory	int32	Insight Category	☐	
insightKey	string	Insight Key	☐	
isActive	boolean	Is Active	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
referenceUrl	string	Reference URL	☐	
secret	string	Secret	☐	
title	string	Title	☐	
vendorSuppliedID	string	Vendor Supplied ID	☐	

181.1.2 IntegrationVendorInsightsById

Catalog: Autotask

Schema: IntegrationVendorInsights

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IntegrationVendorInsightsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function IntegrationVendorInsightsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
description	string	Description	☐	
height	int32	Height	☐	
id	int64	ID	☐	
insightCategory	int32	Insight Category	☐	
insightKey	string	Insight Key	☐	
isActive	boolean	Is Active	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
referenceUrl	string	Reference URL	☐	
secret	string	Secret	☐	
title	string	Title	☐	
vendorSuppliedID	string	Vendor Supplied ID	☐	

181.1.3 IntegrationVendorInsightsCount

Catalog: Autotask

Schema: IntegrationVendorInsights

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorInsightsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

182 Schema: IntegrationVendorWidgets

182.1 Tables

182.1.1 IntegrationVendorWidgets

Catalog: Autotask

Schema: IntegrationVendorWidgets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorWidgets are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
referenceUrl	string	Reference URL	☐	
secret	string	Secret	☐	
title	string	Title	☐	
vendorSuppliedID	string	Vendor Supplied ID	☐	
w idgetKey	string	Widget Key	☐	
w idth	int32	Width	☐	

182.1.2 IntegrationVendorWidgetsById

Catalog: Autotask

Schema: IntegrationVendorWidgets

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IntegrationVendorWidgetsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function IntegrationVendorWidgetsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
referenceUrl	string	Reference URL	☐	
secret	string	Secret	☐	
title	string	Title	☐	
vendorSuppliedID	string	Vendor Supplied ID	☐	
widgetKey	string	Widget Key	☐	
width	int32	Width	☐	

182.1.3 IntegrationVendorWidgetsCount

Catalog: Autotask

Schema: IntegrationVendorWidgets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorWidgetsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

183 Schema: InternalLocations

183.1 Tables

183.1.1 InternalLocations

Catalog: Autotask

Schema: InternalLocations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInfo	string	Additional Address Information	☐	
address1	string	Address 1	☐	
address2	string	Address 2	☐	
city	string	City	☐	
country	string	Country	☐	
holidaySetId	int64	Holiday Set ID	☐	
id	int64	ID	☐	
isDefault	boolean	Is Default	☐	
name	string	Name	☐	
postalCode	string	Postal Code	☐	
state	string	State	☐	
timeZone	string	Timezone	☐	

183.1.2 InternalLocationsById

Catalog: Autotask

Schema: InternalLocations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InternalLocationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InternalLocationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInfo	string	Additional Address Information	☐	
address1	string	Address 1	☐	
address2	string	Address 2	☐	
city	string	City	☐	
country	string	Country	☐	
holidaySetId	int64	Holiday Set ID	☐	
id	int64	ID	☐	
isDefault	boolean	Is Default	☐	
name	string	Name	☐	
postalCode	string	Postal Code	☐	
state	string	State	☐	
timeZone	string	Timezone	☐	

183.1.3 InternalLocationsCount

Catalog: Autotask

Schema: InternalLocations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

184 Schema: InternalLocationWithBusinessHours

184.1 Tables

184.1.1 InternalLocationWithBusinessHours

Catalog: Autotask

Schema: InternalLocationWithBusinessHours

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationWithBusinessHours are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInfo	string	Additional Address Information	☐	
address1	string	Address 1	☐	
address2	string	Address 2	☐	
city	string	City	☐	
countryID	int32	Country ID	☐	
dateFormat	string	Date Format	☐	
firstDayOfWeek	int32	First Day of Week	☐	
fridayBusinessHoursEndTime	datetime	Friday Business Hours End Time	☐	
fridayBusinessHoursStartTime	datetime	Friday Business Hours Start Time	☐	
fridayExtendedHoursEndTime	datetime	Friday Extended Hours End Time	☐	
fridayExtendedHoursStartTime	datetime	Friday Extended Hours Start Time	☐	
holidayExtendedHoursEndTime	datetime	Holiday Extended Hourse End Time	☐	
holidayExtendedHoursStartTime	datetime	Holiday Extended Hours Start Time	☐	
holidayHoursEndTime	datetime	Holiday Hours End Time	☐	
holidayHoursStartTime	datetime	Holiday Hours Start Time	☐	
holidayHoursType	int32	Holiday Hours Type	☐	
holidaySetID	int32	Holiday Set ID	☐	
id	int64	ID	☐	
isDefault	boolean	Is Default	☐	
mondayBusinessHoursEndTime	datetime	Monday Business Hours End Time	☐	
mondayBusinessHoursStartTime	datetime	Monday Business Hours Start Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
mondayExtendedHoursEndTime	datetime	Monday Extended Hours End Time	☐	
mondayExtendedHoursStartTime	datetime	Monday Extended Hours Start Time	☐	
name	string	Name	☐	
noHoursOnHolidays	boolean	No Hours on Holidays	☐	
numberFormat	string	Number Format	☐	
postalCode	string	Postal Code	☐	
saturdayBusinessHoursEndTime	datetime	Saturday Business Hours End Time	☐	
saturdayBusinessHoursStartTime	datetime	Saturday Business Hours Start Time	☐	
saturdayExtendedHoursEndTime	datetime	Saturday Extended Hours End Time	☐	
saturdayExtendedHoursStartTime	datetime	Saturday Extended Hours Start Time	☐	
state	string	State	☐	
sundayBusinessHoursEndTime	datetime	Sunday Business Hours End Time	☐	
sundayBusinessHoursStartTime	datetime	Sunday Business Hours Start Time	☐	
sundayExtendedHoursEndTime	datetime	Sunday Extended Hours End Time	☐	
sundayExtendedHoursStartTime	datetime	Sunday Extended Hours Start Time	☐	
thursdayBusinessHoursEndTime	datetime	Thursday Business Hours End Time	☐	
thursdayBusinessHoursStartTime	datetime	Thursday Business Hours Start Time	☐	
thursdayExtendedHoursEndTime	datetime	Thursday Extended Hours End Time	☐	
thursdayExtendedHoursStartTime	datetime	Thursday Extended Hours Start Time	☐	
timeFormat	string	Time Format	☐	
timeZoneID	int32	Time Zone ID	☐	
tuesdayBusinessHoursEndTime	datetime	Tuesday Business Hours End Time	☐	
tuesdayBusinessHoursStartTime	datetime	Tuesday Business Hours Start Time	☐	
tuesdayExtendedHoursEndTime	datetime	Tuesday Extended Hours End Time	☐	
tuesdayExtendedHoursStartTime	datetime	Tuesday Extended Hours Start Time	☐	
w ednesdayBusinessHoursEndTim e	datetime	Wednesday Business Hours End Time	☐	
w ednesdayBusinessHoursStartTi me	datetime	Wednesday Business Hours Start Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
wednesdayExtendedHoursEndTime	datetime	Wednesday Extended Hours End Time	☐	
wednesdayExtendedHoursStartTime	datetime	Wednesday Extended Hours Start Time	☐	

184.1.2 InternalLocationWithBusinessHoursById

Catalog: Autotask

Schema: InternalLocationWithBusinessHours

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InternalLocationWithBusinessHoursById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InternalLocationWithBusinessHoursById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalAddressInfo	string	Additional Address Information	☐	
address1	string	Address 1	☐	
address2	string	Address 2	☐	
city	string	City	☐	
countryID	int32	Country ID	☐	
dateFormat	string	Date Format	☐	
firstDayOfWeek	int32	First Day of Week	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fridayBusinessHoursEndTime	datetime	Friday Business Hours End Time	☐	
fridayBusinessHoursStartTime	datetime	Friday Business Hours Start Time	☐	
fridayExtendedHoursEndTime	datetime	Friday Extended Hours End Time	☐	
fridayExtendedHoursStartTime	datetime	Friday Extended Hours Start Time	☐	
holidayExtendedHoursEndTime	datetime	Holiday Extended Hourse End Time	☐	
holidayExtendedHoursStartTime	datetime	Holiday Extended Hours Start Time	☐	
holidayHoursEndTime	datetime	Holiday Hours End Time	☐	
holidayHoursStartTime	datetime	Holiday Hours Start Time	☐	
holidayHoursType	int32	Holiday Hours Type	☐	
holidaySetID	int32	Holiday Set ID	☐	
id	int64	ID	☐	
isDefault	boolean	Is Default	☐	
mondayBusinessHoursEndTime	datetime	Monday Business Hours End Time	☐	
mondayBusinessHoursStartTime	datetime	Monday Business Hours Start Time	☐	
mondayExtendedHoursEndTime	datetime	Monday Extended Hours End Time	☐	
mondayExtendedHoursStartTime	datetime	Monday Extended Hours Start Time	☐	
name	string	Name	☐	
noHoursOnHolidays	boolean	No Hours on Holidays	☐	
numberFormat	string	Number Format	☐	
postalCode	string	Postal Code	☐	
saturdayBusinessHoursEndTime	datetime	Saturday Business Hours End Time	☐	
saturdayBusinessHoursStartTime	datetime	Saturday Business Hours Start Time	☐	
saturdayExtendedHoursEndTime	datetime	Saturday Extended Hours End Time	☐	
saturdayExtendedHoursStartTime	datetime	Saturday Extended Hours Start Time	☐	
state	string	State	☐	
sundayBusinessHoursEndTime	datetime	Sunday Business Hours End Time	☐	
sundayBusinessHoursStartTime	datetime	Sunday Business Hours Start Time	☐	
sundayExtendedHoursEndTime	datetime	Sunday Extended Hours End Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sundayExtendedHoursStartTime	datetime	Sunday Extended Hours Start Time	☐	
thursdayBusinessHoursEndTime	datetime	Thursday Business Hours End Time	☐	
thursdayBusinessHoursStartTime	datetime	Thursday Business Hours Start Time	☐	
thursdayExtendedHoursEndTime	datetime	Thursday Extended Hours End Time	☐	
thursdayExtendedHoursStartTime	datetime	Thursday Extended Hours Start Time	☐	
timeFormat	string	Time Format	☐	
timeZoneID	int32	Time Zone ID	☐	
tuesdayBusinessHoursEndTime	datetime	Tuesday Business Hours End Time	☐	
tuesdayBusinessHoursStartTime	datetime	Tuesday Business Hours Start Time	☐	
tuesdayExtendedHoursEndTime	datetime	Tuesday Extended Hours End Time	☐	
tuesdayExtendedHoursStartTime	datetime	Tuesday Extended Hours Start Time	☐	
w ednesdayBusinessHoursEndTim e	datetime	Wednesday Business Hours End Time	☐	
w ednesdayBusinessHoursStartTi me	datetime	Wednesday Business Hours Start Time	☐	
w ednesdayExtendedHoursEndTim e	datetime	Wednesday Extended Hours End Time	☐	
w ednesdayExtendedHoursStartTi me	datetime	Wednesday Extended Hours Start Time	☐	

184.1.3 InternalLocationWithBusinessHoursCount

Catalog: Autotask

Schema: InternalLocationWithBusinessHours

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationWithBusinessHoursCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

185 Schema: InventoryItems

185.1 Tables

185.1.1 InventoryItems

Catalog: Autotask

Schema: InventoryItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
backOrderQuantity	int32	Backorder Quantity	☐	
bin	string	Bin	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
inventoryLocationID	int32	Inventory Location ID	☐	
productID	int32	Product ID	☐	
quantityMaximum	int32	Quantity Maximum	☐	
quantityMinimum	int32	Quantity Minimum	☐	
quantityOnHand	int32	Quantity On-hand	☐	
quantityOnOrder	int32	Quantity On Order	☐	
quantityPicked	int32	Quantity Picked	☐	
quantityReserved	int32	Quantity Reserved	☐	
referenceNumber	string	Reference Number	☐	

185.1.2 InventoryItemsById

Catalog: Autotask

Schema: InventoryItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InventoryItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
backOrderQuantity	int32	Backorder Quantity	☐	
bin	string	Bin	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
inventoryLocationID	int32	Inventory Location ID	☐	
productID	int32	Product ID	☐	
quantityMaximum	int32	Quantity Maximum	☐	
quantityMinimum	int32	Quantity Minimum	☐	
quantityOnHand	int32	Quantity On-hand	☐	
quantityOnOrder	int32	Quantity On Order	☐	
quantityPicked	int32	Quantity Picked	☐	
quantityReserved	int32	Quantity Reserved	☐	
referenceNumber	string	Reference Number	☐	

185.1.3 InventoryItemsCount

Catalog: Autotask

Schema: InventoryItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemsCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

186 Schema: InventoryItemSerialNumbers

186.1 Tables

186.1.1 InventoryItemSerialNumbers

Catalog: Autotask

Schema: InventoryItemSerialNumbers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemSerialNumbers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
inventoryItemID	int32	Inventory Item ID	☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

186.1.2 InventoryItemSerialNumbersById

Catalog: Autotask

Schema: InventoryItemSerialNumbers

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemSerialNumbersById. A value must be provided at all times for required

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InventoryItemSerialNumbersById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
inventoryItemID	int32	Inventory Item ID	☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

186.1.3 InventoryItemSerialNumbersCount

Catalog: Autotask

Schema: InventoryItemSerialNumbers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table InventoryItemSerialNumbersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

187 Schema: InventoryItemSerialNumbersChild

187.1 Tables

187.1.1 InventoryItemsByParentIdSerialNumbers

Catalog: Autotask

Schema: InventoryItemSerialNumbersChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemsByParentIdSerialNumbers. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function InventoryItemsByParentIdSerialNumbers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
inventoryItemID	int32	Inventory Item ID	☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

187.1.2 InventoryItemsByParentIdSerialNumbersId

Catalog: Autotask

Schema: InventoryItemSerialNumbersChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemsByParentIdSerialNumbersId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function InventoryItemsByParentIdSerialNumbersId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
inventoryItemID	int32	Inventory Item ID	☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

188 Schema: InventoryLocations

188.1 Tables

188.1.1 InventoryLocations

Catalog: Autotask

Schema: InventoryLocations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryLocations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
locationName	string	Location Name	☐	
resourceID	int32	Resource ID	☐	

188.1.2 InventoryLocationsById

Catalog: Autotask

Schema: InventoryLocations

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryLocationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InventoryLocationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
locationName	string	Location Name	☐	
resourceID	int32	Resource ID	☐	

188.1.3 InventoryLocationsCount

Catalog: Autotask

Schema: InventoryLocations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table InventoryLocationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

189 Schema: InventoryProducts

189.1 Tables

189.1.1 InventoryProducts

Catalog: Autotask

Schema: InventoryProducts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryProducts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
availableUnits	int32		☐	
backOrderQuantity	int32	Backorder Quantity	☐	
bin	string	Bin	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
id	int64	ID	☐	
inventoryLocationID	int32	Inventory Location ID	☐	
onHandUnits	int32		☐	
pickedUnits	int32		☐	
productID	int32	Product ID	☐	
quantityMaximum	int32	Quantity Maximum	☐	
quantityMinimum	int32	Quantity Minimum	☐	
referenceNumber	string	Reference Number	☐	
reservedUnits	int32		☐	
unitsOnOrder	int32		☐	

189.1.2 InventoryProductsById

Catalog: Autotask

Schema: InventoryProducts

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InventoryProductsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
availableUnits	int32		☐	
backOrderQuantity	int32	Backorder Quantity	☐	
bin	string	Bin	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
id	int64	ID	☐	
inventoryLocationID	int32	Inventory Location ID	☐	
onHandUnits	int32		☐	
pickedUnits	int32		☐	
productID	int32	Product ID	☐	
quantityMaximum	int32	Quantity Maximum	☐	
quantityMinimum	int32	Quantity Minimum	☐	
referenceNumber	string	Reference Number	☐	
reservedUnits	int32		☐	
unitsOnOrder	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

189.1.3 InventoryProductsCount

Catalog: Autotask

Schema: InventoryProducts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryProductsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

190 Schema: InventoryStockedItems

190.1 Tables

190.1.1 InventoryStockedItems

Catalog: Autotask

Schema: InventoryStockedItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
availableUnits	int32		☐	
companyID	int32	Company ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
contractChargeID	int32	Contract Charge ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
currentInventoryLocationID	int32		☐	
deliveredUnits	int32		☐	
id	int64	ID	☐	
inventoryProductID	int32		☐	
onHandUnits	int32		☐	
parentInventoryStockedItemID	int32		☐	
parentStockedItemReceivedUnits	int32		☐	
pickedRemovedByResourceID	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
pickedRemovedDateTime	datetime		☐	
pickedUnits	int32		☐	
projectChargeID	int32	Project Charge ID	☐	
purchaseOrderID	int32		☐	
purchaseOrderItemID	int32	Purchase Order Item ID	☐	
purchaseOrderItemReceivingID	int32		☐	
quoteItemID	int32	Quote Item ID	☐	
removedUnits	int32		☐	
reservedUnits	int32		☐	
returnPrice	double		☐	
returnTypeID	int32		☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
statusID	int32		☐	
ticketChargeID	int32	Ticket Charge ID	☐	
transferredUnits	int32		☐	
unitCost	double	Unit Cost	☐	
vendorID	int32	Vendor ID	☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

190.1.2 InventoryStockedItemsById

Catalog: Autotask

Schema: InventoryStockedItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryStockedItemsById. A value must be provided at all times for required parameters,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InventoryStockedItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
availableUnits	int32		☐	
companyID	int32	Company ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
contractChargeID	int32	Contract Charge ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
currentInventoryLocationID	int32		☐	
deliveredUnits	int32		☐	
id	int64	ID	☐	
inventoryProductID	int32		☐	
onHandUnits	int32		☐	
parentInventoryStockedItemID	int32		☐	
parentStockedItemReceivedUnits	int32		☐	
pickedRemovedByResourceID	int32		☐	
pickedRemovedDateTime	datetime		☐	
pickedUnits	int32		☐	
projectChargeID	int32	Project Charge ID	☐	
purchaseOrderID	int32		☐	
purchaseOrderItemID	int32	Purchase Order Item ID	☐	
purchaseOrderItemReceivingID	int32		☐	
quoteItemID	int32	Quote Item ID	☐	
removedUnits	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reservedUnits	int32		☐	
returnPrice	double		☐	
returnTypeID	int32		☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
statusID	int32		☐	
ticketChargeID	int32	Ticket Charge ID	☐	
transferredUnits	int32		☐	
unitCost	double	Unit Cost	☐	
vendorID	int32	Vendor ID	☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

190.1.3 InventoryStockedItemsCount

Catalog: Autotask

Schema: InventoryStockedItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

191 Schema: InventoryStockedItemsChild

191.1 Tables

191.1.1 InventoryProductsByParentIdStockedItems

Catalog: Autotask

Schema: InventoryStockedItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
availableUnits	int32		☐	
companyID	int32	Company ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
contractChargeID	int32	Contract Charge ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
currentInventoryLocationID	int32		☐	
deliveredUnits	int32		☐	
id	int64	ID	☐	
inventoryProductID	int32		☐	
onHandUnits	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentInventoryStockedItemID	int32		☐	
parentStockedItemReceivedUnits	int32		☐	
pickedRemovedByResourceID	int32		☐	
pickedRemovedDateTime	datetime		☐	
pickedUnits	int32		☐	
projectChargeID	int32	Project Charge ID	☐	
purchaseOrderID	int32		☐	
purchaseOrderItemID	int32	Purchase Order Item ID	☐	
purchaseOrderItemReceivingID	int32		☐	
quoteItemID	int32	Quote Item ID	☐	
removedUnits	int32		☐	
reservedUnits	int32		☐	
returnPrice	double		☐	
returnTypeID	int32		☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
statusID	int32		☐	
ticketChargeID	int32	Ticket Charge ID	☐	
transferredUnits	int32		☐	
unitCost	double	Unit Cost	☐	
vendorID	int32	Vendor ID	☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

191.1.2 InventoryProductsByParentIdStockedItemsId

Catalog: Autotask

Schema: InventoryStockedItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
availableUnits	int32		☐	
companyID	int32	Company ID	☐	
configurationItemID	int32	Configuration Item ID	☐	
contractChargeID	int32	Contract Charge ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
currentInventoryLocationID	int32		☐	
deliveredUnits	int32		☐	
id	int64	ID	☐	
inventoryProductID	int32		☐	
onHandUnits	int32		☐	
parentInventoryStockedItemID	int32		☐	
parentStockedItemReceivedUnits	int32		☐	
pickedRemovedByResourceID	int32		☐	
pickedRemovedDateTime	datetime		☐	
pickedUnits	int32		☐	
projectChargeID	int32	Project Charge ID	☐	
purchaseOrderID	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
purchaseOrderItemID	int32	Purchase Order Item ID	☐	
purchaseOrderItemReceivingID	int32		☐	
quoteItemID	int32	Quote Item ID	☐	
removedUnits	int32		☐	
reservedUnits	int32		☐	
returnPrice	double		☐	
returnTypeID	int32		☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
statusID	int32		☐	
ticketChargeID	int32	Ticket Charge ID	☐	
transferredUnits	int32		☐	
unitCost	double	Unit Cost	☐	
vendorID	int32	Vendor ID	☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

192 Schema: InventoryTransfers

192.1 Tables

192.1.1 InventoryTransfers

Catalog: Autotask

Schema: InventoryTransfers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryTransfers are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fromLocationID	int64	From Location ID	☐	
id	int64	ID	☐	
notes	string	Notes	☐	
productID	int64	Product ID	☐	
quantityTransferred	int32	Quantity Transferred	☐	
serialNumber	string	Serial Number	☐	
toLocationID	int64	To Location ID	☐	
transferByResourceID	int32	Transfer by Resource ID	☐	
transferDate	datetime	Transfer Date	☐	
updateNote	string	Update Note	☐	

192.1.2 InventoryTransfersById

Catalog: Autotask

Schema: InventoryTransfers

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryTransfersById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InventoryTransfersById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fromLocationID	int64	From Location ID	☐	
id	int64	ID	☐	
notes	string	Notes	☐	
productID	int64	Product ID	☐	
quantityTransferred	int32	Quantity Transferred	☐	
serialNumber	string	Serial Number	☐	
toLocationID	int64	To Location ID	☐	
transferByResourceID	int32	Transfer by Resource ID	☐	
transferDate	datetime	Transfer Date	☐	
updateNote	string	Update Note	☐	

192.1.3 InventoryTransfersCount

Catalog: Autotask

Schema: InventoryTransfers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryTransfersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

193 Schema: InvoiceMarkupApiIntegration

193.1 Tables

193.1.1 InvoicesByIdInvoiceMarkupHtml

Catalog: Autotask

Schema: InvoiceMarkupApiIntegration

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InvoicesByIdInvoiceMarkupHtml. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int32	☑		

Columns of Table Function

The columns of the table function InvoicesByIdInvoiceMarkupHtml are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
invoiceMarkup	string	Invoice Markup	☐	

193.1.2 InvoicesByIdInvoiceMarkupXml

Catalog: Autotask

Schema: InvoiceMarkupApiIntegration

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InvoicesByIdInvoiceMarkupXml. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int32	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function InvoicesByIdInvoiceMarkupXml are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
invoiceMarkup	string	Invoice Markup	☐	

194 Schema: Invoices

194.1 Tables

194.1.1 Invoices

Catalog: Autotask

Schema: Invoices

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Invoices are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
batchID	int32	Batch ID	☐	
comments	string	Comments	☐	
companyID	int32	Company ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
dueDate	datetime	Due Date	☐	
fromDate	datetime	From Date	☐	
id	int64	ID	☐	
invoiceDateTime	datetime	Invoice Date/Time	☐	
invoiceEditorTemplateID	int32	Invoice Editor Template ID	☐	
invoiceNumber	string	Invoice Number	☐	
invoiceTotal	double	Invoice Total	☐	
isVoided	boolean	Is Voided	☐	
orderNumber	string	Order Number	☐	
paidDate	datetime	Paid Date	☐	
paymentTerm	int32	Payment Term	☐	
taxGroup	int32	Tax Group	☐	
taxRegionName	string	Tax Region Name	☐	
toDate	datetime	To Date	☐	
totalTaxValue	double	Total Tax Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voidedByResourceID	int32	Voided by Resource ID	☐	
voidedDate	datetime	Voided Date	☐	
w ebServiceDate	datetime	Webservice Date	☐	

194.1.2 InvoicesById

Catalog: Autotask

Schema: Invoices

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InvoicesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InvoicesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
batchID	int32	Batch ID	☐	
comments	string	Comments	☐	
companyID	int32	Company ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
dueDate	datetime	Due Date	☐	
fromDate	datetime	From Date	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
invoiceDateTime	datetime	Invoice Date/Time	☐	
invoiceEditorTemplateID	int32	Invoice Editor Template ID	☐	
invoiceNumber	string	Invoice Number	☐	
invoiceTotal	double	Invoice Total	☐	
isVoided	boolean	Is Voided	☐	
orderNumber	string	Order Number	☐	
paidDate	datetime	Paid Date	☐	
paymentTerm	int32	Payment Term	☐	
taxGroup	int32	Tax Group	☐	
taxRegionName	string	Tax Region Name	☐	
toDate	datetime	To Date	☐	
totalTaxValue	double	Total Tax Value	☐	
voidedByResourceID	int32	Voided by Resource ID	☐	
voidedDate	datetime	Voided Date	☐	
webServiceDate	datetime	Webservice Date	☐	

194.1.3 InvoicesCount

Catalog: Autotask

Schema: Invoices

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoicesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

195 Schema: InvoiceTemplates

195.1 Tables

195.1.1 InvoiceTemplates

Catalog: Autotask

Schema: InvoiceTemplates

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table InvoiceTemplates are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
coveredByBlockRetainerContractLabel	string	Covered by Block Retainer Contract Label	☐	
coveredByRecurringServiceFixedPricePerTicketContractLabel	string	Covered by Recurring Service Fixed Price per Ticket Contract Label	☐	
currencyNegativeFormat	string	Currency Negative Format	☐	
currencyPositiveFormat	string	Currency Positive Format	☐	
dateFormat	int32	Date Format	☐	
displayFixedPriceContractLabor	boolean	Display Fixed Price Contract Labor	☐	
displayRecurringServiceContractLabor	boolean	Display Recurring Service Contract Labor	☐	
displaySeparateLineItemForEachTax	boolean	Display Separate Line Item for each Tax	☐	
displayTaxCategory	boolean	Display Tax Category	☐	
displayTaxCategorySuperscripts	boolean	Display Tax Category Super Scripts	☐	
displayZeroAmountRecurringServicesAndBundles	boolean	Display Zero Amount Recurring Services and Bundles	☐	
groupBy	int32	Group by	☐	
id	int64	ID	☐	
itemizeItemsInEachGroup	int32	Itemize Items in each Group	☐	
itemizeServicesAndBundles	boolean	Itemize Services and Bundles	☐	
name	string	Name	☐	
nonBillableLaborLabel	string	Non-billable Labor Label	☐	
numberFormat	int32	Number Format	☐	
pageLayout	int32	Page Layout	☐	
pageNumberFormat	int32	Page Number Format	☐	
paymentTerms	int32	Payment Terms	☐	
rateCostExpression	string	Rate Cost Expression	☐	
showGridHeader	boolean	Show Grid Header	☐	
showVerticalGridLines	boolean	Show Vertical Grid Lines	☐	
sortBy	int32	Sort by	☐	
timeFormat	int32	Time Format	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

195.1.2 InvoiceTemplatesById

Catalog: Autotask

Schema: InvoiceTemplates

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InvoiceTemplatesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function InvoiceTemplatesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
coveredByBlockRetainerContractLabel	string	Covered by Block Retainer Contract Label	☐	
coveredByRecurringServiceFixedPricePerTicketContractLabel	string	Covered by Recurring Service Fixed Price per Ticket Contract Label	☐	
currencyNegativeFormat	string	Currency Negative Format	☐	
currencyPositiveFormat	string	Currency Positive Format	☐	
dateFormat	int32	Date Format	☐	
displayFixedPriceContractLabor	boolean	Display Fixed Price Contract Labor	☐	
displayRecurringServiceContractLabor	boolean	Display Recurring Service Contract	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
		Labor		
displaySeparateLineItemForEachTax	boolean	Display Separate Line Item for each Tax	☐	
displayTaxCategory	boolean	Display Tax Category	☐	
displayTaxCategorySuperscripts	boolean	Display Tax Category Super Scripts	☐	
displayZeroAmountRecurringServicesAndBundles	boolean	Display Zero Amount Recurring Services and Bundles	☐	
groupBy	int32	Group by	☐	
id	int64	ID	☐	
itemizeItemsInEachGroup	int32	Itemize Items in each Group	☐	
itemizeServicesAndBundles	boolean	Itemize Services and Bundles	☐	
name	string	Name	☐	
nonBillableLaborLabel	string	Non-billable Labor Label	☐	
numberFormat	int32	Number Format	☐	
pageLayout	int32	Page Layout	☐	
pageNumberFormat	int32	Page Number Format	☐	
paymentTerms	int32	Payment Terms	☐	
rateCostExpression	string	Rate Cost Expression	☐	
showGridHeader	boolean	Show Grid Header	☐	
showVerticalGridLines	boolean	Show Vertical Grid Lines	☐	
sortBy	int32	Sort by	☐	
timeFormat	int32	Time Format	☐	

195.1.3 InvoiceTemplatesCount

Catalog: Autotask

Schema: InvoiceTemplates

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoiceTemplatesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

196 Schema: KnowledgeBaseArticles

196.1 Tables

196.1.1 KnowledgeBaseArticles

Catalog: Autotask

Schema: KnowledgeBaseArticles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseArticles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleCategoryID	int32	Article Category ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
errorCodes	string	Error Codes	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
keywords	string	Keywords	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
publish	int32	Publish	☐	
referenceLink	string	Reference Link	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

196.1.2 KnowledgeBaseArticlesById

Catalog: Autotask

Schema: KnowledgeBaseArticles

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleCategoryID	int32	Article Category ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
errorCodes	string	Error Codes	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
keywords	string	Keywords	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
publish	int32	Publish	☐	
referenceLink	string	Reference Link	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

196.1.3 KnowledgeBaseArticlesCount

Catalog: Autotask

Schema: KnowledgeBaseArticles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseArticlesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

197 Schema: KnowledgeBaseArticlesChild

197.1 Tables

197.1.1 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticles

Catalog: Autotask

Schema: KnowledgeBaseArticlesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticles. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleCategoryID	int32	Article Category ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
errorCodes	string	Error Codes	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
keywords	string	Keywords	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
publish	int32	Publish	☐	
referenceLink	string	Reference Link	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

197.1.2 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesId

Catalog: Autotask

Schema: KnowledgeBaseArticlesChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
articleCategoryID	int32	Article Category ID	☐	
createdByResourceID	int32	Created by Resource ID	☐	
createdDateTime	datetime	Created	☐	
errorCodes	string	Error Codes	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
keyw ords	string	Keyw ords	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
publish	int32	Publish	☐	
referenceLink	string	Reference Link	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

198 Schema: KnowledgeBaseCategories

198.1 Tables

198.1.1 KnowledgeBaseCategories

Catalog: Autotask

Schema: KnowledgeBaseCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseCategories are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
name	string	Name	☐	
parentCategoryID	int32	Parent Category ID	☐	

198.1.2 KnowledgeBaseCategoriesById

Catalog: Autotask

Schema: KnowledgeBaseCategories

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseCategoriesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseCategoriesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
name	string	Name	☐	
parentCategoryID	int32	Parent Category ID	☐	

198.1.3 KnowledgeBaseCategoriesCount

Catalog: Autotask

Schema: KnowledgeBaseCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseCategoriesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199 Schema: Metadata

199.1 Tables

199.1.1 ActionTypesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ActionTypesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.2 ActionTypesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ActionTypesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.3 ActionTypesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ActionTypesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.4 ActionTypesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ActionTypesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.5 ActionTypesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ActionTypesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.6 AdditionalInvoiceFieldValuesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AdditionalInvoiceFieldValuesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.7 AdditionalInvoiceFieldValuesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AdditionalInvoiceFieldValuesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.8 AdditionalInvoiceFieldValuesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AdditionalInvoiceFieldValuesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.9 AdditionalInvoiceFieldValuesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table AdditionalInvoiceFieldValuesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.10 AdditionalInvoiceFieldValuesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AdditionalInvoiceFieldValuesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.11 AppointmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AppointmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.12 AppointmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AppointmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.13 AppointmentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AppointmentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.14 AppointmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AppointmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.15 AppointmentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AppointmentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.16 ArticleAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.17 ArticleAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.18 ArticleAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.19 ArticleConfigurationItemCategoryAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleConfigurationItemCategoryAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.20 ArticleConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.21 ArticleConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.22 ArticleConfigurationItemCategoryAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleConfigurationItemCategoryAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.23 ArticleConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.24 ArticleNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.25 ArticleNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.26 ArticleNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.27 ArticleNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.28 ArticleNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.29 ArticlePlainTextContentEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ArticlePlainTextContentEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.30 ArticlePlainTextContentEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticlePlainTextContentEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.31 ArticlePlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticlePlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.32 ArticlePlainTextContentEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticlePlainTextContentEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.33 ArticlePlainTextContentEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticlePlainTextContentEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.34 ArticleTagAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTagAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.35 ArticleTagAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTagAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.36 ArticleTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.37 ArticleTagAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTagAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.38 ArticleTagAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTagAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.39 ArticleTicketAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ArticleTicketAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.40 ArticleTicketAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTicketAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.41 ArticleTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.42 ArticleTicketAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTicketAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.43 ArticleTicketAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleTicketAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.44 ArticleToArticleAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToArticleAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.45 ArticleToArticleAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToArticleAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.46 ArticleToArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.47 ArticleToArticleAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToArticleAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.48 ArticleToArticleAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToArticleAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.49 ArticleToDocumentAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ArticleToDocumentAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.50 ArticleToDocumentAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToDocumentAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.51 ArticleToDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.52 ArticleToDocumentAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToDocumentAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.53 ArticleToDocumentAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ArticleToDocumentAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.54 AttachmentInfoEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AttachmentInfoEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.55 AttachmentInfoEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AttachmentInfoEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.56 AttachmentInfoEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AttachmentInfoEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.57 AttachmentInfoEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AttachmentInfoEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.58 AttachmentInfoEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table AttachmentInfoEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.59 BillingCodesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table BillingCodesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.60 BillingCodesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingCodesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.61 BillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.62 BillingCodesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingCodesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.63 BillingCodesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingCodesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.64 BillingItemApprovalLevelsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemApprovalLevelsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.65 BillingItemApprovalLevelsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemApprovalLevelsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.66 BillingItemApprovalLevelsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table BillingItemApprovalLevelsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.67 BillingItemApprovalLevelsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemApprovalLevelsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.68 BillingItemApprovalLevelsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemApprovalLevelsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.69 BillingItemsEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.70 BillingItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.71 BillingItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.72 BillingItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.73 BillingItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table BillingItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.74 ChangeOrderChargesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeOrderChargesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.75 ChangeOrderChargesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeOrderChargesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.76 ChangeOrderChargesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeOrderChargesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.77 ChangeOrderChargesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeOrderChargesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.78 ChangeOrderChargesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeOrderChargesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.79 ChangeRequestLinksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ChangeRequestLinksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.80 ChangeRequestLinksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeRequestLinksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.81 ChangeRequestLinksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeRequestLinksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.82 ChangeRequestLinksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeRequestLinksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.83 ChangeRequestLinksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChangeRequestLinksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.84 ChecklistLibrariesByParentIdChecklistItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.85
ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.86 ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.87 ChecklistLibrariesByParentIdChecklistItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.88 ChecklistLibrariesByParentIdChecklistItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ChecklistLibrariesByParentIdChecklistItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.89 ChecklistLibrariesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibrariesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.90 ChecklistLibrariesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibrariesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.91 ChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.92 ChecklistLibrariesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibrariesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.93 ChecklistLibrariesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibrariesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.94 ChecklistLibraryChecklistItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibraryChecklistItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.95 ChecklistLibraryChecklistItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibraryChecklistItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.96
ChecklistLibraryChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibraryChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.97 ChecklistLibraryChecklistItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibraryChecklistItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.98 ChecklistLibraryChecklistItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ChecklistLibraryChecklistItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.99 ClassificationIconsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClassificationIconsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.100 ClassificationIconsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClassificationIconsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.101 ClassificationIconsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClassificationIconsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.102 ClassificationIconsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClassificationIconsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.103 ClassificationIconsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClassificationIconsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.104 ClientPortalUsersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ClientPortalUsersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.105 ClientPortalUsersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClientPortalUsersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.106 ClientPortalUsersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClientPortalUsersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.107 ClientPortalUsersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClientPortalUsersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.108 ClientPortalUsersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ClientPortalUsersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.109 ComanagedAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ComanagedAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.110 ComanagedAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ComanagedAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.111 ComanagedAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ComanagedAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.112 ComanagedAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ComanagedAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.113 ComanagedAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ComanagedAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.114 CompaniesByParentIdAlertsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAlertsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdAlertsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.115 CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.116 CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.117 CompaniesByParentIdAlertsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAlertsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdAlertsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.118 CompaniesByParentIdAlertsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdAlertsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function CompaniesByParentIdAlertsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.119 CompaniesByParentIdContactsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdContactsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function CompaniesByParentIdContactsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.120 CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.121
CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.122 CompaniesByParentIdContactsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdContactsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdContactsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.123 CompaniesByParentIdContactsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdContactsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdContactsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.124 CompaniesByParentIdLocationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdLocationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdLocationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.125 CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.126
CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.127 CompaniesByParentIdLocationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdLocationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdLocationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.128 CompaniesByParentIdLocationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdLocationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdLocationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.129 CompaniesByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.130 CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.131 CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.132 CompaniesByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.133 CompaniesByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.134 CompaniesByParentIdSiteConfigurationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdSiteConfigurationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function CompaniesByParentIdSiteConfigurationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.135 CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.136 CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.137 CompaniesByParentIdSiteConfigurationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdSiteConfigurationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdSiteConfigurationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.138 CompaniesByParentIdSiteConfigurationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdSiteConfigurationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdSiteConfigurationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.139 CompaniesByParentIdTeamsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdTeamsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdTeamsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.140 CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.141 CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.142 CompaniesByParentIdTeamsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdTeamsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdTeamsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.143 CompaniesByParentIdTeamsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdTeamsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdTeamsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.144 CompaniesByParentIdToDosEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdToDosEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdToDosEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.145 CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.146 CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.147 CompaniesByParentIdToDosEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdToDosEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdToDosEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.148 CompaniesByParentIdToDosEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompaniesByParentIdToDosEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompaniesByParentIdToDosEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.149 CompaniesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompaniesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.150 CompaniesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompaniesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.151 CompaniesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompaniesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.152 CompaniesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompaniesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.153 CompaniesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompaniesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.154 CompanyAlertsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table CompanyAlertsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.155 CompanyAlertsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAlertsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.156 CompanyAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.157 CompanyAlertsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAlertsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.158 CompanyAlertsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAlertsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.159 CompanyAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.160 CompanyAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.161 CompanyAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.162 CompanyCategoriesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyCategoriesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.163 CompanyCategoriesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyCategoriesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.164 CompanyCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.165 CompanyCategoriesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyCategoriesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.166 CompanyCategoriesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyCategoriesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.167 CompanyLocationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table CompanyLocationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.168 CompanyLocationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyLocationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.169 CompanyLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.170 CompanyLocationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyLocationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.171 CompanyLocationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyLocationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.172 CompanyNoteAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNoteAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.173 CompanyNoteAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNoteAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.174 CompanyNoteAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNoteAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.175 CompanyNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.176 CompanyNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.177 CompanyNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.178 CompanyNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.179 CompanyNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.180 CompanySiteConfigurationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table CompanySiteConfigurationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.181 CompanySiteConfigurationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanySiteConfigurationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.182 CompanySiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanySiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
type	string	Type	☐	
value	string	Value	☐	

199.1.183 CompanySiteConfigurationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanySiteConfigurationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.184 CompanySiteConfigurationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanySiteConfigurationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.185 CompanyTeamsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyTeamsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.186 CompanyTeamsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyTeamsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.187 CompanyTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.188 CompanyTeamsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyTeamsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.189 CompanyTeamsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyTeamsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.190 CompanyToDosEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table CompanyToDosEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.191 CompanyToDosEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyToDosEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.192 CompanyToDosEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyToDosEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.193 CompanyToDosEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyToDosEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.194 CompanyToDosEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyToDosEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.195 CompanyWebhookExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.196 CompanyWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.197 CompanyWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table CompanyWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.198 CompanyWebhookExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.199 CompanyWebhookExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.200 CompanyWebhookFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.201 CompanyWebhookFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.202 CompanyWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.203 CompanyWebhookFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.204 CompanyWebhookFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table CompanyWebhookFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.205 CompanyWebhooksByParentIdExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.206
CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.207 CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.208 CompanyWebhooksByParentIdExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.209
CompanyWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.210 CompanyWebhooksByParentIdFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdFieldsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.211 CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.212 CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.213 CompanyWebhooksByParentIdFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.214 CompanyWebhooksByParentIdFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.215 CompanyWebhooksByParentIdUdfFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.216 CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.217 CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.218 CompanyWebhooksByParentIdUdfFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.219 CompanyWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function CompanyWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.220 CompanyWebhooksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhooksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.221 CompanyWebhooksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhooksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.222 CompanyWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.223 CompanyWebhooksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhooksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.224 CompanyWebhooksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhooksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.225 CompanyWebhookUdfFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookUdfFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.226 CompanyWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.227 CompanyWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.228 CompanyWebhookUdfFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookUdfFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.229 CompanyWebhookUdfFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CompanyWebhookUdfFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.230 ConfigurationItemAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.231 ConfigurationItemAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.232 ConfigurationItemAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.233 ConfigurationItemBillingProductAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemBillingProductAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.234 ConfigurationItemBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.235 ConfigurationItemBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.236 ConfigurationItemBillingProductAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemBillingProductAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.237 ConfigurationItemBillingProductAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ConfigurationItemBillingProductAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.238 ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.239
ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation_FieldsPicklistValues Fields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.241 ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.242 ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.243 ConfigurationItemCategoriesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoriesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.244 ConfigurationItemCategoriesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoriesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.245 ConfigurationItemCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.246 ConfigurationItemCategoriesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoriesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.247 ConfigurationItemCategoriesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemCategoriesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.248 ConfigurationItemCategoryUdfAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoryUdfAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.249
ConfigurationItemCategoryUdfAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoryUdfAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.250 ConfigurationItemCategoryUdfAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoryUdfAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.251 ConfigurationItemCategoryUdfAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoryUdfAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.252 ConfigurationItemCategoryUdfAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemCategoryUdfAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.253 ConfigurationItemDnsRecordsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemDnsRecordsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.254 ConfigurationItemDnsRecordsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ConfigurationItemDnsRecordsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.255 ConfigurationItemDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.256 ConfigurationItemDnsRecordsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemDnsRecordsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	

199.1.257 ConfigurationItemDnsRecordsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemDnsRecordsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.258 ConfigurationItemNoteAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNoteAttachmentsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.259 ConfigurationItemNoteAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNoteAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.260 ConfigurationItemNoteAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNoteAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.261 ConfigurationItemNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNotesEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.262 ConfigurationItemNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.263 ConfigurationItemNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.264 ConfigurationItemNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.265 ConfigurationItemNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.266 ConfigurationItemRelatedItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemRelatedItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.267 ConfigurationItemRelatedItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemRelatedItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.268
ConfigurationItemRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.269 ConfigurationItemRelatedItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemRelatedItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.270 ConfigurationItemRelatedItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemRelatedItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.271 ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.272
ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValues Fields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.274 ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.275
ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.276 ConfigurationItemsByParentIdDnsRecordsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.277
ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.278 ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.279 ConfigurationItemsByParentIdDnsRecordsEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.280 ConfigurationItemsByParentIdDnsRecordsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdDnsRecordsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.281 ConfigurationItemsByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.282 ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.283
ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.284 ConfigurationItemsByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.285 ConfigurationItemsByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.286 ConfigurationItemsByParentIdRelatedItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.287
ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.288 ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.289 ConfigurationItemsByParentIdRelatedItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.290 ConfigurationItemsByParentIdRelatedItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdRelatedItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.291 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.292 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.294 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.295 ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.296 ConfigurationItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.297 ConfigurationItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.298 ConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.299 ConfigurationItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.300 ConfigurationItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.301 ConfigurationItemSslSubjectAlternativeNamesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemSslSubjectAlternativeNamesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.302
ConfigurationItemSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.303 ConfigurationItemSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.304 ConfigurationItemSslSubjectAlternativeNamesEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemSslSubjectAlternativeNamesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.305 ConfigurationItemSslSubjectAlternativeNamesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemSslSubjectAlternativeNamesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.306 ConfigurationItemTypesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemTypesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.307 ConfigurationItemTypesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemTypesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.308 ConfigurationItemTypesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemTypesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.309 ConfigurationItemTypesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemTypesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.310 ConfigurationItemTypesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemTypesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.311 ConfigurationItemWebhookExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ConfigurationItemWebhookExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.312
ConfigurationItemWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.313 ConfigurationItemWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.314 ConfigurationItemWebhookExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.315 ConfigurationItemWebhookExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.316 ConfigurationItemWebhookFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.317 ConfigurationItemWebhookFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.318 ConfigurationItemWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ConfigurationItemWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.319 ConfigurationItemWebhookFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.320 ConfigurationItemWebhookFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.321 ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.322 ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.324 ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.325
ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.326 ConfigurationItemWebhooksByParentIdFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.327
ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.328 ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.329 ConfigurationItemWebhooksByParentIdFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.330 ConfigurationItemWebhooksByParentIdFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.331 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.332
ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.333 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.334 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.335 ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.336 ConfigurationItemWebhooksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhooksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.337 ConfigurationItemWebhooksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhooksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.338 ConfigurationItemWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.339 ConfigurationItemWebhooksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhooksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.340 ConfigurationItemWebhooksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ConfigurationItemWebhooksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.341 ConfigurationItemWebhookUdfFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookUdfFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.342 ConfigurationItemWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.343 ConfigurationItemWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.344 ConfigurationItemWebhookUdfFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookUdfFieldsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.345 ConfigurationItemWebhookUdfFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ConfigurationItemWebhookUdfFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.346 ContactBillingProductAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactBillingProductAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.347 ContactBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.348 ContactBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.349 ContactBillingProductAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactBillingProductAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.350 ContactBillingProductAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContactBillingProductAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.351 ContactGroupContactsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupContactsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.352 ContactGroupContactsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupContactsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.353 ContactGroupContactsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupContactsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.354 ContactGroupContactsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupContactsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.355 ContactGroupContactsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupContactsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.356 ContactGroupsByParentIdContactsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactGroupsByParentIdContactsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactGroupsByParentIdContactsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.357 ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.358
ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.359 ContactGroupsByParentIdContactsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactGroupsByParentIdContactsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactGroupsByParentIdContactsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.360 ContactGroupsByParentIdContactsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactGroupsByParentIdContactsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactGroupsByParentIdContactsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.361 ContactGroupsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.362 ContactGroupsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.363 ContactGroupsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.364 ContactGroupsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContactGroupsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.365 ContactGroupsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactGroupsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.366 ContactsByParentIdBillingProductAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactsByParentIdBillingProductAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactsByParentIdBillingProductAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.367
ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.368 ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.369 ContactsByParentIdBillingProductAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactsByParentIdBillingProductAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactsByParentIdBillingProductAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.370 ContactsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.371 ContactsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContactsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.372 ContactsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.373 ContactsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.374 ContactsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.375 ContactsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.376 ContactWebhookExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.377 ContactWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.378 ContactWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContactWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.379 ContactWebhookExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.380 ContactWebhookExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.381 ContactWebhookFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.382 ContactWebhookFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.383 ContactWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.384 ContactWebhookFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.385 ContactWebhookFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContactWebhookFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.386 ContactWebhooksByParentIdExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.387
ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.388
ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.389 ContactWebhooksByParentIdExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.390 ContactWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.391 ContactWebhooksByParentIdFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdFieldsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.392 ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.393
ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.394 ContactWebhooksByParentIdFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.395 ContactWebhooksByParentIdFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.396 ContactWebhooksByParentIdUdfFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdUdfFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdUdfFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.397 ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.398
ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.399 ContactWebhooksByParentIdUdfFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdUdfFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdUdfFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.400 ContactWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContactWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContactWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.401 ContactWebhooksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhooksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.402 ContactWebhooksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhooksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.403 ContactWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.404 ContactWebhooksEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhooksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.405 ContactWebhooksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhooksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.406 ContactWebhookUdfFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookUdfFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.407 ContactWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContactWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.408 ContactWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.409 ContactWebhookUdfFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookUdfFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.410 ContactWebhookUdfFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContactWebhookUdfFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.411 ContractBillingRulesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBillingRulesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.412 ContractBillingRulesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBillingRulesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.413 ContractBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.414 ContractBillingRulesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBillingRulesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.415 ContractBillingRulesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBillingRulesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.416 ContractBlockHourFactorsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlockHourFactorsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.417 ContractBlockHourFactorsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlockHourFactorsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.418 ContractBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.419 ContractBlockHourFactorsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlockHourFactorsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.420 ContractBlockHourFactorsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlockHourFactorsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.421 ContractBlocksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractBlocksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.422 ContractBlocksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlocksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.423 ContractBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.424 ContractBlocksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlocksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.425 ContractBlocksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractBlocksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.426 ContractChargesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractChargesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.427 ContractChargesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractChargesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.428 ContractChargesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractChargesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.429 ContractChargesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractChargesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.430 ContractChargesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractChargesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.431 ContractExclusionBillingCodesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractExclusionBillingCodesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.432 ContractExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.433
ContractExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.434 ContractExclusionBillingCodesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionBillingCodesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.435 ContractExclusionBillingCodesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionBillingCodesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.436 ContractExclusionRolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.437 ContractExclusionRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.438 ContractExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContractExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.439 ContractExclusionRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.440 ContractExclusionRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.441 ContractExclusionSetExcludedRolesEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.442 ContractExclusionSetExcludedRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.443
ContractExclusionSetExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.444 ContractExclusionSetExcludedRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.445 ContractExclusionSetExcludedRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContractExclusionSetExcludedRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.446 ContractExclusionSetExcludedWorkTypesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedWorkTypesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.447
ContractExclusionSetExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.448 ContractExclusionSetExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.449 ContractExclusionSetExcludedWorkTypesEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedWorkTypesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.450 ContractExclusionSetExcludedWorkTypesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetExcludedWorkTypesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.451 ContractExclusionSetsByParentIdExcludedRolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.452
ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.453 ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.454 ContractExclusionSetsByParentIdExcludedRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.455 ContractExclusionSetsByParentIdExcludedRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.456 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.457 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.458 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.459 ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.460
ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.461 ContractExclusionSetsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.462 ContractExclusionSetsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.463 ContractExclusionSetsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.464 ContractExclusionSetsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.465 ContractExclusionSetsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractExclusionSetsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.466 ContractMilestonesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractMilestonesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.467 ContractMilestonesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractMilestonesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.468 ContractMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.469 ContractMilestonesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractMilestonesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.470 ContractMilestonesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractMilestonesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.471 ContractNoteAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContractNoteAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.472 ContractNoteAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNoteAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.473 ContractNoteAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNoteAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.474 ContractNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContractNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.475 ContractNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.476 ContractNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.477 ContractNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.478 ContractNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.479 ContractRatesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRatesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.480 ContractRatesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRatesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.481 ContractRatesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRatesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.482 ContractRatesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRatesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.483 ContractRatesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRatesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.484 ContractRetainersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContractRetainersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.485 ContractRetainersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRetainersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.486 ContractRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.487 ContractRetainersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRetainersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.488 ContractRetainersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRetainersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.489 ContractRoleCostsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRoleCostsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.490 ContractRoleCostsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRoleCostsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.491 ContractRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.492 ContractRoleCostsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRoleCostsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.493 ContractRoleCostsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractRoleCostsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.494 ContractsByParentIdBillingRulesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBillingRulesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBillingRulesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.495 ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.496
ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.497 ContractsByParentIdBillingRulesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBillingRulesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBillingRulesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.498 ContractsByParentIdBillingRulesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBillingRulesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBillingRulesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.499 ContractsByParentIdBlockHourFactorsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlockHourFactorsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContractsByParentIdBlockHourFactorsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.500 ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.501
ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.502 ContractsByParentIdBlockHourFactorsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlockHourFactorsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlockHourFactorsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.503 ContractsByParentIdBlockHourFactorsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlockHourFactorsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlockHourFactorsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.504 ContractsByParentIdBlocksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlocksEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlocksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.505 ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.506 ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.507 ContractsByParentIdBlocksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlocksEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlocksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.508 ContractsByParentIdBlocksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdBlocksEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdBlocksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.509 ContractsByParentIdChargesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdChargesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdChargesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.510 ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.511 ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.512 ContractsByParentIdChargesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdChargesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdChargesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.513 ContractsByParentIdChargesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdChargesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdChargesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.514 ContractsByParentIdExclusionBillingCodesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionBillingCodesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionBillingCodesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.515
ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.516 ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.517 ContractsByParentIdExclusionBillingCodesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionBillingCodesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionBillingCodesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.518 ContractsByParentIdExclusionBillingCodesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionBillingCodesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionBillingCodesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.519 ContractsByParentIdExclusionRolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionRolesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.520 ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.521
ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.522 ContractsByParentIdExclusionRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionRolesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.523 ContractsByParentIdExclusionRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdExclusionRolesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdExclusionRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.524 ContractsByParentIdMilestonesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdMilestonesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdMilestonesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.525 ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.526
ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.527 ContractsByParentIdMilestonesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdMilestonesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdMilestonesEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.528 ContractsByParentIdMilestonesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdMilestonesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContractsByParentIdMilestonesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.529 ContractsByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContractsByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.530 ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.531 ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.532 ContractsByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.533 ContractsByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.534 ContractsByParentIdRatesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRatesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRatesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.535 ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.536 ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.537 ContractsByParentIdRatesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRatesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRatesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.538 ContractsByParentIdRatesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRatesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRatesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.539 ContractsByParentIdRetainersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRetainersEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRetainersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.540 ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.541
ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.542 ContractsByParentIdRetainersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRetainersEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRetainersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.543 ContractsByParentIdRetainersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRetainersEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRetainersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.544 ContractsByParentIdRoleCostsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRoleCostsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContractsByParentIdRoleCostsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.545 ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.546
ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.547 ContractsByParentIdRoleCostsEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRoleCostsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRoleCostsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.548 ContractsByParentIdRoleCostsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdRoleCostsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdRoleCostsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.549 ContractsByParentIdServiceAdjustmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceAdjustmentsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceAdjustmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.550 ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.551 ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.552 ContractsByParentIdServiceAdjustmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceAdjustmentsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceAdjustmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.553 ContractsByParentIdServiceAdjustmentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceAdjustmentsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceAdjustmentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.554 ContractsByParentIdServiceBundleAdjustmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.555
ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.556 ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.557 ContractsByParentIdServiceBundleAdjustmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.558 ContractsByParentIdServiceBundleAdjustmentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ContractsByParentIdServiceBundleAdjustmentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.559 ContractsByParentIdServiceBundlesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundlesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundlesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.560 ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.561
ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedField

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

s. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.562 ContractsByParentIdServiceBundlesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundlesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundlesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	

199.1.563 ContractsByParentIdServiceBundlesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundlesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundlesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.564 ContractsByParentIdServiceBundleUnitsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleUnitsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleUnitsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.565 ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.566 ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.567 ContractsByParentIdServiceBundleUnitsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleUnitsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleUnitsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.568 ContractsByParentIdServiceBundleUnitsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceBundleUnitsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceBundleUnitsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.569 ContractsByParentIdServicesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServicesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServicesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.570 ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.571 ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.572 ContractsByParentIdServicesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServicesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServicesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.573 ContractsByParentIdServicesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServicesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServicesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.574 ContractsByParentIdServiceUnitsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceUnitsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceUnitsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.575 ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.576
ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.577 ContractsByParentIdServiceUnitsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceUnitsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceUnitsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.578 ContractsByParentIdServiceUnitsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdServiceUnitsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdServiceUnitsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.579 ContractsByParentIdTicketPurchasesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdTicketPurchasesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdTicketPurchasesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.580 ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.581
ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.582 ContractsByParentIdTicketPurchasesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ContractsByParentIdTicketPurchasesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdTicketPurchasesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.583 ContractsByParentIdTicketPurchasesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContractsByParentIdTicketPurchasesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ContractsByParentIdTicketPurchasesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.584 ContractsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.585 ContractsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.586 ContractsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.587 ContractsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.588 ContractsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContractsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.589 ContractServiceAdjustmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceAdjustmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForUpdate	string		☐	

199.1.590 ContractServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.591 ContractServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.592 ContractServiceAdjustmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceAdjustmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.593 ContractServiceAdjustmentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceAdjustmentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.594 ContractServiceBundleAdjustmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleAdjustmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.595 ContractServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.596
ContractServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.597 ContractServiceBundleAdjustmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleAdjustmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.598 ContractServiceBundleAdjustmentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractServiceBundleAdjustmentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.599 ContractServiceBundlesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundlesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.600 ContractServiceBundlesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundlesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.601 ContractServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.602 ContractServiceBundlesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ContractServiceBundlesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.603 ContractServiceBundlesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundlesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.604 ContractServiceBundleUnitsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleUnitsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.605 ContractServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.606 ContractServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.607 ContractServiceBundleUnitsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleUnitsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.608 ContractServiceBundleUnitsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceBundleUnitsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.609 ContractServicesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServicesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.610 ContractServicesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServicesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.611 ContractServicesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServicesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.612 ContractServicesEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServicesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.613 ContractServicesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServicesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.614 ContractServiceUnitsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceUnitsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.615 ContractServiceUnitsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ContractServiceUnitsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.616 ContractServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.617 ContractServiceUnitsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceUnitsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.618 ContractServiceUnitsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractServiceUnitsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.619 ContractTicketPurchasesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractTicketPurchasesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.620 ContractTicketPurchasesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractTicketPurchasesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.621 ContractTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.622 ContractTicketPurchasesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractTicketPurchasesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.623 ContractTicketPurchasesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ContractTicketPurchasesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.624 CountriesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CountriesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.625 CountriesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CountriesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.626 CountriesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CountriesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.627 CountriesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CountriesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.628 CountriesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CountriesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.629 CurrenciesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table CurrenciesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.630 CurrenciesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CurrenciesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.631 CurrenciesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CurrenciesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.632 CurrenciesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CurrenciesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.633 CurrenciesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table CurrenciesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.634 DeletedTaskActivityLogsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTaskActivityLogsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.635 DeletedTaskActivityLogsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTaskActivityLogsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.636 DeletedTaskActivityLogsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTaskActivityLogsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.637 DeletedTaskActivityLogsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTaskActivityLogsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.638 DeletedTaskActivityLogsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTaskActivityLogsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.639 DeletedTicketActivityLogsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table DeletedTicketActivityLogsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.640 DeletedTicketActivityLogsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketActivityLogsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.641 DeletedTicketActivityLogsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketActivityLogsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
type	string	Type	☐	
value	string	Value	☐	

199.1.642 DeletedTicketActivityLogsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketActivityLogsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.643 DeletedTicketActivityLogsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketActivityLogsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.644 DeletedTicketLogsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketLogsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.645 DeletedTicketLogsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketLogsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.646 DeletedTicketLogsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketLogsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.647 DeletedTicketLogsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketLogsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.648 DeletedTicketLogsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DeletedTicketLogsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.649 DepartmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table DepartmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.650 DepartmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DepartmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.651 DepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.652 DepartmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DepartmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.653 DepartmentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DepartmentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.654 DocumentAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.655 DocumentAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.656 DocumentAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.657 DocumentCategoriesByParentIdDocumentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentCategoriesByParentIdDocumentsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function DocumentCategoriesByParentIdDocumentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.658
DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.659 DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.660 DocumentCategoriesByParentIdDocumentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentCategoriesByParentIdDocumentsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentCategoriesByParentIdDocumentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.661 DocumentCategoriesByParentIdDocumentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentCategoriesByParentIdDocumentsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentCategoriesByParentIdDocumentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.662 DocumentCategoriesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentCategoriesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.663 DocumentCategoriesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentCategoriesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.664 DocumentCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.665 DocumentCategoriesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentCategoriesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.666 DocumentCategoriesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentCategoriesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.667 DocumentChecklistItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.668 DocumentChecklistItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.669 DocumentChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.670 DocumentChecklistItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.671 DocumentChecklistItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.672 DocumentChecklistLibrariesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistLibrariesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.673 DocumentChecklistLibrariesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistLibrariesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.674 DocumentChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.675 DocumentChecklistLibrariesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistLibrariesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.676 DocumentChecklistLibrariesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentChecklistLibrariesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.677 DocumentConfigurationItemAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table DocumentConfigurationItemAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.678 DocumentConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.679 DocumentConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.680 DocumentConfigurationItemAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.681 DocumentConfigurationItemAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.682 DocumentConfigurationItemCategoryAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemCategoryAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.683 DocumentConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.684 DocumentConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table DocumentConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.685 DocumentConfigurationItemCategoryAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemCategoryAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.686 DocumentConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.687 DocumentNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.688 DocumentNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.689 DocumentNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.690 DocumentNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.691 DocumentNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table DocumentNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.692 DocumentPlainTextContentEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentPlainTextContentEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.693 DocumentPlainTextContentEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentPlainTextContentEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.694 DocumentPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.695 DocumentPlainTextContentEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentPlainTextContentEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.696 DocumentPlainTextContentEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentPlainTextContentEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.697 DocumentsByParentIdArticleAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdArticleAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdArticleAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.698 DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.699 DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.700 DocumentsByParentIdArticleAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdArticleAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdArticleAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.701 DocumentsByParentIdArticleAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdArticleAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdArticleAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.702 DocumentsByParentIdChecklistItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.703 DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.704
DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.705 DocumentsByParentIdChecklistItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistItemsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.706 DocumentsByParentIdChecklistItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function DocumentsByParentIdChecklistItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.707 DocumentsByParentIdChecklistLibrariesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistLibrariesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistLibrariesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.708 DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.709 DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.710 DocumentsByParentIdChecklistLibrariesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistLibrariesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistLibrariesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.711 DocumentsByParentIdChecklistLibrariesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdChecklistLibrariesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdChecklistLibrariesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.712 DocumentsByParentIdConfigurationItemAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.713 DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.714 DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.715 DocumentsByParentIdConfigurationItemAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.716
DocumentsByParentIdConfigurationItemAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.717 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.718 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.720 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.721 DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.722 DocumentsByParentIdDocumentAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdDocumentAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdDocumentAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.723
DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.724 DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.725 DocumentsByParentIdDocumentAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdDocumentAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdDocumentAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.726 DocumentsByParentIdDocumentAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdDocumentAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdDocumentAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.727 DocumentsByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.728 DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.729 DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.730 DocumentsByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.731 DocumentsByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.732 DocumentsByParentIdPlainTextContentEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdPlainTextContentEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdPlainTextContentEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.733 DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.734 DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.735 DocumentsByParentIdPlainTextContentEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdPlainTextContentEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdPlainTextContentEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.736 DocumentsByParentIdPlainTextContentEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdPlainTextContentEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdPlainTextContentEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.737 DocumentsByParentIdTagAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTagAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTagAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.738 DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.739
DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.740 DocumentsByParentIdTagAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTagAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTagAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.741 DocumentsByParentIdTagAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTagAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function DocumentsByParentIdTagAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.742 DocumentsByParentIdTicketAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTicketAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTicketAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.743 DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.744 DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.745 DocumentsByParentIdTicketAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTicketAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTicketAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.746 DocumentsByParentIdTicketAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DocumentsByParentIdTicketAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function DocumentsByParentIdTicketAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.747 DocumentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.748 DocumentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.749 DocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.750 DocumentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.751 DocumentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.752 DocumentTagAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table DocumentTagAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.753 DocumentTagAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTagAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.754 DocumentTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.755 DocumentTagAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTagAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.756 DocumentTagAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTagAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.757 DocumentTicketAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTicketAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.758 DocumentTicketAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTicketAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.759 DocumentTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.760 DocumentTicketAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTicketAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.761 DocumentTicketAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentTicketAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.762 DocumentToArticleAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table DocumentToArticleAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.763 DocumentToArticleAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToArticleAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.764
DocumentToArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.765 DocumentToArticleAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToArticleAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.766 DocumentToArticleAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToArticleAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.767 DocumentToDocumentAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToDocumentAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.768 DocumentToDocumentAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToDocumentAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.769 DocumentToDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table DocumentToDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.770 DocumentToDocumentAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToDocumentAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.771 DocumentToDocumentAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DocumentToDocumentAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.772 DomainRegistrarsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DomainRegistrarsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.773 DomainRegistrarsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DomainRegistrarsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.774 DomainRegistrarsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DomainRegistrarsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.775 DomainRegistrarsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table DomainRegistrarsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.776 DomainRegistrarsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table DomainRegistrarsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.777 ExpenseItemAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.778 ExpenseItemAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.779 ExpenseItemAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.780 ExpenseItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.781 ExpenseItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.782 ExpenseItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.783 ExpenseItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.784 ExpenseItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.785 ExpenseReportAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.786 ExpenseReportAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.787 ExpenseReportAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.788 ExpenseReportsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.789 ExpenseReportsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.790 ExpenseReportsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.791 ExpenseReportsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ExpenseReportsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.792 ExpenseReportsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ExpenseReportsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.793 ExpensesByParentIdItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpensesByParentIdItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ExpensesByParentIdItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.794 ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.795 ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.796 ExpensesByParentIdItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpensesByParentIdItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ExpensesByParentIdItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.797 ExpensesByParentIdItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ExpensesByParentIdItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ExpensesByParentIdItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.798 HolidaysEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaysEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.799 HolidaysEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaysEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.800 HolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.801 HolidaysEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaysEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.802 HolidaysEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaysEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.803 HolidaySetsByParentIdHolidaysEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function HolidaySetsByParentIdHolidaysEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function HolidaySetsByParentIdHolidaysEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.804 HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.805
HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.806 HolidaySetsByParentIdHolidaysEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function HolidaySetsByParentIdHolidaysEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function HolidaySetsByParentIdHolidaysEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.807 HolidaySetsByParentIdHolidaysEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function HolidaySetsByParentIdHolidaysEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function HolidaySetsByParentIdHolidaysEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.808 HolidaySetsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaySetsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.809 HolidaySetsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table HolidaySetsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.810 HolidaySetsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaySetsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.811 HolidaySetsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaySetsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	

199.1.812 HolidaySetsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table HolidaySetsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.813 IntegrationVendorInsightsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorInsightsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.814 IntegrationVendorInsightsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorInsightsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.815 IntegrationVendorInsightsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorInsightsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.816 IntegrationVendorInsightsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorInsightsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.817 IntegrationVendorInsightsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorInsightsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.818 IntegrationVendorWidgetsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorWidgetsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.819 IntegrationVendorWidgetsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorWidgetsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.820 IntegrationVendorWidgetsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorWidgetsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.821 IntegrationVendorWidgetsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorWidgetsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.822 IntegrationVendorWidgetsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table IntegrationVendorWidgetsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.823 InternalLocationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table InternalLocationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.824 InternalLocationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.825 InternalLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.826 InternalLocationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.827 InternalLocationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.828 InternalLocationWithBusinessHoursEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationWithBusinessHoursEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.829 InternalLocationWithBusinessHoursEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationWithBusinessHoursEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.830 InternalLocationWithBusinessHoursEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table InternalLocationWithBusinessHoursEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.831 InternalLocationWithBusinessHoursEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationWithBusinessHoursEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.832 InternalLocationWithBusinessHoursEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InternalLocationWithBusinessHoursEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.833 InventoryItemsByParentIdSerialNumbersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemsByParentIdSerialNumbersEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryItemsByParentIdSerialNumbersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.834 InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.835 InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.836 InventoryItemsByParentIdSerialNumbersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemsByParentIdSerialNumbersEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryItemsByParentIdSerialNumbersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.837 InventoryItemsByParentIdSerialNumbersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryItemsByParentIdSerialNumbersEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryItemsByParentIdSerialNumbersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.838 InventoryItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.839 InventoryItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.840 InventoryItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.841 InventoryItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.842 InventoryItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.843 InventoryItemSerialNumbersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemSerialNumbersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.844 InventoryItemSerialNumbersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemSerialNumbersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.845 InventoryItemSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.846 InventoryItemSerialNumbersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemSerialNumbersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.847 InventoryItemSerialNumbersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryItemSerialNumbersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.848 InventoryLocationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table InventoryLocationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.849 InventoryLocationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryLocationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.850 InventoryLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.851 InventoryLocationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryLocationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.852 InventoryLocationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryLocationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.853 InventoryProductsByParentIdStockedItemsAddEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsAddEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function InventoryProductsByParentIdStockedItemsAddEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.854
InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.855 InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.856 InventoryProductsByParentIdStockedItemsAddEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsAddEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsAddEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.857 InventoryProductsByParentIdStockedItemsAddEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsAddEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsAddEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.858 InventoryProductsByParentIdStockedItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.859
InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.860 InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.861 InventoryProductsByParentIdStockedItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.862 InventoryProductsByParentIdStockedItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.863 InventoryProductsByParentIdStockedItemsRemoveEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.864
InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.865 InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.866 InventoryProductsByParentIdStockedItemsRemoveEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.867
InventoryProductsByParentIdStockedItemsRemoveEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsRemoveEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.868 InventoryProductsByParentIdStockedItemsTransferEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.869
InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.870 InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.871 InventoryProductsByParentIdStockedItemsTransferEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.872
InventoryProductsByParentIdStockedItemsTransferEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function InventoryProductsByParentIdStockedItemsTransferEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.873 InventoryProductsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryProductsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.874 InventoryProductsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryProductsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.875 InventoryProductsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryProductsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.876 InventoryProductsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryProductsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.877 InventoryProductsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryProductsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.878 InventoryStockedItemsAddEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table InventoryStockedItemsAddEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.879 InventoryStockedItemsAddEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsAddEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.880 InventoryStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
type	string	Type	☐	
value	string	Value	☐	

199.1.881 InventoryStockedItemsAddEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsAddEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.882 InventoryStockedItemsAddEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsAddEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.883 InventoryStockedItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.884 InventoryStockedItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.885 InventoryStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.886 InventoryStockedItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.887 InventoryStockedItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.888 InventoryStockedItemsRemoveEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table InventoryStockedItemsRemoveEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.889 InventoryStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.890
InventoryStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.891 InventoryStockedItemsRemoveEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsRemoveEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.892 InventoryStockedItemsRemoveEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsRemoveEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.893 InventoryStockedItemsTransferEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsTransferEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.894 InventoryStockedItemsTransferEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsTransferEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.895 InventoryStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table InventoryStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.896 InventoryStockedItemsTransferEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsTransferEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.897 InventoryStockedItemsTransferEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryStockedItemsTransferEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.898 InventoryTransfersEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryTransfersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.899 InventoryTransfersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryTransfersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.900 InventoryTransfersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryTransfersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.901 InventoryTransfersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryTransfersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.902 InventoryTransfersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InventoryTransfersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.903 InvoicesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoicesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.904 InvoicesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoicesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.905 InvoicesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoicesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.906 InvoicesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoicesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.907 InvoicesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoicesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.908 InvoiceTemplatesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table InvoiceTemplatesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.909 InvoiceTemplatesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoiceTemplatesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.910 InvoiceTemplatesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoiceTemplatesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.911 InvoiceTemplatesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoiceTemplatesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.912 InvoiceTemplatesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table InvoiceTemplatesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.913 KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.914 KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation_FieldsPicklistValues Fields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.916 KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.917
KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.918
KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.919 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.921 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.922 KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.923 KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.924 KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.926 KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.927
KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.928 KnowledgeBaseArticlesByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.929 KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.930 KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.931 KnowledgeBaseArticlesByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.932 KnowledgeBaseArticlesByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.933 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.934 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.935 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.936 KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.937
KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.938 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.939 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.940 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.941 KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.942
KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.943 KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.944 KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.946 KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.947
KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.948 KnowledgeBaseArticlesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseArticlesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.949 KnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.950 KnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.951 KnowledgeBaseArticlesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseArticlesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.952 KnowledgeBaseArticlesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseArticlesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.953 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.954 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.956 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.957 KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.958 KnowledgeBaseCategoriesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table KnowledgeBaseCategoriesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.959 KnowledgeBaseCategoriesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseCategoriesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.960 KnowledgeBaseCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.961 KnowledgeBaseCategoriesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseCategoriesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.962 KnowledgeBaseCategoriesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table KnowledgeBaseCategoriesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.963 NotificationHistoryEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table NotificationHistoryEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.964 NotificationHistoryEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table NotificationHistoryEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.965 NotificationHistoryEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table NotificationHistoryEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.966 NotificationHistoryEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table NotificationHistoryEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.967 NotificationHistoryEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table NotificationHistoryEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.968 OpportunitiesByParentIdSalesOrdersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdSalesOrdersEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function OpportunitiesByParentIdSalesOrdersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.969 OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.970
OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.971 OpportunitiesByParentIdSalesOrdersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdSalesOrdersEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function OpportunitiesByParentIdSalesOrdersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.972 OpportunitiesByParentIdSalesOrdersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdSalesOrdersEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function OpportunitiesByParentIdSalesOrdersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.973 OpportunitiesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunitiesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.974 OpportunitiesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunitiesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.975 OpportunitiesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunitiesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.976 OpportunitiesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunitiesEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.977 OpportunitiesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunitiesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.978 OpportunityAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunityAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.979 OpportunityAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunityAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.980 OpportunityAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunityAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.981 OrganizationalLevel1sEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel1sEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.982 OrganizationalLevel1sEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel1sEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.983 OrganizationalLevel1sEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel1sEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.984 OrganizationalLevel1sEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel1sEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.985 OrganizationalLevel1sEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table OrganizationalLevel1sEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.986 OrganizationalLevel2sEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel2sEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.987 OrganizationalLevel2sEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel2sEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.988 OrganizationalLevel2sEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel2sEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.989 OrganizationalLevel2sEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel2sEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.990 OrganizationalLevel2sEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel2sEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.991 OrganizationalLevelAssociationsByParentIdResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevelAssociationsByParentIdResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function OrganizationalLevelAssociationsByParentIdResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.992 OrganizationalLevelAssociationsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevelAssociationsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function OrganizationalLevelAssociationsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.994 OrganizationalLevelAssociationsByParentIdResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevelAssociationsByParentIdResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function OrganizationalLevelAssociationsByParentIdResourcesEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.995
OrganizationalLevelAssociationsByParentIdResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevelAssociationsByParentIdResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function OrganizationalLevelAssociationsByParentIdResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.996 OrganizationalLevelAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevelAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.997 OrganizationalLevelAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevelAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.998 OrganizationalLevelAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevelAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.999 OrganizationalLevelAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevelAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1000 OrganizationalLevelAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevelAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1001 OrganizationalResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1002 OrganizationalResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1003 OrganizationalResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1004 OrganizationalResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1005 OrganizationalResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table OrganizationalResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1006 PaymentTermsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PaymentTermsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1007 PaymentTermsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PaymentTermsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1008 PaymentTermsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PaymentTermsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1009 PaymentTermsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PaymentTermsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1010 PaymentTermsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PaymentTermsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1011 PhasesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PhasesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1012 PhasesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PhasesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1013 PhasesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PhasesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1014 PhasesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PhasesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1015 PhasesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table PhasesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1016 PriceListMaterialCodesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListMaterialCodesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForUpdate	string		☐	

199.1.1017 PriceListMaterialCodesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListMaterialCodesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1018 PriceListMaterialCodesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table PriceListMaterialCodesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1019 PriceListMaterialCodesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListMaterialCodesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1020 PriceListMaterialCodesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListMaterialCodesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1021 PriceListProductsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1022 PriceListProductsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1023 PriceListProductsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1024 PriceListProductsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1025 PriceListProductsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table PriceListProductsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1026 PriceListProductTiersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductTiersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1027 PriceListProductTiersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductTiersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1028 PriceListProductTiersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductTiersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1029 PriceListProductTiersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductTiersEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1030 PriceListProductTiersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductTiersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1031 PriceListRolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1032 PriceListRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1033 PriceListRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1034 PriceListRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1035 PriceListRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table PriceListRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1036 PriceListServiceBundlesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServiceBundlesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1037 PriceListServiceBundlesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServiceBundlesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1038 PriceListServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1039 PriceListServiceBundlesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServiceBundlesEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1040 PriceListServiceBundlesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServiceBundlesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1041 PriceListServicesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServicesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1042 PriceListServicesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServicesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1043 PriceListServicesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServicesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1044 PriceListServicesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServicesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1045 PriceListServicesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table PriceListServicesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1046 PriceListWorkTypeModifiersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListWorkTypeModifiersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1047 PriceListWorkTypeModifiersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListWorkTypeModifiersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1048 PriceListWorkTypeModifiersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListWorkTypeModifiersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1049 PriceListWorkTypeModifiersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListWorkTypeModifiersEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1050 PriceListWorkTypeModifiersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListWorkTypeModifiersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1051 ProductNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1052 ProductNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1053 ProductNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1054 ProductNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1055 ProductNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ProductNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1056 ProductsByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1057 ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1058 ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1059 ProductsByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1060 ProductsByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1061 ProductsByParentIdTiersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdTiersEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdTiersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1062 ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1063 ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1064 ProductsByParentIdTiersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdTiersEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdTiersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1065 ProductsByParentIdTiersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdTiersEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdTiersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1066 ProductsByParentIdVendorsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdVendorsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdVendorsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1067 ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1068
ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1069 ProductsByParentIdVendorsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdVendorsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdVendorsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1070 ProductsByParentIdVendorsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdVendorsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdVendorsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1071 ProductsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1072 ProductsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1073 ProductsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1074 ProductsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1075 ProductsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1076 ProductTiersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ProductTiersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1077 ProductTiersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductTiersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1078 ProductTiersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductTiersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.1079 ProductTiersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductTiersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1080 ProductTiersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductTiersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1081 ProductVendorsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductVendorsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1082 ProductVendorsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductVendorsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1083 ProductVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1084 ProductVendorsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductVendorsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1085 ProductVendorsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductVendorsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1086 ProjectAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ProjectAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1087 ProjectAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1088 ProjectAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1089 ProjectChargesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ProjectChargesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1090 ProjectChargesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectChargesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1091 ProjectChargesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectChargesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1092 ProjectChargesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectChargesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1093 ProjectChargesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectChargesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1094 ProjectNoteAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNoteAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1095 ProjectNoteAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNoteAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1096 ProjectNoteAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNoteAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1097 ProjectNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1098 ProjectNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1099 ProjectNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1100 ProjectNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1101 ProjectNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1102 ProjectsByParentIdChargesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdChargesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdChargesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1103 ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1104 ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1105 ProjectsByParentIdChargesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdChargesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdChargesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1106 ProjectsByParentIdChargesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdChargesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdChargesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1107 ProjectsByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ProjectsByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1108 ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1109 ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1110 ProjectsByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1111 ProjectsByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1112 ProjectsByParentIdPhasesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdPhasesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdPhasesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1113 ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1114 ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1115 ProjectsByParentIdPhasesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdPhasesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ProjectsByParentIdPhasesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1116 ProjectsByParentIdPhasesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdPhasesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ProjectsByParentIdPhasesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1117 ProjectsByParentIdTasksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdTasksEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdTasksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1118 ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1119 ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.1120 ProjectsByParentIdTasksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdTasksEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdTasksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1121 ProjectsByParentIdTasksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdTasksEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdTasksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1122 ProjectsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1123 ProjectsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ProjectsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1124 ProjectsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1125 ProjectsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	

199.1.1126 ProjectsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1127 PurchaseApprovalsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseApprovalsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1128 PurchaseApprovalsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseApprovalsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1129 PurchaseApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1130 PurchaseApprovalsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseApprovalsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1131 PurchaseApprovalsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseApprovalsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1132 PurchaseOrderItemReceivingEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemReceivingEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1133 PurchaseOrderItemReceivingEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemReceivingEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1134
PurchaseOrderItemReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1135 PurchaseOrderItemReceivingEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemReceivingEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1136 PurchaseOrderItemReceivingEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemReceivingEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1137 PurchaseOrderItemsByParentIdReceivingEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemsByParentIdReceivingEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function PurchaseOrderItemsByParentIdReceivingEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1138
PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1139 PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1140 PurchaseOrderItemsByParentIdReceivingEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemsByParentIdReceivingEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function PurchaseOrderItemsByParentIdReceivingEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1141 PurchaseOrderItemsByParentIdReceivingEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemsByParentIdReceivingEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function PurchaseOrderItemsByParentIdReceivingEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1142 PurchaseOrderItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1143 PurchaseOrderItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1144 PurchaseOrderItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1145 PurchaseOrderItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table PurchaseOrderItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1146 PurchaseOrderItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1147 PurchaseOrdersByParentIdItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrdersByParentIdItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function PurchaseOrdersByParentIdItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1148 PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1149
PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1150 PurchaseOrdersByParentIdItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrdersByParentIdItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function PurchaseOrdersByParentIdItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1151 PurchaseOrdersByParentIdItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrdersByParentIdItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function PurchaseOrdersByParentIdItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1152 PurchaseOrdersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrdersEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1153 PurchaseOrdersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrdersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1154 PurchaseOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1155 PurchaseOrdersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrdersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1156 PurchaseOrdersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrdersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1157 QuoteItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1158 QuoteItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1159 QuoteItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1160 QuoteItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1161 QuoteItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1162 QuoteLocationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table QuoteLocationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1163 QuoteLocationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteLocationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1164 QuoteLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1165 QuoteLocationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteLocationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1166 QuoteLocationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteLocationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1167 QuotesByParentIdItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuotesByParentIdItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function QuotesByParentIdItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1168 QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1169 QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1170 QuotesByParentIdItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function QuotesByParentIdItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function QuotesByParentIdItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1171 QuotesByParentIdItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function QuotesByParentIdItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function QuotesByParentIdItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1172 QuotesEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1173 QuotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1174 QuotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1175 QuotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1176 QuotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1177 QuoteTemplatesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteTemplatesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1178 QuoteTemplatesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteTemplatesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1179 QuoteTemplatesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteTemplatesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1180 QuoteTemplatesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteTemplatesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1181 QuoteTemplatesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteTemplatesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1182 ResourceAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ResourceAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1183 ResourceAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1184 ResourceAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1185 ResourceRoleDepartmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ResourceRoleDepartmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1186 ResourceRoleDepartmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleDepartmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1187 ResourceRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1188 ResourceRoleDepartmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleDepartmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1189 ResourceRoleDepartmentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleDepartmentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1190 ResourceRoleQueuesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleQueuesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1191 ResourceRoleQueuesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleQueuesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1192 ResourceRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1193 ResourceRoleQueuesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleQueuesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1194 ResourceRoleQueuesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleQueuesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1195 ResourceRolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ResourceRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1196 ResourceRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1197 ResourceRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1198 ResourceRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1199 ResourceRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1200 ResourcesByParentIdRoleDepartmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleDepartmentsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleDepartmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1201 ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1202
ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1203 ResourcesByParentIdRoleDepartmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleDepartmentsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleDepartmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1204 ResourcesByParentIdRoleDepartmentsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleDepartmentsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleDepartmentsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1205 ResourcesByParentIdRoleQueuesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleQueuesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleQueuesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1206 ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1207
ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1208 ResourcesByParentIdRoleQueuesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleQueuesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleQueuesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1209 ResourcesByParentIdRoleQueuesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleQueuesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleQueuesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1210 ResourcesByParentIdRolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRolesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1211 ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1212 ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1213 ResourcesByParentIdRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRolesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1214 ResourcesByParentIdRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRolesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1215 ResourcesByParentIdServiceDeskRolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdServiceDeskRolesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdServiceDeskRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1216 ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1217
ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1218 ResourcesByParentIdServiceDeskRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdServiceDeskRolesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdServiceDeskRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1219 ResourcesByParentIdServiceDeskRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdServiceDeskRolesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdServiceDeskRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1220 ResourcesByParentIdSkillsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdSkillsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdSkillsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1221 ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1222 ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1223 ResourcesByParentIdSkillsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdSkillsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ResourcesByParentIdSkillsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1224 ResourcesByParentIdSkillsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdSkillsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ResourcesByParentIdSkillsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1225 ResourcesByParentIdTimeOffRequestsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdTimeOffRequestsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdTimeOffRequestsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1226 ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1227
ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.1228 ResourcesByParentIdTimeOffRequestsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdTimeOffRequestsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdTimeOffRequestsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1229 ResourcesByParentIdTimeOffRequestsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdTimeOffRequestsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdTimeOffRequestsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1230 ResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1231 ResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1232 ResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1233 ResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1234 ResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1235 ResourceServiceDeskRolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ResourceServiceDeskRolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1236 ResourceServiceDeskRolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceServiceDeskRolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1237 ResourceServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1238 ResourceServiceDeskRolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceServiceDeskRolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1239 ResourceServiceDeskRolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceServiceDeskRolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1240 ResourceSkillsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceSkillsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1241 ResourceSkillsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceSkillsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1242 ResourceSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1243 ResourceSkillsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceSkillsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1244 ResourceSkillsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceSkillsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1245 RolesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table RolesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1246 RolesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table RolesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1247 RolesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table RolesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1248 RolesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table RolesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1249 RolesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table RolesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1250 SalesOrderAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrderAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1251 SalesOrderAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrderAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1252 SalesOrderAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrderAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1253 SalesOrdersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrdersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1254 SalesOrdersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrdersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1255 SalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1256 SalesOrdersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrdersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1257 SalesOrdersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrdersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1258 ServiceBundlesByParentIdServicesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ServiceBundlesByParentIdServicesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceBundlesByParentIdServicesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1259 ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1260
ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1261 ServiceBundlesByParentIdServicesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceBundlesByParentIdServicesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceBundlesByParentIdServicesEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1262 ServiceBundlesByParentIdServicesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceBundlesByParentIdServicesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ServiceBundlesByParentIdServicesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1263 ServiceBundlesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundlesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1264 ServiceBundlesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundlesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1265 ServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1266 ServiceBundlesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundlesEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1267 ServiceBundlesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundlesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1268 ServiceBundleServicesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundleServicesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1269 ServiceBundleServicesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundleServicesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1270 ServiceBundleServicesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundleServicesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1271 ServiceBundleServicesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundleServicesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1272 ServiceBundleServicesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ServiceBundleServicesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1273 ServiceCallsByParentIdTasksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTasksEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTasksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1274 ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1275
ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields. A

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1276 ServiceCallsByParentIdTasksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTasksEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTasksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1277 ServiceCallsByParentIdTasksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTasksEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTasksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1278 ServiceCallsByParentIdTicketsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTicketsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTicketsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1279 ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1280
ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1281 ServiceCallsByParentIdTicketsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTicketsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTicketsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1282 ServiceCallsByParentIdTicketsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTicketsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTicketsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1283 ServiceCallsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ServiceCallsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1284 ServiceCallsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1285 ServiceCallsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1286 ServiceCallsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1287 ServiceCallsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1288 ServiceCallTaskResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTaskResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1289 ServiceCallTaskResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTaskResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1290 ServiceCallTaskResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTaskResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1291 ServiceCallTaskResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTaskResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1292 ServiceCallTaskResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTaskResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1293 ServiceCallTasksByParentIdResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTasksByParentIdResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallTasksByParentIdResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1294 ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1295
ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1296 ServiceCallTasksByParentIdResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTasksByParentIdResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ServiceCallTasksByParentIdResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1297 ServiceCallTasksByParentIdResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTasksByParentIdResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ServiceCallTasksByParentIdResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1298 ServiceCallTasksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTasksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1299 ServiceCallTasksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTasksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1300 ServiceCallTasksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTasksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1301 ServiceCallTasksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ServiceCallTasksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1302 ServiceCallTasksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTasksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1303 ServiceCallTicketResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1304 ServiceCallTicketResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1305 ServiceCallTicketResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1306 ServiceCallTicketResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1307 ServiceCallTicketResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1308 ServiceCallTicketsByParentIdResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketsByParentIdResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallTicketsByParentIdResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1309 ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1310 ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1311 ServiceCallTicketsByParentIdResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketsByParentIdResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallTicketsByParentIdResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1312 ServiceCallTicketsByParentIdResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketsByParentIdResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceCallTicketsByParentIdResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1313 ServiceCallTicketsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1314 ServiceCallTicketsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1315 ServiceCallTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1316 ServiceCallTicketsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1317 ServiceCallTicketsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1318 ServiceLevelAgreementResultsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ServiceLevelAgreementResultsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1319 ServiceLevelAgreementResultsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceLevelAgreementResultsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1320
ServiceLevelAgreementResultsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceLevelAgreementResultsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1321 ServiceLevelAgreementResultsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceLevelAgreementResultsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1322 ServiceLevelAgreementResultsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceLevelAgreementResultsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1323 ServiceLevelAgreementsByParentIdResultsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceLevelAgreementsByParentIdResultsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ServiceLevelAgreementsByParentIdResultsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1324
ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1325 ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1326 ServiceLevelAgreementsByParentIdResultsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceLevelAgreementsByParentIdResultsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceLevelAgreementsByParentIdResultsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1327 ServiceLevelAgreementsByParentIdResultsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceLevelAgreementsByParentIdResultsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function ServiceLevelAgreementsByParentIdResultsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1328 ServicesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServicesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1329 ServicesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServicesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1330 ServicesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServicesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1331 ServicesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServicesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1332 ServicesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServicesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1333 ShippingTypesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ShippingTypesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1334 ShippingTypesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ShippingTypesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1335 ShippingTypesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ShippingTypesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1336 ShippingTypesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ShippingTypesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1337 ShippingTypesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ShippingTypesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1338 SkillsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SkillsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1339 SkillsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SkillsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1340 SkillsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SkillsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1341 SkillsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SkillsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1342 SkillsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SkillsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1343 SubscriptionPeriodsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionPeriodsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1344 SubscriptionPeriodsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionPeriodsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1345 SubscriptionPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1346 SubscriptionPeriodsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table SubscriptionPeriodsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1347 SubscriptionPeriodsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionPeriodsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1348 SubscriptionsByParentIdPeriodsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionsByParentIdPeriodsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function SubscriptionsByParentIdPeriodsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1349 SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1350
SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1351 SubscriptionsByParentIdPeriodsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionsByParentIdPeriodsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function SubscriptionsByParentIdPeriodsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1352 SubscriptionsByParentIdPeriodsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionsByParentIdPeriodsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function SubscriptionsByParentIdPeriodsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1353 SubscriptionsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1354 SubscriptionsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1355 SubscriptionsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1356 SubscriptionsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1357 SubscriptionsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1358 SurveyResultsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveyResultsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1359 SurveyResultsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveyResultsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1360 SurveyResultsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveyResultsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1361 SurveyResultsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveyResultsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1362 SurveyResultsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveyResultsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1363 SurveysEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table SurveysEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1364 SurveysEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveysEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1365 SurveysEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveysEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1366 SurveysEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveysEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1367 SurveysEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveysEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1368 TagAliasesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagAliasesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1369 TagAliasesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagAliasesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1370 TagAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1371 TagAliasesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagAliasesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1372 TagAliasesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagAliasesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1373 TagGroupsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TagGroupsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1374 TagGroupsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagGroupsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1375 TagGroupsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagGroupsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1376 TagGroupsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagGroupsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1377 TagGroupsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagGroupsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1378 TagsByParentIdAliasesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagsByParentIdAliasesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TagsByParentIdAliasesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1379 TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1380 TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1381 TagsByParentIdAliasesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function TagsByParentIdAliasesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TagsByParentIdAliasesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1382 TagsByParentIdAliasesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function TagsByParentIdAliasesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TagsByParentIdAliasesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1383 TagsEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1384 TagsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1385 TagsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1386 TagsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1387 TagsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1388 TaskAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1389 TaskAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1390 TaskAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1391 TaskNoteAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNoteAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1392 TaskNoteAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNoteAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1393 TaskNoteAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNoteAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1394 TaskNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1395 TaskNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1396 TaskNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1397 TaskNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1398 TaskNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1399 TaskPredecessorsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TaskPredecessorsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1400 TaskPredecessorsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskPredecessorsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1401 TaskPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.1402 TaskPredecessorsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskPredecessorsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1403 TaskPredecessorsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskPredecessorsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1404 TasksByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1405 TasksByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function TasksByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1406 TasksByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1407 TasksByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1408 TasksByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1409 TasksByParentIdPredecessorsEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdPredecessorsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdPredecessorsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1410 TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1411
TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1412 TasksByParentIdPredecessorsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdPredecessorsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TasksByParentIdPredecessorsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1413 TasksByParentIdPredecessorsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdPredecessorsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TasksByParentIdPredecessorsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1414 TasksByParentIdSecondaryResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdSecondaryResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdSecondaryResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1415 TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1416
TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFie

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

lds. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1417 TasksByParentIdSecondaryResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdSecondaryResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdSecondaryResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	

199.1.1418 TasksByParentIdSecondaryResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdSecondaryResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TasksByParentIdSecondaryResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1419 TaskSecondaryResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskSecondaryResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1420 TaskSecondaryResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TaskSecondaryResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1421 TaskSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1422 TaskSecondaryResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskSecondaryResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1423 TaskSecondaryResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskSecondaryResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1424 TasksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TasksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1425 TasksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TasksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1426 TasksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TasksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1427 TasksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TasksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1428 TasksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TasksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1429 TaxCategoriesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxCategoriesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1430 TaxCategoriesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxCategoriesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1431 TaxCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1432 TaxCategoriesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxCategoriesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1433 TaxCategoriesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxCategoriesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1434 TaxesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TaxesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1435 TaxesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1436 TaxesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1437 TaxesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1438 TaxesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1439 TaxRegionsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxRegionsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1440 TaxRegionsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxRegionsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1441 TaxRegionsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxRegionsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1442 TaxRegionsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxRegionsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1443 TaxRegionsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxRegionsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1444 TicketAdditionalConfigurationItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TicketAdditionalConfigurationItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1445 TicketAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1446
TicketAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.1447 TicketAdditionalConfigurationItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalConfigurationItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1448 TicketAdditionalConfigurationItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalConfigurationItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1449 TicketAdditionalContactsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalContactsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1450 TicketAdditionalContactsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalContactsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1451 TicketAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TicketAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1452 TicketAdditionalContactsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalContactsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1453 TicketAdditionalContactsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalContactsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1454 TicketAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1455 TicketAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1456 TicketAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1457 TicketCategoriesByParentIdFieldDefaultsEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1458
TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1459 TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1460 TicketCategoriesByParentIdFieldIdDefaultsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoriesByParentIdFieldIdDefaultsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1461 TicketCategoriesByParentIdFieldDefaultsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketCategoriesByParentIdFieldDefaultsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1462 TicketCategoriesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoriesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1463 TicketCategoriesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoriesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1464 TicketCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1465 TicketCategoriesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoriesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1466 TicketCategoriesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoriesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1467 TicketCategoryFieldDefaultsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoryFieldDefaultsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1468 TicketCategoryFieldDefaultsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoryFieldDefaultsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1469
TicketCategoryFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoryFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1470 TicketCategoryFieldDefaultsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoryFieldDefaultsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1471 TicketCategoryFieldDefaultsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoryFieldDefaultsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1472 TicketChangeRequestApprovalsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TicketChangeRequestApprovalsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1473 TicketChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1474
TicketChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1475 TicketChangeRequestApprovalsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChangeRequestApprovalsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1476 TicketChangeRequestApprovalsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChangeRequestApprovalsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1477 TicketChargesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChargesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1478 TicketChargesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChargesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1479 TicketChargesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChargesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1480 TicketChargesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChargesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1481 TicketChargesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChargesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1482 TicketChecklistItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TicketChecklistItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1483 TicketChecklistItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1484 TicketChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.1485 TicketChecklistItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1486 TicketChecklistItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1487 TicketChecklistLibrariesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistLibrariesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1488 TicketChecklistLibrariesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistLibrariesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1489 TicketChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TicketChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1490 TicketChecklistLibrariesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistLibrariesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1491 TicketChecklistLibrariesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistLibrariesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1492 TicketHistoryEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketHistoryEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1493 TicketHistoryEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketHistoryEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1494 TicketHistoryEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketHistoryEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1495 TicketHistoryEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketHistoryEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1496 TicketHistoryEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketHistoryEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1497 TicketNoteAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1498 TicketNoteAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1499 TicketNoteAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1500 TicketNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1501 TicketNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1502 TicketNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1503 TicketNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1504 TicketNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1505 TicketNoteWebhookExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TicketNoteWebhookExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1506 TicketNoteWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1507 TicketNoteWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1508 TicketNoteWebhookExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1509 TicketNoteWebhookExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1510 TicketNoteWebhookFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1511 TicketNoteWebhookFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1512 TicketNoteWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TicketNoteWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1513 TicketNoteWebhookFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1514 TicketNoteWebhookFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1515 TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1516
TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1517
TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1518 TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1519
TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1520 TicketNoteWebhooksByParentIdFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1521 TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields. A value

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1522
TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1523 TicketNoteWebhooksByParentIdFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdFieldsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1524 TicketNoteWebhooksByParentIdFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function TicketNoteWebhooksByParentIdFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1525 TicketNoteWebhooksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhooksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1526 TicketNoteWebhooksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhooksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1527 TicketNoteWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1528 TicketNoteWebhooksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhooksEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1529 TicketNoteWebhooksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhooksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1530 TicketRmaCreditsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketRmaCreditsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1531 TicketRmaCreditsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketRmaCreditsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1532 TicketRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1533 TicketRmaCreditsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketRmaCreditsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1534 TicketRmaCreditsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TicketRmaCreditsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1535 TicketsByParentIdAdditionalConfigurationItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1536
TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1537
TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1538 TicketsByParentIdAdditionalConfigurationItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1539 TicketsByParentIdAdditionalConfigurationItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalConfigurationItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1540 TicketsByParentIdAdditionalContactsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalContactsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalContactsEntityInformation are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1541 TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1542
TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1543 TicketsByParentIdAdditionalContactsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalContactsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalContactsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1544 TicketsByParentIdAdditionalContactsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalContactsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalContactsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1545 TicketsByParentIdChangeRequestApprovalsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChangeRequestApprovalsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChangeRequestApprovalsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1546
TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1547 TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1548 TicketsByParentIdChangeRequestApprovalsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChangeRequestApprovalsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChangeRequestApprovalsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1549 TicketsByParentIdChangeRequestApprovalsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChangeRequestApprovalsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChangeRequestApprovalsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1550 TicketsByParentIdChargesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChargesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChargesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1551 TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1552 TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1553 TicketsByParentIdChargesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChargesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChargesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1554 TicketsByParentIdChargesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChargesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChargesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1555 TicketsByParentIdChecklistItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function TicketsByParentIdChecklistItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1556 TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1557
TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1558 TicketsByParentIdChecklistItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1559 TicketsByParentIdChecklistItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1560 TicketsByParentIdChecklistLibrariesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistLibrariesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistLibrariesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1561 TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1562
TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1563 TicketsByParentIdChecklistLibrariesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistLibrariesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistLibrariesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1564 TicketsByParentIdChecklistLibrariesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistLibrariesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistLibrariesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1565 TicketsByParentIdNotesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdNotesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdNotesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1566 TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1567 TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1568 TicketsByParentIdNotesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdNotesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdNotesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1569 TicketsByParentIdNotesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdNotesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdNotesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1570 TicketsByParentIdRmaCreditsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdRmaCreditsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdRmaCreditsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1571 TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1572
TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1573 TicketsByParentIdRmaCreditsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function TicketsByParentIdRmaCreditsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdRmaCreditsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1574 TicketsByParentIdRmaCreditsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function TicketsByParentIdRmaCreditsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdRmaCreditsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1575 TicketsByParentIdSecondaryResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdSecondaryResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdSecondaryResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1576 TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1577 TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1578 TicketsByParentIdSecondaryResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdSecondaryResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdSecondaryResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1579 TicketsByParentIdSecondaryResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdSecondaryResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdSecondaryResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1580 TicketsByParentIdTagAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdTagAssociationsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdTagAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1581 TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1582
TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1583 TicketsByParentIdTagAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdTagAssociationsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdTagAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1584 TicketsByParentIdTagAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdTagAssociationsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdTagAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1585 TicketSecondaryResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketSecondaryResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1586 TicketSecondaryResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketSecondaryResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1587 TicketSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TicketSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1588 TicketSecondaryResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketSecondaryResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1589 TicketSecondaryResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketSecondaryResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1590 TicketsEntityInformation

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1591 TicketsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1592 TicketsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1593 TicketsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1594 TicketsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1595 TicketTagAssociationsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketTagAssociationsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1596 TicketTagAssociationsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketTagAssociationsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1597 TicketTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1598 TicketTagAssociationsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketTagAssociationsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1599 TicketTagAssociationsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketTagAssociationsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1600 TicketWebhookExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TicketWebhookExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1601 TicketWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1602
TicketWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1603 TicketWebhookExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1604 TicketWebhookExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1605 TicketWebhookFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1606 TicketWebhookFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1607 TicketWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1608 TicketWebhookFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1609 TicketWebhookFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1610 TicketWebhooksByParentIdExcludedResourcesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1611
TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1612 TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1613 TicketWebhooksByParentIdExcludedResourcesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1614 TicketWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1615 TicketWebhooksByParentIdFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1616 TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1617
TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1618 TicketWebhooksByParentIdFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1619 TicketWebhooksByParentIdFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1620 TicketWebhooksByParentIdUdfFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdUdfFieldsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdUdfFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1621 TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1622
TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1623 TicketWebhooksByParentIdUdfFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdUdfFieldsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdUdfFieldsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1624 TicketWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1625 TicketWebhooksEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhooksEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1626 TicketWebhooksEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhooksEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1627 TicketWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1628 TicketWebhooksEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhooksEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1629 TicketWebhooksEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TicketWebhooksEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1630 TicketWebhookUdfFieldsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookUdfFieldsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1631 TicketWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1632 TicketWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1633 TicketWebhookUdfFieldsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookUdfFieldsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1634 TicketWebhookUdfFieldsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookUdfFieldsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1635 TimeEntriesEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntriesEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1636 TimeEntriesEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntriesEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1637 TimeEntriesEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntriesEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1638 TimeEntriesEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntriesEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1639 TimeEntriesEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TimeEntriesEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1640 TimeEntryAttachmentsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntryAttachmentsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1641 TimeEntryAttachmentsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntryAttachmentsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1642 TimeEntryAttachmentsEntityInformationFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntryAttachmentsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1643 TimeOffRequestsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeOffRequestsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1644 TimeOffRequestsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeOffRequestsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1645 TimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1646 TimeOffRequestsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeOffRequestsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1647 TimeOffRequestsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeOffRequestsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1648 UserDefinedFieldDefinitionsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldDefinitionsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1649 UserDefinedFieldDefinitionsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldDefinitionsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1650 UserDefinedFieldDefinitionsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldDefinitionsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1651 UserDefinedFieldDefinitionsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldDefinitionsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1652 UserDefinedFieldDefinitionsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table UserDefinedFieldDefinitionsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1653 UserDefinedFieldListItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldListItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1654 UserDefinedFieldListItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldListItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1655 UserDefinedFieldListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1656 UserDefinedFieldListItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldListItemsEntityInformationFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1657 UserDefinedFieldListItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldListItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1658 UserDefinedFieldsByParentIdListItemsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldsByParentIdListItemsEntityInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldsByParentIdListItemsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1659 UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1660
UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1661 UserDefinedFieldsByParentIdListItemsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldsByParentIdListItemsEntityInformationFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldsByParentIdListItemsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1662 UserDefinedFieldsByParentIdListItemsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldsByParentIdListItemsEntityInformationUserDefinedFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	string	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldsByParentIdListItemsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1663 WebhookEventErrorLogsEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WebhookEventErrorLogsEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1664 WebhookEventErrorLogsEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WebhookEventErrorLogsEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
value	string	Value	☐	

199.1.1665 WebhookEventErrorLogsEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WebhookEventErrorLogsEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

199.1.1666 WebhookEventErrorLogsEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WebhookEventErrorLogsEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1667 WebhookEventErrorLogsEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WebhookEventErrorLogsEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

199.1.1668 WorkTypeModifiersEntityInformation

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WorkTypeModifiersEntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

199.1.1669 WorkTypeModifiersEntityInformation_FieldsPicklistValuesFields

Catalog: Autotask

Schema: Metadata

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WorkTypeModifiersEntityInformation_FieldsPicklistValuesFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
value	string	Value	☐	

199.1.1670 WorkTypeModifiersEntityInformation_FieldsPicklistValuesUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WorkTypeModifiersEntityInformation_FieldsPicklistValuesUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefaultValue	boolean	Is Default Value	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
isSystem	boolean	Is System	☐	
label_1	string	Label	☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
parentValue	string	Parent 4 Value	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
sortOrder	int32	Sort Order	☐	
type	string	Type	☐	
value	string	Value	☐	

199.1.1671 WorkTypeModifiersEntityInformationFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WorkTypeModifiersEntityInformationFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
dataType	string	Data Type	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
length	int32	Length	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	

199.1.1672 WorkTypeModifiersEntityInformationUserDefinedFields

Catalog: Autotask

Schema: Metadata

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WorkTypeModifiersEntityInformationUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
defaultValue	string	Default Value	☐	
description	string	Description	☐	
isPickList	boolean	Is Picklist	☐	
isQueryable	boolean	Is Queryable	☐	
isReadOnly	boolean	Is Read-only	☐	
isReference	boolean	Is Reference	☐	
isRequired	boolean	Is Required	☐	
isSupportedWebhookField	string		☐	
label	string	Label	☐	
length	int32	Length	☐	
name	string	Name	☐	
picklistParentValueField	string	Pick List Parent Value Field	☐	
referenceEntityType	string	Reference Entity Type	☐	
type	string	Type	☐	

200 Schema: MetadataApiIntegration

200.1 Tables

200.1.1 EntityInformation

Catalog: Autotask

Schema: MetadataApiIntegration

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table EntityInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
info_canCreate	boolean	Can Create	☐	
info_canDelete	boolean	Can Delete	☐	
info_canQuery	boolean	Can Query	☐	
info_canUpdate	boolean	Can Update	☐	
info_hasUserDefinedFields	boolean	Has User Defined Fields	☐	
info_name	string	Name	☐	
info_supportsWebhookCallouts	boolean	Supports Webhook Call-outs	☐	
info_userAccessForCreate	string		☐	
info_userAccessForDelete	string		☐	
info_userAccessForQuery	string		☐	
info_userAccessForUpdate	string		☐	

201 Schema: ModuleAccessApiIntegration

201.1 Tables

201.1.1 Modules

Catalog: Autotask

Schema: ModuleAccessApiIntegration

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Modules are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
key	int32	Key	☐	
value	boolean	Value	☐	

202 Schema: Native

202.1 Tables

202.1.1 NATIVEPLATFORMSCALARREQUESTS: Autotask Native Platform Scalar Requests

{res:itgen_native_platform_scalar_requests_desc}

Catalog: Autotask

Schema: Native

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Alias: `npt`

Label: Native Platform Scalar Requests

Documentation:

The NativePlatformScalarRequests table provides direct access to the native API protocol over an established connection to the Autotask API server. It will contain a new row for every row inserted with a native API request in PAYLOAD_TEXT with the results of unaltered forwarding of the payload to the Autotask API server.

Retrieve: true

Insert: true

Update: false

Delete: false

View Columns

The columns of the view NATIVEPLATFORMSCALARREQUESTS are shown below. Each column has an SQL data type. A new non-null value must be provided for every required column at all times during insert.

Name	Data Type	Label	Required	Documentation
BLOB_PREFERRED	boolean	BLOB Preferred	☑	Indicator whether a BLOB result is preferred over text.
BOL_RESPONSE_CACHE_MAX_AGE_SEC	int32	Response Cache Maximum Age (sec)	☐	Maximum age in seconds of Bridge Online response cache entries to be used.
CONTENT_TYPE	string(240)	Content Type	☐	
DATE_ENDED	datetime	End Date	☑	
DATE_STARTED	datetime	Start Date	☑	
DRY_RUN	boolean	Run without Actions	☑	
DURATION_MS	int64	Duration (ms)	☑	
ERROR_MESSAGE_CODE	string(30)	Error Message Code	☐	
ERROR_MESSAGE_TEXT	string(32000)	Error Message Text	☐	
FAIL_ON_ERROR	boolean	Fail on Error	☑	Whether to raise an exception when processing the native request triggered an error from the provider.
HTTP_DISK_CACHE_MAX_AGE_SEC	int32	HTTP Disk Cache Maximum Age (sec)	☐	Maximum age in seconds of HTTP disk cache entries to be used.
HTTP_DISK_CACHE_SAVE	boolean	Save HTTP Disk Cache	☐	Whether results can be stored in HTTP disk cache.
HTTP_DISK_CACHE_USE	boolean	Use HTTP Disk Cache	☐	Whether results can be fetched from HTTP disk cache.
HTTP_MEMORY_CACHE_MAX_AGE_SEC	int32	HTTP Memory Cache Maximum Age (sec)	☐	Maximum age in seconds of HTTP memory cache entries to be used.
HTTP_MEMORY_CACHE_SAVE	boolean	Save HTTP Memory Cache	☐	Whether results can be stored in HTTP memory cache.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
HTTP_MEMORY_CACHE_USE	boolean	Use HTTP Memory Cache	☐	Whether results can be fetched from HTTP memory cache.
HTTP_METHOD	string(30)	HTTP Method	☐	
HTTP_STATUS_CODE	int32	HTTP Status Code	☐	
ORIG_SYSTEM_GROUP	string(4000)	Original System Group	☐	
ORIG_SYSTEM_REFERENCE	string(4000)	Original System Reference	☐	
PAYLOAD_TEXT	string	Payload	☐	
RESULT_BLOB	byte[]	Result BLOB	☐	
RESULT_DATE_TIME_UTC	datetime	Result Date Time	☐	
RESULT_NUMBER	decimal	Result Number	☐	
RESULT_TEXT	string	Result Text	☐	
SUCCESSFUL	boolean	Succesful	☑	
TIMEOUT_SEC	int32	Timeout (sec)	☐	Timeout in seconds.
TRANSACTION_ID	int64	Transaction ID	☑	Incrementing ID of the transaction.
URL	string(4000)	URL	☐	

203 Schema: NotificationHistory

203.1 Tables

203.1.1 NotificationHistory

Catalog: Autotask

Schema: NotificationHistory

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table NotificationHistory are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int64	Company ID	☐	
entityNumber	string	Entity Number	☐	
entityTitle	string	Entity Title	☐	
id	int64	ID	☐	
initiatingContactID	int64	Initiating Contact ID	☐	
initiatingResourceID	int64	Initiating Resource ID	☐	
isActive	boolean	Is Active	☐	
isDeleted	boolean	Is Deleted	☐	
isTemplateJob	boolean	Is Template Job	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
notificationHistoryTypeID	int32	Notification History Type ID	☐	
notificationSentTime	datetime	Notification Sent Time	☐	
opportunityID	int64	Opportunity ID	☐	
projectID	int64	Project ID	☐	
quoteID	int64	Quote ID	☐	
recipientDisplayName	string	Recipient Display Name	☐	
recipientEmailAddress	string	Recipient Email Address	☐	
taskID	int64	Task ID	☐	
templateName	string	Template Name	☐	
ticketID	int64	Ticket ID	☐	
timeEntryID	int64	Time Entry ID	☐	

203.1.2 NotificationHistoryById

Catalog: Autotask

Schema: NotificationHistory

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function NotificationHistoryById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function NotificationHistoryById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
companyID	int64	Company ID	☐	
entityNumber	string	Entity Number	☐	
entityTitle	string	Entity Title	☐	
id	int64	ID	☐	
initiatingContactID	int64	Initiating Contact ID	☐	
initiatingResourceID	int64	Initiating Resource ID	☐	
isActive	boolean	Is Active	☐	
isDeleted	boolean	Is Deleted	☐	
isTemplateJob	boolean	Is Template Job	☐	
notificationHistoryTypeID	int32	Notification History Type ID	☐	
notificationSentTime	datetime	Notification Sent Time	☐	
opportunityID	int64	Opportunity ID	☐	
projectID	int64	Project ID	☐	
quoteID	int64	Quote ID	☐	
recipientDisplayName	string	Recipient Display Name	☐	
recipientEmailAddress	string	Recipient Email Address	☐	
taskID	int64	Task ID	☐	
templateName	string	Template Name	☐	
ticketID	int64	Ticket ID	☐	
timeEntryID	int64	Time Entry ID	☐	

203.1.3 NotificationHistoryCount

Catalog: Autotask

Schema: NotificationHistory

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table NotificationHistoryCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

204 Schema: Opportunities

204.1 Tables

204.1.1 Opportunities

Catalog: Autotask

Schema: Opportunities

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Opportunities are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
advancedField1	double	Advanced Field 1	☐	
advancedField2	double	Advanced Field 2	☐	
advancedField3	double	Advanced Field 3	☐	
advancedField4	double	Advanced Field 4	☐	
advancedField5	double	Advanced Field 5	☐	
amount	double	Amount	☐	
assessmentScore	double	Assessment Score	☐	
barriers	string	Barriers	☐	
closedDate	datetime	Closed Date	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
cost	double	Cost	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
helpNeeded	string	Help Needed	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
lastActivity	datetime	Last Activity	☐	
leadSource	int32	Lead Source	☐	
lossReason	int32	Loss Reason	☐	
lossReasonDetail	string	Loss Reason Detail	☐	
lostDate	datetime	Lost Date	☐	
market	string	Market	☐	
monthlyCost	double	Monthly Cost	☐	
monthlyRevenue	double	Monthly Revenue	☐	
nextStep	string	Next Step	☐	
onetimeCost	double	One-time Cost	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
onetimeRevenue	double	One-time Revenue	☐	
opportunityCategoryID	int32	Opportunity Category ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ownerResourceID	int32	Owner Resource ID	☐	
primaryCompetitor	int32	Primary Competitor	☐	
probability	int32	Probability	☐	
productID	int32	Product ID	☐	
projectedCloseDate	datetime	Projected Close Date	☐	
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
promotionName	string	Promotion Name	☐	
quarterlyCost	double	Quarterly Cost	☐	
quarterlyRevenue	double	Quarterly Revenue	☐	
rating	int32	Rating	☐	
relationshipAssessmentScore	double	Relationship Assessment Score	☐	
revenueSpread	int32	Revenue Spread	☐	
revenueSpreadUnit	string	Revenue Spread Unit	☐	
salesOrderID	int32	Sales Order ID	☐	
salesProcessPercentComplete	double	Sales Process Percent Complete	☐	
semiannualCost	double	Semi-annual Cost	☐	
semiannualRevenue	double	Semi-annual Revenue	☐	
stage	int32	Stage	☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
technicalAssessmentScore	double	Technical Assessment Score	☐	
throughDate	datetime	Through Date	☐	
title	string	Title	☐	
totalAmountMonths	int32	Total Amount Months	☐	
useQuoteTotals	boolean	Use Quote Totals	☐	
winReason	int32	Win Reason	☐	
winReasonDetail	string	Win Reason Detail	☐	
yearlyCost	double	Yearly Cost	☐	
yearlyRevenue	double	Yearly Revenue	☐	

204.1.2 Opportunities_ItemsUserDefinedFields

Catalog: Autotask

Schema: Opportunities

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Opportunities_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
advancedField1	double	Advanced Field 1	☐	
advancedField2	double	Advanced Field 2	☐	
advancedField3	double	Advanced Field 3	☐	
advancedField4	double	Advanced Field 4	☐	
advancedField5	double	Advanced Field 5	☐	
amount	double	Amount	☐	
assessmentScore	double	Assessment Score	☐	
barriers	string	Barriers	☐	
closedDate	datetime	Closed Date	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
cost	double	Cost	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
helpNeeded	string	Help Needed	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
lastActivity	datetime	Last Activity	☐	
leadSource	int32	Lead Source	☐	
lossReason	int32	Loss Reason	☐	
lossReasonDetail	string	Loss Reason Detail	☐	
lostDate	datetime	Lost Date	☐	
market	string	Market	☐	
monthlyCost	double	Monthly Cost	☐	
monthlyRevenue	double	Monthly Revenue	☐	
name	string	Name	☐	
nextStep	string	Next Step	☐	
onetimeCost	double	One-time Cost	☐	
onetimeRevenue	double	One-time Revenue	☐	
opportunityCategoryID	int32	Opportunity Category ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
ownerResourceID	int32	Owner Resource ID	☐	
primaryCompetitor	int32	Primary Competitor	☐	
probability	int32	Probability	☐	
productID	int32	Product ID	☐	
projectedCloseDate	datetime	Projected Close Date	☐	
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
promotionName	string	Promotion Name	☐	
quarterlyCost	double	Quarterly Cost	☐	
quarterlyRevenue	double	Quarterly Revenue	☐	
rating	int32	Rating	☐	
relationshipAssessmentScore	double	Relationship Assessment Score	☐	
revenueSpread	int32	Revenue Spread	☐	
revenueSpreadUnit	string	Revenue Spread Unit	☐	
salesOrderID	int32	Sales Order ID	☐	
salesProcessPercentComplete	double	Sales Process Percent Complete	☐	
semiannualCost	double	Semi-annual Cost	☐	
semiannualRevenue	double	Semi-annual Revenue	☐	
stage	int32	Stage	☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
technicalAssessmentScore	double	Technical Assessment Score	☐	
throughDate	datetime	Through Date	☐	
title	string	Title	☐	
totalAmountMonths	int32	Total Amount Months	☐	
useQuoteTotals	boolean	Use Quote Totals	☐	
value	string	Value	☐	
winReason	int32	Win Reason	☐	
winReasonDetail	string	Win Reason Detail	☐	
yearlyCost	double	Yearly Cost	☐	
yearlyRevenue	double	Yearly Revenue	☐	

204.1.3 OpportunitiesById

Catalog: Autotask

Schema: Opportunities

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function OpportunitiesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
advancedField1	double	Advanced Field 1	☐	
advancedField2	double	Advanced Field 2	☐	
advancedField3	double	Advanced Field 3	☐	
advancedField4	double	Advanced Field 4	☐	
advancedField5	double	Advanced Field 5	☐	
amount	double	Amount	☐	
assessmentScore	double	Assessment Score	☐	
barriers	string	Barriers	☐	
closedDate	datetime	Closed Date	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
cost	double	Cost	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
helpNeeded	string	Help Needed	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
lastActivity	datetime	Last Activity	☐	
leadSource	int32	Lead Source	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
lossReason	int32	Loss Reason	☐	
lossReasonDetail	string	Loss Reason Detail	☐	
lostDate	datetime	Lost Date	☐	
market	string	Market	☐	
monthlyCost	double	Monthly Cost	☐	
monthlyRevenue	double	Monthly Revenue	☐	
nextStep	string	Next Step	☐	
onetimeCost	double	One-time Cost	☐	
onetimeRevenue	double	One-time Revenue	☐	
opportunityCategoryID	int32	Opportunity Category ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ow nerResourceID	int32	Ow ner Resource ID	☐	
primaryCompetitor	int32	Primary Competitor	☐	
probability	int32	Probability	☐	
productID	int32	Product ID	☐	
projectedCloseDate	datetime	Projected Close Date	☐	
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
promotionName	string	Promotion Name	☐	
quarterlyCost	double	Quarterly Cost	☐	
quarterlyRevenue	double	Quarterly Revenue	☐	
rating	int32	Rating	☐	
relationshipAssessmentScore	double	Relationship Assessment Score	☐	
revenueSpread	int32	Revenue Spread	☐	
revenueSpreadUnit	string	Revenue Spread Unit	☐	
salesOrderID	int32	Sales Order ID	☐	
salesProcessPercentComplete	double	Sales Process Percent Complete	☐	
semiannualCost	double	Semi-annual Cost	☐	
semiannualRevenue	double	Semi-annual Revenue	☐	
stage	int32	Stage	☐	
startDate	datetime	Start Date	☐	
status	int32	Status	☐	
technicalAssessmentScore	double	Technical Assessment Score	☐	
throughDate	datetime	Through Date	☐	
title	string	Title	☐	
totalAmountMonths	int32	Total Amount Months	☐	
useQuoteTotals	boolean	Use Quote Totals	☐	
w inReason	int32	Win Reason	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
w inReasonDetail	string	Win Reason Detail	☐	
yearlyCost	double	Yearly Cost	☐	
yearlyRevenue	double	Yearly Revenue	☐	

204.1.4 OpportunitiesCount

Catalog: Autotask

Schema: Opportunities

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunitiesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

205 Schema: OpportunityAttachments

205.1 Tables

205.1.1 OpportunityAttachments

Catalog: Autotask

Schema: OpportunityAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunityAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

205.1.2 OpportunityAttachmentsById

Catalog: Autotask

Schema: OpportunityAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunityAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function OpportunityAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

205.1.3 OpportunityAttachmentsCount

Catalog: Autotask

Schema: OpportunityAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OpportunityAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

206 Schema: OpportunityAttachmentsChild

206.1 Tables

206.1.1 OpportunitiesByParentIdAttachments

Catalog: Autotask

Schema: OpportunityAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function OpportunitiesByParentIdAttachments are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

206.1.2 OpportunitiesByParentIdAttachmentsId

Catalog: Autotask

Schema: OpportunityAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdAttachmentsId. A value must be provided at all times for required

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function OpportunitiesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

207 Schema: OrganizationalLevel1

207.1 Tables

207.1.1 OrganizationalLevel1s

Catalog: Autotask

Schema: OrganizationalLevel1

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel1s are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

207.1.2 OrganizationalLevel1sById

Catalog: Autotask

Schema: OrganizationalLevel1

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevel1sById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function OrganizationalLevel1sById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

207.1.3 OrganizationalLevel1sCount

Catalog: Autotask

Schema: OrganizationalLevel1

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel1sCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

208 Schema: OrganizationalLevel2

208.1 Tables

208.1.1 OrganizationalLevel2s

Catalog: Autotask

Schema: OrganizationalLevel2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel2s are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

208.1.2 OrganizationalLevel2sById

Catalog: Autotask

Schema: OrganizationalLevel2

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevel2sById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function OrganizationalLevel2sById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

208.1.3 OrganizationalLevel2sCount

Catalog: Autotask

Schema: OrganizationalLevel2

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevel2sCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

209 Schema: OrganizationalLevelAssociation

209.1 Tables

209.1.1 OrganizationalLevelAssociations

Catalog: Autotask

Schema: OrganizationalLevelAssociation

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalLevelAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
organizationalLevel1ID	int32	Organizational Level 1 ID	☐	
organizationalLevel2ID	int32	Organizational Level 2 ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

209.1.2 OrganizationalLevelAssociationsById

Catalog: Autotask

Schema: OrganizationalLevelAssociation

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevelAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function OrganizationalLevelAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
organizationalLevel1ID	int32	Organizational Level 1 ID	☐	
organizationalLevel2ID	int32	Organizational Level 2 ID	☐	

209.1.3 OrganizationalLevelAssociationsCount

Catalog: Autotask

Schema: OrganizationalLevelAssociation

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table OrganizationalLevelAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

210 Schema: OrganizationalResources

210.1 Tables

210.1.1 OrganizationalResources

Catalog: Autotask

Schema: OrganizationalResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

210.1.2 OrganizationalResourcesById

Catalog: Autotask

Schema: OrganizationalResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function OrganizationalResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

210.1.3 OrganizationalResourcesCount

Catalog: Autotask

Schema: OrganizationalResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table OrganizationalResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

211 Schema: OrganizationalResourcesChild

211.1 Tables

211.1.1 OrganizationalLevelAssociationsByParentIdResources

Catalog: Autotask

Schema: OrganizationalResourcesChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevelAssociationsByParentIdResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function OrganizationalLevelAssociationsByParentIdResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

211.1.2 OrganizationalLevelAssociationsByParentIdResourcesId

Catalog: Autotask

Schema: OrganizationalResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OrganizationalLevelAssociationsByParentIdResourcesId. A value must be provided at all

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function OrganizationalLevelAssociationsByParentIdResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

212 Schema: PaymentTerms

212.1 Tables

212.1.1 PaymentTerms

Catalog: Autotask

Schema: PaymentTerms

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PaymentTerms are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	
paymentDueInDays	int32	Payment due in Days	☐	

212.1.2 PaymentTermsById

Catalog: Autotask

Schema: PaymentTerms

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PaymentTermsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PaymentTermsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	
paymentDueInDays	int32	Payment due in Days	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

212.1.3 PaymentTermsCount

Catalog: Autotask

Schema: PaymentTerms

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PaymentTermsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

213 Schema: Phases

213.1 Tables

213.1.1 Phases

Catalog: Autotask

Schema: Phases

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Phases are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
dueDate	datetime	Due Date	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
id	int64	ID	☐	
isScheduled	boolean	Is Scheduled	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
parentPhaseID	int32	Parent Phase ID	☐	
phaseNumber	string	Phase Number	☐	
projectID	int32	Project ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
title	string	Title	☐	

213.1.2 PhasesById

Catalog: Autotask

Schema: Phases

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PhasesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PhasesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
dueDate	datetime	Due Date	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
id	int64	ID	☐	
isScheduled	boolean	Is Scheduled	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
parentPhaseID	int32	Parent Phase ID	☐	
phaseNumber	string	Phase Number	☐	
projectID	int32	Project ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
title	string	Title	☐	

213.1.3 PhasesCount

Catalog: Autotask

Schema: Phases

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PhasesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

214 Schema: PhasesChild

214.1 Tables

214.1.1 ProjectsByParentIdPhases

Catalog: Autotask

Schema: PhasesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdPhases. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdPhases are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
dueDate	datetime	Due Date	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
id	int64	ID	☐	
isScheduled	boolean	Is Scheduled	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
parentPhaseID	int32	Parent Phase ID	☐	
phaseNumber	string	Phase Number	☐	
projectID	int32	Project ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
title	string	Title	☐	

214.1.2 ProjectsByParentIdPhasesId

Catalog: Autotask

Schema: PhasesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdPhasesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ProjectsByParentIdPhasesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
dueDate	datetime	Due Date	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
id	int64	ID	☐	
isScheduled	boolean	Is Scheduled	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
parentPhaseID	int32	Parent Phase ID	☐	
phaseNumber	string	Phase Number	☐	
projectID	int32	Project ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDate	datetime	Start Date	☐	
title	string	Title	☐	

215 Schema: PriceListMaterialCodes

215.1 Tables

215.1.1 PriceListMaterialCodes

Catalog: Autotask

Schema: PriceListMaterialCodes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListMaterialCodes are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
billingCodeID	int32	Billing Code ID	☐	
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

215.1.2 PriceListMaterialCodesById

Catalog: Autotask

Schema: PriceListMaterialCodes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PriceListMaterialCodesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PriceListMaterialCodesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int32	Billing Code ID	☐	
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

215.1.3 PriceListMaterialCodesCount

Catalog: Autotask

Schema: PriceListMaterialCodes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListMaterialCodesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

216 Schema: PriceListProducts

216.1 Tables

216.1.1 PriceListProducts

Catalog: Autotask

Schema: PriceListProducts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProducts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
productID	int32	Product ID	☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

216.1.2 PriceListProductsById

Catalog: Autotask

Schema: PriceListProducts

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PriceListProductsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PriceListProductsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
productID	int32	Product ID	☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

216.1.3 PriceListProductsCount

Catalog: Autotask

Schema: PriceListProducts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

217 Schema: PriceListProductTiers

217.1 Tables

217.1.1 PriceListProductTiers

Catalog: Autotask

Schema: PriceListProductTiers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListProductTiers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
productTierID	int32	Product-tier ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

217.1.2 PriceListProductTiersById

Catalog: Autotask

Schema: PriceListProductTiers

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PriceListProductTiersById. A value must be provided at all times for required parameters, but

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PriceListProductTiersById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
productTierID	int32	Product-tier ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

217.1.3 PriceListProductTiersCount

Catalog: Autotask

Schema: PriceListProductTiers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table PriceListProductTiersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

218 Schema: PriceListRoles

218.1 Tables

218.1.1 PriceListRoles

Catalog: Autotask

Schema: PriceListRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListRoles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
hourlyRate	double	Hourly Rate	☐	
id	int64	ID	☐	
roleID	int32	Role ID	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

218.1.2 PriceListRolesById

Catalog: Autotask

Schema: PriceListRoles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PriceListRolesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PriceListRolesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
hourlyRate	double	Hourly Rate	☐	
id	int64	ID	☐	
roleID	int32	Role ID	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

218.1.3 PriceListRolesCount

Catalog: Autotask

Schema: PriceListRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListRolesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

219 Schema: PriceListServiceBundles

219.1 Tables

219.1.1 PriceListServiceBundles

Catalog: Autotask

Schema: PriceListServiceBundles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServiceBundles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
serviceBundleID	int32	Service Bundle ID	☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

219.1.2 PriceListServiceBundlesById

Catalog: Autotask

Schema: PriceListServiceBundles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PriceListServiceBundlesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function PriceListServiceBundlesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
serviceBundleID	int32	Service Bundle ID	☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

219.1.3 PriceListServiceBundlesCount

Catalog: Autotask

Schema: PriceListServiceBundles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServiceBundlesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

220 Schema: PriceListServices

220.1 Tables

220.1.1 PriceListServices

Catalog: Autotask

Schema: PriceListServices

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServices are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceID	int32	Service ID	☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

220.1.2 PriceListServicesById

Catalog: Autotask

Schema: PriceListServices

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PriceListServicesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PriceListServicesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
serviceID	int32	Service ID	☐	
unitPrice	double	Unit Price	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

220.1.3 PriceListServicesCount

Catalog: Autotask

Schema: PriceListServices

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListServicesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

221 Schema: PriceListWorkTypeModifiers

221.1 Tables

221.1.1 PriceListWorkTypeModifiers

Catalog: Autotask

Schema: PriceListWorkTypeModifiers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PriceListWorkTypeModifiers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
modifierType	int32	Modifier Type	☐	
modifierValue	double	Modifier Value	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	
workTypeModifierID	int32	Work Type Modifier ID	☐	

221.1.2 PriceListWorkTypeModifiersById

Catalog: Autotask

Schema: PriceListWorkTypeModifiers

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PriceListWorkTypeModifiersById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PriceListWorkTypeModifiersById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currencyID	int32	Currency ID	☐	
id	int64	ID	☐	
modifierType	int32	Modifier Type	☐	
modifierValue	double	Modifier Value	☐	
usesInternalCurrencyPrice	boolean	Uses Internal Currency Price	☐	
w orkTypeModifierID	int32	Work Type Modifier ID	☐	

221.1.3 PriceListWorkTypeModifiersCount

Catalog: Autotask

Schema: PriceListWorkTypeModifiers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table PriceListWorkTypeModifiersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

222 Schema: ProductNotes

222.1 Tables

222.1.1 ProductNotes

Catalog: Autotask

Schema: ProductNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

222.1.2 ProductNotesById

Catalog: Autotask

Schema: ProductNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProductNotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

222.1.3 ProductNotesCount

Catalog: Autotask

Schema: ProductNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductNotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

223 Schema: ProductNotesChild

223.1 Tables

223.1.1 ProductsByParentIdNotes

Catalog: Autotask

Schema: ProductNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

223.1.2 ProductsByParentIdNotesId

Catalog: Autotask

Schema: ProductNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ProductsByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdNotesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

224 Schema: Products

224.1 Tables

224.1.1 Products

Catalog: Autotask

Schema: Products

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Products are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingType	int32	Billing Type	☐	
chargeBillingCodeID	int32	Charge Billing Code ID	☐	
defaultInstalledProductCategoryID	int32	Defaul linstalled Product Category ID	☐	
defaultVendorID	int32	Default Vendor ID	☐	
description	string	Description	☐	
doesNotRequireProcurement	boolean	Does not require Procurement	☐	
externalProductID	string	External Product ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
internalProductID	string	Internal Product ID	☐	
isActive	boolean	Is Active	☐	
isEligibleForRma	boolean	Is Eligible for RMA	☐	
isSerialized	boolean	Is Serialized	☐	
link	string	Link	☐	
manufacturerName	string	Manufacturer Name	☐	
manufacturerProductName	string	Manufacturer Product Name	☐	
markupRate	double	Mark-up Rate	☐	
msrp	double	MSRP	☐	
name	string	Name	☐	
periodType	int32	Period Type	☐	
priceCostMethod	int32	Price Cost Method	☐	
productBillingCodeID	int32	Product Billing Code ID	☐	
productCategory	int32	Product Category	☐	
sku	string	SKU	☐	
unitCost	double	Unit Cost	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
unitPrice	double	Unit Price	☐	
vendorProductNumber	string	Vendor Product Number	☐	

224.1.2 Products_ItemsUserDefinedFields

Catalog: Autotask

Schema: Products

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Products_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingType	int32	Billing Type	☐	
chargeBillingCodeID	int32	Charge Billing Code ID	☐	
defaultInstalledProductCategoryID	int32	Defaul linstalled Product Category ID	☐	
defaultVendorID	int32	Default Vendor ID	☐	
description	string	Description	☐	
doesNotRequireProcurement	boolean	Does not require Procurement	☐	
externalProductID	string	External Product ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
internalProductID	string	Internal Product ID	☐	
isActive	boolean	Is Active	☐	
isEligibleForRma	boolean	Is Eligible for RMA	☐	
isSerialized	boolean	Is Serialized	☐	
link	string	Link	☐	
manufacturerName	string	Manufacturer Name	☐	
manufacturerProductName	string	Manufacturer Product Name	☐	
markupRate	double	Mark-up Rate	☐	
msrp	double	MSRP	☐	
name_1	string	Name	☐	
name	string	Name	☐	
periodType	int32	Period Type	☐	
priceCostMethod	int32	Price Cost Method	☐	
productBillingCodeID	int32	Product Billing Code ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
productCategory	int32	Product Category	☐	
sku	string	SKU	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
value	string	Value	☐	
vendorProductNumber	string	Vendor Product Number	☐	

224.1.3 ProductsById

Catalog: Autotask

Schema: Products

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProductsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingType	int32	Billing Type	☐	
chargeBillingCodeID	int32	Charge Billing Code ID	☐	
defaultInstalledProductCategoryID	int32	Defaul linstalled Product Category ID	☐	
defaultVendorID	int32	Default Vendor ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
doesNotRequireProcurement	boolean	Does not require Procurement	☐	
externalProductID	string	External Product ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
internalProductID	string	Internal Product ID	☐	
isActive	boolean	Is Active	☐	
isEligibleForRma	boolean	Is Eligible for RMA	☐	
isSerialized	boolean	Is Serialized	☐	
link	string	Link	☐	
manufacturerName	string	Manufacturer Name	☐	
manufacturerProductName	string	Manufacturer Product Name	☐	
markupRate	double	Mark-up Rate	☐	
msrp	double	MSRP	☐	
name	string	Name	☐	
periodType	int32	Period Type	☐	
priceCostMethod	int32	Price Cost Method	☐	
productBillingCodeID	int32	Product Billing Code ID	☐	
productCategory	int32	Product Category	☐	
sku	string	SKU	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
vendorProductNumber	string	Vendor Product Number	☐	

224.1.4 ProductsCount

Catalog: Autotask

Schema: Products

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

225 Schema: ProductTiers

225.1 Tables

225.1.1 ProductTiers

Catalog: Autotask

Schema: ProductTiers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductTiers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
upToUnitCount	double	Up-to Unit Count	☐	

225.1.2 ProductTiersById

Catalog: Autotask

Schema: ProductTiers

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductTiersById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProductTiersById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
upToUnitCount	double	Up-to Unit Count	☐	

225.1.3 ProductTiersCount

Catalog: Autotask

Schema: ProductTiers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ProductTiersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

226 Schema: ProductTiersChild

226.1 Tables

226.1.1 ProductsByParentIdTiers

Catalog: Autotask

Schema: ProductTiersChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdTiers. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdTiers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
upToUnitCount	double	Up-to Unit Count	☐	

226.1.2 ProductsByParentIdTiersId

Catalog: Autotask

Schema: ProductTiersChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdTiersId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdTiersId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
upToUnitCount	double	Up-to Unit Count	☐	

227 Schema: ProductVendors

227.1 Tables

227.1.1 ProductVendors

Catalog: Autotask

Schema: ProductVendors

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductVendors are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
vendorCost	double	Vendor Cost	☐	
vendorID	int32	Vendor ID	☐	
vendorPartNumber	string	Vendor Part Number	☐	

227.1.2 ProductVendorsById

Catalog: Autotask

Schema: ProductVendors

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductVendorsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProductVendorsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
productID	int32	Product ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
vendorCost	double	Vendor Cost	☐	
vendorID	int32	Vendor ID	☐	
vendorPartNumber	string	Vendor Part Number	☐	

227.1.3 ProductVendorsCount

Catalog: Autotask

Schema: ProductVendors

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProductVendorsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

228 Schema: ProductVendorsChild

228.1 Tables

228.1.1 ProductsByParentIdVendors

Catalog: Autotask

Schema: ProductVendorsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdVendors. A value must be provided at all times for required parameters,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdVendors are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
vendorCost	double	Vendor Cost	☐	
vendorID	int32	Vendor ID	☐	
vendorPartNumber	string	Vendor Part Number	☐	

228.1.2 ProductsByParentIdVendorsId

Catalog: Autotask

Schema: ProductVendorsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProductsByParentIdVendorsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProductsByParentIdVendorsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
productID	int32	Product ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
vendorCost	double	Vendor Cost	☐	
vendorID	int32	Vendor ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
vendorPartNumber	string	Vendor Part Number	☐	

229 Schema: ProjectAttachments

229.1 Tables

229.1.1 ProjectAttachments

Catalog: Autotask

Schema: ProjectAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

229.1.2 ProjectAttachmentsById

Catalog: Autotask

Schema: ProjectAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProjectAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

229.1.3 ProjectAttachmentsCount

Catalog: Autotask

Schema: ProjectAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

230 Schema: ProjectAttachmentsChild

230.1 Tables

230.1.1 ProjectsByParentIdAttachments

Catalog: Autotask

Schema: ProjectAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

230.1.2 ProjectsByParentIdAttachmentsId

Catalog: Autotask

Schema: ProjectAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
title	string	Title	☐	

231 Schema: ProjectCharges

231.1 Tables

231.1.1 ProjectCharges

Catalog: Autotask

Schema: ProjectCharges

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectCharges are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
estimatedCost	double	Estimated Cost	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
projectID	int64	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

231.1.2 ProjectChargesById

Catalog: Autotask

Schema: ProjectCharges

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectChargesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProjectChargesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
estimatedCost	double	Estimated Cost	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
projectID	int64	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

231.1.3 ProjectChargesCount

Catalog: Autotask

Schema: ProjectCharges

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectChargesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

232 Schema: ProjectChargesChild

232.1 Tables

232.1.1 ProjectsByParentIdCharges

Catalog: Autotask

Schema: ProjectChargesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdCharges. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdCharges are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
estimatedCost	double	Estimated Cost	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
projectID	int64	Project ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

232.1.2 ProjectsByParentIdChargesId

Catalog: Autotask

Schema: ProjectChargesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdChargesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdChargesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
estimatedCost	double	Estimated Cost	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
projectID	int64	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

233 Schema: ProjectNoteAttachments

233.1 Tables

233.1.1 ProjectNoteAttachments

Catalog: Autotask

Schema: ProjectNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNoteAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

233.1.2 ProjectNoteAttachmentsById

Catalog: Autotask

Schema: ProjectNoteAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectNoteAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProjectNoteAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

233.1.3 ProjectNoteAttachmentsCount

Catalog: Autotask

Schema: ProjectNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNoteAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

234 Schema: ProjectNoteAttachmentsChild

234.1 Tables

234.1.1 ProjectNotesByParentIdAttachments

Catalog: Autotask

Schema: ProjectNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectNotesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectNotesByParentIdAttachments are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

234.1.2 ProjectNotesByParentIdAttachmentsId

Catalog: Autotask

Schema: ProjectNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectNotesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectNotesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
projectID	int32	Project ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
projectNoteID	int32	Project Note ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

235 Schema: ProjectNotes

235.1 Tables

235.1.1 ProjectNotes

Catalog: Autotask

Schema: ProjectNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
isAnnouncement	boolean	Is Announcement	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
projectID	int32	Project ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

235.1.2 ProjectNotesById

Catalog: Autotask

Schema: ProjectNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProjectNotesById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
isAnnouncement	boolean	Is Announcement	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
projectID	int32	Project ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

235.1.3 ProjectNotesCount

Catalog: Autotask

Schema: ProjectNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectNotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

236 Schema: ProjectNotesChild

236.1 Tables

236.1.1 ProjectsByParentIdNotes

Catalog: Autotask

Schema: ProjectNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
isAnnouncement	boolean	Is Announcement	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
projectID	int32	Project ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

236.1.2 ProjectsByParentIdNotesId

Catalog: Autotask

Schema: ProjectNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ProjectsByParentIdNotesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
isAnnouncement	boolean	Is Announcement	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
projectID	int32	Project ID	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

237 Schema: Projects

237.1 Tables

237.1.1 Projects

Catalog: Autotask

Schema: Projects

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Projects are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
actualBilledHours	double	Actual Billed Hours	☐	
actualHours	double	Actual Hours	☐	
changeOrdersBudget	double	Change Orders Budget	☐	
changeOrdersRevenue	double	Change Orders Revenue	☐	
companyID	int32	Company ID	☐	
companyOwnerResourceID	int32	Company-owner Resource ID	☐	
completedDateTime	datetime	Completed	☐	
completedPercentage	int32	Completed Percentage	☐	
contractID	int32	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
department	int32	Department	☐	
description	string	Description	☐	
duration	int32	Duration	☐	
endDateTime	datetime	End Date/Time	☐	
estimatedSalesCost	double	Estimated Sales Cost	☐	
estimatedTime	double	Estimated Time	☐	
extProjectNumber	string	External Project Number	☐	
extProjectType	int32	External Project Type	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
laborEstimatedCosts	double	Labor Estimated Costs	☐	
laborEstimatedMarginPercentage	double	Labor Estimated Margin Percentage	☐	
laborEstimatedRevenue	double	Labor Estimated Revenue	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
originalEstimatedRevenue	double	Original Estimated Revenue	☐	
projectCostEstimatedMarginPercentage	double	Project Cost Estimated Margin Percentage	☐	
projectCostsBudget	double	Project Costs Budget	☐	
projectCostsRevenue	double	Project Costs Revenue	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
projectLeadResourceID	int32	Project Lead Resource ID	☐	
projectName	string	Project Name	☐	
projectNumber	string	Project Number	☐	
projectType	int32	Project Type	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
sgda	double	SGDA	☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
statusDateTime	datetime	Status Date/Time	☐	
statusDetail	string	Status Detail	☐	

237.1.2 Projects_ItemsUserDefinedFields

Catalog: Autotask

Schema: Projects

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Projects_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actualBilledHours	double	Actual Billed Hours	☐	
actualHours	double	Actual Hours	☐	
changeOrdersBudget	double	Change Orders Budget	☐	
changeOrdersRevenue	double	Change Orders Revenue	☐	
companyID	int32	Company ID	☐	
companyOwnerResourceID	int32	Company-owner Resource ID	☐	
completedDateTime	datetime	Completed	☐	
completedPercentage	int32	Completed Percentage	☐	
contractID	int32	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
department	int32	Department	☐	
description	string	Description	☐	
duration	int32	Duration	☐	
endDateTime	datetime	End Date/Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimatedSalesCost	double	Estimated Sales Cost	☐	
estimatedTime	double	Estimated Time	☐	
extProjectNumber	string	External Project Number	☐	
extProjectType	int32	External Project Type	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
laborEstimatedCosts	double	Labor Estimated Costs	☐	
laborEstimatedMarginPercentage	double	Labor Estimated Margin Percentage	☐	
laborEstimatedRevenue	double	Labor Estimated Revenue	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
name	string	Name	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
originalEstimatedRevenue	double	Original Estimated Revenue	☐	
projectCostEstimatedMarginPercentage	double	Project Cost Estimated Margin Percentage	☐	
projectCostsBudget	double	Project Costs Budget	☐	
projectCostsRevenue	double	Project Costs Revenue	☐	
projectLeadResourceID	int32	Project Lead Resource ID	☐	
projectName	string	Project Name	☐	
projectNumber	string	Project Number	☐	
projectType	int32	Project Type	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
sgda	double	SGDA	☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
statusDateTime	datetime	Status Date/Time	☐	
statusDetail	string	Status Detail	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

237.1.3 ProjectsById

Catalog: Autotask

Schema: Projects

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ProjectsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
actualBilledHours	double	Actual Billed Hours	☐	
actualHours	double	Actual Hours	☐	
changeOrdersBudget	double	Change Orders Budget	☐	
changeOrdersRevenue	double	Change Orders Revenue	☐	
companyID	int32	Company ID	☐	
companyOwnerResourceID	int32	Company-owner Resource ID	☐	
completedDateTime	datetime	Completed	☐	
completedPercentage	int32	Completed Percentage	☐	
contractID	int32	Contract ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
department	int32	Department	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
duration	int32	Duration	☐	
endDateTime	datetime	End Date/Time	☐	
estimatedSalesCost	double	Estimated Sales Cost	☐	
estimatedTime	double	Estimated Time	☐	
extProjectNumber	string	External Project Number	☐	
extProjectType	int32	External Project Type	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
laborEstimatedCosts	double	Labor Estimated Costs	☐	
laborEstimatedMarginPercentage	double	Labor Estimated Margin Percentage	☐	
laborEstimatedRevenue	double	Labor Estimated Revenue	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
originalEstimatedRevenue	double	Original Estimated Revenue	☐	
projectCostEstimatedMarginPercentage	double	Project Cost Estimated Margin Percentage	☐	
projectCostsBudget	double	Project Costs Budget	☐	
projectCostsRevenue	double	Project Costs Revenue	☐	
projectLeadResourceID	int32	Project Lead Resource ID	☐	
projectName	string	Project Name	☐	
projectNumber	string	Project Number	☐	
projectType	int32	Project Type	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
sgda	double	SGDA	☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
statusDateTime	datetime	Status Date/Time	☐	
statusDetail	string	Status Detail	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

237.1.4 ProjectsCount

Catalog: Autotask

Schema: Projects

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ProjectsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

238 Schema: PurchaseApprovals

238.1 Tables

238.1.1 PurchaseApprovals

Catalog: Autotask

Schema: PurchaseApprovals

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseApprovals are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
costType	string	Cost Type	☐	
id	int64	ID	☐	
isApproved	boolean	Is Approved	☐	
rejectNote	string	Reject Note	☐	

238.1.2 PurchaseApprovalsById

Catalog: Autotask

Schema: PurchaseApprovals

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function PurchaseApprovalsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PurchaseApprovalsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
costType	string	Cost Type	☐	
id	int64	ID	☐	
isApproved	boolean	Is Approved	☐	
rejectNote	string	Reject Note	☐	

238.1.3 PurchaseApprovalsCount

Catalog: Autotask

Schema: PurchaseApprovals

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseApprovalsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

239 Schema: PurchaseOrderItemReceiving

239.1 Tables

239.1.1 PurchaseOrderItemReceiving

Catalog: Autotask

Schema: PurchaseOrderItemReceiving

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemReceiving are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
purchaseOrderItemID	int64	Purchase Order Item ID	☐	
quantityBackOrdered	int32	Quantity Backordered	☐	
quantityNow Receiving	int32	Quantity Now Receiving	☐	
quantityPreviouslyReceived	int32	Quantity Previously Received	☐	
receiveDate	datetime	Receive Date	☐	
receivedByResourceID	int32	Received by Resource ID	☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

239.1.2 PurchaseOrderItemReceivingById

Catalog: Autotask

Schema: PurchaseOrderItemReceiving

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemReceivingById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PurchaseOrderItemReceivingById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
purchaseOrderItemID	int64	Purchase Order Item ID	☐	
quantityBackOrdered	int32	Quantity Backordered	☐	
quantityNow Receiving	int32	Quantity Now Receiving	☐	
quantityPreviouslyReceived	int32	Quantity Previously Received	☐	
receiveDate	datetime	Receive Date	☐	
receivedByResourceID	int32	Received by Resource ID	☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

239.1.3 PurchaseOrderItemReceivingCount

Catalog: Autotask

Schema: PurchaseOrderItemReceiving

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemReceivingCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

240 Schema: PurchaseOrderItemReceivingChild

240.1 Tables

240.1.1 PurchaseOrderItemsByParentIdReceiving

Catalog: Autotask

Schema: PurchaseOrderItemReceivingChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemsByParentIdReceiving. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function PurchaseOrderItemsByParentIdReceiving are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
purchaseOrderItemID	int64	Purchase Order Item ID	☐	
quantityBackOrdered	int32	Quantity Backordered	☐	
quantityNow Receiving	int32	Quantity Now Receiving	☐	
quantityPreviouslyReceived	int32	Quantity Previously Received	☐	
receiveDate	datetime	Receive Date	☐	
receivedByResourceID	int32	Received by Resource ID	☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

240.1.2 PurchaseOrderItemsByParentIdReceivingId

Catalog: Autotask

Schema: PurchaseOrderItemReceivingChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemsByParentIdReceivingId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function PurchaseOrderItemsByParentIdReceivingId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
purchaseOrderItemID	int64	Purchase Order Item ID	☐	
quantityBackOrdered	int32	Quantity Backordered	☐	
quantityNow Receiving	int32	Quantity Now Receiving	☐	
quantityPreviouslyReceived	int32	Quantity Previously Received	☐	
receiveDate	datetime	Receive Date	☐	
receivedByResourceID	int32	Received by Resource ID	☐	
serialNumber	string	Serial Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

241 Schema: PurchaseOrderItems

241.1 Tables

241.1.1 PurchaseOrderItems

Catalog: Autotask

Schema: PurchaseOrderItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
chargeID	int32	Charge ID	☐	
contractID	int64	Contract ID	☐	
estimatedArrivalDate	datetime	Estimated Arrival	☐	
id	int64	ID	☐	
internalCurrencyUnitCost	double	Internal Currency Unit Cost	☐	
inventoryLocationID	int32	Inventory Location ID	☐	
memo	string	Memo	☐	
orderID	int32	Order ID	☐	
productID	int32	Product ID	☐	
projectID	int64	Project ID	☐	
quantity	int32	Quantity	☐	
salesOrderID	int64	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
ticketID	int64	Ticket ID	☐	
unitCost	double	Unit Cost	☐	

241.1.2 PurchaseOrderItemsById

Catalog: Autotask

Schema: PurchaseOrderItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrderItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PurchaseOrderItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
chargeID	int32	Charge ID	☐	
contractID	int64	Contract ID	☐	
estimatedArrivalDate	datetime	Estimated Arrival	☐	
id	int64	ID	☐	
internalCurrencyUnitCost	double	Internal Currency Unit Cost	☐	
inventoryLocationID	int32	Inventory Location ID	☐	
memo	string	Memo	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
orderID	int32	Order ID	☐	
productID	int32	Product ID	☐	
projectID	int64	Project ID	☐	
quantity	int32	Quantity	☐	
salesOrderID	int64	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int64	Ticket ID	☐	
unitCost	double	Unit Cost	☐	

241.1.3 PurchaseOrderItemsCount

Catalog: Autotask

Schema: PurchaseOrderItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrderItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

242 Schema: PurchaseOrderItemsChild

242.1 Tables

242.1.1 PurchaseOrdersByParentIdItems

Catalog: Autotask

Schema: PurchaseOrderItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrdersByParentIdItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function PurchaseOrdersByParentIdItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
chargeID	int32	Charge ID	☐	
contractID	int64	Contract ID	☐	
estimatedArrivalDate	datetime	Estimated Arrival	☐	
id	int64	ID	☐	
internalCurrencyUnitCost	double	Internal Currency Unit Cost	☐	
inventoryLocationID	int32	Inventory Location ID	☐	
memo	string	Memo	☐	
orderID	int32	Order ID	☐	
productID	int32	Product ID	☐	
projectID	int64	Project ID	☐	
quantity	int32	Quantity	☐	
salesOrderID	int64	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int64	Ticket ID	☐	
unitCost	double	Unit Cost	☐	

242.1.2 PurchaseOrdersByParentIdItemsId

Catalog: Autotask

Schema: PurchaseOrderItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrdersByParentIdItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function PurchaseOrdersByParentIdItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
chargeID	int32	Charge ID	☐	
contractID	int64	Contract ID	☐	
estimatedArrivalDate	datetime	Estimated Arrival	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
internalCurrencyUnitCost	double	Internal Currency Unit Cost	☐	
inventoryLocationID	int32	Inventory Location ID	☐	
memo	string	Memo	☐	
orderID	int32	Order ID	☐	
productID	int32	Product ID	☐	
projectID	int64	Project ID	☐	
quantity	int32	Quantity	☐	
salesOrderID	int64	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int64	Ticket ID	☐	
unitCost	double	Unit Cost	☐	

243 Schema: PurchaseOrders

243.1 Tables

243.1.1 PurchaseOrders

Catalog: Autotask

Schema: PurchaseOrders

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrders are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
cancelDateTime	datetime	Cancel Date/Time	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
externalPONumber	string	External PO Number	☐	
fax	string	Fax	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
freight	double	Freight	☐	
generalMemo	string	General Memo	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
internalCurrencyFreight	double	Internal Currency Freight	☐	
latestEstimatedArrivalDate	datetime	Latest Estimated Arrival Date	☐	
paymentTerm	int32	Payment Term	☐	
phone	string	Phone	☐	
purchaseForCompanyID	int32	Purchase for Company ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
purchaseOrderTemplateID	int32	Purchase Order Template ID	☐	
shippingDate	datetime	Shipping Date	☐	
shippingType	int32	Shipping Type	☐	
shipToAddress1	string	Ship-to Address 1	☐	
shipToAddress2	string	Ship-to Address 2	☐	
shipToCity	string	Ship-to City	☐	
shipToName	string	Ship-to Name	☐	
shipToPostalCode	string	Ship-to Postal Code	☐	
shipToState	string	Ship-to State	☐	
showEachTaxInGroup	boolean	Show Each Tax in Group	☐	
showTaxCategory	boolean	Show Tax Category	☐	
status	int32	Status	☐	
submitDateTime	datetime	Submit Date/Time	☐	
taxRegionID	int32	Tax Region ID	☐	
useItemDescriptionsFrom	int32	Use Item Descriptions from	☐	
vendorID	int32	Vendor ID	☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

243.1.2 PurchaseOrdersById

Catalog: Autotask

Schema: PurchaseOrders

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function PurchaseOrdersById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function PurchaseOrdersById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
cancelDateTime	datetime	Cancel Date/Time	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
externalPONumber	string	External PO Number	☐	
fax	string	Fax	☐	
freight	double	Freight	☐	
generalMemo	string	General Memo	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
internalCurrencyFreight	double	Internal Currency Freight	☐	
latestEstimatedArrivalDate	datetime	Latest Estimated Arrival Date	☐	
paymentTerm	int32	Payment Term	☐	
phone	string	Phone	☐	
purchaseForCompanyID	int32	Purchase for Company ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
purchaseOrderTemplateID	int32	Purchase Order Template ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
shippingDate	datetime	Shipping Date	☐	
shippingType	int32	Shipping Type	☐	
shipToAddress1	string	Ship-to Address 1	☐	
shipToAddress2	string	Ship-to Address 2	☐	
shipToCity	string	Ship-to City	☐	
shipToName	string	Ship-to Name	☐	
shipToPostalCode	string	Ship-to Postal Code	☐	
shipToState	string	Ship-to State	☐	
showEachTaxInGroup	boolean	Show Each Tax in Group	☐	
showTaxCategory	boolean	Show Tax Category	☐	
status	int32	Status	☐	
submitDateTime	datetime	Submit Date/Time	☐	
taxRegionID	int32	Tax Region ID	☐	
useItemDescriptionsFrom	int32	Use Item Descriptions from	☐	
vendorID	int32	Vendor ID	☐	
vendorInvoiceNumber	string	Vendor Invoice Number	☐	

243.1.3 PurchaseOrdersCount

Catalog: Autotask

Schema: PurchaseOrders

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table PurchaseOrdersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

244 Schema: QuoteItems

244.1 Tables

244.1.1 QuoteItems

Catalog: Autotask

Schema: QuoteItems

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
averageCost	double	Average Cost	☐	
chargeID	int32	Charge ID	☐	
description	string	Description	☐	
expenseID	int32	Expense ID	☐	
highestCost	double	Highest Cost	☐	
id	int64	ID	☐	
internalCurrencyLineDiscount	double	Internal Currency Line Discount	☐	
internalCurrencyUnitDiscount	double	Internal Currency Unit Discount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
isOptional	boolean	Is Optional	☐	
isTaxable	boolean	Is Taxable	☐	
laborID	int32	Labor ID	☐	
lineDiscount	double	Line Discount	☐	
markupRate	double	Mark-up Rate	☐	
name	string	Name	☐	
percentageDiscount	double	Discount Percentage	☐	
periodType	int32	Period Type	☐	
productID	int32	Product ID	☐	
quantity	double	Quantity	☐	
quoteID	int32	Quote ID	☐	
quoteItemType	int32	Quote Item Type	☐	
serviceBundleID	int32	Service Bundle ID	☐	
serviceID	int32	Service ID	☐	
shippingID	int32	Shipping ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
sortOrderID	int32	Sort Order ID	☐	
taxCategoryID	int32	Tax Category ID	☐	
totalEffectiveTax	double	Total Effective Tax	☐	
unitCost	double	Unit Cost	☐	
unitDiscount	double	Unit Discount	☐	
unitPrice	double	Unit Price	☐	

244.1.2 QuoteItemsById

Catalog: Autotask

Schema: QuoteItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuoteItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function QuoteItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
averageCost	double	Average Cost	☐	
chargeID	int32	Charge ID	☐	
description	string	Description	☐	
expenseID	int32	Expense ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
highestCost	double	Highest Cost	☐	
id	int64	ID	☐	
internalCurrencyLineDiscount	double	Internal Currency Line Discount	☐	
internalCurrencyUnitDiscount	double	Internal Currency Unit Discount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
isOptional	boolean	Is Optional	☐	
isTaxable	boolean	Is Taxable	☐	
laborID	int32	Labor ID	☐	
lineDiscount	double	Line Discount	☐	
markupRate	double	Mark-up Rate	☐	
name	string	Name	☐	
percentageDiscount	double	Discount Percentage	☐	
periodType	int32	Period Type	☐	
productID	int32	Product ID	☐	
quantity	double	Quantity	☐	
quoteID	int32	Quote ID	☐	
quoteItemType	int32	Quote Item Type	☐	
serviceBundleID	int32	Service Bundle ID	☐	
serviceID	int32	Service ID	☐	
shippingID	int32	Shipping ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
sortOrderID	int32	Sort Order ID	☐	
taxCategoryID	int32	Tax Category ID	☐	
totalEffectiveTax	double	Total Effective Tax	☐	
unitCost	double	Unit Cost	☐	
unitDiscount	double	Unit Discount	☐	
unitPrice	double	Unit Price	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

244.1.3 QuoteItemsCount

Catalog: Autotask

Schema: QuoteItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

245 Schema: QuoteItemsChild

245.1 Tables

245.1.1 QuotesByParentIdItems

Catalog: Autotask

Schema: QuoteItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuotesByParentIdItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function QuotesByParentIdItems are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
averageCost	double	Average Cost	☐	
chargeID	int32	Charge ID	☐	
description	string	Description	☐	
expenseID	int32	Expense ID	☐	
highestCost	double	Highest Cost	☐	
id	int64	ID	☐	
internalCurrencyLineDiscount	double	Internal Currency Line Discount	☐	
internalCurrencyUnitDiscount	double	Internal Currency Unit Discount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
isOptional	boolean	Is Optional	☐	
isTaxable	boolean	Is Taxable	☐	
laborID	int32	Labor ID	☐	
lineDiscount	double	Line Discount	☐	
markupRate	double	Mark-up Rate	☐	
name	string	Name	☐	
percentageDiscount	double	Discount Percentage	☐	
periodType	int32	Period Type	☐	
productID	int32	Product ID	☐	
quantity	double	Quantity	☐	
quoteID	int32	Quote ID	☐	
quoteItemType	int32	Quote Item Type	☐	
serviceBundleID	int32	Service Bundle ID	☐	
serviceID	int32	Service ID	☐	
shippingID	int32	Shipping ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
sortOrderID	int32	Sort Order ID	☐	
taxCategoryID	int32	Tax Category ID	☐	
totalEffectiveTax	double	Total Effective Tax	☐	
unitCost	double	Unit Cost	☐	
unitDiscount	double	Unit Discount	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
unitPrice	double	Unit Price	☐	

245.1.2 QuotesByParentIdItemsId

Catalog: Autotask

Schema: QuoteItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuotesByParentIdItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function QuotesByParentIdItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
averageCost	double	Average Cost	☐	
chargeID	int32	Charge ID	☐	
description	string	Description	☐	
expenseID	int32	Expense ID	☐	
highestCost	double	Highest Cost	☐	
id	int64	ID	☐	
internalCurrencyLineDiscount	double	Internal Currency Line Discount	☐	
internalCurrencyUnitDiscount	double	Internal Currency Unit Discount	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
isOptional	boolean	Is Optional	☐	
isTaxable	boolean	Is Taxable	☐	
laborID	int32	Labor ID	☐	
lineDiscount	double	Line Discount	☐	
markupRate	double	Mark-up Rate	☐	
name	string	Name	☐	
percentageDiscount	double	Discount Percentage	☐	
periodType	int32	Period Type	☐	
productID	int32	Product ID	☐	
quantity	double	Quantity	☐	
quoteID	int32	Quote ID	☐	
quoteItemType	int32	Quote Item Type	☐	
serviceBundleID	int32	Service Bundle ID	☐	
serviceID	int32	Service ID	☐	
shippingID	int32	Shipping ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
sortOrderID	int32	Sort Order ID	☐	
taxCategoryID	int32	Tax Category ID	☐	
totalEffectiveTax	double	Total Effective Tax	☐	
unitCost	double	Unit Cost	☐	
unitDiscount	double	Unit Discount	☐	
unitPrice	double	Unit Price	☐	

246 Schema: QuoteLocations

246.1 Tables

246.1.1 QuoteLocations

Catalog: Autotask

Schema: QuoteLocations

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteLocations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
address1	string	Address 1	☐	
address2	string	Address 2	☐	
city	string	City	☐	
id	int64	ID	☐	
postalCode	string	Postal Code	☐	
state	string	State	☐	

246.1.2 QuoteLocationsById

Catalog: Autotask

Schema: QuoteLocations

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuoteLocationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function QuoteLocationsById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
address1	string	Address 1	☐	
address2	string	Address 2	☐	
city	string	City	☐	
id	int64	ID	☐	
postalCode	string	Postal Code	☐	
state	string	State	☐	

246.1.3 QuoteLocationsCount

Catalog: Autotask

Schema: QuoteLocations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteLocationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

247 Schema: Quotes

247.1 Tables

247.1.1 Quotes

Catalog: Autotask

Schema: Quotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Quotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approvalStatus	int32	Approval Status	☐	
approvalStatusChangedByResourceID	int32	Approval Status Changed by Resource ID	☐	
approvalStatusChangedDate	datetime	Approval Status Changed Date	☐	
billToLocationID	int32	Bill-to Location ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
calculateTaxSeparately	boolean	Calculate Tax Separately	☐	
comment	string	Comment	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
extApprovalContactResponse	int32	External Approval Contact Response	☐	
extApprovalResponseDate	datetime	External Approval Response Date	☐	
extApprovalResponseSignature	string	External Approval Response Signature	☐	
externalQuoteNumber	string	External Quote Number	☐	
groupByID	int32	Group by ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	boolean	Is Active	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastModifiedBy	int32	Last Modified by	☐	
lastPublishedByResourceID	int32	Last Published by Resource ID	☐	
lastPublishedDateTime	datetime	Last Published Date/Time	☐	
name	string	Name	☐	
opportunityID	int32	Opportunity ID	☐	
paymentTerm	int32	Payment Term	☐	
paymentType	int32	Payment Type	☐	
primaryQuote	boolean	Primary Quote	☐	
proposalProjectID	int32	Proposal Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
quoteNumber	int32	Quote Number	☐	
quoteTemplateID	int32	Quote Template ID	☐	
shippingType	int32	Shipping Type	☐	
shipToLocationID	int32	Ship-to Location ID	☐	
showEachTaxInGroup	boolean	Show Each Tax in Group	☐	
showTaxCategory	boolean	Show Tax Category	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soldToLocationID	int32	Sold-to Location ID	☐	
taxRegionID	int32	Tax Region ID	☐	

247.1.2 QuotesById

Catalog: Autotask

Schema: Quotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function QuotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approvalStatus	int32	Approval Status	☐	
approvalStatusChangedByResourceID	int32	Approval Status Changed by Resource ID	☐	
approvalStatusChangedDate	datetime	Approval Status Changed Date	☐	
billToLocationID	int32	Bill-to Location ID	☐	
calculateTaxSeparately	boolean	Calculate Tax Separately	☐	
comment	string	Comment	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
extApprovalContactResponse	int32	External Approval Contact Response	☐	
extApprovalResponseDate	datetime	External Approval Response Date	☐	
extApprovalResponseSignature	string	External Approval Response Signature	☐	
externalQuoteNumber	string	External Quote Number	☐	
groupByID	int32	Group by ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isActive	boolean	Is Active	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastModifiedBy	int32	Last Modified by	☐	
lastPublishedByResourceID	int32	Last Published by Resource ID	☐	
lastPublishedDateTime	datetime	Last Published Date/Time	☐	
name	string	Name	☐	
opportunityID	int32	Opportunity ID	☐	
paymentTerm	int32	Payment Term	☐	
paymentType	int32	Payment Type	☐	
primaryQuote	boolean	Primary Quote	☐	
proposalProjectID	int32	Proposal Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
quoteNumber	int32	Quote Number	☐	
quoteTemplateID	int32	Quote Template ID	☐	
shippingType	int32	Shipping Type	☐	
shipToLocationID	int32	Ship-to Location ID	☐	
showEachTaxInGroup	boolean	Show Each Tax in Group	☐	
showTaxCategory	boolean	Show Tax Category	☐	
soldToLocationID	int32	Sold-to Location ID	☐	
taxRegionID	int32	Tax Region ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

247.1.3 QuotesCount

Catalog: Autotask

Schema: Quotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

248 Schema: QuoteTemplates

248.1 Tables

248.1.1 QuoteTemplates

Catalog: Autotask

Schema: QuoteTemplates

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteTemplates are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
calculateTaxSeparately	boolean	Calculate Tax Separately	☐	
createDate	datetime	Created	☐	
createdBy	int32	Created by	☐	
currencyNegativeFormat	string	Currency Negative Format	☐	
currencyPositiveFormat	string	Currency Positive Format	☐	
dateFormat	int32	Date Format	☐	
description	string	Description	☐	
displayTaxCategorySuperscripts	boolean	Display Tax Category Super Scripts	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
lastActivityBy	int32	Last Activity by	☐	
lastActivityDate	datetime	Last Activity Date	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberFormat	int32	Number Format	☐	
pageLayout	int32	Page Layout	☐	
pageNumberFormat	int32	Page Number Format	☐	
showEachTaxInGroup	boolean	Show Each Tax in Group	☐	
showGridHeader	boolean	Show Grid Header	☐	
showTaxCategory	boolean	Show Tax Category	☐	
showVerticalGridLines	boolean	Show Vertical Grid Lines	☐	

248.1.2 QuoteTemplatesById

Catalog: Autotask

Schema: QuoteTemplates

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function QuoteTemplatesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function QuoteTemplatesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
calculateTaxSeparately	boolean	Calculate Tax Separately	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
createdBy	int32	Created by	☐	
currencyNegativeFormat	string	Currency Negative Format	☐	
currencyPositiveFormat	string	Currency Positive Format	☐	
dateFormat	int32	Date Format	☐	
description	string	Description	☐	
displayTaxCategorySuperscripts	boolean	Display Tax Category Super Scripts	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
lastActivityBy	int32	Last Activity by	☐	
lastActivityDate	datetime	Last Activity Date	☐	
name	string	Name	☐	
numberFormat	int32	Number Format	☐	
pageLayout	int32	Page Layout	☐	
pageNumberFormat	int32	Page Number Format	☐	
showEachTaxInGroup	boolean	Show Each Tax in Group	☐	
showGridHeader	boolean	Show Grid Header	☐	
showTaxCategory	boolean	Show Tax Category	☐	
showVerticalGridLines	boolean	Show Vertical Grid Lines	☐	

248.1.3 QuoteTemplatesCount

Catalog: Autotask

Schema: QuoteTemplates

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table QuoteTemplatesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

249 Schema: ResourceAttachments

249.1 Tables

249.1.1 ResourceAttachments

Catalog: Autotask

Schema: ResourceAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
title	string	Title	☐	

249.1.2 ResourceAttachmentsById

Catalog: Autotask

Schema: ResourceAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourceAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ResourceAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

249.1.3 ResourceAttachmentsCount

Catalog: Autotask

Schema: ResourceAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

250 Schema: ResourceAttachmentsChild

250.1 Tables

250.1.1 ResourcesByParentIdAttachments

Catalog: Autotask

Schema: ResourceAttachmentsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
publish	int32	Publish	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

250.1.2 ResourcesByParentIdAttachmentsId

Catalog: Autotask

Schema: ResourceAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ResourcesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

251 Schema: ResourceRoleDepartments

251.1 Tables

251.1.1 ResourceRoleDepartments

Catalog: Autotask

Schema: ResourceRoleDepartments

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleDepartments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
departmentID	int32	Department ID	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
isDepartmentLead	boolean	Is Department Lead	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

251.1.2 ResourceRoleDepartmentsById

Catalog: Autotask

Schema: ResourceRoleDepartments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourceRoleDepartmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ResourceRoleDepartmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
departmentID	int32	Department ID	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
isDepartmentLead	boolean	Is Department Lead	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

251.1.3 ResourceRoleDepartmentsCount

Catalog: Autotask

Schema: ResourceRoleDepartments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleDepartmentsCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

252 Schema: ResourceRoleDepartmentsChild

252.1 Tables

252.1.1 ResourcesByParentIdRoleDepartments

Catalog: Autotask

Schema: ResourceRoleDepartmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleDepartments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleDepartments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
departmentID	int32	Department ID	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
isDepartmentLead	boolean	Is Department Lead	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

252.1.2 ResourcesByParentIdRoleDepartmentsId

Catalog: Autotask

Schema: ResourceRoleDepartmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleDepartmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleDepartmentsId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
departmentID	int32	Department ID	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
isDepartmentLead	boolean	Is Department Lead	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

253 Schema: ResourceRoleQueues

253.1 Tables

253.1.1 ResourceRoleQueues

Catalog: Autotask

Schema: ResourceRoleQueues

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleQueues are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
queueID	int32	Queue ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

253.1.2 ResourceRoleQueuesById

Catalog: Autotask

Schema: ResourceRoleQueues

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourceRoleQueuesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ResourceRoleQueuesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
queueID	int32	Queue ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

253.1.3 ResourceRoleQueuesCount

Catalog: Autotask

Schema: ResourceRoleQueues

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoleQueuesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

254 Schema: ResourceRoleQueuesChild

254.1 Tables

254.1.1 ResourcesByParentIdRoleQueues

Catalog: Autotask

Schema: ResourceRoleQueuesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleQueues. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleQueues are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
queueID	int32	Queue ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

254.1.2 ResourcesByParentIdRoleQueuesId

Catalog: Autotask

Schema: ResourceRoleQueuesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoleQueuesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoleQueuesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
queueID	int32	Queue ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

255 Schema: ResourceRoles

255.1 Tables

255.1.1 ResourceRoles

Catalog: Autotask

Schema: ResourceRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRoles are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
departmentID	int64	Department ID	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
queueID	int64	Queue ID	☐	
resourceID	int64	Resource ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

255.1.2 ResourceRolesById

Catalog: Autotask

Schema: ResourceRoles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourceRolesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ResourceRolesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
departmentID	int64	Department ID	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queueID	int64	Queue ID	☐	
resourceID	int64	Resource ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

255.1.3 ResourceRolesCount

Catalog: Autotask

Schema: ResourceRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceRolesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

256 Schema: ResourceRolesChild

256.1 Tables

256.1.1 ResourcesByParentIdRoles

Catalog: Autotask

Schema: ResourceRolesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRoles. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRoles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
departmentID	int64	Department ID	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
queueID	int64	Queue ID	☐	
resourceID	int64	Resource ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

256.1.2 ResourcesByParentIdRolesId

Catalog: Autotask

Schema: ResourceRolesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdRolesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdRolesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
departmentID	int64	Department ID	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
queueID	int64	Queue ID	☐	
resourceID	int64	Resource ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	

257 Schema: Resources

257.1 Tables

257.1.1 Resources

Catalog: Autotask

Schema: Resources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Resources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountingReferenceID	string	Accounting Reference ID	☐	
dateFormat	string	Date Format	☐	
defaultServiceDeskRoleID	int64	Default Service Desk Role ID	☐	
email	string	Email	☐	
email2	string	Email 2	☐	
email3	string	Email 3	☐	
emailTypeCode	string	Email Type Code	☐	
emailTypeCode2	string	Email Type Code 2	☐	
emailTypeCode3	string	Email Type Code 3	☐	
firstName	string	First Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
gender	string	Gender	☐	
greeting	int32	Greeting	☐	
hireDate	datetime	Hire Date	☐	
homePhone	string	Home Phone	☐	
id	int64	ID	☐	
initials	string	Initials	☐	
internalCost	double	Internal Cost	☐	
isActive	boolean	Is Active	☐	
lastName	string	Last Name	☐	
licenseType	int32	License Type	☐	
locationID	int32	Location ID	☐	
middleName	string	Middle Name	☐	
mobilePhone	string	Mobile Phone	☐	
numberFormat	string	Number Format	☐	
officeExtension	string	Office Extension	☐	
officePhone	string	Office Phone	☐	
payrollType	int32	Payroll Type	☐	
resourceType	string	Resource Type	☐	
suffix	int32	Suffix	☐	
surveyResourceRating	double	Survey Resource Rating	☐	
timeFormat	string	Time Format	☐	
title	string	Title	☐	
travelAvailabilityPct	string	Travel Availability (%)	☐	
userName	string	User Name	☐	
userType	int32	User Type	☐	

257.1.2 ResourcesById

Catalog: Autotask

Schema: Resources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountingReferenceID	string	Accounting Reference ID	☐	
dateFormat	string	Date Format	☐	
defaultServiceDeskRoleID	int64	Default Service Desk Role ID	☐	
email	string	Email	☐	
email2	string	Email 2	☐	
email3	string	Email 3	☐	
emailTypeCode	string	Email Type Code	☐	
emailTypeCode2	string	Email Type Code 2	☐	
emailTypeCode3	string	Email Type Code 3	☐	
firstName	string	First Name	☐	
gender	string	Gender	☐	
greeting	int32	Greeting	☐	
hireDate	datetime	Hire Date	☐	
homePhone	string	Home Phone	☐	
id	int64	ID	☐	
initials	string	Initials	☐	
internalCost	double	Internal Cost	☐	
isActive	boolean	Is Active	☐	
lastName	string	Last Name	☐	
licenseType	int32	License Type	☐	
locationID	int32	Location ID	☐	
middleName	string	Middle Name	☐	
mobilePhone	string	Mobile Phone	☐	
numberFormat	string	Number Format	☐	
officeExtension	string	Office Extension	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
officePhone	string	Office Phone	☐	
payrollType	int32	Payroll Type	☐	
resourceType	string	Resource Type	☐	
suffix	int32	Suffix	☐	
surveyResourceRating	double	Survey Resource Rating	☐	
timeFormat	string	Time Format	☐	
title	string	Title	☐	
travelAvailabilityPct	string	Travel Availability (%)	☐	
userName	string	User Name	☐	
userType	int32	User Type	☐	

257.1.3 ResourcesCount

Catalog: Autotask

Schema: Resources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

258 Schema: ResourceServiceDeskRoles

258.1 Tables

258.1.1 ResourceServiceDeskRoles

Catalog: Autotask

Schema: ResourceServiceDeskRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceServiceDeskRoles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

258.1.2 ResourceServiceDeskRolesById

Catalog: Autotask

Schema: ResourceServiceDeskRoles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourceServiceDeskRolesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ResourceServiceDeskRolesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

258.1.3 ResourceServiceDeskRolesCount

Catalog: Autotask

Schema: ResourceServiceDeskRoles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceServiceDeskRolesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

259 Schema: ResourceServiceDeskRolesChild

259.1 Tables

259.1.1 ResourcesByParentIdServiceDeskRoles

Catalog: Autotask

Schema: ResourceServiceDeskRolesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdServiceDeskRoles. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdServiceDeskRoles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

259.1.2 ResourcesByParentIdServiceDeskRolesId

Catalog: Autotask

Schema: ResourceServiceDeskRolesChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdServiceDeskRolesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdServiceDeskRolesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isDefault	boolean	Is Default	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

260 Schema: ResourceSkills

260.1 Tables

260.1.1 ResourceSkills

Catalog: Autotask

Schema: ResourceSkills

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ResourceSkills are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int64	Resource ID	☐	
skillDescription	string	Skill Description	☐	
skillID	int64	Skill ID	☐	
skillLevel	int64	Skill Level	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

260.1.2 ResourceSkillsById

Catalog: Autotask

Schema: ResourceSkills

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourceSkillsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ResourceSkillsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int64	Resource ID	☐	
skillDescription	string	Skill Description	☐	
skillID	int64	Skill ID	☐	
skillLevel	int64	Skill Level	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

260.1.3 ResourceSkillsCount

Catalog: Autotask

Schema: ResourceSkills

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ResourceSkillsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

261 Schema: ResourceSkillsChild

261.1 Tables

261.1.1 ResourcesByParentIdSkills

Catalog: Autotask

Schema: ResourceSkillsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdSkills. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdSkills are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int64	Resource ID	☐	
skillDescription	string	Skill Description	☐	
skillID	int64	Skill ID	☐	
skillLevel	int64	Skill Level	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

261.1.2 ResourcesByParentIdSkillsId

Catalog: Autotask

Schema: ResourceSkillsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdSkillsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdSkillsId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int64	Resource ID	☐	
skillDescription	string	Skill Description	☐	
skillID	int64	Skill ID	☐	
skillLevel	int64	Skill Level	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

262 Schema: Roles

262.1 Tables

262.1.1 Roles

Catalog: Autotask

Schema: Roles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Roles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
hourlyFactor	double	Hourly Factor	☐	
hourlyRate	double	Hourly Rate	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isExcludedFromNew Contracts	boolean	Is Excluded from New Contracts	☐	
isSystemRole	boolean	Is System Role	☐	
name	string	Name	☐	
quoteItemDefaultTaxCategoryId	int32	Quote Item Default Tax Category ID	☐	
roleType	int32	Role Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

262.1.2 RolesById

Catalog: Autotask

Schema: Roles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function RolesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function RolesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
hourlyFactor	double	Hourly Factor	☐	
hourlyRate	double	Hourly Rate	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isExcludedFromNew Contracts	boolean	Is Excluded from New Contracts	☐	
isSystemRole	boolean	Is System Role	☐	
name	string	Name	☐	
quoteItemDefaultTaxCategoryId	int32	Quote Item Default Tax Category ID	☐	
roleType	int32	Role Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

262.1.3 RolesCount

Catalog: Autotask

Schema: Roles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table RolesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

263 Schema: SalesOrderAttachments

263.1 Tables

263.1.1 SalesOrderAttachments

Catalog: Autotask

Schema: SalesOrderAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrderAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

263.1.2 SalesOrderAttachmentsById

Catalog: Autotask

Schema: SalesOrderAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SalesOrderAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function SalesOrderAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

263.1.3 SalesOrderAttachmentsCount

Catalog: Autotask

Schema: SalesOrderAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table SalesOrderAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

264 Schema: SalesOrderAttachmentsChild

264.1 Tables

264.1.1 SalesOrdersByParentIdAttachments

Catalog: Autotask

Schema: SalesOrderAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SalesOrdersByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function SalesOrdersByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

264.1.2 SalesOrdersByParentIdAttachmentsId

Catalog: Autotask

Schema: SalesOrderAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SalesOrdersByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function SalesOrdersByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
salesOrderID	int32	Sales Order ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
title	string	Title	☐	

265 Schema: SalesOrders

265.1 Tables

265.1.1 SalesOrders

Catalog: Autotask

Schema: SalesOrders

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrders are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalBillToAddressInformation	string	Additional Bill-to Address Information	☐	
additionalShipToAddressInformation	string	Additional Ship-to Address Information	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToCity	string	Bill-to City	☐	
billToCountryID	int32	Bill-to Country ID	☐	
billToPostalCode	string	Bill-to Postal Code	☐	
billToState	string	Bill-to State	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ownerResourceID	int32	Owner Resource ID	☐	
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
salesOrderDate	datetime	Sales Order Date	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
shipToAddress1	string	Ship-to Address 1	☐	
shipToAddress2	string	Ship-to Address 2	☐	
shipToCity	string	Ship-to City	☐	
shipToCountryID	int32	Ship-to Country ID	☐	
shipToPostalCode	string	Ship-to Postal Code	☐	
shipToState	string	Ship-to State	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	

265.1.2 SalesOrders_ItemsUserDefinedFields

Catalog: Autotask

Schema: SalesOrders

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrders_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalBillToAddressInformation	string	Additional Bill-to Address Information	☐	
additionalShipToAddressInformation	string	Additional Ship-to Address Information	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToCity	string	Bill-to City	☐	
billToCountryID	int32	Bill-to Country ID	☐	
billToPostalCode	string	Bill-to Postal Code	☐	
billToState	string	Bill-to State	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
name	string	Name	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ow nerResourceID	int32	Ow ner Resource ID	☐	
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
salesOrderDate	datetime	Sales Order Date	☐	
shipToAddress1	string	Ship-to Address 1	☐	
shipToAddress2	string	Ship-to Address 2	☐	
shipToCity	string	Ship-to City	☐	
shipToCountryID	int32	Ship-to Country ID	☐	
shipToPostalCode	string	Ship-to Postal Code	☐	
shipToState	string	Ship-to State	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	
value	string	Value	☐	

265.1.3 SalesOrdersById

Catalog: Autotask

Schema: SalesOrders

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function SalesOrdersById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function SalesOrdersById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalBillToAddressInformation	string	Additional Bill-to Address Information	☐	
additionalShipToAddressInformation	string	Additional Ship-to Address Information	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToCity	string	Bill-to City	☐	
billToCountryID	int32	Bill-to Country ID	☐	
billToPostalCode	string	Bill-to Postal Code	☐	
billToState	string	Bill-to State	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ownerResourceID	int32	Owner Resource ID	☐	
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
salesOrderDate	datetime	Sales Order Date	☐	
shipToAddress1	string	Ship-to Address 1	☐	
shipToAddress2	string	Ship-to Address 2	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
shipToCity	string	Ship-to City	☐	
shipToCountryID	int32	Ship-to Country ID	☐	
shipToPostalCode	string	Ship-to Postal Code	☐	
shipToState	string	Ship-to State	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	

265.1.4 SalesOrdersCount

Catalog: Autotask

Schema: SalesOrders

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SalesOrdersCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

266 Schema: SalesOrdersChild

266.1 Tables

266.1.1 OpportunitiesByParentId_ItemsUserDefinedFieldsSalesOrders

Catalog: Autotask

Schema: SalesOrdersChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentId_ItemsUserDefinedFieldsSalesOrders. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function OpportunitiesByParentId_ItemsUserDefinedFieldsSalesOrders are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalBillToAddressInformation	string	Additional Bill-to Address Information	☐	
additionalShipToAddressInformation	string	Additional Ship-to Address Information	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToCity	string	Bill-to City	☐	
billToCountryID	int32	Bill-to Country ID	☐	
billToPostalCode	string	Bill-to Postal Code	☐	
billToState	string	Bill-to State	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
name	string	Name	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ownerResourceID	int32	Owner Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
salesOrderDate	datetime	Sales Order Date	☐	
shipToAddress1	string	Ship-to Address 1	☐	
shipToAddress2	string	Ship-to Address 2	☐	
shipToCity	string	Ship-to City	☐	
shipToCountryID	int32	Ship-to Country ID	☐	
shipToPostalCode	string	Ship-to Postal Code	☐	
shipToState	string	Ship-to State	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	
value	string	Value	☐	

266.1.2 OpportunitiesByParentIdSalesOrders

Catalog: Autotask

Schema: SalesOrdersChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdSalesOrders. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function OpportunitiesByParentIdSalesOrders are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
additionalBillToAddressInformation	string	Additional Bill-to Address Information	☐	
additionalShipToAddressInformation	string	Additional Ship-to Address Information	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToCity	string	Bill-to City	☐	
billToCountryID	int32	Bill-to Country ID	☐	
billToPostalCode	string	Bill-to Postal Code	☐	
billToState	string	Bill-to State	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ownerResourceID	int32	Owner Resource ID	☐	
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
salesOrderDate	datetime	Sales Order Date	☐	
shipToAddress1	string	Ship-to Address 1	☐	
shipToAddress2	string	Ship-to Address 2	☐	
shipToCity	string	Ship-to City	☐	
shipToCountryID	int32	Ship-to Country ID	☐	
shipToPostalCode	string	Ship-to Postal Code	☐	
shipToState	string	Ship-to State	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	

266.1.3 OpportunitiesByParentIdSalesOrdersId

Catalog: Autotask

Schema: SalesOrdersChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function OpportunitiesByParentIdSalesOrdersId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function OpportunitiesByParentIdSalesOrdersId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
additionalBillToAddressInformation	string	Additional Bill-to Address Information	☐	
additionalShipToAddressInformation	string	Additional Ship-to Address Information	☐	
billingAddress1	string	Billing Address 1	☐	
billingAddress2	string	Billing Address 2	☐	
billToCity	string	Bill-to City	☐	
billToCountryID	int32	Bill-to Country ID	☐	
billToPostalCode	string	Bill-to Postal Code	☐	
billToState	string	Bill-to State	☐	
companyID	int32	Company ID	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
ownerResourceID	int32	Owner Resource ID	☐	
promisedFulfillmentDate	datetime	Promised Fulfillment Date	☐	
salesOrderDate	datetime	Sales Order Date	☐	
shipToAddress1	string	Ship-to Address 1	☐	
shipToAddress2	string	Ship-to Address 2	☐	
shipToCity	string	Ship-to City	☐	
shipToCountryID	int32	Ship-to Country ID	☐	
shipToPostalCode	string	Ship-to Postal Code	☐	
shipToState	string	Ship-to State	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int32	Status	☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

267 Schema: ServiceBundles

267.1 Tables

267.1.1 ServiceBundles

Catalog: Autotask

Schema: ServiceBundles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundles are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int32	Billing Code ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
invoiceDescription	string	Invoice Description	☐	
isActive	boolean	Is Active	☐	
lastModifiedDate	datetime	Last Modified	☐	
name	string	Name	☐	
percentageDiscount	double	Discount Percentage	☐	
periodType	int32	Period Type	☐	
serviceLevelAgreementID	int64	Service Level Agreement ID	☐	
unitCost	double	Unit Cost	☐	
unitDiscount	double	Unit Discount	☐	
unitPrice	double	Unit Price	☐	
updateResourceID	int32	Update Resource ID	☐	

267.1.2 ServiceBundlesById

Catalog: Autotask

Schema: ServiceBundles

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceBundlesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ServiceBundlesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int32	Billing Code ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
invoiceDescription	string	Invoice Description	☐	
isActive	boolean	Is Active	☐	
lastModifiedDate	datetime	Last Modified	☐	
name	string	Name	☐	
percentageDiscount	double	Discount Percentage	☐	
periodType	int32	Period Type	☐	
serviceLevelAgreementID	int64	Service Level Agreement ID	☐	
unitCost	double	Unit Cost	☐	
unitDiscount	double	Unit Discount	☐	
unitPrice	double	Unit Price	☐	
updateResourceID	int32	Update Resource ID	☐	

267.1.3 ServiceBundlesCount

Catalog: Autotask

Schema: ServiceBundles

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table ServiceBundlesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

268 Schema: ServiceBundleServices

268.1 Tables

268.1.1 ServiceBundleServices

Catalog: Autotask

Schema: ServiceBundleServices

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundleServices are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceBundleID	int64	Service Bundle ID	☐	
serviceID	int64	Service ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

268.1.2 ServiceBundleServicesById

Catalog: Autotask

Schema: ServiceBundleServices

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceBundleServicesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ServiceBundleServicesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceBundleID	int64	Service Bundle ID	☐	
serviceID	int64	Service ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

268.1.3 ServiceBundleServicesCount

Catalog: Autotask

Schema: ServiceBundleServices

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceBundleServicesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

269 Schema: ServiceBundleServicesChild

269.1 Tables

269.1.1 ServiceBundlesByParentIdServices

Catalog: Autotask

Schema: ServiceBundleServicesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceBundlesByParentIdServices. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceBundlesByParentIdServices are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
serviceBundleID	int64	Service Bundle ID	☐	
serviceID	int64	Service ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

269.1.2 ServiceBundlesByParentIdServicesId

Catalog: Autotask

Schema: ServiceBundleServicesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceBundlesByParentIdServicesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ServiceBundlesByParentIdServicesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceBundleID	int64	Service Bundle ID	☐	
serviceID	int64	Service ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

270 Schema: ServiceCalls

270.1 Tables

270.1.1 ServiceCalls

Catalog: Autotask

Schema: ServiceCalls

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCalls are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
cancelationNoticeHours	double	Cancelation Notice Hours	☐	
canceledByResourceID	int32	Canceled by Resource ID	☐	
canceledDateTime	datetime	Canceled Date/Time	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
duration	double	Duration	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isComplete	int32	Is Complete	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	

270.1.2 ServiceCallsById

Catalog: Autotask

Schema: ServiceCalls

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
cancelationNoticeHours	double	Cancelation Notice Hours	☐	
canceledByResourceID	int32	Canceled by Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
canceledDateTime	datetime	Canceled Date/Time	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
duration	double	Duration	☐	
endDateTime	datetime	End Date/Time	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isComplete	int32	Is Complete	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	

270.1.3 ServiceCallsCount

Catalog: Autotask

Schema: ServiceCalls

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

271 Schema: ServiceCallTaskResources

271.1 Tables

271.1.1 ServiceCallTaskResources

Catalog: Autotask

Schema: ServiceCallTaskResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ServiceCallTaskResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
serviceCallTaskID	int32	Service Call Task ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

271.1.2 ServiceCallTaskResourcesById

Catalog: Autotask

Schema: ServiceCallTaskResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTaskResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ServiceCallTaskResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
serviceCallTaskID	int32	Service Call Task ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

271.1.3 ServiceCallTaskResourcesCount

Catalog: Autotask

Schema: ServiceCallTaskResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTaskResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

272 Schema: ServiceCallTaskResourcesChild

272.1 Tables

272.1.1 ServiceCallTasksByParentIdResources

Catalog: Autotask

Schema: ServiceCallTaskResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTasksByParentIdResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallTasksByParentIdResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
serviceCallTaskID	int32	Service Call Task ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

272.1.2 ServiceCallTasksByParentIdResourcesId

Catalog: Autotask

Schema: ServiceCallTaskResourcesChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTasksByParentIdResourcesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallTasksByParentIdResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
serviceCallTaskID	int32	Service Call Task ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

273 Schema: ServiceCallTasks

273.1 Tables

273.1.1 ServiceCallTasks

Catalog: Autotask

Schema: ServiceCallTasks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTasks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceCallID	int32	Service Call ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

273.1.2 ServiceCallTasksById

Catalog: Autotask

Schema: ServiceCallTasks

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTasksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallTasksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceCallID	int32	Service Call ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

273.1.3 ServiceCallTasksCount

Catalog: Autotask

Schema: ServiceCallTasks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTasksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

274 Schema: ServiceCallTasksChild

274.1 Tables

274.1.1 ServiceCallsByParentIdTasks

Catalog: Autotask

Schema: ServiceCallTasksChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTasks. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTasks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceCallID	int32	Service Call ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

274.1.2 ServiceCallsByParentIdTasksId

Catalog: Autotask

Schema: ServiceCallTasksChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTasksId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTasksId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceCallID	int32	Service Call ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

275 Schema: ServiceCallTicketResources

275.1 Tables

275.1.1 ServiceCallTicketResources

Catalog: Autotask

Schema: ServiceCallTicketResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
serviceCallTicketID	int32	Service Call Ticket ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

275.1.2 ServiceCallTicketResourcesById

Catalog: Autotask

Schema: ServiceCallTicketResources

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallTicketResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
serviceCallTicketID	int32	Service Call Ticket ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

275.1.3 ServiceCallTicketResourcesCount

Catalog: Autotask

Schema: ServiceCallTicketResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

276 Schema: ServiceCallTicketResourcesChild

276.1 Tables

276.1.1 ServiceCallTicketsByParentIdResources

Catalog: Autotask

Schema: ServiceCallTicketResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketsByParentIdResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallTicketsByParentIdResources are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
serviceCallTicketID	int32	Service Call Ticket ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

276.1.2 ServiceCallTicketsByParentIdResourcesId

Catalog: Autotask

Schema: ServiceCallTicketResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketsByParentIdResourcesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function ServiceCallTicketsByParentIdResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
serviceCallTicketID	int32	Service Call Ticket ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

277 Schema: ServiceCallTickets

277.1 Tables

277.1.1 ServiceCallTickets

Catalog: Autotask

Schema: ServiceCallTickets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTickets are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceCallID	int32	Service Call ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

277.1.2 ServiceCallTicketsById

Catalog: Autotask

Schema: ServiceCallTickets

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallTicketsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallTicketsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceCallID	int32	Service Call ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

277.1.3 ServiceCallTicketsCount

Catalog: Autotask

Schema: ServiceCallTickets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceCallTicketsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

278 Schema: ServiceCallTicketsChild

278.1 Tables

278.1.1 ServiceCallsByParentIdTickets

Catalog: Autotask

Schema: ServiceCallTicketsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTickets. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTickets are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceCallID	int32	Service Call ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

278.1.2 ServiceCallsByParentIdTicketsId

Catalog: Autotask

Schema: ServiceCallTicketsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceCallsByParentIdTicketsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceCallsByParentIdTicketsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
serviceCallID	int32	Service Call ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

279 Schema: ServiceLevelAgreementResults

279.1 Tables

279.1.1 ServiceLevelAgreementResults

Catalog: Autotask

Schema: ServiceLevelAgreementResults

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceLevelAgreementResults are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
firstResponseElapsedHours	double	First Response Elapsed Hours	☐	
firstResponseInitiatingResourceID	int32	First Response Initiating Resource ID	☐	
firstResponseResourceID	int32	First Response Resource ID	☐	
id	int64	ID	☐	
isFirstResponseMet	boolean	Is First Response Met	☐	
isResolutionMet	boolean	Is Resolution Met	☐	
isResolutionPlanMet	boolean	Is Resolution Plan Met	☐	
resolutionElapsedHours	double	Resolution Elapsed Hours	☐	
resolutionPlanElapsedHours	double	Resolution Plan Elapsed Hours	☐	
resolutionPlanResourceID	int32	Resolution Plan Resource ID	☐	
resolutionResourceID	int32	Resolution Resource ID	☐	
serviceLevelAgreementName	string	Service Level Agreement Name	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
ticketID	int32	Ticket ID	☐	

279.1.2 ServiceLevelAgreementResultsById

Catalog: Autotask

Schema: ServiceLevelAgreementResults

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceLevelAgreementResultsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ServiceLevelAgreementResultsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
firstResponseElapsedHours	double	First Response Elapsed Hours	☐	
firstResponseInitiatingResourceID	int32	First Response Initiating Resource ID	☐	
firstResponseResourceID	int32	First Response Resource ID	☐	
id	int64	ID	☐	
isFirstResponseMet	boolean	Is First Response Met	☐	
isResolutionMet	boolean	Is Resolution Met	☐	
isResolutionPlanMet	boolean	Is Resolution Plan Met	☐	
resolutionElapsedHours	double	Resolution Elapsed Hours	☐	
resolutionPlanElapsedHours	double	Resolution Plan Elapsed Hours	☐	
resolutionPlanResourceID	int32	Resolution Plan Resource ID	☐	
resolutionResourceID	int32	Resolution Resource ID	☐	
serviceLevelAgreementName	string	Service Level Agreement Name	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
ticketID	int32	Ticket ID	☐	

279.1.3 ServiceLevelAgreementResultsCount

Catalog: Autotask

Schema: ServiceLevelAgreementResults

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServiceLevelAgreementResultsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

280 Schema: ServiceLevelAgreementResultsChild

280.1 Tables

280.1.1 ServiceLevelAgreementsByParentIdResults

Catalog: Autotask

Schema: ServiceLevelAgreementResultsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceLevelAgreementsByParentIdResults. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceLevelAgreementsByParentIdResults are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
firstResponseElapsedHours	double	First Response Elapsed Hours	☐	
firstResponseInitiatingResourceID	int32	First Response Initiating Resource ID	☐	
firstResponseResourceID	int32	First Response Resource ID	☐	
id	int64	ID	☐	
isFirstResponseMet	boolean	Is First Response Met	☐	
isResolutionMet	boolean	Is Resolution Met	☐	
isResolutionPlanMet	boolean	Is Resolution Plan Met	☐	
resolutionElapsedHours	double	Resolution Elapsed Hours	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
resolutionPlanElapsedHours	double	Resolution Plan Elapsed Hours	☐	
resolutionPlanResourceID	int32	Resolution Plan Resource ID	☐	
resolutionResourceID	int32	Resolution Resource ID	☐	
serviceLevelAgreementName	string	Service Level Agreement Name	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
ticketID	int32	Ticket ID	☐	

280.1.2 ServiceLevelAgreementsByParentIdResultsId

Catalog: Autotask

Schema: ServiceLevelAgreementResultsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServiceLevelAgreementsByParentIdResultsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ServiceLevelAgreementsByParentIdResultsId are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
firstResponseElapsedHours	double	First Response Elapsed Hours	☐	
firstResponseInitiatingResourceID	int32	First Response Initiating Resource ID	☐	
firstResponseResourceID	int32	First Response Resource ID	☐	
id	int64	ID	☐	
isFirstResponseMet	boolean	Is First Response Met	☐	
isResolutionMet	boolean	Is Resolution Met	☐	
isResolutionPlanMet	boolean	Is Resolution Plan Met	☐	
resolutionElapsedHours	double	Resolution Elapsed Hours	☐	
resolutionPlanElapsedHours	double	Resolution Plan Elapsed Hours	☐	
resolutionPlanResourceID	int32	Resolution Plan Resource ID	☐	
resolutionResourceID	int32	Resolution Resource ID	☐	
serviceLevelAgreementName	string	Service Level Agreement Name	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
ticketID	int32	Ticket ID	☐	

281 Schema: Services

281.1 Tables

281.1.1 Services

Catalog: Autotask

Schema: Services

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Services are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int32	Billing Code ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
invoiceDescription	string	Invoice Description	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
lastModifiedDate	datetime	Last Modified	☐	
markupRate	double	Mark-up Rate	☐	
name	string	Name	☐	
periodType	int32	Period Type	☐	
serviceLevelAgreementID	int64	Service Level Agreement ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
updateResourceID	int32	Update Resource ID	☐	
vendorCompanyID	int32	Vendor Company ID	☐	

281.1.2 ServicesById

Catalog: Autotask

Schema: Services

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ServicesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ServicesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int32	Billing Code ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
invoiceDescription	string	Invoice Description	☐	
isActive	boolean	Is Active	☐	
lastModifiedDate	datetime	Last Modified	☐	
markupRate	double	Mark-up Rate	☐	
name	string	Name	☐	
periodType	int32	Period Type	☐	
serviceLevelAgreementID	int64	Service Level Agreement ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
updateResourceID	int32	Update Resource ID	☐	
vendorCompanyID	int32	Vendor Company ID	☐	

281.1.3 ServicesCount

Catalog: Autotask

Schema: Services

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ServicesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

282 Schema: ShippingTypes

282.1 Tables

282.1.1 ShippingTypes

Catalog: Autotask

Schema: ShippingTypes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table ShippingTypes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int32	Billing Code ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

282.1.2 ShippingTypesById

Catalog: Autotask

Schema: ShippingTypes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ShippingTypesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function ShippingTypesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingCodeID	int32	Billing Code ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	

282.1.3 ShippingTypesCount

Catalog: Autotask

Schema: ShippingTypes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ShippingTypesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

283 Schema: Skills

283.1 Tables

283.1.1 Skills

Catalog: Autotask

Schema: Skills

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Skills are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
categoryID	int64	Category ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

283.1.2 SkillsById

Catalog: Autotask

Schema: Skills

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SkillsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function SkillsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
categoryID	int64	Category ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

283.1.3 SkillsCount

Catalog: Autotask

Schema: Skills

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SkillsCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

284 Schema: SubscriptionPeriods

284.1 Tables

284.1.1 SubscriptionPeriods

Catalog: Autotask

Schema: SubscriptionPeriods

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionPeriods are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
periodCost	double	Period Cost	☐	
periodDate	datetime	Period Date	☐	
periodPrice	double	Period Price	☐	
postedDate	datetime	Posted	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
subscriptionID	int32	Subscription ID	☐	

284.1.2 SubscriptionPeriodsById

Catalog: Autotask

Schema: SubscriptionPeriods

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionPeriodsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function SubscriptionPeriodsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
periodCost	double	Period Cost	☐	
periodDate	datetime	Period Date	☐	
periodPrice	double	Period Price	☐	
postedDate	datetime	Posted	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
subscriptionID	int32	Subscription ID	☐	

284.1.3 SubscriptionPeriodsCount

Catalog: Autotask

Schema: SubscriptionPeriods

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SubscriptionPeriodsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

285 Schema: SubscriptionPeriodsChild

285.1 Tables

285.1.1 SubscriptionsByParentIdPeriods

Catalog: Autotask

Schema: SubscriptionPeriodsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionsByParentIdPeriods. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function SubscriptionsByParentIdPeriods are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
periodCost	double	Period Cost	☐	
periodDate	datetime	Period Date	☐	
periodPrice	double	Period Price	☐	
postedDate	datetime	Posted	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
subscriptionID	int32	Subscription ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

285.1.2 SubscriptionsByParentIdPeriodsId

Catalog: Autotask

Schema: SubscriptionPeriodsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionsByParentIdPeriodsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function SubscriptionsByParentIdPeriodsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
periodCost	double	Period Cost	☐	
periodDate	datetime	Period Date	☐	
periodPrice	double	Period Price	☐	
postedDate	datetime	Posted	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
subscriptionID	int32	Subscription ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

286 Schema: Subscriptions

286.1 Tables

286.1.1 Subscriptions

Catalog: Autotask

Schema: Subscriptions

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Subscriptions are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
description	string	Description	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
materialCodeID	int32	Material Code ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
periodCost	double	Period Cost	☐	
periodPrice	double	Period Price	☐	
periodType	int32	Period Type	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
status	int32	Status	☐	
subscriptionName	string	Subscription Name	☐	
totalCost	double	Total Cost	☐	
totalPrice	double	Total Price	☐	
vendorID	int32	Vendor ID	☐	

286.1.2 Subscriptions_ItemsUserDefinedFields

Catalog: Autotask

Schema: Subscriptions

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table Subscriptions_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
description	string	Description	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
materialCodeID	int32	Material Code ID	☐	
name	string	Name	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
periodCost	double	Period Cost	☐	
periodPrice	double	Period Price	☐	
periodType	int32	Period Type	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
status	int32	Status	☐	
subscriptionName	string	Subscription Name	☐	
totalCost	double	Total Cost	☐	
totalPrice	double	Total Price	☐	
value	string	Value	☐	
vendorID	int32	Vendor ID	☐	

286.1.3 SubscriptionsById

Catalog: Autotask

Schema: Subscriptions

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SubscriptionsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function SubscriptionsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
description	string	Description	☐	
effectiveDate	datetime	Effective Date	☐	
expirationDate	datetime	Expiration Date	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
materialCodeID	int32	Material Code ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
periodCost	double	Period Cost	☐	
periodPrice	double	Period Price	☐	
periodType	int32	Period Type	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
status	int32	Status	☐	
subscriptionName	string	Subscription Name	☐	
totalCost	double	Total Cost	☐	
totalPrice	double	Total Price	☐	
vendorID	int32	Vendor ID	☐	

286.1.4 SubscriptionsCount

Catalog: Autotask

Schema: Subscriptions

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table SubscriptionsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

287 Schema: SurveyResults

287.1 Tables

287.1.1 SurveyResults

Catalog: Autotask

Schema: SurveyResults

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveyResults are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
companyRating	double	Company Rating	☐	
completeDate	datetime	Complete Date	☐	
contactID	int32	Contact ID	☐	
contactRating	double	Contact Rating	☐	
id	int64	ID	☐	
resourceRating	double	Resource Rating	☐	
sendDate	datetime	Send Date	☐	
surveyID	int32	Survey ID	☐	
surveyRating	double	Survey Rating	☐	
ticketID	int32	Ticket ID	☐	

287.1.2 SurveyResultsById

Catalog: Autotask

Schema: SurveyResults

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SurveyResultsById. A value must be provided at all times for required parameters, but

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function SurveyResultsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
companyID	int32	Company ID	☐	
companyRating	double	Company Rating	☐	
completeDate	datetime	Complete Date	☐	
contactID	int32	Contact ID	☐	
contactRating	double	Contact Rating	☐	
id	int64	ID	☐	
resourceRating	double	Resource Rating	☐	
sendDate	datetime	Send Date	☐	
surveyID	int32	Survey ID	☐	
surveyRating	double	Survey Rating	☐	
ticketID	int32	Ticket ID	☐	

287.1.3 SurveyResultsCount

Catalog: Autotask

Schema: SurveyResults

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveyResultsCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

288 Schema: Surveys

288.1 Tables

288.1.1 Surveys

Catalog: Autotask

Schema: Surveys

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Surveys are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
displayName	string	Display Name	☐	
id	int64	ID	☐	
name	string	Name	☐	

288.1.2 SurveysById

Catalog: Autotask

Schema: Surveys

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SurveysById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function SurveysById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
displayName	string	Display Name	☐	
id	int64	ID	☐	
name	string	Name	☐	

288.1.3 SurveysCount

Catalog: Autotask

Schema: Surveys

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table SurveysCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

289 Schema: TagAliases

289.1 Tables

289.1.1 TagAliases

Catalog: Autotask

Schema: TagAliases

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagAliases are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
alias	string	Alias	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

289.1.2 TagAliasesById

Catalog: Autotask

Schema: TagAliases

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagAliasesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TagAliasesById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
alias	string	Alias	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

289.1.3 TagAliasesCount

Catalog: Autotask

Schema: TagAliases

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagAliasesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

290 Schema: TagAliasesChild

290.1 Tables

290.1.1 TagsByParentIdAliases

Catalog: Autotask

Schema: TagAliasesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagsByParentIdAliases. A value must be provided at all times for required parameters, but

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TagsByParentIdAliases are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
alias	string	Alias	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

290.1.2 TagsByParentIdAliasesId

Catalog: Autotask

Schema: TagAliasesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function TagsByParentIdAliasesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TagsByParentIdAliasesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
alias	string	Alias	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	

291 Schema: TagGroups

291.1 Tables

291.1.1 TagGroups

Catalog: Autotask

Schema: TagGroups

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagGroups are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
displayColor	int32	Display Color	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

291.1.2 TagGroupsById

Catalog: Autotask

Schema: TagGroups

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagGroupsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TagGroupsById are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
displayColor	int32	Display Color	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	

291.1.3 TagGroupsCount

Catalog: Autotask

Schema: TagGroups

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagGroupsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

292 Schema: Tags

292.1 Tables

292.1.1 Tags

Catalog: Autotask

Schema: Tags

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Tags are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isExcludedFromAutomaticTagging	boolean	Is Excluded from Automatic Tagging	☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
lastModifiedDateTime	datetime	Last Modified	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
tagGroupID	int32	Tag Group ID	☐	

292.1.2 TagsById

Catalog: Autotask

Schema: Tags

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TagsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isExcludedFromAutomaticTagging	boolean	Is Excluded from Automatic Tagging	☐	
isSystem	boolean	Is System	☐	
label	string	Label	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
tagGroupID	int32	Tag Group ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

292.1.3 TagsCount

Catalog: Autotask

Schema: Tags

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TagsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

293 Schema: TaskAttachments

293.1 Tables

293.1.1 TaskAttachments

Catalog: Autotask

Schema: TaskAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

293.1.2 TaskAttachmentsById

Catalog: Autotask

Schema: TaskAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaskAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TaskAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

293.1.3 TaskAttachmentsCount

Catalog: Autotask

Schema: TaskAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

294 Schema: TaskAttachmentsChild

294.1 Tables

294.1.1 TasksByParentIdAttachments

Catalog: Autotask

Schema: TaskAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TasksByParentIdAttachments are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

294.1.2 TasksByParentIdAttachmentsId

Catalog: Autotask

Schema: TaskAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TasksByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

295 Schema: TaskNoteAttachments

295.1 Tables

295.1.1 TaskNoteAttachments

Catalog: Autotask

Schema: TaskNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNoteAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
title	string	Title	☐	

295.1.2 TaskNoteAttachmentsById

Catalog: Autotask

Schema: TaskNoteAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaskNoteAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TaskNoteAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

295.1.3 TaskNoteAttachmentsCount

Catalog: Autotask

Schema: TaskNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNoteAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

296 Schema: TaskNoteAttachmentsChild

296.1 Tables

296.1.1 TaskNotesByParentIdAttachments

Catalog: Autotask

Schema: TaskNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaskNotesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TaskNotesByParentIdAttachments are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
title	string	Title	☐	

296.1.2 TaskNotesByParentIdAttachmentsId

Catalog: Autotask

Schema: TaskNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function TaskNotesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TaskNotesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
taskNoteID	int32	Task Note ID	☐	
title	string	Title	☐	

297 Schema: TaskNotes

297.1 Tables

297.1.1 TaskNotes

Catalog: Autotask

Schema: TaskNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
title	string	Title	☐	

297.1.2 TaskNotesById

Catalog: Autotask

Schema: TaskNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaskNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TaskNotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
title	string	Title	☐	

297.1.3 TaskNotesCount

Catalog: Autotask

Schema: TaskNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskNotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

298 Schema: TaskNotesChild

298.1 Tables

298.1.1 TasksByParentIdNotes

Catalog: Autotask

Schema: TaskNotesChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TasksByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
title	string	Title	☐	

298.1.2 TasksByParentIdNotesId

Catalog: Autotask

Schema: TaskNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TasksByParentIdNotesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
title	string	Title	☐	

299 Schema: TaskPredecessors

299.1 Tables

299.1.1 TaskPredecessors

Catalog: Autotask

Schema: TaskPredecessors

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskPredecessors are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
lagDays	int32	Lag Days	☐	
predecessorTaskID	int32	Pre-decessor Task ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
successorTaskID	int32	Successor Task ID	☐	

299.1.2 TaskPredecessorsById

Catalog: Autotask

Schema: TaskPredecessors

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaskPredecessorsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TaskPredecessorsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
lagDays	int32	Lag Days	☐	
predecessorTaskID	int32	Pre-decessor Task ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
successorTaskID	int32	Successor Task ID	☐	

299.1.3 TaskPredecessorsCount

Catalog: Autotask

Schema: TaskPredecessors

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskPredecessorsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

300 Schema: TaskPredecessorsChild

300.1 Tables

300.1.1 TasksByParentIdPredecessors

Catalog: Autotask

Schema: TaskPredecessorsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdPredecessors. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TasksByParentIdPredecessors are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
lagDays	int32	Lag Days	☐	
predecessorTaskID	int32	Pre-decessor Task ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
successorTaskID	int32	Successor Task ID	☐	

300.1.2 TasksByParentIdPredecessorsId

Catalog: Autotask

Schema: TaskPredecessorsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdPredecessorsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TasksByParentIdPredecessorsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
lagDays	int32	Lag Days	☐	
predecessorTaskID	int32	Pre-decessor Task ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
successorTaskID	int32	Successor Task ID	☐	

301 Schema: Tasks

301.1 Tables

301.1.1 Tasks

Catalog: Autotask

Schema: Tasks

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Tasks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
assignedResourceID	int32	Assigned Resource ID	☐	
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	
canClientPortalUserCompleteTask	boolean	Can Client Portal User Complete Task	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedByType	int32	Completed by Type	☐	
completedDateTime	datetime	Completed	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	
departmentID	int32	Department ID	☐	
description	string	Description	☐	
endDateTime	datetime	End Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	
id	int64	ID	☐	
isTaskBillable	boolean	Is Task Billable	☐	
isVisibleInClientPortal	boolean	Is Visible in Client Portal	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
phaseID	int32	Phase ID	☐	
priority	int32	Priority	☐	
priorityLabel	int32	Priority Label	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
remainingHours	double	Remaining Hours	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
taskCategoryID	int32	Task Category ID	☐	
taskNumber	string	Task Number	☐	
taskType	int32	Task Type	☐	
title	string	Title	☐	

301.1.2 Tasks_ItemsUserDefinedFields

Catalog: Autotask

Schema: Tasks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Tasks_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
assignedResourceID	int32	Assigned Resource ID	☐	
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	
canClientPortalUserCompleteTask	boolean	Can Client Portal User Complete Task	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedByType	int32	Completed by Type	☐	
completedDateTime	datetime	Completed	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
departmentID	int32	Department ID	☐	
description	string	Description	☐	
endDateTime	datetime	End Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	
id	int64	ID	☐	
isTaskBillable	boolean	Is Task Billable	☐	
isVisibleInClientPortal	boolean	Is Visible in Client Portal	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
name	string	Name	☐	
phaseID	int32	Phase ID	☐	
priority	int32	Priority	☐	
priorityLabel	int32	Priority Label	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
remainingHours	double	Remaining Hours	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
taskCategoryID	int32	Task Category ID	☐	
taskNumber	string	Task Number	☐	
taskType	int32	Task Type	☐	
title	string	Title	☐	
value	string	Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

301.1.3 TasksById

Catalog: Autotask

Schema: Tasks

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TasksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
assignedResourceID	int32	Assigned Resource ID	☐	
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	
canClientPortalUserCompleteTask	boolean	Can Client Portal User Complete Task	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedByType	int32	Completed by Type	☐	
completedDateTime	datetime	Completed	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	
departmentID	int32	Department ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
endDateTime	datetime	End Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	
id	int64	ID	☐	
isTaskBillable	boolean	Is Task Billable	☐	
isVisibleInClientPortal	boolean	Is Visible in Client Portal	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
phaseID	int32	Phase ID	☐	
priority	int32	Priority	☐	
priorityLabel	int32	Priority Label	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
remainingHours	double	Remaining Hours	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
taskCategoryID	int32	Task Category ID	☐	
taskNumber	string	Task Number	☐	
taskType	int32	Task Type	☐	
title	string	Title	☐	

301.1.4 TasksCount

Catalog: Autotask

Schema: Tasks

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TasksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

302 Schema: TasksChild

302.1 Tables

302.1.1 ProjectsByParentId_ItemsUserDefinedFieldsTasks

Catalog: Autotask

Schema: TasksChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentId_ItemsUserDefinedFieldsTasks. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentId_ItemsUserDefinedFieldsTasks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
assignedResourceID	int32	Assigned Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	
canClientPortalUserCompleteTask	boolean	Can Client Portal User Complete Task	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedByType	int32	Completed by Type	☐	
completedDateTime	datetime	Completed	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	
departmentID	int32	Department ID	☐	
description	string	Description	☐	
endDateTime	datetime	End Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	
id	int64	ID	☐	
isTaskBillable	boolean	Is Task Billable	☐	
isVisibleInClientPortal	boolean	Is Visible in Client Portal	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
name	string	Name	☐	
phaseID	int32	Phase ID	☐	
priority	int32	Priority	☐	
priorityLabel	int32	Priority Label	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
remainingHours	double	Remaining Hours	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
taskCategoryID	int32	Task Category ID	☐	
taskNumber	string	Task Number	☐	
taskType	int32	Task Type	☐	
title	string	Title	☐	
value	string	Value	☐	

302.1.2 ProjectsByParentIdTasks

Catalog: Autotask

Schema: TasksChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdTasks. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdTasks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
assignedResourceID	int32	Assigned Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	
canClientPortalUserCompleteTask	boolean	Can Client Portal User Complete Task	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedByType	int32	Completed by Type	☐	
completedDateTime	datetime	Completed	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	
departmentID	int32	Department ID	☐	
description	string	Description	☐	
endDateTime	datetime	End Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	
id	int64	ID	☐	
isTaskBillable	boolean	Is Task Billable	☐	
isVisibleInClientPortal	boolean	Is Visible in Client Portal	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
phaseID	int32	Phase ID	☐	
priority	int32	Priority	☐	
priorityLabel	int32	Priority Label	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
remainingHours	double	Remaining Hours	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
taskCategoryID	int32	Task Category ID	☐	
taskNumber	string	Task Number	☐	
taskType	int32	Task Type	☐	
title	string	Title	☐	

302.1.3 ProjectsByParentIdTasksId

Catalog: Autotask

Schema: TasksChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectsByParentIdTasksId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function ProjectsByParentIdTasksId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
assignedResourceID	int32	Assigned Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	
canClientPortalUserCompleteTask	boolean	Can Client Portal User Complete Task	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedByType	int32	Completed by Type	☐	
completedDateTime	datetime	Completed	☐	
createDateTime	datetime	Created	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	
departmentID	int32	Department ID	☐	
description	string	Description	☐	
endDateTime	datetime	End Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	
id	int64	ID	☐	
isTaskBillable	boolean	Is Task Billable	☐	
isVisibleInClientPortal	boolean	Is Visible in Client Portal	☐	
lastActivityDateTime	datetime	Last Activity Date/Time	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
phaseID	int32	Phase ID	☐	
priority	int32	Priority	☐	
priorityLabel	int32	Priority Label	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
remainingHours	double	Remaining Hours	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startDateTime	datetime	Start Date/Time	☐	
status	int32	Status	☐	
taskCategoryID	int32	Task Category ID	☐	
taskNumber	string	Task Number	☐	
taskType	int32	Task Type	☐	
title	string	Title	☐	

303 Schema: TaskSecondaryResources

303.1 Tables

303.1.1 TaskSecondaryResources

Catalog: Autotask

Schema: TaskSecondaryResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskSecondaryResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

303.1.2 TaskSecondaryResourcesById

Catalog: Autotask

Schema: TaskSecondaryResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaskSecondaryResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TaskSecondaryResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

303.1.3 TaskSecondaryResourcesCount

Catalog: Autotask

Schema: TaskSecondaryResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaskSecondaryResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

304 Schema: TaskSecondaryResourcesChild

304.1 Tables

304.1.1 TasksByParentIdSecondaryResources

Catalog: Autotask

Schema: TaskSecondaryResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdSecondaryResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function TasksByParentIdSecondaryResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

304.1.2 TasksByParentIdSecondaryResourcesId

Catalog: Autotask

Schema: TaskSecondaryResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TasksByParentIdSecondaryResourcesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TasksByParentIdSecondaryResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

305 Schema: TaxCategories

305.1 Tables

305.1.1 TaxCategories

Catalog: Autotask

Schema: TaxCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxCategories are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

305.1.2 TaxCategoriesById

Catalog: Autotask

Schema: TaxCategories

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaxCategoriesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TaxCategoriesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

305.1.3 TaxCategoriesCount

Catalog: Autotask

Schema: TaxCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table TaxCategoriesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

306 Schema: Taxes

306.1 Tables

306.1.1 Taxes

Catalog: Autotask

Schema: Taxes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Taxes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isCompounded	boolean	Is Compounded	☐	
taxCategoryID	int32	Tax Category ID	☐	
taxName	string	Tax Name	☐	
taxRate	double	Tax Rate	☐	
taxRegionID	int32	Tax Region ID	☐	

306.1.2 TaxesById

Catalog: Autotask

Schema: Taxes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaxesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TaxesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isCompounded	boolean	Is Compounded	☐	
taxCategoryID	int32	Tax Category ID	☐	
taxName	string	Tax Name	☐	
taxRate	double	Tax Rate	☐	
taxRegionID	int32	Tax Region ID	☐	

306.1.3 TaxesCount

Catalog: Autotask

Schema: Taxes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

307 Schema: TaxRegions

307.1 Tables

307.1.1 TaxRegions

Catalog: Autotask

Schema: TaxRegions

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TaxRegions are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

307.1.2 TaxRegionsById

Catalog: Autotask

Schema: TaxRegions

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TaxRegionsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TaxRegionsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

307.1.3 TaxRegionsCount

Catalog: Autotask

Schema: TaxRegions

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TaxRegionsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

308 Schema: ThresholdApiIntegration

308.1 Tables

308.1.1 ThresholdInformation

Catalog: Autotask

Schema: ThresholdApiIntegration

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table ThresholdInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
currentTimeframeRequestCount	int32	Current Time Frame Request Count	☐	
externalRequestThreshold	int32	External Request Threshold	☐	
requestThresholdTimeframe	int32	Request Threshold Timeframe	☐	

309 Schema: TicketAdditionalConfigurationItems

309.1 Tables

309.1.1 TicketAdditionalConfigurationItems

Catalog: Autotask

Schema: TicketAdditionalConfigurationItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TicketAdditionalConfigurationItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

309.1.2 TicketAdditionalConfigurationItemsById

Catalog: Autotask

Schema: TicketAdditionalConfigurationItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketAdditionalConfigurationItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TicketAdditionalConfigurationItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

309.1.3 TicketAdditionalConfigurationItemsCount

Catalog: Autotask

Schema: TicketAdditionalConfigurationItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalConfigurationItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

310 Schema: TicketAdditionalConfigurationItemsChild

310.1 Tables

310.1.1 TicketsByParentIdAdditionalConfigurationItems

Catalog: Autotask

Schema: TicketAdditionalConfigurationItemsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalConfigurationItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalConfigurationItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

310.1.2 TicketsByParentIdAdditionalConfigurationItemsId

Catalog: Autotask

Schema: TicketAdditionalConfigurationItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalConfigurationItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalConfigurationItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
configurationItemID	int32	Configuration Item ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

311 Schema: TicketAdditionalContacts

311.1 Tables

311.1.1 TicketAdditionalContacts

Catalog: Autotask

Schema: TicketAdditionalContacts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalContacts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

311.1.2 TicketAdditionalContactsById

Catalog: Autotask

Schema: TicketAdditionalContacts

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketAdditionalContactsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketAdditionalContactsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

311.1.3 TicketAdditionalContactsCount

Catalog: Autotask

Schema: TicketAdditionalContacts

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAdditionalContactsCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

312 Schema: TicketAdditionalContactsChild

312.1 Tables

312.1.1 TicketsByParentIdAdditionalContacts

Catalog: Autotask

Schema: TicketAdditionalContactsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalContacts. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalContacts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

312.1.2 TicketsByParentIdAdditionalContactsId

Catalog: Autotask

Schema: TicketAdditionalContactsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAdditionalContactsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAdditionalContactsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

313 Schema: TicketAttachments

313.1 Tables

313.1.1 TicketAttachments

Catalog: Autotask

Schema: TicketAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

313.1.2 TicketAttachmentsById

Catalog: Autotask

Schema: TicketAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TicketAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

313.1.3 TicketAttachmentsCount

Catalog: Autotask

Schema: TicketAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

314 Schema: TicketAttachmentsChild

314.1 Tables

314.1.1 TicketsByParentIdAttachments

Catalog: Autotask

Schema: TicketAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAttachments are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

314.1.2 TicketsByParentIdAttachmentsId

Catalog: Autotask

Schema: TicketAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentAttachmentID	int32	Parent Attachment ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

315 Schema: TicketCategories

315.1 Tables

315.1.1 TicketCategories

Catalog: Autotask

Schema: TicketCategories

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategories are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
displayColorRGB	int32	Display Color RGB	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isApiOnly	boolean	Is API Only	☐	
isGlobalDefault	boolean	Is Global Default	☐	
name	string	Name	☐	
nickname	string	Nickname	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

315.1.2 TicketCategoriesById

Catalog: Autotask

Schema: TicketCategories

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoriesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketCategoriesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
displayColorRGB	int32	Display Color RGB	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isApiOnly	boolean	Is API Only	☐	
isGlobalDefault	boolean	Is Global Default	☐	
name	string	Name	☐	
nickname	string	Nickname	☐	

315.1.3 TicketCategoriesCount

Catalog: Autotask

Schema: TicketCategories

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoriesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

316 Schema: TicketCategoryFieldDefaults

316.1 Tables

316.1.1 TicketCategoryFieldDefaults

Catalog: Autotask

Schema: TicketCategoryFieldDefaults

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoryFieldDefaults are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
estimatedHours	double	Estimated Hours	☐	
id	int64	ID	☐	
issueTypeID	int32	Issue Type ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
priority	int32	Priority	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
queueID	int32	Queue ID	☐	
resolution	string	Resolution	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
sourceID	int32	Source ID	☐	
status	int32	Status	☐	
subIssueTypeID	int32	Sub-issue Type ID	☐	
ticketCategoryID	int32	Ticket Category ID	☐	
ticketTypeID	int32	Ticket Type ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
title	string	Title	☐	
w orkTypeID	int32	Worktype ID	☐	

316.1.2 TicketCategoryFieldDefaultsById

Catalog: Autotask

Schema: TicketCategoryFieldDefaults

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoryFieldDefaultsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketCategoryFieldDefaultsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
estimatedHours	double	Estimated Hours	☐	
id	int64	ID	☐	
issueTypeID	int32	Issue Type ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
priority	int32	Priority	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
queueID	int32	Queue ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
resolution	string	Resolution	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
sourceID	int32	Source ID	☐	
status	int32	Status	☐	
subIssueTypeID	int32	Sub-issue Type ID	☐	
ticketCategoryID	int32	Ticket Category ID	☐	
ticketTypeID	int32	Ticket Type ID	☐	
title	string	Title	☐	
w orkTypeID	int32	Worktype ID	☐	

316.1.3 TicketCategoryFieldDefaultsCount

Catalog: Autotask

Schema: TicketCategoryFieldDefaults

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCategoryFieldDefaultsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

317 Schema: TicketCategoryFieldDefaultsChild

317.1 Tables

317.1.1 TicketCategoriesByParentIdFieldDefaults

Catalog: Autotask

Schema: TicketCategoryFieldDefaultsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoriesByParentIdFieldDefaults. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketCategoriesByParentIdFieldDefaults are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
estimatedHours	double	Estimated Hours	☐	
id	int64	ID	☐	
issueTypeID	int32	Issue Type ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
priority	int32	Priority	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
queueID	int32	Queue ID	☐	
resolution	string	Resolution	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
sourceID	int32	Source ID	☐	
status	int32	Status	☐	
subIssueTypeID	int32	Sub-issue Type ID	☐	
ticketCategoryID	int32	Ticket Category ID	☐	
ticketTypeID	int32	Ticket Type ID	☐	
title	string	Title	☐	
w orkTypeID	int32	Worktype ID	☐	

317.1.2 TicketCategoriesByParentIdFieldDefaultsId

Catalog: Autotask

Schema: TicketCategoryFieldDefaultsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketCategoriesByParentIdFieldDefaultsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketCategoriesByParentIdFieldDefaultsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
estimatedHours	double	Estimated Hours	☐	
id	int64	ID	☐	
issueTypeID	int32	Issue Type ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
priority	int32	Priority	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
queueID	int32	Queue ID	☐	
resolution	string	Resolution	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
sourceID	int32	Source ID	☐	
status	int32	Status	☐	
subIssueTypeID	int32	Sub-issue Type ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
ticketCategoryID	int32	Ticket Category ID	☐	
ticketTypeID	int32	Ticket Type ID	☐	
title	string	Title	☐	
w orkTypeID	int32	Worktype ID	☐	

318 Schema: TicketChangeRequestApprovals

318.1 Tables

318.1.1 TicketChangeRequestApprovals

Catalog: Autotask

Schema: TicketChangeRequestApprovals

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChangeRequestApprovals are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveRejectDateTime	datetime	Approver Eject Date/Time	☐	
approveRejectNote	string	Approver Eject Note	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
isApproved	boolean	Is Approved	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

318.1.2 TicketChangeRequestApprovalsById

Catalog: Autotask

Schema: TicketChangeRequestApprovals

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketChangeRequestApprovalsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketChangeRequestApprovalsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveRejectDateTime	datetime	Approver Eject Date/Time	☐	
approveRejectNote	string	Approver Eject Note	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
isApproved	boolean	Is Approved	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

318.1.3 TicketChangeRequestApprovalsCount

Catalog: Autotask

Schema: TicketChangeRequestApprovals

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChangeRequestApprovalsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

319 Schema: TicketChangeRequestApprovalsChild

319.1 Tables

319.1.1 TicketsByParentIdChangeRequestApprovals

Catalog: Autotask

Schema: TicketChangeRequestApprovalsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChangeRequestApprovals. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChangeRequestApprovals are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveRejectDateTime	datetime	Approver Eject Date/Time	☐	
approveRejectNote	string	Approver Eject Note	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
isApproved	boolean	Is Approved	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

319.1.2 TicketsByParentIdChangeRequestApprovalsId

Catalog: Autotask

Schema: TicketChangeRequestApprovalsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChangeRequestApprovalsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChangeRequestApprovalsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approveRejectDateTime	datetime	Approver Eject Date/Time	☐	
approveRejectNote	string	Approver Eject Note	☐	
contactID	int32	Contact ID	☐	
id	int64	ID	☐	
isApproved	boolean	Is Approved	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

320 Schema: TicketCharges

320.1 Tables

320.1.1 TicketCharges

Catalog: Autotask

Schema: TicketCharges

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketCharges are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
ticketID	int64	Ticket ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

320.1.2 TicketChargesById

Catalog: Autotask

Schema: TicketCharges

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketChargesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketChargesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
chargeType	int32	Charge Type	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
ticketID	int64	Ticket ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
unitQuantity	double	Unit Quantity	☐	

320.1.3 TicketChargesCount

Catalog: Autotask

Schema: TicketCharges

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChargesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

321 Schema: TicketChargesChild

321.1 Tables

321.1.1 TicketsByParentIdCharges

Catalog: Autotask

Schema: TicketChargesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdCharges. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TicketsByParentIdCharges are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
ticketID	int64	Ticket ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

321.1.2 TicketsByParentIdChargesId

Catalog: Autotask

Schema: TicketChargesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChargesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChargesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billableAmount	double	Billable Amount	☐	
billingCodeID	int64	Billing Code ID	☐	
chargeType	int32	Charge Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
creatorResourceID	int64	Creator Resource ID	☐	
datePurchased	datetime	Purchase Date	☐	
description	string	Description	☐	
extendedCost	double	Extended Cost	☐	
id	int64	ID	☐	
internalCurrencyBillableAmount	double	Internal Currency Billable Amount	☐	
internalCurrencyUnitPrice	double	Internal Currency Unit Price	☐	
internalPurchaseOrderNumber	string	Internal Purchase Order Number	☐	
isBillableToCompany	boolean	Is Billable to Company	☐	
isBilled	boolean	Is Billed	☐	
name	string	Name	☐	
notes	string	Notes	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
productID	int64	Product ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
status	int64	Status	☐	
statusLastModifiedBy	int64	Status Last Modified by	☐	
statusLastModifiedDate	datetime	Status Last Modified Date	☐	
ticketID	int64	Ticket ID	☐	
unitCost	double	Unit Cost	☐	
unitPrice	double	Unit Price	☐	
unitQuantity	double	Unit Quantity	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

322 Schema: TicketChecklistItems

322.1 Tables

322.1.1 TicketChecklistItems

Catalog: Autotask

Schema: TicketChecklistItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
completedByResourceID	int32	Completed by Resource ID	☐	
completedDateTime	datetime	Completed	☐	
id	int64	ID	☐	
isCompleted	boolean	Is Completed	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
knowledgebaseArticleID	int32	Knowledgebase Article ID	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

322.1.2 TicketChecklistItemsById

Catalog: Autotask

Schema: TicketChecklistItems

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketChecklistItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketChecklistItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
completedByResourceID	int32	Completed by Resource ID	☐	
completedDateTime	datetime	Completed	☐	
id	int64	ID	☐	
isCompleted	boolean	Is Completed	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
knowledgebaseArticleID	int32	Knowledgebase Article ID	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

322.1.3 TicketChecklistItemsCount

Catalog: Autotask

Schema: TicketChecklistItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketChecklistItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

323 Schema: TicketChecklistItemsChild

323.1 Tables

323.1.1 TicketsByParentIdChecklistItems

Catalog: Autotask

Schema: TicketChecklistItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
completedByResourceID	int32	Completed by Resource ID	☐	
completedDateTime	datetime	Completed	☐	
id	int64	ID	☐	
isCompleted	boolean	Is Completed	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
knowledgebaseArticleID	int32	Knowledgebase Article ID	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

323.1.2 TicketsByParentIdChecklistItemsId

Catalog: Autotask

Schema: TicketChecklistItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdChecklistItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdChecklistItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
completedByResourceID	int32	Completed by Resource ID	☐	
completedDateTime	datetime	Completed	☐	
id	int64	ID	☐	
isCompleted	boolean	Is Completed	☐	
isImportant	boolean	Is Important	☐	
itemName	string	Item Name	☐	
knowledgebaseArticleID	int32	Knowledgebase Article ID	☐	
position	int32	Position	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

324 Schema: TicketHistory

324.1 Tables

324.1.1 TicketHistory

Catalog: Autotask

Schema: TicketHistory

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketHistory. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
ticketId	string	☑		

Columns of Table Function

The columns of the table function TicketHistory are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
action	string	Action	☐	
date	datetime	Date	☐	
detail	string	Detail	☐	
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

324.1.2 TicketHistoryById

Catalog: Autotask

Schema: TicketHistory

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketHistoryById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketHistoryById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
action	string	Action	☐	
date	datetime	Date	☐	
detail	string	Detail	☐	
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId	int64	SOAP Parent Property ID	☐	
ticketID	int32	Ticket ID	☐	

324.1.3 TicketHistoryCount

Catalog: Autotask

Schema: TicketHistory

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketHistoryCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

325 Schema: TicketNoteAttachments

325.1 Tables

325.1.1 TicketNoteAttachments

Catalog: Autotask

Schema: TicketNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
title	string	Title	☐	

325.1.2 TicketNoteAttachmentsById

Catalog: Autotask

Schema: TicketNoteAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function TicketNoteAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
title	string	Title	☐	

325.1.3 TicketNoteAttachmentsCount

Catalog: Autotask

Schema: TicketNoteAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Columns

The columns of the table TicketNoteAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

326 Schema: TicketNoteAttachmentsChild

326.1 Tables

326.1.1 TicketNotesByParentIdAttachments

Catalog: Autotask

Schema: TicketNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNotesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketNotesByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
title	string	Title	☐	

326.1.2 TicketNotesByParentIdAttachmentsId

Catalog: Autotask

Schema: TicketNoteAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNotesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketNotesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
ticketNoteID	int32	Ticket Note ID	☐	
title	string	Title	☐	

327 Schema: TicketNotes

327.1 Tables

327.1.1 TicketNotes

Catalog: Autotask

Schema: TicketNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
title	string	Title	☐	

327.1.2 TicketNotesById

Catalog: Autotask

Schema: TicketNotes

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNotesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketNotesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
title	string	Title	☐	

327.1.3 TicketNotesCount

Catalog: Autotask

Schema: TicketNotes

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNotesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

328 Schema: TicketNotesChild

328.1 Tables

328.1.1 TicketsByParentIdNotes

Catalog: Autotask

Schema: TicketNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function TicketsByParentIdNotes. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdNotes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
ticketID	int32	Ticket ID	☐	
title	string	Title	☐	

328.1.2 TicketsByParentIdNotesId

Catalog: Autotask

Schema: TicketNotesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdNotesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdNotesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
description	string	Description	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
lastActivityDate	datetime	Last Activity Date	☐	
noteType	int32	Note Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	
title	string	Title	☐	

329 Schema: TicketNoteWebhookExcludedResources

329.1 Tables

329.1.1 TicketNoteWebhookExcludedResources

Catalog: Autotask

Schema: TicketNoteWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

329.1.2 TicketNoteWebhookExcludedResourcesById

Catalog: Autotask

Schema: TicketNoteWebhookExcludedResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhookExcludedResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhookExcludedResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
w ebhookID	int32	Webhook ID	☐	

329.1.3 TicketNoteWebhookExcludedResourcesCount

Catalog: Autotask

Schema: TicketNoteWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookExcludedResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

330 Schema: TicketNoteWebhookExcludedResourcesChild

330.1 Tables

330.1.1 TicketNoteWebhooksByParentIdExcludedResources

Catalog: Autotask

Schema: TicketNoteWebhookExcludedResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdExcludedResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

330.1.2 TicketNoteWebhooksByParentIdExcludedResourcesId

Catalog: Autotask

Schema: TicketNoteWebhookExcludedResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdExcludedResourcesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdExcludedResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

331 Schema: TicketNoteWebhookFields

331.1 Tables

331.1.1 TicketNoteWebhookFields

Catalog: Autotask

Schema: TicketNoteWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

331.1.2 TicketNoteWebhookFieldsById

Catalog: Autotask

Schema: TicketNoteWebhookFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhookFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TicketNoteWebhookFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

331.1.3 TicketNoteWebhookFieldsCount

Catalog: Autotask

Schema: TicketNoteWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhookFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

332 Schema: TicketNoteWebhookFieldsChild

332.1 Tables

332.1.1 TicketNoteWebhooksByParentIdFields

Catalog: Autotask

Schema: TicketNoteWebhookFieldsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

332.1.2 TicketNoteWebhooksByParentIdFieldsId

Catalog: Autotask

Schema: TicketNoteWebhookFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksByParentIdFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksByParentIdFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

333 Schema: TicketNoteWebhooks

333.1 Tables

333.1.1 TicketNoteWebhooks

Catalog: Autotask

Schema: TicketNoteWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhooks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

333.1.2 TicketNoteWebhooksById

Catalog: Autotask

Schema: TicketNoteWebhooks

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketNoteWebhooksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketNoteWebhooksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

333.1.3 TicketNoteWebhooksCount

Catalog: Autotask

Schema: TicketNoteWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketNoteWebhooksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

334 Schema: TicketRmaCredits

334.1 Tables

334.1.1 TicketRmaCredits

Catalog: Autotask

Schema: TicketRmaCredits

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketRmaCredits are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
creditAmount	double	Credit Amount	☐	
creditDetails	string	Credit Details	☐	
id	int64	ID	☐	
internalCurrencyCreditAmount	double	Internal Currency Credit Amount	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

334.1.2 TicketRmaCreditsById

Catalog: Autotask

Schema: TicketRmaCredits

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketRmaCreditsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketRmaCreditsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
creditAmount	double	Credit Amount	☐	
creditDetails	string	Credit Details	☐	
id	int64	ID	☐	
internalCurrencyCreditAmount	double	Internal Currency Credit Amount	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

334.1.3 TicketRmaCreditsCount

Catalog: Autotask

Schema: TicketRmaCredits

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketRmaCreditsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

335 Schema: TicketRmaCreditsChild

335.1 Tables

335.1.1 TicketsByParentIdRmaCredits

Catalog: Autotask

Schema: TicketRmaCreditsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdRmaCredits. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdRmaCredits are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
creditAmount	double	Credit Amount	☐	
creditDetails	string	Credit Details	☐	
id	int64	ID	☐	
internalCurrencyCreditAmount	double	Internal Currency Credit Amount	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

335.1.2 TicketsByParentIdRmaCreditsId

Catalog: Autotask

Schema: TicketRmaCreditsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdRmaCreditsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdRmaCreditsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
creditAmount	double	Credit Amount	☐	
creditDetails	string	Credit Details	☐	
id	int64	ID	☐	
internalCurrencyCreditAmount	double	Internal Currency Credit Amount	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int32	Ticket ID	☐	

336 Schema: Tickets

336.1 Tables

336.1.1 Tickets

Catalog: Autotask

Schema: Tickets

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Tickets are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
apiVendorID	int32	API Vendor ID	☐	
assignedResourceID	int32	Assigned Resource ID	☐	
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	
changeApprovalBoard	int32	Change Approval Board	☐	
changeApprovalStatus	int32	Change Approval Status	☐	
changeApprovalType	int32	Change Approval Type	☐	
changeInfoField1	string	Change Information Field 1	☐	
changeInfoField2	string	Change Information Field 2	☐	
changeInfoField3	string	Change Information Field 3	☐	
changeInfoField4	string	Change Information Field 4	☐	
changeInfoField5	string	Change Information Field 5	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedDate	datetime	Completion Date	☐	
configurationItemID	int32	Configuration Item ID	☐	
contactID	int32	Contact ID	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	
currentServiceThermometerRating	int32	Current Service Thermometer Rating	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
dueDateTime	datetime	Due Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
firstResponseAssignedResourceID	int32	First Response Assigned Resource ID	☐	
firstResponseDateTime	datetime	First Response Date/Time	☐	
firstResponseDueDateTime	datetime	First Response Due Date/Time	☐	
firstResponseInitiatingResourceID	int32	First Response Initiating Resource ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isAssignedToComanaged	boolean	Is Assigned to Co-managed	☐	
issueType	int32	Issue Type	☐	
isVisibleToComanaged	boolean	Is Visible to Co-managed	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
lastCustomerNotificationDateTime	datetime	Last Customer Notification Date/Time	☐	
lastCustomerVisibleActivityDateTime	datetime	Last Customer Visible Activity Date/Time	☐	
lastTrackedModificationDateTime	datetime	Last Tracked Modification Date/Time	☐	
monitorID	int64	Monitor ID	☐	
monitorTypeID	int32	Monitor Type ID	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
previousServiceThermometerRating	int32	Previous Service Thermometer Rating	☐	
priority	int32	Priority	☐	
problemTicketId	int32	Problem Ticket ID	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
queueID	int32	Queue ID	☐	
resolution	string	Resolution	☐	
resolutionPlanDateTime	datetime	Resolution Plan Date/Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
resolutionPlanDueDateTime	datetime	Resolution Plan Due Date/Time	☐	
resolvedDateTime	datetime	Resolved Date/Time	☐	
resolvedDueDateTime	datetime	Resolved Due Date/Time	☐	
rmaStatus	int32	RMA status	☐	
rmaType	int32	RMA Type	☐	
rmmAlertID	string	Alert ID	☐	
serviceLevelAgreementHasBeenMet	boolean	Service Level Agreement has been Met	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
serviceLevelAgreementPausedNextEventHours	double	Service Level Agreement Paused next Event Hours	☐	
serviceThermometerTemperature	int32	Service Thermometer Temperature	☐	
source	int32	Source	☐	
status	int32	Status	☐	
subIssueType	int32	Sub-issue Type	☐	
ticketCategory	int32	Ticket Category	☐	
ticketNumber	string	Ticket Number	☐	
ticketType	int32	Ticket Type	☐	
title	string	Title	☐	

336.1.2 Tickets_ItemsUserDefinedFields

Catalog: Autotask

Schema: Tickets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table Tickets_ItemsUserDefinedFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
apiVendorID	int32	API Vendor ID	☐	
assignedResourceID	int32	Assigned Resource ID	☐	
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
changeApprovalBoard	int32	Change Approval Board	☐	
changeApprovalStatus	int32	Change Approval Status	☐	
changeApprovalType	int32	Change Approval Type	☐	
changeInfoField1	string	Change Information Field 1	☐	
changeInfoField2	string	Change Information Field 2	☐	
changeInfoField3	string	Change Information Field 3	☐	
changeInfoField4	string	Change Information Field 4	☐	
changeInfoField5	string	Change Information Field 5	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedDate	datetime	Completion Date	☐	
configurationItemID	int32	Configuration Item ID	☐	
contactID	int32	Contact ID	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	
currentServiceThermometerRating	int32	Current Service Thermometer Rating	☐	
description	string	Description	☐	
dueDateTime	datetime	Due Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	
firstResponseAssignedResourceID	int32	First Response Assigned Resource ID	☐	
firstResponseDateTime	datetime	First Response Date/Time	☐	
firstResponseDueDateTime	datetime	First Response Due Date/Time	☐	
firstResponseInitiatingResourceID	int32	First Response Initiating Resource ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isAssignedToComanaged	boolean	Is Assigned to Co-managed	☐	
issueType	int32	Issue Type	☐	
isVisibleToComanaged	boolean	Is Visible to Co-managed	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
lastCustomerNotificationDateTime	datetime	Last Customer Notification Date/Time	☐	
lastCustomerVisibleActivityDateTime	datetime	Last Customer Visible Activity Date/Time	☐	
lastTrackedModificationDateTime	datetime	Last Tracked Modification Date/Time	☐	
monitorID	int64	Monitor ID	☐	
monitorTypeID	int32	Monitor Type ID	☐	
name	string	Name	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
previousServiceThermometerRating	int32	Previous Service Thermometer Rating	☐	
priority	int32	Priority	☐	
problemTicketId	int32	Problem Ticket ID	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
queueID	int32	Queue ID	☐	
resolution	string	Resolution	☐	
resolutionPlanDateTime	datetime	Resolution Plan Date/Time	☐	
resolutionPlanDueDateTime	datetime	Resolution Plan Due Date/Time	☐	
resolvedDateTime	datetime	Resolved Date/Time	☐	
resolvedDueDateTime	datetime	Resolved Due Date/Time	☐	
rmaStatus	int32	RMA status	☐	
rmaType	int32	RMA Type	☐	
rmmAlertID	string	Alert ID	☐	
serviceLevelAgreementHasBeenMet	boolean	Service Level Agreement has been Met	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
serviceLevelAgreementPausedNextEventHours	double	Service Level Agreement Paused next Event Hours	☐	
serviceThermometerTemperature	int32	Service Thermometer Temperature	☐	
source	int32	Source	☐	
status	int32	Status	☐	
subIssueType	int32	Sub-issue Type	☐	
ticketCategory	int32	Ticket Category	☐	
ticketNumber	string	Ticket Number	☐	
ticketType	int32	Ticket Type	☐	
title	string	Title	☐	
value	string	Value	☐	

336.1.3 TicketsById

Catalog: Autotask

Schema: Tickets

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function TicketsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
apiVendorID	int32	API Vendor ID	☐	
assignedResourceID	int32	Assigned Resource ID	☐	
assignedResourceRoleID	int32	Assigned Resource Role ID	☐	
billingCodeID	int32	Billing Code ID	☐	
changeApprovalBoard	int32	Change Approval Board	☐	
changeApprovalStatus	int32	Change Approval Status	☐	
changeApprovalType	int32	Change Approval Type	☐	
changeInfoField1	string	Change Information Field 1	☐	
changeInfoField2	string	Change Information Field 2	☐	
changeInfoField3	string	Change Information Field 3	☐	
changeInfoField4	string	Change Information Field 4	☐	
changeInfoField5	string	Change Information Field 5	☐	
companyID	int32	Company ID	☐	
companyLocationID	int32	Company Location ID	☐	
completedByResourceID	int32	Completed by Resource ID	☐	
completedDate	datetime	Completion Date	☐	
configurationItemID	int32	Configuration Item ID	☐	
contactID	int32	Contact ID	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDate	datetime	Created	☐	
createdByContactID	int32	Created by Contact ID	☐	
creatorResourceID	int32	Creator Resource ID	☐	
creatorType	int32	Creator Type	☐	
currentServiceThermometerRating	int32	Current Service Thermometer Rating	☐	
description	string	Description	☐	
dueDateTime	datetime	Due Date/Time	☐	
estimatedHours	double	Estimated Hours	☐	
externalID	string	External ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
firstResponseAssignedResourceID	int32	First Response Assigned Resource ID	☐	
firstResponseDateTime	datetime	First Response Date/Time	☐	
firstResponseDueDateTime	datetime	First Response Due Date/Time	☐	
firstResponseInitiatingResourceID	int32	First Response Initiating Resource ID	☐	
hoursToBeScheduled	double	Hours to be Scheduled	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isAssignedToComanaged	boolean	Is Assigned to Co-managed	☐	
issueType	int32	Issue Type	☐	
isVisibleToComanaged	boolean	Is Visible to Co-managed	☐	
lastActivityDate	datetime	Last Activity Date	☐	
lastActivityPersonType	int32	Last Acitvity Person Type	☐	
lastActivityResourceID	int32	Last Activity Resource ID	☐	
lastCustomerNotificationDateTime	datetime	Last Customer Notification Date/Time	☐	
lastCustomerVisibleActivityDateTime	datetime	Last Customer Visible Activity Date/Time	☐	
lastTrackedModificationDateTime	datetime	Last Tracked Modification Date/Time	☐	
monitorID	int64	Monitor ID	☐	
monitorTypeID	int32	Monitor Type ID	☐	
opportunityID	int32	Opportunity ID	☐	
organizationalLevelAssociationID	int32	Organizational Level Association ID	☐	
previousServiceThermometerRating	int32	Previous Service Thermometer Rating	☐	
priority	int32	Priority	☐	
problemTicketId	int32	Problem Ticket ID	☐	
projectID	int32	Project ID	☐	
purchaseOrderNumber	string	Purchase Order Number	☐	
queueID	int32	Queue ID	☐	
resolution	string	Resolution	☐	
resolutionPlanDateTime	datetime	Resolution Plan Date/Time	☐	
resolutionPlanDueDateTime	datetime	Resolution Plan Due Date/Time	☐	
resolvedDateTime	datetime	Resolved Date/Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
resolvedDueDateTime	datetime	Resolved Due Date/Time	☐	
rmaStatus	int32	RMA status	☐	
rmaType	int32	RMA Type	☐	
rmmAlertID	string	Alert ID	☐	
serviceLevelAgreementHasBeenMet	boolean	Service Level Agreement has been Met	☐	
serviceLevelAgreementID	int32	Service Level Agreement ID	☐	
serviceLevelAgreementPausedNextEventHours	double	Service Level Agreement Paused next Event Hours	☐	
serviceThermometerTemperature	int32	Service Thermometer Temperature	☐	
source	int32	Source	☐	
status	int32	Status	☐	
subIssueType	int32	Sub-issue Type	☐	
ticketCategory	int32	Ticket Category	☐	
ticketNumber	string	Ticket Number	☐	
ticketType	int32	Ticket Type	☐	
title	string	Title	☐	

336.1.4 TicketsCount

Catalog: Autotask

Schema: Tickets

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

337 Schema: TicketSecondaryResources

337.1 Tables

337.1.1 TicketSecondaryResources

Catalog: Autotask

Schema: TicketSecondaryResources

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketSecondaryResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int64	Resource ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int64	Ticket ID	☐	

337.1.2 TicketSecondaryResourcesById

Catalog: Autotask

Schema: TicketSecondaryResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketSecondaryResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketSecondaryResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int64	Resource ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int64	Ticket ID	☐	

337.1.3 TicketSecondaryResourcesCount

Catalog: Autotask

Schema: TicketSecondaryResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketSecondaryResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

338 Schema: TicketSecondaryResourcesChild

338.1 Tables

338.1.1 TicketsByParentIdSecondaryResources

Catalog: Autotask

Schema: TicketSecondaryResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdSecondaryResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdSecondaryResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int64	Resource ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
ticketID	int64	Ticket ID	☐	

338.1.2 TicketsByParentIdSecondaryResourcesId

Catalog: Autotask

Schema: TicketSecondaryResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdSecondaryResourcesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdSecondaryResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int64	Resource ID	☐	
roleID	int64	Role ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
ticketID	int64	Ticket ID	☐	

339 Schema: TicketTagAssociations

339.1 Tables

339.1.1 TicketTagAssociations

Catalog: Autotask

Schema: TicketTagAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketTagAssociations are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	
ticketID	int32	Ticket ID	☐	

339.1.2 TicketTagAssociationsById

Catalog: Autotask

Schema: TicketTagAssociations

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketTagAssociationsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketTagAssociationsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

339.1.3 TicketTagAssociationsCount

Catalog: Autotask

Schema: TicketTagAssociations

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketTagAssociationsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

340 Schema: TicketTagAssociationsChild

340.1 Tables

340.1.1 TicketsByParentIdTagAssociations

Catalog: Autotask

Schema: TicketTagAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdTagAssociations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketsByParentIdTagAssociations are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	
ticketID	int32	Ticket ID	☐	

340.1.2 TicketsByParentIdTagAssociationsId

Catalog: Autotask

Schema: TicketTagAssociationsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketsByParentIdTagAssociationsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function TicketsByParentIdTagAssociationsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
tagID	int32	Tag ID	☐	
ticketID	int32	Ticket ID	☐	

341 Schema: TicketWebhookExcludedResources

341.1 Tables

341.1.1 TicketWebhookExcludedResources

Catalog: Autotask

Schema: TicketWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
w ebhookID	int32	Webhook ID	☐	

341.1.2 TicketWebhookExcludedResourcesById

Catalog: Autotask

Schema: TicketWebhookExcludedResources

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhookExcludedResourcesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhookExcludedResourcesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

341.1.3 TicketWebhookExcludedResourcesCount

Catalog: Autotask

Schema: TicketWebhookExcludedResources

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookExcludedResourcesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

342 Schema: TicketWebhookExcludedResourcesChild

342.1 Tables

342.1.1 TicketWebhooksByParentIdExcludedResources

Catalog: Autotask

Schema: TicketWebhookExcludedResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdExcludedResources. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdExcludedResources are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

342.1.2 TicketWebhooksByParentIdExcludedResourcesId

Catalog: Autotask

Schema: TicketWebhookExcludedResourcesChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdExcludedResourcesId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdExcludedResourcesId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

343 Schema: TicketWebhookFields

343.1 Tables

343.1.1 TicketWebhookFields

Catalog: Autotask

Schema: TicketWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookFields are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

343.1.2 TicketWebhookFieldsById

Catalog: Autotask

Schema: TicketWebhookFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhookFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function TicketWebhookFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

343.1.3 TicketWebhookFieldsCount

Catalog: Autotask

Schema: TicketWebhookFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

344 Schema: TicketWebhookFieldsChild

344.1 Tables

344.1.1 TicketWebhooksByParentIdFields

Catalog: Autotask

Schema: TicketWebhookFieldsChild

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

344.1.2 TicketWebhooksByParentIdFieldsId

Catalog: Autotask

Schema: TicketWebhookFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
fieldID	int32	Field ID	☐	
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
webhookID	int32	Webhook ID	☐	

345 Schema: TicketWebhooks

345.1 Tables

345.1.1 TicketWebhooks

Catalog: Autotask

Schema: TicketWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhooks are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

345.1.2 TicketWebhooksById

Catalog: Autotask

Schema: TicketWebhooks

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhooksById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
deactivationUrl	string	Deactivation URL	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isReady	boolean	Is Ready	☐	
isSubscribedToCreateEvents	boolean	Is Subscribed to Create Events	☐	
isSubscribedToDeleteEvents	boolean	Is Subscribed to Delete Events	☐	
isSubscribedToUpdateEvents	boolean	Is Subscribed to Update Events	☐	
name	string	Name	☐	
notificationEmailAddress	string	Notification Email Address	☐	
ownerResourceID	int32	Owner Resource ID	☐	
secretKey	string	Secret Key	☐	
sendThresholdExceededNotification	boolean	Send Threshold Exceeded Notification	☐	
webhookGUID	string	Webhook GUID	☐	
webhookUrl	string	Webhook URL	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

345.1.3 TicketWebhooksCount

Catalog: Autotask

Schema: TicketWebhooks

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhooksCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

346 Schema: TicketWebhookUdfFields

346.1 Tables

346.1.1 TicketWebhookUdfFields

Catalog: Autotask

Schema: TicketWebhookUdfFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookUdfFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

346.1.2 TicketWebhookUdfFieldsById

Catalog: Autotask

Schema: TicketWebhookUdfFields

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhookUdfFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhookUdfFieldsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

346.1.3 TicketWebhookUdfFieldsCount

Catalog: Autotask

Schema: TicketWebhookUdfFields

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TicketWebhookUdfFieldsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

347 Schema: TicketWebhookUdfFieldsChild

347.1 Tables

347.1.1 TicketWebhooksByParentIdUdfFields

Catalog: Autotask

Schema: TicketWebhookUdfFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdUdfFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdUdfFields are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

347.1.2 TicketWebhooksByParentIdUdfFieldsId

Catalog: Autotask

Schema: TicketWebhookUdfFieldsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TicketWebhooksByParentIdUdfFieldsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TicketWebhooksByParentIdUdfFieldsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
isDisplayAlwaysField	boolean	Is Display Always Field	☐	
isSubscribedField	boolean	Is Subscribed Field	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldID	int32	UDF Field ID	☐	
webhookID	int32	Webhook ID	☐	

348 Schema: TimeEntries

348.1 Tables

348.1.1 TimeEntries

Catalog: Autotask

Schema: TimeEntries

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntries are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingApprovalDateTime	datetime	Billing Approval Date/Time	☐	
billingApprovalLevelMostRecent	int32	Billing Approval Level Most Recent	☐	
billingApprovalResourceID	int32	Billing Approval Resource ID	☐	
billingCodeID	int32	Billing Code ID	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDateTime	datetime	Created	☐	
creatorUserID	int32	Creator User ID	☐	
dateWorked	datetime	Date Worked	☐	
endDateTime	datetime	End Date/Time	☐	
hoursToBill	double	Hours to Bill	☐	
hoursWorked	double	Hours Worked	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
internalBillingCodeID	int32	Internal Billing Code ID	☐	
internalNotes	string	Internal Notes	☐	
isInternalNotesVisibleToComanaged	boolean	Is Internal Notes Visible to Co-managed	☐	
isNonBillable	boolean	Is Non-billable	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
lastModifiedUserID	int32	Last Modified User ID	☐	
offsetHours	double	Off-set Hours	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
showOnInvoice	boolean	Show on Invoice	☐	
startDateTime	datetime	Start Date/Time	☐	
summaryNotes	string	Summary Notes	☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	
timeEntryType	int32	Time Entry Type	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

348.1.2 TimeEntriesById

Catalog: Autotask

Schema: TimeEntries

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TimeEntriesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TimeEntriesById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
billingApprovalDateTime	datetime	Billing Approval Date/Time	☐	
billingApprovalLevelMostRecent	int32	Billing Approval Level Most Recent	☐	
billingApprovalResourceID	int32	Billing Approval Resource ID	☐	
billingCodeID	int32	Billing Code ID	☐	
contractID	int32	Contract ID	☐	
contractServiceBundleID	int64	Contract Service Bundle ID	☐	
contractServiceID	int64	Contract Service ID	☐	
createDateTime	datetime	Created	☐	
creatorUserID	int32	Creator User ID	☐	
dateWorked	datetime	Date Worked	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
endDateTime	datetime	End Date/Time	☐	
hoursToBill	double	Hours to Bill	☐	
hoursWorked	double	Hours Worked	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
impersonatorUpdaterResourceID	int32	Impersonator Updater Resource ID	☐	
internalBillingCodeID	int32	Internal Billing Code ID	☐	
internalNotes	string	Internal Notes	☐	
isInternalNotesVisibleToComanaged	boolean	Is Internal Notes Visible to Co-managed	☐	
isNonBillable	boolean	Is Non-billable	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
lastModifiedUserID	int32	Last Modified User ID	☐	
offsetHours	double	Off-set Hours	☐	
resourceID	int32	Resource ID	☐	
roleID	int32	Role ID	☐	
show OnInvoice	boolean	Show on Invoice	☐	
startDateTime	datetime	Start Date/Time	☐	
summaryNotes	string	Summary Notes	☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	
timeEntryType	int32	Time Entry Type	☐	

348.1.3 TimeEntriesCount

Catalog: Autotask

Schema: TimeEntries

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntriesCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

349 Schema: TimeEntryAttachments

349.1 Tables

349.1.1 TimeEntryAttachments

Catalog: Autotask

Schema: TimeEntryAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntryAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
ticketID	int32	Ticket ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

349.1.2 TimeEntryAttachmentsById

Catalog: Autotask

Schema: TimeEntryAttachments

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TimeEntryAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TimeEntryAttachmentsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

349.1.3 TimeEntryAttachmentsCount

Catalog: Autotask

Schema: TimeEntryAttachments

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeEntryAttachmentsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

350 Schema: TimeEntryAttachmentsChild

350.1 Tables

350.1.1 TimeEntriesByParentIdAttachments

Catalog: Autotask

Schema: TimeEntryAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TimeEntriesByParentIdAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function TimeEntriesByParentIdAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

350.1.2 TimeEntriesByParentIdAttachmentsId

Catalog: Autotask

Schema: TimeEntryAttachmentsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TimeEntriesByParentIdAttachmentsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function TimeEntriesByParentIdAttachmentsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
attachDate	datetime	Attach Date	☐	
attachedByContactID	int64	Attached by Contact ID	☐	
attachedByResourceID	int64	Attached by Resource ID	☐	
attachmentType	string	Attachment Type	☐	
contentType	string	Content Type	☐	
creatorType	int32	Creator Type	☐	
data	byte[]	Data	☐	
fileSize	double	File Size	☐	
fullPath	string	Full Path	☐	
id	int64	ID	☐	
impersonatorCreatorResourceID	int32	Imperonsator Creator Resource ID	☐	
isTaskAttachment	boolean	Is Task Attachment	☐	
opportunityID	int64	Opportunity ID	☐	
parentID	int64	Parent ID	☐	
parentType	int32	Parent Type	☐	
publish	int32	Publish	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
taskID	int32	Task ID	☐	
ticketID	int32	Ticket ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
timeEntryID	int32	Time Entry ID	☐	
title	string	Title	☐	

351 Schema: TimeOffRequests

351.1 Tables

351.1.1 TimeOffRequests

Catalog: Autotask

Schema: TimeOffRequests

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeOffRequests are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approvedDateTime	datetime	Approved Date/Time	☐	
approveRejectResourceID	int32	Approver Eject Resource ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
endTime	datetime	End Time	☐	
hours	double	Hours	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
reason	string	Reason	☐	
rejectReason	string	Reject Reason	☐	
requestDate	datetime	Request Date	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startTime	datetime	Start Time	☐	
status	int32	Status	☐	
timeOffRequestType	int32	Time of Request Type	☐	

351.1.2 TimeOffRequestsById

Catalog: Autotask

Schema: TimeOffRequests

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TimeOffRequestsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function TimeOffRequestsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approvedDateTime	datetime	Approved Date/Time	☐	
approveRejectResourceID	int32	Approver Eject Resource ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
endTime	datetime	End Time	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
hours	double	Hours	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
reason	string	Reason	☐	
rejectReason	string	Reject Reason	☐	
requestDate	datetime	Request Date	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startTime	datetime	Start Time	☐	
status	int32	Status	☐	
timeOffRequestType	int32	Time of Request Type	☐	

351.1.3 TimeOffRequestsCount

Catalog: Autotask

Schema: TimeOffRequests

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table TimeOffRequestsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

352 Schema: TimeOffRequestsChild

352.1 Tables

352.1.1 ResourcesByParentIdTimeOffRequests

Catalog: Autotask

Schema: TimeOffRequestsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdTimeOffRequests. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function ResourcesByParentIdTimeOffRequests are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approvedDateTime	datetime	Approved Date/Time	☐	
approveRejectResourceID	int32	Approver Eject Resource ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
endTime	datetime	End Time	☐	
hours	double	Hours	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
reason	string	Reason	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
rejectReason	string	Reject Reason	☐	
requestDate	datetime	Request Date	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startTime	datetime	Start Time	☐	
status	int32	Status	☐	
timeOffRequestType	int32	Time of Request Type	☐	

352.1.2 ResourcesByParentIdTimeOffRequestsId

Catalog: Autotask

Schema: TimeOffRequestsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ResourcesByParentIdTimeOffRequestsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Columns of Table Function

The columns of the table function ResourcesByParentIdTimeOffRequestsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
approvedDateTime	datetime	Approved Date/Time	☐	
approveRejectResourceID	int32	Approver Eject Resource ID	☐	
createDateTime	datetime	Created	☐	
createdByResourceID	int32	Created by Resource ID	☐	
endTime	datetime	End Time	☐	
hours	double	Hours	☐	
id	int64	ID	☐	
lastModifiedByResourceID	int32	Last Modified by Resource ID	☐	
lastModifiedDateTime	datetime	Last Modified	☐	
reason	string	Reason	☐	
rejectReason	string	Reject Reason	☐	
requestDate	datetime	Request Date	☐	
resourceID	int32	Resource ID	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
startTime	datetime	Start Time	☐	
status	int32	Status	☐	
timeOffRequestType	int32	Time of Request Type	☐	

353 Schema: UserDefinedFieldDefinitions

353.1 Tables

353.1.1 UserDefinedFieldDefinitions

Catalog: Autotask

Schema: UserDefinedFieldDefinitions

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldDefinitions are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
crmToProjectUdfId	int64	CRM to Project UDF ID	☐	
dataType	int32	Data Type	☐	
defaultValue	string	Default Value	☐	
description	string	Description	☐	
displayFormat	int32	Display Format	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isEncrypted	boolean	Is Encrypted	☐	
isFieldMapping	boolean	Is Field Mapping	☐	
isPrivate	boolean	Is Private	☐	
isProtected	boolean	Is Protected	☐	
isRequired	boolean	Is Required	☐	
isVisibleToClientPortal	boolean	Is Visible to Client Portal	☐	
mergeVariableName	string	Merge Variable Name	☐	
name	string	Name	☐	
numberOfDecimalPlaces	int32	Number of Decimal Places	☐	
sortOrder	int32	Sort Order	☐	
udfType	int32	UDF Type	☐	

353.1.2 UserDefinedFieldDefinitionsById

Catalog: Autotask

Schema: UserDefinedFieldDefinitions

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldDefinitionsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldDefinitionsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
crmToProjectUdfId	int64	CRM to Project UDF ID	☐	
dataType	int32	Data Type	☐	
defaultValue	string	Default Value	☐	
description	string	Description	☐	
displayFormat	int32	Display Format	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
isEncrypted	boolean	Is Encrypted	☐	
isFieldMapping	boolean	Is Field Mapping	☐	
isPrivate	boolean	Is Private	☐	
isProtected	boolean	Is Protected	☐	
isRequired	boolean	Is Required	☐	
isVisibleToClientPortal	boolean	Is Visible to Client Portal	☐	
mergeVariableName	string	Merge Variable Name	☐	
name	string	Name	☐	
numberOfDecimalPlaces	int32	Number of Decimal Places	☐	
sortOrder	int32	Sort Order	☐	
udfType	int32	UDF Type	☐	

353.1.3 UserDefinedFieldDefinitionsCount

Catalog: Autotask

Schema: UserDefinedFieldDefinitions

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldDefinitionsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

354 Schema: UserDefinedFieldListItems

354.1 Tables

354.1.1 UserDefinedFieldListItems

Catalog: Autotask

Schema: UserDefinedFieldListItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldListItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldId	int64	UDF Field ID	☐	
valueForDisplay	string	Value for Display	☐	
valueForExport	string	Value for Export	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

354.1.2 UserDefinedFieldListItemsById

Catalog: Autotask

Schema: UserDefinedFieldListItems

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldListItemsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldListItemsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldId	int64	UDF Field ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
valueForDisplay	string	Value for Display	☐	
valueForExport	string	Value for Export	☐	

354.1.3 UserDefinedFieldListItemsCount

Catalog: Autotask

Schema: UserDefinedFieldListItems

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table UserDefinedFieldListItemsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

355 Schema: UserDefinedFieldListItemsChild

355.1 Tables

355.1.1 UserDefinedFieldsByParentIdListItems

Catalog: Autotask

Schema: UserDefinedFieldListItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldsByParentIdListItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
parentId	int64	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldsByParentIdListItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldId	int64	UDF Field ID	☐	
valueForDisplay	string	Value for Display	☐	
valueForExport	string	Value for Export	☐	

355.1.2 UserDefinedFieldsByParentIdListItemsId

Catalog: Autotask

Schema: UserDefinedFieldListItemsChild

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserDefinedFieldsByParentIdListItemsId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		
parentId	int64	☑		

Columns of Table Function

The columns of the table function UserDefinedFieldsByParentIdListItemsId are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
createDate	datetime	Created	☐	
id	int64	ID	☐	
isActive	boolean	Is Active	☐	
soapParentPropertyId_body_canReduce	boolean		☐	
soapParentPropertyId_body_nodeType	string		☐	
soapParentPropertyId_body_type	string		☐	
soapParentPropertyId_canReduce	boolean		☐	
soapParentPropertyId_name	string		☐	
soapParentPropertyId_nodeType	string		☐	
soapParentPropertyId_returnType	string		☐	
soapParentPropertyId_tailCall	boolean		☐	
soapParentPropertyId_type	string		☐	
udfFieldId	int64	UDF Field ID	☐	
valueForDisplay	string	Value for Display	☐	
valueForExport	string	Value for Export	☐	

356 Schema: WebhookEventErrorLogs

356.1 Tables

356.1.1 WebhookEventErrorLogs

Catalog: Autotask

Schema: WebhookEventErrorLogs

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table WebhookEventErrorLogs are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountWebhookID	int32	Account Webhook ID	☐	
contactWebhookID	int32	Contact Webhook ID	☐	
createDateTime	datetime	Created	☐	
errorMessage	string	Error Message	☐	
id	int64	ID	☐	
payload	string	Payload	☐	
sequenceNumber	int32	Sequence Number	☐	

356.1.2 WebhookEventErrorLogsById

Catalog: Autotask

Schema: WebhookEventErrorLogs

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function WebhookEventErrorLogsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function WebhookEventErrorLogsById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountWebhookID	int32	Account Webhook ID	☐	
contactWebhookID	int32	Contact Webhook ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createDateTime	datetime	Created	☐	
errorMessage	string	Error Message	☐	
id	int64	ID	☐	
payload	string	Payload	☐	
sequenceNumber	int32	Sequence Number	☐	

356.1.3 WebhookEventErrorLogsCount

Catalog: Autotask

Schema: WebhookEventErrorLogs

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WebhookEventErrorLogsCount are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

357 Schema: WorkTypeModifiers

357.1 Tables

357.1.1 WorkTypeModifiers

Catalog: Autotask

Schema: WorkTypeModifiers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WorkTypeModifiers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
modifierType	int32	Modifier Type	☐	
modifierValue	double	Modifier Value	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

357.1.2 WorkTypeModifiersById

Catalog: Autotask

Schema: WorkTypeModifiers

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function WorkTypeModifiersById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	int64	☑		

Columns of Table Function

The columns of the table function WorkTypeModifiersById are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
id	int64	ID	☐	
modifierType	int32	Modifier Type	☐	
modifierValue	double	Modifier Value	☐	

357.1.3 WorkTypeModifiersCount

Catalog: Autotask

Schema: WorkTypeModifiers

This is a read-only table. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Table Columns

The columns of the table WorkTypeModifiersCount are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
queryCount	int32	Query Count	☐	

358 Schema: ZoneInformationApiIntegration

358.1 Tables

358.1.1 ZoneInformation

Catalog: Autotask

Schema: ZoneInformationApiIntegration

This is a read-only table function. The Autotask API may not support changing the data or the Invantive UniversalSQL driver for Autotask does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Autotask API.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ZoneInformation. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be evaluated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example: a `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
user	string	☑		

Columns of Table Function

The columns of the table function ZoneInformation are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
ci	int32	CI	☐	
url	string	URL	☐	
webUrl	string	Web URL	☐	
zoneName	string	Zone Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Index

- A -

Account Manager When Approved ID 65, 67
Account Webhook ID 2302, 2303
Accounting Reference ID 2054, 2055
accountingReferenceID 2054, 2055
accountManagerWhenApprovedID 65, 67
accountWebhookID 2302, 2303
Action 2219, 2220
Action Type 123, 124, 126, 127, 139, 140, 142, 144
actionType 123, 124, 126, 127, 139, 140, 142, 144
ActionTypes 17
ActionTypesById 17
ActionTypesCount 18
ActionTypesEntityInformation 495
ActionTypesEntityInformation_FieldsPicklistValuesFields 495
ActionTypesEntityInformation_FieldsPicklistValuesUserDefinedFields 496
ActionTypesEntityInformationFields 497
ActionTypesEntityInformationUserDefinedFields 497
Activity Date Time 361, 362, 364
Activity Description 139, 140, 142, 144
activityDateTime 361, 362, 364
activityDescription 139, 140, 142, 144
Actual Billed Hours 1999, 2001, 2003
Actual Hours 1999, 2001, 2003
actualBilledHours 1999, 2001, 2003
actualHours 1999, 2001, 2003
Additional Address Information 86, 88, 90, 105, 107, 109, 235, 237, 239, 454, 456, 458
Additional Bill-to Address Information 2074, 2075, 2076, 2078, 2080, 2082
Additional Invoice Field ID 18, 19
Additional Ship-to Address Information 2074, 2075, 2076, 2078, 2080, 2082
additionalAddressInfo 454, 456, 458
additionalAddressInformation 86, 88, 90, 105, 107, 109, 235, 237, 239
additionalBillToAddressInformation 2074, 2075, 2076, 2078, 2080, 2082
additionalInvoiceFieldID 18, 19
AdditionalInvoiceFieldValues 18
AdditionalInvoiceFieldValuesById 19
AdditionalInvoiceFieldValuesCount 20
AdditionalInvoiceFieldValuesEntityInformation 498
AdditionalInvoiceFieldValuesEntityInformation_FieldsPicklistValuesFields 499
AdditionalInvoiceFieldValuesEntityInformation_FieldsPicklistValuesUserDefinedFields 500
AdditionalInvoiceFieldValuesEntityInformationFields 500
AdditionalInvoiceFieldValuesEntityInformationUserDefinedFields 501
additionalShipToAddressInformation 2074, 2075, 2076, 2078, 2080, 2082
add-odata-mandatory-filters 2
Address 1 86, 88, 90, 111, 112, 114, 116, 454, 456, 458, 2027, 2028
Address 2 86, 88, 90, 111, 112, 114, 116, 454, 456, 458, 2027, 2028
Address Format ID 358
Address Line 105, 107, 109, 235, 237, 239
Address Line 1 105, 107, 109, 235, 237, 239
address1 86, 88, 90, 111, 112, 114, 116, 454, 456, 458, 2027, 2028
address2 86, 88, 90, 111, 112, 114, 116, 454, 456, 458, 2027, 2028
addressFormatID 358
addressLine 105, 107, 109, 235, 237, 239
addressLine1 105, 107, 109, 235, 237, 239
Adjusted Price 333, 334, 336, 337
adjustedPrice 333, 334, 336, 337
Advanced Field 1 1917, 1918, 1920
Advanced Field 2 1917, 1918, 1920
Advanced Field 3 1917, 1918, 1920
Advanced Field 4 1917, 1918, 1920
Advanced Field 5 1917, 1918, 1920
advancedField1 1917, 1918, 1920
advancedField2 1917, 1918, 1920
advancedField3 1917, 1918, 1920
advancedField4 1917, 1918, 1920
advancedField5 1917, 1918, 1920
After Hours Work Type 61, 62
afterHoursWorkType 61, 62
Alert ID 2247, 2250, 2253
Alert Text 93, 95, 96
Alert Type ID 93, 95, 96
alertText 93, 95, 96
alertTypeID 93, 95, 96
Alias 2130, 2131, 2132, 2133
Alternate Phone 105, 107, 109, 235, 237, 239
Alternate Phone 1 86, 88, 90, 111, 112, 114, 116
Alternate Phone 2 86, 88, 90, 111, 112, 114, 116
alternatePhone 105, 107, 109, 235, 237, 239
alternatePhone1 86, 88, 90, 111, 112, 114, 116
alternatePhone2 86, 88, 90, 111, 112, 114, 116
Amount 298, 299, 300, 302, 319, 320, 321, 323, 1917, 1918, 1920
Amount Approved 319, 320, 321, 323

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Amount Due 441, 442
amountApproved 319, 320, 321, 323
amountDue 441, 442
analysis-enforce-row-uniqueness 2
API Vendor ID 86, 88, 90, 105, 107, 109, 194, 198, 202, 235, 237, 239, 2247, 2250, 2253
api-access-token 2
api-client-id 2
api-client-secret 2
api-integration-code 2
api-pre-expiry-refresh-sec 2
api-redirect-url 2
api-refresh-token 2
api-scope 2
api-token-url 2
api-url 2
apiVendorID 86, 88, 90, 105, 107, 109, 194, 198, 202, 235, 237, 239, 2247, 2250, 2253
Appointments 20
AppointmentsById 21
AppointmentsCount 22
AppointmentsEntityInformation 502
AppointmentsEntityInformation_FieldsPicklistValuesFields 502
AppointmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 503
AppointmentsEntityInformationFields 504
AppointmentsEntityInformationUserDefinedFields 505
Approval Date/Time 64
Approval Level 64
Approval Resource ID 64
Approval Status 2029, 2031
Approval Status Changed by Resource ID 2029, 2031
Approval Status Changed Date 2029, 2031
approvalDateTime 64
approvalLevel 64
approvalResourceID 64
approvalStatus 2029, 2031
approvalStatusChangedByResourceID 2029, 2031
approvalStatusChangedDate 2029, 2031
Approve and Post Date 338, 339, 341, 342, 348, 349, 350, 351
approveAndPostDate 338, 339, 341, 342, 348, 349, 350, 351
Approved Date 441, 442
Approved Date/Time 2290, 2291, 2293, 2294
approvedDate 441, 442
approvedDateTime 2290, 2291, 2293, 2294
Approver Eject Date/Time 2202, 2203, 2204, 2205
Approver Eject Note 2202, 2203, 2204, 2205
Approver Eject Resource ID 2290, 2291, 2293, 2294
Approver ID 441, 442
approveRejectDateTime 2202, 2203, 2204, 2205
approveRejectNote 2202, 2203, 2204, 2205
approveRejectResourceID 2290, 2291, 2293, 2294
approverID 441, 442
Article Category ID 488, 490, 491
Article ID 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59
ArticleAttachments 22
ArticleAttachmentsById 23
ArticleAttachmentsCount 25
ArticleAttachmentsEntityInformation 505
ArticleAttachmentsEntityInformation_FieldsPicklistValuesFields 506
ArticleAttachmentsEntityInformationFields 507
articleCategoryID 488, 490, 491
ArticleConfigurationItemCategoryAssociations 28
ArticleConfigurationItemCategoryAssociationsById 29
ArticleConfigurationItemCategoryAssociationsCount 30
ArticleConfigurationItemCategoryAssociationsEntityInformation 507
ArticleConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields 508
ArticleConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 509
ArticleConfigurationItemCategoryAssociationsEntityInformationFields 510
ArticleConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields 510
articleID 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59
ArticleNotes 31
ArticleNotesById 32
ArticleNotesCount 33
ArticleNotesEntityInformation 511
ArticleNotesEntityInformation_FieldsPicklistValuesFields 511
ArticleNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 512
ArticleNotesEntityInformationFields 513
ArticleNotesEntityInformationUserDefinedFields 514
ArticlePlainTextContent 36
ArticlePlainTextContentById 37
ArticlePlainTextContentCount 38
ArticlePlainTextContentEntityInformation 514
ArticlePlainTextContentEntityInformation_FieldsPicklistValuesFields 515

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ArticlePlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields 516
ArticlePlainTextContentEntityInformationFields 517
ArticlePlainTextContentEntityInformationUserDefinedFields 517
ArticleTagAssociations 40
ArticleTagAssociationsById 41
ArticleTagAssociationsCount 42
ArticleTagAssociationsEntityInformation 518
ArticleTagAssociationsEntityInformation_FieldsPicklistValuesFields 518
ArticleTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 519
ArticleTagAssociationsEntityInformationFields 520
ArticleTagAssociationsEntityInformationUserDefinedFields 521
ArticleTicketAssociations 45
ArticleTicketAssociationsById 46
ArticleTicketAssociationsCount 47
ArticleTicketAssociationsEntityInformation 521
ArticleTicketAssociationsEntityInformation_FieldsPicklistValuesFields 522
ArticleTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 523
ArticleTicketAssociationsEntityInformationFields 524
ArticleTicketAssociationsEntityInformationUserDefinedFields 524
ArticleToArticleAssociations 49
ArticleToArticleAssociationsById 50
ArticleToArticleAssociationsCount 51
ArticleToArticleAssociationsEntityInformation 525
ArticleToArticleAssociationsEntityInformation_FieldsPicklistValuesFields 525
ArticleToArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 526
ArticleToArticleAssociationsEntityInformationFields 527
ArticleToArticleAssociationsEntityInformationUserDefinedFields 528
ArticleToDocumentAssociations 53
ArticleToDocumentAssociationsById 54
ArticleToDocumentAssociationsCount 55
ArticleToDocumentAssociationsEntityInformation 528
ArticleToDocumentAssociationsEntityInformation_FieldsPicklistValuesFields 529
ArticleToDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 530
ArticleToDocumentAssociationsEntityInformationFields 531
ArticleToDocumentAssociationsEntityInformationUserDefinedFields 531
Assessment Score 1917, 1918, 1920
assessmentScore 1917, 1918, 1920
Asset Value 86, 88, 90
assetValue 86, 88, 90
Assigned Resource ID 123, 124, 126, 127, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
Assigned Resource Role ID 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
Assigned to Resource ID 139, 140, 142, 144
assignedResourceID 123, 124, 126, 127, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
assignedResourceRoleID 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
assignedToResourceID 139, 140, 142, 144
Associated Article ID 49, 50, 51, 52, 412, 413, 414, 415
Associated Document ID 53, 54, 55, 57, 416, 417, 418, 419
associatedArticleID 49, 50, 51, 52, 412, 413, 414, 415
associatedDocumentID 53, 54, 55, 57, 416, 417, 418, 419
Attach Date 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
attachDate 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
Attached by Contact ID 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Attached by Resource ID 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
attachedByContactID 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
attachedByResourceID 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
Attachment Type 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
AttachmentInfo 58
AttachmentInfoById 59
AttachmentInfoCount 61
AttachmentInfoEntityInformation 532
AttachmentInfoEntityInformation_FieldsPicklistValues Fields 533
AttachmentInfoEntityInformation_FieldsPicklistValues UserDefinedFields 533
AttachmentInfoEntityInformationFields 534
AttachmentInfoEntityInformationUserDefinedFields 535
attachmentType 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Autotask 1, 17, 18, 19, 20, 21, 22, 23, 25, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 58, 59, 61, 62, 63, 64, 65, 67, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 81, 82, 83, 84, 85, 86, 88, 90, 92, 93, 94, 95, 96, 97, 98, 100, 102, 103, 104, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 154, 156, 157, 158, 159, 160, 162, 163, 165, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 194, 198, 202, 206, 207, 208, 209, 210, 211, 212, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 234, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 248, 250, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 294, 295, 296, 297, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 311, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 329, 330, 331, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 347, 348, 349, 350, 351, 352, 353, 355, 356, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 372, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 386, 387, 388, 389, 390, 391, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 421, 422, 423, 425, 427, 428, 429, 431, 432, 433, 435, 436, 438, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 458, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 471, 472, 474, 475, 476, 478, 479, 480, 481, 482, 483, 484, 486, 487, 488, 490, 491, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 582, 583, 584, 586, 587, 588, 589, 590, 591, 592, 593, 594, 596, 597, 598, 599, 600, 601, 603, 604, 605, 606, 607, 608, 609, 610, 611, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 642, 643, 644, 645, 646, 647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 658, 660, 661, 662, 663, 664, 665, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 685, 686, 687, 688, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 714, 715, 716, 717, 719, 720, 721, 722, 723, 724, 725, 726, 728, 729, 730, 731, 732, 733, 734, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 762, 763, 764, 765, 766, 767, 768, 770, 771, 772, 773, 774, 775, 776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792, 793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 813, 814, 815, 816, 817, 818, 819, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834,
Available Kilobytes 194, 198, 202
availableUnits 469, 471, 472, 475, 476
Average Cost 2020, 2022, 2024, 2026
averageCost 2020, 2022, 2024, 2026

- B -

Backorder Quantity 461, 469
backOrderQuantity 461, 469
Barriers 1917, 1918, 1920
Batch ID 482, 483
batchID 482, 483
Billable Amount 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
billableAmount 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
Billing Address 1 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
Billing Address 2 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
Billing Approval Date/Time 2280, 2282
Billing Approval Level Most Recent 2280, 2282
Billing Approval Resource ID 2280, 2282
Billing Code ID 65, 67, 70, 71, 272, 273, 275, 277, 279, 280, 281, 282, 298, 299, 300, 302, 1944, 1945, 1981, 1982, 1984, 1986, 2084, 2114, 2115, 2116, 2117, 2159, 2161, 2163, 2165, 2167, 2169, 2206, 2208, 2210, 2212, 2247, 2250, 2253, 2280, 2282
Billing Code Type 61, 62
Billing Item Type 65, 67
Billing Preference 329, 330, 331
Billing Product ID 167, 169, 225, 226, 227, 228
Billing Type 1962, 1963, 1964
billingAddress1 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
billingAddress2 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
billingApprovalDateTime 2280, 2282
billingApprovalLevelMostRecent 2280, 2282
billingApprovalResourceID 2280, 2282
billingCodeID 65, 67, 70, 71, 272, 273, 275, 277, 279, 280, 281, 282, 298, 299, 300, 302, 1944, 1945, 1981, 1982, 1984, 1986, 2084, 2114, 2115, 2116, 2117, 2159, 2161, 2163, 2165, 2167, 2169, 2206, 2208, 2210, 2212, 2247, 2250, 2253, 2280, 2282
BillingCodes 61
BillingCodesById 62
BillingCodesCount 63
BillingCodesEntityInformation 535
BillingCodesEntityInformation_FieldsPicklistValuesFields 536
BillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields 537

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

BillingCodesEntityInformationFields 538
BillingCodesEntityInformationUserDefinedFields 538
billingCodeType 61, 62
BillingItemApprovalLevels 64
BillingItemApprovalLevelsById 64
BillingItemApprovalLevelsCount 65
BillingItemApprovalLevelsEntityInformation 539
BillingItemApprovalLevelsEntityInformation_FieldsPicklistValuesFields 540
BillingItemApprovalLevelsEntityInformation_FieldsPicklistValuesUserDefinedFields 540
BillingItemApprovalLevelsEntityInformationFields 541
BillingItemApprovalLevelsEntityInformationUserDefinedFields 542
BillingItems 65
BillingItemsById 67
BillingItemsCount 69
BillingItemsEntityInformation 542
BillingItemsEntityInformation_FieldsPicklistValuesFields 543
BillingItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 544
BillingItemsEntityInformationFields 545
BillingItemsEntityInformationUserDefinedFields 545
billingItemType 65, 67
billingPreference 329, 330, 331
billingProductID 167, 169, 225, 226, 227, 228
billingType 1962, 1963, 1964
Bill-to Additional Address Information 86, 88, 90
Bill-to Address to Use 86, 88, 90
Bill-to Attention 86, 88, 90
Bill-to City 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
Bill-to Company Contact ID 329, 330, 331
Bill-to Company ID 329, 330, 331
Bill-to Company Location ID 86, 88, 90
Bill-to Country ID 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
Bill-to Location ID 2029, 2031
Bill-to Postal Code 2074, 2075, 2076, 2078, 2080, 2082
Bill-to State 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
Bill-to ZIP Code 86, 88, 90
billToAdditionalAddressInformation 86, 88, 90
billToAddressToUse 86, 88, 90
billToAttention 86, 88, 90
billToCity 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
billToCompanyContactID 329, 330, 331
billToCompanyID 329, 330, 331
billToCompanyLocationID 86, 88, 90
billToCountryID 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
billToLocationID 2029, 2031
billToPostalCode 2074, 2075, 2076, 2078, 2080, 2082
billToState 86, 88, 90, 2074, 2075, 2076, 2078, 2080, 2082
billToZipCode 86, 88, 90
Bin 461, 469
BLOB Preferred 1912
BLOB_PREFERRED 1912
Block Hour Multiplier 262, 263, 264, 265
blockHourMultiplier 262, 263, 264, 265
BOL_RESPONSE_CACHE_MAX_AGE_SEC 1912
Build 61
Bulk Email Opt-out Time 105, 107, 109, 235, 237, 239
bulk-delete-page-size-rows 2
bulkEmailOptOutTime 105, 107, 109, 235, 237, 239
bulk-insert-page-size-bytes 2
bulk-insert-page-size-rows 2

- C -

Calculate Tax Separately 2029, 2031, 2033, 2034
calculateTaxSeparately 2029, 2031, 2033, 2034
Can Client Portal User Complete Task 2159, 2161, 2163, 2165, 2167, 2169

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Can Create 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

Can Delete 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Can Query 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 834, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

Can Update 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 834, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

Cancel Date/Time 2017, 2018
Cancelation Notice Hours 2090, 2091
cancelationNoticeHours 2090, 2091
cancelDateTime 2017, 2018
Canceled by Resource ID 2090, 2091
Canceled Date/Time 2090, 2091
canceledByResourceID 2090, 2091
canceledDateTime 2090, 2091
canClientPortalUserCompleteTask 2159, 2161, 2163, 2165, 2167, 2169
Category ID 2118
categoryID 2118
Change Approval Board 2247, 2250, 2253
Change Approval Status 2247, 2250, 2253
Change Approval Type 2247, 2250, 2253
Change Information Field 1 2247, 2250, 2253
Change Information Field 2 2247, 2250, 2253

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Change Information Field 3 2247, 2250, 2253
Change Information Field 4 2247, 2250, 2253
Change Information Field 5 2247, 2250, 2253
Change Order Hours 70, 71
Change Orders Budget 1999, 2001, 2003
Change Orders Revenue 1999, 2001, 2003
Change Request Ticket ID 73
changeApprovalBoard 2247, 2250, 2253
changeApprovalStatus 2247, 2250, 2253
changeApprovalType 2247, 2250, 2253
changeInfoField1 2247, 2250, 2253
changeInfoField2 2247, 2250, 2253
changeInfoField3 2247, 2250, 2253
changeInfoField4 2247, 2250, 2253
changeInfoField5 2247, 2250, 2253
ChangeOrderCharges 70
ChangeOrderChargesById 71
ChangeOrderChargesCount 72
ChangeOrderChargesEntityInformation 546
ChangeOrderChargesEntityInformation_FieldsPicklistValuesFields 547
ChangeOrderChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 547
ChangeOrderChargesEntityInformationFields 548
ChangeOrderChargesEntityInformationUserDefinedFields 549
changeOrderHours 70, 71
changeOrdersBudget 1999, 2001, 2003
changeOrdersRevenue 1999, 2001, 2003
ChangeRequestLinks 73
ChangeRequestLinksById 73
ChangeRequestLinksCount 74
ChangeRequestLinksEntityInformation 549
ChangeRequestLinksEntityInformation_FieldsPicklistValuesFields 550
ChangeRequestLinksEntityInformation_FieldsPicklistValuesUserDefinedFields 551
ChangeRequestLinksEntityInformationFields 552
ChangeRequestLinksEntityInformationUserDefinedFields 552
changeRequestTicketID 73
Charge Billing Code ID 1962, 1963, 1964
Charge ID 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026
Charge Type 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
chargeBillingCodeID 1962, 1963, 1964
chargeID 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026
chargeType 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
Checklist Library ID 76, 77, 78, 79
ChecklistLibraries 74
ChecklistLibrariesById 75
ChecklistLibrariesByParentIdChecklistItems 78
ChecklistLibrariesByParentIdChecklistItemsEntityInformation 553
ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields 554
ChecklistLibrariesByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 555
ChecklistLibrariesByParentIdChecklistItemsEntityInformationFields 556
ChecklistLibrariesByParentIdChecklistItemsEntityInformationUserDefinedFields 558
ChecklistLibrariesByParentIdChecklistItemsId 79
ChecklistLibrariesCount 76
ChecklistLibrariesEntityInformation 559
ChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 559
ChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 560
ChecklistLibrariesEntityInformationFields 561
ChecklistLibrariesEntityInformationUserDefinedFields 562
ChecklistLibraryChecklistItems 76
ChecklistLibraryChecklistItemsById 77
ChecklistLibraryChecklistItemsCount 78
ChecklistLibraryChecklistItemsEntityInformation 562
ChecklistLibraryChecklistItemsEntityInformation_FieldsPicklistValuesFields 563
ChecklistLibraryChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 564
ChecklistLibraryChecklistItemsEntityInformationFields 565
ChecklistLibraryChecklistItemsEntityInformationUserDefinedFields 565
checklistLibraryID 76, 77, 78, 79
CI 2306
City 86, 88, 90, 105, 107, 109, 111, 112, 114, 116, 235, 237, 239, 454, 456, 458, 2027, 2028
Classification 86, 88, 90
ClassificationIcons 81
ClassificationIconsById 81
ClassificationIconsCount 82
ClassificationIconsEntityInformation 566
ClassificationIconsEntityInformation_FieldsPicklistValuesFields 566
ClassificationIconsEntityInformation_FieldsPicklistValuesUserDefinedFields 567
ClassificationIconsEntityInformationFields 568
ClassificationIconsEntityInformationUserDefinedFields 569
ClientPortalUsers 82

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ClientPortalUsersById 83
ClientPortalUsersCount 84
ClientPortalUsersEntityInformation 569
ClientPortalUsersEntityInformation_FieldsPicklistValuesFields 570
ClientPortalUsersEntityInformation_FieldsPicklistValuesUserDefinedFields 571
ClientPortalUsersEntityInformationFields 572
ClientPortalUsersEntityInformationUserDefinedFields 572
Closed Date 1917, 1918, 1920
closedDate 1917, 1918, 1920
ComanagedAssociations 84
ComanagedAssociationsById 85
ComanagedAssociationsCount 86
ComanagedAssociationsEntityInformation 573
ComanagedAssociationsEntityInformation_FieldsPicklistValuesFields 573
ComanagedAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 574
ComanagedAssociationsEntityInformationFields 575
ComanagedAssociationsEntityInformationUserDefinedFields 576
Comment 2029, 2031
Comments 482, 483
Companies 86
Companies_ItemsUserDefinedFields 88
CompaniesById 90
CompaniesByParentId_ItemsUserDefinedFieldsContacts 105
CompaniesByParentId_ItemsUserDefinedFieldsSiteConfigurations 132
CompaniesByParentIdAlerts 95
CompaniesByParentIdAlertsEntityInformation 576
CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesFields 577
CompaniesByParentIdAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields 579
CompaniesByParentIdAlertsEntityInformationFields 580
CompaniesByParentIdAlertsEntityInformationUserDefinedFields 581
CompaniesByParentIdAlertsId 96
CompaniesByParentIdAttachments 100
CompaniesByParentIdAttachmentsId 102
CompaniesByParentIdContacts 107
CompaniesByParentIdContactsEntityInformation 582
CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesFields 583
CompaniesByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields 584
CompaniesByParentIdContactsEntityInformationFields 586
CompaniesByParentIdContactsEntityInformationUserDefinedFields 587
CompaniesByParentIdContactsId 109
CompaniesByParentIdLocations 114
CompaniesByParentIdLocationsEntityInformation 588
CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesFields 589
CompaniesByParentIdLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields 590
CompaniesByParentIdLocationsEntityInformationFields 591
CompaniesByParentIdLocationsEntityInformationUserDefinedFields 592
CompaniesByParentIdLocationsId 116
CompaniesByParentIdNotes 126
CompaniesByParentIdNotesEntityInformation 593
CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesFields 594
CompaniesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 596
CompaniesByParentIdNotesEntityInformationFields 597
CompaniesByParentIdNotesEntityInformationUserDefinedFields 598
CompaniesByParentIdNotesId 127
CompaniesByParentIdSiteConfigurations 133
CompaniesByParentIdSiteConfigurationsEntityInformation 599
CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesFields 600
CompaniesByParentIdSiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields 601
CompaniesByParentIdSiteConfigurationsEntityInformationFields 603
CompaniesByParentIdSiteConfigurationsEntityInformationUserDefinedFields 604
CompaniesByParentIdSiteConfigurationsId 134
CompaniesByParentIdTeams 137
CompaniesByParentIdTeamsEntityInformation 605
CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesFields 606
CompaniesByParentIdTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields 607
CompaniesByParentIdTeamsEntityInformationFields 608
CompaniesByParentIdTeamsEntityInformationUserDefinedFields 609
CompaniesByParentIdTeamsId 138
CompaniesByParentIdToDos 142
CompaniesByParentIdToDosEntityInformation 610

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesFields 611
CompaniesByParentIdToDosEntityInformation_FieldsPicklistValuesUserDefinedFields 613
CompaniesByParentIdToDosEntityInformationFields 614
CompaniesByParentIdToDosEntityInformationUserDefinedFields 615
CompaniesByParentIdToDosId 144
CompaniesCount 92
CompaniesEntityInformation 616
CompaniesEntityInformation_FieldsPicklistValuesFields 617
CompaniesEntityInformation_FieldsPicklistValuesUserDefinedFields 617
CompaniesEntityInformationFields 618
CompaniesEntityInformationUserDefinedFields 619
Company Category ID 86, 88, 90
Company ID 58, 59, 65, 67, 84, 85, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 194, 198, 202, 235, 237, 239, 329, 330, 331, 398, 399, 401, 402, 428, 429, 432, 433, 471, 472, 475, 476, 482, 483, 1914, 1915, 1917, 1918, 1920, 1999, 2001, 2003, 2029, 2031, 2074, 2075, 2076, 2078, 2080, 2082, 2090, 2091, 2127, 2247, 2250, 2253
Company Location ID 105, 107, 109, 194, 198, 202, 235, 237, 239, 2090, 2091, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
Company Name 86, 88, 90
Company Note ID 58, 59, 97, 98, 100, 102, 117, 118, 120, 122
Company Number 86, 88, 90
Company Rating 2127
Company Type 86, 88, 90
CompanyAlerts 93
CompanyAlertsById 93
CompanyAlertsCount 94
CompanyAlertsEntityInformation 619
CompanyAlertsEntityInformation_FieldsPicklistValuesFields 620
CompanyAlertsEntityInformation_FieldsPicklistValuesUserDefinedFields 621
CompanyAlertsEntityInformationFields 622
CompanyAlertsEntityInformationUserDefinedFields 622
CompanyAttachments 97
CompanyAttachmentsById 98
CompanyAttachmentsCount 100
CompanyAttachmentsEntityInformation 623
CompanyAttachmentsEntityInformation_FieldsPicklistValuesFields 624
CompanyAttachmentsEntityInformationFields 624
CompanyCategories 103
CompanyCategoriesById 104
CompanyCategoriesCount 105
CompanyCategoriesEntityInformation 625
CompanyCategoriesEntityInformation_FieldsPicklistValuesFields 626
CompanyCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 626
CompanyCategoriesEntityInformationFields 627
CompanyCategoriesEntityInformationUserDefinedFields 628
CompanyCategoryID 86, 88, 90
companyID 58, 59, 65, 67, 84, 85, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 194, 198, 202, 235, 237, 239, 329, 330, 331, 398, 399, 401, 402, 428, 429, 432, 433, 471, 472, 475, 476, 482, 483, 1914, 1915, 1917, 1918, 1920, 1999, 2001, 2003, 2029, 2031, 2074, 2075, 2076, 2078, 2080, 2082, 2090, 2091, 2127, 2247, 2250, 2253
companyLocationID 105, 107, 109, 194, 198, 202, 235, 237, 239, 2090, 2091, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
CompanyLocations 111
CompanyLocationsById 112
CompanyLocationsCount 114
CompanyLocationsEntityInformation 628
CompanyLocationsEntityInformation_FieldsPicklistValuesFields 629
CompanyLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields 630
CompanyLocationsEntityInformationFields 631
CompanyLocationsEntityInformationUserDefinedFields 631
companyName 86, 88, 90
CompanyNoteAttachments 117
CompanyNoteAttachmentsById 118
CompanyNoteAttachmentsCount 120
CompanyNoteAttachmentsEntityInformation 632
CompanyNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 633
CompanyNoteAttachmentsEntityInformationFields 633
companyNoteID 58, 59, 97, 98, 100, 102, 117, 118, 120, 122
CompanyNotes 123
CompanyNotesById 124
CompanyNotesByParentIdAttachments 120
CompanyNotesByParentIdAttachmentsId 122
CompanyNotesCount 126
CompanyNotesEntityInformation 634
CompanyNotesEntityInformation_FieldsPicklistValuesFields 635

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

CompanyNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 635
CompanyNotesEntityInformationFields 636
CompanyNotesEntityInformationUserDefinedFields 637
companyNumber 86, 88, 90
Company-owner Resource ID 1999, 2001, 2003
companyOwnerResourceID 1999, 2001, 2003
companyRating 2127
CompanySiteConfigurations 129
CompanySiteConfigurations_ItemsUserDefinedFields 130
CompanySiteConfigurationsById 130
CompanySiteConfigurationsCount 131
CompanySiteConfigurationsEntityInformation 637
CompanySiteConfigurationsEntityInformation_FieldsPicklistValuesFields 638
CompanySiteConfigurationsEntityInformation_FieldsPicklistValuesUserDefinedFields 639
CompanySiteConfigurationsEntityInformationFields 640
CompanySiteConfigurationsEntityInformationUserDefinedFields 640
CompanyTeams 135
CompanyTeamsById 136
CompanyTeamsCount 137
CompanyTeamsEntityInformation 641
CompanyTeamsEntityInformation_FieldsPicklistValuesFields 642
CompanyTeamsEntityInformation_FieldsPicklistValuesUserDefinedFields 642
CompanyTeamsEntityInformationFields 643
CompanyTeamsEntityInformationUserDefinedFields 644
CompanyToDos 139
CompanyToDosById 140
CompanyToDosCount 142
CompanyToDosEntityInformation 644
CompanyToDosEntityInformation_FieldsPicklistValuesFields 645
CompanyToDosEntityInformation_FieldsPicklistValuesUserDefinedFields 646
CompanyToDosEntityInformationFields 647
CompanyToDosEntityInformationUserDefinedFields 647
companyType 86, 88, 90
CompanyWebhookExcludedResources 145
CompanyWebhookExcludedResourcesById 146
CompanyWebhookExcludedResourcesCount 147
CompanyWebhookExcludedResourcesEntityInformation 648
CompanyWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields 649
CompanyWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 649
CompanyWebhookExcludedResourcesEntityInformationFields 650
CompanyWebhookExcludedResourcesEntityInformationUserDefinedFields 651
CompanyWebhookFields 149
CompanyWebhookFieldsById 150
CompanyWebhookFieldsCount 151
CompanyWebhookFieldsEntityInformation 652
CompanyWebhookFieldsEntityInformation_FieldsPicklistValuesFields 652
CompanyWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 653
CompanyWebhookFieldsEntityInformationFields 654
CompanyWebhookFieldsEntityInformationUserDefinedFields 654
CompanyWebhooks 154
CompanyWebhooksById 154
CompanyWebhooksByParentIdExcludedResources 147
CompanyWebhooksByParentIdExcludedResourcesEntityInformation 655
CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 656
CompanyWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 657
CompanyWebhooksByParentIdExcludedResourcesEntityInformationFields 659
CompanyWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 660
CompanyWebhooksByParentIdExcludedResourcesId 148
CompanyWebhooksByParentIdFields 151
CompanyWebhooksByParentIdFieldsEntityInformation 661
CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 662
CompanyWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 663
CompanyWebhooksByParentIdFieldsEntityInformationFields 664
CompanyWebhooksByParentIdFieldsEntityInformationUserDefinedFields 665
CompanyWebhooksByParentIdFieldsId 153
CompanyWebhooksByParentIdUdfFields 158
CompanyWebhooksByParentIdUdfFieldsEntityInformation 667
CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields 668
CompanyWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 669

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

CompanyWebhooksByParentIdUdfFieldsEntityInformationFields 670
CompanyWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields 671
CompanyWebhooksByParentIdUdfFieldsId 159
CompanyWebhooksCount 156
CompanyWebhooksEntityInformation 672
CompanyWebhooksEntityInformation_FieldsPicklistValuesFields 673
CompanyWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 674
CompanyWebhooksEntityInformationFields 675
CompanyWebhooksEntityInformationUserDefinedFields 675
CompanyWebhookUdfFields 156
CompanyWebhookUdfFieldsById 157
CompanyWebhookUdfFieldsCount 158
CompanyWebhookUdfFieldsEntityInformation 676
CompanyWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields 676
CompanyWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 677
CompanyWebhookUdfFieldsEntityInformationFields 678
CompanyWebhookUdfFieldsEntityInformationUserDefinedFields 679
Competitor ID 86, 88, 90
competitorID 86, 88, 90
Complete Date 2127
Completed 123, 124, 126, 127, 1999, 2001, 2003, 2159, 2161, 2163, 2165, 2167, 2169, 2214, 2216, 2217
Completed by Resource ID 2159, 2161, 2163, 2165, 2167, 2169, 2214, 2216, 2217, 2247, 2250, 2253
Completed by Type 2159, 2161, 2163, 2165, 2167, 2169
Completed Percentage 1999, 2001, 2003
completeDate 2127
completedByResourceID 2159, 2161, 2163, 2165, 2167, 2169, 2214, 2216, 2217, 2247, 2250, 2253
completedByType 2159, 2161, 2163, 2165, 2167, 2169
completedDate 139, 140, 142, 144, 2247, 2250, 2253
completedDateTime 123, 124, 126, 127, 1999, 2001, 2003, 2159, 2161, 2163, 2165, 2167, 2169, 2214, 2216, 2217
completedPercentage 1999, 2001, 2003
Completion Date 139, 140, 142, 144, 2247, 2250, 2253
Configuration Item Category ID 172, 174, 194, 198, 202
Configuration Item ID 58, 59, 65, 67, 160, 162, 163, 165, 167, 169, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 206, 207, 208, 381, 382, 383, 384, 471, 472, 475, 476, 2124, 2125, 2180, 2181, 2182, 2184, 2247, 2250, 2253
Configuration Item Note ID 58, 59, 160, 162, 163, 165, 179, 180, 182, 183
Configuration Item Type 194, 198, 202
ConfigurationItemAttachments 160
ConfigurationItemAttachmentsById 162
ConfigurationItemAttachmentsCount 163
ConfigurationItemAttachmentsEntityInformation 679
ConfigurationItemAttachmentsEntityInformation_FieldsPicklistValuesFields 680
ConfigurationItemAttachmentsEntityInformationFields 681
ConfigurationItemBillingProductAssociations 167
ConfigurationItemBillingProductAssociationsById 167
ConfigurationItemBillingProductAssociationsCount 168
ConfigurationItemBillingProductAssociationsEntityInformation 681
ConfigurationItemBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields 682
ConfigurationItemBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 683
ConfigurationItemBillingProductAssociationsEntityInformationFields 684
ConfigurationItemBillingProductAssociationsEntityInformationUserDefinedFields 684
ConfigurationItemCategories 170
ConfigurationItemCategoriesById 170
ConfigurationItemCategoriesByParentIdUdfAssociations 174
ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation 685
ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformation_FieldsPicklistValuesFields 686
ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationFields 687
ConfigurationItemCategoriesByParentIdUdfAssociationsEntityInformationUserDefinedFields 688
ConfigurationItemCategoriesCount 171
ConfigurationItemCategoriesEntityInformation 690
ConfigurationItemCategoriesEntityInformation_FieldsPicklistValuesFields 690
ConfigurationItemCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 691
ConfigurationItemCategoriesEntityInformationFields 692
ConfigurationItemCategoriesEntityInformationUserDefinedFields 692

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

configurationItemCategoryID 172, 174, 194, 198, 202
ConfigurationItemCategoryUdfAssociations 172
ConfigurationItemCategoryUdfAssociationsById 172
ConfigurationItemCategoryUdfAssociationsCount 173
ConfigurationItemCategoryUdfAssociationsEntityInformation 693
ConfigurationItemCategoryUdfAssociationsEntityInformation_FieldsPicklistValuesFields 694
ConfigurationItemCategoryUdfAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 695
ConfigurationItemCategoryUdfAssociationsEntityInformationFields 695
ConfigurationItemCategoryUdfAssociationsEntityInformationUserDefinedFields 696
ConfigurationItemDnsRecords 175
ConfigurationItemDnsRecordsById 176
ConfigurationItemDnsRecordsCount 176
ConfigurationItemDnsRecordsEntityInformation 697
ConfigurationItemDnsRecordsEntityInformation_FieldsPicklistValuesFields 697
ConfigurationItemDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields 698
ConfigurationItemDnsRecordsEntityInformationFields 699
ConfigurationItemDnsRecordsEntityInformationUserDefinedFields 700
configurationItemID 58, 59, 65, 67, 160, 162, 163, 165, 167, 169, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 206, 207, 208, 381, 382, 383, 384, 471, 472, 475, 476, 2124, 2125, 2180, 2181, 2182, 2184, 2247, 2250, 2253
ConfigurationItemNoteAttachments 179
ConfigurationItemNoteAttachmentsById 180
ConfigurationItemNoteAttachmentsCount 181
ConfigurationItemNoteAttachmentsEntityInformation 700
ConfigurationItemNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 701
ConfigurationItemNoteAttachmentsEntityInformationFields 702
configurationItemNoteID 58, 59, 160, 162, 163, 165, 179, 180, 182, 183
ConfigurationItemNotes 185
ConfigurationItemNotesById 186
ConfigurationItemNotesByParentIdAttachments 182
ConfigurationItemNotesByParentIdAttachmentsId 183
ConfigurationItemNotesCount 187
ConfigurationItemNotesEntityInformation 702
ConfigurationItemNotesEntityInformation_FieldsPicklistValuesFields 703
ConfigurationItemNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 704
ConfigurationItemNotesEntityInformationFields 705
ConfigurationItemNotesEntityInformationUserDefinedFields 705
ConfigurationItemRelatedItems 190
ConfigurationItemRelatedItemsById 191
ConfigurationItemRelatedItemsCount 192
ConfigurationItemRelatedItemsEntityInformation 706
ConfigurationItemRelatedItemsEntityInformation_FieldsPicklistValuesFields 706
ConfigurationItemRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 707
ConfigurationItemRelatedItemsEntityInformationFields 708
ConfigurationItemRelatedItemsEntityInformationUserDefinedFields 709
ConfigurationItems 194
ConfigurationItems_ItemsUserDefinedFields 198
ConfigurationItemsById 202
ConfigurationItemsByParentIdAttachments 163
ConfigurationItemsByParentIdAttachmentsId 165
ConfigurationItemsByParentIdBillingProductAssociations 169
ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation 709
ConfigurationItemsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields 710
ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationFields 712
ConfigurationItemsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields 713
ConfigurationItemsByParentIdDnsRecords 177
ConfigurationItemsByParentIdDnsRecordsEntityInformation 714
ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesFields 715
ConfigurationItemsByParentIdDnsRecordsEntityInformation_FieldsPicklistValuesUserDefinedFields 716
ConfigurationItemsByParentIdDnsRecordsEntityInformationFields 717
ConfigurationItemsByParentIdDnsRecordsEntityInformationUserDefinedFields 719
ConfigurationItemsByParentIdDnsRecordsId 178
ConfigurationItemsByParentIdNotes 187
ConfigurationItemsByParentIdNotesEntityInformation 720
ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 721
ConfigurationItemsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 722
ConfigurationItemsByParentIdNotesEntityInformationFields 723

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ConfigurationItemsByParentIdNotesEntityInformationUserDefinedFields 724
ConfigurationItemsByParentIdNotesId 189
ConfigurationItemsByParentIdRelatedItems 192
ConfigurationItemsByParentIdRelatedItemsEntityInformation 725
ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesFields 726
ConfigurationItemsByParentIdRelatedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 728
ConfigurationItemsByParentIdRelatedItemsEntityInformationFields 729
ConfigurationItemsByParentIdRelatedItemsEntityInformationUserDefinedFields 730
ConfigurationItemsByParentIdRelatedItemsId 193
ConfigurationItemsByParentIdSslSubjectAlternativeNames 208
ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation 731
ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields 732
ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationFields 733
ConfigurationItemsByParentIdSslSubjectAlternativeNamesEntityInformationUserDefinedFields 734
ConfigurationItemsCount 206
ConfigurationItemsEntityInformation 736
ConfigurationItemsEntityInformation_FieldsPicklistValuesFields 736
ConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 737
ConfigurationItemsEntityInformationFields 738
ConfigurationItemsEntityInformationUserDefinedFields 738
ConfigurationItemSslSubjectAlternativeNames 206
ConfigurationItemSslSubjectAlternativeNamesById 207
ConfigurationItemSslSubjectAlternativeNamesCount 207
ConfigurationItemSslSubjectAlternativeNamesEntityInformation 739
ConfigurationItemSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesFields 740
ConfigurationItemSslSubjectAlternativeNamesEntityInformation_FieldsPicklistValuesUserDefinedFields 741
ConfigurationItemSslSubjectAlternativeNamesEntityInformationFields 741
ConfigurationItemSslSubjectAlternativeNamesEntityInformationUserDefinedFields 742
configurationItemType 194, 198, 202
ConfigurationItemTypes 209
ConfigurationItemTypesById 209
ConfigurationItemTypesCount 210
ConfigurationItemTypesEntityInformation 743
ConfigurationItemTypesEntityInformation_FieldsPicklistValuesFields 743
ConfigurationItemTypesEntityInformation_FieldsPicklistValuesUserDefinedFields 744
ConfigurationItemTypesEntityInformationFields 745
ConfigurationItemTypesEntityInformationUserDefinedFields 746
ConfigurationItemWebhookExcludedResources 210
ConfigurationItemWebhookExcludedResourcesById 211
ConfigurationItemWebhookExcludedResourcesCount 212
ConfigurationItemWebhookExcludedResourcesEntityInformation 746
ConfigurationItemWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields 747
ConfigurationItemWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 748
ConfigurationItemWebhookExcludedResourcesEntityInformationFields 749
ConfigurationItemWebhookExcludedResourcesEntityInformationUserDefinedFields 749
ConfigurationItemWebhookFields 214
ConfigurationItemWebhookFieldsById 214
ConfigurationItemWebhookFieldsCount 215
ConfigurationItemWebhookFieldsEntityInformation 750
ConfigurationItemWebhookFieldsEntityInformation_FieldsPicklistValuesFields 751
ConfigurationItemWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 751
ConfigurationItemWebhookFieldsEntityInformationFields 752
ConfigurationItemWebhookFieldsEntityInformationUserDefinedFields 753
ConfigurationItemWebhooks 218
ConfigurationItemWebhooksById 219
ConfigurationItemWebhooksByParentIdExcludedResources 212
ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation 754
ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 755
ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationFields 756
ConfigurationItemWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 757
ConfigurationItemWebhooksByParentIdFields 216
ConfigurationItemWebhooksByParentIdFieldsEntityInformation 758

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 759
ConfigurationItemWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 760
ConfigurationItemWebhooksByParentIdFieldsEntityInformationFields 762
ConfigurationItemWebhooksByParentIdFieldsEntityInformationUserDefinedFields 763
ConfigurationItemWebhooksByParentIdFieldsId 217
ConfigurationItemWebhooksByParentIdUdfFields 223
ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation 764
ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields 765
ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 766
ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationFields 767
ConfigurationItemWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields 768
ConfigurationItemWebhooksByParentIdUdfFieldsId 224
ConfigurationItemWebhooksCount 220
ConfigurationItemWebhooksEntityInformation 770
ConfigurationItemWebhooksEntityInformation_FieldsPicklistValuesFields 770
ConfigurationItemWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 771
ConfigurationItemWebhooksEntityInformationFields 772
ConfigurationItemWebhooksEntityInformationUserDefinedFields 772
ConfigurationItemWebhookUdfFields 220
ConfigurationItemWebhookUdfFieldsById 221
ConfigurationItemWebhookUdfFieldsCount 222
ConfigurationItemWebhookUdfFieldsEntityInformation 773
ConfigurationItemWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields 774
ConfigurationItemWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 774
ConfigurationItemWebhookUdfFieldsEntityInformationFields 775
ConfigurationItemWebhookUdfFieldsEntityInformationUserDefinedFields 776
Contact Group ID 229, 230, 231, 232
Contact ID 82, 83, 123, 124, 126, 127, 139, 140, 142, 144, 194, 198, 202, 225, 226, 227, 228, 229, 230, 231, 232, 329, 330, 331, 1917, 1918, 1920, 2029, 2031, 2074, 2075, 2076, 2078, 2080, 2082, 2127, 2185, 2187, 2188, 2202, 2203, 2204, 2205, 2247, 2250, 2253
Contact Name 329, 330, 331
Contact Rating 2127
Contact Webhook ID 2302, 2303
ContactBillingProductAssociations 225
ContactBillingProductAssociationsById 226
ContactBillingProductAssociationsCount 227
ContactBillingProductAssociationsEntityInformation 777
ContactBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields 777
ContactBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 778
ContactBillingProductAssociationsEntityInformationFields 779
ContactBillingProductAssociationsEntityInformationUserDefinedFields 779
ContactGroupContacts 229
ContactGroupContactsById 230
ContactGroupContactsCount 231
ContactGroupContactsEntityInformation 780
ContactGroupContactsEntityInformation_FieldsPicklistValuesFields 781
ContactGroupContactsEntityInformation_FieldsPicklistValuesUserDefinedFields 781
ContactGroupContactsEntityInformationFields 782
ContactGroupContactsEntityInformationUserDefinedFields 783
contactGroupId 229, 230, 231, 232
ContactGroups 234
ContactGroupsById 234
ContactGroupsByParentIdContacts 231
ContactGroupsByParentIdContactsEntityInformation 784
ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesFields 785
ContactGroupsByParentIdContactsEntityInformation_FieldsPicklistValuesUserDefinedFields 786
ContactGroupsByParentIdContactsEntityInformationFields 787
ContactGroupsByParentIdContactsEntityInformationUserDefinedFields 788
ContactGroupsByParentIdContactsId 232
ContactGroupsCount 235
ContactGroupsEntityInformation 789
ContactGroupsEntityInformation_FieldsPicklistValuesFields 790
ContactGroupsEntityInformation_FieldsPicklistValuesUserDefinedFields 791
ContactGroupsEntityInformationFields 791
ContactGroupsEntityInformationUserDefinedFields 792

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

contactID 82, 83, 123, 124, 126, 127, 139, 140, 142, 144, 194, 198, 202, 225, 226, 227, 228, 229, 230, 231, 232, 329, 330, 331, 1917, 1918, 1920, 2029, 2031, 2074, 2075, 2076, 2078, 2080, 2082, 2127, 2185, 2187, 2188, 2202, 2203, 2204, 2205, 2247, 2250, 2253
contactName 329, 330, 331
contactRating 2127
Contacts 235
Contacts_ItemsUserDefinedFields 237
ContactsById 239
ContactsByParentIdBillingProductAssociations 227
ContactsByParentIdBillingProductAssociationsEntityInformation 793
ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesFields 794
ContactsByParentIdBillingProductAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 795
ContactsByParentIdBillingProductAssociationsEntityInformationFields 796
ContactsByParentIdBillingProductAssociationsEntityInformationUserDefinedFields 797
ContactsByParentIdBillingProductAssociationsId 228
ContactsCount 241
ContactsEntityInformation 798
ContactsEntityInformation_FieldsPicklistValuesFields 799
ContactsEntityInformation_FieldsPicklistValuesUserDefinedFields 800
ContactsEntityInformationFields 801
ContactsEntityInformationUserDefinedFields 801
ContactWebhookExcludedResources 241
ContactWebhookExcludedResourcesById 242
ContactWebhookExcludedResourcesCount 243
ContactWebhookExcludedResourcesEntityInformation 802
ContactWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields 803
ContactWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 803
ContactWebhookExcludedResourcesEntityInformationFields 804
ContactWebhookExcludedResourcesEntityInformationUserDefinedFields 805
ContactWebhookFields 245
ContactWebhookFieldsById 246
ContactWebhookFieldsCount 247
ContactWebhookFieldsEntityInformation 806
ContactWebhookFieldsEntityInformation_FieldsPicklistValuesFields 806
ContactWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 807
ContactWebhookFieldsEntityInformationFields 808
ContactWebhookFieldsEntityInformationUserDefinedFields 808
contactWebhookID 2302, 2303
ContactWebhooks 250
ContactWebhooksById 250
ContactWebhooksByParentIdExcludedResources 243
ContactWebhooksByParentIdExcludedResourcesEntityInformation 809
ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 810
ContactWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 811
ContactWebhooksByParentIdExcludedResourcesEntityInformationFields 813
ContactWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 814
ContactWebhooksByParentIdExcludedResourcesId 244
ContactWebhooksByParentIdFields 247
ContactWebhooksByParentIdFieldsEntityInformation 815
ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 816
ContactWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 817
ContactWebhooksByParentIdFieldsEntityInformationFields 818
ContactWebhooksByParentIdFieldsEntityInformationUserDefinedFields 819
ContactWebhooksByParentIdFieldsId 249
ContactWebhooksByParentIdUdfFields 254
ContactWebhooksByParentIdUdfFieldsEntityInformation 821
ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields 822
ContactWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 823
ContactWebhooksByParentIdUdfFieldsEntityInformationFields 824
ContactWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields 825
ContactWebhooksByParentIdUdfFieldsId 255
ContactWebhooksCount 252
ContactWebhooksEntityInformation 826
ContactWebhooksEntityInformation_FieldsPicklistValuesFields 827
ContactWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 828
ContactWebhooksEntityInformationFields 828
ContactWebhooksEntityInformationUserDefinedFields 829

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ContactWebhookUdfFields 252
ContactWebhookUdfFieldsById 253
ContactWebhookUdfFieldsCount 254
ContactWebhookUdfFieldsEntityInformation 830
ContactWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields 830
ContactWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 831
ContactWebhookUdfFieldsEntityInformationFields 832
ContactWebhookUdfFieldsEntityInformationUserDefinedFields 833
Content Data 36, 37, 38, 39, 394, 396, 397
Content Type 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1912, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
CONTENT_TYPE 1912
contentData 36, 37, 38, 39, 394, 396, 397
contentType 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
Contract Category 329, 330, 331
Contract Charge ID 65, 67, 471, 472, 475, 476
Contract Exclusion Set ID 287, 288, 290, 291, 292, 294, 295, 329, 330, 331
Contract Hourly Rate 314, 315, 316, 318
Contract ID 58, 59, 65, 67, 139, 140, 142, 144, 194, 198, 202, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 338, 339, 341, 342, 343, 344, 345, 347, 348, 349, 350, 351, 352, 353, 355, 356, 1999, 2001, 2003, 2012, 2013, 2014, 2016, 2247, 2250, 2253, 2280, 2282
Contract Name 329, 330, 331
Contract Note ID 58, 59, 303, 304, 306, 308
Contract Number 329, 330, 331
Contract Period Type 329, 330, 331
Contract Service Adjustment ID 65, 67
Contract Service Bundle Adjustment ID 65, 67
Contract Service Bundle ID 65, 67, 70, 71, 194, 198, 202, 272, 273, 275, 277, 338, 339, 341, 342, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212, 2247, 2250, 2253, 2280, 2282
Contract Service Bundle Period ID 65, 67
Contract Service ID 65, 67, 70, 71, 194, 198, 202, 272, 273, 275, 277, 348, 349, 350, 351, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212, 2247, 2250, 2253, 2280, 2282
Contract Service Period ID 65, 67
Contract Type 329, 330, 331
ContractBillingRules 256
ContractBillingRulesById 257
ContractBillingRulesCount 259
ContractBillingRulesEntityInformation 833
ContractBillingRulesEntityInformation_FieldsPicklistValuesFields 834
ContractBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields 835
ContractBillingRulesEntityInformationFields 836
ContractBillingRulesEntityInformationUserDefinedFields 836
ContractBlockHourFactors 262
ContractBlockHourFactorsById 263
ContractBlockHourFactorsCount 264
ContractBlockHourFactorsEntityInformation 837
ContractBlockHourFactorsEntityInformation_FieldsPicklistValuesFields 837
ContractBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields 838
ContractBlockHourFactorsEntityInformationFields 839
ContractBlockHourFactorsEntityInformationUserDefinedFields 840
ContractBlocks 267
ContractBlocksById 267
ContractBlocksCount 269
ContractBlocksEntityInformation 840
ContractBlocksEntityInformation_FieldsPicklistValuesFields 841
ContractBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields 842
ContractBlocksEntityInformationFields 843
ContractBlocksEntityInformationUserDefinedFields 843
contractCategory 329, 330, 331
contractChargeID 65, 67, 471, 472, 475, 476
ContractCharges 272
ContractChargesById 273
ContractChargesCount 275
ContractChargesEntityInformation 844
ContractChargesEntityInformation_FieldsPicklistValuesFields 845

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ContractChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 845
ContractChargesEntityInformationFields 846
ContractChargesEntityInformationUserDefinedFields 847
ContractExclusionBillingCodes 279
ContractExclusionBillingCodesById 280
ContractExclusionBillingCodesCount 281
ContractExclusionBillingCodesEntityInformation 847
ContractExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields 848
ContractExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields 849
ContractExclusionBillingCodesEntityInformationFields 850
ContractExclusionBillingCodesEntityInformationUserDefinedFields 850
ContractExclusionRoles 283
ContractExclusionRolesById 284
ContractExclusionRolesCount 285
ContractExclusionRolesEntityInformation 851
ContractExclusionRolesEntityInformation_FieldsPicklistValuesFields 852
ContractExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 852
ContractExclusionRolesEntityInformationFields 853
ContractExclusionRolesEntityInformationUserDefinedFields 854
ContractExclusionSetExcludedRoles 287
ContractExclusionSetExcludedRolesById 288
ContractExclusionSetExcludedRolesCount 289
ContractExclusionSetExcludedRolesEntityInformation 854
ContractExclusionSetExcludedRolesEntityInformation_FieldsPicklistValuesFields 855
ContractExclusionSetExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 856
ContractExclusionSetExcludedRolesEntityInformationFields 857
ContractExclusionSetExcludedRolesEntityInformationUserDefinedFields 857
ContractExclusionSetExcludedWorkTypes 292
ContractExclusionSetExcludedWorkTypesById 292
ContractExclusionSetExcludedWorkTypesCount 294
ContractExclusionSetExcludedWorkTypesEntityInformation 858
ContractExclusionSetExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields 859
ContractExclusionSetExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields 860
ContractExclusionSetExcludedWorkTypesEntityInformationFields 860
ContractExclusionSetExcludedWorkTypesEntityInformationUserDefinedFields 861
contractExclusionSetID 287, 288, 290, 291, 292, 294, 295, 329, 330, 331
ContractExclusionSets 296
ContractExclusionSetsById 297
ContractExclusionSetsByParentIdExcludedRoles 290
ContractExclusionSetsByParentIdExcludedRolesEntityInformation 862
ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesFields 863
ContractExclusionSetsByParentIdExcludedRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 864
ContractExclusionSetsByParentIdExcludedRolesEntityInformationFields 865
ContractExclusionSetsByParentIdExcludedRolesEntityInformationUserDefinedFields 866
ContractExclusionSetsByParentIdExcludedRolesId 291
ContractExclusionSetsByParentIdExcludedWorkTypes 294
ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation 868
ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesFields 869
ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformation_FieldsPicklistValuesUserDefinedFields 870
ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationFields 871
ContractExclusionSetsByParentIdExcludedWorkTypesEntityInformationUserDefinedFields 872
ContractExclusionSetsByParentIdExcludedWorkTypesId 295
ContractExclusionSetsCount 297
ContractExclusionSetsEntityInformation 873
ContractExclusionSetsEntityInformation_FieldsPicklistValuesFields 874
ContractExclusionSetsEntityInformation_FieldsPicklistValuesUserDefinedFields 875
ContractExclusionSetsEntityInformationFields 876
ContractExclusionSetsEntityInformationUserDefinedFields 876
contractHourlyRate 314, 315, 316, 318
contractID 58, 59, 65, 67, 139, 140, 142, 144, 194, 198, 202, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 338, 339, 341, 342, 343, 344, 345, 347, 348, 349, 350, 351, 352, 353, 355, 356, 1999, 2001, 2003, 2012, 2013, 2014, 2016, 2247, 2250, 2253, 2280, 2282

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ContractMilestones 298
ContractMilestonesById 299
ContractMilestonesCount 300
ContractMilestonesEntityInformation 877
ContractMilestonesEntityInformation_FieldsPicklistValuesFields 877
ContractMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields 878
ContractMilestonesEntityInformationFields 879
ContractMilestonesEntityInformationUserDefinedFields 880
contractName 329, 330, 331
ContractNoteAttachments 303
ContractNoteAttachmentsById 304
ContractNoteAttachmentsCount 306
ContractNoteAttachmentsEntityInformation 880
ContractNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 881
ContractNoteAttachmentsEntityInformationFields 882
contractNoteID 58, 59, 303, 304, 306, 308
ContractNotes 309
ContractNotesById 310
ContractNotesByParentIdAttachments 306
ContractNotesByParentIdAttachmentsId 308
ContractNotesCount 311
ContractNotesEntityInformation 882
ContractNotesEntityInformation_FieldsPicklistValuesFields 883
ContractNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 884
ContractNotesEntityInformationFields 885
ContractNotesEntityInformationUserDefinedFields 885
contractNumber 329, 330, 331
contractPeriodType 329, 330, 331
ContractRates 314
ContractRatesById 315
ContractRatesCount 316
ContractRatesEntityInformation 886
ContractRatesEntityInformation_FieldsPicklistValuesFields 886
ContractRatesEntityInformation_FieldsPicklistValuesUserDefinedFields 887
ContractRatesEntityInformationFields 888
ContractRatesEntityInformationUserDefinedFields 889
ContractRetainers 319
ContractRetainersById 320
ContractRetainersCount 321
ContractRetainersEntityInformation 889
ContractRetainersEntityInformation_FieldsPicklistValuesFields 890
ContractRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields 891
ContractRetainersEntityInformationFields 892
ContractRetainersEntityInformationUserDefinedFields 892
ContractRoleCosts 324
ContractRoleCostsById 325
ContractRoleCostsCount 326
ContractRoleCostsEntityInformation 893
ContractRoleCostsEntityInformation_FieldsPicklistValuesFields 893
ContractRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields 894
ContractRoleCostsEntityInformationFields 895
ContractRoleCostsEntityInformationUserDefinedFields 896
Contracts 329
Contracts_ItemsUserDefinedFields 330
ContractsById 331
ContractsByParentIdBillingRules 259
ContractsByParentIdBillingRulesEntityInformation 896
ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesFields 897
ContractsByParentIdBillingRulesEntityInformation_FieldsPicklistValuesUserDefinedFields 899
ContractsByParentIdBillingRulesEntityInformationFields 900
ContractsByParentIdBillingRulesEntityInformationUserDefinedFields 901
ContractsByParentIdBillingRulesId 261
ContractsByParentIdBlockHourFactors 264
ContractsByParentIdBlockHourFactorsEntityInformation 902
ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesFields 903
ContractsByParentIdBlockHourFactorsEntityInformation_FieldsPicklistValuesUserDefinedFields 904
ContractsByParentIdBlockHourFactorsEntityInformationFields 906
ContractsByParentIdBlockHourFactorsEntityInformationUserDefinedFields 907
ContractsByParentIdBlockHourFactorsId 265
ContractsByParentIdBlocks 269
ContractsByParentIdBlocksEntityInformation 908
ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesFields 909
ContractsByParentIdBlocksEntityInformation_FieldsPicklistValuesUserDefinedFields 910
ContractsByParentIdBlocksEntityInformationFields 911
ContractsByParentIdBlocksEntityInformationUserDefinedFields 912
ContractsByParentIdBlocksId 270

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ContractsByParentIdCharges 275
ContractsByParentIdChargesEntityInformation 913
ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesFields 914
ContractsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 916
ContractsByParentIdChargesEntityInformationFields 917
ContractsByParentIdChargesEntityInformationUserDefinedFields 918
ContractsByParentIdChargesId 277
ContractsByParentIdExclusionBillingCodes 281
ContractsByParentIdExclusionBillingCodesEntityInformation 919
ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesFields 920
ContractsByParentIdExclusionBillingCodesEntityInformation_FieldsPicklistValuesUserDefinedFields 921
ContractsByParentIdExclusionBillingCodesEntityInformationFields 923
ContractsByParentIdExclusionBillingCodesEntityInformationUserDefinedFields 924
ContractsByParentIdExclusionBillingCodesId 282
ContractsByParentIdExclusionRoles 285
ContractsByParentIdExclusionRolesEntityInformation 925
ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesFields 926
ContractsByParentIdExclusionRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 927
ContractsByParentIdExclusionRolesEntityInformationFields 928
ContractsByParentIdExclusionRolesEntityInformationUserDefinedFields 929
ContractsByParentIdExclusionRolesId 286
ContractsByParentIdMilestones 300
ContractsByParentIdMilestonesEntityInformation 930
ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesFields 931
ContractsByParentIdMilestonesEntityInformation_FieldsPicklistValuesUserDefinedFields 933
ContractsByParentIdMilestonesEntityInformationFields 934
ContractsByParentIdMilestonesEntityInformationUserDefinedFields 935
ContractsByParentIdMilestonesId 302
ContractsByParentIdNotes 312
ContractsByParentIdNotesEntityInformation 936
ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 937
ContractsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 938
ContractsByParentIdNotesEntityInformationFields 940
ContractsByParentIdNotesEntityInformationUserDefinedFields 941
ContractsByParentIdNotesId 313
ContractsByParentIdRates 316
ContractsByParentIdRatesEntityInformation 942
ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesFields 943
ContractsByParentIdRatesEntityInformation_FieldsPicklistValuesUserDefinedFields 944
ContractsByParentIdRatesEntityInformationFields 945
ContractsByParentIdRatesEntityInformationUserDefinedFields 946
ContractsByParentIdRatesId 318
ContractsByParentIdRetainers 321
ContractsByParentIdRetainersEntityInformation 947
ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesFields 948
ContractsByParentIdRetainersEntityInformation_FieldsPicklistValuesUserDefinedFields 950
ContractsByParentIdRetainersEntityInformationFields 951
ContractsByParentIdRetainersEntityInformationUserDefinedFields 952
ContractsByParentIdRetainersId 323
ContractsByParentIdRoleCosts 326
ContractsByParentIdRoleCostsEntityInformation 953
ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesFields 954
ContractsByParentIdRoleCostsEntityInformation_FieldsPicklistValuesUserDefinedFields 955
ContractsByParentIdRoleCostsEntityInformationFields 956
ContractsByParentIdRoleCostsEntityInformationUserDefinedFields 957
ContractsByParentIdRoleCostsId 327
ContractsByParentIdServiceAdjustmentsEntityInformation 959
ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields 960
ContractsByParentIdServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 961
ContractsByParentIdServiceAdjustmentsEntityInformationFields 962
ContractsByParentIdServiceAdjustmentsEntityInformationUserDefinedFields 963
ContractsByParentIdServiceBundleAdjustmentsEntityInformation 964
ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields 965

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ContractsByParentIdServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 967
ContractsByParentIdServiceBundleAdjustmentsEntityInformationFields 968
ContractsByParentIdServiceBundleAdjustmentsEntityInformationUserDefinedFields 969
ContractsByParentIdServiceBundles 336
ContractsByParentIdServiceBundlesEntityInformation 970
ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesFields 971
ContractsByParentIdServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields 972
ContractsByParentIdServiceBundlesEntityInformationFields 974
ContractsByParentIdServiceBundlesEntityInformationUserDefinedFields 975
ContractsByParentIdServiceBundlesId 337
ContractsByParentIdServiceBundleUnits 341
ContractsByParentIdServiceBundleUnitsEntityInformation 976
ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields 977
ContractsByParentIdServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields 978
ContractsByParentIdServiceBundleUnitsEntityInformationFields 979
ContractsByParentIdServiceBundleUnitsEntityInformationUserDefinedFields 980
ContractsByParentIdServiceBundleUnitsId 342
ContractsByParentIdServices 345
ContractsByParentIdServicesEntityInformation 982
ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesFields 983
ContractsByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 984
ContractsByParentIdServicesEntityInformationFields 985
ContractsByParentIdServicesEntityInformationUserDefinedFields 986
ContractsByParentIdServicesId 347
ContractsByParentIdServiceUnits 350
ContractsByParentIdServiceUnitsEntityInformation 987
ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesFields 988
ContractsByParentIdServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields 989
ContractsByParentIdServiceUnitsEntityInformationFields 991
ContractsByParentIdServiceUnitsEntityInformationUserDefinedFields 992
ContractsByParentIdServiceUnitsId 351
ContractsByParentIdTicketPurchases 355
ContractsByParentIdTicketPurchasesEntityInformation 993
ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesFields 994
ContractsByParentIdTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields 995
ContractsByParentIdTicketPurchasesEntityInformationFields 996
ContractsByParentIdTicketPurchasesEntityInformationUserDefinedFields 997
ContractsByParentIdTicketPurchasesId 356
ContractsCount 333
ContractsEntityInformation 999
ContractsEntityInformation_FieldsPicklistValuesFields 999
ContractsEntityInformation_FieldsPicklistValuesUserDefinedFields 1000
ContractsEntityInformationFields 1001
ContractsEntityInformationUserDefinedFields 1001
contractServiceAdjustmentID 65, 67
ContractServiceAdjustmentsEntityInformation 1002
ContractServiceAdjustmentsEntityInformation_FieldsPicklistValuesFields 1003
ContractServiceAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1003
ContractServiceAdjustmentsEntityInformationFields 1004
ContractServiceAdjustmentsEntityInformationUserDefinedFields 1005
contractServiceBundleAdjustmentID 65, 67
ContractServiceBundleAdjustmentsEntityInformation 1006
ContractServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesFields 1006
ContractServiceBundleAdjustmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1007
ContractServiceBundleAdjustmentsEntityInformationFields 1008
ContractServiceBundleAdjustmentsEntityInformationUserDefinedFields 1008
contractServiceBundleID 65, 67, 70, 71, 194, 198, 202, 272, 273, 275, 277, 338, 339, 341, 342, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212, 2247, 2250, 2253, 2280, 2282
contractServiceBundlePeriodID 65, 67
ContractServiceBundles 333
ContractServiceBundlesById 334
ContractServiceBundlesCount 335
ContractServiceBundlesEntityInformation 1009
ContractServiceBundlesEntityInformation_FieldsPicklistValuesFields 1010
ContractServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields 1011

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ContractServiceBundlesEntityInformationFields 1011
ContractServiceBundlesEntityInformationUserDefinedFields 1012
ContractServiceBundleUnits 338
ContractServiceBundleUnitsById 339
ContractServiceBundleUnitsCount 340
ContractServiceBundleUnitsEntityInformation 1013
ContractServiceBundleUnitsEntityInformation_FieldsPicklistValuesFields 1013
ContractServiceBundleUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields 1014
ContractServiceBundleUnitsEntityInformationFields 1015
ContractServiceBundleUnitsEntityInformationUserDefinedFields 1016
contractServiceID 65, 67, 70, 71, 194, 198, 202, 272, 273, 275, 277, 348, 349, 350, 351, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212, 2247, 2250, 2253, 2280, 2282
contractServicePeriodID 65, 67
ContractServices 343
ContractServicesById 344
ContractServicesCount 345
ContractServicesEntityInformation 1016
ContractServicesEntityInformation_FieldsPicklistValuesFields 1017
ContractServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1018
ContractServicesEntityInformationFields 1018
ContractServicesEntityInformationUserDefinedFields 1019
ContractServiceUnits 348
ContractServiceUnitsById 349
ContractServiceUnitsCount 350
ContractServiceUnitsEntityInformation 1020
ContractServiceUnitsEntityInformation_FieldsPicklistValuesFields 1020
ContractServiceUnitsEntityInformation_FieldsPicklistValuesUserDefinedFields 1021
ContractServiceUnitsEntityInformationFields 1022
ContractServiceUnitsEntityInformationUserDefinedFields 1023
ContractTicketPurchases 352
ContractTicketPurchasesById 353
ContractTicketPurchasesCount 355
ContractTicketPurchasesEntityInformation 1023
ContractTicketPurchasesEntityInformation_FieldsPicklistValuesFields 1024
ContractTicketPurchasesEntityInformation_FieldsPicklistValuesUserDefinedFields 1025
ContractTicketPurchasesEntityInformationFields 1026
ContractTicketPurchasesEntityInformationUserDefinedFields 1026
contractType 329, 330, 331
Cost 338, 339, 341, 342, 348, 349, 350, 351, 1917, 1918, 1920
Cost Type 2005
costType 2005
Countries 358
CountriesById 358
CountriesCount 359
CountriesEntityInformation 1027
CountriesEntityInformation_FieldsPicklistValuesFields 1027
CountriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1028
CountriesEntityInformationFields 1029
CountriesEntityInformationUserDefinedFields 1030
Country 454
Country Code 358
Country ID 86, 88, 90, 105, 107, 109, 111, 112, 114, 116, 235, 237, 239, 456, 458
countryCode 358
countryID 86, 88, 90, 105, 107, 109, 111, 112, 114, 116, 235, 237, 239, 456, 458
Covered by Block Retainer Contract Label 484, 486
Covered by Recurring Service Fixed Price per Ticket Contract Label 484, 486
coveredByBlockRetainerContractLabel 484, 486
coveredByRecurringServiceFixedPricePerTicketContractLabel 484, 486
Create Charges as Billable 256, 257, 259, 261
createChargesAsBillable 256, 257, 259, 261
Created by 2033, 2034
Created by Contact ID 1994, 1995, 1997, 1998, 2150, 2151, 2152, 2154, 2227, 2228, 2229, 2231, 2247, 2250, 2253
Created by Person ID 194, 198, 202
Created by Resource ID 31, 32, 34, 35, 40, 41, 43, 44, 86, 88, 90, 361, 362, 364, 389, 390, 391, 393, 398, 399, 401, 402, 403, 404, 405, 407, 469, 471, 472, 475, 476, 488, 490, 491, 2290, 2291, 2293, 2294
createDate 70, 71, 86, 88, 90, 105, 107, 109, 194, 198, 202, 235, 237, 239, 272, 273, 275, 277, 298, 299, 300, 302, 1917, 1918, 1920, 1939, 1940, 1942, 1943, 1981, 1982, 1984, 1986, 2029, 2031, 2033, 2034, 2084, 2114, 2115, 2206, 2208, 2210, 2212, 2247, 2250, 2253, 2295, 2296, 2298, 2299, 2300, 2301

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

createDateTime 20, 21, 40, 41, 43, 44, 123, 124, 126, 127, 139, 140, 142, 144, 175, 176, 177, 178, 185, 186, 187, 189, 309, 310, 312, 313, 403, 404, 405, 407, 450, 452, 469, 471, 472, 475, 476, 482, 483, 1957, 1958, 1959, 1960, 1994, 1995, 1997, 1998, 1999, 2001, 2003, 2017, 2018, 2090, 2091, 2136, 2137, 2150, 2151, 2152, 2154, 2159, 2161, 2163, 2165, 2167, 2169, 2227, 2228, 2229, 2231, 2280, 2282, 2290, 2291, 2293, 2294, 2302, 2303
createdBy 2033, 2034
createdByContactID 1994, 1995, 1997, 1998, 2150, 2151, 2152, 2154, 2227, 2228, 2229, 2231, 2247, 2250, 2253
createdByPersonID 194, 198, 202
createdByResourceID 31, 32, 34, 35, 40, 41, 43, 44, 86, 88, 90, 361, 362, 364, 389, 390, 391, 393, 398, 399, 401, 402, 403, 404, 405, 407, 469, 471, 472, 475, 476, 488, 490, 491, 2290, 2291, 2293, 2294
createdDateTime 31, 32, 34, 35, 389, 390, 391, 393, 398, 399, 401, 402, 488, 490, 491
Creator Resource ID 20, 21, 70, 71, 139, 140, 142, 144, 185, 186, 187, 189, 272, 273, 275, 277, 298, 299, 300, 302, 309, 310, 312, 313, 482, 483, 1917, 1918, 1920, 1939, 1940, 1942, 1943, 1957, 1958, 1959, 1960, 1981, 1982, 1984, 1986, 1994, 1995, 1997, 1998, 1999, 2001, 2003, 2017, 2018, 2029, 2031, 2084, 2090, 2091, 2114, 2115, 2150, 2151, 2152, 2154, 2159, 2161, 2163, 2165, 2167, 2169, 2206, 2208, 2210, 2212, 2227, 2228, 2229, 2231, 2247, 2250, 2253
Creator Type 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2159, 2161, 2163, 2165, 2167, 2169, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2247, 2250, 2253, 2284, 2285, 2287, 2288
Creator User ID 2280, 2282
creatorResourceID 20, 21, 70, 71, 139, 140, 142, 144, 185, 186, 187, 189, 272, 273, 275, 277, 298, 299, 300, 302, 309, 310, 312, 313, 482, 483, 1917, 1918, 1920, 1939, 1940, 1942, 1943, 1957, 1958, 1959, 1960, 1981, 1982, 1984, 1986, 1994, 1995, 1997, 1998, 1999, 2001, 2003, 2017, 2018, 2029, 2031, 2084, 2090, 2091, 2114, 2115, 2150, 2151, 2152, 2154, 2159, 2161, 2163, 2165, 2167, 2169, 2206, 2208, 2210, 2212, 2227, 2228, 2229, 2231, 2247, 2250, 2253
creatorType 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2159, 2161, 2163, 2165, 2167, 2169, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2247, 2250, 2253, 2284, 2285, 2287, 2288
creatorUserID 2280, 2282
Credit Amount 2243, 2244, 2245, 2246
Credit Details 2243, 2244, 2245, 2246
creditAmount 2243, 2244, 2245, 2246
creditDetails 2243, 2244, 2245, 2246
CRM to Project UDF ID 2295, 2296
crmToProjectUdfId 2295, 2296
Currencies 359
CurrenciesById 360
CurrenciesCount 361
CurrenciesEntityInformation 1030
CurrenciesEntityInformation_FieldsPicklistValuesFields 1031
CurrenciesEntityInformation_FieldsPicklistValuesUserDefinedFields 1032
CurrenciesEntityInformationFields 1033
CurrenciesEntityInformationUserDefinedFields 1033
Currency ID 86, 88, 90, 1944, 1945, 1946, 1948, 1950, 1952, 1953, 1954, 1955
Currency Negative Format 359, 360, 484, 486, 2033, 2034
Currency Positive Format 359, 360, 484, 486, 2033, 2034
currencyID 86, 88, 90, 1944, 1945, 1946, 1948, 1950, 1952, 1953, 1954, 1955
currencyNegativeFormat 359, 360, 484, 486, 2033, 2034
currencyPositiveFormat 359, 360, 484, 486, 2033, 2034
Current Service Thermometer Rating 2247, 2250, 2253
Current Time Frame Request Count 2180
currentInventoryLocationID 471, 472, 475, 476
currentServiceThermometerRating 2247, 2250, 2253
currentTimeframeRequestCount 2180

- D -

Daily Cost 194, 198, 202
Daily Pro-rated Cost 256, 257, 259, 261
Daily Pro-rated Price 256, 257, 259, 261
dailyCost 194, 198, 202
dailyProratedCost 256, 257, 259, 261

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

dailyProratedPrice 256, 257, 259, 261
Data 22, 23, 25, 27, 97, 98, 100, 102, 117, 118,
120, 122, 160, 162, 163, 165, 175, 176, 177, 178, 179,
180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374,
422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924,
1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989,
1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069,
2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145,
2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222,
2224, 2225, 2284, 2285, 2287, 2288

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Data Type	495, 497, 499, 500, 502, 504, 506, 507, 508, 510, 511, 513, 515, 517, 518, 520, 522, 524, 525, 527, 529, 531, 533, 534, 536, 538, 540, 541, 543, 545, 547, 548, 550, 552, 554, 556, 559, 561, 563, 565, 566, 568, 570, 572, 573, 575, 577, 580, 583, 586, 589, 591, 594, 597, 600, 603, 606, 608, 611, 614, 617, 618, 620, 622, 624, 626, 627, 629, 631, 633, 635, 636, 638, 640, 642, 643, 645, 647, 649, 650, 652, 654, 656, 659, 662, 664, 668, 670, 673, 675, 676, 678, 680, 681, 682, 684, 686, 687, 690, 692, 694, 695, 697, 699, 701, 702, 703, 705, 706, 708, 710, 712, 715, 717, 721, 723, 726, 729, 732, 733, 736, 738, 740, 741, 743, 745, 747, 749, 751, 752, 755, 756, 759, 762, 765, 767, 770, 772, 774, 775, 777, 779, 781, 782, 785, 787, 790, 791, 794, 796, 799, 801, 803, 804, 806, 808, 810, 813, 816, 818, 822, 824, 827, 828, 830, 832, 834, 836, 837, 839, 841, 843, 845, 846, 848, 850, 852, 853, 855, 857, 859, 860, 863, 865, 869, 871, 874, 876, 877, 879, 881, 882, 883, 885, 886, 888, 890, 892, 893, 895, 897, 900, 903, 906, 909, 911, 914, 917, 920, 923, 926, 928, 931, 934, 937, 940, 943, 945, 948, 951, 954, 956, 960, 962, 965, 968, 971, 974, 977, 979, 983, 985, 988, 991, 994, 996, 999, 1001, 1003, 1004, 1006, 1008, 1010, 1011, 1013, 1015, 1017, 1018, 1020, 1022, 1024, 1026, 1027, 1029, 1031, 1033, 1034, 1036, 1038, 1040, 1042, 1043, 1045, 1047, 1049, 1051, 1053, 1056, 1058, 1060, 1062, 1063, 1065, 1067, 1069, 1071, 1072, 1074, 1076, 1078, 1079, 1082, 1084, 1087, 1090, 1093, 1096, 1099, 1101, 1105, 1106, 1109, 1112, 1115, 1117, 1121, 1123, 1126, 1129, 1132, 1135, 1137, 1139, 1141, 1143, 1144, 1146, 1148, 1150, 1152, 1153, 1155, 1157, 1159, 1161, 1162, 1164, 1165, 1166, 1168, 1170, 1173, 1175, 1177, 1179, 1182, 1184, 1186, 1188, 1190, 1191, 1193, 1195, 1197, 1199, 1200, 1203, 1205, 1208, 1210, 1211, 1213, 1215, 1217, 1219, 1221, 1225, 1227, 1230, 1233, 1236, 1239, 1242, 1243, 1245, 1247, 1249, 1250, 1252, 1254, 1256, 1257, 1259, 1261, 1263, 1264, 1266, 1268, 1270, 1271, 1274, 1276, 1279, 1280, 1283, 1286, 1289, 1292, 1295, 1298, 1301, 1302, 1305, 1307, 1309, 1310, 1313, 1315, 1316, 1318, 1320, 1323, 1326, 1327, 1329, 1330, 1331, 1333, 1335, 1336, 1339, 1340, 1343, 1344, 1346, 1348, 1350, 1351, 1353, 1355, 1357, 1358, 1360, 1362, 1364, 1365, 1367, 1369, 1371, 1372, 1374, 1376, 1378, 1379, 1381, 1383, 1385, 1388, 1391, 1393, 1396, 1399, 1402, 1403, 1405, 1407, 1409, 1410, 1412, 1413, 1414, 1416, 1417, 1418, 1419, 1421, 1423, 1426, 1429, 1431, 1435, 1437, 1440, 1443, 1445, 1447, 1449, 1451, 1452, 1454, 1456, 1459, 1462, 1463, 1466, 1468, 1471, 1473, 1474, 1476, 1478, 1480, 1482, 1484, 1487, 1489, 1491, 1492, 1494, 1495, 1496, 1498, 1499, 1501, 1503, 1505, 1507, 1509, 1513, 1515, 1518, 1521, 1524, 1526, 1530, 1532, 1535, 1538, 1540, 1542, 1544, 1546, 1547, 1549, 1551, 1553, 1554, 1555, 1556, 1558, 1560, 1563, 1566, 1567, 1569, 1571, 1573, 1576, 1579, 1581, 1584, 1586, 1587, 1589, 1591, 1594, 1597, 1598, 1600, 1602, 1604, 1607, 1610, 1611, 1613, 1615, 1617, 1620, 1622, 1624, 1626, 1627, 1629, 1631, 1633, 1634, 1637, 1639, 1642, 1644, 1645, 1647, 1649, 1651, 1652, 1654, 1656, 1658, 1660, 1662, 1665, 1667, 1669, 1671, 1673, 1674, 1676, 1678, 1680, 1682, 1685, 1688, 1691, 1694,	Database Driver	1

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

dataType 495, 497, 499, 500, 502, 504, 506, 507, 508, 510, 511, 513, 515, 517, 518, 520, 522, 524, 525, 527, 529, 531, 533, 534, 536, 538, 540, 541, 543, 545, 547, 548, 550, 552, 554, 556, 559, 561, 563, 565, 566, 568, 570, 572, 573, 575, 577, 580, 583, 586, 589, 591, 594, 597, 600, 603, 606, 608, 611, 614, 617, 618, 620, 622, 624, 626, 627, 629, 631, 633, 635, 636, 638, 640, 642, 643, 645, 647, 649, 650, 652, 654, 656, 659, 662, 664, 668, 670, 673, 675, 676, 678, 680, 681, 682, 684, 686, 687, 690, 692, 694, 695, 697, 699, 701, 702, 703, 705, 706, 708, 710, 712, 715, 717, 721, 723, 726, 729, 732, 733, 736, 738, 740, 741, 743, 745, 747, 749, 751, 752, 755, 756, 759, 762, 765, 767, 770, 772, 774, 775, 777, 779, 781, 782, 785, 787, 790, 791, 794, 796, 799, 801, 803, 804, 806, 808, 810, 813, 816, 818, 822, 824, 827, 828, 830, 832, 834, 836, 837, 839, 841, 843, 845, 846, 848, 850, 852, 853, 855, 857, 859, 860, 863, 865, 869, 871, 874, 876, 877, 879, 881, 882, 883, 885, 886, 888, 890, 892, 893, 895, 897, 900, 903, 906, 909, 911, 914, 917, 920, 923, 926, 928, 931, 934, 937, 940, 943, 945, 948, 951, 954, 956, 960, 962, 965, 968, 971, 974, 977, 979, 983, 985, 988, 991, 994, 996, 999, 1001, 1003, 1004, 1006, 1008, 1010, 1011, 1013, 1015, 1017, 1018, 1020, 1022, 1024, 1026, 1027, 1029, 1031, 1033, 1034, 1036, 1038, 1040, 1042, 1043, 1045, 1047, 1049, 1051, 1053, 1056, 1058, 1060, 1062, 1063, 1065, 1067, 1069, 1071, 1072, 1074, 1076, 1078, 1079, 1082, 1084, 1087, 1090, 1093, 1096, 1099, 1101, 1105, 1106, 1109, 1112, 1115, 1117, 1121, 1123, 1126, 1129, 1132, 1135, 1137, 1139, 1141, 1143, 1144, 1146, 1148, 1150, 1152, 1153, 1155, 1157, 1159, 1161, 1162, 1164, 1165, 1166, 1168, 1170, 1173, 1175, 1177, 1179, 1182, 1184, 1186, 1188, 1190, 1191, 1193, 1195, 1197, 1199, 1200, 1203, 1205, 1208, 1210, 1211, 1213, 1215, 1217, 1219, 1221, 1225, 1227, 1230, 1233, 1236, 1239, 1242, 1243, 1245, 1247, 1249, 1250, 1252, 1254, 1256, 1257, 1259, 1261, 1263, 1264, 1266, 1268, 1270, 1271, 1274, 1276, 1279, 1280, 1283, 1286, 1289, 1292, 1295, 1298, 1301, 1302, 1305, 1307, 1309, 1310, 1313, 1315, 1316, 1318, 1320, 1323, 1326, 1327, 1329, 1330, 1331, 1333, 1335, 1336, 1339, 1340, 1343, 1344, 1346, 1348, 1350, 1351, 1353, 1355, 1357, 1358, 1360, 1362, 1364, 1365, 1367, 1369, 1371, 1372, 1374, 1376, 1378, 1379, 1381, 1383, 1385, 1388, 1391, 1393, 1396, 1399, 1402, 1403, 1405, 1407, 1409, 1410, 1412, 1413, 1414, 1416, 1417, 1418, 1419, 1421, 1423, 1426, 1429, 1431, 1435, 1437, 1440, 1443, 1445, 1447, 1449, 1451, 1452, 1454, 1456, 1459, 1462, 1463, 1466, 1468, 1471, 1473, 1474, 1476, 1478, 1480, 1482, 1484, 1487, 1489, 1491, 1492, 1494, 1495, 1496, 1498, 1499, 1501, 1503, 1505, 1507, 1509, 1513, 1515, 1518, 1521, 1524, 1526, 1530, 1532, 1535, 1538, 1540, 1542, 1544, 1546, 1547, 1549, 1551, 1553, 1554, 1555, 1556, 1558, 1560, 1563, 1566, 1567, 1569, 1571, 1573, 1576, 1579, 1581, 1584, 1586, 1587, 1589, 1591, 1594, 1597, 1598, 1600, 1602, 1604, 1607, 1610, 1611, 1613, 1615, 1617, 1620, 1622, 1624, 1626, 1627, 1629, 1631, 1633, 1634, 1637, 1639, 1642, 1644, 1645, 1647, 1649, 1651, 1652, 1654, 1656, 1658, 1660, 1662, 1665, 1667, 1669, 1671, 1673, 1674, 1676, 1678, 1680, 1682, 1685, 1688, 1691, 1694,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Date 2219, 2220
Date Due 298, 299, 300, 302
Date Format 82, 83, 456, 458, 484, 486, 2033, 2034, 2054, 2055
Date Worked 2280, 2282
DATE_ENDED 1912
DATE_STARTED 1912
dateDue 298, 299, 300, 302
dateFormat 82, 83, 456, 458, 484, 486, 2033, 2034, 2054, 2055
datePurchased 70, 71, 267, 269, 270, 272, 273, 275, 277, 319, 320, 321, 323, 352, 353, 355, 356, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
dateWorked 2280, 2282
dattoAvailableKilobytes 194, 198, 202
dattoDeviceMemoryMegabytes 194, 198, 202
dattoDrivesErrors 194, 198, 202
dattoHostname 194, 198, 202
dattoInternalIP 194, 198, 202
dattoKernelVersionID 194, 198, 202
dattoLastCheckInDateTime 194, 198, 202
dattoNICSpeedKilobitsPerSecond 194, 198, 202
dattoNumberOfAgents 194, 198, 202
dattoNumberOfDrives 194, 198, 202
dattoNumberOfVolumes 194, 198, 202
dattoOffsiteUsedBytes 194, 198, 202
dattoOSVersionID 194, 198, 202
dattoPercentageUsed 194, 198, 202
dattoProtectedKilobytes 194, 198, 202
dattoRemoteIP 194, 198, 202
dattoSerialNumber 194, 198, 202
dattoUptimeSeconds 194, 198, 202
dattoUsedKilobytes 194, 198, 202
dattoZFSVersionID 194, 198, 202
Deactivation URL 154, 218, 219, 250, 2241, 2274
deactivationUrl 154, 218, 219, 250, 2241, 2274
Defaul linstalled Product Category ID 1962, 1963, 1964
Default Service Desk Role ID 2054, 2055

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Default Value 496, 497, 500, 501, 503, 505, 509, 510, 512, 514, 516, 517, 519, 521, 523, 524, 526, 528, 530, 531, 533, 535, 537, 538, 540, 542, 544, 545, 547, 549, 551, 552, 555, 558, 560, 562, 564, 565, 567, 569, 571, 572, 574, 576, 579, 581, 584, 587, 590, 592, 596, 598, 601, 604, 607, 609, 613, 615, 617, 619, 621, 622, 626, 628, 630, 631, 635, 637, 639, 640, 642, 644, 646, 647, 649, 651, 653, 654, 657, 660, 663, 665, 669, 671, 674, 675, 677, 679, 683, 684, 688, 691, 692, 695, 696, 698, 700, 704, 705, 707, 709, 713, 716, 719, 722, 724, 728, 730, 734, 737, 738, 741, 742, 744, 746, 748, 749, 751, 753, 757, 760, 763, 766, 768, 771, 772, 774, 776, 778, 779, 781, 783, 786, 788, 791, 792, 795, 797, 800, 801, 803, 805, 807, 808, 811, 814, 817, 819, 823, 825, 828, 829, 831, 833, 835, 836, 838, 840, 842, 843, 845, 847, 849, 850, 852, 854, 856, 857, 860, 861, 864, 866, 870, 872, 875, 876, 878, 880, 884, 885, 887, 889, 891, 892, 894, 896, 899, 901, 904, 907, 910, 912, 916, 918, 921, 924, 927, 929, 933, 935, 938, 941, 944, 946, 950, 952, 955, 957, 961, 963, 967, 969, 972, 975, 978, 980, 984, 986, 989, 992, 995, 997, 1000, 1001, 1003, 1005, 1007, 1008, 1011, 1012, 1014, 1016, 1018, 1019, 1021, 1023, 1025, 1026, 1028, 1030, 1032, 1033, 1035, 1037, 1039, 1040, 1042, 1044, 1046, 1047, 1052, 1055, 1057, 1059, 1061, 1062, 1064, 1066, 1068, 1069, 1071, 1073, 1075, 1076, 1078, 1080, 1083, 1085, 1089, 1091, 1094, 1097, 1100, 1102, 1107, 1110, 1113, 1116, 1118, 1122, 1124, 1128, 1130, 1133, 1136, 1138, 1140, 1142, 1143, 1145, 1147, 1149, 1150, 1152, 1154, 1156, 1157, 1161, 1163, 1167, 1168, 1171, 1174, 1176, 1177, 1180, 1183, 1185, 1187, 1189, 1190, 1192, 1194, 1196, 1197, 1199, 1201, 1204, 1206, 1209, 1210, 1212, 1214, 1216, 1217, 1220, 1223, 1226, 1228, 1232, 1234, 1237, 1240, 1242, 1244, 1246, 1247, 1249, 1251, 1253, 1254, 1256, 1258, 1260, 1261, 1263, 1265, 1267, 1268, 1272, 1277, 1281, 1285, 1287, 1290, 1293, 1296, 1299, 1303, 1306, 1307, 1311, 1314, 1315, 1317, 1319, 1322, 1324, 1326, 1328, 1332, 1333, 1335, 1337, 1341, 1343, 1345, 1347, 1348, 1350, 1352, 1354, 1355, 1357, 1359, 1361, 1362, 1364, 1366, 1368, 1369, 1371, 1373, 1375, 1376, 1378, 1380, 1382, 1383, 1386, 1389, 1392, 1394, 1398, 1400, 1402, 1404, 1406, 1407, 1409, 1411, 1415, 1416, 1420, 1422, 1425, 1427, 1430, 1432, 1436, 1438, 1441, 1444, 1446, 1448, 1450, 1451, 1453, 1455, 1458, 1460, 1463, 1464, 1467, 1469, 1472, 1473, 1475, 1477, 1479, 1480, 1483, 1485, 1488, 1489, 1491, 1493, 1497, 1498, 1500, 1502, 1504, 1505, 1508, 1510, 1514, 1516, 1519, 1522, 1525, 1527, 1531, 1533, 1536, 1539, 1541, 1543, 1545, 1546, 1548, 1550, 1552, 1553, 1557, 1559, 1562, 1564, 1566, 1568, 1570, 1571, 1574, 1577, 1580, 1582, 1585, 1586, 1588, 1590, 1593, 1595, 1598, 1599, 1601, 1603, 1605, 1608, 1610, 1612, 1614, 1615, 1618, 1621, 1623, 1624, 1627, 1628, 1630, 1631, 1634, 1635, 1638, 1640, 1643, 1644, 1646, 1648, 1650, 1651, 1653, 1655, 1657, 1658, 1661, 1663, 1666, 1667, 1673, 1675, 1677, 1678, 1681, 1683, 1687, 1689, 1692, 1695, 1697, 1699, 1701, 1702, 1704, 1706, 1708, 1709, 1711, 1713, 1715, 1716, 1718, 1720, 1725, 1727, 1730, 1731, 1733, 1735, 1737, 1738, 1740, 1742, 1744, 1745, 1747, 1749, 1751, 1752, 1756, 1758, 1760,

Default Vendor ID 1962, 1963, 1964

defaultInstalledProductCategoryID 1962, 1963, 1964

defaultServiceDeskRoleID 2054, 2055

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

defaultValue 496, 497, 500, 501, 503, 505, 509, 510, 512, 514, 516, 517, 519, 521, 523, 524, 526, 528, 530, 531, 533, 535, 537, 538, 540, 542, 544, 545, 547, 549, 551, 552, 555, 558, 560, 562, 564, 565, 567, 569, 571, 572, 574, 576, 579, 581, 584, 587, 590, 592, 596, 598, 601, 604, 607, 609, 613, 615, 617, 619, 621, 622, 626, 628, 630, 631, 635, 637, 639, 640, 642, 644, 646, 647, 649, 651, 653, 654, 657, 660, 663, 665, 669, 671, 674, 675, 677, 679, 683, 684, 688, 691, 692, 695, 696, 698, 700, 704, 705, 707, 709, 713, 716, 719, 722, 724, 728, 730, 734, 737, 738, 741, 742, 744, 746, 748, 749, 751, 753, 757, 760, 763, 766, 768, 771, 772, 774, 776, 778, 779, 781, 783, 786, 788, 791, 792, 795, 797, 800, 801, 803, 805, 807, 808, 811, 814, 817, 819, 823, 825, 828, 829, 831, 833, 835, 836, 838, 840, 842, 843, 845, 847, 849, 850, 852, 854, 856, 857, 860, 861, 864, 866, 870, 872, 875, 876, 878, 880, 884, 885, 887, 889, 891, 892, 894, 896, 899, 901, 904, 907, 910, 912, 916, 918, 921, 924, 927, 929, 933, 935, 938, 941, 944, 946, 950, 952, 955, 957, 961, 963, 967, 969, 972, 975, 978, 980, 984, 986, 989, 992, 995, 997, 1000, 1001, 1003, 1005, 1007, 1008, 1011, 1012, 1014, 1016, 1018, 1019, 1021, 1023, 1025, 1026, 1028, 1030, 1032, 1033, 1035, 1037, 1039, 1040, 1042, 1044, 1046, 1047, 1052, 1055, 1057, 1059, 1061, 1062, 1064, 1066, 1068, 1069, 1071, 1073, 1075, 1076, 1078, 1080, 1083, 1085, 1089, 1091, 1094, 1097, 1100, 1102, 1107, 1110, 1113, 1116, 1118, 1122, 1124, 1128, 1130, 1133, 1136, 1138, 1140, 1142, 1143, 1145, 1147, 1149, 1150, 1152, 1154, 1156, 1157, 1161, 1163, 1167, 1168, 1171, 1174, 1176, 1177, 1180, 1183, 1185, 1187, 1189, 1190, 1192, 1194, 1196, 1197, 1199, 1201, 1204, 1206, 1209, 1210, 1212, 1214, 1216, 1217, 1220, 1223, 1226, 1228, 1232, 1234, 1237, 1240, 1242, 1244, 1246, 1247, 1249, 1251, 1253, 1254, 1256, 1258, 1260, 1261, 1263, 1265, 1267, 1268, 1272, 1277, 1281, 1285, 1287, 1290, 1293, 1296, 1299, 1303, 1306, 1307, 1311, 1314, 1315, 1317, 1319, 1322, 1324, 1326, 1328, 1332, 1333, 1335, 1337, 1341, 1343, 1345, 1347, 1348, 1350, 1352, 1354, 1355, 1357, 1359, 1361, 1362, 1364, 1366, 1368, 1369, 1371, 1373, 1375, 1376, 1378, 1380, 1382, 1383, 1386, 1389, 1392, 1394, 1398, 1400, 1402, 1404, 1406, 1407, 1409, 1411, 1415, 1416, 1420, 1422, 1425, 1427, 1430, 1432, 1436, 1438, 1441, 1444, 1446, 1448, 1450, 1451, 1453, 1455, 1458, 1460, 1463, 1464, 1467, 1469, 1472, 1473, 1475, 1477, 1479, 1480, 1483, 1485, 1488, 1489, 1491, 1493, 1497, 1498, 1500, 1502, 1504, 1505, 1508, 1510, 1514, 1516, 1519, 1522, 1525, 1527, 1531, 1533, 1536, 1539, 1541, 1543, 1545, 1546, 1548, 1550, 1552, 1553, 1557, 1559, 1562, 1564, 1566, 1568, 1570, 1571, 1574, 1577, 1580, 1582, 1585, 1586, 1588, 1590, 1593, 1595, 1598, 1599, 1601, 1603, 1605, 1608, 1610, 1612, 1614, 1615, 1618, 1621, 1623, 1624, 1627, 1628, 1630, 1631, 1634, 1635, 1638, 1640, 1643, 1644, 1646, 1648, 1650, 1651, 1653, 1655, 1657, 1658, 1661, 1663, 1666, 1667, 1673, 1675, 1677, 1678, 1681, 1683, 1687, 1689, 1692, 1695, 1697, 1699, 1701, 1702, 1704, 1706, 1708, 1709, 1711, 1713, 1715, 1716, 1718, 1720, 1725, 1727, 1730, 1731, 1733, 1735, 1737, 1738, 1740, 1742, 1744, 1745, 1747, 1749, 1751, 1752, 1756, 1758, 1760,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

defaultVendorID 1962, 1963, 1964
Deleted by Resource ID 361, 362, 364, 366
Deleted Date/Time 361, 362, 364, 366
deletedByResourceID 361, 362, 364, 366
deletedDateTime 361, 362, 364, 366
DeletedTaskActivityLogs 361
DeletedTaskActivityLogsById 362
DeletedTaskActivityLogsCount 363
DeletedTaskActivityLogsEntityInformation 1034
DeletedTaskActivityLogsEntityInformation_FieldsPicklistValuesFields 1034
DeletedTaskActivityLogsEntityInformation_FieldsPicklistValuesUserDefinedFields 1035
DeletedTaskActivityLogsEntityInformationFields 1036
DeletedTaskActivityLogsEntityInformationUserDefinedFields 1037
DeletedTicketActivityLogs 364
DeletedTicketActivityLogsById 364
DeletedTicketActivityLogsCount 365
DeletedTicketActivityLogsEntityInformation 1037
DeletedTicketActivityLogsEntityInformation_FieldsPicklistValuesFields 1038
DeletedTicketActivityLogsEntityInformation_FieldsPicklistValuesUserDefinedFields 1039
DeletedTicketActivityLogsEntityInformationFields 1040
DeletedTicketActivityLogsEntityInformationUserDefinedFields 1040
DeletedTicketLogs 366
DeletedTicketLogsById 366
DeletedTicketLogsCount 367
DeletedTicketLogsEntityInformation 1041
DeletedTicketLogsEntityInformation_FieldsPicklistValuesFields 1042
DeletedTicketLogsEntityInformation_FieldsPicklistValuesUserDefinedFields 1042
DeletedTicketLogsEntityInformationFields 1043
DeletedTicketLogsEntityInformationUserDefinedFields 1044
deliveredUnits 471, 472, 475, 476
Department 61, 62, 1999, 2001, 2003
Department ID 2041, 2042, 2044, 2045, 2050, 2051, 2052, 2053, 2159, 2161, 2163, 2165, 2167, 2169
Department Number 441, 442
departmentID 2041, 2042, 2044, 2045, 2050, 2051, 2052, 2053, 2159, 2161, 2163, 2165, 2167, 2169
departmentNumber 441, 442
Departments 367
DepartmentsById 368
DepartmentsCount 369
DepartmentsEntityInformation 1044
DepartmentsEntityInformation_FieldsPicklistValuesFields 1045
DepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1046
DepartmentsEntityInformationFields 1047
DepartmentsEntityInformationUserDefinedFields 1047
Destination 428, 429, 432, 433
Detail 2219, 2220
Determine Unit 256, 257, 259, 261
determineUnits 256, 257, 259, 261
Device Audit Anti-virus Status ID 194, 198, 202
Device Audit Architecture ID 194, 198, 202
Device Audit Backup Status ID 194, 198, 202
Device Audit Description 194, 198, 202
Device Audit Device Type ID 194, 198, 202
Device Audit Display Adaptor ID 194, 198, 202
Device Audit Domain ID 194, 198, 202
Device Audit External IP Address 194, 198, 202
Device Audit Hostname 194, 198, 202
Device Audit Last User 194, 198, 202
Device Audit MAC Address 194, 198, 202
Device Audit Manufacturer ID 194, 198, 202
Device Audit Memory Bytes 194, 198, 202
Device Audit Missing Patch Count 194, 198, 202
Device Audit Mobile Network Operator ID 194, 198, 202
Device Audit Mobile Number 194, 198, 202
Device Audit Model ID 194, 198, 202
Device Audit Motherboard ID 194, 198, 202
Device Audit Operating System 194, 198, 202
Device Audit Patch Status ID 194, 198, 202
Device Audit Processor ID 194, 198, 202
Device Audit Service Pack ID 194, 198, 202
Device Audit SNMP Contact 194, 198, 202
Device Audit SNMP Location 194, 198, 202
Device Audit SNMP Name 194, 198, 202
Device Audit Software Status ID 194, 198, 202
Device Audit Storage Bytes 194, 198, 202
Device ID 194, 198, 202
Device Memory Megabytes 194, 198, 202
Device Networking ID 194, 198, 202
Device UID 194, 198, 202
deviceNetworkingID 194, 198, 202
Devuce Audit IP-address 194, 198, 202
Discount Percentage 2020, 2022, 2024, 2026, 2084
Display Color 2134, 2135
Display Color RGB 103, 104, 170, 2195, 2196
Display Fixed Price Contract Labor 484, 486
Display Format 2295, 2296
Display Name 358, 2129
Display Recurring Service Contract Labor 484, 486

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Display Separate Line Item for each Tax 484, 486
Display Symbol 359, 360
Display Tax Category 484, 486
Display Tax Category Super Scripts 484, 486, 2033, 2034
Display Zero Amount Recurring Services and Bundles 484, 486
displayColor 2134, 2135
displayColorRGB 103, 104, 170, 2195, 2196
displayFixedPriceContractLabor 484, 486
displayFormat 2295, 2296
displayName 358, 2129
displayRecurringServiceContractLabor 484, 486
displaySeparateLineItemForEachTax 484, 486
displaySymbol 359, 360
displayTaxCategory 484, 486
displayTaxCategorySuperscripts 484, 486, 2033, 2034
displayZeroAmountRecurringServicesAndBundles 484, 486
DNS Type 175, 176, 177, 178
dnsType 175, 176, 177, 178
Document Category ID 398, 399, 401, 402
Document ID 58, 59, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419
DocumentAttachments 369
DocumentAttachmentsById 370
DocumentAttachmentsCount 372
DocumentAttachmentsEntityInformation 1048
DocumentAttachmentsEntityInformation_FieldsPicklistValuesFields 1049
DocumentAttachmentsEntityInformationFields 1049
DocumentCategories 375
DocumentCategoriesById 376
DocumentCategoriesByParentIdDocuments 401
DocumentCategoriesByParentIdDocumentsEntityInformation 1050
DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesFields 1051
DocumentCategoriesByParentIdDocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1052
DocumentCategoriesByParentIdDocumentsEntityInformationFields 1053
DocumentCategoriesByParentIdDocumentsEntityInformationUserDefinedFields 1055
DocumentCategoriesByParentIdDocumentsId 402
DocumentCategoriesCount 376
DocumentCategoriesEntityInformation 1056
DocumentCategoriesEntityInformation_FieldsPicklistValuesFields 1056
DocumentCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1057
DocumentCategoriesEntityInformationFields 1058
DocumentCategoriesEntityInformationUserDefinedFields 1059
documentCategoryID 398, 399, 401, 402
DocumentChecklistItems 377
DocumentChecklistItemsById 377
DocumentChecklistItemsCount 378
DocumentChecklistItemsEntityInformation 1059
DocumentChecklistItemsEntityInformation_FieldsPicklistValuesFields 1060
DocumentChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1061
DocumentChecklistItemsEntityInformationFields 1062
DocumentChecklistItemsEntityInformationUserDefinedFields 1062
DocumentChecklistLibrariesEntityInformation 1063
DocumentChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 1063
DocumentChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 1064
DocumentChecklistLibrariesEntityInformationFields 1065
DocumentChecklistLibrariesEntityInformationUserDefinedFields 1066
DocumentConfigurationItemAssociations 381
DocumentConfigurationItemAssociationsById 382
DocumentConfigurationItemAssociationsCount 383
DocumentConfigurationItemAssociationsEntityInformation 1066
DocumentConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields 1067
DocumentConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1068
DocumentConfigurationItemAssociationsEntityInformationFields 1069
DocumentConfigurationItemAssociationsEntityInformationUserDefinedFields 1069
DocumentConfigurationItemCategoryAssociations 386
DocumentConfigurationItemCategoryAssociationsById 386
DocumentConfigurationItemCategoryAssociationsCount 387
DocumentConfigurationItemCategoryAssociationsEntityInformation 1070
DocumentConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields 1071
DocumentConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1071

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

DocumentConfigurationItemCategoryAssociationsEntityInformationFields 1072
DocumentConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields 1073
documentID 58, 59, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419
DocumentNotes 389
DocumentNotesById 390
DocumentNotesCount 391
DocumentNotesEntityInformation 1074
DocumentNotesEntityInformation_FieldsPicklistValuesFields 1074
DocumentNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1075
DocumentNotesEntityInformationFields 1076
DocumentNotesEntityInformationUserDefinedFields 1076
DocumentPlainTextContent 394
DocumentPlainTextContentById 394
DocumentPlainTextContentCount 395
DocumentPlainTextContentEntityInformation 1077
DocumentPlainTextContentEntityInformation_FieldsPicklistValuesFields 1078
DocumentPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields 1078
DocumentPlainTextContentEntityInformationFields 1079
DocumentPlainTextContentEntityInformationUserDefinedFields 1080
Documents 398
DocumentsById 399
DocumentsByParentIdArticleAssociations 414
DocumentsByParentIdArticleAssociationsEntityInformation 1081
DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields 1082
DocumentsByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1083
DocumentsByParentIdArticleAssociationsEntityInformationFields 1084
DocumentsByParentIdArticleAssociationsEntityInformationUserDefinedFields 1085
DocumentsByParentIdArticleAssociationsId 415
DocumentsByParentIdAttachments 372
DocumentsByParentIdAttachmentsId 374
DocumentsByParentIdChecklistItems 379
DocumentsByParentIdChecklistItemsEntityInformation 1086
DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields 1087
DocumentsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1089
DocumentsByParentIdChecklistItemsEntityInformationFields 1090
DocumentsByParentIdChecklistItemsEntityInformationUserDefinedFields 1091
DocumentsByParentIdChecklistItemsId 380
DocumentsByParentIdChecklistLibrariesEntityInformation 1092
DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 1093
DocumentsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 1094
DocumentsByParentIdChecklistLibrariesEntityInformationFields 1096
DocumentsByParentIdChecklistLibrariesEntityInformationUserDefinedFields 1097
DocumentsByParentIdConfigurationItemAssociations 383
DocumentsByParentIdConfigurationItemAssociationsEntityInformation 1098
DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesFields 1099
DocumentsByParentIdConfigurationItemAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1100
DocumentsByParentIdConfigurationItemAssociationsEntityInformationFields 1101
DocumentsByParentIdConfigurationItemAssociationsEntityInformationUserDefinedFields 1102
DocumentsByParentIdConfigurationItemAssociationsId 384
DocumentsByParentIdConfigurationItemCategoryAssociations 388
DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation 1104
DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields 1105
DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationFields 1106
DocumentsByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields 1107
DocumentsByParentIdDocumentAssociations 418
DocumentsByParentIdDocumentAssociationsEntityInformation 1108
DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields 1109
DocumentsByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1110
DocumentsByParentIdDocumentAssociationsEntityInformationFields 1112
DocumentsByParentIdDocumentAssociationsEntityInformationUserDefinedFields 1113
DocumentsByParentIdDocumentAssociationsId 419
DocumentsByParentIdNotes 391

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

DocumentsByParentIdNotesEntityInformation 1114
DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1115
DocumentsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1116
DocumentsByParentIdNotesEntityInformationFields 1117
DocumentsByParentIdNotesEntityInformationUserDefinedFields 1118
DocumentsByParentIdNotesId 393
DocumentsByParentIdPlainTextContent 396
DocumentsByParentIdPlainTextContentEntityInformation 1120
DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields 1121
DocumentsByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields 1122
DocumentsByParentIdPlainTextContentEntityInformationFields 1123
DocumentsByParentIdPlainTextContentEntityInformationUserDefinedFields 1124
DocumentsByParentIdPlainTextContentId 397
DocumentsByParentIdTagAssociations 405
DocumentsByParentIdTagAssociationsEntityInformation 1125
DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields 1126
DocumentsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1128
DocumentsByParentIdTagAssociationsEntityInformationFields 1129
DocumentsByParentIdTagAssociationsEntityInformationUserDefinedFields 1130
DocumentsByParentIdTagAssociationsId 407
DocumentsByParentIdTicketAssociations 410
DocumentsByParentIdTicketAssociationsEntityInformation 1131
DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields 1132
DocumentsByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1133
DocumentsByParentIdTicketAssociationsEntityInformationFields 1135
DocumentsByParentIdTicketAssociationsEntityInformationUserDefinedFields 1136
DocumentsByParentIdTicketAssociationsId 411
DocumentsCount 400
DocumentsEntityInformation 1137
DocumentsEntityInformation_FieldsPicklistValuesFields 1137
DocumentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1138
DocumentsEntityInformationFields 1139
DocumentsEntityInformationUserDefinedFields 1140
DocumentTagAssociations 403
DocumentTagAssociationsById 404
DocumentTagAssociationsCount 405
DocumentTagAssociationsEntityInformation 1140
DocumentTagAssociationsEntityInformation_FieldsPicklistValuesFields 1141
DocumentTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1142
DocumentTagAssociationsEntityInformationFields 1143
DocumentTagAssociationsEntityInformationUserDefinedFields 1143
DocumentTicketAssociations 408
DocumentTicketAssociationsById 408
DocumentTicketAssociationsCount 409
DocumentTicketAssociationsEntityInformation 1144
DocumentTicketAssociationsEntityInformation_FieldsPicklistValuesFields 1144
DocumentTicketAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1145
DocumentTicketAssociationsEntityInformationFields 1146
DocumentTicketAssociationsEntityInformationUserDefinedFields 1147
DocumentToArticleAssociations 412
DocumentToArticleAssociationsById 413
DocumentToArticleAssociationsCount 414
DocumentToArticleAssociationsEntityInformation 1147
DocumentToArticleAssociationsEntityInformation_FieldsPicklistValuesFields 1148
DocumentToArticleAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1149
DocumentToArticleAssociationsEntityInformationFields 1150
DocumentToArticleAssociationsEntityInformationUserDefinedFields 1150
DocumentToDocumentAssociations 416
DocumentToDocumentAssociationsById 417
DocumentToDocumentAssociationsCount 418
DocumentToDocumentAssociationsEntityInformation 1151
DocumentToDocumentAssociationsEntityInformation_FieldsPicklistValuesFields 1152
DocumentToDocumentAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1152
DocumentToDocumentAssociationsEntityInformationFields 1153
DocumentToDocumentAssociationsEntityInformationUserDefinedFields 1154
Does not require Procurement 1962, 1963, 1964
doesNotRequireProcurement 1962, 1963, 1964
Domain 194, 198, 202
Domain Expiration Date/Time 194, 198, 202

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Domain Last Updated Date/Time 194, 198, 202
Domain Registrar ID 194, 198, 202
Domain Registration Date/Time 194, 198, 202
domainExpirationDateTime 194, 198, 202
domainLastUpdatedDateTime 194, 198, 202
domainRegistrarID 194, 198, 202
DomainRegistrars 421
DomainRegistrarsById 421
DomainRegistrarsCount 422
DomainRegistrarsEntityInformation 1155
DomainRegistrarsEntityInformation_FieldsPicklistValuesFields 1155
DomainRegistrarsEntityInformation_FieldsPicklistValuesUserDefinedFields 1156
DomainRegistrarsEntityInformationFields 1157
DomainRegistrarsEntityInformationUserDefinedFields 1157
domainRegistrationDateTime 194, 198, 202
download-error-400-bad-request-max-tries 2
download-error-400-bad-request-sleep-initial-ms 2
download-error-400-bad-request-sleep-max-ms 2
download-error-400-bad-request-sleep-multiplicator 2
download-error-408-request-timeout-max-tries 2
download-error-408-request-timeout-sleep-initial-ms 2
download-error-408-request-timeout-sleep-max-ms 2
download-error-408-request-timeout-sleep-multiplicator 2
download-error-422-bad-request-max-tries 2
download-error-422-bad-request-sleep-initial-ms 2
download-error-422-bad-request-sleep-max-ms 2
download-error-422-bad-request-sleep-multiplicator 2
download-error-429-too-many-requests-max-tries 2
download-error-429-too-many-requests-sleep-initial-ms 2
download-error-429-too-many-requests-sleep-max-ms 2
download-error-429-too-many-requests-sleep-multiplicator 2
download-error-500-internal-server-error-max-tries 2
download-error-500-internal-server-error-sleep-initial-ms 2
download-error-500-internal-server-error-sleep-max-ms 2
download-error-500-internal-server-error-sleep-multiplicator 2
download-error-502-server-unavailable-max-tries 2
download-error-502-server-unavailable-sleep-initial-ms 2
download-error-502-server-unavailable-sleep-max-ms 2
download-error-502-server-unavailable-sleep-multiplicator 2
download-error-503-server-unavailable-max-tries 2
download-error-503-server-unavailable-sleep-initial-ms 2
download-error-503-server-unavailable-sleep-max-ms 2
download-error-503-server-unavailable-sleep-multiplicator 2
download-error-504-gateway-timeout-max-tries 2
download-error-504-gateway-timeout-sleep-initial-ms 2
download-error-504-gateway-timeout-sleep-max-ms 2
download-error-504-gateway-timeout-sleep-multiplicator 2
download-error-590-network-connect-timeout-max-tries 2
download-error-590-network-connect-timeout-sleep-initial-ms 2
download-error-590-network-connect-timeout-sleep-max-ms 2
download-error-590-network-connect-timeout-sleep-multiplicator 2
download-error-599-network-connect-timeout-max-tries 2
download-error-599-network-connect-timeout-sleep-initial-ms 2
download-error-599-network-connect-timeout-sleep-max-ms 2
download-error-599-network-connect-timeout-sleep-multiplicator 2
download-error-argument-exception-max-tries 2
download-error-argument-exception-sleep-initial-ms 2
download-error-argument-exception-sleep-max-ms 2
download-error-argument-exception-sleep-multiplicator 2
download-error-internet-down-max-tries 2
download-error-internet-down-sleep-initial-ms 2
download-error-internet-down-sleep-max-ms 2
download-error-internet-down-sleep-multiplicator 2
download-error-io-exception-max-tries 2
download-error-io-exception-sleep-initial-ms 2
download-error-io-exception-sleep-max-ms 2
download-error-io-exception-sleep-multiplicator 2
download-error-json-exception-max-tries 2
download-error-json-exception-sleep-initial-ms 2
download-error-json-exception-sleep-max-ms 2
download-error-json-exception-sleep-multiplicator 2
download-error-name-resolution-failure-max-tries 2
download-error-name-resolution-failure-sleep-initial-ms 2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

download-error-name-resolution-failure-sleep-max-ms 2
download-error-name-resolution-failure-sleep-multiplicator 2
download-error-other-exception-max-tries 2
download-error-other-exception-sleep-initial-ms 2
download-error-other-exception-sleep-max-ms 2
download-error-other-exception-sleep-multiplicator 2
download-error-socket-exception-max-tries 2
download-error-socket-exception-sleep-initial-ms 2
download-error-socket-exception-sleep-max-ms 2
download-error-socket-exception-sleep-multiplicator 2
download-error-web-exception-max-tries 2
download-error-web-exception-sleep-initial-ms 2
download-error-web-exception-sleep-max-ms 2
download-error-web-exception-sleep-multiplicator 2
download-error-web-not-found-max-tries 2
download-error-web-not-found-sleep-initial-ms 2
download-error-web-not-found-sleep-max-ms 2
download-error-web-not-found-sleep-multiplicator 2
download-error-web-not-implemented-max-tries 2
download-error-web-not-implemented-sleep-initial-ms 2
download-error-web-not-implemented-sleep-max-ms 2
download-error-web-not-implemented-sleep-multiplicator 2
download-error-web-timeout-max-tries 2
download-error-web-timeout-sleep-initial-ms 2
download-error-web-timeout-sleep-max-ms 2
download-error-web-timeout-sleep-multiplicator 2
download-error-web-unauthorized-max-tries 2
download-error-web-unauthorized-sleep-initial-ms 2
download-error-web-unauthorized-sleep-max-ms 2
download-error-web-unauthorized-sleep-multiplicator 2
Drives Errors 194, 198, 202
DRY_RUN 1912
Due Date 482, 483, 1939, 1940, 1942, 1943
Due Date/Time 2247, 2250, 2253
dueDate 482, 483, 1939, 1940, 1942, 1943
dueDateTime 2247, 2250, 2253
duplicate-row-mode 2
Duration 1999, 2001, 2003, 2090, 2091
Duration (ms) 1912
DURATION_MS 1912

- E -

Effective Date 167, 169, 225, 226, 227, 228, 2029, 2031, 2124, 2125
effectiveDate 167, 169, 225, 226, 227, 228, 2029, 2031, 2124, 2125
Email 2054, 2055
Email 2 2054, 2055
Email 3 2054, 2055
Email Address 105, 107, 109, 235, 237, 239
Email Address 2 105, 107, 109, 235, 237, 239
Email Address 3 105, 107, 109, 235, 237, 239
Email Type Code 2054, 2055
Email Type Code 2 2054, 2055
Email Type Code 3 2054, 2055
email2 2054, 2055
email3 2054, 2055
emailAddress 105, 107, 109, 235, 237, 239
emailAddress2 105, 107, 109, 235, 237, 239
emailAddress3 105, 107, 109, 235, 237, 239
emailTypeCode 2054, 2055
emailTypeCode2 2054, 2055
emailTypeCode3 2054, 2055
End Date 256, 257, 259, 261, 267, 269, 270, 319, 320, 321, 323, 329, 330, 331, 338, 339, 341, 342, 348, 349, 350, 351, 352, 353, 355, 356, 1912
End Date/Time 20, 21, 123, 124, 126, 127, 139, 140, 142, 144, 361, 362, 364, 1999, 2001, 2003, 2090, 2091, 2159, 2161, 2163, 2165, 2167, 2169, 2280, 2282
endDate 256, 257, 259, 261, 267, 269, 270, 319, 320, 321, 323, 329, 330, 331, 338, 339, 341, 342, 348, 349, 350, 351, 352, 353, 355, 356
endDateTime 20, 21, 123, 124, 126, 127, 139, 140, 142, 144, 361, 362, 364, 1999, 2001, 2003, 2090, 2091, 2159, 2161, 2163, 2165, 2167, 2169, 2280, 2282
Entertainment Location 428, 429, 432, 433
entertainmentLocation 428, 429, 432, 433
Entity Number 1914, 1915
Entity Title 1914, 1915
Entity Type 74, 75
EntityInformation 1911
entityNumber 1914, 1915
entityTitle 1914, 1915
entityType 74, 75
Error Codes 398, 399, 401, 402, 488, 490, 491
Error Message 2302, 2303
Error Message Code 1912
Error Message Text 1912
ERROR_MESSAGE_CODE 1912
ERROR_MESSAGE_TEXT 1912
errorCodes 398, 399, 401, 402, 488, 490, 491
errorMessage 2302, 2303
Estimated Arrival 2012, 2013, 2014, 2016

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Estimated Cost 329, 330, 331, 1981, 1982, 1984, 1986
Estimated Hours 329, 330, 331, 1939, 1940, 1942, 1943, 2159, 2161, 2163, 2165, 2167, 2169, 2197, 2198, 2199, 2200, 2247, 2250, 2253
Estimated Revenue 329, 330, 331
Estimated Sales Cost 1999, 2001, 2003
Estimated Time 1999, 2001, 2003
estimatedArrivalDate 2012, 2013, 2014, 2016
estimatedCost 329, 330, 331, 1981, 1982, 1984, 1986
estimatedHours 329, 330, 331, 1939, 1940, 1942, 1943, 2159, 2161, 2163, 2165, 2167, 2169, 2197, 2198, 2199, 2200, 2247, 2250, 2253
estimatedRevenue 329, 330, 331
estimatedSalesCost 1999, 2001, 2003
estimatedTime 1999, 2001, 2003
Exchange Rate 359, 360
exchangeRate 359, 360
Excluded Role ID 287, 288, 290, 291
Excluded Work Type ID 292, 294, 295
excludedRoleID 287, 288, 290, 291
excludedWorkTypeID 292, 294, 295
Exclusion Contract ID 329, 330, 331
exclusionContractID 329, 330, 331
Execution Method 256, 257, 259, 261
executionMethod 256, 257, 259, 261
Expense Category 428, 429, 432, 433
Expense Currency Expense Amount 428, 429, 432, 433
Expense Currency ID 428, 429, 432, 433
Expense Date 428, 429, 432, 433
Expense ID 2020, 2022, 2024, 2026
Expense Item ID 58, 59, 65, 67, 422, 423, 425, 427, 435, 436, 438, 440
Expense Report ID 58, 59, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440
expenseCategory 428, 429, 432, 433
expenseCurrencyExpenseAmount 428, 429, 432, 433
expenseCurrencyID 428, 429, 432, 433
expenseDate 428, 429, 432, 433
expenseID 2020, 2022, 2024, 2026
ExpenseItemAttachments 422
ExpenseItemAttachmentsById 423
ExpenseItemAttachmentsCount 425
ExpenseItemAttachmentsEntityInformation 1158
ExpenseItemAttachmentsEntityInformation_FieldsPicklistValuesFields 1159
ExpenseItemAttachmentsEntityInformationFields 1159
expenseItemID 58, 59, 65, 67, 422, 423, 425, 427, 435, 436, 438, 440
ExpenseItems 428
ExpenseItemsById 429
ExpenseItemsByParentIdAttachments 425
ExpenseItemsByParentIdAttachmentsId 427
ExpenseItemsCount 431
ExpenseItemsEntityInformation 1160
ExpenseItemsEntityInformation_FieldsPicklistValuesFields 1161
ExpenseItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1161
ExpenseItemsEntityInformationFields 1162
ExpenseItemsEntityInformationUserDefinedFields 1163
ExpenseReportAttachments 435
ExpenseReportAttachmentsById 436
ExpenseReportAttachmentsCount 438
ExpenseReportAttachmentsEntityInformation 1164
ExpenseReportAttachmentsEntityInformation_FieldsPicklistValuesFields 1164
ExpenseReportAttachmentsEntityInformationFields 1165
expenseReportID 58, 59, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440
ExpenseReports 441
ExpenseReportsById 442
ExpenseReportsByParentIdAttachments 438
ExpenseReportsByParentIdAttachmentsId 440
ExpenseReportsCount 443
ExpenseReportsEntityInformation 1166
ExpenseReportsEntityInformation_FieldsPicklistValuesFields 1166
ExpenseReportsEntityInformation_FieldsPicklistValuesUserDefinedFields 1167
ExpenseReportsEntityInformationFields 1168
ExpenseReportsEntityInformationUserDefinedFields 1168
ExpensesByParentIdItems 432
ExpensesByParentIdItemsEntityInformation 1169
ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesFields 1170
ExpensesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1171
ExpensesByParentIdItemsEntityInformationFields 1173
ExpensesByParentIdItemsEntityInformationUserDefinedFields 1174
ExpensesByParentIdItemsId 433
Expiration Date 167, 169, 225, 226, 227, 228, 2029, 2031, 2124, 2125
expirationDate 167, 169, 225, 226, 227, 228, 2029, 2031, 2124, 2125
extApprovalContactResponse 2029, 2031
extApprovalResponseDate 2029, 2031

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

extApprovalResponseSignature 2029, 2031
Extended Cost 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
Extended Price 65, 67
extendedCost 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
extendedPrice 65, 67
Extension 105, 107, 109, 235, 237, 239
External Approval Contact Response 2029, 2031
External Approval Response Date 2029, 2031
External Approval Response Signature 2029, 2031
External ID 105, 107, 109, 235, 237, 239, 1939, 1940, 1942, 1943, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
External Number 61, 62
External PO Number 2017, 2018
External Product ID 1962, 1963, 1964
External Project Number 1999, 2001, 2003
External Project Type 1999, 2001, 2003
External Quote Number 2029, 2031
External Request Threshold 2180
externalID 105, 107, 109, 235, 237, 239, 1939, 1940, 1942, 1943, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
externalNumber 61, 62
externalPONumber 2017, 2018
externalProductID 1962, 1963, 1964
externalQuoteNumber 2029, 2031
externalRequestThreshold 2180
extProjectNumber 1999, 2001, 2003
extProjectType 1999, 2001, 2003

- F -

Facebook URL 105, 107, 109, 235, 237, 239
facebookUrl 105, 107, 109, 235, 237, 239
Fail on Error 1912
FAIL_ON_ERROR 1912
Fax 86, 88, 90, 111, 112, 114, 116, 2017, 2018
Fax Number 105, 107, 109, 235, 237, 239
faxNumber 105, 107, 109, 235, 237, 239
Field ID 149, 150, 151, 153, 214, 216, 217, 245, 246, 247, 249, 2236, 2237, 2238, 2240, 2269, 2270, 2271, 2273
Field Value 18, 19
fieldID 149, 150, 151, 153, 214, 216, 217, 245, 246, 247, 249, 2236, 2237, 2238, 2240, 2269, 2270, 2271, 2273
fieldValue 18, 19
File Size 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
fileSize 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
First Day of Week 456, 458
First Name 105, 107, 109, 235, 237, 239, 2054, 2055
First Response Assigned Resource ID 2247, 2250, 2253
First Response Date/Time 2247, 2250, 2253
First Response Due Date/Time 2247, 2250, 2253
First Response Elapsed Hours 2109, 2110, 2112, 2113
First Response Initiating Resource ID 2109, 2110, 2112, 2113, 2247, 2250, 2253
First Response Resource ID 2109, 2110, 2112, 2113
firstDayOfWeek 456, 458
firstName 105, 107, 109, 235, 237, 239, 2054, 2055
firstResponseAssignedResourceID 2247, 2250, 2253
firstResponseDateTime 2247, 2250, 2253
firstResponseDueDateTime 2247, 2250, 2253
firstResponseElapsedHours 2109, 2110, 2112, 2113
firstResponseInitiatingResourceID 2109, 2110, 2112, 2113, 2247, 2250, 2253
firstResponseResourceID 2109, 2110, 2112, 2113
force-case-sensitive-identifiers 2
forced-casing-identifiers 2
Freight 2017, 2018
Friday Business Hours End Time 456, 458
Friday Business Hours Start Time 456, 458
Friday Extended Hours End Time 456, 458
Friday Extended Hours Start Time 456, 458
fridayBusinessHoursEndTime 456, 458
fridayBusinessHoursStartTime 456, 458
fridayExtendedHoursEndTime 456, 458
fridayExtendedHoursStartTime 456, 458
From Date 482, 483
From Location ID 478, 479

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

fromDate 482, 483
fromLocationID 478, 479
Full Path 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
fullPath 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288

- G -

Gender 2054, 2055
General Ledger Account 61, 62
General Memo 2017, 2018
generalLedgerAccount 61, 62
generalMemo 2017, 2018
GL Code 428, 429, 432, 433
glCode 428, 429, 432, 433
Greeting 2054, 2055
Group by 484, 486
Group by ID 2029, 2031
groupBy 484, 486
groupByID 2029, 2031

- H -

Has User Defined Fields 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911
Have Receipt 428, 429, 432, 433
haveReceipt 428, 429, 432, 433
Height 450
Help Needed 1917, 1918, 1920
helpNeeded 1917, 1918, 1920
Highest Cost 2020, 2022, 2024, 2026
highestCost 2020, 2022, 2024, 2026
Hire Date 2054, 2055
hireDate 2054, 2055
Holiday Date 444, 446, 447
Holiday Extended Hours Start Time 456, 458
Holiday Extended Hourse End Time 456, 458

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Holiday Hours End Time 456, 458
Holiday Hours Start Time 456, 458
Holiday Hours Type 456, 458
Holiday Name 444, 446, 447
Holiday Set Description 448
Holiday Set ID 444, 446, 447, 454, 456, 458
Holiday Set Name 448
holidayDate 444, 446, 447
holidayExtendedHoursEndTime 456, 458
holidayExtendedHoursStartTime 456, 458
holidayHoursEndTime 456, 458
holidayHoursStartTime 456, 458
holidayHoursType 456, 458
holidayName 444, 446, 447
Holidays 444
HolidaysById 444
HolidaysCount 445
HolidaysEntityInformation 1175
HolidaysEntityInformation_FieldsPicklistValuesFields 1175
HolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields 1176
HolidaysEntityInformationFields 1177
HolidaysEntityInformationUserDefinedFields 1177
holidaySetDescription 448
holidaySetID 444, 446, 447, 454, 456, 458
holidaySetName 448
HolidaySets 448
HolidaySetsById 448
HolidaySetsByParentIdHolidays 446
HolidaySetsByParentIdHolidaysEntityInformation 1178
HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesFields 1179
HolidaySetsByParentIdHolidaysEntityInformation_FieldsPicklistValuesUserDefinedFields 1180
HolidaySetsByParentIdHolidaysEntityInformationFields 1182
HolidaySetsByParentIdHolidaysEntityInformationUserDefinedFields 1183
HolidaySetsByParentIdHolidaysId 447
HolidaySetsCount 449
HolidaySetsEntityInformation 1184
HolidaySetsEntityInformation_FieldsPicklistValuesFields 1184
HolidaySetsEntityInformation_FieldsPicklistValuesUserDefinedFields 1185
HolidaySetsEntityInformationFields 1186
HolidaySetsEntityInformationUserDefinedFields 1187
Home Phone 2054, 2055
homePhone 2054, 2055
Hostname 194, 198, 202
Hourly Cost 194, 198, 202
Hourly Factor 2066, 2067
Hourly Rate 267, 269, 270, 1950, 2066, 2067
hourlyCost 194, 198, 202
hourlyFactor 2066, 2067
hourlyRate 267, 269, 270, 1950, 2066, 2067
Hours 267, 269, 270, 2290, 2291, 2293, 2294
Hours Approved 267, 269, 270
Hours to be Scheduled 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
Hours to Bill 2280, 2282
Hours Worked 361, 362, 364, 2280, 2282
hoursApproved 267, 269, 270
hoursToBeScheduled 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
hoursToBill 2280, 2282
hoursWorked 361, 362, 364, 2280, 2282
HTTP Disk Cache Maximum Age (sec) 1912
HTTP Memory Cache Maximum Age (sec) 1912
HTTP Method 1912
HTTP Status Code 1912
HTTP_DISK_CACHE_MAX_AGE_SEC 1912
HTTP_DISK_CACHE_SAVE 1912
HTTP_DISK_CACHE_USE 1912
HTTP_MEMORY_CACHE_MAX_AGE_SEC 1912
HTTP_MEMORY_CACHE_SAVE 1912
HTTP_MEMORY_CACHE_USE 1912
HTTP_METHOD 1912
HTTP_STATUS_CODE 1912
http-disk-cache-compression-level 2
http-disk-cache-directory 2
http-disk-cache-ignore-write-errors 2
http-disk-cache-max-age-sec 2
http-get-timeout-max-ms 2
http-get-timeout-ms 2
http-memory-cache-compression-level 2
http-memory-cache-max-age-sec 2
http-post-timeout-max-ms 2
http-post-timeout-ms 2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

- I -

id 17, 19, 21, 23, 27, 29, 32, 35, 37, 39, 41, 44, 46, 48, 50, 52, 54, 57, 59, 62, 64, 67, 71, 73, 75, 77, 79, 81, 83, 85, 90, 93, 96, 98, 102, 104, 109, 112, 116, 118, 122, 124, 127, 130, 134, 136, 138, 140, 144, 146, 148, 150, 153, 154, 157, 159, 162, 165, 167, 170, 172, 176, 178, 180, 183, 186, 189, 191, 193, 202, 207, 209, 211, 214, 217, 219, 221, 224, 226, 228, 230, 232, 234, 239, 242, 244, 246, 249, 250, 253, 255, 257, 261, 263, 265, 267, 270, 273, 277, 280, 282, 284, 286, 288, 291, 292, 295, 297, 299, 302, 304, 308, 310, 313, 315, 318, 320, 323, 325, 327, 331, 334, 337, 339, 342, 344, 347, 349, 351, 353, 356, 358, 360, 362, 364, 366, 368, 370, 374, 376, 377, 380, 382, 384, 386, 390, 393, 394, 397, 399, 402, 404, 407, 408, 411, 413, 415, 417, 419, 421, 423, 427, 429, 433, 436, 440, 442, 444, 447, 448, 450, 452, 454, 458, 461, 463, 466, 467, 469, 472, 476, 479, 480, 481, 483, 486, 488, 491, 493, 1915, 1920, 1924, 1927, 1929, 1931, 1933, 1934, 1936, 1938, 1940, 1943, 1945, 1946, 1948, 1950, 1952, 1954, 1955, 1958, 1960, 1964, 1966, 1969, 1971, 1973, 1976, 1979, 1982, 1986, 1989, 1992, 1995, 1998, 2003, 2005, 2007, 2010, 2013, 2016, 2018, 2022, 2026, 2028, 2031, 2034, 2037, 2040, 2042, 2045, 2047, 2049, 2051, 2053, 2055, 2058, 2060, 2062, 2065, 2067, 2069, 2072, 2076, 2082, 2084, 2086, 2089, 2091, 2093, 2095, 2097, 2100, 2101, 2104, 2106, 2108, 2110, 2113, 2115, 2117, 2118, 2120, 2123, 2125, 2127, 2129, 2131, 2133, 2135, 2137, 2139, 2142, 2145, 2148, 2151, 2154, 2156, 2158, 2163, 2169, 2172, 2174, 2176, 2177, 2179, 2181, 2184, 2185, 2188, 2190, 2193, 2196, 2198, 2200, 2203, 2205, 2208, 2212, 2214, 2217, 2220, 2222, 2225, 2228, 2231, 2233, 2235, 2237, 2240, 2241, 2244, 2246, 2253, 2257, 2260, 2261, 2264, 2266, 2268, 2270, 2273, 2274, 2277, 2279, 2282, 2285, 2288, 2291, 2294, 2296, 2299, 2301, 2303, 2305

ignore-http-400-errors 2

ignore-http-401-errors 2

ignore-http-402-errors 2

ignore-http-403-errors 2

ignore-http-404-errors 2

ignore-http-422-errors 2

ignore-http-429-errors 2

ignore-http-500-errors 2

ignore-http-502-errors 2

ignore-http-503-errors 2

ignore-unknown-path-type 2

ignore-values-unknown-path 2

Imperonsator Creator Resource ID 22, 23, 25, 27, 58, 59, 86, 88, 90, 97, 98, 100, 102, 105, 107, 109, 117, 118, 120, 122, 123, 124, 126, 127, 139, 140, 142, 144, 160, 162, 163, 165, 179, 180, 182, 183, 185, 186, 187, 189, 194, 198, 202, 235, 237, 239, 303, 304, 306, 308, 309, 310, 312, 313, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 461, 467, 1917, 1918, 1920, 1923, 1924, 1926, 1927, 1957, 1958, 1959, 1960, 1962, 1963, 1964, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 1999, 2001, 2003, 2017, 2018, 2029, 2031, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2090, 2091, 2124, 2125, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2247, 2250, 2253, 2280, 2282, 2284, 2285, 2287, 2288

Impersonator Updater Resource ID 123, 124, 126, 127, 185, 186, 187, 189, 309, 310, 312, 313, 1957, 1958, 1959, 1960, 1994, 1995, 1997, 1998, 2150, 2151, 2152, 2154, 2227, 2228, 2229, 2231, 2280, 2282

impersonatorCreatorResourceID 22, 23, 25, 27, 58, 59, 86, 88, 90, 97, 98, 100, 102, 105, 107, 109, 117, 118, 120, 122, 123, 124, 126, 127, 139, 140, 142, 144, 160, 162, 163, 165, 179, 180, 182, 183, 185, 186, 187, 189, 194, 198, 202, 235, 237, 239, 303, 304, 306, 308, 309, 310, 312, 313, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 461, 467, 1917, 1918, 1920, 1923, 1924, 1926, 1927, 1957, 1958, 1959, 1960, 1962, 1963, 1964, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 1999, 2001, 2003, 2017, 2018, 2029, 2031, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2090, 2091, 2124, 2125, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2247, 2250, 2253, 2280, 2282, 2284, 2285, 2287, 2288

impersonatorUpdaterResourceID 123, 124, 126, 127, 185, 186, 187, 189, 309, 310, 312, 313, 1957, 1958, 1959, 1960, 1994, 1995, 1997, 1998, 2150, 2151, 2152, 2154, 2227, 2228, 2229, 2231, 2280, 2282

Include Items in Charge Description 256, 257, 259, 261

includeItemsInChargeDescription 256, 257, 259, 261

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

info_canCreate 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

info_canDelete 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

info_canQuery 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

info_canUpdate 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

info_hasUserDefinedFields 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

info_name 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

info_supportsWebhookCallouts 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

info_userAccessForCreate 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

info_userAccessForDelete 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

info_userAccessForQuery 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

info_userAccessForUpdate 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911
Initials 2054, 2055
Initiating Contact ID 1914, 1915
Initiating Resource ID 1914, 1915
initiatingContactID 1914, 1915
initiatingResourceID 1914, 1915
Insight Category 450
Insight Key 450
insightCategory 450
insightKey 450
Install Date 194, 198, 202
installDate 194, 198, 202
Installed by Contact ID 194, 198, 202
Installed by ID 194, 198, 202
Installed Product Category ID 28, 29, 30, 386, 388
Installed Product ID 175, 176, 177, 178
installedByContactID 194, 198, 202
installedByID 194, 198, 202
installedProductCategoryID 28, 29, 30, 386, 388
installedProductID 175, 176, 177, 178
IntegrationVendorInsights 450
IntegrationVendorInsightsById 450
IntegrationVendorInsightsCount 451
IntegrationVendorInsightsEntityInformation 1187
IntegrationVendorInsightsEntityInformation_FieldsPicklistValuesFields 1188
IntegrationVendorInsightsEntityInformation_FieldsPicklistValuesUserDefinedFields 1189
IntegrationVendorInsightsEntityInformationFields 1190
IntegrationVendorInsightsEntityInformationUserDefinedFields 1190
IntegrationVendorWidgets 452
IntegrationVendorWidgetsById 452
IntegrationVendorWidgetsCount 453
IntegrationVendorWidgetsEntityInformation 1191
IntegrationVendorWidgetsEntityInformation_FieldsPicklistValuesFields 1191
IntegrationVendorWidgetsEntityInformation_FieldsPicklistValuesUserDefinedFields 1192
IntegrationVendorWidgetsEntityInformationFields 1193
IntegrationVendorWidgetsEntityInformationUserDefinedFields 1194
Internal Billing Code ID 2280, 2282
Internal Cost 2054, 2055
Internal Currency Adjusted Price 333, 334, 336, 337, 343, 344, 345, 347
Internal Currency Amount 298, 299, 300, 302, 319, 320, 321, 323
Internal Currency Amount Approved 319, 320, 321, 323
Internal Currency Billable Amount 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
Internal Currency Cash Advance Amount 441, 442
Internal Currency Contract Hourly Rate 314, 315, 316, 318
Internal Currency Credit Amount 2243, 2244, 2245, 2246
Internal Currency Expense Amount 428, 429, 432, 433
Internal Currency Expense Total 441, 442
Internal Currency Extended Price 65, 67
Internal Currency Freight 2017, 2018
Internal Currency Line Discount 2020, 2022, 2024, 2026
Internal Currency Overage Billing Rate 329, 330, 331
Internal Currency Price 338, 339, 341, 342, 348, 349, 350, 351

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Internal Currency Rate 65, 67
Internal Currency Reimbursement Amount 428, 429, 432, 433
Internal Currency Setup Fee 329, 330, 331
Internal Currency Tax Dollars 65, 67
Internal Currency Total Amount 65, 67
Internal Currency Unit Cost 2012, 2013, 2014, 2016
Internal Currency Unit Discount 2020, 2022, 2024, 2026
Internal Currency Unit Price 70, 71, 272, 273, 275, 277, 333, 334, 336, 337, 343, 344, 345, 347, 1981, 1982, 1984, 1986, 2020, 2022, 2024, 2026, 2206, 2208, 2210, 2212
Internal Description 333, 334, 336, 337, 343, 344, 345, 347
Internal IP 194, 198, 202
Internal Notes 2280, 2282
Internal Product ID 1962, 1963, 1964
Internal Purchase Order Number 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
internalBillingCodeID 2280, 2282
internalCost 2054, 2055
internalCurrencyAdjustedPrice 333, 334, 336, 337, 343, 344, 345, 347
internalCurrencyAmount 298, 299, 300, 302, 319, 320, 321, 323
internalCurrencyAmountApproved 319, 320, 321, 323
internalCurrencyBillableAmount 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
internalCurrencyCashAdvanceAmount 441, 442
internalCurrencyContractHourlyRate 314, 315, 316, 318
internalCurrencyCreditAmount 2243, 2244, 2245, 2246
internalCurrencyExpenseAmount 428, 429, 432, 433
internalCurrencyExpenseTotal 441, 442
internalCurrencyExtendedPrice 65, 67
internalCurrencyFreight 2017, 2018
internalCurrencyLineDiscount 2020, 2022, 2024, 2026
internalCurrencyOverageBillingRate 329, 330, 331
internalCurrencyPrice 338, 339, 341, 342, 348, 349, 350, 351
internalCurrencyRate 65, 67
internalCurrencyReimbursementAmount 428, 429, 432, 433
internalCurrencySetupFee 329, 330, 331
internalCurrencyTaxDollars 65, 67
internalCurrencyTotalAmount 65, 67
internalCurrencyUnitCost 2012, 2013, 2014, 2016
internalCurrencyUnitDiscount 2020, 2022, 2024, 2026
internalCurrencyUnitPrice 70, 71, 272, 273, 275, 277, 333, 334, 336, 337, 343, 344, 345, 347, 1981, 1982, 1984, 1986, 2020, 2022, 2024, 2026, 2206, 2208, 2210, 2212
internalDescription 333, 334, 336, 337, 343, 344, 345, 347
InternalLocations 454
InternalLocationsById 454
InternalLocationsCount 455
InternalLocationsEntityInformation 1194
InternalLocationsEntityInformation_FieldsPicklistValuesFields 1195
InternalLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1196
InternalLocationsEntityInformationFields 1197
InternalLocationsEntityInformationUserDefinedFields 1197
InternalLocationWithBusinessHours 456
InternalLocationWithBusinessHoursById 458
InternalLocationWithBusinessHoursCount 460
InternalLocationWithBusinessHoursEntityInformation 1198
InternalLocationWithBusinessHoursEntityInformation_FieldsPicklistValuesFields 1199
InternalLocationWithBusinessHoursEntityInformation_FieldsPicklistValuesUserDefinedFields 1199
InternalLocationWithBusinessHoursEntityInformationFields 1200
InternalLocationWithBusinessHoursEntityInformationUserDefinedFields 1201
internalNotes 2280, 2282
internalProductID 1962, 1963, 1964
internalPurchaseOrderNumber 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
invalid-json-on-get-max-tries 2
invalid-json-on-get-sleep-initial-ms 2
invalid-json-on-get-sleep-max-ms 2
invalid-json-on-get-sleep-multiplicator 2
invalid-json-on-post-max-tries 2
invalid-json-on-post-sleep-initial-ms 2
invalid-json-on-post-sleep-max-ms 2
invalid-json-on-post-sleep-multiplicator 2
invantive-sql-compress-sparse-arrays 2
invantive-sql-correct-invalid-date 2
invantive-sql-execution-profile-disk-path 2
invantive-sql-execution-profile-to-disk 2
invantive-sql-forward-filters-to-data-containers 2
invantive-sql-share-byte-arrays 2
invantive-sql-share-strings 2
invantive-sql-shuffle-fetch-results-data-containers 2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

invantive-use-cache 2
Inventory Item ID 463, 465, 466
Inventory Location ID 461, 469, 2012, 2013, 2014, 2016
inventoryItemID 463, 465, 466
InventoryItems 461
InventoryItemsById 461
InventoryItemsByParentIdSerialNumbers 465
InventoryItemsByParentIdSerialNumbersEntityInformation 1202
InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesFields 1203
InventoryItemsByParentIdSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields 1204
InventoryItemsByParentIdSerialNumbersEntityInformationFields 1205
InventoryItemsByParentIdSerialNumbersEntityInformationUserDefinedFields 1206
InventoryItemsByParentIdSerialNumbersId 466
InventoryItemsCount 462
InventoryItemsEntityInformation 1207
InventoryItemsEntityInformation_FieldsPicklistValuesFields 1208
InventoryItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1209
InventoryItemsEntityInformationFields 1210
InventoryItemsEntityInformationUserDefinedFields 1210
InventoryItemSerialNumbers 463
InventoryItemSerialNumbersById 463
InventoryItemSerialNumbersCount 464
InventoryItemSerialNumbersEntityInformation 1211
InventoryItemSerialNumbersEntityInformation_FieldsPicklistValuesFields 1211
InventoryItemSerialNumbersEntityInformation_FieldsPicklistValuesUserDefinedFields 1212
InventoryItemSerialNumbersEntityInformationFields 1213
InventoryItemSerialNumbersEntityInformationUserDefinedFields 1214
inventoryLocationID 461, 469, 2012, 2013, 2014, 2016
InventoryLocations 467
InventoryLocationsById 467
InventoryLocationsCount 468
InventoryLocationsEntityInformation 1214
InventoryLocationsEntityInformation_FieldsPicklistValuesFields 1215
InventoryLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1216
InventoryLocationsEntityInformationFields 1217
InventoryLocationsEntityInformationUserDefinedFields 1217
inventoryProductID 471, 472, 475, 476
InventoryProducts 469
InventoryProductsById 469
InventoryProductsByParentIdStockedItems 475
InventoryProductsByParentIdStockedItemsAddEntityInformation 1218
InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesFields 1219
InventoryProductsByParentIdStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields 1220
InventoryProductsByParentIdStockedItemsAddEntityInformationFields 1221
InventoryProductsByParentIdStockedItemsAddEntityInformationUserDefinedFields 1223
InventoryProductsByParentIdStockedItemsEntityInformation 1224
InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesFields 1225
InventoryProductsByParentIdStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1226
InventoryProductsByParentIdStockedItemsEntityInformationFields 1227
InventoryProductsByParentIdStockedItemsEntityInformationUserDefinedFields 1228
InventoryProductsByParentIdStockedItemsId 476
InventoryProductsByParentIdStockedItemsRemoveEntityInformation 1229
InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields 1230
InventoryProductsByParentIdStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields 1232
InventoryProductsByParentIdStockedItemsRemoveEntityInformationFields 1233
InventoryProductsByParentIdStockedItemsRemoveEntityInformationUserDefinedFields 1234
InventoryProductsByParentIdStockedItemsTransferEntityInformation 1235
InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesFields 1236
InventoryProductsByParentIdStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields 1237
InventoryProductsByParentIdStockedItemsTransferEntityInformationFields 1239
InventoryProductsByParentIdStockedItemsTransferEntityInformationUserDefinedFields 1240
InventoryProductsCount 471
InventoryProductsEntityInformation 1241
InventoryProductsEntityInformation_FieldsPicklistValuesFields 1242

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

InventoryProductsEntityInformation_FieldsPicklistValuesUserDefinedFields 1242
InventoryProductsEntityInformationFields 1243
InventoryProductsEntityInformationUserDefinedFields 1244
InventoryStockedItems 471
InventoryStockedItemsAddEntityInformation 1244
InventoryStockedItemsAddEntityInformation_FieldsPicklistValuesFields 1245
InventoryStockedItemsAddEntityInformation_FieldsPicklistValuesUserDefinedFields 1246
InventoryStockedItemsAddEntityInformationFields 1247
InventoryStockedItemsAddEntityInformationUserDefinedFields 1247
InventoryStockedItemsById 472
InventoryStockedItemsCount 474
InventoryStockedItemsEntityInformation 1248
InventoryStockedItemsEntityInformation_FieldsPicklistValuesFields 1249
InventoryStockedItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1249
InventoryStockedItemsEntityInformationFields 1250
InventoryStockedItemsEntityInformationUserDefinedFields 1251
InventoryStockedItemsRemoveEntityInformation 1251
InventoryStockedItemsRemoveEntityInformation_FieldsPicklistValuesFields 1252
InventoryStockedItemsRemoveEntityInformation_FieldsPicklistValuesUserDefinedFields 1253
InventoryStockedItemsRemoveEntityInformationFields 1254
InventoryStockedItemsRemoveEntityInformationUserDefinedFields 1254
InventoryStockedItemsTransferEntityInformation 1255
InventoryStockedItemsTransferEntityInformation_FieldsPicklistValuesFields 1256
InventoryStockedItemsTransferEntityInformation_FieldsPicklistValuesUserDefinedFields 1256
InventoryStockedItemsTransferEntityInformationFields 1257
InventoryStockedItemsTransferEntityInformationUserDefinedFields 1258
InventoryTransfers 478
InventoryTransfersById 479
InventoryTransfersCount 480
InventoryTransfersEntityInformation 1258
InventoryTransfersEntityInformation_FieldsPicklistValuesFields 1259
InventoryTransfersEntityInformation_FieldsPicklistValuesUserDefinedFields 1260
InventoryTransfersEntityInformationFields 1261
InventoryTransfersEntityInformationUserDefinedFields 1261
Invoice Batch ID 18, 19
Invoice Date/Time 482, 483
Invoice Description 256, 257, 259, 261, 333, 334, 336, 337, 343, 344, 345, 347, 2084, 2114, 2115
Invoice Editor Template ID 482, 483
Invoice Email Message ID 86, 88, 90
Invoice ID 65, 67
Invoice Markup 480, 481
Invoice Method 86, 88, 90
Invoice Non-contract Items to Parent Company 86, 88, 90
Invoice Number 267, 269, 270, 319, 320, 321, 323, 352, 353, 355, 356, 482, 483
Invoice Template ID 86, 88, 90, 358
Invoice Total 482, 483
invoiceBatchID 18, 19
invoiceDateTime 482, 483
invoiceDescription 256, 257, 259, 261, 333, 334, 336, 337, 343, 344, 345, 347, 2084, 2114, 2115
invoiceEditorTemplateID 482, 483
invoiceEmailMessageID 86, 88, 90
invoiceID 65, 67
invoiceMarkup 480, 481
invoiceMethod 86, 88, 90
invoiceNonContractItemsToParentCompany 86, 88, 90
invoiceNumber 267, 269, 270, 319, 320, 321, 323, 352, 353, 355, 356, 482, 483
Invoices 482
InvoicesById 483
InvoicesByIdInvoiceMarkupHtml 480
InvoicesByIdInvoiceMarkupXml 481
InvoicesCount 484
InvoicesEntityInformation 1262
InvoicesEntityInformation_FieldsPicklistValuesFields 1263
InvoicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1263
InvoicesEntityInformationFields 1264
InvoicesEntityInformationUserDefinedFields 1265
InvoiceTemplateID 86, 88, 90, 358
InvoiceTemplates 484
InvoiceTemplatesById 486
InvoiceTemplatesCount 487
InvoiceTemplatesEntityInformation 1265
InvoiceTemplatesEntityInformation_FieldsPicklistValueFields 1266
InvoiceTemplatesEntityInformation_FieldsPicklistValueUserDefinedFields 1267
InvoiceTemplatesEntityInformationFields 1268

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

InvoiceTemplatesEntityInformationUserDefinedFields
1268
invoiceTotal 482, 483

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Active 17, 61, 62, 74, 75, 81, 86, 88, 90, 103, 104, 105, 107, 109, 111, 112, 114, 116, 154, 170, 194, 198, 202, 209, 218, 219, 234, 235, 237, 239, 250, 256, 257, 259, 261, 296, 297, 358, 359, 360, 398, 399, 401, 402, 450, 452, 467, 488, 490, 491, 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733,

Is Announcement 1994, 1995, 1997, 1998

Is API Only 103, 104, 2195, 2196

Is Approved 2005, 2202, 2203, 2204, 2205

Is Assigned to Co-managed 2247, 2250, 2253

Is Associated as Co-managed 135, 136, 137, 138

Is Billable to Company 70, 71, 272, 273, 275, 277, 428, 429, 432, 433, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212

Is Billed 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212

Is Client Portal Active 82, 83, 86, 88, 90

Is Client Portal Default 170

Is Complete 2090, 2091

Is Completed 2214, 2216, 2217

Is Compliant 329, 330, 331

Is Compounded 2177

Is Daily Pro-ration Enabled 256, 257, 259, 261

Is Default 454, 456, 458, 467, 1970, 1971, 1972, 1973, 2041, 2042, 2044, 2045, 2057, 2058, 2059, 2060

Is Default Contract 329, 330, 331

Is Default Country 358

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Default Value 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809, 1814, 1815, 1819,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Deleted 1914, 1915
Is Department Lead 2041, 2042, 2044, 2045
Is Display Always Field 149, 150, 151, 153, 156, 157, 158, 159, 214, 216, 217, 220, 221, 223, 224, 245, 246, 247, 249, 252, 253, 254, 255, 2236, 2237, 2238, 2240, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279
Is Eligible for RMA 1962, 1963, 1964
Is Enabled for Co-managed 86, 88, 90
Is Encrypted 2295, 2296
Is Excluded from Automatic Tagging 2136, 2137
Is Excluded from New Contracts 61, 62, 2066, 2067
Is Field Mapping 2295, 2296
Is First Response Met 2109, 2110, 2112, 2113
Is Global Default 103, 104, 170, 2195, 2196
Is Important 76, 77, 78, 79, 377, 379, 380, 2214, 2216, 2217
Is Initial Payment 298, 299, 300, 302
Is Internal Currency 359, 360
Is Internal Notes Visible to Co-managed 2280, 2282
Is Non-billable 2280, 2282
Is Opted Out from Bulk Email 105, 107, 109, 235, 237, 239
Is Optional 2020, 2022, 2024, 2026
Is Paid 267, 269, 270, 319, 320, 321, 323, 352, 353, 355, 356

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Picklist 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257, 1258,

Is Primary 111, 112, 114, 116

Is Primary Co-managed Resource 84, 85

Is Private 2295, 2296

Is Protected 2295, 2296

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Queryable 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Read-only 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Ready	154, 218, 219, 250, 2241, 2274

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Reference 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257,

Is Reimbursable 428, 429, 432, 433

Is Rejected 428, 429, 432, 433

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Required 172, 174, 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Resolution Met 2109, 2110, 2112, 2113
Is Resolution Plan Met 2109, 2110, 2112, 2113
Is Sample 86, 88, 90
Is Scheduled 1939, 1940, 1942, 1943
Is Serialized 1962, 1963, 1964
Is Subscribed Field 149, 150, 151, 153, 156, 157, 158, 159, 214, 216, 217, 220, 221, 223, 224, 245, 246, 247, 249, 252, 253, 254, 255, 2236, 2237, 2238, 2240, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279
Is Subscribed to Create Events 154, 218, 219, 250, 2241, 2274
Is Subscribed to Delete Events 154, 218, 219, 250, 2241, 2274
Is Subscribed to Update Events 154, 218, 219, 250, 2241, 2274

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is System 81, 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 972, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809, 1814, 1815, 1819,
Is System Action Type 17
Is System Role 2066, 2067
Is Task Attachment 22, 23, 25, 27, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
Is Task Billable 2159, 2161, 2163, 2165, 2167, 2169
Is Task Fire Active 86, 88, 90
Is Tax Exempt 86, 88, 90, 111, 112, 114, 116
Is Taxable 2020, 2022, 2024, 2026
Is Template Job 1914, 1915
Is Visible in Client Portal 2159, 2161, 2163, 2165, 2167, 2169
Is Visible to Client Portal 2295, 2296
Is Visible to Co-managed 2247, 2250, 2253
Is Voided 482, 483

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isActive 17, 61, 62, 74, 75, 81, 86, 88, 90, 103, 104, 105, 107, 109, 111, 112, 114, 116, 154, 170, 194, 198, 202, 209, 218, 219, 234, 235, 237, 239, 250, 256, 257, 259, 261, 296, 297, 358, 359, 360, 398, 399, 401, 402, 450, 452, 467, 488, 490, 491, 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isAnnouncement 1994, 1995, 1997, 1998
isApiOnly 103, 104, 2195, 2196
isApproved 2005, 2202, 2203, 2204, 2205
isAssignedToComanaged 2247, 2250, 2253
isAssociatedAsComanaged 135, 136, 137, 138
isBillableToCompany 70, 71, 272, 273, 275, 277, 428, 429, 432, 433, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
isBilled 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
isClientPortalActive 82, 83, 86, 88, 90
isClientPortalDefault 170
isComplete 2090, 2091
isCompleted 2214, 2216, 2217
isCompliant 329, 330, 331
isCompounded 2177
isDailyProrationEnabled 256, 257, 259, 261
isDefault 454, 456, 458, 467, 1970, 1971, 1972, 1973, 2041, 2042, 2044, 2045, 2057, 2058, 2059, 2060
isDefaultContract 329, 330, 331
isDefaultCountry 358

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isDefaultValue 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 814, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809, 1814, 1815, 1819,

isDeleted 1914, 1915

isDepartmentLead 2041, 2042, 2044, 2045

isDisplayAlwaysField 149, 150, 151, 153, 156, 157, 158, 159, 214, 216, 217, 220, 221, 223, 224, 245, 246, 247, 249, 252, 253, 254, 255, 2236, 2237, 2238, 2240, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279

isEligibleForRma 1962, 1963, 1964

isEnabledForComanaged 86, 88, 90

isEncrypted 2295, 2296

isExcludedFromAutomaticTagging 2136, 2137

isExcludedFromNewContracts 61, 62, 2066, 2067

isFieldMapping 2295, 2296

isFirstResponseMet 2109, 2110, 2112, 2113

isGlobalDefault 103, 104, 170, 2195, 2196

isImportant 76, 77, 78, 79, 377, 379, 380, 2214, 2216, 2217

isInitialPayment 298, 299, 300, 302

isInternalCurrency 359, 360

isInternalNotesVisibleToComanaged 2280, 2282

isNonBillable 2280, 2282

isOptedOutFromBulkEmail 105, 107, 109, 235, 237, 239

isOptional 2020, 2022, 2024, 2026

isPaid 267, 269, 270, 319, 320, 321, 323, 352, 353, 355, 356

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isPickList 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257, 1258,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isPrimary 111, 112, 114, 116
isPrimaryComanagedResource 84, 85
isPrivate 2295, 2296
isProtected 2295, 2296

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isQueryable 495, 496, 497, 499, 500, 501, 502,
503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513,
514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524,
525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536,
537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549,
550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562,
563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573,
574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587,
589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603,
604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618,
619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631,
633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645,
646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659,
660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674,
675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686,
687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699,
700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710,
712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726,
728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741,
742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753,
755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768,
770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782,
783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796,
797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810,
811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825,
827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837,
838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849,
850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863,
864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877,
878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888,
889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900,
901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916,
917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931,
933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946,
948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962,
963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978,
979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994,
995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005,
1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014,
1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022,
1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030,
1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038,
1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047,
1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058,
1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066,
1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075,
1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085,
1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097,
1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109,
1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121,
1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132,
1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141,
1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149,
1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159,
1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168,
1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179,
1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188,
1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196,
1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206,
1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215,
1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226,
1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237,
1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247,
1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isReadOnly 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257, 1258,

isReady 154, 218, 219, 250, 2241, 2274

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isReference 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isReimbursable 428, 429, 432, 433
isRejected 428, 429, 432, 433

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isRequired 172, 174, 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256,

isResolutionMet 2109, 2110, 2112, 2113

isResolutionPlanMet 2109, 2110, 2112, 2113

isSample 86, 88, 90

isScheduled 1939, 1940, 1942, 1943

isSerialized 1962, 1963, 1964

isSubscribedField 149, 150, 151, 153, 156, 157, 158, 159, 214, 216, 217, 220, 221, 223, 224, 245, 246, 247, 249, 252, 253, 254, 255, 2236, 2237, 2238, 2240, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279

isSubscribedToCreateEvents 154, 218, 219, 250, 2241, 2274

isSubscribedToDeleteEvents 154, 218, 219, 250, 2241, 2274

isSubscribedToUpdateEvents 154, 218, 219, 250, 2241, 2274

Issue Type 2247, 2250, 2253

Issue Type ID 2197, 2198, 2199, 2200

issueType 2247, 2250, 2253

issueTypeID 2197, 2198, 2199, 2200

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isSupportedWebhookField 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isSystem 81, 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809, 1814, 1815, 1819,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

isSystemActionType 17
isSystemRole 2066, 2067
isTaskAttachment 22, 23, 25, 27, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
isTaskBillable 2159, 2161, 2163, 2165, 2167, 2169
isTaskFireActive 86, 88, 90
isTaxable 2020, 2022, 2024, 2026
isTaxExempt 86, 88, 90, 111, 112, 114, 116
isTemplateJob 1914, 1915
isVisibleInClientPortal 2159, 2161, 2163, 2165, 2167, 2169
isVisibleToClientPortal 2295, 2296
isVisibleToComanaged 2247, 2250, 2253
isVoided 482, 483
Item Approver ID 65, 67
Item Date 65, 67
Item Name 65, 67, 76, 77, 78, 79, 377, 379, 380, 2214, 2216, 2217
itemApproverID 65, 67
itemDate 65, 67
Itemize Items in each Group 484, 486
Itemize Services and Bundles 484, 486
itemizeItemsInEachGroup 484, 486
itemizeServicesAndBundles 484, 486
itemName 65, 67, 76, 77, 78, 79, 377, 379, 380, 2214, 2216, 2217

- J -

join-set-points-per-request 2

- K -

Kernel Version ID 194, 198, 202
Key 1912
Keywords 398, 399, 401, 402, 488, 490, 491
Knowledgebase Article ID 76, 77, 78, 79, 2214, 2216, 2217
knowledgebaseArticleID 76, 77, 78, 79, 2214, 2216, 2217
KnowledgeBaseArticles 488
KnowledgeBaseArticlesById 488
KnowledgeBaseArticlesByParentIdArticleAssociations 51
KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation 1269
KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformation_FieldsPicklistValuesFields 1270
KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationFields 1271
KnowledgeBaseArticlesByParentIdArticleAssociationsEntityInformationUserDefinedFields 1272
KnowledgeBaseArticlesByParentIdArticleAssociationsId 52
KnowledgeBaseArticlesByParentIdAttachments 25
KnowledgeBaseArticlesByParentIdAttachmentsId 27
KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociations 30
KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation 1273
KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformation_FieldsPicklistValuesFields 1274
KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationFields 1276
KnowledgeBaseArticlesByParentIdConfigurationItemCategoryAssociationsEntityInformationUserDefinedFields 1277
KnowledgeBaseArticlesByParentIdDocumentAssociations 55
KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation 1278
KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformation_FieldsPicklistValuesFields 1279
KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationFields 1280
KnowledgeBaseArticlesByParentIdDocumentAssociationsEntityInformationUserDefinedFields 1281
KnowledgeBaseArticlesByParentIdDocumentAssociationsId 57
KnowledgeBaseArticlesByParentIdNotes 34
KnowledgeBaseArticlesByParentIdNotesEntityInformation 1282
KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1283
KnowledgeBaseArticlesByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1285
KnowledgeBaseArticlesByParentIdNotesEntityInformationFields 1286
KnowledgeBaseArticlesByParentIdNotesEntityInformationUserDefinedFields 1287
KnowledgeBaseArticlesByParentIdNotesId 35
KnowledgeBaseArticlesByParentIdPlainTextContent 38
KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation 1288

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesFields 1289
KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformation_FieldsPicklistValuesUserDefinedFields 1290
KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationFields 1292
KnowledgeBaseArticlesByParentIdPlainTextContentEntityInformationUserDefinedFields 1293
KnowledgeBaseArticlesByParentIdPlainTextContentId 39
KnowledgeBaseArticlesByParentIdTagAssociations 43
KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation 1294
KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields 1295
KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1296
KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationFields 1298
KnowledgeBaseArticlesByParentIdTagAssociationsEntityInformationUserDefinedFields 1299
KnowledgeBaseArticlesByParentIdTagAssociationsId 44
KnowledgeBaseArticlesByParentIdTicketAssociations 47
KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation 1300
KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformation_FieldsPicklistValuesFields 1301
KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationFields 1302
KnowledgeBaseArticlesByParentIdTicketAssociationsEntityInformationUserDefinedFields 1303
KnowledgeBaseArticlesByParentIdTicketAssociationsId 48
KnowledgeBaseArticlesCount 490
KnowledgeBaseArticlesEntityInformation 1304
KnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields 1305
KnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesUserDefinedFields 1306
KnowledgeBaseArticlesEntityInformationFields 1307
KnowledgeBaseArticlesEntityInformationUserDefinedFields 1307
KnowledgeBaseCategories 493
KnowledgeBaseCategoriesById 493
KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticles 490
KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation 1308
KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformation_FieldsPicklistValuesFields 1309
KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationFields 1310
KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesEntityInformationUserDefinedFields 1311
KnowledgeBaseCategoriesByParentIdKnowledgeBaseArticlesId 491
KnowledgeBaseCategoriesCount 494
KnowledgeBaseCategoriesEntityInformation 1312
KnowledgeBaseCategoriesEntityInformation_FieldsPicklistValuesFields 1313
KnowledgeBaseCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1314
KnowledgeBaseCategoriesEntityInformationFields 1315
KnowledgeBaseCategoriesEntityInformationUserDefinedFields 1315

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

- L -

Label 495, 496, 497, 499, 500, 501, 502, 503, 505, 506, 508, 509, 510, 511, 512, 514, 515, 516, 517, 518, 519, 521, 522, 523, 524, 525, 526, 528, 529, 530, 531, 533, 535, 536, 537, 538, 540, 542, 543, 544, 545, 547, 549, 550, 551, 552, 554, 555, 558, 559, 560, 562, 563, 564, 565, 566, 567, 569, 570, 571, 572, 573, 574, 576, 577, 579, 581, 583, 584, 587, 589, 590, 592, 594, 596, 598, 600, 601, 604, 606, 607, 609, 611, 613, 615, 617, 619, 620, 621, 622, 624, 626, 628, 629, 630, 631, 633, 635, 637, 638, 639, 640, 642, 644, 645, 646, 647, 649, 651, 652, 653, 654, 656, 657, 660, 662, 663, 665, 668, 669, 671, 673, 674, 675, 676, 677, 679, 680, 682, 683, 684, 686, 688, 690, 691, 692, 694, 695, 696, 697, 698, 700, 701, 703, 704, 705, 706, 707, 709, 710, 713, 715, 716, 719, 721, 722, 724, 726, 728, 730, 732, 734, 736, 737, 738, 740, 741, 742, 743, 744, 746, 747, 748, 749, 751, 753, 755, 757, 759, 760, 763, 765, 766, 768, 770, 771, 772, 774, 776, 777, 778, 779, 781, 783, 785, 786, 788, 790, 791, 792, 794, 795, 797, 799, 800, 801, 803, 805, 806, 807, 808, 810, 811, 814, 816, 817, 819, 822, 823, 825, 827, 828, 829, 830, 831, 833, 834, 835, 836, 837, 838, 840, 841, 842, 843, 845, 847, 848, 849, 850, 852, 854, 855, 856, 857, 859, 860, 861, 863, 864, 866, 869, 870, 872, 874, 875, 876, 877, 878, 880, 881, 883, 884, 885, 886, 887, 889, 890, 891, 892, 893, 894, 896, 897, 899, 901, 903, 904, 907, 909, 910, 912, 914, 916, 918, 920, 921, 924, 926, 927, 929, 931, 933, 935, 937, 938, 941, 943, 944, 946, 948, 950, 952, 954, 955, 957, 960, 961, 963, 965, 967, 969, 971, 972, 975, 977, 978, 980, 983, 984, 986, 988, 989, 992, 994, 995, 997, 999, 1000, 1001, 1003, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1016, 1017, 1018, 1019, 1020, 1021, 1023, 1024, 1025, 1026, 1027, 1028, 1030, 1031, 1032, 1033, 1034, 1035, 1037, 1038, 1039, 1040, 1042, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1055, 1056, 1057, 1059, 1060, 1061, 1062, 1063, 1064, 1066, 1067, 1068, 1069, 1071, 1073, 1074, 1075, 1076, 1078, 1080, 1082, 1083, 1085, 1087, 1089, 1091, 1093, 1094, 1097, 1099, 1100, 1102, 1105, 1107, 1109, 1110, 1113, 1115, 1116, 1118, 1121, 1122, 1124, 1126, 1128, 1130, 1132, 1133, 1136, 1137, 1138, 1140, 1141, 1142, 1143, 1144, 1145, 1147, 1148, 1149, 1150, 1152, 1154, 1155, 1156, 1157, 1159, 1161, 1163, 1164, 1166, 1167, 1168, 1170, 1171, 1174, 1175, 1176, 1177, 1179, 1180, 1183, 1184, 1185, 1187, 1188, 1189, 1190, 1191, 1192, 1194, 1195, 1196, 1197, 1199, 1201, 1203, 1204, 1206, 1208, 1209, 1210, 1211, 1212, 1214, 1215, 1216, 1217, 1219, 1220, 1223, 1225, 1226, 1228, 1230, 1232, 1234, 1236, 1237, 1240, 1242, 1244, 1245, 1246, 1247, 1249, 1251, 1252, 1253, 1254, 1256, 1258, 1259, 1260, 1261, 1263, 1265, 1266, 1267, 1268, 1270, 1272, 1274, 1277, 1279, 1281, 1283, 1285, 1287, 1289, 1290, 1293, 1295, 1296, 1299, 1301, 1303, 1305, 1306, 1307, 1309, 1311, 1313, 1314, 1315, 1316, 1317, 1319, 1320, 1322, 1324, 1326, 1328, 1329, 1331, 1332, 1333, 1335, 1337, 1339, 1341, 1343, 1345, 1346, 1347, 1348, 1350, 1352, 1353, 1354, 1355, 1357, 1359, 1360, 1361, 1362, 1364, 1366, 1367, 1368, 1369, 1371, 1373, 1374, 1375, 1376, 1378, 1380, 1381, 1382, 1383, 1385, 1386, 1389, 1391, 1392, 1394, 1396, 1398, 1400, 1402, 1404, 1405, 1406, 1407, 1409, 1411, 1412, 1414, 1415,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

label_1 496, 500, 503, 509, 512, 516, 519, 523, 526, 530, 533, 537, 540, 544, 547, 551, 555, 560, 564, 567, 571, 574, 579, 584, 590, 596, 601, 607, 613, 617, 621, 626, 630, 635, 639, 642, 646, 649, 653, 657, 663, 669, 674, 677, 683, 691, 695, 698, 704, 707, 716, 722, 728, 737, 741, 744, 748, 751, 760, 766, 771, 774, 778, 781, 786, 791, 795, 800, 803, 807, 811, 817, 823, 828, 831, 835, 838, 842, 845, 849, 852, 856, 860, 864, 870, 875, 878, 884, 887, 891, 894, 899, 904, 910, 916, 921, 927, 933, 938, 944, 950, 955, 961, 967, 972, 978, 984, 989, 995, 1000, 1003, 1007, 1011, 1014, 1018, 1021, 1025, 1028, 1032, 1035, 1039, 1042, 1046, 1052, 1057, 1061, 1064, 1068, 1071, 1075, 1078, 1083, 1089, 1094, 1100, 1110, 1116, 1122, 1128, 1133, 1138, 1142, 1145, 1149, 1152, 1156, 1161, 1167, 1171, 1176, 1180, 1185, 1189, 1192, 1196, 1199, 1204, 1209, 1212, 1216, 1220, 1226, 1232, 1237, 1242, 1246, 1249, 1253, 1256, 1260, 1263, 1267, 1285, 1290, 1296, 1306, 1314, 1317, 1322, 1326, 1332, 1335, 1343, 1347, 1350, 1354, 1357, 1361, 1364, 1368, 1371, 1375, 1378, 1382, 1386, 1392, 1398, 1402, 1406, 1409, 1415, 1420, 1425, 1430, 1436, 1441, 1446, 1450, 1453, 1458, 1463, 1467, 1472, 1475, 1479, 1483, 1488, 1491, 1497, 1500, 1504, 1508, 1514, 1519, 1525, 1531, 1536, 1541, 1545, 1548, 1552, 1557, 1562, 1566, 1570, 1574, 1580, 1585, 1588, 1593, 1598, 1601, 1605, 1610, 1614, 1618, 1623, 1627, 1630, 1634, 1638, 1643, 1646, 1650, 1653, 1657, 1661, 1666, 1673, 1677, 1681, 1687, 1692, 1697, 1701, 1704, 1708, 1711, 1715, 1718, 1725, 1730, 1733, 1737, 1740, 1744, 1747, 1751, 1756, 1760, 1763, 1768, 1774, 1778, 1782, 1786, 1792, 1798, 1804, 1809, 1815, 1820, 1826, 1832, 1838, 1842, 1846, 1849, 1853, 1856, 1861, 1866, 1872, 1877, 1880, 1884, 1889, 1893, 1896, 1901, 1906, 1909

Labor Estimated Costs 1999, 2001, 2003

Labor Estimated Margin Percentage 1999, 2001, 2003

Labor Estimated Revenue 1999, 2001, 2003

Labor ID 2020, 2022, 2024, 2026

laborEstimatedCosts 1999, 2001, 2003

laborEstimatedMarginPercentage 1999, 2001, 2003

laborEstimatedRevenue 1999, 2001, 2003

laborID 2020, 2022, 2024, 2026

Lag Days 2155, 2156, 2157, 2158

lagDays 2155, 2156, 2157, 2158

Last Acitvity Person Type 194, 198, 202, 1999, 2001, 2003, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253

Last Activity 1917, 1918, 1920

Last Activity by 2033, 2034

Last Activity Date 86, 88, 90, 105, 107, 109, 185, 186, 187, 189, 235, 237, 239, 309, 310, 312, 313, 1957, 1958, 1959, 1960, 1994, 1995, 1997, 1998, 2029, 2031, 2033, 2034, 2150, 2151, 2152, 2154, 2227, 2228, 2229, 2231, 2247, 2250, 2253

Last Activity Date/Time 1939, 1940, 1942, 1943, 1999, 2001, 2003, 2159, 2161, 2163, 2165, 2167, 2169

Last Activity Person ID 194, 198, 202

Last Activity Resource ID 1999, 2001, 2003, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253

Last Check-in Date/Time 194, 198, 202

Last Customer Notification Date/Time 2247, 2250, 2253

Last Customer Visible Activity Date/Time 2247, 2250, 2253

Last Modified 31, 32, 34, 35, 105, 107, 109, 123, 124, 126, 127, 139, 140, 142, 144, 235, 237, 239, 359, 360, 389, 390, 391, 393, 398, 399, 401, 402, 450, 452, 488, 490, 491, 2084, 2090, 2091, 2114, 2115, 2136, 2137, 2280, 2282, 2290, 2291, 2293, 2294

Last Modified by 2029, 2031

Last Modified by Resource ID 31, 32, 34, 35, 389, 390, 391, 393, 398, 399, 401, 402, 488, 490, 491, 2290, 2291, 2293, 2294

Last Modified Time 194, 198, 202

Last Modified User ID 2280, 2282

Last Name 105, 107, 109, 235, 237, 239, 2054, 2055

Last Published by Resource ID 2029, 2031

Last Published Date/Time 2029, 2031

Last Tracked Modification Date/Time 2247, 2250, 2253

Last Tracked Modified Date/Time 86, 88, 90

lastActivity 1917, 1918, 1920

lastActivityBy 2033, 2034

lastActivityDate 86, 88, 90, 105, 107, 109, 185, 186, 187, 189, 235, 237, 239, 309, 310, 312, 313, 1957, 1958, 1959, 1960, 1994, 1995, 1997, 1998, 2029, 2031, 2033, 2034, 2150, 2151, 2152, 2154, 2227, 2228, 2229, 2231, 2247, 2250, 2253

lastActivityDateTime 1939, 1940, 1942, 1943, 1999, 2001, 2003, 2159, 2161, 2163, 2165, 2167, 2169

lastActivityPersonID 194, 198, 202

lastActivityPersonType 194, 198, 202, 1999, 2001, 2003, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253

lastActivityResourceID 1999, 2001, 2003, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253

lastCustomerNotificationDateTime 2247, 2250, 2253

lastCustomerVisibleActivityDateTime 2247, 2250, 2253

lastModifiedBy 2029, 2031

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

lastModifiedByResourceID 31, 32, 34, 35, 389, 390, 391, 393, 398, 399, 401, 402, 488, 490, 491, 2290, 2291, 2293, 2294
lastModifiedDate 105, 107, 109, 123, 124, 126, 127, 139, 140, 142, 144, 235, 237, 239, 2084, 2114, 2115
lastModifiedDateTime 31, 32, 34, 35, 359, 360, 389, 390, 391, 393, 398, 399, 401, 402, 450, 452, 488, 490, 491, 2090, 2091, 2136, 2137, 2280, 2282, 2290, 2291, 2293, 2294
lastModifiedTime 194, 198, 202
lastModifiedUserID 2280, 2282
lastName 105, 107, 109, 235, 237, 239, 2054, 2055
lastPublishedByResourceID 2029, 2031
lastPublishedDateTime 2029, 2031
lastTrackedModificationDateTime 2247, 2250, 2253
lastTrackedModifiedDateTime 86, 88, 90
Latest Estimated Arrival Date 2017, 2018
latestEstimatedArrivalDate 2017, 2018
Lead Source 1917, 1918, 1920
leadSource 1917, 1918, 1920

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Length 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256, 1257, 1258, 1259,
License Type 2054, 2055
licenseType 2054, 2055
limit-partition-calls-left 2
Line Discount 2020, 2022, 2024, 2026
Line Item Full Description 65, 67
Line Item Group Description 65, 67
lineDiscount 2020, 2022, 2024, 2026
lineItemFullDescription 65, 67
lineItemGroupDescription 65, 67
Link 1962, 1963, 1964
LinkedIn URL 105, 107, 109, 235, 237, 239
linkedInUrl 105, 107, 109, 235, 237, 239
Location 194, 198, 202
Location ID 2054, 2055
Location Name 129, 130, 132, 133, 134, 467
locationID 2054, 2055
locationName 129, 130, 132, 133, 134, 467
log-native-calls-to-disk-max-events 2
log-native-calls-to-disk-max-seconds 2
log-native-calls-to-disk-on-error 2
log-native-calls-to-disk-on-success 2
log-native-calls-to-trace 2
Loss Reason 1917, 1918, 1920
Loss Reason Detail 1917, 1918, 1920
lossReason 1917, 1918, 1920
lossReasonDetail 1917, 1918, 1920
Lost Date 1917, 1918, 1920
lostDate 1917, 1918, 1920

- M -

Major Version 61
majorVersion 61
Manufacturer Name 1962, 1963, 1964
Manufacturer Product Name 1962, 1963, 1964
manufacturerName 1962, 1963, 1964
manufacturerProductName 1962, 1963, 1964
Market 1917, 1918, 1920
Market Segment ID 86, 88, 90
marketSegmentID 86, 88, 90
Mark-up Rate 61, 62, 1962, 1963, 1964, 2020, 2022, 2024, 2026, 2114, 2115
markupRate 61, 62, 1962, 1963, 1964, 2020, 2022, 2024, 2026, 2114, 2115
Material Code ID 2124, 2125
materialCodeID 2124, 2125
Maximum Units 256, 257, 259, 261
maximum-discovered-column-count 2
maximum-length-identifiers 2
maximumUnits 256, 257, 259, 261
maximum-url-length 2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

- N -

max-odata-filters 2
max-url-length-accepted 2
max-url-length-desired 2
Memo 2012, 2013, 2014, 2016
Merge Variable Name 2295, 2296
mergeVariableName 2295, 2296
metadata-cache-max-age-sec 2
Middle Initial 105, 107, 109, 235, 237, 239
Middle Name 2054, 2055
middleInitial 105, 107, 109, 235, 237, 239
middleName 2054, 2055
Miles 428, 429, 432, 433
Milestone ID 65, 67
milestoneID 65, 67
Minimum Units 256, 257, 259, 261
minimumUnits 256, 257, 259, 261
Minor Version 61
minorVersion 61
Mobile Phone 105, 107, 109, 235, 237, 239, 2054, 2055
mobilePhone 105, 107, 109, 235, 237, 239, 2054, 2055
Modifier Type 1955, 2304, 2305
Modifier Value 1955, 2304, 2305
modifierType 1955, 2304, 2305
modifierValue 1955, 2304, 2305
Modules 1912
Monday Business Hours End Time 456, 458
Monday Business Hours Start Time 456, 458
Monday Extended Hours End Time 456, 458
Monday Extended Hours Start Time 456, 458
mondayBusinessHoursEndTime 456, 458
mondayBusinessHoursStartTime 456, 458
mondayExtendedHoursEndTime 456, 458
mondayExtendedHoursStartTime 456, 458
Monitor ID 2247, 2250, 2253
Monitor Type ID 2247, 2250, 2253
monitorID 2247, 2250, 2253
monitorTypeID 2247, 2250, 2253
Monthly Cost 194, 198, 202, 1917, 1918, 1920
Monthly Revenue 1917, 1918, 1920
monthlyCost 194, 198, 202, 1917, 1918, 1920
monthlyRevenue 1917, 1918, 1920
MSRP 1962, 1963, 1964

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name 17, 61, 62, 70, 71, 74, 75, 81, 88, 103, 104, 105, 111, 112, 114, 116, 123, 124, 126, 127, 130, 132, 154, 170, 198, 206, 207, 208, 209, 218, 219, 234, 237, 250, 272, 273, 275, 277, 296, 297, 330, 358, 359, 360, 367, 368, 375, 376, 421, 441, 442, 454, 456, 458, 484, 486, 493, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 582, 583, 584, 586, 587, 588, 589, 590, 591, 592, 593, 594, 596, 597, 598, 599, 600, 601, 603, 604, 605, 606, 607, 608, 609, 610, 611, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 642, 643, 644, 645, 646, 647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 659, 660, 661, 662, 663, 664, 665, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 685, 686, 687, 688, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 714, 715, 716, 717, 719, 720, 721, 722, 723, 724, 725, 726, 728, 729, 730, 731, 732, 733, 734, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 762, 763, 764, 765, 766, 767, 768, 770, 771, 772, 773, 774, 775, 776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792, 793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 813, 814, 815, 816, 817, 818, 819, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 844, 845, 846, 847, 848, 849, 850, 851, 852, 853, 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 868, 869, 870, 871, 872, 873, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 902, 903, 904, 906, 907, 908, 909, 910, 911, 912, 913, 914, 916, 917, 918, 919, 920, 921, 923, 924, 925, 926, 927, 928, 929, 930, 931, 933, 934, 935, 936, 937, 938, 940, 941, 942, 943, 944, 945, 946, 947, 948, 950, 951, 952, 953, 954, 955, 956, 957, 959, 960, 961, 962, 963, 964, 965, 967, 968, 969, 970, 971, 972, 974, 975, 976, 977, 978, 979, 980, 982, 983, 984, 985, 986, 987, 988, 989, 991, 992, 993, 994, 995, 996, 997, 999, 1000, 1001, 1002, 1003, 1004, 1005, 1006, 1007, 1008, 1009, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1041, 1042, 1043, 1044, 1045, 1046, 1047, 1048, 1049, 1050, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1070, 1071, 1072, 1073, 1074, 1075, 1076, 1077, 1078, 1079, 1080, 1081, 1082, 1083, 1084, 1085, 1086, 1087, 1089, 1090, 1091, 1092, 1093, 1094, 1096, 1097, 1098, 1099, 1100, 1101, 1102, 1104, 1105, 1106, 1107, 1108, 1109, 1110, 1112, 1113, 1114, 1115, 1116, 1117, 1118, 1120, 1121, 1122, 1123, 1124, 1125, 1126, 1128, 1129, 1130, 1131, 1132,

Name Prefix 105, 107, 109, 235, 237, 239
Name Suffix 105, 107, 109, 235, 237, 239
name_1 1963
namePrefix 105, 107, 109, 235, 237, 239
nameSuffix 105, 107, 109, 235, 237, 239
Native Platform Scalar Requests 1912
NATIVEPLATFORMSCALARREQUESTS 1912
Next Step 1917, 1918, 1920
nextStep 1917, 1918, 1920
Nickname 103, 104, 170, 2195, 2196
No Hours on Holidays 456, 458
noHoursOnHolidays 456, 458
nonBillable 65, 67
Non-billable 65, 67
Non-billable Labor Label 484, 486
nonBillableLaborLabel 484, 486
Note 105, 107, 109, 123, 124, 126, 127, 235, 237, 239
Note or Attachment Title 361, 362, 364
Note Type 185, 186, 187, 189, 1994, 1995, 1997, 1998, 2150, 2151, 2152, 2154, 2227, 2228, 2229, 2231
noteOrAttachmentTitle 361, 362, 364
notes 70, 71, 194, 198, 202, 272, 273, 275, 277, 478, 479, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
noteType 185, 186, 187, 189, 1994, 1995, 1997, 1998, 2150, 2151, 2152, 2154, 2227, 2228, 2229, 2231
Notification Email Address 154, 218, 219, 250, 2241, 2274
Notification History Type ID 1914, 1915
Notification Sent Time 1914, 1915
notificationEmailAddress 154, 218, 219, 250, 2241, 2274
NotificationHistory 1914
NotificationHistoryById 1915
NotificationHistoryCount 1916
NotificationHistoryEntityInformation 1316
NotificationHistoryEntityInformation_FieldsPicklistValuesFields 1316
NotificationHistoryEntityInformation_FieldsPicklistValuesUserDefinedFields 1317
NotificationHistoryEntityInformationFields 1318
NotificationHistoryEntityInformationUserDefinedFields 1319
notificationHistoryTypeID 1914, 1915
notificationSentTime 1914, 1915
npt 1912
Number 367, 368
Number Format 82, 83, 456, 458, 484, 486, 2033, 2034, 2054, 2055
Number of Agents 194, 198, 202
Number of Decimal Places 2295, 2296
Number of Drives 194, 198, 202

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Number of Users 194, 198, 202
Number of Volumes 194, 198, 202
numberFormat 82, 83, 456, 458, 484, 486, 2033, 2034, 2054, 2055
numberOfDecimalPlaces 2295, 2296
numberOfUsers 194, 198, 202

- O -

oauth-unauthorized-max-tries 2
oauth-unauthorized-sleep-initial-ms 2
oauth-unauthorized-sleep-max-ms 2
oauth-unauthorized-sleep-multiplicator 2
Odometer End 428, 429, 432, 433
Odometer Start 428, 429, 432, 433
odometerEnd 428, 429, 432, 433
odometerStart 428, 429, 432, 433
Office Extension 2054, 2055
Office Phone 2054, 2055
officeExtension 2054, 2055
officePhone 2054, 2055
Off-set Hours 2280, 2282
offsetHours 2280, 2282
Off-site Used Bytes 194, 198, 202
One-time Cost 1917, 1918, 1920
One-time Revenue 1917, 1918, 1920
onetimeCost 1917, 1918, 1920
onetimeRevenue 1917, 1918, 1920
onHandUnits 469, 471, 472, 475, 476
Open Alert Count 194, 198, 202
Opportunities 1917
Opportunities_ItemsUserDefinedFields 1918
OpportunitiesById 1920
OpportunitiesByParentId_ItemsUserDefinedFieldsSalesOrders 2078
OpportunitiesByParentIdAttachments 1926
OpportunitiesByParentIdAttachmentsId 1927
OpportunitiesByParentIdSalesOrders 2080
OpportunitiesByParentIdSalesOrdersEntityInformation 1319
OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesFields 1320
OpportunitiesByParentIdSalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields 1322
OpportunitiesByParentIdSalesOrdersEntityInformationFields 1323
OpportunitiesByParentIdSalesOrdersEntityInformationUserDefinedFields 1324
OpportunitiesByParentIdSalesOrdersId 2082
OpportunitiesCount 1923
OpportunitiesEntityInformation 1325
OpportunitiesEntityInformation_FieldsPicklistValuesFields 1326
OpportunitiesEntityInformation_FieldsPicklistValuesUserDefinedFields 1326
OpportunitiesEntityInformationFields 1327
OpportunitiesEntityInformationUserDefinedFields 1328
Opportunity Category ID 1917, 1918, 1920
Opportunity ID 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 123, 124, 126, 127, 139, 140, 142, 144, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 329, 330, 331, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1914, 1915, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 1999, 2001, 2003, 2029, 2031, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2247, 2250, 2253, 2284, 2285, 2287, 2288
OpportunityAttachments 1923
OpportunityAttachmentsById 1924
OpportunityAttachmentsCount 1926
OpportunityAttachmentsEntityInformation 1329
OpportunityAttachmentsEntityInformation_FieldsPicklistValuesFields 1329
OpportunityAttachmentsEntityInformationFields 1330
opportunityCategoryID 1917, 1918, 1920
opportunityID 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 123, 124, 126, 127, 139, 140, 142, 144, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 329, 330, 331, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1914, 1915, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 1999, 2001, 2003, 2029, 2031, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2247, 2250, 2253, 2284, 2285, 2287, 2288
Order ID 2012, 2013, 2014, 2016
Order Number 482, 483
orderID 2012, 2013, 2014, 2016
orderNumber 482, 483
Organizational Level 1 ID 1932, 1933
Organizational Level 2 ID 1932, 1933
Organizational Level Association ID 65, 67, 70, 71, 272, 273, 275, 277, 298, 299, 300, 302, 329, 330, 331, 338, 339, 341, 342, 348, 349, 350, 351, 441, 442, 1917, 1918, 1920, 1934, 1935, 1936, 1981, 1982, 1984, 1986, 1999, 2001, 2003, 2074, 2075, 2076, 2078, 2080, 2082, 2124, 2125, 2197, 2198, 2199, 2200, 2206, 2208, 2210, 2212, 2247, 2250, 2253
organizationalLevel1ID 1932, 1933

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

OrganizationalLevel1s 1929
OrganizationalLevel1sById 1929
OrganizationalLevel1sCount 1930
OrganizationalLevel1sEntityInformation 1331
OrganizationalLevel1sEntityInformation_FieldsPicklistValuesFields 1331
OrganizationalLevel1sEntityInformation_FieldsPicklistValuesUserDefinedFields 1332
OrganizationalLevel1sEntityInformationFields 1333
OrganizationalLevel1sEntityInformationUserDefinedFields 1333
organizationalLevel2ID 1932, 1933
OrganizationalLevel2s 1930
OrganizationalLevel2sById 1931
OrganizationalLevel2sCount 1932
OrganizationalLevel2sEntityInformation 1334
OrganizationalLevel2sEntityInformation_FieldsPicklistValuesFields 1335
OrganizationalLevel2sEntityInformation_FieldsPicklistValuesUserDefinedFields 1335
OrganizationalLevel2sEntityInformationFields 1336
OrganizationalLevel2sEntityInformationUserDefinedFields 1337
organizationalLevelAssociationID 65, 67, 70, 71, 272, 273, 275, 277, 298, 299, 300, 302, 329, 330, 331, 338, 339, 341, 342, 348, 349, 350, 351, 441, 442, 1917, 1918, 1920, 1934, 1935, 1936, 1981, 1982, 1984, 1986, 1999, 2001, 2003, 2074, 2075, 2076, 2078, 2080, 2082, 2124, 2125, 2197, 2198, 2199, 2200, 2206, 2208, 2210, 2212, 2247, 2250, 2253
OrganizationalLevelAssociations 1932
OrganizationalLevelAssociationsById 1933
OrganizationalLevelAssociationsByParentIdResources 1935
OrganizationalLevelAssociationsByParentIdResourcesEntityInformation 1338
OrganizationalLevelAssociationsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields 1339
OrganizationalLevelAssociationsByParentIdResourcesEntityInformationFields 1340
OrganizationalLevelAssociationsByParentIdResourcesEntityInformationUserDefinedFields 1341
OrganizationalLevelAssociationsByParentIdResourcesId 1936
OrganizationalLevelAssociationsCount 1933
OrganizationalLevelAssociationsEntityInformation 1342
OrganizationalLevelAssociationsEntityInformation_FieldsPicklistValuesFields 1343
OrganizationalLevelAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1343
OrganizationalLevelAssociationsEntityInformationFields 1344
OrganizationalLevelAssociationsEntityInformationUserDefinedFields 1345
OrganizationalResources 1934
OrganizationalResourcesById 1934
OrganizationalResourcesCount 1935
OrganizationalResourcesEntityInformation 1346
OrganizationalResourcesEntityInformation_FieldsPicklistValuesFields 1346
OrganizationalResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1347
OrganizationalResourcesEntityInformationFields 1348
OrganizationalResourcesEntityInformationUserDefinedFields 1348
ORIG_SYSTEM_GROUP 1912
ORIG_SYSTEM_REFERENCE 1912
Origin 428, 429, 432, 433
Original Estimated Revenue 1999, 2001, 2003
Original System Group 1912
Original System Reference 1912
originalEstimatedRevenue 1999, 2001, 2003
OS Version ID 194, 198, 202
Our Cost 65, 67
ourCost 65, 67
Overage Billing Rate 329, 330, 331
overageBillingRate 329, 330, 331
Override Company Tax Settings 111, 112, 114, 116
overrideCompanyTaxSettings 111, 112, 114, 116
Owner Resource ID 86, 88, 90, 154, 218, 219, 250, 1917, 1918, 1920, 2074, 2075, 2076, 2078, 2080, 2082, 2241, 2274
ownerResourceID 86, 88, 90, 154, 218, 219, 250, 1917, 1918, 1920, 2074, 2075, 2076, 2078, 2080, 2082, 2241, 2274
OZFS Version ID 194, 198, 202

- P -

Page Layout 484, 486, 2033, 2034
Page Number Format 484, 486, 2033, 2034
pageLayout 484, 486, 2033, 2034
pageNumberFormat 484, 486, 2033, 2034
Paid Date 482, 483
paidDate 482, 483

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parent 4 Value 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809, 1814, 1815, 1819,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parent Attachment ID 58, 59, 97, 98, 100, 102, 160, 162, 163, 165, 1988, 1989, 1991, 1992, 2138, 2139, 2141, 2142, 2189, 2190, 2192, 2193
Parent Category ID 375, 376, 493
Parent Company ID 86, 88, 90
Parent Configuration Item ID 194, 198, 202
Parent ID 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
Parent Phase ID 1939, 1940, 1942, 1943
Parent Type 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288
parentAttachmentID 58, 59, 97, 98, 100, 102, 160, 162, 163, 165, 1988, 1989, 1991, 1992, 2138, 2139, 2141, 2142, 2189, 2190, 2192, 2193
parentCategoryID 375, 376, 493
parentCompanyID 86, 88, 90
parentConfigurationItemID 194, 198, 202

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parentId 22, 23, 25, 27, 30, 34, 35, 38, 39, 43, 44, 47, 48, 51, 52, 55, 57, 58, 59, 78, 79, 95, 96, 97, 98, 100, 102, 105, 107, 109, 114, 116, 117, 118, 120, 122, 126, 127, 132, 133, 134, 137, 138, 142, 144, 147, 148, 151, 153, 158, 159, 160, 162, 163, 165, 169, 174, 177, 178, 179, 180, 182, 183, 187, 189, 192, 193, 208, 212, 216, 217, 223, 224, 227, 228, 231, 232, 243, 244, 247, 249, 254, 255, 259, 261, 264, 265, 269, 270, 275, 277, 281, 282, 285, 286, 290, 291, 294, 295, 300, 302, 303, 304, 306, 308, 312, 313, 316, 318, 321, 323, 326, 327, 336, 337, 341, 342, 345, 347, 350, 351, 355, 356, 369, 370, 372, 374, 379, 380, 383, 384, 388, 391, 393, 396, 397, 401, 402, 405, 407, 410, 411, 414, 415, 418, 419, 422, 423, 425, 427, 432, 433, 435, 436, 438, 440, 446, 447, 465, 466, 475, 476, 490, 491, 553, 554, 555, 556, 558, 576, 577, 579, 580, 581, 582, 583, 584, 586, 587, 588, 589, 590, 591, 592, 593, 594, 596, 597, 598, 599, 600, 601, 603, 604, 605, 606, 607, 608, 609, 610, 611, 613, 614, 615, 655, 656, 657, 659, 660, 661, 662, 663, 664, 665, 667, 668, 669, 670, 671, 685, 686, 687, 688, 709, 710, 712, 713, 714, 715, 716, 717, 719, 720, 721, 722, 723, 724, 725, 726, 728, 729, 730, 731, 732, 733, 734, 754, 755, 756, 757, 758, 759, 760, 762, 763, 764, 765, 766, 767, 768, 784, 785, 786, 787, 788, 793, 794, 795, 796, 797, 809, 810, 811, 813, 814, 815, 816, 817, 818, 819, 821, 822, 823, 824, 825, 862, 863, 864, 865, 866, 868, 869, 870, 871, 872, 896, 897, 899, 900, 901, 902, 903, 904, 906, 907, 908, 909, 910, 911, 912, 913, 914, 916, 917, 918, 919, 920, 921, 923, 924, 925, 926, 927, 928, 929, 930, 931, 933, 934, 935, 936, 937, 938, 940, 941, 942, 943, 944, 945, 946, 947, 948, 950, 951, 952, 953, 954, 955, 956, 957, 959, 960, 961, 962, 963, 964, 965, 967, 968, 969, 970, 971, 972, 974, 975, 976, 977, 978, 979, 980, 982, 983, 984, 985, 986, 987, 988, 989, 991, 992, 993, 994, 995, 996, 997, 1050, 1051, 1052, 1053, 1055, 1081, 1082, 1083, 1084, 1085, 1086, 1087, 1089, 1090, 1091, 1092, 1093, 1094, 1096, 1097, 1098, 1099, 1100, 1101, 1102, 1104, 1105, 1106, 1107, 1108, 1109, 1110, 1112, 1113, 1114, 1115, 1116, 1117, 1118, 1120, 1121, 1122, 1123, 1124, 1125, 1126, 1128, 1129, 1130, 1131, 1132, 1133, 1135, 1136, 1169, 1170, 1171, 1173, 1174, 1178, 1179, 1180, 1182, 1183, 1202, 1203, 1204, 1205, 1206, 1218, 1219, 1220, 1221, 1223, 1224, 1225, 1226, 1227, 1228, 1229, 1230, 1232, 1233, 1234, 1235, 1236, 1237, 1239, 1240, 1269, 1270, 1271, 1272, 1273, 1274, 1276, 1277, 1278, 1279, 1280, 1281, 1282, 1283, 1285, 1286, 1287, 1288, 1289, 1290, 1292, 1293, 1294, 1295, 1296, 1298, 1299, 1300, 1301, 1302, 1303, 1308, 1309, 1310, 1311, 1319, 1320, 1322, 1323, 1324, 1338, 1339, 1340, 1341, 1384, 1385, 1386, 1388, 1389, 1390, 1391, 1392, 1393, 1394, 1395, 1396, 1398, 1399, 1400, 1422, 1423, 1425, 1426, 1427, 1428, 1429, 1430, 1431, 1432, 1434, 1435, 1436, 1437, 1438, 1439, 1440, 1441, 1443, 1444, 1455, 1456, 1458, 1459, 1460, 1465, 1466, 1467, 1468, 1469, 1481, 1482, 1483, 1484, 1485, 1506, 1507, 1508, 1509, 1510, 1512, 1513, 1514, 1515, 1516, 1517, 1518, 1519, 1521, 1522, 1523, 1524, 1525, 1526, 1527, 1529, 1530, 1531, 1532, 1533, 1534, 1535, 1536, 1538, 1539, 1559, 1560, 1562, 1563, 1564, 1572, 1573, 1574, 1576, 1577, 1578, 1579, 1580, 1581, 1582, 1590, 1591, 1593, 1594, 1595, 1603,

parentInventoryStockedItemID 471, 472, 475, 476

parentPhaseID 1939, 1940, 1942, 1943

parentStockedItemReceivedUnits 471, 472, 475, 476

parentType 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 422, 423, 425, 427, 435, 436, 438, 440, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2284, 2285, 2287, 2288

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parentValue 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809, 1814, 1815, 1819,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

partition-slot-based-rate-limit-length-ms 2
partition-slot-based-rate-limit-slots 2
Password 82, 83
Payload 1912, 2302, 2303
PAYLOAD_TEXT 1912
Payment due in Days 1937, 1938
Payment ID 319, 320, 321, 323
Payment Number 267, 269, 270, 319, 320, 321, 323, 352, 353, 355, 356
Payment Term 482, 483, 2017, 2018, 2029, 2031
Payment Terms 484, 486
Payment Type 267, 269, 270, 352, 353, 355, 356, 428, 429, 432, 433, 2029, 2031
paymentDueInDays 1937, 1938
paymentID 319, 320, 321, 323
paymentNumber 267, 269, 270, 319, 320, 321, 323, 352, 353, 355, 356
paymentTerm 482, 483, 2017, 2018, 2029, 2031
PaymentTerms 484, 486, 1937
PaymentTermsById 1938
PaymentTermsCount 1939
PaymentTermsEntityInformation 1349
PaymentTermsEntityInformation_FieldsPicklistValues Fields 1350
PaymentTermsEntityInformation_FieldsPicklistValues UserDefinedFields 1350
PaymentTermsEntityInformationFields 1351
PaymentTermsEntityInformationUserDefinedFields 1352
paymentType 267, 269, 270, 352, 353, 355, 356, 428, 429, 432, 433, 2029, 2031
Payroll Type 2054, 2055
payrollType 2054, 2055
Per Ticket Rate 352, 353, 355, 356
Per Use Cost 194, 198, 202
Percentage Used 194, 198, 202
percentageDiscount 2020, 2022, 2024, 2026, 2084
Period Cost 2120, 2122, 2123, 2124, 2125
Period Date 2120, 2122, 2123
Period Price 2120, 2122, 2123, 2124, 2125
Period Type 1962, 1963, 1964, 2020, 2022, 2024, 2026, 2084, 2114, 2115, 2124, 2125
periodCost 2120, 2122, 2123, 2124, 2125
periodDate 2120, 2122, 2123
periodPrice 2120, 2122, 2123, 2124, 2125
periodType 1962, 1963, 1964, 2020, 2022, 2024, 2026, 2084, 2114, 2115, 2124, 2125
perTicketRate 352, 353, 355, 356
perUseCost 194, 198, 202
Phase ID 2159, 2161, 2163, 2165, 2167, 2169
Phase Number 1939, 1940, 1942, 1943
phaseID 2159, 2161, 2163, 2165, 2167, 2169
phaseNumber 1939, 1940, 1942, 1943
Phases 1939
PhasesById 1940
PhasesCount 1941
PhasesEntityInformation 1353
PhasesEntityInformation_FieldsPicklistValuesFields 1353
PhasesEntityInformation_FieldsPicklistValuesUserDefinedFields 1354
PhasesEntityInformationFields 1355
PhasesEntityInformationUserDefinedFields 1355
Phone 86, 88, 90, 105, 107, 109, 111, 112, 114, 116, 235, 237, 239, 2017, 2018

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Pick List Parent Value Field 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

pickedRemovedByResourceID 471, 472, 475, 476
pickedRemovedDateTime 471, 472, 475, 476
pickedUnits 469, 471, 472, 475, 476

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

picklistParentValueField 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 512, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256,

Position 76, 77, 78, 79, 377, 379, 380, 2214, 2216, 2217

Postal Code 86, 88, 90, 111, 112, 114, 116, 454, 456, 458, 2027, 2028

postalCode 86, 88, 90, 111, 112, 114, 116, 454, 456, 458, 2027, 2028

Posted 65, 67, 2120, 2122, 2123

Posted on-time 65, 67

postedDate 65, 67, 2120, 2122, 2123

postedOnTime 65, 67

Pre-decessor Task ID 2155, 2156, 2157, 2158

predecessorTaskID 2155, 2156, 2157, 2158

Pre-request-delay-ms 2

Previous Service Thermometer Rating 2247, 2250, 2253

previousServiceThermometerRating 2247, 2250, 2253

Price 338, 339, 341, 342, 348, 349, 350, 351

Price Cost Method 1962, 1963, 1964

priceCostMethod 1962, 1963, 1964

PriceListMaterialCodes 1944

PriceListMaterialCodesById 1945

PriceListMaterialCodesCount 1946

PriceListMaterialCodesEntityInformation 1356

PriceListMaterialCodesEntityInformation_FieldsPicklistValuesFields 1357

PriceListMaterialCodesEntityInformation_FieldsPicklistValuesUserDefinedFields 1357

PriceListMaterialCodesEntityInformationFields 1358

PriceListMaterialCodesEntityInformationUserDefinedFields 1359

PriceListProducts 1946

PriceListProductsById 1946

PriceListProductsCount 1947

PriceListProductsEntityInformation 1360

PriceListProductsEntityInformation_FieldsPicklistValuesFields 1360

PriceListProductsEntityInformation_FieldsPicklistValuesUserDefinedFields 1361

PriceListProductsEntityInformationFields 1362

PriceListProductsEntityInformationUserDefinedFields 1362

PriceListProductTiers 1948

PriceListProductTiersById 1948

PriceListProductTiersCount 1949

PriceListProductTiersEntityInformation 1363

PriceListProductTiersEntityInformation_FieldsPicklistValuesFields 1364

PriceListProductTiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1364

PriceListProductTiersEntityInformationFields 1365

PriceListProductTiersEntityInformationUserDefinedFields 1366

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

PriceListRoles 1950
PriceListRolesById 1950
PriceListRolesCount 1951
PriceListRolesEntityInformation 1367
PriceListRolesEntityInformation_FieldsPicklistValuesFields 1367
PriceListRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1368
PriceListRolesEntityInformationFields 1369
PriceListRolesEntityInformationUserDefinedFields 1369
PriceListServiceBundles 1952
PriceListServiceBundlesById 1952
PriceListServiceBundlesCount 1953
PriceListServiceBundlesEntityInformation 1370
PriceListServiceBundlesEntityInformation_FieldsPicklistValuesFields 1371
PriceListServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields 1371
PriceListServiceBundlesEntityInformationFields 1372
PriceListServiceBundlesEntityInformationUserDefinedFields 1373
PriceListServices 1953
PriceListServicesById 1954
PriceListServicesCount 1955
PriceListServicesEntityInformation 1374
PriceListServicesEntityInformation_FieldsPicklistValuesFields 1374
PriceListServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1375
PriceListServicesEntityInformationFields 1376
PriceListServicesEntityInformationUserDefinedFields 1376
PriceListWorkTypeModifiers 1955
PriceListWorkTypeModifiersById 1955
PriceListWorkTypeModifiersCount 1956
PriceListWorkTypeModifiersEntityInformation 1377
PriceListWorkTypeModifiersEntityInformation_FieldsPicklistValuesFields 1378
PriceListWorkTypeModifiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1378
PriceListWorkTypeModifiersEntityInformationFields 1379
PriceListWorkTypeModifiersEntityInformationUserDefinedFields 1380
Primary Competitor 1917, 1918, 1920
Primary Contact 105, 107, 109, 235, 237, 239
Primary Location ID 367, 368
Primary Quote 2029, 2031
primaryCompetitor 1917, 1918, 1920
primaryContact 105, 107, 109, 235, 237, 239
primaryLocationID 367, 368
primaryQuote 2029, 2031
Priority 2159, 2161, 2163, 2165, 2167, 2169, 2197, 2198, 2199, 2200, 2247, 2250, 2253
Priority Label 2159, 2161, 2163, 2165, 2167, 2169
priorityLabel 2159, 2161, 2163, 2165, 2167, 2169
Probability 1917, 1918, 1920
Problem Ticket ID 2247, 2250, 2253
problemOrIncidentTicketID 73
problemTicketId 2247, 2250, 2253
Product Billing Code ID 1962, 1963, 1964
Product Category 1962, 1963, 1964
Product ID 70, 71, 194, 198, 202, 256, 257, 259, 261, 272, 273, 275, 277, 461, 469, 478, 479, 1917, 1918, 1920, 1946, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1981, 1982, 1984, 1986, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2206, 2208, 2210, 2212
productBillingCodeID 1962, 1963, 1964
productCategory 1962, 1963, 1964
productID 70, 71, 194, 198, 202, 256, 257, 259, 261, 272, 273, 275, 277, 461, 469, 478, 479, 1917, 1918, 1920, 1946, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1981, 1982, 1984, 1986, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2206, 2208, 2210, 2212
ProductNotes 1957
ProductNotesById 1958
ProductNotesCount 1959
ProductNotesEntityInformation 1381
ProductNotesEntityInformation_FieldsPicklistValuesFields 1381
ProductNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1382
ProductNotesEntityInformationFields 1383
ProductNotesEntityInformationUserDefinedFields 1383
Products 1962
Products_ItemsUserDefinedFields 1963
ProductsById 1964
ProductsByParentIdNotes 1959
ProductsByParentIdNotesEntityInformation 1384
ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1385
ProductsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1386
ProductsByParentIdNotesEntityInformationFields 1388
ProductsByParentIdNotesEntityInformationUserDefinedFields 1389
ProductsByParentIdNotesId 1960
ProductsByParentIdTiers 1968
ProductsByParentIdTiersEntityInformation 1390
ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesFields 1391

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ProductsByParentIdTiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1392
ProductsByParentIdTiersEntityInformationFields 1393
ProductsByParentIdTiersEntityInformationUserDefinedFields 1394
ProductsByParentIdTiersId 1969
ProductsByParentIdVendors 1972
ProductsByParentIdVendorsEntityInformation 1395
ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesFields 1396
ProductsByParentIdVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields 1398
ProductsByParentIdVendorsEntityInformationFields 1399
ProductsByParentIdVendorsEntityInformationUserDefinedFields 1400
ProductsByParentIdVendorsId 1973
ProductsCount 1965
ProductsEntityInformation 1401
ProductsEntityInformation_FieldsPicklistValuesFields 1402
ProductsEntityInformation_FieldsPicklistValuesUserDefinedFields 1402
ProductsEntityInformationFields 1403
ProductsEntityInformationUserDefinedFields 1404
Product-tier ID 1948
productTierID 1948
ProductTiers 1966
ProductTiersById 1966
ProductTiersCount 1967
ProductTiersEntityInformation 1404
ProductTiersEntityInformation_FieldsPicklistValuesFields 1405
ProductTiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1406
ProductTiersEntityInformationFields 1407
ProductTiersEntityInformationUserDefinedFields 1407
ProductVendors 1970
ProductVendorsById 1971
ProductVendorsCount 1972
ProductVendorsEntityInformation 1408
ProductVendorsEntityInformation_FieldsPicklistValuesFields 1409
ProductVendorsEntityInformation_FieldsPicklistValuesUserDefinedFields 1409
ProductVendorsEntityInformationFields 1410
ProductVendorsEntityInformationUserDefinedFields 1411
Project Charge ID 65, 67, 471, 472, 475, 476
Project Cost Estimated Margin Percentage 1999, 2001, 2003
Project Costs Budget 1999, 2001, 2003
Project Costs Revenue 1999, 2001, 2003
Project ID 58, 59, 65, 67, 428, 429, 432, 433, 1914, 1915, 1939, 1940, 1942, 1943, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2012, 2013, 2014, 2016, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
Project Lead Resource ID 1999, 2001, 2003
Project Name 1999, 2001, 2003
Project Note ID 58, 59, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992
Project Number 1999, 2001, 2003
Project or Incident Ticket ID 73
Project Type 1999, 2001, 2003
ProjectAttachments 1975
ProjectAttachmentsById 1976
ProjectAttachmentsCount 1977
ProjectAttachmentsEntityInformation 1411
ProjectAttachmentsEntityInformation_FieldsPicklistValuesFields 1412
ProjectAttachmentsEntityInformationFields 1413
projectChargeID 65, 67, 471, 472, 475, 476
ProjectCharges 1981
ProjectChargesById 1982
ProjectChargesCount 1984
ProjectChargesEntityInformation 1413
ProjectChargesEntityInformation_FieldsPicklistValuesFields 1414
ProjectChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 1415
ProjectChargesEntityInformationFields 1416
ProjectChargesEntityInformationUserDefinedFields 1416
projectCostEstimatedMarginPercentage 1999, 2001, 2003
projectCostsBudget 1999, 2001, 2003
projectCostsRevenue 1999, 2001, 2003
Projected Close Date 1917, 1918, 1920
projectedCloseDate 1917, 1918, 1920
projectID 58, 59, 65, 67, 428, 429, 432, 433, 1914, 1915, 1939, 1940, 1942, 1943, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2012, 2013, 2014, 2016, 2159, 2161, 2163, 2165, 2167, 2169, 2247, 2250, 2253
projectLeadResourceID 1999, 2001, 2003
projectName 1999, 2001, 2003
ProjectNoteAttachments 1988
ProjectNoteAttachmentsById 1989
ProjectNoteAttachmentsCount 1991
ProjectNoteAttachmentsEntityInformation 1417

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ProjectNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 1417
ProjectNoteAttachmentsEntityInformationFields 1418
projectNoteID 58, 59, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992
ProjectNotes 1994
ProjectNotesById 1995
ProjectNotesByParentIdAttachments 1991
ProjectNotesByParentIdAttachmentsId 1992
ProjectNotesCount 1996
ProjectNotesEntityInformation 1419
ProjectNotesEntityInformation_FieldsPicklistValuesFields 1419
ProjectNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1420
ProjectNotesEntityInformationFields 1421
ProjectNotesEntityInformationUserDefinedFields 1422
projectNumber 1999, 2001, 2003
Projects 1999
Projects_ItemsUserDefinedFields 2001
ProjectsById 2003
ProjectsByParentId_ItemsUserDefinedFieldsTasks 2165
ProjectsByParentIdAttachments 1978
ProjectsByParentIdAttachmentsId 1979
ProjectsByParentIdCharges 1984
ProjectsByParentIdChargesEntityInformation 1422
ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesFields 1423
ProjectsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 1425
ProjectsByParentIdChargesEntityInformationFields 1426
ProjectsByParentIdChargesEntityInformationUserDefinedFields 1427
ProjectsByParentIdChargesId 1986
ProjectsByParentIdNotes 1997
ProjectsByParentIdNotesEntityInformation 1428
ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1429
ProjectsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1430
ProjectsByParentIdNotesEntityInformationFields 1431
ProjectsByParentIdNotesEntityInformationUserDefinedFields 1432
ProjectsByParentIdNotesId 1998
ProjectsByParentIdPhases 1942
ProjectsByParentIdPhasesEntityInformation 1434
ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesFields 1435
ProjectsByParentIdPhasesEntityInformation_FieldsPicklistValuesUserDefinedFields 1436
ProjectsByParentIdPhasesEntityInformationFields 1437
ProjectsByParentIdPhasesEntityInformationUserDefinedFields 1438
ProjectsByParentIdPhasesId 1943
ProjectsByParentIdTasks 2167
ProjectsByParentIdTasksEntityInformation 1439
ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesFields 1440
ProjectsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields 1441
ProjectsByParentIdTasksEntityInformationFields 1443
ProjectsByParentIdTasksEntityInformationUserDefinedFields 1444
ProjectsByParentIdTasksId 2169
ProjectsCount 2005
ProjectsEntityInformation 1445
ProjectsEntityInformation_FieldsPicklistValuesFields 1445
ProjectsEntityInformation_FieldsPicklistValuesUserDefinedFields 1446
ProjectsEntityInformationFields 1447
ProjectsEntityInformationUserDefinedFields 1448
projectType 1999, 2001, 2003
Promised Fulfillment Date 1917, 1918, 1920, 2074, 2075, 2076, 2078, 2080, 2082
promisedFulfillmentDate 1917, 1918, 1920, 2074, 2075, 2076, 2078, 2080, 2082
Promotion Name 1917, 1918, 1920
promotionName 1917, 1918, 1920
Proposal Project ID 2029, 2031
proposalProjectID 2029, 2031
Protected Kilobytes 194, 198, 202
Publish 22, 23, 25, 27, 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 303, 304, 306, 308, 369, 370, 372, 374, 398, 399, 401, 402, 422, 423, 425, 427, 435, 436, 438, 440, 488, 490, 491, 1923, 1924, 1926, 1927, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2036, 2037, 2038, 2040, 2068, 2069, 2071, 2072, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2284, 2285, 2287, 2288
Purchase Date 70, 71, 267, 269, 270, 272, 273, 275, 277, 319, 320, 321, 323, 352, 353, 355, 356, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
Purchase for Company ID 2017, 2018
Purchase Order Item ID 471, 472, 475, 476, 2007, 2009, 2010

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Purchase Order Number 65, 67, 70, 71, 272, 273, 275, 277, 329, 330, 331, 428, 429, 432, 433, 1981, 1982, 1984, 1986, 1999, 2001, 2003, 2017, 2018, 2029, 2031, 2120, 2122, 2123, 2124, 2125, 2159, 2161, 2163, 2165, 2167, 2169, 2197, 2198, 2199, 2200, 2206, 2208, 2210, 2212, 2247, 2250, 2253
Purchase Order Template ID 86, 88, 90, 358, 2017, 2018
PurchaseApprovals 2005
PurchaseApprovalsById 2005
PurchaseApprovalsCount 2006
PurchaseApprovalsEntityInformation 1448
PurchaseApprovalsEntityInformation_FieldsPicklistValuesFields 1449
PurchaseApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields 1450
PurchaseApprovalsEntityInformationFields 1451
PurchaseApprovalsEntityInformationUserDefinedFields 1451
purchaseForCompanyID 2017, 2018
purchaseOrderID 471, 472, 475, 476
purchaseOrderItemID 471, 472, 475, 476, 2007, 2009, 2010
PurchaseOrderItemReceiving 2007
PurchaseOrderItemReceivingById 2007
PurchaseOrderItemReceivingCount 2009
PurchaseOrderItemReceivingEntityInformation 1452
PurchaseOrderItemReceivingEntityInformation_FieldsPicklistValuesFields 1452
PurchaseOrderItemReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields 1453
PurchaseOrderItemReceivingEntityInformationFields 1454
PurchaseOrderItemReceivingEntityInformationUserDefinedFields 1455
purchaseOrderItemReceivingID 471, 472, 475, 476
PurchaseOrderItems 2012
PurchaseOrderItemsById 2013
PurchaseOrderItemsByParentIdReceiving 2009
PurchaseOrderItemsByParentIdReceivingEntityInformation 1455
PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesFields 1456
PurchaseOrderItemsByParentIdReceivingEntityInformation_FieldsPicklistValuesUserDefinedFields 1458
PurchaseOrderItemsByParentIdReceivingEntityInformationFields 1459
PurchaseOrderItemsByParentIdReceivingEntityInformationUserDefinedFields 1460
PurchaseOrderItemsByParentIdReceivingId 2010
PurchaseOrderItemsCount 2014
PurchaseOrderItemsEntityInformation 1461
PurchaseOrderItemsEntityInformation_FieldsPicklistValuesFields 1462
PurchaseOrderItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1463
PurchaseOrderItemsEntityInformationFields 1463
PurchaseOrderItemsEntityInformationUserDefinedFields 1464
purchaseOrderNumber 65, 67, 70, 71, 272, 273, 275, 277, 329, 330, 331, 428, 429, 432, 433, 1981, 1982, 1984, 1986, 1999, 2001, 2003, 2017, 2018, 2029, 2031, 2120, 2122, 2123, 2124, 2125, 2159, 2161, 2163, 2165, 2167, 2169, 2197, 2198, 2199, 2200, 2206, 2208, 2210, 2212, 2247, 2250, 2253
PurchaseOrders 2017
PurchaseOrdersById 2018
PurchaseOrdersByParentIdItems 2014
PurchaseOrdersByParentIdItemsEntityInformation 1465
PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesFields 1466
PurchaseOrdersByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1467
PurchaseOrdersByParentIdItemsEntityInformationFields 1468
PurchaseOrdersByParentIdItemsEntityInformationUserDefinedFields 1469
PurchaseOrdersByParentIdItemsId 2016
PurchaseOrdersCount 2020
PurchaseOrdersEntityInformation 1470
PurchaseOrdersEntityInformation_FieldsPicklistValuesFields 1471
PurchaseOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields 1472
PurchaseOrdersEntityInformationFields 1473
PurchaseOrdersEntityInformationUserDefinedFields 1473
purchaseOrderTemplateID 86, 88, 90, 358, 2017, 2018

- Q -

Quantity 65, 67, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026
Quantity Backordered 2007, 2009, 2010
Quantity Maximum 461, 469
Quantity Minimum 461, 469
Quantity Now Receiving 2007, 2009, 2010
Quantity On Order 461
Quantity On-hand 461
Quantity Picked 461
Quantity Previously Received 2007, 2009, 2010
Quantity Reserved 461
Quantity Transferred 478, 479
quantityBackOrdered 2007, 2009, 2010
quantityMaximum 461, 469

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

quantityMinimum 461, 469
quantityNowReceiving 2007, 2009, 2010
quantityOnHand 461
quantityOnOrder 461
quantityPicked 461
quantityPreviouslyReceived 2007, 2009, 2010
quantityReserved 461
quantityTransferred 478, 479
Quarterly Cost 1917, 1918, 1920
Quarterly Revenue 1917, 1918, 1920
quarterlyCost 1917, 1918, 1920
quarterlyRevenue 1917, 1918, 1920
Query Count 18, 20, 22, 25, 30, 33, 38, 42, 47, 51, 55, 61, 63, 65, 69, 72, 74, 76, 78, 82, 84, 86, 92, 94, 100, 105, 114, 120, 126, 131, 137, 142, 147, 151, 156, 158, 163, 168, 171, 173, 176, 181, 187, 192, 206, 207, 210, 212, 215, 220, 222, 227, 231, 235, 241, 243, 247, 252, 254, 259, 264, 269, 275, 281, 285, 289, 294, 297, 300, 306, 311, 316, 321, 326, 333, 335, 340, 345, 350, 355, 359, 361, 363, 365, 367, 369, 372, 376, 378, 383, 387, 391, 395, 400, 405, 409, 414, 418, 422, 425, 431, 438, 443, 445, 449, 451, 453, 455, 460, 462, 464, 468, 471, 474, 480, 484, 487, 490, 494, 1916, 1923, 1926, 1930, 1932, 1933, 1935, 1939, 1941, 1946, 1947, 1949, 1951, 1953, 1955, 1956, 1959, 1965, 1967, 1972, 1977, 1984, 1991, 1996, 2005, 2006, 2009, 2014, 2020, 2024, 2029, 2033, 2035, 2038, 2043, 2048, 2052, 2057, 2059, 2063, 2068, 2070, 2078, 2085, 2087, 2092, 2094, 2098, 2103, 2107, 2111, 2116, 2118, 2119, 2121, 2126, 2128, 2130, 2132, 2136, 2138, 2141, 2147, 2152, 2157, 2164, 2173, 2176, 2178, 2180, 2182, 2186, 2192, 2196, 2199, 2204, 2210, 2216, 2220, 2223, 2229, 2234, 2238, 2243, 2245, 2256, 2258, 2263, 2267, 2271, 2276, 2278, 2283, 2286, 2292, 2297, 2300, 2304, 2305
queryCount 18, 20, 22, 25, 30, 33, 38, 42, 47, 51, 55, 61, 63, 65, 69, 72, 74, 76, 78, 82, 84, 86, 92, 94, 100, 105, 114, 120, 126, 131, 137, 142, 147, 151, 156, 158, 163, 168, 171, 173, 176, 181, 187, 192, 206, 207, 210, 212, 215, 220, 222, 227, 231, 235, 241, 243, 247, 252, 254, 259, 264, 269, 275, 281, 285, 289, 294, 297, 300, 306, 311, 316, 321, 326, 333, 335, 340, 345, 350, 355, 359, 361, 363, 365, 367, 369, 372, 376, 378, 383, 387, 391, 395, 400, 405, 409, 414, 418, 422, 425, 431, 438, 443, 445, 449, 451, 453, 455, 460, 462, 464, 468, 471, 474, 480, 484, 487, 490, 494, 1916, 1923, 1926, 1930, 1932, 1933, 1935, 1939, 1941, 1946, 1947, 1949, 1951, 1953, 1955, 1956, 1959, 1965, 1967, 1972, 1977, 1984, 1991, 1996, 2005, 2006, 2009, 2014, 2020, 2024, 2029, 2033, 2035, 2038, 2043, 2048, 2052, 2057, 2059, 2063, 2068, 2070, 2078, 2085, 2087, 2092, 2094, 2098, 2103, 2107, 2111, 2116, 2118, 2119, 2121, 2126, 2128, 2130, 2132, 2136, 2138, 2141, 2147, 2152, 2157, 2164, 2173, 2176, 2178, 2180, 2182, 2186, 2192, 2196, 2199, 2204, 2210, 2216, 2220, 2223, 2229, 2234, 2238, 2243, 2245, 2256, 2258, 2263, 2267, 2271, 2276, 2278, 2283, 2286, 2292, 2297, 2300, 2304, 2305
Queue ID 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2053, 2197, 2198, 2199, 2200, 2247, 2250, 2253
queueID 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2053, 2197, 2198, 2199, 2200, 2247, 2250, 2253
Quickbooks Reference Number 441, 442
quickBooksReferenceNumber 441, 442
Quote Email Message ID 86, 88, 90
Quote ID 1914, 1915, 2020, 2022, 2024, 2026
Quote Item Default Tax Category ID 2066, 2067
Quote Item ID 333, 334, 336, 337, 343, 344, 345, 347, 471, 472, 475, 476
Quote Item Type 2020, 2022, 2024, 2026
Quote Number 2029, 2031
Quote Template ID 86, 88, 90, 358, 2029, 2031
quoteEmailMessageID 86, 88, 90
quoteID 1914, 1915, 2020, 2022, 2024, 2026
quoteItemDefaultTaxCategoryId 2066, 2067
quoteItemID 333, 334, 336, 337, 343, 344, 345, 347, 471, 472, 475, 476
QuoteItems 2020
QuoteItemsById 2022
QuoteItemsCount 2024
QuoteItemsEntityInformation 1474
QuoteItemsEntityInformation_FieldsPicklistValuesFields 1474
QuoteItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1475
QuoteItemsEntityInformationFields 1476
QuoteItemsEntityInformationUserDefinedFields 1477
quoteItemType 2020, 2022, 2024, 2026
QuoteLocations 2027

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

QuoteLocationsById 2028
QuoteLocationsCount 2029
QuoteLocationsEntityInformation 1477
QuoteLocationsEntityInformation_FieldsPicklistValuesFields 1478
QuoteLocationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1479
QuoteLocationsEntityInformationFields 1480
QuoteLocationsEntityInformationUserDefinedFields 1480
quoteNumber 2029, 2031
Quotes 2029
QuotesById 2031
QuotesByParentIdItems 2024
QuotesByParentIdItemsEntityInformation 1481
QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesFields 1482
QuotesByParentIdItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1483
QuotesByParentIdItemsEntityInformationFields 1484
QuotesByParentIdItemsEntityInformationUserDefinedFields 1485
QuotesByParentIdItemsId 2026
QuotesCount 2033
QuotesEntityInformation 1486
QuotesEntityInformation_FieldsPicklistValuesFields 1487
QuotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1488
QuotesEntityInformationFields 1489
QuotesEntityInformationUserDefinedFields 1489
quoteTemplateID 86, 88, 90, 358, 2029, 2031
QuoteTemplates 2033
QuoteTemplatesById 2034
QuoteTemplatesCount 2035
QuoteTemplatesEntityInformation 1490
QuoteTemplatesEntityInformation_FieldsPicklistValuesFields 1491
QuoteTemplatesEntityInformation_FieldsPicklistValuesUserDefinedFields 1491
QuoteTemplatesEntityInformationFields 1492
QuoteTemplatesEntityInformationUserDefinedFields 1493

- R -

Rate 65, 67, 324, 325, 326, 327
Rate Cost Expression 484, 486
rateCostExpression 484, 486
Rating 1917, 1918, 1920
Reason 2290, 2291, 2293, 2294
Receive Date 2007, 2009, 2010
Received by Resource ID 2007, 2009, 2010
receiveDate 2007, 2009, 2010
receivedByResourceID 2007, 2009, 2010
Receives Email Notification 105, 107, 109, 235, 237, 239
receivesEmailNotifications 105, 107, 109, 235, 237, 239
Recipient Display Name 1914, 1915
Recipient Email Address 1914, 1915
recipientDisplayName 1914, 1915
recipientEmailAddress 1914, 1915

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Reference Entity Type 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Reference Link 398, 399, 401, 402, 488, 490, 491
Reference Number 194, 198, 202, 461, 469
Reference Title 194, 198, 202
Reference URL 450, 452

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

referenceEntityType 495, 496, 497, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 533, 534, 535, 536, 537, 538, 540, 541, 542, 543, 544, 545, 547, 548, 549, 550, 551, 552, 554, 555, 556, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 579, 580, 581, 583, 584, 586, 587, 589, 590, 591, 592, 594, 596, 597, 598, 600, 601, 603, 604, 606, 607, 608, 609, 611, 613, 614, 615, 617, 618, 619, 620, 621, 622, 624, 626, 627, 628, 629, 630, 631, 633, 635, 636, 637, 638, 639, 640, 642, 643, 644, 645, 646, 647, 649, 650, 651, 652, 653, 654, 656, 657, 659, 660, 662, 663, 664, 665, 668, 669, 670, 671, 674, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 690, 691, 692, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 712, 713, 715, 716, 717, 719, 721, 722, 723, 724, 726, 728, 729, 730, 732, 733, 734, 736, 737, 738, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 751, 752, 753, 755, 756, 757, 759, 760, 762, 763, 765, 766, 767, 768, 770, 771, 772, 774, 775, 776, 777, 778, 779, 781, 782, 783, 785, 786, 787, 788, 790, 791, 792, 794, 795, 796, 797, 799, 800, 801, 803, 804, 805, 806, 807, 808, 810, 811, 813, 814, 816, 817, 818, 819, 822, 823, 824, 825, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 845, 846, 847, 848, 849, 850, 852, 853, 854, 855, 856, 857, 859, 860, 861, 863, 864, 865, 866, 869, 870, 871, 872, 874, 875, 876, 877, 878, 879, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 899, 900, 901, 903, 904, 906, 907, 909, 910, 911, 912, 914, 916, 917, 918, 920, 921, 923, 924, 926, 927, 928, 929, 931, 933, 934, 935, 937, 938, 940, 941, 943, 944, 945, 946, 948, 950, 951, 952, 954, 955, 956, 957, 960, 961, 962, 963, 965, 967, 968, 969, 971, 972, 974, 975, 977, 978, 979, 980, 983, 984, 985, 986, 988, 989, 991, 992, 994, 995, 996, 997, 999, 1000, 1001, 1003, 1004, 1005, 1006, 1007, 1008, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1042, 1043, 1044, 1045, 1046, 1047, 1049, 1051, 1052, 1053, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1071, 1072, 1073, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1085, 1087, 1089, 1090, 1091, 1093, 1094, 1096, 1097, 1099, 1100, 1101, 1102, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1115, 1116, 1117, 1118, 1121, 1122, 1123, 1124, 1126, 1128, 1129, 1130, 1132, 1133, 1135, 1136, 1137, 1138, 1139, 1140, 1141, 1142, 1143, 1144, 1145, 1146, 1147, 1148, 1149, 1150, 1152, 1153, 1154, 1155, 1156, 1157, 1159, 1161, 1162, 1163, 1164, 1165, 1166, 1167, 1168, 1170, 1171, 1173, 1174, 1175, 1176, 1177, 1179, 1180, 1182, 1183, 1184, 1185, 1186, 1187, 1188, 1189, 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1199, 1200, 1201, 1203, 1204, 1205, 1206, 1208, 1209, 1210, 1211, 1212, 1213, 1214, 1215, 1216, 1217, 1219, 1220, 1221, 1223, 1225, 1226, 1227, 1228, 1230, 1232, 1233, 1234, 1236, 1237, 1239, 1240, 1242, 1243, 1244, 1245, 1246, 1247, 1249, 1250, 1251, 1252, 1253, 1254, 1256,

referenceLink 398, 399, 401, 402, 488, 490, 491

referenceNumber 194, 198, 202, 461, 469

referenceTitle 194, 198, 202

referenceUrl 450, 452

Reimbursement Currency Amount Due 441, 442

Reimbursement Currency and Amount 428, 429, 432, 433

Reimbursement Currency Cash Advance Amount 441, 442

Reimbursement Currency ID 441, 442

reimbursementCurrencyAmountDue 441, 442

reimbursementCurrencyCashAdvanceAmount 441, 442

reimbursementCurrencyID 441, 442

reimbursementCurrencyReimbursementAmount 428, 429, 432, 433

Reject Note 2005

Reject Reason 2290, 2291, 2293, 2294

Rejection Reason 441, 442

rejectionReason 441, 442

rejectNote 2005

rejectReason 2290, 2291, 2293, 2294

Related Configuration Item ID 190, 191, 192, 193

relatedConfigurationItemID 190, 191, 192, 193

Relationship 190, 191, 192, 193

Relationship Assessment Score 1917, 1918, 1920

relationshipAssessmentScore 1917, 1918, 1920

Relative URL 81

relativeUrl 81

Remaining Hours 2159, 2161, 2163, 2165, 2167, 2169

remainingHours 2159, 2161, 2163, 2165, 2167, 2169

Remote IP 194, 198, 202

removedUnits 471, 472, 475, 476

Renewed Contract ID 329, 330, 331

renewedContractID 329, 330, 331

Request Date 2290, 2291, 2293, 2294

Request Threshold Timeframe 2180

requestDate 2290, 2291, 2293, 2294

requested-page-size 2

requests-parallel-max 2

requestThresholdTimeframe 2180

reservedUnits 469, 471, 472, 475, 476

Resolution 2197, 2198, 2199, 2200, 2247, 2250, 2253

Resolution Elapsed Hours 2109, 2110, 2112, 2113

Resolution Plan Date/Time 2247, 2250, 2253

Resolution Plan Due Date/Time 2247, 2250, 2253

Resolution Plan Elapsed Hours 2109, 2110, 2112, 2113

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Resolution Plan Resource ID 2109, 2110, 2112, 2113
Resolution Resource ID 2109, 2110, 2112, 2113
resolutionElapsedHours 2109, 2110, 2112, 2113
resolutionPlanDateTime 2247, 2250, 2253
resolutionPlanDueDateTime 2247, 2250, 2253
resolutionPlanElapsedHours 2109, 2110, 2112, 2113
resolutionPlanResourceID 2109, 2110, 2112, 2113
resolutionResourceID 2109, 2110, 2112, 2113
Resolved Date/Time 2247, 2250, 2253
Resolved Due Date/Time 2247, 2250, 2253
resolvedDateTime 2247, 2250, 2253
resolvedDueDateTime 2247, 2250, 2253
Resource ID 20, 21, 58, 59, 84, 85, 135, 136, 137, 138, 145, 146, 147, 148, 210, 211, 212, 241, 242, 243, 244, 324, 325, 326, 327, 467, 1934, 1935, 1936, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2053, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2092, 2093, 2094, 2095, 2101, 2103, 2104, 2171, 2172, 2173, 2174, 2202, 2203, 2204, 2205, 2219, 2220, 2232, 2233, 2234, 2235, 2256, 2257, 2259, 2260, 2265, 2266, 2267, 2268, 2280, 2282, 2290, 2291, 2293, 2294
Resource Rating 2127
Resource Type 2054, 2055
ResourceAttachments 2036
ResourceAttachmentsById 2037
ResourceAttachmentsCount 2038
ResourceAttachmentsEntityInformation 1493
ResourceAttachmentsEntityInformation_FieldsPicklistValuesFields 1494
ResourceAttachmentsEntityInformationFields 1495
resourceID 20, 21, 58, 59, 84, 85, 135, 136, 137, 138, 145, 146, 147, 148, 210, 211, 212, 241, 242, 243, 244, 324, 325, 326, 327, 467, 1934, 1935, 1936, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2050, 2051, 2052, 2053, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2092, 2093, 2094, 2095, 2101, 2103, 2104, 2171, 2172, 2173, 2174, 2202, 2203, 2204, 2205, 2219, 2220, 2232, 2233, 2234, 2235, 2256, 2257, 2259, 2260, 2265, 2266, 2267, 2268, 2280, 2282, 2290, 2291, 2293, 2294
resourceRating 2127
ResourceRoleDepartments 2041
ResourceRoleDepartmentsById 2042
ResourceRoleDepartmentsCount 2043
ResourceRoleDepartmentsEntityInformation 1495
ResourceRoleDepartmentsEntityInformation_FieldsPicklistValuesFields 1496
ResourceRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1497
ResourceRoleDepartmentsEntityInformationFields 1498
ResourceRoleDepartmentsEntityInformationUserDefinedFields 1498
ResourceRoleQueues 2046
ResourceRoleQueuesById 2047
ResourceRoleQueuesCount 2048
ResourceRoleQueuesEntityInformation 1499
ResourceRoleQueuesEntityInformation_FieldsPicklistValuesFields 1499
ResourceRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields 1500
ResourceRoleQueuesEntityInformationFields 1501
ResourceRoleQueuesEntityInformationUserDefinedFields 1502
ResourceRoles 2050
ResourceRolesById 2051
ResourceRolesCount 2052
ResourceRolesEntityInformation 1502
ResourceRolesEntityInformation_FieldsPicklistValuesFields 1503
ResourceRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1504
ResourceRolesEntityInformationFields 1505
ResourceRolesEntityInformationUserDefinedFields 1505
Resources 2054
ResourcesById 2055
ResourcesByParentIdAttachments 2038
ResourcesByParentIdAttachmentsId 2040
ResourcesByParentIdRoleDepartments 2044
ResourcesByParentIdRoleDepartmentsEntityInformation 1506
ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesFields 1507
ResourcesByParentIdRoleDepartmentsEntityInformation_FieldsPicklistValuesUserDefinedFields 1508
ResourcesByParentIdRoleDepartmentsEntityInformationFields 1509
ResourcesByParentIdRoleDepartmentsEntityInformationUserDefinedFields 1510
ResourcesByParentIdRoleDepartmentsId 2045
ResourcesByParentIdRoleQueues 2048
ResourcesByParentIdRoleQueuesEntityInformation 1512
ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesFields 1513
ResourcesByParentIdRoleQueuesEntityInformation_FieldsPicklistValuesUserDefinedFields 1514
ResourcesByParentIdRoleQueuesEntityInformationFields 1515
ResourcesByParentIdRoleQueuesEntityInformationUserDefinedFields 1516
ResourcesByParentIdRoleQueuesId 2049
ResourcesByParentIdRoles 2052

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ResourcesByParentIdRolesEntityInformation 1517
ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesFields 1518
ResourcesByParentIdRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1519
ResourcesByParentIdRolesEntityInformationFields 1521
ResourcesByParentIdRolesEntityInformationUserDefinedFields 1522
ResourcesByParentIdRolesId 2053
ResourcesByParentIdServiceDeskRoles 2059
ResourcesByParentIdServiceDeskRolesEntityInformation 1523
ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesFields 1524
ResourcesByParentIdServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1525
ResourcesByParentIdServiceDeskRolesEntityInformationFields 1526
ResourcesByParentIdServiceDeskRolesEntityInformationUserDefinedFields 1527
ResourcesByParentIdServiceDeskRolesId 2060
ResourcesByParentIdSkills 2064
ResourcesByParentIdSkillsEntityInformation 1529
ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesFields 1530
ResourcesByParentIdSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields 1531
ResourcesByParentIdSkillsEntityInformationFields 1532
ResourcesByParentIdSkillsEntityInformationUserDefinedFields 1533
ResourcesByParentIdSkillsId 2065
ResourcesByParentIdTimeOffRequests 2293
ResourcesByParentIdTimeOffRequestsEntityInformation 1534
ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesFields 1535
ResourcesByParentIdTimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields 1536
ResourcesByParentIdTimeOffRequestsEntityInformationFields 1538
ResourcesByParentIdTimeOffRequestsEntityInformationUserDefinedFields 1539
ResourcesByParentIdTimeOffRequestsId 2294
ResourcesCount 2057
ResourcesEntityInformation 1540
ResourcesEntityInformation_FieldsPicklistValuesFields 1540
ResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1541
ResourcesEntityInformationFields 1542
ResourcesEntityInformationUserDefinedFields 1543
ResourceServiceDeskRoles 2057
ResourceServiceDeskRolesById 2058
ResourceServiceDeskRolesCount 2059
ResourceServiceDeskRolesEntityInformation 1543
ResourceServiceDeskRolesEntityInformation_FieldsPicklistValuesFields 1544
ResourceServiceDeskRolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1545
ResourceServiceDeskRolesEntityInformationFields 1546
ResourceServiceDeskRolesEntityInformationUserDefinedFields 1546
ResourceSkills 2062
ResourceSkillsById 2062
ResourceSkillsCount 2063
ResourceSkillsEntityInformation 1547
ResourceSkillsEntityInformation_FieldsPicklistValuesFields 1547
ResourceSkillsEntityInformation_FieldsPicklistValuesUserDefinedFields 1548
ResourceSkillsEntityInformationFields 1549
ResourceSkillsEntityInformationUserDefinedFields 1550
resourceType 2054, 2055
Response Cache Maximum Age (sec) 1912
Result BLOB 1912
Result Date Time 1912
Result Number 1912
Result Text 1912
RESULT_BLOB 1912
RESULT_DATE_TIME_UTC 1912
RESULT_NUMBER 1912
RESULT_TEXT 1912
returnPrice 471, 472, 475, 476
returnTypeID 471, 472, 475, 476
Revenue Spread 1917, 1918, 1920
Revenue Spread Unit 1917, 1918, 1920
revenueSpread 1917, 1918, 1920
revenueSpreadUnit 1917, 1918, 1920
RMA status 2247, 2250, 2253
RMA Type 2247, 2250, 2253
rmaStatus 2247, 2250, 2253
rmaType 2247, 2250, 2253
rmmAlertID 2247, 2250, 2253
rmmDeviceAuditAntivirusStatusID 194, 198, 202
rmmDeviceAuditArchitectureID 194, 198, 202
rmmDeviceAuditBackupStatusID 194, 198, 202
rmmDeviceAuditDescription 194, 198, 202
rmmDeviceAuditDeviceTypeID 194, 198, 202
rmmDeviceAuditDisplayAdaptorID 194, 198, 202
rmmDeviceAuditDomainID 194, 198, 202
rmmDeviceAuditExternalIPAddress 194, 198, 202
rmmDeviceAuditHostname 194, 198, 202

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

rmmDeviceAuditIPAddress 194, 198, 202
rmmDeviceAuditLastUser 194, 198, 202
rmmDeviceAuditMacAddress 194, 198, 202
rmmDeviceAuditManufacturerID 194, 198, 202
rmmDeviceAuditMemoryBytes 194, 198, 202
rmmDeviceAuditMissingPatchCount 194, 198, 202
rmmDeviceAuditMobileNetworkOperatorID 194, 198, 202
rmmDeviceAuditMobileNumber 194, 198, 202
rmmDeviceAuditModelID 194, 198, 202
rmmDeviceAuditMotherboardID 194, 198, 202
rmmDeviceAuditOperatingSystem 194, 198, 202
rmmDeviceAuditPatchStatusID 194, 198, 202
rmmDeviceAuditProcessorID 194, 198, 202
rmmDeviceAuditServicePackID 194, 198, 202
rmmDeviceAuditSNMPContact 194, 198, 202
rmmDeviceAuditSNMPLocation 194, 198, 202
rmmDeviceAuditSNMPName 194, 198, 202
rmmDeviceAuditSoftwareStatusID 194, 198, 202
rmmDeviceAuditStorageBytes 194, 198, 202
rmmDeviceID 194, 198, 202
rmmDeviceUID 194, 198, 202
rmmOpenAlertCount 194, 198, 202
Role ID 65, 67, 262, 263, 264, 265, 283, 284, 285, 286, 314, 315, 316, 318, 324, 325, 326, 327, 1950, 2041, 2042, 2044, 2045, 2050, 2051, 2052, 2053, 2057, 2058, 2059, 2060, 2171, 2172, 2173, 2174, 2256, 2257, 2259, 2260, 2280, 2282
Role Type 2066, 2067
roleID 65, 67, 262, 263, 264, 265, 283, 284, 285, 286, 314, 315, 316, 318, 324, 325, 326, 327, 1950, 2041, 2042, 2044, 2045, 2050, 2051, 2052, 2053, 2057, 2058, 2059, 2060, 2171, 2172, 2173, 2174, 2256, 2257, 2259, 2260, 2280, 2282
Roles 2066
RolesById 2067
RolesCount 2068
RolesEntityInformation 1550
RolesEntityInformation_FieldsPicklistValuesFields 1551
RolesEntityInformation_FieldsPicklistValuesUserDefinedFields 1552
RolesEntityInformationFields 1553
RolesEntityInformationUserDefinedFields 1553
roleType 2066, 2067
Room Number 105, 107, 109, 235, 237, 239
roomNumber 105, 107, 109, 235, 237, 239
Roundtrip Distance 111, 112, 114, 116
roundtripDistance 111, 112, 114, 116
Run without Actions 1912

- S -

Sales Order Date 2074, 2075, 2076, 2078, 2080, 2082
Sales Order ID 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 1917, 1918, 1920, 2012, 2013, 2014, 2016, 2068, 2069, 2071, 2072
Sales Process Percent Complete 1917, 1918, 1920
SalesOrderAttachments 2068
SalesOrderAttachmentsById 2069
SalesOrderAttachmentsCount 2070
SalesOrderAttachmentsEntityInformation 1554
SalesOrderAttachmentsEntityInformation_FieldsPicklistValuesFields 1554
SalesOrderAttachmentsEntityInformationFields 1555
salesOrderDate 2074, 2075, 2076, 2078, 2080, 2082
salesOrderID 58, 59, 97, 98, 100, 102, 117, 118, 120, 122, 1917, 1918, 1920, 2012, 2013, 2014, 2016, 2068, 2069, 2071, 2072
SalesOrders 2074
SalesOrders_ItemsUserDefinedFields 2075
SalesOrdersById 2076
SalesOrdersByParentIdAttachments 2071
SalesOrdersByParentIdAttachmentsId 2072
SalesOrdersCount 2078
SalesOrdersEntityInformation 1556
SalesOrdersEntityInformation_FieldsPicklistValuesFields 1556
SalesOrdersEntityInformation_FieldsPicklistValuesUserDefinedFields 1557
SalesOrdersEntityInformationFields 1558
SalesOrdersEntityInformationUserDefinedFields 1559
salesProcessPercentComplete 1917, 1918, 1920
Saturday Business Hours End Time 456, 458
Saturday Business Hours Start Time 456, 458
Saturday Extended Hours End Time 456, 458
Saturday Extended Hours Start Time 456, 458
saturdayBusinessHoursEndTime 456, 458
saturdayBusinessHoursStartTime 456, 458
saturdayExtendedHoursEndTime 456, 458
saturdayExtendedHoursStartTime 456, 458
Save HTTP Disk Cache 1912
Save HTTP Memory Cache 1912
Secret 450, 452
Secret Key 154, 218, 219, 250, 2241, 2274
secretKey 154, 218, 219, 250, 2241, 2274
Security Level 82, 83
securityLevel 82, 83

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Semi-annual Cost 1917, 1918, 1920
Semi-annual Revenue 1917, 1918, 1920
semiannualCost 1917, 1918, 1920
semiannualRevenue 1917, 1918, 1920
Send Date 2127
Send Threshold Exceeded Notification 154, 218, 219, 250, 2241, 2274
sendDate 2127
sendThresholdExceededNotification 154, 218, 219, 250, 2241, 2274
Sequence Number 2302, 2303
sequenceNumber 2302, 2303
Serial Number 194, 198, 202, 463, 465, 466, 471, 472, 475, 476, 478, 479, 2007, 2009, 2010
serialNumber 194, 198, 202, 463, 465, 466, 471, 472, 475, 476, 478, 479, 2007, 2009, 2010
Service Bundle ID 65, 67, 194, 198, 202, 333, 334, 336, 337, 338, 339, 341, 342, 1952, 2020, 2022, 2024, 2026, 2086, 2088, 2089
Service Call ID 2097, 2099, 2100, 2105, 2106, 2107, 2108
Service Call Task ID 2092, 2093, 2094, 2095
Service Call Ticket ID 2101, 2103, 2104
Service ID 65, 67, 194, 198, 202, 343, 344, 345, 347, 348, 349, 350, 351, 1953, 1954, 2020, 2022, 2024, 2026, 2086, 2088, 2089
Service Level Agreement has been Met 2247, 2250, 2253
Service Level Agreement ID 194, 198, 202, 329, 330, 331, 2084, 2114, 2115, 2197, 2198, 2199, 2200, 2247, 2250, 2253
Service Level Agreement Name 2109, 2110, 2112, 2113
Service Level Agreement Paused next Event Hours 2247, 2250, 2253
Service Thermometer Temperature 2247, 2250, 2253
serviceBundleID 65, 67, 194, 198, 202, 333, 334, 336, 337, 338, 339, 341, 342, 1952, 2020, 2022, 2024, 2026, 2086, 2088, 2089
ServiceBundles 2084
ServiceBundlesById 2084
ServiceBundlesByParentIdServices 2088
ServiceBundlesByParentIdServicesEntityInformation 1559
ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesFields 1560
ServiceBundlesByParentIdServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1562
ServiceBundlesByParentIdServicesEntityInformationFields 1563
ServiceBundlesByParentIdServicesEntityInformationUserDefinedFields 1564
ServiceBundlesByParentIdServicesId 2089
ServiceBundlesCount 2085
ServiceBundlesEntityInformation 1565
ServiceBundlesEntityInformation_FieldsPicklistValuesFields 1566
ServiceBundlesEntityInformation_FieldsPicklistValuesUserDefinedFields 1566
ServiceBundlesEntityInformationFields 1567
ServiceBundlesEntityInformationUserDefinedFields 1568
ServiceBundleServices 2086
ServiceBundleServicesById 2086
ServiceBundleServicesCount 2087
ServiceBundleServicesEntityInformation 1569
ServiceBundleServicesEntityInformation_FieldsPicklistValuesFields 1569
ServiceBundleServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1570
ServiceBundleServicesEntityInformationFields 1571
ServiceBundleServicesEntityInformationUserDefinedFields 1571
serviceCallID 2097, 2099, 2100, 2105, 2106, 2107, 2108
ServiceCalls 2090
ServiceCallsById 2091
ServiceCallsByParentIdTasks 2099
ServiceCallsByParentIdTasksEntityInformation 1572
ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesFields 1573
ServiceCallsByParentIdTasksEntityInformation_FieldsPicklistValuesUserDefinedFields 1574
ServiceCallsByParentIdTasksEntityInformationFields 1576
ServiceCallsByParentIdTasksEntityInformationUserDefinedFields 1577
ServiceCallsByParentIdTasksId 2100
ServiceCallsByParentIdTickets 2107
ServiceCallsByParentIdTicketsEntityInformation 1578
ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesFields 1579
ServiceCallsByParentIdTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields 1580
ServiceCallsByParentIdTicketsEntityInformationFields 1581
ServiceCallsByParentIdTicketsEntityInformationUserDefinedFields 1582
ServiceCallsByParentIdTicketsId 2108
ServiceCallsCount 2092
ServiceCallsEntityInformation 1583
ServiceCallsEntityInformation_FieldsPicklistValuesFields 1584
ServiceCallsEntityInformation_FieldsPicklistValuesUserDefinedFields 1585
ServiceCallsEntityInformationFields 1586

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ServiceCallsEntityInformationUserDefinedFields 1586
serviceCallTaskID 2092, 2093, 2094, 2095
ServiceCallTaskResources 2092
ServiceCallTaskResourcesById 2093
ServiceCallTaskResourcesCount 2094
ServiceCallTaskResourcesEntityInformation 1587
ServiceCallTaskResourcesEntityInformation_FieldsPicklistValuesFields 1587
ServiceCallTaskResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1588
ServiceCallTaskResourcesEntityInformationFields 1589
ServiceCallTaskResourcesEntityInformationUserDefinedFields 1590
ServiceCallTasks 2097
ServiceCallTasksById 2097
ServiceCallTasksByParentIdResources 2094
ServiceCallTasksByParentIdResourcesEntityInformation 1590
ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesFields 1591
ServiceCallTasksByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1593
ServiceCallTasksByParentIdResourcesEntityInformationFields 1594
ServiceCallTasksByParentIdResourcesEntityInformationUserDefinedFields 1595
ServiceCallTasksByParentIdResourcesId 2095
ServiceCallTasksCount 2098
ServiceCallTasksEntityInformation 1596
ServiceCallTasksEntityInformation_FieldsPicklistValuesFields 1597
ServiceCallTasksEntityInformation_FieldsPicklistValuesUserDefinedFields 1598
ServiceCallTasksEntityInformationFields 1598
ServiceCallTasksEntityInformationUserDefinedFields 1599
serviceCallTicketID 2101, 2103, 2104
ServiceCallTicketResources 2101
ServiceCallTicketResourcesById 2101
ServiceCallTicketResourcesCount 2103
ServiceCallTicketResourcesEntityInformation 1600
ServiceCallTicketResourcesEntityInformation_FieldsPicklistValuesFields 1600
ServiceCallTicketResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1601
ServiceCallTicketResourcesEntityInformationFields 1602
ServiceCallTicketResourcesEntityInformationUserDefinedFields 1603
ServiceCallTickets 2105
ServiceCallTicketsById 2106
ServiceCallTicketsByParentIdResources 2103
ServiceCallTicketsByParentIdResourcesEntityInformation 1603
ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesFields 1604
ServiceCallTicketsByParentIdResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1605
ServiceCallTicketsByParentIdResourcesEntityInformationFields 1607
ServiceCallTicketsByParentIdResourcesEntityInformationUserDefinedFields 1608
ServiceCallTicketsByParentIdResourcesId 2104
ServiceCallTicketsCount 2107
ServiceCallTicketsEntityInformation 1609
ServiceCallTicketsEntityInformation_FieldsPicklistValuesFields 1610
ServiceCallTicketsEntityInformation_FieldsPicklistValuesUserDefinedFields 1610
ServiceCallTicketsEntityInformationFields 1611
ServiceCallTicketsEntityInformationUserDefinedFields 1612
serviceID 65, 67, 194, 198, 202, 343, 344, 345, 347, 348, 349, 350, 351, 1953, 1954, 2020, 2022, 2024, 2026, 2086, 2088, 2089
serviceLevelAgreementHasBeenMet 2247, 2250, 2253
serviceLevelAgreementID 194, 198, 202, 329, 330, 331, 2084, 2114, 2115, 2197, 2198, 2199, 2200, 2247, 2250, 2253
serviceLevelAgreementName 2109, 2110, 2112, 2113
serviceLevelAgreementPausedNextEventHours 2247, 2250, 2253
ServiceLevelAgreementResults 2109
ServiceLevelAgreementResultsById 2110
ServiceLevelAgreementResultsCount 2111
ServiceLevelAgreementResultsEntityInformation 1612
ServiceLevelAgreementResultsEntityInformation_FieldsPicklistValuesFields 1613
ServiceLevelAgreementResultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1614
ServiceLevelAgreementResultsEntityInformationFields 1615
ServiceLevelAgreementResultsEntityInformationUserDefinedFields 1615
ServiceLevelAgreementsByParentIdResults 2112
ServiceLevelAgreementsByParentIdResultsEntityInformation 1616
ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesFields 1617
ServiceLevelAgreementsByParentIdResultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1618

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ServiceLevelAgreementsByParentIdResultsEntityInformationFields 1620
ServiceLevelAgreementsByParentIdResultsEntityInformationUserDefinedFields 1621
ServiceLevelAgreementsByParentIdResultsId 2113
Services 2114
ServicesById 2115
ServicesCount 2116
ServicesEntityInformation 1622
ServicesEntityInformation_FieldsPicklistValuesFields 1622
ServicesEntityInformation_FieldsPicklistValuesUserDefinedFields 1623
ServicesEntityInformationFields 1624
ServicesEntityInformationUserDefinedFields 1624
serviceThermometerTemperature 2247, 2250, 2253
Setup Fee 194, 198, 202, 329, 330, 331
Setup Fee Billing Code ID 329, 330, 331
setupFee 194, 198, 202, 329, 330, 331
setupFeeBillingCodeID 329, 330, 331
SGDA 1999, 2001, 2003
Shipping Date 2017, 2018
Shipping ID 2020, 2022, 2024, 2026
Shipping Type 2017, 2018, 2029, 2031
shippingDate 2017, 2018
shippingID 2020, 2022, 2024, 2026
shippingType 2017, 2018, 2029, 2031
ShippingTypes 2116
ShippingTypesById 2117
ShippingTypesCount 2118
ShippingTypesEntityInformation 1625
ShippingTypesEntityInformation_FieldsPicklistValuesFields 1626
ShippingTypesEntityInformation_FieldsPicklistValuesUserDefinedFields 1627
ShippingTypesEntityInformationFields 1627
ShippingTypesEntityInformationUserDefinedFields 1628
Ship-to Address 1 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
Ship-to Address 2 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
Ship-to City 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
Ship-to Country ID 2074, 2075, 2076, 2078, 2080, 2082
Ship-to Location ID 2029, 2031
Ship-to Name 2017, 2018
Ship-to Postal Code 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
Ship-to State 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
shipToAddress1 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
shipToAddress2 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
shipToCity 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
shipToCountryID 2074, 2075, 2076, 2078, 2080, 2082
shipToLocationID 2029, 2031
shipToName 2017, 2018
shipToPostalCode 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
shipToState 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082
Show Each Tax in Group 2017, 2018, 2029, 2031, 2033, 2034
Show Grid Header 484, 486, 2033, 2034
Show on Invoice 2280, 2282
Show Tax Category 2017, 2018, 2029, 2031, 2033, 2034
Show Vertical Grid Lines 484, 486, 2033, 2034
showEachTaxInGroup 2017, 2018, 2029, 2031, 2033, 2034
showGridHeader 484, 486, 2033, 2034
showOnInvoice 2280, 2282
showTaxCategory 2017, 2018, 2029, 2031, 2033, 2034
showVerticalGridLines 484, 486, 2033, 2034
SIC Code 86, 88, 90
sicCode 86, 88, 90
simulate-http-400-errors 2
simulate-http-400-errors-percentage 2
simulate-http-401-errors 2
simulate-http-401-errors-percentage 2
simulate-http-403-errors 2
simulate-http-403-errors-percentage 2
simulate-http-408-errors 2
simulate-http-408-errors-percentage 2
simulate-http-429-errors 2
simulate-http-429-errors-percentage 2
simulate-http-500-errors 2
simulate-http-500-errors-percentage 2
simulate-http-502-errors 2
simulate-http-502-errors-percentage 2
simulate-http-503-errors 2
simulate-http-503-errors-percentage 2
simulate-http-504-errors 2
simulate-http-504-errors-percentage 2
simulate-http-522-errors 2
simulate-http-522-errors-percentage 2
simulate-http-524-errors 2
simulate-http-524-errors-percentage 2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

simulate-http-protocol-errors 2
simulate-http-protocol-errors-percentage 2
simulate-http-timeout-errors 2
simulate-http-timeout-errors-percentage 2
Skill Description 2062, 2064, 2065
Skill ID 2062, 2064, 2065
Skill Level 2062, 2064, 2065
skillDescription 2062, 2064, 2065
skillID 2062, 2064, 2065
skillLevel 2062, 2064, 2065
Skills 2118
SkillsById 2118
SkillsCount 2119
SkillsEntityInformation 1629
SkillsEntityInformation_FieldsPicklistValuesFields 1629
SkillsEntityInformation_FieldsPicklistValuesUserDefinedFields 1630
SkillsEntityInformationFields 1631
SkillsEntityInformationUserDefinedFields 1631
SKU 1962, 1963, 1964
slot-based-rate-limit-length-ms 2
slot-based-rate-limit-slots 2
SOAP Parent Property ID 58, 59, 175, 176, 177, 178, 206, 207, 208, 338, 339, 341, 342, 348, 349, 350, 351, 1934, 1935, 1936, 2050, 2051, 2052, 2053, 2109, 2110, 2112, 2113, 2120, 2122, 2123, 2197, 2198, 2199, 2200, 2219, 2220
soapParentPropertyId 58, 59, 175, 176, 177, 178, 206, 207, 208, 338, 339, 341, 342, 348, 349, 350, 351, 1934, 1935, 1936, 2050, 2051, 2052, 2053, 2109, 2110, 2112, 2113, 2120, 2122, 2123, 2197, 2198, 2199, 2200, 2219, 2220
soapParentPropertyId_body_canReduce 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

soapParentPropertyId_body_nodeType 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

soapParentPropertyId_body_type 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

soapParentPropertyId_canReduce 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

soapParentPropertyId_name 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

soapParentPropertyId_nodeType 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

soapParentPropertyId_returnType 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

soapParentPropertyId_tailCall 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

soapParentPropertyId_type 22, 23, 25, 27, 28, 29, 30, 31, 32, 34, 35, 36, 37, 38, 39, 40, 41, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 57, 76, 77, 78, 79, 93, 95, 96, 97, 98, 100, 102, 105, 107, 109, 111, 112, 114, 116, 117, 118, 120, 122, 123, 124, 126, 127, 129, 130, 132, 133, 134, 135, 136, 137, 138, 139, 140, 142, 144, 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 160, 162, 163, 165, 167, 169, 172, 174, 179, 180, 182, 183, 185, 186, 187, 189, 190, 191, 192, 193, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 235, 237, 239, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 256, 257, 259, 261, 262, 263, 264, 265, 267, 269, 270, 272, 273, 275, 277, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 290, 291, 292, 294, 295, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 314, 315, 316, 318, 319, 320, 321, 323, 324, 325, 326, 327, 333, 334, 336, 337, 343, 344, 345, 347, 352, 353, 355, 356, 369, 370, 372, 374, 377, 379, 380, 381, 382, 383, 384, 386, 388, 389, 390, 391, 393, 394, 396, 397, 398, 399, 401, 402, 403, 404, 405, 407, 408, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 422, 423, 425, 427, 428, 429, 432, 433, 435, 436, 438, 440, 444, 446, 447, 463, 465, 466, 471, 472, 475, 476, 488, 490, 491, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1948, 1957, 1958, 1959, 1960, 1966, 1968, 1969, 1970, 1971, 1972, 1973, 1975, 1976, 1978, 1979, 1981, 1982, 1984, 1986, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2007, 2009, 2010, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2036, 2037, 2038, 2040, 2041, 2042, 2044, 2045, 2046, 2047, 2048, 2049, 2057, 2058, 2059, 2060, 2062, 2064, 2065, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2086, 2088, 2089, 2092, 2093, 2094, 2095, 2097, 2099, 2100, 2101, 2103, 2104, 2105, 2106, 2107, 2108, 2130, 2131, 2132, 2133, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2155, 2156, 2157, 2158, 2159, 2161, 2163, 2165, 2167, 2169, 2171, 2172, 2173, 2174, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279, 2284, 2285, 2287, 2288, 2290, 2291, 2293, 2294, 2298, 2299, 2300, 2301

Sold-to Location ID 2029, 2031

soldToLocationID 2029, 2031

solicitationOptOut 105, 107, 109, 235, 237, 239

solicitationOptOutTime 105, 107, 109, 235, 237, 239

Sollicitation Opt-out 105, 107, 109, 235, 237, 239

Sollicitation Opt-out Time 105, 107, 109, 235, 237, 239

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Sort by 484, 486

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Sort Order 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809, 1814, 1815, 1819, 1820,

Sort Order ID 65, 67, 2020, 2022, 2024, 2026

SortBy 484, 486

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

sortOrder 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809, 1814, 1815, 1819, 1820,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

sortOrderID 65, 67, 2020, 2022, 2024, 2026
Source 2247, 2250, 2253
Source Charge ID 194, 198, 202
Source Charge Type 194, 198, 202
Source ID 2197, 2198, 2199, 2200
sourceChargeID 194, 198, 202
sourceChargeType 194, 198, 202
sourceID 2197, 2198, 2199, 2200
Speed Kilobits per Second 194, 198, 202
SSL Common Name 194, 198, 202
SSL Issued by 194, 198, 202
SSL Location 194, 198, 202
SSL Organization 194, 198, 202
SSL Organization Unit 194, 198, 202
SSL Serial Number 194, 198, 202
SSL Signature Algorithm 194, 198, 202
SSL Source 194, 198, 202
SSL Valid from Date/Time 194, 198, 202
SSL Valid until Date/Time 194, 198, 202
sslCommonName 194, 198, 202
sslIssuedBy 194, 198, 202
sslLocation 194, 198, 202
sslOrganization 194, 198, 202
sslOrganizationUnit 194, 198, 202
sslSerialNumber 194, 198, 202
sslSignatureAlgorithm 194, 198, 202
sslSource 194, 198, 202
sslValidFromDateTime 194, 198, 202
sslValidUntilDateTime 194, 198, 202
Stage 1917, 1918, 1920
standardize-identifiers 2
standardize-identifiers-casing 2
Start Date 256, 257, 259, 261, 267, 269, 270, 319, 320, 321, 323, 329, 330, 331, 338, 339, 341, 342, 348, 349, 350, 351, 352, 353, 355, 356, 1912, 1917, 1918, 1920, 1939, 1940, 1942, 1943
Start Date/Time 20, 21, 123, 124, 126, 127, 139, 140, 142, 144, 361, 362, 364, 1999, 2001, 2003, 2090, 2091, 2159, 2161, 2163, 2165, 2167, 2169, 2280, 2282
Start Time 2290, 2291, 2293, 2294
startDate 256, 257, 259, 261, 267, 269, 270, 319, 320, 321, 323, 329, 330, 331, 338, 339, 341, 342, 348, 349, 350, 351, 352, 353, 355, 356, 1917, 1918, 1920, 1939, 1940, 1942, 1943
startDateTime 20, 21, 123, 124, 126, 127, 139, 140, 142, 144, 361, 362, 364, 1999, 2001, 2003, 2090, 2091, 2159, 2161, 2163, 2165, 2167, 2169, 2280, 2282
startTime 2290, 2291, 2293, 2294
State 86, 88, 90, 105, 107, 109, 111, 112, 114, 116, 235, 237, 239, 454, 456, 458, 2027, 2028
Status 70, 71, 267, 269, 270, 272, 273, 275, 277, 298, 299, 300, 302, 319, 320, 321, 323, 329, 330, 331, 352, 353, 355, 356, 441, 442, 1917, 1918, 1920, 1981, 1982, 1984, 1986, 1999, 2001, 2003, 2017, 2018, 2074, 2075, 2076, 2078, 2080, 2082, 2090, 2091, 2124, 2125, 2159, 2161, 2163, 2165, 2167, 2169, 2197, 2198, 2199, 2200, 2206, 2208, 2210, 2212, 2247, 2250, 2253, 2290, 2291, 2293, 2294
Status Date/Time 1999, 2001, 2003
Status Detail 1999, 2001, 2003
Status Last Modified by 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
Status Last Modified Date 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
statusDateTime 1999, 2001, 2003
statusDetail 1999, 2001, 2003
statusID 471, 472, 475, 476
statusLastModifiedBy 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
statusLastModifiedDate 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
Stock Market 86, 88, 90
Stock Symbol 86, 88, 90
stockMarket 86, 88, 90
stockSymbol 86, 88, 90
Sub-issue Type 2247, 2250, 2253
Sub-issue Type ID 2197, 2198, 2199, 2200
subIssueType 2247, 2250, 2253
subIssueTypeID 2197, 2198, 2199, 2200
Submit 441, 442
Submit Date 441, 442
Submit Date/Time 2017, 2018
submitDate 441, 442
submitDateTime 2017, 2018
Submitter ID 441, 442
submitterID 441, 442
Subscription ID 2120, 2122, 2123
Subscription Name 2124, 2125
subscriptionID 2120, 2122, 2123
subscriptionName 2124, 2125
SubscriptionPeriods 2120
SubscriptionPeriodsById 2120
SubscriptionPeriodsCount 2121
SubscriptionPeriodsEntityInformation 1632
SubscriptionPeriodsEntityInformation_FieldsPicklistValuesFields 1633
SubscriptionPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields 1634
SubscriptionPeriodsEntityInformationFields 1634
SubscriptionPeriodsEntityInformationUserDefinedFields 1635
Subscriptions 2124
Subscriptions_ItemsUserDefinedFields 2124

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

SubscriptionsById 2125
SubscriptionsByParentIdPeriods 2122
SubscriptionsByParentIdPeriodsEntityInformation 1636
SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesFields 1637
SubscriptionsByParentIdPeriodsEntityInformation_FieldsPicklistValuesUserDefinedFields 1638
SubscriptionsByParentIdPeriodsEntityInformationFields 1639
SubscriptionsByParentIdPeriodsEntityInformationUserDefinedFields 1640
SubscriptionsByParentIdPeriodsId 2123
SubscriptionsCount 2126
SubscriptionsEntityInformation 1641
SubscriptionsEntityInformation_FieldsPicklistValuesFields 1642
SubscriptionsEntityInformation_FieldsPicklistValuesUserDefinedFields 1643
SubscriptionsEntityInformationFields 1644
SubscriptionsEntityInformationUserDefinedFields 1644
subType 65, 67
Sub-type 65, 67
Succesful 1912
SUCCESSFUL 1912
Successor Task ID 2155, 2156, 2157, 2158
successorTaskID 2155, 2156, 2157, 2158
Suffix 2054, 2055
Summary Notes 2280, 2282
summaryNotes 2280, 2282
Sunday Business Hours End Time 456, 458
Sunday Business Hours Start Time 456, 458
Sunday Extended Hours End Time 456, 458
Sunday Extended Hours Start Time 456, 458
sundayBusinessHoursEndTime 456, 458
sundayBusinessHoursStartTime 456, 458
sundayExtendedHoursEndTime 456, 458
sundayExtendedHoursStartTime 456, 458
Supports Webhook Call-outs 495, 498, 502, 505, 507, 511, 514, 518, 521, 525, 528, 532, 535, 539, 542, 546, 549, 553, 559, 562, 566, 569, 573, 576, 582, 588, 593, 599, 605, 610, 616, 619, 623, 625, 628, 632, 634, 637, 641, 644, 648, 652, 655, 661, 667, 672, 676, 679, 681, 685, 690, 693, 697, 700, 702, 706, 709, 714, 720, 725, 731, 736, 739, 743, 746, 750, 754, 758, 764, 770, 773, 777, 780, 784, 789, 793, 798, 802, 806, 809, 815, 821, 826, 830, 833, 837, 840, 844, 847, 851, 854, 858, 862, 868, 873, 877, 880, 882, 886, 889, 893, 896, 902, 908, 913, 919, 925, 930, 936, 942, 947, 953, 959, 964, 970, 976, 982, 987, 993, 999, 1002, 1006, 1009, 1013, 1016, 1020, 1023, 1027, 1030, 1034, 1037, 1041, 1044, 1048, 1050, 1056, 1059, 1063, 1066, 1070, 1074, 1077, 1081, 1086, 1092, 1098, 1104, 1108, 1114, 1120, 1125, 1131, 1137, 1140, 1144, 1147, 1151, 1155, 1158, 1160, 1164, 1166, 1169, 1175, 1178, 1184, 1187, 1191, 1194, 1198, 1202, 1207, 1211, 1214, 1218, 1224, 1229, 1235, 1241, 1244, 1248, 1251, 1255, 1258, 1262, 1265, 1269, 1273, 1278, 1282, 1288, 1294, 1300, 1304, 1308, 1312, 1316, 1319, 1325, 1329, 1331, 1334, 1338, 1342, 1346, 1349, 1353, 1356, 1360, 1363, 1367, 1370, 1374, 1377, 1381, 1384, 1390, 1395, 1401, 1404, 1408, 1411, 1413, 1417, 1419, 1422, 1428, 1434, 1439, 1445, 1448, 1452, 1455, 1461, 1465, 1470, 1474, 1477, 1481, 1486, 1490, 1493, 1495, 1499, 1502, 1506, 1512, 1517, 1523, 1529, 1534, 1540, 1543, 1547, 1550, 1554, 1556, 1559, 1565, 1569, 1572, 1578, 1583, 1587, 1590, 1596, 1600, 1603, 1609, 1612, 1616, 1622, 1625, 1629, 1632, 1636, 1641, 1645, 1648, 1652, 1655, 1659, 1664, 1668, 1670, 1672, 1675, 1679, 1684, 1690, 1696, 1699, 1703, 1706, 1710, 1713, 1717, 1720, 1722, 1728, 1732, 1735, 1739, 1742, 1746, 1749, 1753, 1755, 1758, 1762, 1765, 1771, 1777, 1781, 1784, 1790, 1796, 1801, 1807, 1813, 1818, 1824, 1829, 1835, 1841, 1844, 1848, 1851, 1855, 1858, 1864, 1870, 1876, 1879, 1883, 1886, 1888, 1892, 1895, 1899, 1904, 1908, 1911
Survey Company Rating 86, 88, 90
Survey ID 2127
Survey Opt-out 105, 107, 109, 235, 237, 239
Survey Rating 2127
Survey Resource Rating 2054, 2055
surveyCompanyRating 86, 88, 90
surveyID 2127
surveyOptOut 105, 107, 109, 235, 237, 239
surveyRating 2127
surveyResourceRating 2054, 2055
SurveyResults 2127
SurveyResultsById 2127
SurveyResultsCount 2128
SurveyResultsEntityInformation 1645
SurveyResultsEntityInformation_FieldsPicklistValuesFields 1645

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

SurveyResultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1646
SurveyResultsEntityInformationFields 1647
SurveyResultsEntityInformationUserDefinedFields 1648
Surveys 2129
SurveysById 2129
SurveysCount 2130
SurveysEntityInformation 1648
SurveysEntityInformation_FieldsPicklistValuesFields 1649
SurveysEntityInformation_FieldsPicklistValuesUserDefinedFields 1650
SurveysEntityInformationFields 1651
SurveysEntityInformationUserDefinedFields 1651
swagger-specification-download-tries 2
swagger-specification-file 2
swagger-specification-http-disk-cache-max-age-sec 2
swagger-specification-url 2

- T -

Tag Group ID 2136, 2137
Tag ID 40, 41, 43, 44, 403, 404, 405, 407, 2130, 2131, 2132, 2133, 2261, 2263, 2264
TagAliases 2130
TagAliasesById 2131
TagAliasesCount 2132
TagAliasesEntityInformation 1652
TagAliasesEntityInformation_FieldsPicklistValuesFields 1652
TagAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields 1653
TagAliasesEntityInformationFields 1654
TagAliasesEntityInformationUserDefinedFields 1655
tagGroupID 2136, 2137
TagGroups 2134
TagGroupsById 2135
TagGroupsCount 2136
TagGroupsEntityInformation 1655
TagGroupsEntityInformation_FieldsPicklistValuesFields 1656
TagGroupsEntityInformation_FieldsPicklistValuesUserDefinedFields 1657
TagGroupsEntityInformationFields 1658
TagGroupsEntityInformationUserDefinedFields 1658
tagID 40, 41, 43, 44, 403, 404, 405, 407, 2130, 2131, 2132, 2133, 2261, 2263, 2264
Tags 2136
TagsById 2137
TagsByParentIdAliases 2132
TagsByParentIdAliasesEntityInformation 1659
TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesFields 1660
TagsByParentIdAliasesEntityInformation_FieldsPicklistValuesUserDefinedFields 1661
TagsByParentIdAliasesEntityInformationFields 1662
TagsByParentIdAliasesEntityInformationUserDefinedFields 1663
TagsByParentIdAliasesId 2133
TagsCount 2138
TagsEntityInformation 1664
TagsEntityInformation_FieldsPicklistValuesFields 1665
TagsEntityInformation_FieldsPicklistValuesUserDefinedFields 1666
TagsEntityInformationFields 1667
TagsEntityInformationUserDefinedFields 1667
Task Category ID 2159, 2161, 2163, 2165, 2167, 2169
Task ID 58, 59, 65, 67, 70, 71, 361, 362, 428, 429, 432, 433, 1914, 1915, 2097, 2099, 2100, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2171, 2172, 2173, 2174, 2280, 2282, 2284, 2285, 2287, 2288
Task Note ID 58, 59, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148
Task Number 361, 362, 2159, 2161, 2163, 2165, 2167, 2169
Task Type 2159, 2161, 2163, 2165, 2167, 2169
TaskAttachments 2138
TaskAttachmentsById 2139
TaskAttachmentsCount 2141
TaskAttachmentsEntityInformation 1668
TaskAttachmentsEntityInformation_FieldsPicklistValuesFields 1669
TaskAttachmentsEntityInformationFields 1669
taskCategoryID 2159, 2161, 2163, 2165, 2167, 2169
taskID 58, 59, 65, 67, 70, 71, 361, 362, 428, 429, 432, 433, 1914, 1915, 2097, 2099, 2100, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2171, 2172, 2173, 2174, 2280, 2282, 2284, 2285, 2287, 2288
TaskNoteAttachments 2144
TaskNoteAttachmentsById 2145
TaskNoteAttachmentsCount 2147
TaskNoteAttachmentsEntityInformation 1670
TaskNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 1671
TaskNoteAttachmentsEntityInformationFields 1671
taskNoteID 58, 59, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148
TaskNotes 2150
TaskNotesById 2151

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

TaskNotesByParentIdAttachments 2147
TaskNotesByParentIdAttachmentsId 2148
TaskNotesCount 2152
TaskNotesEntityInformation 1672
TaskNotesEntityInformation_FieldsPicklistValuesFields 1673
TaskNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1673
TaskNotesEntityInformationFields 1674
TaskNotesEntityInformationUserDefinedFields 1675
taskNumber 361, 362, 2159, 2161, 2163, 2165, 2167, 2169
TaskPredecessors 2155
TaskPredecessorsById 2156
TaskPredecessorsCount 2157
TaskPredecessorsEntityInformation 1675
TaskPredecessorsEntityInformation_FieldsPicklistValuesFields 1676
TaskPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields 1677
TaskPredecessorsEntityInformationFields 1678
TaskPredecessorsEntityInformationUserDefinedFields 1678
Tasks 2159
Tasks_ItemsUserDefinedFields 2161
TasksById 2163
TasksByParentIdAttachments 2141
TasksByParentIdAttachmentsId 2142
TasksByParentIdNotes 2152
TasksByParentIdNotesEntityInformation 1679
TasksByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1680
TasksByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1681
TasksByParentIdNotesEntityInformationFields 1682
TasksByParentIdNotesEntityInformationUserDefinedFields 1683
TasksByParentIdNotesId 2154
TasksByParentIdPredecessors 2157
TasksByParentIdPredecessorsEntityInformation 1684
TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesFields 1685
TasksByParentIdPredecessorsEntityInformation_FieldsPicklistValuesUserDefinedFields 1687
TasksByParentIdPredecessorsEntityInformationFields 1688
TasksByParentIdPredecessorsEntityInformationUserDefinedFields 1689
TasksByParentIdPredecessorsId 2158
TasksByParentIdSecondaryResources 2173
TasksByParentIdSecondaryResourcesEntityInformation 1690
TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields 1691
TasksByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1692
TasksByParentIdSecondaryResourcesEntityInformationFields 1694
TasksByParentIdSecondaryResourcesEntityInformationUserDefinedFields 1695
TasksByParentIdSecondaryResourcesId 2174
TasksCount 2164
TaskSecondaryResources 2171
TaskSecondaryResourcesById 2172
TaskSecondaryResourcesCount 2173
TaskSecondaryResourcesEntityInformation 1696
TaskSecondaryResourcesEntityInformation_FieldsPicklistValuesFields 1696
TaskSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1697
TaskSecondaryResourcesEntityInformationFields 1698
TaskSecondaryResourcesEntityInformationUserDefinedFields 1699
TasksEntityInformation 1699
TasksEntityInformation_FieldsPicklistValuesFields 1700
TasksEntityInformation_FieldsPicklistValuesUserDefinedFields 1701
TasksEntityInformationFields 1702
TasksEntityInformationUserDefinedFields 1702
taskType 2159, 2161, 2163, 2165, 2167, 2169
Tax Category ID 61, 62, 2020, 2022, 2024, 2026, 2177
Tax Dollars 65, 67
Tax Group 482, 483
Tax ID 86, 88, 90
Tax Name 2177
Tax Rate 2177
Tax Region ID 86, 88, 90, 111, 112, 114, 116, 2017, 2018, 2029, 2031, 2177
Tax Region Name 482, 483
TaxCategories 2175
TaxCategoriesById 2176
TaxCategoriesCount 2176
TaxCategoriesEntityInformation 1703
TaxCategoriesEntityInformation_FieldsPicklistValuesFields 1703
TaxCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1704
TaxCategoriesEntityInformationFields 1705
TaxCategoriesEntityInformationUserDefinedFields 1706
taxCategoryID 61, 62, 2020, 2022, 2024, 2026, 2177

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

taxDollars 65, 67
Taxes 2177
TaxesById 2177
TaxesCount 2178
TaxesEntityInformation 1706
TaxesEntityInformation_FieldsPicklistValuesFields 1707
TaxesEntityInformation_FieldsPicklistValuesUserDefinedFields 1708
TaxesEntityInformationFields 1709
TaxesEntityInformationUserDefinedFields 1709
taxGroup 482, 483
taxID 86, 88, 90
taxName 2177
taxRate 2177
taxRegionID 86, 88, 90, 111, 112, 114, 116, 2017, 2018, 2029, 2031, 2177
taxRegionName 482, 483
TaxRegions 2178
TaxRegionsById 2179
TaxRegionsCount 2180
TaxRegionsEntityInformation 1710
TaxRegionsEntityInformation_FieldsPicklistValuesFields 1710
TaxRegionsEntityInformation_FieldsPicklistValuesUserDefinedFields 1711
TaxRegionsEntityInformationFields 1712
TaxRegionsEntityInformationUserDefinedFields 1713
Technical Assessment Score 1917, 1918, 1920
technicalAssessmentScore 1917, 1918, 1920
Template Name 1914, 1915
templateName 1914, 1915
Territory ID 86, 88, 90
territoryID 86, 88, 90
TEXT 20
ThresholdInformation 2180
Through Date 1917, 1918, 1920
throughDate 1917, 1918, 1920
Thursday Business Hours End Time 456, 458
Thursday Business Hours Start Time 456, 458
Thursday Extended Hours End Time 456, 458
Thursday Extended Hours Start Time 456, 458
thursdayBusinessHoursEndTime 456, 458
thursdayBusinessHoursStartTime 456, 458
thursdayExtendedHoursEndTime 456, 458
thursdayExtendedHoursStartTime 456, 458
Ticket Category 2247, 2250, 2253
Ticket Category ID 2197, 2198, 2199, 2200
Ticket Charge ID 65, 67, 471, 472, 475, 476
Ticket ID 45, 46, 47, 48, 58, 59, 65, 67, 139, 140, 142, 144, 364, 366, 408, 410, 411, 428, 429, 432, 433, 1914, 1915, 2012, 2013, 2014, 2016, 2105, 2106, 2107, 2108, 2109, 2110, 2112, 2113, 2127, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2219, 2220, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2280, 2282, 2284, 2285, 2287, 2288
Ticket Note ID 58, 59, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225
Ticket Number 364, 366, 2247, 2250, 2253
Ticket Title 366
Ticket Type 2247, 2250, 2253
Ticket Type ID 2197, 2198, 2199, 2200
TicketAdditionalConfigurationItems 2180
TicketAdditionalConfigurationItemsById 2181
TicketAdditionalConfigurationItemsCount 2182
TicketAdditionalConfigurationItemsEntityInformation 1713
TicketAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields 1714
TicketAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1715
TicketAdditionalConfigurationItemsEntityInformationFields 1716
TicketAdditionalConfigurationItemsEntityInformationUserDefinedFields 1716
TicketAdditionalContacts 2185
TicketAdditionalContactsById 2185
TicketAdditionalContactsCount 2186
TicketAdditionalContactsEntityInformation 1717
TicketAdditionalContactsEntityInformation_FieldsPicklistValuesFields 1718
TicketAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields 1718
TicketAdditionalContactsEntityInformationFields 1719
TicketAdditionalContactsEntityInformationUserDefinedFields 1720
TicketAttachments 2189
TicketAttachmentsById 2190
TicketAttachmentsCount 2192
TicketAttachmentsEntityInformation 1720
TicketAttachmentsEntityInformation_FieldsPicklistValuesFields 1721
TicketAttachmentsEntityInformationFields 1722
TicketCategories 2195
TicketCategoriesById 2196
TicketCategoriesByParentIdFieldDefaults 2199
TicketCategoriesByParentIdFieldDefaultsEntityInformation 1722

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesFields 1724
TicketCategoriesByParentIdFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1725
TicketCategoriesByParentIdFieldDefaultsEntityInformationFields 1726
TicketCategoriesByParentIdFieldDefaultsEntityInformationUserDefinedFields 1727
TicketCategoriesByParentIdFieldDefaultsId 2200
TicketCategoriesCount 2196
TicketCategoriesEntityInformation 1728
TicketCategoriesEntityInformation_FieldsPicklistValuesFields 1729
TicketCategoriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1730
TicketCategoriesEntityInformationFields 1731
TicketCategoriesEntityInformationUserDefinedFields 1731
ticketCategory 2247, 2250, 2253
TicketCategoryFieldDefaults 2197
TicketCategoryFieldDefaultsById 2198
TicketCategoryFieldDefaultsCount 2199
TicketCategoryFieldDefaultsEntityInformation 1732
TicketCategoryFieldDefaultsEntityInformation_FieldsPicklistValuesFields 1732
TicketCategoryFieldDefaultsEntityInformation_FieldsPicklistValuesUserDefinedFields 1733
TicketCategoryFieldDefaultsEntityInformationFields 1734
TicketCategoryFieldDefaultsEntityInformationUserDefinedFields 1735
ticketCategoryID 2197, 2198, 2199, 2200
TicketChangeRequestApprovals 2202
TicketChangeRequestApprovalsById 2203
TicketChangeRequestApprovalsCount 2204
TicketChangeRequestApprovalsEntityInformation 1735
TicketChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields 1736
TicketChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields 1737
TicketChangeRequestApprovalsEntityInformationFields 1738
TicketChangeRequestApprovalsEntityInformationUserDefinedFields 1738
ticketChargeID 65, 67, 471, 472, 475, 476
TicketCharges 2206
TicketChargesById 2208
TicketChargesCount 2210
TicketChargesEntityInformation 1739
TicketChargesEntityInformation_FieldsPicklistValuesFields 1740
TicketChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 1740
TicketChargesEntityInformationFields 1741
TicketChargesEntityInformationUserDefinedFields 1742
TicketChecklistItems 2214
TicketChecklistItemsById 2214
TicketChecklistItemsCount 2216
TicketChecklistItemsEntityInformation 1742
TicketChecklistItemsEntityInformation_FieldsPicklistValuesFields 1743
TicketChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1744
TicketChecklistItemsEntityInformationFields 1745
TicketChecklistItemsEntityInformationUserDefinedFields 1745
TicketChecklistLibrariesEntityInformation 1746
TicketChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 1747
TicketChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 1747
TicketChecklistLibrariesEntityInformationFields 1748
TicketChecklistLibrariesEntityInformationUserDefinedFields 1749
TicketHistory 2219
TicketHistoryById 2220
TicketHistoryCount 2220
TicketHistoryEntityInformation 1749
TicketHistoryEntityInformation_FieldsPicklistValuesFields 1750
TicketHistoryEntityInformation_FieldsPicklistValuesUserDefinedFields 1751
TicketHistoryEntityInformationFields 1752
TicketHistoryEntityInformationUserDefinedFields 1752
ticketID 45, 46, 47, 48, 58, 59, 65, 67, 139, 140, 142, 144, 364, 366, 408, 410, 411, 428, 429, 432, 433, 1914, 1915, 2012, 2013, 2014, 2016, 2105, 2106, 2107, 2108, 2109, 2110, 2112, 2113, 2127, 2180, 2181, 2182, 2184, 2185, 2187, 2188, 2189, 2190, 2192, 2193, 2202, 2203, 2204, 2205, 2206, 2208, 2210, 2212, 2214, 2216, 2217, 2219, 2220, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2243, 2244, 2245, 2246, 2256, 2257, 2259, 2260, 2261, 2263, 2264, 2280, 2282, 2284, 2285, 2287, 2288
TicketNoteAttachments 2221
TicketNoteAttachmentsById 2222
TicketNoteAttachmentsCount 2223
TicketNoteAttachmentsEntityInformation 1753
TicketNoteAttachmentsEntityInformation_FieldsPicklistValuesFields 1754
TicketNoteAttachmentsEntityInformationFields 1754
ticketNoteID 58, 59, 2189, 2190, 2192, 2193, 2221, 2222, 2224, 2225
TicketNotes 2227

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

TicketNotesById 2228
TicketNotesByParentIdAttachments 2224
TicketNotesByParentIdAttachmentsId 2225
TicketNotesCount 2229
TicketNotesEntityInformation 1755
TicketNotesEntityInformation_FieldsPicklistValuesFields 1756
TicketNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1756
TicketNotesEntityInformationFields 1757
TicketNotesEntityInformationUserDefinedFields 1758
TicketNoteWebhookExcludedResources 2232
TicketNoteWebhookExcludedResourcesById 2233
TicketNoteWebhookExcludedResourcesCount 2234
TicketNoteWebhookExcludedResourcesEntityInformation 1758
TicketNoteWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields 1759
TicketNoteWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1760
TicketNoteWebhookExcludedResourcesEntityInformationFields 1761
TicketNoteWebhookExcludedResourcesEntityInformationUserDefinedFields 1761
TicketNoteWebhookFields 2236
TicketNoteWebhookFieldsById 2237
TicketNoteWebhookFieldsCount 2238
TicketNoteWebhookFieldsEntityInformation 1762
TicketNoteWebhookFieldsEntityInformation_FieldsPicklistValuesFields 1763
TicketNoteWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1763
TicketNoteWebhookFieldsEntityInformationFields 1764
TicketNoteWebhookFieldsEntityInformationUserDefinedFields 1765
TicketNoteWebhooks 2241
TicketNoteWebhooksById 2241
TicketNoteWebhooksByParentIdExcludedResources 2234
TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation 1765
TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 1767
TicketNoteWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1768
TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationFields 1769
TicketNoteWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 1770
TicketNoteWebhooksByParentIdExcludedResources2 2235
TicketNoteWebhooksByParentIdFields 2238
TicketNoteWebhooksByParentIdFieldsEntityInformation 1771
TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 1772
TicketNoteWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1774
TicketNoteWebhooksByParentIdFieldsEntityInformationFields 1775
TicketNoteWebhooksByParentIdFieldsEntityInformationUserDefinedFields 1776
TicketNoteWebhooksByParentIdFieldsId 2240
TicketNoteWebhooksCount 2243
TicketNoteWebhooksEntityInformation 1777
TicketNoteWebhooksEntityInformation_FieldsPicklistValuesFields 1778
TicketNoteWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 1778
TicketNoteWebhooksEntityInformationFields 1779
TicketNoteWebhooksEntityInformationUserDefinedFields 1780
ticketNumber 364, 366, 2247, 2250, 2253
TicketRmaCredits 2243
TicketRmaCreditsById 2244
TicketRmaCreditsCount 2245
TicketRmaCreditsEntityInformation 1781
TicketRmaCreditsEntityInformation_FieldsPicklistValuesFields 1781
TicketRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields 1782
TicketRmaCreditsEntityInformationFields 1783
TicketRmaCreditsEntityInformationUserDefinedFields 1783
Tickets 2247
Tickets Purchased 352, 353, 355, 356
Tickets Used 352, 353, 355, 356
Tickets_ItemsUserDefinedFields 2250
TicketsById 2253
TicketsByParentIdAdditionalConfigurationItems 2182
TicketsByParentIdAdditionalConfigurationItemsEntityInformation 1784
TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesFields 1785
TicketsByParentIdAdditionalConfigurationItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1786
TicketsByParentIdAdditionalConfigurationItemsEntityInformationFields 1788
TicketsByParentIdAdditionalConfigurationItemsEntityInformationUserDefinedFields 1789
TicketsByParentIdAdditionalConfigurationItemsId 2184
TicketsByParentIdAdditionalContacts 2187

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

TicketsByParentIdAdditionalContactsEntityInformation 1790
TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesFields 1791
TicketsByParentIdAdditionalContactsEntityInformation_FieldsPicklistValuesUserDefinedFields 1792
TicketsByParentIdAdditionalContactsEntityInformationFields 1793
TicketsByParentIdAdditionalContactsEntityInformationUserDefinedFields 1794
TicketsByParentIdAdditionalContactsId 2188
TicketsByParentIdAttachments 2192
TicketsByParentIdAttachmentsId 2193
TicketsByParentIdChangeRequestApprovals 2204
TicketsByParentIdChangeRequestApprovalsEntityInformation 1796
TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesFields 1797
TicketsByParentIdChangeRequestApprovalsEntityInformation_FieldsPicklistValuesUserDefinedFields 1798
TicketsByParentIdChangeRequestApprovalsEntityInformationFields 1799
TicketsByParentIdChangeRequestApprovalsEntityInformationUserDefinedFields 1800
TicketsByParentIdChangeRequestApprovalsId 2205
TicketsByParentIdCharges 2210
TicketsByParentIdChargesEntityInformation 1801
TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesFields 1802
TicketsByParentIdChargesEntityInformation_FieldsPicklistValuesUserDefinedFields 1804
TicketsByParentIdChargesEntityInformationFields 1805
TicketsByParentIdChargesEntityInformationUserDefinedFields 1806
TicketsByParentIdChargesId 2212
TicketsByParentIdChecklistItems 2216
TicketsByParentIdChecklistItemsEntityInformation 1807
TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesFields 1808
TicketsByParentIdChecklistItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1809
TicketsByParentIdChecklistItemsEntityInformationFields 1810
TicketsByParentIdChecklistItemsEntityInformationUserDefinedFields 1811
TicketsByParentIdChecklistItemsId 2217
TicketsByParentIdChecklistLibrariesEntityInformation 1813
TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesFields 1814
TicketsByParentIdChecklistLibrariesEntityInformation_FieldsPicklistValuesUserDefinedFields 1815
TicketsByParentIdChecklistLibrariesEntityInformationFields 1816
TicketsByParentIdChecklistLibrariesEntityInformationUserDefinedFields 1817
TicketsByParentIdNotes 2229
TicketsByParentIdNotesEntityInformation 1818
TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesFields 1819
TicketsByParentIdNotesEntityInformation_FieldsPicklistValuesUserDefinedFields 1820
TicketsByParentIdNotesEntityInformationFields 1822
TicketsByParentIdNotesEntityInformationUserDefinedFields 1823
TicketsByParentIdNotesId 2231
TicketsByParentIdRmaCredits 2245
TicketsByParentIdRmaCreditsEntityInformation 1824
TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesFields 1825
TicketsByParentIdRmaCreditsEntityInformation_FieldsPicklistValuesUserDefinedFields 1826
TicketsByParentIdRmaCreditsEntityInformationFields 1827
TicketsByParentIdRmaCreditsEntityInformationUserDefinedFields 1828
TicketsByParentIdRmaCreditsId 2246
TicketsByParentIdSecondaryResources 2259
TicketsByParentIdSecondaryResourcesEntityInformation 1829
TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesFields 1831
TicketsByParentIdSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1832
TicketsByParentIdSecondaryResourcesEntityInformationFields 1833
TicketsByParentIdSecondaryResourcesEntityInformationUserDefinedFields 1834
TicketsByParentIdSecondaryResourcesId 2260
TicketsByParentIdTagAssociations 2263
TicketsByParentIdTagAssociationsEntityInformation 1835
TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesFields 1836
TicketsByParentIdTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1838
TicketsByParentIdTagAssociationsEntityInformationFields 1839
TicketsByParentIdTagAssociationsEntityInformationUserDefinedFields 1840
TicketsByParentIdTagAssociationsId 2264
TicketsCount 2256

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

TicketSecondaryResources 2256
TicketSecondaryResourcesById 2257
TicketSecondaryResourcesCount 2258
TicketSecondaryResourcesEntityInformation 1841
TicketSecondaryResourcesEntityInformation_FieldsPicklistValuesFields 1842
TicketSecondaryResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1842
TicketSecondaryResourcesEntityInformationFields 1843
TicketSecondaryResourcesEntityInformationUserDefinedFields 1844
TicketsEntityInformation 1844
TicketsEntityInformation_FieldsPicklistValuesFields 1845
TicketsEntityInformation_FieldsPicklistValuesUserDefinedFields 1846
TicketsEntityInformationFields 1847
TicketsEntityInformationUserDefinedFields 1847
ticketsPurchased 352, 353, 355, 356
ticketsUsed 352, 353, 355, 356
TicketTagAssociations 2261
TicketTagAssociationsById 2261
TicketTagAssociationsCount 2263
TicketTagAssociationsEntityInformation 1848
TicketTagAssociationsEntityInformation_FieldsPicklistValuesFields 1849
TicketTagAssociationsEntityInformation_FieldsPicklistValuesUserDefinedFields 1849
TicketTagAssociationsEntityInformationFields 1850
TicketTagAssociationsEntityInformationUserDefinedFields 1851
ticketTitle 366
ticketType 2247, 2250, 2253
ticketTypeID 2197, 2198, 2199, 2200
TicketWebhookExcludedResources 2265
TicketWebhookExcludedResourcesById 2266
TicketWebhookExcludedResourcesCount 2267
TicketWebhookExcludedResourcesEntityInformation 1851
TicketWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesFields 1852
TicketWebhookExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1853
TicketWebhookExcludedResourcesEntityInformationFields 1854
TicketWebhookExcludedResourcesEntityInformationUserDefinedFields 1854
TicketWebhookFields 2269
TicketWebhookFieldsById 2270
TicketWebhookFieldsCount 2271
TicketWebhookFieldsEntityInformation 1855
TicketWebhookFieldsEntityInformation_FieldsPicklistValuesFields 1856
TicketWebhookFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1856
TicketWebhookFieldsEntityInformationFields 1857
TicketWebhookFieldsEntityInformationUserDefinedFields 1858
TicketWebhooks 2274
TicketWebhooksById 2274
TicketWebhooksByParentIdExcludedResources 2267
TicketWebhooksByParentIdExcludedResourcesEntityInformation 1858
TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesFields 1859
TicketWebhooksByParentIdExcludedResourcesEntityInformation_FieldsPicklistValuesUserDefinedFields 1861
TicketWebhooksByParentIdExcludedResourcesEntityInformationFields 1862
TicketWebhooksByParentIdExcludedResourcesEntityInformationUserDefinedFields 1863
TicketWebhooksByParentIdExcludedResourcesId 2268
TicketWebhooksByParentIdFields 2271
TicketWebhooksByParentIdFieldsEntityInformation 1864
TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesFields 1865
TicketWebhooksByParentIdFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1866
TicketWebhooksByParentIdFieldsEntityInformationFields 1868
TicketWebhooksByParentIdFieldsEntityInformationUserDefinedFields 1869
TicketWebhooksByParentIdFieldsId 2273
TicketWebhooksByParentIdUdfFields 2278
TicketWebhooksByParentIdUdfFieldsEntityInformation 1870
TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesFields 1871
TicketWebhooksByParentIdUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1872
TicketWebhooksByParentIdUdfFieldsEntityInformationFields 1873
TicketWebhooksByParentIdUdfFieldsEntityInformationUserDefinedFields 1874
TicketWebhooksByParentIdUdfFieldsId 2279
TicketWebhooksCount 2276
TicketWebhooksEntityInformation 1876
TicketWebhooksEntityInformation_FieldsPicklistValuesFields 1876
TicketWebhooksEntityInformation_FieldsPicklistValuesUserDefinedFields 1877

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

TicketWebhooksEntityInformationFields 1878
TicketWebhooksEntityInformationUserDefinedFields 1878
TicketWebhookUdfFields 2276
TicketWebhookUdfFieldsById 2277
TicketWebhookUdfFieldsCount 2278
TicketWebhookUdfFieldsEntityInformation 1879
TicketWebhookUdfFieldsEntityInformation_FieldsPicklistValuesFields 1880
TicketWebhookUdfFieldsEntityInformation_FieldsPicklistValuesUserDefinedFields 1880
TicketWebhookUdfFieldsEntityInformationFields 1881
TicketWebhookUdfFieldsEntityInformationUserDefinedFields 1882
Time Entry ID 58, 59, 64, 65, 67, 1914, 1915, 2138, 2139, 2141, 2142, 2189, 2190, 2192, 2193, 2284, 2285, 2287, 2288
Time Entry Type 2280, 2282
Time Format 82, 83, 456, 458, 484, 486, 2054, 2055
Time of Request Type 2290, 2291, 2293, 2294
Time Reporting Requires Start and Stop Times 329, 330, 331
Time Zone ID 456, 458
TimeEntries 2280
TimeEntriesById 2282
TimeEntriesByParentIdAttachments 2287
TimeEntriesByParentIdAttachmentsId 2288
TimeEntriesCount 2283
TimeEntriesEntityInformation 1883
TimeEntriesEntityInformation_FieldsPicklistValuesFields 1883
TimeEntriesEntityInformation_FieldsPicklistValuesUserDefinedFields 1884
TimeEntriesEntityInformationFields 1885
TimeEntriesEntityInformationUserDefinedFields 1885
TimeEntryAttachments 2284
TimeEntryAttachmentsById 2285
TimeEntryAttachmentsCount 2286
TimeEntryAttachmentsEntityInformation 1886
TimeEntryAttachmentsEntityInformation_FieldsPicklistValuesFields 1887
TimeEntryAttachmentsEntityInformationFields 1887
timeEntryID 58, 59, 64, 65, 67, 1914, 1915, 2138, 2139, 2141, 2142, 2189, 2190, 2192, 2193, 2284, 2285, 2287, 2288
timeEntryType 2280, 2282
timeFormat 82, 83, 456, 458, 484, 486, 2054, 2055
TimeOffRequests 2290
TimeOffRequestsById 2291
TimeOffRequestsCount 2292
TimeOffRequestsEntityInformation 1888
TimeOffRequestsEntityInformation_FieldsPicklistValuesFields 1889
TimeOffRequestsEntityInformation_FieldsPicklistValuesUserDefinedFields 1889
TimeOffRequestsEntityInformationFields 1890
TimeOffRequestsEntityInformationUserDefinedFields 1891
timeOffRequestType 2290, 2291, 2293, 2294
Timeout (sec) 1912
TIMEOUT_SEC 1912
timeReportingRequiresStartAndStopTimes 329, 330, 331
Time-to-live Seconds 175, 176, 177, 178
timeToLiveSeconds 175, 176, 177, 178
Timezone 454
timeZoneID 456, 458
Title 20, 21, 22, 23, 25, 27, 31, 32, 34, 35, 58, 59, 97, 98, 100, 102, 105, 107, 109, 117, 118, 120, 122, 160, 162, 163, 165, 179, 180, 182, 183, 185, 186, 187, 189, 235, 237, 239, 298, 299, 300, 302, 303, 304, 306, 308, 309, 310, 312, 313, 369, 370, 372, 374, 389, 390, 391, 393, 398, 399, 401, 402, 422, 423, 425, 427, 435, 436, 438, 440, 450, 452, 488, 490, 491, 1917, 1918, 1920, 1923, 1924, 1926, 1927, 1939, 1940, 1942, 1943, 1957, 1958, 1959, 1960, 1975, 1976, 1978, 1979, 1988, 1989, 1991, 1992, 1994, 1995, 1997, 1998, 2036, 2037, 2038, 2040, 2054, 2055, 2068, 2069, 2071, 2072, 2074, 2075, 2076, 2078, 2080, 2082, 2138, 2139, 2141, 2142, 2144, 2145, 2147, 2148, 2150, 2151, 2152, 2154, 2159, 2161, 2163, 2165, 2167, 2169, 2189, 2190, 2192, 2193, 2197, 2198, 2199, 2200, 2221, 2222, 2224, 2225, 2227, 2228, 2229, 2231, 2247, 2250, 2253, 2284, 2285, 2287, 2288
To Date 482, 483
To Location ID 478, 479
toDate 482, 483
toLocationID 478, 479
Total Amount 65, 67
Total Amount Months 1917, 1918, 1920
Total Cost 2124, 2125
Total Effective Tax 2020, 2022, 2024, 2026
Total Price 2124, 2125
Total Tax Value 482, 483
totalAmount 65, 67
totalAmountMonths 1917, 1918, 1920
totalCost 2124, 2125
totalEffectiveTax 2020, 2022, 2024, 2026
totalPrice 2124, 2125
totalTaxValue 482, 483
Transaction ID 1912
TRANSACTION_ID 1912
Transfer by Resource ID 478, 479

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Transfer Date 478, 479
transferByResourceID 478, 479
transferDate 478, 479
transferredUnits 471, 472, 475, 476
Travel Availability (%) 2054, 2055
travelAvailabilityPct 2054, 2055
Tuesday Business Hours End Time 456, 458
Tuesday Business Hours Start Time 456, 458
Tuesday Extended Hours End Time 456, 458
Tuesday Extended Hours Start Time 456, 458
tuesdayBusinessHoursEndTime 456, 458
tuesdayBusinessHoursStartTime 456, 458
tuesdayExtendedHoursEndTime 456, 458
tuesdayExtendedHoursStartTime 456, 458
Twitter URL 105, 107, 109, 235, 237, 239
twitterUrl 105, 107, 109, 235, 237, 239

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Type 496, 497, 500, 501, 503, 505, 509, 510, 512, 514, 516, 517, 519, 521, 523, 524, 526, 528, 530, 531, 533, 535, 537, 538, 540, 542, 544, 545, 547, 549, 551, 552, 555, 558, 560, 562, 564, 565, 567, 569, 571, 572, 574, 576, 579, 581, 584, 587, 590, 592, 596, 598, 601, 604, 607, 609, 613, 615, 617, 619, 621, 622, 626, 628, 630, 631, 635, 637, 639, 640, 642, 644, 646, 647, 649, 651, 653, 654, 657, 660, 663, 665, 669, 671, 674, 675, 677, 679, 683, 684, 688, 691, 692, 695, 696, 698, 702, 704, 705, 707, 709, 713, 716, 719, 722, 724, 728, 730, 734, 737, 738, 741, 742, 744, 746, 748, 749, 751, 753, 757, 760, 763, 766, 768, 771, 772, 774, 776, 778, 779, 781, 783, 786, 788, 791, 792, 795, 797, 800, 801, 803, 805, 807, 808, 811, 814, 817, 819, 823, 825, 828, 829, 831, 833, 835, 836, 838, 840, 842, 843, 845, 847, 849, 850, 852, 854, 856, 857, 860, 861, 864, 866, 870, 872, 875, 876, 878, 880, 884, 885, 887, 889, 891, 892, 894, 896, 899, 901, 904, 907, 910, 912, 916, 918, 921, 924, 927, 929, 933, 935, 938, 941, 944, 946, 950, 952, 955, 957, 961, 963, 967, 969, 972, 975, 978, 980, 984, 986, 989, 992, 995, 997, 1000, 1001, 1003, 1005, 1007, 1008, 1011, 1012, 1014, 1016, 1018, 1019, 1021, 1023, 1025, 1026, 1028, 1030, 1032, 1033, 1035, 1037, 1039, 1040, 1042, 1044, 1046, 1047, 1052, 1055, 1057, 1059, 1061, 1062, 1064, 1066, 1068, 1069, 1071, 1073, 1075, 1076, 1078, 1080, 1083, 1085, 1089, 1091, 1094, 1097, 1100, 1102, 1107, 1110, 1113, 1116, 1118, 1122, 1124, 1128, 1130, 1133, 1136, 1138, 1140, 1142, 1143, 1145, 1147, 1149, 1150, 1152, 1154, 1156, 1157, 1161, 1163, 1167, 1168, 1171, 1174, 1176, 1177, 1180, 1183, 1185, 1187, 1189, 1190, 1192, 1194, 1196, 1197, 1199, 1201, 1204, 1206, 1209, 1210, 1212, 1214, 1216, 1217, 1220, 1223, 1226, 1228, 1232, 1234, 1237, 1240, 1242, 1244, 1246, 1247, 1249, 1251, 1253, 1254, 1256, 1258, 1260, 1261, 1263, 1265, 1267, 1268, 1272, 1277, 1281, 1285, 1287, 1290, 1293, 1296, 1299, 1303, 1306, 1307, 1311, 1314, 1315, 1317, 1319, 1322, 1324, 1326, 1328, 1332, 1333, 1335, 1337, 1341, 1343, 1345, 1347, 1348, 1350, 1352, 1354, 1355, 1357, 1359, 1361, 1362, 1364, 1366, 1368, 1369, 1371, 1373, 1375, 1376, 1378, 1380, 1382, 1383, 1386, 1389, 1392, 1394, 1398, 1400, 1402, 1404, 1406, 1407, 1409, 1411, 1415, 1416, 1420, 1422, 1425, 1427, 1430, 1432, 1436, 1438, 1441, 1444, 1446, 1448, 1450, 1451, 1453, 1455, 1458, 1460, 1463, 1464, 1467, 1469, 1472, 1473, 1475, 1477, 1479, 1480, 1483, 1485, 1488, 1489, 1491, 1493, 1497, 1498, 1500, 1502, 1504, 1505, 1508, 1510, 1514, 1516, 1519, 1522, 1525, 1527, 1531, 1533, 1536, 1539, 1541, 1543, 1545, 1546, 1548, 1550, 1552, 1553, 1557, 1559, 1562, 1564, 1566, 1568, 1570, 1571, 1574, 1577, 1580, 1582, 1585, 1586, 1588, 1590, 1593, 1595, 1598, 1599, 1601, 1603, 1605, 1608, 1610, 1612, 1614, 1615, 1618, 1621, 1623, 1624, 1627, 1628, 1630, 1631, 1634, 1635, 1638, 1640, 1643, 1644, 1646, 1648, 1650, 1651, 1653, 1655, 1657, 1658, 1661, 1663, 1666, 1667, 1673, 1675, 1677, 1678, 1681, 1683, 1687, 1689, 1692, 1695, 1697, 1699, 1701, 1702, 1704, 1706, 1708, 1709, 1711, 1713, 1715, 1716, 1718, 1720, 1725, 1727, 1730, 1731, 1733, 1735, 1737, 1738, 1740, 1742, 1744, 1745, 1747, 1749, 1751, 1752, 1756, 1758, 1760, 1761,
Type ID 361, 362, 364
typeID 361, 362, 364

U -

UDF Field ID 156, 157, 158, 159, 220, 221, 223, 224, 252, 253, 254, 255, 2276, 2277, 2278, 2279, 2298, 2299, 2300, 2301
UDF Type 2295, 2296
udfFieldId 156, 157, 158, 159, 220, 221, 223, 224, 252, 253, 254, 255, 2276, 2277, 2278, 2279, 2298, 2299, 2300, 2301
udfType 2295, 2296
Unit Cost 61, 62, 70, 71, 272, 273, 275, 277, 343, 344, 345, 347, 471, 472, 475, 476, 1962, 1963, 1964, 1966, 1968, 1969, 1981, 1982, 1984, 1986, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2084, 2114, 2115, 2206, 2208, 2210, 2212
Unit Discount 2020, 2022, 2024, 2026, 2084
Unit Price 61, 62, 70, 71, 272, 273, 275, 277, 333, 334, 336, 337, 343, 344, 345, 347, 1944, 1945, 1946, 1948, 1952, 1953, 1954, 1962, 1963, 1964, 1966, 1968, 1969, 1981, 1982, 1984, 1986, 2020, 2022, 2024, 2026, 2084, 2114, 2115, 2206, 2208, 2210, 2212
Unit Quantity 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
unitCost 61, 62, 70, 71, 272, 273, 275, 277, 343, 344, 345, 347, 471, 472, 475, 476, 1962, 1963, 1964, 1966, 1968, 1969, 1981, 1982, 1984, 1986, 2012, 2013, 2014, 2016, 2020, 2022, 2024, 2026, 2084, 2114, 2115, 2206, 2208, 2210, 2212
unitDiscount 2020, 2022, 2024, 2026, 2084
unitPrice 61, 62, 70, 71, 272, 273, 275, 277, 333, 334, 336, 337, 343, 344, 345, 347, 1944, 1945, 1946, 1948, 1952, 1953, 1954, 1962, 1963, 1964, 1966, 1968, 1969, 1981, 1982, 1984, 1986, 2020, 2022, 2024, 2026, 2084, 2114, 2115, 2206, 2208, 2210, 2212
unitQuantity 70, 71, 272, 273, 275, 277, 1981, 1982, 1984, 1986, 2206, 2208, 2210, 2212
Units 338, 339, 341, 342, 348, 349, 350, 351
unitsOnOrder 469
Update Date/Time 20, 21
Update Note 478, 479
Update Resource ID 359, 360, 2084, 2114, 2115
updateDateTime 20, 21
updateNote 478, 479
updateResourceID 359, 360, 2084, 2114, 2115
Up-time (seconds) 194, 198, 202
Up-to Unit Count 1966, 1968, 1969
upToUnitCount 1966, 1968, 1969
URL 421, 1912, 2306
Use HTTP Disk Cache 1912
Use HTTP Memory Cache 1912

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Use Item Descriptions from 2017, 2018
Use Quote Totals 1917, 1918, 1920
Use Type 61, 62
use-batch-insert 2
Used (Kilobytes) 194, 198, 202
use-http-disk-cache-read 2
use-http-disk-cache-write 2
use-http-memory-cache-read 2
use-http-memory-cache-write 2
useItemDescriptionsFrom 2017, 2018
useQuoteTotals 1917, 1918, 1920
user 2306
User Name 82, 83, 2054, 2055
User Type 2054, 2055
User-defined Field Definition ID 172, 174
userDefinedFieldDefinitionID 172, 174
UserDefinedFieldDefinitions 2295
UserDefinedFieldDefinitionsById 2296
UserDefinedFieldDefinitionsCount 2297
UserDefinedFieldDefinitionsEntityInformation 1892
UserDefinedFieldDefinitionsEntityInformation_FieldsPicklistValuesFields 1892
UserDefinedFieldDefinitionsEntityInformation_FieldsPicklistValuesUserDefinedFields 1893
UserDefinedFieldDefinitionsEntityInformationFields 1894
UserDefinedFieldDefinitionsEntityInformationUserDefinedFields 1894
UserDefinedFieldListItems 2298
UserDefinedFieldListItemsById 2299
UserDefinedFieldListItemsCount 2300
UserDefinedFieldListItemsEntityInformation 1895
UserDefinedFieldListItemsEntityInformation_FieldsPicklistValuesFields 1896
UserDefinedFieldListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1896
UserDefinedFieldListItemsEntityInformationFields 1897
UserDefinedFieldListItemsEntityInformationUserDefinedFields 1898
UserDefinedFieldsByParentIdListItems 2300
UserDefinedFieldsByParentIdListItemsEntityInformation 1899
UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesFields 1900
UserDefinedFieldsByParentIdListItemsEntityInformation_FieldsPicklistValuesUserDefinedFields 1901
UserDefinedFieldsByParentIdListItemsEntityInformationFields 1902
UserDefinedFieldsByParentIdListItemsEntityInformationUserDefinedFields 1903
UserDefinedFieldsByParentIdListItemsId 2301
userName 82, 83, 2054, 2055
userType 2054, 2055
Uses Internal Currency Price 1944, 1945, 1946, 1948, 1950, 1952, 1953, 1954, 1955
usesInternalCurrencyPrice 1944, 1945, 1946, 1948, 1950, 1952, 1953, 1954, 1955
useType 61, 62

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

- V -

Value 88, 105, 130, 132, 198, 237, 330, 495, 496, 499, 500, 502, 503, 506, 508, 509, 511, 512, 515, 516, 518, 519, 522, 523, 525, 526, 529, 530, 533, 536, 537, 540, 543, 544, 547, 550, 551, 554, 555, 559, 560, 563, 564, 566, 567, 570, 571, 573, 574, 577, 579, 583, 584, 589, 590, 594, 596, 600, 601, 606, 607, 611, 613, 617, 620, 621, 624, 626, 629, 630, 633, 635, 638, 639, 642, 645, 646, 649, 652, 653, 656, 657, 662, 663, 668, 669, 673, 674, 676, 677, 680, 682, 683, 686, 690, 691, 694, 695, 697, 698, 701, 703, 704, 706, 707, 710, 715, 716, 721, 722, 726, 728, 732, 736, 737, 740, 741, 743, 744, 747, 748, 751, 755, 759, 760, 765, 766, 770, 771, 774, 777, 778, 781, 785, 786, 790, 791, 794, 795, 799, 800, 803, 806, 807, 810, 811, 816, 817, 822, 823, 827, 828, 830, 831, 834, 835, 837, 838, 841, 842, 845, 848, 849, 852, 855, 856, 859, 860, 863, 864, 869, 870, 874, 875, 877, 878, 881, 883, 884, 886, 887, 890, 891, 893, 894, 897, 899, 903, 904, 909, 910, 914, 916, 920, 921, 926, 927, 931, 933, 937, 938, 943, 944, 948, 950, 954, 955, 960, 961, 965, 967, 971, 972, 977, 978, 983, 984, 988, 989, 994, 995, 999, 1000, 1003, 1006, 1007, 1010, 1011, 1013, 1014, 1017, 1018, 1020, 1021, 1024, 1025, 1027, 1028, 1031, 1032, 1034, 1035, 1038, 1039, 1042, 1045, 1046, 1049, 1051, 1052, 1056, 1057, 1060, 1061, 1063, 1064, 1067, 1068, 1071, 1074, 1075, 1078, 1082, 1083, 1087, 1089, 1093, 1094, 1099, 1100, 1105, 1109, 1110, 1115, 1116, 1121, 1122, 1126, 1128, 1132, 1133, 1137, 1138, 1141, 1142, 1144, 1145, 1148, 1149, 1152, 1155, 1156, 1159, 1161, 1164, 1166, 1167, 1170, 1171, 1175, 1176, 1179, 1180, 1184, 1185, 1188, 1189, 1191, 1192, 1195, 1196, 1199, 1203, 1204, 1208, 1209, 1211, 1212, 1215, 1216, 1219, 1220, 1225, 1226, 1230, 1232, 1236, 1237, 1242, 1245, 1246, 1249, 1252, 1253, 1256, 1259, 1260, 1263, 1266, 1267, 1270, 1274, 1279, 1283, 1285, 1289, 1290, 1295, 1296, 1301, 1305, 1306, 1309, 1313, 1314, 1316, 1317, 1320, 1322, 1326, 1329, 1331, 1332, 1335, 1339, 1343, 1346, 1347, 1350, 1353, 1354, 1357, 1360, 1361, 1364, 1367, 1368, 1371, 1374, 1375, 1378, 1381, 1382, 1385, 1386, 1391, 1392, 1396, 1398, 1402, 1405, 1406, 1409, 1412, 1414, 1415, 1417, 1419, 1420, 1423, 1425, 1429, 1430, 1435, 1436, 1440, 1441, 1445, 1446, 1449, 1450, 1452, 1453, 1456, 1458, 1462, 1463, 1466, 1467, 1471, 1472, 1474, 1475, 1478, 1479, 1482, 1483, 1487, 1488, 1491, 1494, 1496, 1497, 1499, 1500, 1503, 1504, 1507, 1508, 1513, 1514, 1518, 1519, 1524, 1525, 1530, 1531, 1535, 1536, 1540, 1541, 1544, 1545, 1547, 1548, 1551, 1552, 1554, 1556, 1557, 1560, 1562, 1566, 1569, 1570, 1573, 1574, 1579, 1580, 1584, 1585, 1587, 1588, 1591, 1593, 1597, 1598, 1600, 1601, 1604, 1605, 1610, 1613, 1614, 1617, 1618, 1622, 1623, 1626, 1627, 1629, 1630, 1633, 1634, 1637, 1638, 1642, 1643, 1645, 1646, 1649, 1650, 1652, 1653, 1656, 1657, 1660, 1661, 1665, 1666, 1669, 1671, 1673, 1676, 1677, 1680, 1681, 1685, 1687, 1691, 1692, 1696, 1697, 1700, 1701, 1703, 1704, 1707, 1708, 1710, 1711, 1714, 1715, 1718, 1721, 1724, 1725, 1729, 1730, 1732, 1733, 1736, 1737, 1740, 1743, 1744, 1747, 1750, 1751, 1754, 1756, 1759, 1760, 1763, 1767, 1768, 1772, 1774, 1778, 1781, 1782, 1785, 1786, 1791, 1792, 1797, 1798, 1802, 1804, 1808, 1809,

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value for Display 2298, 2299, 2300, 2301
Value for Export 2298, 2299, 2300, 2301
valueForDisplay 2298, 2299, 2300, 2301
valueForExport 2298, 2299, 2300, 2301
Vendor Company ID 348, 349, 350, 351, 2114, 2115
Vendor Cost 1970, 1971, 1972, 1973
Vendor ID 65, 67, 194, 198, 202, 471, 472, 475, 476, 1970, 1971, 1972, 1973, 2017, 2018, 2124, 2125
Vendor Invoice Number 471, 472, 475, 476, 2007, 2009, 2010, 2017, 2018
Vendor Part Number 1970, 1971, 1972, 1973
Vendor Product Number 1962, 1963, 1964
Vendor Supplied ID 450, 452
vendorCompanyID 348, 349, 350, 351, 2114, 2115
vendorCost 1970, 1971, 1972, 1973
vendorID 65, 67, 194, 198, 202, 471, 472, 475, 476, 1970, 1971, 1972, 1973, 2017, 2018, 2124, 2125
vendorInvoiceNumber 471, 472, 475, 476, 2007, 2009, 2010, 2017, 2018
vendorPartNumber 1970, 1971, 1972, 1973
vendorProductNumber 1962, 1963, 1964
vendorSuppliedID 450, 452
Version 61
VersionInformation 20
View 17
Voided by Resource ID 482, 483
Voided Date 482, 483
voidedByResourceID 482, 483
voidedDate 482, 483

- W -

Warranty Expiration Date 194, 198, 202
warrantyExpirationDate 194, 198, 202
Web Address 86, 88, 90
Web URL 2306
webAddress 86, 88, 90
Webhook GUID 154, 218, 219, 250, 2241, 2274
Webhook ID 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279
Webhook URL 154, 218, 219, 250, 2241, 2274
WebhookEventErrorLogs 2302
WebhookEventErrorLogsById 2303
WebhookEventErrorLogsCount 2304
WebhookEventErrorLogsEntityInformation 1904
WebhookEventErrorLogsEntityInformation_FieldsPicklistValuesFields 1905
WebhookEventErrorLogsEntityInformation_FieldsPicklistValuesUserDefinedFields 1906
WebhookEventErrorLogsEntityInformationFields 1907
WebhookEventErrorLogsEntityInformationUserDefinedFields 1907
webhookGUID 154, 218, 219, 250, 2241, 2274
webhookID 145, 146, 147, 148, 149, 150, 151, 153, 156, 157, 158, 159, 210, 211, 212, 214, 216, 217, 220, 221, 223, 224, 241, 242, 243, 244, 245, 246, 247, 249, 252, 253, 254, 255, 2232, 2233, 2234, 2235, 2236, 2237, 2238, 2240, 2265, 2266, 2267, 2268, 2269, 2270, 2271, 2273, 2276, 2277, 2278, 2279
webhookUrl 154, 218, 219, 250, 2241, 2274
Webservice Date 65, 67, 482, 483
webServiceDate 65, 67, 482, 483
webUrl 2306
Wednesday Business Hours End Time 456, 458
Wednesday Business Hours Start Time 456, 458
Wednesday Extended Hours End Time 456, 458
Wednesday Extended Hours Start Time 456, 458
wednesdayBusinessHoursEndTime 456, 458
wednesdayBusinessHoursStartTime 456, 458
wednesdayExtendedHoursEndTime 456, 458
wednesdayExtendedHoursStartTime 456, 458
Weekending 441, 442
Widget Key 452
widgetKey 452
Width 452
Win Reason 1917, 1918, 1920
Win Reason Detail 1917, 1918, 1920
winReason 1917, 1918, 1920
winReasonDetail 1917, 1918, 1920
Work Type 428, 429, 432, 433
Work Type Modifier ID 1955
workType 428, 429, 432, 433
Worktype ID 2197, 2198, 2199, 2200
workTypeID 2197, 2198, 2199, 2200
workTypeModifierID 1955
WorkTypeModifiers 2304
WorkTypeModifiersById 2305
WorkTypeModifiersCount 2305
WorkTypeModifiersEntityInformation 1908
WorkTypeModifiersEntityInformation_FieldsPicklistValuesFields 1908
WorkTypeModifiersEntityInformation_FieldsPicklistValuesUserDefinedFields 1909
WorkTypeModifiersEntityInformationFields 1910
WorkTypeModifiersEntityInformationUserDefinedFields 1911

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

- Y -

Yearly Cost 1917, 1918, 1920
Yearly Revenue 1917, 1918, 1920
yearlyCost 1917, 1918, 1920
yearlyRevenue 1917, 1918, 1920

- Z -

ZIP Code 105, 107, 109, 235, 237, 239
zipCode 105, 107, 109, 235, 237, 239
Zone Name 2306
ZoneInformation 2306
zoneName 2306

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.



Invantive B.V.
Biesteweg 11
3849 RD Hierden
the Netherlands

Tel: +31 88 00 26 500
Fax: +31 84 22 58 178
info@invantive.com
invantive.com

IBAN NL25 BUNQ 2098 2586 07
Chamber of Industry and Commerce
13031406
VAT NL812602377B01
RSIN 8122602377
Managing Director: Guido Leenders
Registered office: Roermond

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.
24.0.92
29/06/2026, 18:27
ISBN 978-94-6302-000-8: