

OpenArch Data Model

for use with Invantive SQL

24.0

invantive
the SQL company

Auteursrecht

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Alle rechten voorbehouden. Niets uit deze uitgave mag worden verveelvoudigd, opgeslagen in een geautomatiseerd gegevensbestand, of openbaar gemaakt, in enige vorm of op enige wijze, hetzij elektronisch, mechanisch, door fotokopieen, opnamen, of enig andere manier, zonder voorafgaande schriftelijke toestemming van de uitgever.

Ondanks alle aan de samenstelling van deze tekst bestede zorg, kan noch de schrijver noch de uitgever aansprakelijkheid aanvaarden voor eventuele schade, die zou kunnen voortvloeien uit enige fout, die in deze uitgave zou kunnen voorkomen.

Deze handleiding is een naslagwerk bedoeld om het gebruik te verduidelijken. Indien gegevens in de voorbeeldafbeeldingen overeenkomen met gegevens in uw systeem, dan is de overeenkomst toevallig.

Belangrijke Informatie over Veiligheid en Gebruik

Beoogd gebruik en beperkingen: Deze software, ontwikkeld door Invantive, is ontworpen om een verscheidenheid aan zakelijke en informatietechnologische gegevensverwerkingsfuncties te ondersteunen, zoals boekhouding, financiÃ«le rapportage en verkooprapportage. Het is belangrijk om op te merken dat deze software niet is ontworpen, getest of goedgekeurd voor gebruik in omgevingen waar een storing of defect kan leiden tot levensbedreigende situaties, ernstige fysieke schade of milieuschade. Dit omvat, maar is niet beperkt tot:

- Nucleaire faciliteiten: de software mag niet worden gebruikt voor operaties of functies die verband houden met de controle, het onderhoud of de werking van nucleaire faciliteiten.
- Defensie en militaire toepassingen: deze software is niet geschikt voor gebruik in defensiegerelateerde toepassingen, inclusief maar niet beperkt tot wapenbeheer, militaire strategieplanning of andere aspecten van nationale defensie.
- Luchtvaart: de software is niet bedoeld voor gebruik in de bediening, navigatie of communicatiesystemen van vliegtuigen of luchtverkeersleidingomgevingen.
- Gezondheidszorg en medicijnproductie: deze software mag niet worden gebruikt voor de werking van medische apparaten, de analyse van patiÃ«ntgegevens voor kritieke gezondheidsbeslissingen, farmaceutische productie of medisch onderzoek waarbij een storing of defect de gezondheid van de patiÃ«nt kan beÃ¯nvloeden.
- Verwerking van chemische en/of gevaarlijke stoffen: deze software is niet bedoeld voor het beheer, de controle of de operationele aspecten van chemische fabrieken of faciliteiten voor de verwerking van chemische en/of gevaarlijke stoffen. Elke storing in de software die in deze omgevingen wordt gebruikt kan leiden tot gevaarlijke chemische lozingen, explosies of milieurampen.
- Transport- en verkeerscontrolesystemen: de software mag niet worden gebruikt voor de besturing, bediening of het beheer van transportsystemen, waaronder de besturing van spoorwegsignalen, metrosystemen of verkeerslichten. Storingen in dergelijke kritieke systemen kunnen tot ernstige ongelukken leiden en de openbare veiligheid in gevaar brengen.
- Energienetwerk- en nutsbesturingssystemen: deze software is niet ontworpen voor de besturing of bediening van energienetwerksystemen, waaronder elektrische onderstations, besturingssystemen voor hernieuwbare energie of besturingssystemen van waternutsbedrijven. Het falen van software op deze gebieden kan leiden tot aanzienlijke stroomonderbrekingen, onderbrekingen in de watervoorziening of andere storingen in openbare voorzieningen, waardoor gemeenschappen in gevaar kunnen komen en grote schade kan worden aangericht.
- Andere omgevingen met een hoog risico: alle andere kritieke infrastructuren en omgevingen waar een storing in de software kan leiden tot aanzienlijke schade aan personen of het milieu.

Gebruikersverantwoordelijkheid: gebruikers moeten ervoor zorgen dat ze het beoogde gebruik van de software begrijpen en de software niet gebruiken in een omgeving die buiten het beoogde doel valt. Het is de verantwoordelijkheid van de gebruiker om de geschiktheid van de software voor de beoogde toepassing te beoordelen, vooral in scenario's die een risico kunnen vormen voor leven, gezondheid en/of milieu.
Afwijzing van aansprakelijkheid: Invantive wijst elke verantwoordelijkheid af voor schade, letsel of welke gevolgen die voortvloeien uit het gebruik of misbruik van deze software in verboden en/of onbedoelde toepassingen.

Inhoud

1 SQL Driver for OpenArch API 1

2 SQL Driver Attributes for OpenArch API 2

3 Schema: Native 14

3.1 Tables ... 14
3.1.1 NATIVEPLATFORMSCALARREQUESTS ... 14

4 Schema: OPENARCH 15

4.1 Tables ... 15
4.1.1 openarch_archive_statistics ... 15
4.1.2 openarch_archives ... 16
4.1.3 openarch_archives_by_name ... 16
4.1.4 openarch_comment_statistics ... 18
4.1.5 openarch_family_names ... 19
4.1.6 openarch_links_statistics ... 19
4.1.7 openarch_persons ... 20
4.1.8 openarch_persons_per_year ... 21
4.1.9 openarch_professions ... 23
4.1.10 openarch_relations ... 23
4.1.11 openarch_source_types ... 24

Index 26

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

1 SQL Driver for OpenArch API

Invantive SQL is the fastest, easiest and most reliable way to exchange data with the OpenArch API.

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the user community. Other users or Invantive Support will try to help you to our best.

OpenArch is cloud software for research. OpenArch combines numerous genealogical sources in the Netherlands. The data is typically cleaned from the original sources.

The OpenArch driver covers 12 tables and 75 columns.

OpenArch API Clients

Invantive SQL is available on many user interfaces ("clients" in traditional server-client paradigma). All Invantive SQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL. High-volume replication of data taken from the OpenArch API into traditional databases such as SQL Server (on-premise and Azure), MySQL, PostgreSQL and Oracle is possible using Invantive Data Replicator. Invantive Data Replicator automatically creates and maintains OpenArch datawarehouses, possibly in combination with data from over 70 other (cloud) platforms. Data Replicator supports data volumes up to over 1 TB and over 5.000 companies. The on-premise edition of Invantive Bridge offers an OpenArch ADO.net provider.

Monitor API Calls

When a query or DML-statement has been executed on Invantive SQL a developer can evaluate the actual calls made to the OpenArch API using a query on sessionios@DataDictionary. As an alternative, extensive request and response logging can be enabled by setting log-native-calls-to-disk to true. In the %USERPROFILE% \Invantive\NativeLog folder Invantive SQL will create log files per API request and response.

Specifications

The SQL driver for OpenArch does not support partitioning. Define one data container in a database for each company in OpenArch to enable parallel access for data from multiple companies.

An introduction into the concepts of Invantive SQL such as databases, data containers and partitioning can be found in the Invantive SQL grammar.

The configuration can be changed using various attributes during log on and use. A full list of configuration options is listed in the driver attributes 2.

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On OpenArch the comparison of two texts is case sensitive by default.

Changes and bug fixes on the OpenArch SQL driver can be found in the release notes. There is currently no specific section on the Invantive forums for OpenArch. Please reach out to other users of OpenArch by leaving a question or contact request.

Driver code for use in settings.xml: `OpenArch`

Alias: `openarch`

Recommended alias: `oah`

Status: Non-production

More technical documentation as provided by the supplier of the OpenArch API on the native APIconnection used can be found at https://www.openarch.nl/api/docs/.

Updated: 29-05-2022 00:58 using Invantive SQL version 22.0.196-PROD+3400.

2 SQL Driver Attributes for OpenArch API

The SQL driver for OpenArch has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the API server of OpenArch or high-volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The OpenArch driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Drivers file: the providers.xml file (obsolete starting release 17.32).
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for OpenArch can be found in the settings*.xml file used for the database. Settings*.xml files are typically located in the `%USERPROFILE%\invantive` folder in most deployment scenarios. The reference manuals contain instructions how to relocate the settings*.xml files. Each data container of a database in the connection string can have a `connectionString` element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: `set NAME VALUE`, or for a distributed database: `set NAME@ALIAS VALUE`. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The OpenArch driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
add-odata-mandatory-filters	Whether to automatically add OData filters deemed necessary by the platform.	OData	False	✓	✓	✓	
analysis-enforce-row-uniqueness	Use for analysis only! Enforce rows to be unique.	Shared	False	✓	✓	✓	
api-url	URL to access the API.	OData		✓		✓	
bulk-delete-page-size-rows	Number of rows to delete per batch when bulk deleting	Shared	10000	✓	✓	✓	
bulk-insert-page-size-bytes	Approximate maximum size in bytes of batch when bulk inserting	Shared	10000000	✓	✓	✓	
bulk-insert-page-size-rows	Number of rows to insert per batch when bulk inserting	Shared	250	✓	✓	✓	
download-error-400-bad-request-max-tries	Maximum number of tries when OData server reports bad format during retrieval of data.		30	✓	✓	✓	
download-error-400-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		10000	✓	✓	✓	
download-error-400-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		300000	✓	✓	✓	
download-error-400-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
download-error-408-request-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 408.		10	✓	✓	✓	
download-error-408-request-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 408.		10000	✓	✓	✓	
download-error-408-request-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 408.		300000	✓	✓	✓	
download-error-408-request-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 408.		2	✓	✓	✓	
download-error-422-bad-request-max-tries	Maximum number of tries when OData server reports unprocessable entity during retrieval of data.		30	✓	✓	✓	
download-error-422-bad-request-	Initial sleep in milliseconds between retries when OData server reports		10000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
sleep-initial-ms	unprocessable entity during retrieval of data.						
download-error-422-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports unprocessable entity during retrieval of data.		300000	✓	✓	✓	
download-error-422-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports unprocessable entity during retrieval of data.		2	✓	✓	✓	
download-error-429-too-many-requests-max-tries	Maximum number of tries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10	✓	✓	✓	
download-error-429-too-many-requests-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10000	✓	✓	✓	
download-error-429-too-many-requests-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		300000	✓	✓	✓	
download-error-429-too-many-requests-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		2	✓	✓	✓	
download-error-502-server-unavailable-max-tries	Maximum number of tries when OData server reports a bad gateway during retrieval of data.		30	✓	✓	✓	
download-error-502-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports a bad gateway during retrieval of data.		10000	✓	✓	✓	
download-error-502-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that a bad gateway during retrieval of data.		300000	✓	✓	✓	
download-error-502-server-unavailable-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports a bad gateway during retrieval of data.		2	✓	✓	✓	
download-error-503-server-unavailable-max-tries	Maximum number of tries when OData server reports that the API server is unavailable during retrieval of data.		30	✓	✓	✓	
download-error-503-server-	Initial sleep in milliseconds between retries when OData server reports		10000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
unavailable-sleep-initial-ms	that the API server is unavailable during retrieval of data.						
download-error-503-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		300000	✓	✓	✓	
download-error-503-server-unavailable-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
download-error-504-gateway-timeout-max-tries	Maximum number of tries when the website reports a gateway timeout.		10	✓	✓	✓	
download-error-504-gateway-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a gateway timeout.		10000	✓	✓	✓	
download-error-504-gateway-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a gateway timeout.		300000	✓	✓	✓	
download-error-504-gateway-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a gateway timeout.		2	✓	✓	✓	
download-error-590-network-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 590.		10	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 590.		10000	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 590.		300000	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 590.		2	✓	✓	✓	
download-error-599-network-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 599.		10	✓	✓	✓	
download-error-599-network-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 599.		10000	✓	✓	✓	
download-error-599-network-	Maximum sleep in milliseconds between retries when the website		300000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
connect-timeout-sleep-max-ms	reports a HTTP status 599.						
download-error-599-network-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 599.		2	✓	✓	✓	
download-error-argument-exception-max-tries	Maximum number of tries when an argument exception is returned when downloading a blob.		10	✓	✓	✓	
download-error-argument-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		10000	✓	✓	✓	
download-error-argument-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		300000	✓	✓	✓	
download-error-argument-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an argument exception is returned when downloading a blob.		2	✓	✓	✓	
download-error-internet-down-max-tries	Maximum number of tries when the Internet connection seems down during retrieval of data.		10	✓	✓	✓	
download-error-internet-down-sleep-initial-ms	Initial sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		10000	✓	✓	✓	
download-error-internet-down-sleep-max-ms	Maximum sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		300000	✓	✓	✓	
download-error-internet-down-sleep-multiplicator	Multiplication factor for sleep between retries when the Internet connection seems down during retrieval of data.		2	✓	✓	✓	
download-error-io-exception-max-tries	Maximum number of tries when a network I/O connection failure occurs during retrieval of data.		10	✓	✓	✓	
download-error-io-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		10000	✓	✓	✓	
download-error-io-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		300000	✓	✓	✓	
download-error-io-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a network I/O connection failure occurs during retrieval of data.		2	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
download-error-json-exception-max-tries	Maximum number of tries when an invalid JSON body is returned.		3	✓	✓	✓	
download-error-json-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an invalid JSON body is returned.		1000	✓	✓	✓	
download-error-json-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an invalid JSON body is returned.		10000	✓	✓	✓	
download-error-json-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an invalid JSON body is returned.		2	✓	✓	✓	
download-error-other-exception-max-tries	Maximum number of tries when an unqualified error occurs during retrieval of data.		3	✓	✓	✓	
download-error-other-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an unqualified error ocurrs during retrieval of data.		10000	✓	✓	✓	
download-error-other-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an unqualified error ocurrs during retrieval of data.		300000	✓	✓	✓	
download-error-other-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an unqualified error ocurrs during retrieval of data.		2	✓	✓	✓	
download-error-socket-exception-max-tries	Maximum number of tries when the network connection is forcible dropped during retrieval of data.		10	✓	✓	✓	
download-error-socket-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when the network connection is forcible dropped during retrieval of data.		10000	✓	✓	✓	
download-error-socket-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when the network connection is forcible dropped during retrieval of data.		300000	✓	✓	✓	
download-error-socket-exception-sleep-multiplicator	Multiplication factor for sleep between retries when the network connection is forcible dropped during retrieval of data.		2	✓	✓	✓	
download-error-web-exception-max-tries	Maximum number of tries when a web connection failure occurs during retrieval of data.		10	✓	✓	✓	
download-error-web-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		10000	✓	✓	✓	
download-error-web-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		300000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
download-error-web-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a web connection failure occurs during retrieval of data.		2	✓	✓	✓	
download-error-web-not-implemented-max-tries	Maximum number of tries when the connection reports not implemented.		1	✓	✓	✓	
download-error-web-not-implemented-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports not implemented.		10000	✓	✓	✓	
download-error-web-not-implemented-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports not implemented.		300000	✓	✓	✓	
download-error-web-not-implemented-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports not implemented.		2	✓	✓	✓	
download-error-web-timeout-max-tries	Maximum number of tries when the connection reports a timeout.		10	✓	✓	✓	
download-error-web-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports a timeout.		10000	✓	✓	✓	
download-error-web-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports a timeout.		300000	✓	✓	✓	
download-error-web-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports a timeout.		2	✓	✓	✓	
download-error-web-unauthorized-max-tries	Maximum number of tries when the connection reports an unauthorized error.		1	✓	✓	✓	
download-error-web-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports an unauthorized error.		10000	✓	✓	✓	
download-error-web-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports an unauthorized error.		300000	✓	✓	✓	
download-error-web-unauthorized-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports an unauthorized error.		2	✓	✓	✓	
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	Shared	False	✓	✓	✓	
forced-casing-identifiers	Forced casing of identifiers. Choose from Unset, Lower, Upper and	Shared		✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
	Mixed.						
http-disk-cache-compression-level	Compression level for the HTTP disk cache, ranging from 1 (little) to 9 (intense). Default is 5.	Shared	5	✓	✓	✓	
http-disk-cache-directory	Directory where HTTP cache is stored.	Shared	C:\Users\gle3.WS212\Invantive\Cache\http\gle3\shared	✓	✓	✓	
http-disk-cache-ignore-write-errors	Whether to ignore write errors to disk cache.	Shared	False	✓	✓	✓	
http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP disk cache.	Shared	2592000	✓	✓	✓	
http-get-timeout-ms	HTTP GET timeout (ms).		300000	✓	✓	✓	
http-memory-cache-compression-level	Compression level for the HTTP memory cache, ranging from 1 (little) to 9 (intense). Default is 5.	OData	5	✓	✓	✓	
http-memory-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP memory cache.	OData	14400	✓	✓	✓	
http-post-timeout-ms	HTTP POST timeout (ms).		300000	✓	✓	✓	
ignore-http-400-errors	Ignore HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-401-errors	Ignore HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-402-errors	Ignore HTTP 402 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-403-errors	Ignore HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-404-errors	Ignore HTTP 404 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-422-errors	Ignore HTTP 422 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-429-errors	Ignore HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-500-errors	Ignore HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-502-errors	Ignore HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
ignore-http-503-errors	Ignore HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
invalid-json-on-get-max-tries	Maximum number of tries when the JSON received on GET is invalid.		10	✓	✓	✓	
invalid-json-on-get-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on GET is invalid.		10000	✓	✓	✓	
invalid-json-on-get-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on GET is invalid.		300000	✓	✓	✓	
invalid-json-on-get-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on GET is invalid.		2	✓	✓	✓	
invalid-json-on-post-max-tries	Maximum number of tries when the JSON received on POST is invalid.		1	✓	✓	✓	
invalid-json-on-post-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on POST is invalid.		10000	✓	✓	✓	
invalid-json-on-post-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on POST is invalid.		300000	✓	✓	✓	
invalid-json-on-post-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on POST is invalid.		2	✓	✓	✓	
invantive-sql-compress-sparse-arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753.	SQL Engine V1	False	✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-shuffle-fetch-results-data-containers	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	✓	✓	✓	
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	✓	✓	✓	
join-set-points-per-request	Maximum number of values in a request when executing a join set.	OData	60	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
limit-partition-calls-left	Minimum number of remaining API calls on a partition towards a hard limit. When below, an error is raised.	OData	500	✓	✓	✓	
log-native-calls-to-disk-max-events	Maximum number of events to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-max-seconds	Maximum number of seconds to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-on-error	Registers native calls to data container backend as disk files when an error occurred.	Shared	False	✓	✓	✓	
log-native-calls-to-disk-on-success	Registers native calls to data container backend as disk files when successful.	Shared	False	✓	✓	✓	
log-native-calls-to-trace	Log native calls to data container backend on the trace.	Shared	False	✓	✓	✓	
maximum-length-identifiers	Non-default maximum length in characters of identifier names.	Shared		✓	✓	✓	
max-odata-filters	The maximum number of OData filter elements.	OData	100	✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	Shared	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	Shared	8000	✓	✓	✓	
metadata-cache-max-age-sec	Maximum acceptable age in seconds for re-use of metadata.	OData		✓	✓	✓	
oauth-unauthorized-max-tries	Maximum number of tries when an OAuth exception occurs.	OData	2	✓	✓	✓	
oauth-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between OAuth reauthentication tries when the OAuth authentication fails.	OData	10000	✓	✓	✓	
oauth-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between OAuth reauthentication tries when the OAuth authentication fails.	OData	1000	✓	✓	✓	
oauth-unauthorized-sleep-multiplicator	Multiplication factor for sleep between OAuth reauthentication tries when the OAuth authentication fails.	OData	2	✓	✓	✓	
partition-slot-based-rate-limit-length-ms	Total length in ms across all slots of a partition-based rate limit.	Shared	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	Shared	0	✓	✓	✓	
requested-page-size	Preferred number of rows to exchange per round trip; only	Shared		✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
	effective on limited platforms such as AFAS Online						
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	Shared	32	✓	✓	✓	
simulate-http-400-errors	Simulate HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-400-errors-percentage	Percentage of simulated HTTP 400 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-401-errors	Simulate HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-401-errors-percentage	Percentage of simulated HTTP 401 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-403-errors	Simulate HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-403-errors-percentage	Percentage of simulated HTTP 403 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-408-errors	Simulate HTTP 408 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-408-errors-percentage	Percentage of simulated HTTP 408 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-429-errors	Simulate HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-429-errors-percentage	Percentage of simulated HTTP 429 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-500-errors	Simulate HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-500-errors-percentage	Percentage of simulated HTTP 500 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-502-errors	Simulate HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-502-errors-percentage	Percentage of simulated HTTP 502 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-503-errors	Simulate HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
simulate-http-503-errors-percentage	Percentage of simulated HTTP 503 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-protocol-errors	Simulate HTTP protocol errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-protocol-errors-percentage	Percentage of simulated HTTP protocol errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-timeout-errors	Simulate HTTP timeout errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-timeout-errors-percentage	Percentage of simulated HTTP timeout errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
slot-based-rate-limit-length-ms	Total length in ms across all slots of a slot-based rate limit.	Shared	60000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	✓	✓	✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	Shared	True	✓	✓	✓	
use-batch-insert	Whether to use batch insert.	OData	True	✓	✓	✓	
use-http-disk-cache-read	Whether to use HTTP responses from previous queries stored on disk to answer the current query.	Shared	False	✓	✓	✓	
use-http-disk-cache-write	Whether to memorize HTTP responses on disk.	Shared	False	✓	✓	✓	
use-http-memory-cache-read	Whether to use HTTP responses from previous queries stored in memory that can answer the current query.	OData	True	✓	✓	✓	
use-http-memory-cache-write	Whether to memorize HTTP responses from previous queries for use by future queries.	OData	True	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

3 Schema: Native

3.1 Tables

3.1.1 NATIVEPLATFORMSCALARREQUESTS

Direct access to native API.

Catalog: OPENARCH

Schema: Native

Alias: `npt`

Documentation:

The NativePlatformScalarRequests table provides direct access to the native API protocol over an established connection to the OpenArch API server. It will contain a new row for every row inserted with a native API request in PAYLOAD_TEXT with the results of unaltered forwarding of the payload to the OpenArch API server.

Retrieve: true

Insert: true

Update: false

Delete: false

View Columns

The columns of the view `NATIVEPLATFORMSCALARREQUESTS` are shown below. Each column has an SQL data type. A new non-null value must be provided for every required column at all times during insert.

Name	Data Type	Label	Required	Documentation
BLOB_PREFERRED	boolean		☑	Indicator w hether a BLOB result is preferred over text.
BOL_RESPONSE_CACHE_MAX_AGE_SEC	int32		☐	Maximum age in seconds of Bridge Online response cache entries to be used.
CONTENT_TYPE	string(240)		☐	
DATE_ENDED	datetime		☑	
DATE_STARTED	datetime		☑	
DRY_RUN	boolean		☑	
DURATION_MS	int32		☑	
ERROR_MESSAGE_CODE	string(30)		☐	
ERROR_MESSAGE_TEXT	string(32000)		☐	
FAIL_ON_ERROR	boolean		☑	Whether to raise an exception w hen processing the native request triggered an error from the provider.
HTTP_DISK_CACHE_MAX_AGE_SEC	int32		☐	Maximum age in seconds of HTTP disk cache entries to be used.
HTTP_DISK_CACHE_SAVE	boolean		☐	Whether results can be stored in HTTP disk cache.

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Name	Data Type	Label	Required	Documentation
HTTP_DISK_CACHE_USE	boolean		☐	Whether results can be fetched from HTTP disk cache.
HTTP_MEMORY_CACHE_MAX_AGE_SEC	int32		☐	Maximum age in seconds of HTTP memory cache entries to be used.
HTTP_MEMORY_CACHE_SAVE	boolean		☐	Whether results can be stored in HTTP memory cache.
HTTP_MEMORY_CACHE_USE	boolean		☐	Whether results can be fetched from HTTP memory cache.
HTTP_METHOD	string(30)		☐	
HTTP_STATUS_CODE	int16		☐	
ORIG_SYSTEM_GROUP	string(4000)		☐	
ORIG_SYSTEM_REFERENCE	string(4000)		☐	
PAYLOAD_TEXT	string		☐	
RESULT_BLOB	byte[]		☐	
RESULT_DATE_TIME_UTC	datetime		☐	
RESULT_NUMBER	decimal		☐	
RESULT_TEXT	string		☐	
SUCCESSFUL	boolean		☑	
TIMEOUT_SEC	int32		☐	Timeout in seconds.
TRANSACTION_ID	int32		☑	Incrementing ID of the transaction.
URL	string(4000)		☐	

4 Schema: OPENARCH

4.1 Tables

4.1.1 openarch_archive_statistics

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL:
`https://api.openarch.nl/1.0/stats/archives.json?`

Insert OpenArch API URL:
`https://api.openarch.nl/1.0/stats/archives.json?`

Update OpenArch API URL:
`https://api.openarch.nl/1.0/stats/archives.json?`

Delete OpenArch API URL:
`https://api.openarch.nl/1.0/stats/archives.json?`

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Field Selection Method: NotRequired

Table Columns

The columns of the table `openarch_archive_statistics` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
archive	string		☐	
count	int64		☐	

4.1.2 openarch_archives

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL:
`https://api.openarch.nl/1.0/stats/records.json?`

Insert OpenArch API URL: `https://api.openarch.nl/1.0/stats/records.json?`

Update OpenArch API URL:
`https://api.openarch.nl/1.0/stats/records.json?`

Delete OpenArch API URL:
`https://api.openarch.nl/1.0/stats/records.json?`

Field Selection Method: NotRequired

Table Columns

The columns of the table `openarch_archives` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
archiefwiki	string		☐	
archive	string		☐	
homepage	string		☐	
name	string		☐	

4.1.3 openarch_archives_by_name

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

This is a read-only table function. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL:
`https://api.openarch.nl/1.0/records/search.json?`

Insert OpenArch API URL:
`https://api.openarch.nl/1.0/records/search.json?`

Update OpenArch API URL:
`https://api.openarch.nl/1.0/records/search.json?`

Delete OpenArch API URL:
`https://api.openarch.nl/1.0/records/search.json?`

Field Selection Method: NotRequired

Base Path: `response.docs.[*]`

Table Function Parameters

The following parameters can be used to control the behaviour of the table function openarch_archives_by_name. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
name	string	☑		

Table Function Columns

The columns of the table function `openarch_archives_by_name` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
archive_code	string		☐	
archive	string		☐	
eventdate_day	string		☐	
eventdate_month	string		☐	
eventdate_year	string		☐	
eventplace	string		☐	
eventtype	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Name	Data Type	Label	Required	Documentation
identifier	string		☐	
personname	string		☐	
relationtype	string		☐	
sourcetype	string		☐	

4.1.4 openarch_comment_statistics

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table function. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL:
`https://api.openarch.nl/1.0/stats/comments.json?`

Insert OpenArch API URL:
`https://api.openarch.nl/1.0/stats/comments.json?`

Update OpenArch API URL:
`https://api.openarch.nl/1.0/stats/comments.json?`

Delete OpenArch API URL:
`https://api.openarch.nl/1.0/stats/comments.json?`

Field Selection Method: NotRequired

Table Function Parameters

The following parameters can be used to control the behaviour of the table function openarch_comment_statistics. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
archive	string	☐		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

The columns of the table function `openarch_comment_statistics` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
archive	string		☐	
count	int64		☐	

4.1.5 openarch_family_names

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL:
`https://api.openarch.nl/1.0/stats/familynames.json?`

Insert OpenArch API URL:
`https://api.openarch.nl/1.0/stats/familynames.json?`

Update OpenArch API URL:
`https://api.openarch.nl/1.0/stats/familynames.json?`

Delete OpenArch API URL:
`https://api.openarch.nl/1.0/stats/familynames.json?`

Field Selection Method: NotRequired

Base Path: `rows.[*].c`

Table Columns

The columns of the table `openarch_family_names` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
count	string		☐	
family_name	string		☐	

4.1.6 openarch_links_statistics

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table function. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL: `https://api.openarch.nl/1.0/stats/links.json?`

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Insert OpenArch API URL: `https://api.openarch.nl/1.0/stats/links.json?`

Update OpenArch API URL: `https://api.openarch.nl/1.0/stats/links.json?`

Delete OpenArch API URL: `https://api.openarch.nl/1.0/stats/links.json?`

Field Selection Method: NotRequired

Table Function Parameters

The following parameters can be used to control the behaviour of the table function openarch_links_statistics. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
archive	string	☐		

Table Function Columns

The columns of the table function `openarch_links_statistics` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
archive	string		☐	
count	int64		☐	

4.1.7 openarch_persons

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table function. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL: `https://api.openarch.nl/1.0/records/show.json?`

Insert OpenArch API URL: `https://api.openarch.nl/1.0/records/show.json?`

Update OpenArch API URL: `https://api.openarch.nl/1.0/records/show.json?`

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Delete OpenArch API URL: `https://api.openarch.nl/1.0/records/show.json?`

Field Selection Method: NotRequired

Base Path: `a2a_Person.[*]`

Table Function Parameters

The following parameters can be used to control the behaviour of the table function openarch_persons. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
archive	string	☑		
identifier	string	☑		

Table Function Columns

The columns of the table function `openarch_persons` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
Event_date_day	string		☐	
Event_date_month	string		☐	
Event_date_year	string		☐	
Event_id	string		☐	
Event_place	string		☐	
Event_type	string		☐	
Person_first_name	string		☐	
person_id	string		☐	
Person_last_name	string		☐	

4.1.8 openarch_persons_per_year

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

This is a read-only table function. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL:
`https://api.openarch.nl/1.0/records/yearsago.json?`

Insert OpenArch API URL:
`https://api.openarch.nl/1.0/records/yearsago.json?`

Update OpenArch API URL:
`https://api.openarch.nl/1.0/records/yearsago.json?`

Delete OpenArch API URL:
`https://api.openarch.nl/1.0/records/yearsago.json?`

Field Selection Method: NotRequired

Table Function Parameters

The following parameters can be used to control the behaviour of the table function openarch_persons_per_year. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
years	string	☑		

Table Function Columns

The columns of the table function `openarch_persons_per_year` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
archive	string		☐	
identifier	string		☐	
name	string		☐	
place	string		☐	
scan	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

4.1.9 openarch_professions

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL:
`https://api.openarch.nl/1.0/stats/professions.json?`

Insert OpenArch API URL:
`https://api.openarch.nl/1.0/stats/professions.json?`

Update OpenArch API URL:
`https://api.openarch.nl/1.0/stats/professions.json?`

Delete OpenArch API URL:
`https://api.openarch.nl/1.0/stats/professions.json?`

Field Selection Method: NotRequired

Base Path: `rows.[*].c`

Table Columns

The columns of the table `openarch_professions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
count	string		☐	
profession	string		☐	

4.1.10 openarch_relations

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table function. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL: `https://api.openarch.nl/1.0/records/show.json?`

Insert OpenArch API URL: `https://api.openarch.nl/1.0/records/show.json?`

Update OpenArch API URL: `https://api.openarch.nl/1.0/records/show.json?`

Delete OpenArch API URL: `https://api.openarch.nl/1.0/records/show.json?`

Field Selection Method: NotRequired

Base Path: `a2a_RelationEP.[*]`

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Table Function Parameters

The following parameters can be used to control the behaviour of the table function openarch_relations. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
archive	string	☑		
identifier	string	☑		

Table Function Columns

The columns of the table function `openarch_relations` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
Person_Event_reference	string		☐	
Person_key_reference	string		☐	
Person_RelationType	string		☐	

4.1.11 openarch_source_types

Catalog: OPENARCH

Schema: OPENARCH

Primary Keys: id

This is a read-only table. The OpenArch API may not support changing the data or the Invantive SQL driver for OpenArch does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the OpenArch API.

Select OpenArch API URL:
`https://api.openarch.nl/1.0/stats/sources.json?`

Insert OpenArch API URL: `https://api.openarch.nl/1.0/stats/sources.json?`

Update OpenArch API URL:
`https://api.openarch.nl/1.0/stats/sources.json?`

Delete OpenArch API URL:
`https://api.openarch.nl/1.0/stats/sources.json?`

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Field Selection Method: NotRequired

Table Columns

The columns of the table `openarch_source_types` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
count	string		☐	
sourcetype	string		☐	
sourcetypeenglish	string		☐	
sourcetypelocal	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Index

- A -

add-odata-mandatory-filters 2
analysis-enforce-row-uniqueness 2
api-url 2
archiefwiki 16
archive 15, 16, 18, 19, 20, 21, 23
archive_code 16

- B -

BLOB_PREFERRED 14
BOL_RESPONSE_CACHE_MAX_AGE_SEC 14
bulk-delete-page-size-rows 2
bulk-insert-page-size-bytes 2
bulk-insert-page-size-rows 2

- C -

CONTENT_TYPE 14
count 15, 18, 19, 23, 24

- D -

DATE_ENDED 14
DATE_STARTED 14
download-error-400-bad-request-max-tries 2
download-error-400-bad-request-sleep-initial-ms 2
download-error-400-bad-request-sleep-max-ms 2
download-error-400-bad-request-sleep-multiplicator 2
download-error-408-request-timeout-max-tries 2
download-error-408-request-timeout-sleep-initial-ms 2
download-error-408-request-timeout-sleep-max-ms 2
download-error-408-request-timeout-sleep-multiplicator 2
download-error-422-bad-request-max-tries 2
download-error-422-bad-request-sleep-initial-ms 2
download-error-422-bad-request-sleep-max-ms 2
download-error-422-bad-request-sleep-multiplicator 2
download-error-429-too-many-requests-max-tries 2
download-error-429-too-many-requests-sleep-initial-ms 2
download-error-429-too-many-requests-sleep-max-ms 2
download-error-429-too-many-requests-sleep-multiplicator 2
download-error-502-server-unavailable-max-tries 2
download-error-502-server-unavailable-sleep-initial-ms 2
download-error-502-server-unavailable-sleep-max-ms 2
download-error-502-server-unavailable-sleep-multiplicator 2
download-error-503-server-unavailable-max-tries 2
download-error-503-server-unavailable-sleep-initial-ms 2
download-error-503-server-unavailable-sleep-max-ms 2
download-error-503-server-unavailable-sleep-multiplicator 2
download-error-504-gateway-timeout-max-tries 2
download-error-504-gateway-timeout-sleep-initial-ms 2
download-error-504-gateway-timeout-sleep-max-ms 2
download-error-504-gateway-timeout-sleep-multiplicator 2
download-error-590-network-connect-timeout-max-tries 2
download-error-590-network-connect-timeout-sleep-initial-ms 2
download-error-590-network-connect-timeout-sleep-max-ms 2
download-error-590-network-connect-timeout-sleep-multiplicator 2
download-error-599-network-connect-timeout-max-tries 2
download-error-599-network-connect-timeout-sleep-initial-ms 2
download-error-599-network-connect-timeout-sleep-max-ms 2
download-error-599-network-connect-timeout-sleep-multiplicator 2
download-error-argument-exception-max-tries 2
download-error-argument-exception-sleep-initial-ms 2
download-error-argument-exception-sleep-max-ms 2
download-error-argument-exception-sleep-multiplicator 2
download-error-internet-down-max-tries 2
download-error-internet-down-sleep-initial-ms 2
download-error-internet-down-sleep-max-ms 2
download-error-internet-down-sleep-multiplicator 2
download-error-io-exception-max-tries 2
download-error-io-exception-sleep-initial-ms 2
download-error-io-exception-sleep-max-ms 2

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

download-error-io-exception-sleep-multiplicator 2
download-error-json-exception-max-tries 2
download-error-json-exception-sleep-initial-ms 2
download-error-json-exception-sleep-max-ms 2
download-error-json-exception-sleep-multiplicator 2
download-error-other-exception-max-tries 2
download-error-other-exception-sleep-initial-ms 2
download-error-other-exception-sleep-max-ms 2
download-error-other-exception-sleep-multiplicator 2
download-error-socket-exception-max-tries 2
download-error-socket-exception-sleep-initial-ms 2
download-error-socket-exception-sleep-max-ms 2
download-error-socket-exception-sleep-multiplicator 2
download-error-web-exception-max-tries 2
download-error-web-exception-sleep-initial-ms 2
download-error-web-exception-sleep-max-ms 2
download-error-web-exception-sleep-multiplicator 2
download-error-web-not-implemented-max-tries 2
download-error-web-not-implemented-sleep-initial-ms 2
download-error-web-not-implemented-sleep-max-ms 2
download-error-web-not-implemented-sleep-multiplicator 2
download-error-web-timeout-max-tries 2
download-error-web-timeout-sleep-initial-ms 2
download-error-web-timeout-sleep-max-ms 2
download-error-web-timeout-sleep-multiplicator 2
download-error-web-unauthorized-max-tries 2
download-error-web-unauthorized-sleep-initial-ms 2
download-error-web-unauthorized-sleep-max-ms 2
download-error-web-unauthorized-sleep-multiplicator 2
Driver 1
DRY_RUN 14
DURATION_MS 14

- E -

ERROR_MESSAGE_CODE 14
ERROR_MESSAGE_TEXT 14
Event_date_day 20
Event_date_month 20
Event_date_year 20
Event_id 20
Event_place 20
Event_type 20
eventdate_day 16
eventdate_month 16
eventdate_year 16
eventplace 16
eventtype 16

- F -

FAIL_ON_ERROR 14
family_name 19
force-case-sensitive-identifiers 2
forced-casing-identifiers 2

- H -

homepage 16
HTTP_DISK_CACHE_MAX_AGE_SEC 14
HTTP_DISK_CACHE_SAVE 14
HTTP_DISK_CACHE_USE 14
HTTP_MEMORY_CACHE_MAX_AGE_SEC 14
HTTP_MEMORY_CACHE_SAVE 14
HTTP_MEMORY_CACHE_USE 14
HTTP_METHOD 14
HTTP_STATUS_CODE 14
http-disk-cache-compression-level 2
http-disk-cache-directory 2
http-disk-cache-ignore-write-errors 2
http-disk-cache-max-age-sec 2
http-get-timeout-ms 2
http-memory-cache-compression-level 2
http-memory-cache-max-age-sec 2
http-post-timeout-ms 2

- I -

identifier 16, 20, 21, 23
ignore-http-400-errors 2
ignore-http-401-errors 2
ignore-http-402-errors 2
ignore-http-403-errors 2
ignore-http-404-errors 2
ignore-http-422-errors 2
ignore-http-429-errors 2
ignore-http-500-errors 2
ignore-http-502-errors 2
ignore-http-503-errors 2
invalid-json-on-get-max-tries 2
invalid-json-on-get-sleep-initial-ms 2
invalid-json-on-get-sleep-max-ms 2
invalid-json-on-get-sleep-multiplicator 2
invalid-json-on-post-max-tries 2
invalid-json-on-post-sleep-initial-ms 2
invalid-json-on-post-sleep-max-ms 2

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

invalid-json-on-post-sleep-multiplicator 2
invantive-sql-compress-sparse-arrays 2
invantive-sql-correct-invalid-date 2
invantive-sql-forward-filters-to-data-containers 2
invantive-sql-share-byte-arrays 2
invantive-sql-share-strings 2
invantive-sql-shuffle-fetch-results-data-containers 2
invantive-use-cache 2

- J -

join-set-points-per-request 2

- L -

limit-partition-calls-left 2
log-native-calls-to-disk-max-events 2
log-native-calls-to-disk-max-seconds 2
log-native-calls-to-disk-on-error 2
log-native-calls-to-disk-on-success 2
log-native-calls-to-trace 2

- M -

maximum-length-identifiers 2
max-odata-filters 2
max-url-length-accepted 2
max-url-length-desired 2
metadata-cache-max-age-sec 2

- N -

name 16, 21
NATIVEPLATFORMSCALARREQUESTS 14
npt 14

- O -

oauth-unauthorized-max-tries 2
oauth-unauthorized-sleep-initial-ms 2
oauth-unauthorized-sleep-max-ms 2
oauth-unauthorized-sleep-multiplicator 2
OpenArch 1, 14, 15, 16, 18, 19, 20, 21, 23, 24
openarch_archive_statistics 15
openarch_archives 16
openarch_archives_by_name 16
openarch_comment_statistics 18
openarch_family_names 19
openarch_links_statistics 19
openarch_persons 20
openarch_persons_per_year 21
openarch_professions 23
openarch_relations 23
openarch_source_types 24
ORIG_SYSTEM_GROUP 14
ORIG_SYSTEM_REFERENCE 14

- P -

partition-slot-based-rate-limit-length-ms 2
partition-slot-based-rate-limit-slots 2
PAYLOAD_TEXT 14
Person_Event_reference 23
Person_first_name 20
person_id 20
Person_key_reference 23
Person_last_name 20
Person_RelationType 23
personname 16
place 21
pre-request-delay-ms 2
profession 23

- R -

relationtype 16
requested-page-size 2
requests-parallel-max 2
RESULT_BLOB 14
RESULT_DATE_TIME_UTC 14
RESULT_NUMBER 14
RESULT_TEXT 14

- S -

scan 21
simulate-http-400-errors 2
simulate-http-400-errors-percentage 2
simulate-http-401-errors 2
simulate-http-401-errors-percentage 2
simulate-http-403-errors 2
simulate-http-403-errors-percentage 2
simulate-http-408-errors 2
simulate-http-408-errors-percentage 2
simulate-http-429-errors 2
simulate-http-429-errors-percentage 2
simulate-http-500-errors 2
simulate-http-500-errors-percentage 2
simulate-http-502-errors 2

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

simulate-http-502-errors-percentage 2
simulate-http-503-errors 2
simulate-http-503-errors-percentage 2
simulate-http-protocol-errors 2
simulate-http-protocol-errors-percentage 2
simulate-http-timeout-errors 2
simulate-http-timeout-errors-percentage 2
slot-based-rate-limit-length-ms 2
slot-based-rate-limit-slots 2
sourcetype 16, 24
sourcetypeenglish 24
sourcetypelocal 24
standardize-identifiers 2
standardize-identifiers-casing 2
SUCCESSFUL 14

- T -

TIMEOUT_SEC 14
TRANSACTION_ID 14

- U -

URL 14
use-batch-insert 2
use-http-disk-cache-read 2
use-http-disk-cache-write 2
use-http-memory-cache-read 2
use-http-memory-cache-write 2

- Y -

years 21

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.



Invantive B.V.
Biesteweg 11
3849 RD Hierden
Nederland

Tel: +31 88 00 26 500
Fax: +31 84 22 58 178
info@invantive.nl
invantive.nl

IBAN NL25 BUNQ 2098 2586 07
Kamer van Koophandel 13031406
BTW NL812602377B01
RSIN 8122602377
Algemeen Directeur: Guido Leenders
Statutaire zetel: Roermond

(C) Copyright 2004-2025 Invantive Software B.V., Nederland. Alle rechten voorbehouden.
24.0.92
29/06/2026, 21:37
ISBN 978-94-6302-000-8: