

YouTrack API Data Model

for use with Invantive SQL

24.0

invantive
the SQL company

Copyright

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

Important Safety and Usage Information

Intended Use and Limitations: This software, developed by Invantive, is designed to support a variety of business and information technology data processing functions, such as accounting, financial reporting an sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- Nuclear facilities: The software should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.
- Defense and Military Applications: This software is not suitable for use in defense-related applications, including but not limited to weaponry control, military strategy planning, or any other aspects of national defense.
- Aviation: The software is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.
- Healthcare and Medicine Production: This software should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.
- Chemical and Hazardous Material Handling: This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.
- Transportation and Traffic Control Systems: The software should not be used for the control, operation, or management of transportation systems, including railway signal controls, subway systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.
- Energy Grid and Utility Control Systems: This software is not designed for the control or operation of energy grid systems, including electrical substations, renewable energy control systems, or water utility control systems. The failure of software in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.
- Other High-Risk Environments: Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

User Responsibility: Users must ensure that they understand the intended use of the software and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the software for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment.
Disclaimer of Liability: Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this software in prohibited or unintended applications.

Contents

1 SQL Driver for YouTrack API 1

2 SQL Driver Attributes for YouTrack API 2

3 Schema: Activities 15

3.1 Tables 15
3.1.1 Activities: YouTrack Activities 15
3.1.2 ActivityById 17
3.1.3 ActivityPages 18
3.1.4 ProjectActivityPages 20

4 Schema: Admin 22

4.1 Tables 22
4.1.1 AllowedOriginRestSettings 22
4.1.2 AppearanceSettings 23
4.1.3 GlobalSettings 24
4.1.4 IssueAttachments 26
4.1.5 IssueComments 30
4.1.6 IssueCustomFields 34
4.1.7 IssueLinks 38
4.1.8 Issues 41
4.1.9 IssueTags: YouTrack Issue Tags 45
4.1.10 Licenses 49
4.1.11 LocaleSettings 50
4.1.12 NotificationSettings 50
4.1.13 RestSettings 51
4.1.14 SystemSettings 52
4.1.15 Telemetry 53
4.1.16 TimeTrackingSettings 54
4.1.17 TimeTrackingSettingWorkItemTypes 55
4.1.18 TimeTrackingSettingWorkItemTypesByWorkItemTypeId 55
4.1.19 TimeTrackingWorkTimeSettings 56
4.1.20 WorkItemTypeTimeTrackingSettings 57

5 Schema: Agile 58

5.1 Tables 58
5.1.1 ProjectBySprintId 58
5.1.2 ProjectIssues 65
5.1.3 ProjectIssuesBySprintId 72
5.1.4 Projects 79
5.1.5 SprintById 85
5.1.6 SprintById1 91
5.1.7 SprintById2 97
5.1.8 SprintIssueAttachmentsBySprintId 101
5.1.9 SprintIssueCommentsBySprintId 108
5.1.10 SprintIssueCustomFieldsBySprintId 114
5.1.11 SprintIssueLinksBySprintId 120
5.1.12 SprintIssues 126
5.1.13 SprintIssuesBySprintId 133
5.1.14 SprintIssuesBySprintId1 140
5.1.15 SprintIssueTagsBySprintId 146

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

5.1.16 Sprints ... 152
5.1.17 Sprints1 ... 157

6 Schema: Articles 163

6.1 Tables ... 163
6.1.1 ArticleById ... 163
6.1.2 Articles: YouTrack Articles ... 168
6.1.3 AttachmentById ... 172
6.1.4 Attachments ... 179
6.1.5 ChildArticleAttachments ... 185
6.1.6 ChildArticleAttachmentsById ... 192
6.1.7 ChildArticleComments ... 200
6.1.8 ChildArticleCommentsById ... 206
6.1.9 ChildArticles ... 213
6.1.10 ChildArticlesById ... 219
6.1.11 ChildChildArticles ... 226
6.1.12 ChildChildArticlesById ... 232
6.1.13 CommentAttachments ... 239
6.1.14 CommentAttachmentsByIssueId ... 245
6.1.15 Comments ... 251
6.1.16 CommentsByIssueId ... 256
6.1.17 GroupById ... 262
6.1.18 Groups ... 264
6.1.19 IssueLinkTypes ... 266
6.1.20 IssueLinkTypesById ... 266
6.1.21 IssueTagAttachmentIssuesByTagId ... 268
6.1.22 IssueTagById ... 273
6.1.23 IssueTagById2 ... 275
6.1.24 IssueTagCommentAttachmentIssuesByTagId ... 280
6.1.25 IssueTagCommentIssuesByTagId ... 285
6.1.26 IssueTagCustomFieldIssuesByTagId ... 290
6.1.27 IssueTagIssueAttachments ... 295
6.1.28 IssueTagIssueAttachmentsById ... 299
6.1.29 IssueTagIssueById ... 304
6.1.30 IssueTagIssueComments ... 308
6.1.31 IssueTagIssueCommentsById ... 312
6.1.32 IssueTagIssueCustomFields ... 316
6.1.33 IssueTagIssueLinks ... 320
6.1.34 IssueTagIssueLinksById ... 324
6.1.35 IssueTagIssues ... 328
6.1.36 IssueTagIssuesCustomFieldsById ... 332
6.1.37 IssueTagIssuesTags ... 336
6.1.38 IssueTagIssueTagsById ... 340
6.1.39 IssueTagLinkIssuesByTagId ... 345
6.1.40 IssueTagLinkIssuesByTagId1 ... 349
6.1.41 IssueTagLinkTrimmedIssuesByTagId ... 355
6.1.42 IssueTags: YouTrack Issue Tags ... 361
6.1.43 TagIssuesByTagId ... 363
6.1.44 TagIssuesByTagId2 ... 368

7 Schema: Backups 374

7.1 Tables ... 374
7.1.1 DatabaseBackupById ... 374
7.1.2 DatabaseBackups ... 375
7.1.3 DatabaseBackupSettingBackupStatuses ... 376
7.1.4 DatabaseBackupSettings ... 377
7.1.5 NotifiedUserSavedQuerySettings ... 378
7.1.6 NotifiedUserSettings ... 379

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

7.1.7 NotifiedUserTagSettings ... 380

8 Schema: CustomFields 382

8.1 Tables ... 382

8.1.1 CustomFieldAggregatedUserSavedQueriesByUserBundleId ... 382
8.1.2 CustomFieldAggregatedUsersByUserBundleId ... 383
8.1.3 CustomFieldAggregatedUserTagsByUserBundleId ... 384
8.1.4 CustomFieldBuildBundles ... 386
8.1.5 CustomFieldBuildByBuildBundleId ... 386
8.1.6 CustomFieldBuildByBuildBundleIdAndElementId ... 387
8.1.7 CustomFieldBuildValues ... 389
8.1.8 CustomFieldBuildValuesByBuildBundleId ... 390
8.1.9 CustomFieldBuildValuesByBuildBundleId1 ... 392
8.1.10 CustomFieldEnumBundleByEnumFieldBundleId ... 393
8.1.11 CustomFieldEnumBundles ... 394
8.1.12 CustomFieldEnumBundleValuesByEnumFieldBundleId ... 395
8.1.13 CustomFieldEnumByEnumFieldBundleId ... 396
8.1.14 CustomFieldEnumByEnumFieldBundleIdAndElementId ... 398
8.1.15 CustomFieldEnumValues ... 399
8.1.16 CustomFieldIndividualUsers ... 400
8.1.17 CustomFieldIndividualUserSavedQueries ... 401
8.1.18 CustomFieldIndividualUserSavedQueriesByUserBundleId ... 402
8.1.19 CustomFieldIndividualUsersByUserBundleId ... 404
8.1.20 CustomFieldIndividualUserTags ... 405
8.1.21 CustomFieldIndividualUserTagsByUserBundleId ... 406
8.1.22 CustomFieldInstancesByCustomFieldPrototypeId ... 408
8.1.23 CustomFieldOw nedFieldByOw nedFieldBundleId ... 410
8.1.24 CustomFieldOw nedFieldByOw nedFieldBundleIdAndElementId ... 411
8.1.25 CustomFieldOw nedFieldByValueId ... 413
8.1.26 CustomFieldOw nedFields ... 414
8.1.27 CustomFieldOw nedFieldValues ... 415
8.1.28 CustomFieldOw nedFieldValuesByOw nedFieldBundleId ... 416
8.1.29 CustomFields ... 418
8.1.30 CustomFieldsByCustomFieldPrototypeId ... 420
8.1.31 CustomFieldsByCustomFieldPrototypeId2 ... 421
8.1.32 CustomFieldsByCustomFieldPrototypeId3 ... 423
8.1.33 CustomFieldStateBundleById ... 426
8.1.34 CustomFieldStateBundles ... 427
8.1.35 CustomFieldStateBundleValues2ByStateBundleId ... 427
8.1.36 CustomFieldStateBundleValuesByStateBundleId ... 429
8.1.37 CustomFieldStateByStateBundleIdAndElementId ... 430
8.1.38 CustomFieldStateValues ... 432
8.1.39 CustomFieldUserBundles ... 433
8.1.40 CustomFieldUserBundleUsers ... 434
8.1.41 CustomFieldUserBundleUserSavedQueries ... 435
8.1.42 CustomFieldUserBundleUserTags ... 436
8.1.43 CustomFieldUserByUserBundleId ... 437
8.1.44 CustomFieldUserByUserBundleId1 ... 438
8.1.45 CustomFieldUserByUserBundleId2 ... 441
8.1.46 CustomFieldUserGroupsByUserBundleId ... 444
8.1.47 CustomFieldUserGroupsByUserBundleId1 ... 445
8.1.48 CustomFieldUsers ... 448
8.1.49 CustomFieldUsersByUserBundleId ... 448
8.1.50 CustomFieldUsersByUserBundleId1 ... 451
8.1.51 CustomFieldUsersByUserBundleId2 ... 454
8.1.52 CustomFieldUsersByUserBundleId3 ... 457
8.1.53 CustomFieldUsersByUserBundleId4 ... 459
8.1.54 CustomFieldUsersByUserBundleId5 ... 461

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

8.1.55 CustomFieldUsersByUserBundleId6 ... 464
8.1.56 CustomFieldUsersByUserBundleId7 ... 466
8.1.57 CustomFieldUsersByUserBundleId8 ... 470
8.1.58 CustomFieldUsersByUserBundleId9 ... 472
8.1.59 CustomFieldUsersByUserBundleIdAndGroupId ... 474
8.1.60 CustomFieldUsersByUserId ... 477
8.1.61 CustomFieldUserTagsByUserBundleId ... 479
8.1.62 CustomFieldUserTagsByUserBundleId2 ... 482
8.1.63 CustomFieldVersionByProjectVersionBundleId ... 485
8.1.64 CustomFieldVersions ... 486
8.1.65 CustomFieldVersionValues ... 486
8.1.66 CustomFieldVersionValuesByProjectVersionBundleId ... 488
8.1.67 CustomFieldVersionValuesByProjectVersionBundleId2 ... 489
8.1.68 CustomFieldVersionValuesByProjectVersionBundleId3 ... 491
8.1.69 InstanceCustomFields ... 492
8.1.70 Types ... 494

9 Schema: Issues 495

9.1 Tables ... 495
9.1.1 AttachmentById ... 495
9.1.2 Attachments ... 500
9.1.3 CommentAttachments ... 506
9.1.4 CommentAttachmentsByIssueId ... 512
9.1.5 Comments ... 517
9.1.6 CommentsByIssueId ... 523
9.1.7 CustomFields ... 528
9.1.8 CustomFieldsByIssueId ... 533
9.1.9 IssueById ... 537
9.1.10 IssueLinksByIssueId ... 541
9.1.11 Issues ... 543
9.1.12 IssueTags: YouTrack Issue Tags ... 547
9.1.13 LinkById ... 554
9.1.14 LinkIssues ... 558
9.1.15 LinkIssuesByIssueId ... 565
9.1.16 Links ... 571
9.1.17 LinkTrimmedIssues ... 576
9.1.18 LinkTrimmedIssuesByIssueId ... 581
9.1.19 TagById ... 587
9.1.20 TagIssuesByTagId ... 592
9.1.21 Tags ... 599

10 Schema: Native 604

10.1 Tables ... 604
10.1.1 NATIVEPLATFORMSCALARREQUESTS: YouTrack Native Platform Scalar Requests ... 604

11 Schema: SavedQueries 606

11.1 Tables ... 606
11.1.1 IssueAttachmentsBySavedQueryId ... 606
11.1.2 IssueById ... 610
11.1.3 IssueCommentsBySavedQueryId ... 614
11.1.4 IssueCustomFieldsBySavedQueryId ... 618
11.1.5 Issues ... 623
11.1.6 IssuesAttachments ... 626
11.1.7 IssuesComments ... 630
11.1.8 IssuesCustomFields ... 634
11.1.9 IssuesLinks ... 638
11.1.10 IssuesLinksById ... 642
11.1.11 IssuesTags ... 646

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

11.1.12 IssueTagsBySavedQueryId ... 650
11.1.13 SavedQueries: YouTrack Saved Queries ... 654
11.1.14 SavedQueryById ... 656

12 Schema: Users 658

12.1 Tables ... 658
12.1.1 IssueTags: YouTrack Issue Tags ... 658
12.1.2 Me ... 661
12.1.3 MyIssueTags ... 662
12.1.4 MySavedQueries ... 665
12.1.5 MySavedQueriessues ... 667
12.1.6 MyTags ... 670
12.1.7 ProfileTimeTrackingsByUserId ... 672
12.1.8 SavedQueries: YouTrack Saved Queries ... 673
12.1.9 SavedQueryById ... 675
12.1.10 SavedQueryIssues ... 678
12.1.11 SavedQueryIssuesByUserId ... 680
12.1.12 TagById ... 683
12.1.13 TagIssuesByTagId ... 686
12.1.14 Tags ... 689
12.1.15 UserById ... 691
12.1.16 UserGeneralProfilesBySprintId ... 693
12.1.17 UserIssueAttachmentSavedQueriesByUserId ... 694
12.1.18 UserIssueAttachmentTagsByUserId ... 699
12.1.19 UserIssueCommentSavedQueriesByUserId ... 703
12.1.20 UserIssueCommentTagsByUserId ... 707
12.1.21 UserIssueCustomFieldSavedQueriesByUserId ... 712
12.1.22 UserIssueCustomFieldTagsByUserId ... 716
12.1.23 UserIssueLinkSavedQueriesByUserId ... 720
12.1.24 UserIssueLinkSavedQueryTagsByUserId ... 724
12.1.25 UserIssueSavedQueriesByUserId ... 729
12.1.26 UserIssueTagSavedQueriesByUserId ... 733
12.1.27 UserIssueTagsByUserId ... 737
12.1.28 UserIssueTagsByUserId1 ... 741
12.1.29 UserNotificationProfilesBySprintId ... 746
12.1.30 Users: YouTrack Users ... 747
12.1.31 UserSavedQueriesByUserId ... 748
12.1.32 UserTagsByUserId ... 751
12.1.33 WorkItemById ... 753
12.1.34 WorkItems: YouTrack Work Items ... 757

13 Schema: Views 761

13.1 Views ... 761
13.1.1 IDTypes ... 761

Index 763

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

1 SQL Driver for YouTrack API

Invantive SQL is the fastest, easiest and most reliable way to exchange data with the YouTrack API.

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the user community. Other users or Invantive Support will try to help you to our best.

YouTrack by JetBrains provides bug tracking, issue tracking system and project management.

The YouTrack driver covers 233 tables and 21272 columns.

YouTrack API Clients

Invantive SQL is available on many user interfaces ("clients" in traditional server-client paradigma). All Invantive SQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

The YouTrack Power BI connector is based on the Invantive SQL driver for YouTrack, completed by a high-performance OData connector which works straight on Power BI without any add-on. The OData protocol is always version 4, independent whether the backing platform uses OData, SOAP or another protocol.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL. High-volume replication of data taken from the YouTrack API into traditional databases such as SQL Server (on-premise and Azure), MySQL, PostgreSQL and Oracle is possible using Invantive Data Replicator. Invantive Data Replicator automatically creates and maintains YouTrack datawarehouses, possibly in combination with data from over 70 other (cloud) platforms. Data Replicator supports data volumes up to over 1 TB and over 5.000 companies. The on-premise edition of Invantive Bridge offers an YouTrack ADO.net provider.

Finally, online web apps can be build for YouTrack using App Online of Invantive Cloud.

Monitor API Calls

When a query or DML-statement has been executed on Invantive SQL a developer can evaluate the actual calls made to the YouTrack API using a query on sessionios@DataDictionary. As an alternative, extensive request and response logging can be enabled by setting log-native-calls-to-disk to true. In the %USERPROFILE% \Invantive\NativeLog folder Invantive SQL will create log files per API request and response.

Specifications

The SQL driver for YouTrack does not support partitioning. Define one data container in a database for each company in YouTrack to enable parallel access for data from multiple companies.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

An introduction into the concepts of Invantive SQL such as databases, data containers and partitioning can be found in the Invantive SQL grammar.

The configuration can be changed using various attributes during log on and use. A full list of configuration options is listed in the driver attributes 2.

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On YouTrack the comparison of two texts is case sensitive by default.

Changes and bug fixes on the YouTrack SQL driver can be found in the release notes. Get access to the YouTrack community through the YouTrack section of the Invantive forums.

Driver code for use in settings.xml: `YouTrack`

Alias: `youtrack`

Recommended alias: `ytk`

More technical documentation as provided by the supplier of the YouTrack API on the native APIconnection used can be found at https://www.jetbrains.com/help/youtrack/devportal.

The format of YouTrack record IDs consists of a value from the view IDTypes, a dash as separator and a numeric value.

Updated: 23-06-2022 19:43 using Invantive SQL version 22.0.248-PROD+3461.

2 SQL Driver Attributes for YouTrack API

The SQL driver for YouTrack has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the API server of YouTrack or high-volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The YouTrack driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Drivers file: the providers.xml file (obsolete starting release 17.32).
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for YouTrack can be found in the settings*.xml file used for the database. Settings*.xml files are typically located in the `%USERPROFILE%\invantive` folder in most deployment scenarios. The reference manuals contain instructions how to relocate the settings*.xml files. Each data container of a database in the connection string can have a `connectionString` element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: `set NAME VALUE`, or for a distributed database: `set NAME@ALIAS VALUE`. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The YouTrack driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
add-odata-mandatory-filters	Whether to automatically add OData filters deemed necessary by the platform.	OData	False	✓	✓	✓	
analysis-enforce-row-uniqueness	Use for analysis only! Enforce rows to be unique.	Shared	False	✓	✓	✓	
api-access-token	Access Token is a security token for multiple OAuth2 Flows. With an Access Token you can access protected resources. An Access Token must be stored securely since once compromised allows access to your protected resources.	OData		✓		✓	✓
api-client-id	The client ID is a unique identifier of your application. It is generated by registering an application.	OData		✓		✓	✓
api-client-secret	The client secret is to be kept confidential. Such as a password for a logon code, the client secret is the confidential part of an app identified by a client ID. It is needed during the OAuth2 Code Grant Flow together with the refresh token to get access.	OData		✓		✓	✓
api-pre-expiry-refresh-sec	The number of seconds before the token expires to acquire a new token.	OData		✓	✓	✓	
api-redirect-url	The redirect URI is the website a browser session is redirected to after the OAuth2 authentication process has been completed.	OData		✓		✓	✓
api-refresh-token	Refresh Token is a security token for the OAuth2 Code Grant Flow. With a Refresh Token and client secret you can retrieve a renewed access token to access protected resources. A Refresh Token and client secret must be stored securely since once compromised allows access to your protected resources.	OData		✓		✓	✓
api-scope	The scope to request an OAuth token for.	OData		✓		✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
api-token-url	The token URI is the OAuth2 endpoint to exchange tokens.	OData		✓		✓	
api-url	URL to access the API.	OData		✓		✓	
bulk-delete-page-size-rows	Number of rows to delete per batch when bulk deleting	Shared	10000	✓	✓	✓	
bulk-insert-page-size-bytes	Approximate maximum size in bytes of batch when bulk inserting	Shared	10000000	✓	✓	✓	
bulk-insert-page-size-rows	Number of rows to insert per batch when bulk inserting	Shared	250	✓	✓	✓	
download-error-400-bad-request-max-tries	Maximum number of tries when OData server reports bad format during retrieval of data.		3	✓	✓	✓	
download-error-400-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		500	✓	✓	✓	
download-error-400-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		5000	✓	✓	✓	
download-error-400-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
download-error-408-request-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 408.		10	✓	✓	✓	
download-error-408-request-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 408.		10000	✓	✓	✓	
download-error-408-request-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 408.		300000	✓	✓	✓	
download-error-408-request-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 408.		2	✓	✓	✓	
download-error-422-bad-request-max-tries	Maximum number of tries when OData server reports unprocessable entity during retrieval of data.		30	✓	✓	✓	
download-error-422-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports unprocessable entity during retrieval of data.		10000	✓	✓	✓	
download-error-422-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports unprocessable entity during retrieval of data.		300000	✓	✓	✓	
download-error-422-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server		2	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
	reports unprocessable entity during retrieval of data.						
download-error-429-too-many-requests-max-tries	Maximum number of tries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10	✓	✓	✓	
download-error-429-too-many-requests-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10000	✓	✓	✓	
download-error-429-too-many-requests-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		300000	✓	✓	✓	
download-error-429-too-many-requests-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		2	✓	✓	✓	
download-error-502-server-unavailable-max-tries	Maximum number of tries when OData server reports a bad gateway during retrieval of data.		30	✓	✓	✓	
download-error-502-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports a bad gateway during retrieval of data.		10000	✓	✓	✓	
download-error-502-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that a bad gateway during retrieval of data.		300000	✓	✓	✓	
download-error-502-server-unavailable-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports a bad gateway during retrieval of data.		2	✓	✓	✓	
download-error-503-server-unavailable-max-tries	Maximum number of tries when OData server reports that the API server is unavailable during retrieval of data.		30	✓	✓	✓	
download-error-503-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		10000	✓	✓	✓	
download-error-503-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		300000	✓	✓	✓	
download-error-503-server-	Multiplication factor for sleep between retries OData server		2	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
unavailable-sleep-multiplicator	reports that the API server is unavailable during retrieval of data.						
download-error-504-gateway-timeout-max-tries	Maximum number of tries when the website reports a gateway timeout.		10	✓	✓	✓	
download-error-504-gateway-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a gateway timeout.		10000	✓	✓	✓	
download-error-504-gateway-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a gateway timeout.		300000	✓	✓	✓	
download-error-504-gateway-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a gateway timeout.		2	✓	✓	✓	
download-error-590-network-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 590.		10	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 590.		10000	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 590.		300000	✓	✓	✓	
download-error-590-network-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 590.		2	✓	✓	✓	
download-error-599-network-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 599.		10	✓	✓	✓	
download-error-599-network-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 599.		10000	✓	✓	✓	
download-error-599-network-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 599.		300000	✓	✓	✓	
download-error-599-network-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 599.		2	✓	✓	✓	
download-error-argument-exception-	Maximum number of tries when an argument exception is returned		10	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
max-tries	when downloading a blob.						
download-error-argument-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		10000	✓	✓	✓	
download-error-argument-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		300000	✓	✓	✓	
download-error-argument-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an argument exception is returned when downloading a blob.		2	✓	✓	✓	
download-error-internet-down-max-tries	Maximum number of tries when the Internet connection seems down during retrieval of data.		10	✓	✓	✓	
download-error-internet-down-sleep-initial-ms	Initial sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		10000	✓	✓	✓	
download-error-internet-down-sleep-max-ms	Maximum sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		300000	✓	✓	✓	
download-error-internet-down-sleep-multiplicator	Multiplication factor for sleep between retries when the Internet connection seems down during retrieval of data.		2	✓	✓	✓	
download-error-io-exception-max-tries	Maximum number of tries when a network I/O connection failure occurs during retrieval of data.		10	✓	✓	✓	
download-error-io-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		10000	✓	✓	✓	
download-error-io-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		300000	✓	✓	✓	
download-error-io-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a network I/O connection failure occurs during retrieval of data.		2	✓	✓	✓	
download-error-json-exception-max-tries	Maximum number of tries when an invalid JSON body is returned.		3	✓	✓	✓	
download-error-json-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an invalid JSON body is returned.		1000	✓	✓	✓	
download-error-json-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an invalid JSON body is returned.		10000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
download-error-json-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an invalid JSON body is returned.		2	✓	✓	✓	
download-error-other-exception-max-tries	Maximum number of tries when an unqualified error occurs during retrieval of data.		3	✓	✓	✓	
download-error-other-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an unqualified error ocurrs during retrieval of data.		10000	✓	✓	✓	
download-error-other-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an unqualified error ocurrs during retrieval of data.		300000	✓	✓	✓	
download-error-other-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an unqualified error ocurrs during retrieval of data.		2	✓	✓	✓	
download-error-socket-exception-max-tries	Maximum number of tries when the network connection is forcible dropped during retrieval of data.		10	✓	✓	✓	
download-error-socket-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when the network connection is forcible dropped during retrieval of data.		10000	✓	✓	✓	
download-error-socket-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when the network connection is forcible dropped during retrieval of data.		300000	✓	✓	✓	
download-error-socket-exception-sleep-multiplicator	Multiplication factor for sleep between retries when the network connection is forcible dropped during retrieval of data.		2	✓	✓	✓	
download-error-web-exception-max-tries	Maximum number of tries when a web connection failure occurs during retrieval of data.		10	✓	✓	✓	
download-error-web-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		10000	✓	✓	✓	
download-error-web-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		300000	✓	✓	✓	
download-error-web-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a web connection failure occurs during retrieval of data.		2	✓	✓	✓	
download-error-web-not-implemented-max-tries	Maximum number of tries when the connection reports not implemented.		1	✓	✓	✓	
download-error-web-not-	Initial sleep in milliseconds between retries when the connection reports		10000	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
implemented-sleep-initial-ms	not implemented.						
download-error-web-not-implemented-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports not implemented.		300000	✓	✓	✓	
download-error-web-not-implemented-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports not implemented.		2	✓	✓	✓	
download-error-web-timeout-max-tries	Maximum number of tries when the connection reports a timeout.		10	✓	✓	✓	
download-error-web-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports a timeout.		1000	✓	✓	✓	
download-error-web-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports a timeout.		30000	✓	✓	✓	
download-error-web-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports a timeout.		2	✓	✓	✓	
download-error-web-unauthorized-max-tries	Maximum number of tries when the connection reports an unauthorized error.		1	✓	✓	✓	
download-error-web-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports an unauthorized error.		10000	✓	✓	✓	
download-error-web-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports an unauthorized error.		300000	✓	✓	✓	
download-error-web-unauthorized-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports an unauthorized error.		2	✓	✓	✓	
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	Shared	False	✓	✓	✓	
forced-casing-identifiers	Forced casing of identifiers. Choose from Unset, Lower, Upper and Mixed.	Shared		✓	✓	✓	
http-disk-cache-compression-level	Compression level for the HTTP disk cache, ranging from 1 (little) to 9 (intense). Default is 5.	Shared	5	✓	✓	✓	
http-disk-cache-directory	Directory where HTTP cache is stored.	Shared	C:\Users\gle3.WS212\Invantive\Cache\http\gle3\shared	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
http-disk-cache-ignore-write-errors	Whether to ignore write errors to disk cache.	Shared	False	✓	✓	✓	
http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP disk cache.	Shared	2592000	✓	✓	✓	
http-get-timeout-max-ms	HTTP GET maximum timeout on retry (ms).		300000	✓	✓	✓	
http-get-timeout-ms	HTTP GET timeout (ms).		60000	✓	✓	✓	
http-memory-cache-compression-level	Compression level for the HTTP memory cache, ranging from 1 (little) to 9 (intense). Default is 5.	OData	5	✓	✓	✓	
http-memory-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP memory cache.	OData	14400	✓	✓	✓	
http-post-timeout-max-ms	HTTP POST maximum timeout on retry (ms).		300000	✓	✓	✓	
http-post-timeout-ms	HTTP POST timeout (ms).		300000	✓	✓	✓	
ignore-http-400-errors	Ignore HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-401-errors	Ignore HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-402-errors	Ignore HTTP 402 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-403-errors	Ignore HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-404-errors	Ignore HTTP 404 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-422-errors	Ignore HTTP 422 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-429-errors	Ignore HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-500-errors	Ignore HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-502-errors	Ignore HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-503-errors	Ignore HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
ignore-unknown-path-type	Whether to ignore path types not yet supported. An error will be generated when an unsupported type occurs.		True	✓	✓	✓	✓
ignore-values-unknown-path	Whether to ignore values outside of processed paths. An error will be generated when a value occurs outside a path otherwise.		True	✓	✓	✓	✓
invalid-json-on-get-max-tries	Maximum number of tries when the JSON received on GET is invalid.		10	✓	✓	✓	
invalid-json-on-get-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on GET is invalid.		10000	✓	✓	✓	
invalid-json-on-get-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on GET is invalid.		300000	✓	✓	✓	
invalid-json-on-get-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on GET is invalid.		2	✓	✓	✓	
invalid-json-on-post-max-tries	Maximum number of tries when the JSON received on POST is invalid.		1	✓	✓	✓	
invalid-json-on-post-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on POST is invalid.		10000	✓	✓	✓	
invalid-json-on-post-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on POST is invalid.		300000	✓	✓	✓	
invalid-json-on-post-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on POST is invalid.		2	✓	✓	✓	
invantive-sql-compress-sparse-arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753.	SQL Engine V1	False	✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-shuffle-fetch-	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
results-data-containers							
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	✓	✓	✓	
join-set-points-per-request	Maximum number of values in a request when executing a join set.	OData	60	✓	✓	✓	
limit-partition-calls-left	Minimum number of remaining API calls on a partition towards a hard limit. When below, an error is raised.	OData	500	✓	✓	✓	
log-native-calls-to-disk-max-events	Maximum number of events to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-max-seconds	Maximum number of seconds to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-on-error	Registers native calls to data container backend as disk files when an error occurred.	Shared	False	✓	✓	✓	
log-native-calls-to-disk-on-success	Registers native calls to data container backend as disk files when successful.	Shared	False	✓	✓	✓	
log-native-calls-to-trace	Log native calls to data container backend on the trace.	Shared	False	✓	✓	✓	
maximum-discovered-column-count	Maximum number of discovered columns. An error will be generated when the column exceeds this value.		250	✓	✓	✓	✓
maximum-length-identifiers	Non-default maximum length in characters of identifier names.	Shared		✓	✓	✓	
max-odata-filters	The maximum number of OData filter elements.	OData	100	✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	Shared	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	Shared	8000	✓	✓	✓	
metadata-cache-max-age-sec	Maximum acceptable age in seconds for re-use of metadata.	OData		✓	✓	✓	
oauth-unauthorized-max-tries	Maximum number of tries when an OAuth exception occurs.	OData	2	✓	✓	✓	
oauth-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between OAuth reauthentication tries when the OAuth authentication fails.	OData	10000	✓	✓	✓	
oauth-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between OAuth reauthentication tries when the OAuth authentication fails.	OData	1000	✓	✓	✓	
oauth-unauthorized-sleep-multiplicator	Multiplication factor for sleep between OAuth reauthentication tries when the OAuth authentication fails.	OData	2	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
partition-slot-based-rate-limit-length-ms	Total length in ms across all slots of a partition-based rate limit.	Shared	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	Shared	0	✓	✓	✓	
requested-page-size	Preferred number of rows to exchange per round trip; only effective on limited platforms such as AFAS Online	Shared		✓	✓	✓	
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	Shared	32	✓	✓	✓	
service-url	{res:itgen_cloud_database_youtrack_service_url_tip}	YouTrack		✓		✓	✓
simulate-http-400-errors	Simulate HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-400-errors-percentage	Percentage of simulated HTTP 400 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-401-errors	Simulate HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-401-errors-percentage	Percentage of simulated HTTP 401 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-403-errors	Simulate HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-403-errors-percentage	Percentage of simulated HTTP 403 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-408-errors	Simulate HTTP 408 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-408-errors-percentage	Percentage of simulated HTTP 408 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-429-errors	Simulate HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-429-errors-percentage	Percentage of simulated HTTP 429 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-500-errors	Simulate HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
simulate-http-500-errors-percentage	Percentage of simulated HTTP 500 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-502-errors	Simulate HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-502-errors-percentage	Percentage of simulated HTTP 502 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-503-errors	Simulate HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-503-errors-percentage	Percentage of simulated HTTP 503 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-protocol-errors	Simulate HTTP protocol errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-protocol-errors-percentage	Percentage of simulated HTTP protocol errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-timeout-errors	Simulate HTTP timeout errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-timeout-errors-percentage	Percentage of simulated HTTP timeout errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
slot-based-rate-limit-length-ms	Total length in ms across all slots of a slot-based rate limit.	Shared	60000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	✓	✓	✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	Shared	True	✓	✓	✓	
swagger-specification-file	The Swagger file path, such as C:\temp\swagger.json.			✓	✓	✓	✓
swagger-specification-http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of Swagger specification data in the HTTP disk cache.		86400	✓	✓	✓	
swagger-specification-url	The Swagger URL such as https://example.org/rest/swagger.json.			✓	✓	✓	✓

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
use-batch-insert	Whether to use batch insert.	OData	True	✓	✓	✓	
use-http-disk-cache-read	Whether to use HTTP responses from previous queries stored on disk to answer the current query.	Shared	False	✓	✓	✓	
use-http-disk-cache-write	Whether to memorize HTTP responses on disk.	Shared	False	✓	✓	✓	
use-http-memory-cache-read	Whether to use HTTP responses from previous queries stored in memory that can answer the current query.	OData	True	✓	✓	✓	
use-http-memory-cache-write	Whether to memorize HTTP responses from previous queries for use by future queries.	OData	True	✓	✓	✓	

3 Schema: Activities

3.1 Tables

3.1.1 Activities: YouTrack Activities

Catalog: YouTrack

Schema: Activities

Label: Activities

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/activities`

Insert YouTrack API URL: `/activities`

Update YouTrack API URL: `/activities`

Delete YouTrack API URL: `/activities`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /activities`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function Activities. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
author	string	☐		Parameter to filter activities by the author. The database id or login, or Hub id,or 'me' for the current logged in user could be specified.
categories	string	☐		
end	string	☐		End timestamp of the time interval the activity timestamp belongs to.If the parameter is not set, it is considered as Long.MAX_VALUE.
issueQuery	string	☐		Issues search query. Read more about search syntax.
reverse	boolean	☐		Indicates w hether the order of returning activities is from new est to oldest or the opposite.If "false", then the oldest activity item that matches a selected filter is returned first.If "true", then the new est activity is returned first. By default, "false".
start	string	☐		Start timestamp of the time interval the activity timestamp belongs to.If the parameter is not set, it is considered to be 0.

Table Function Columns

The columns of the table function `Activities` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_login	string		☐	
author_online	boolean		☐	
author_profiles_$type	string		☐	
author_profiles_id	string		☐	
author_ringId	string		☐	
category_$type	string		☐	
category_id	string		☐	
field_$type	string		☐	
field_id	string		☐	
field_name	string		☐	
field_presentation	string		☐	
id	string	ID	☐	
targetMember	string	Target member	☐	
timestamp	int64	Timestamp	☐	

3.1.2 ActivityById

Catalog: YouTrack

Schema: Activities

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/activities/{id}`

Insert YouTrack API URL: `/activities/{id}`

Update YouTrack API URL: `/activities/{id}`

Delete YouTrack API URL: `/activities/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /activities/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ActivityById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `ActivityById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_profiles_$type	string		☐	
author_profiles_id	string		☐	
author_ringId	string		☐	
category_$type	string		☐	
category_id	string		☐	
field_$type	string		☐	
field_id	string		☐	
field_name	string		☐	
field_presentation	string		☐	
id	string	ID	☐	
targetMember	string	Target member	☐	
timestamp	int64	Timestamp	☐	

3.1.3 ActivityPages

Catalog: YouTrack

Schema: Activities

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API URL: `/activitiesPage`

Insert YouTrack API URL: `/activitiesPage`

Update YouTrack API URL: `/activitiesPage`

Delete YouTrack API URL: `/activitiesPage`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /activitiesPage`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ActivityPages. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
activityId	string	☐		ID of the activity that should be included in the page. The activity is allocated to the middle of the page.
author	string	☐		Parameter to filter activities by the author. The database id or login, or Hub id,or 'me' for the current logged in user could be specified.
categories	string	☐		
cursor	string	☐		
end	string	☐		End timestamp of the time interval the activity timestamp belongs to.If the parameter is not set, it is considered as Long.MAX_VALUE.
issueQuery	string	☐		Issues search query. Read more about search syntax.
reverse	boolean	☐		Indicates w hether the order of returning activities is from new est to oldest or the opposite.If "false", then the oldest activity item that matches a selected filter is returned first.If

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
				"true", then the new est activity is returned first. By default, "false".
start	string	☐		Start timestamp of the time interval the activity timestamp belongs to.If the parameter is not set, it is considered to be 0.

Table Function Columns

The columns of the table function `ActivityPages` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
afterCursor	string	After Cursor	☐	
beforeCursor	string	Before Cursor	☐	
hasAfter	boolean	Has After	☐	
hasBefore	boolean	Has Before	☐	
id	string	ID	☐	
reverse	boolean	Reverse	☐	

3.1.4 ProjectActivityPages

Catalog: YouTrack

Schema: Activities

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/activitiesPage`

Insert YouTrack API URL: `/activitiesPage`

Update YouTrack API URL: `/activitiesPage`

Delete YouTrack API URL: `/activitiesPage`

Field Selection Method: NotRequired

Base Path: `activities[*]`

Select YouTrack API Operation: `get /activitiesPage`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectActivityPages. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
activityId	string	☐		ID of the activity that should be included in the page. The activity is allocated to the middle of the page.
author	string	☐		Parameter to filter activities by the author. The database id or login, or Hub id,or 'me' for the current logged in user could be specified.
categories	string	☐		
cursor	string	☐		
end	string	☐		End timestamp of the time interval the activity timestamp belongs to.If the parameter is not set, it is considered as Long.MAX_VALUE.
issueQuery	string	☐		Issues search query. Read more about search syntax.
reverse	boolean	☐		Indicates w hether the order of returning activities is from new est to oldest or the opposite.If "false", then the oldest activity item that matches a selected filter is returned first.If "true", then the new est activity is returned first. By default, "false".
start	string	☐		Start timestamp of the time interval the activity timestamp belongs to.If the parameter is not set, it is considered to be 0.

Table Function Columns

The columns of the table function `ProjectActivityPages` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
afterCursor	string	After Cursor	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
beforeCursor	string	Before Cursor	☐	
category_$type	string		☐	
category_id	string		☐	
field_$type	string		☐	
field_id	string		☐	
field_name	string		☐	
field_presentation	string		☐	
hasAfter	boolean	Has After	☐	
hasBefore	boolean	Has Before	☐	
id_1	string		☐	
id	string	ID	☐	
reverse	boolean	Reverse	☐	
targetMember	string	Target member	☐	
timestamp	int64	Timestamp	☐	

4 Schema: Admin

4.1 Tables

4.1.1 AllowedOriginRestSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/restSettings`

Insert YouTrack API URL: `/admin/globalSettings/restSettings`

Update YouTrack API URL: `/admin/globalSettings/restSettings`

Delete YouTrack API URL: `/admin/globalSettings/restSettings`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Base Path: `allowedOrigins[*]`

Select YouTrack API Operation: `get /admin/globalSettings/restSettings`

Table Function Columns

The columns of the table function `AllowedOriginRestSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
allow AllOrigins	boolean	Allow All Origins	☐	
id	string	ID	☐	
TEXT	string	Text	☐	

4.1.2 AppearanceSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/appearanceSettings`

Insert YouTrack API URL: `/admin/globalSettings/appearanceSettings`

Update YouTrack API URL: `/admin/globalSettings/appearanceSettings`

Delete YouTrack API URL: `/admin/globalSettings/appearanceSettings`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/globalSettings/appearanceSettings`

Table Function Columns

The columns of the table function `AppearanceSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
dateFieldFormat_$type	string		☐	
dateFieldFormat_datePattern	string		☐	
dateFieldFormat_id	string		☐	
dateFieldFormat_pattern	string		☐	
dateFieldFormat_presentation	string		☐	
id	string	ID	☐	
logo_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
logo_id	string		☐	
logo_url	string		☐	
timeZone_$type	string		☐	
timeZone_id	string		☐	
timeZone_offset	int32		☐	
timeZone_presentation	string		☐	

4.1.3 GlobalSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings`

Insert YouTrack API URL: `/admin/globalSettings`

Update YouTrack API URL: `/admin/globalSettings`

Delete YouTrack API URL: `/admin/globalSettings`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/globalSettings`

Table Function Columns

The columns of the table function `GlobalSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
appearanceSettings_$type	string		☐	
appearanceSettings_dateFieldFormat_$type	string		☐	
appearanceSettings_dateFieldFormat_datePattern	string		☐	
appearanceSettings_dateFieldFormat_id	string		☐	
appearanceSettings_dateFieldFormat_pattern	string		☐	
appearanceSettings_dateFieldFormat_presentation	string		☐	
appearanceSettings_id	string		☐	
appearanceSettings_logo_$type	string		☐	
appearanceSettings_logo_id	string		☐	
appearanceSettings_logo_url	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
appearanceSettings_timeZone_$type	string		☐	
appearanceSettings_timeZone_id	string		☐	
appearanceSettings_timeZone_offset	int32		☐	
appearanceSettings_timeZone_presentation	string		☐	
id	string	ID	☐	
license_$type	string		☐	
license_error	string		☐	
license_id	string		☐	
license_license	string		☐	
license_username	string		☐	
localeSettings_$type	string		☐	
localeSettings_id	string		☐	
localeSettings_isRTL	boolean		☐	
localeSettings_locale_$type	string		☐	
localeSettings_locale_community	boolean		☐	
localeSettings_locale_id	string		☐	
localeSettings_locale_language	string		☐	
localeSettings_locale_locale	string		☐	
localeSettings_locale_name	string		☐	
notificationSettings_$type	string		☐	
notificationSettings_emailSettings_$type	string		☐	
notificationSettings_emailSettings_anonymous	boolean		☐	
notificationSettings_emailSettings_from	string		☐	
notificationSettings_emailSettings_host	string		☐	
notificationSettings_emailSettings_id	string		☐	
notificationSettings_emailSettings_isEnabled	boolean		☐	
notificationSettings_emailSettings_login	string		☐	
notificationSettings_emailSettings_mailProtocol	string		☐	
notificationSettings_emailSettings_port	int32		☐	
notificationSettings_emailSettings_replyTo	string		☐	
notificationSettings_id	string		☐	
notificationSettings_jabberSettings_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
notificationSettings_jabberSettings_host	string		☐	
notificationSettings_jabberSettings_id	string		☐	
notificationSettings_jabberSettings_isEnabled	boolean		☐	
notificationSettings_jabberSettings_login	string		☐	
notificationSettings_jabberSettings_port	int32		☐	
notificationSettings_jabberSettings_serviceName	string		☐	
restSettings_$type	string		☐	
restSettings_allowAllOrigins	boolean		☐	
restSettings_id	string		☐	
systemSettings_$type	string		☐	
systemSettings_administratorEmail	string		☐	
systemSettings_allowStatisticsCollection	boolean		☐	
systemSettings_baseUrl	string		☐	
systemSettings_id	string		☐	
systemSettings_isApplicationReadOnly	boolean		☐	
systemSettings_maxExportItems	int32		☐	
systemSettings_maxUploadFileSize	int64		☐	

4.1.4 IssueAttachments

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `IssueAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
description_1	string		☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOw ner_$type	string		☐	
draftOw ner_avatarUrl	string		☐	
draftOw ner_banned	boolean		☐	
draftOw ner_email	string		☐	
draftOw ner_fullName	string		☐	
draftOw ner_guest	boolean		☐	
draftOw ner_id	string		☐	
draftOw ner_jabberAccountName	string		☐	
draftOw ner_login	string		☐	
draftOw ner_online	boolean		☐	
draftOw ner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
replyToEmail	string	Reply-to Email	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
size	int64	Size	☐	
startingNumber	int64	Starting Number	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.5 IssueComments

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `IssueComments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
deleted	boolean	Deleted	☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.6 IssueCustomFields

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: NotRequired

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `IssueCustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
created	int64	Created	☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.7 IssueLinks

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `IssueLinks` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.8 Issues

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `Issues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
description_1	string		☐	
description	string	Description	☐	
draftOw ner_$type	string		☐	
draftOw ner_avatarUrl	string		☐	
draftOw ner_banned	boolean		☐	
draftOw ner_email	string		☐	
draftOw ner_fullName	string		☐	
draftOw ner_guest	boolean		☐	
draftOw ner_id	string		☐	
draftOw ner_jabberAccountName	string		☐	
draftOw ner_login	string		☐	
draftOw ner_online	boolean		☐	
draftOw ner_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_profiles_$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.9 IssueTags: YouTrack Issue Tags

Catalog: YouTrack

Schema: Admin

Label: Issue Tags

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/projects`

Insert YouTrack API URL: `/admin/projects`

Update YouTrack API URL: `/admin/projects`

Delete YouTrack API URL: `/admin/projects`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /admin/projects`

Table Function Columns

The columns of the table function `IssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
createdBy_$type_1	string		☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id_1	string		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_name	string		☐	
createdBy_online	boolean		☐	
createdBy_profiles_$type	string		☐	
createdBy_profiles_id	string		☐	
createdBy_ringId	string		☐	
createdBy_untagOnResolve	boolean		☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
fromEmail	string	From Email	☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_$type_1	string		☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id_1	string		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_name	string		☐	
leader_online	boolean		☐	
leader_profiles_$type	string		☐	
leader_profiles_id	string		☐	
leader_ringId	string		☐	
leader_untagOnResolve	boolean		☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
replyToEmail	string	Reply-to Email	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
startingNumber	int64	Starting Number	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_teamForProject_archived	boolean		☐	
team_teamForProject_description	string		☐	
team_teamForProject_fromEmail	string		☐	
team_teamForProject_iconUrl	string		☐	
team_teamForProject_replyToEmail	string		☐	
team_teamForProject_shortName	string		☐	
team_teamForProject_startingNumber	int64		☐	
team_teamForProject_template	boolean		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
untagOnResolve	boolean		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

4.1.10 Licenses

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/license`

Insert YouTrack API URL: `/admin/globalSettings/license`

Update YouTrack API URL: `/admin/globalSettings/license`

Delete YouTrack API URL: `/admin/globalSettings/license`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/globalSettings/license`

Table Function Columns

The columns of the table function `Licenses` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
error	string	Error	☐	
id	string	ID	☐	
license	string	License	☐	
username	string	User Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

4.1.11 LocaleSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/localeSettings`

Insert YouTrack API URL: `/admin/globalSettings/localeSettings`

Update YouTrack API URL: `/admin/globalSettings/localeSettings`

Delete YouTrack API URL: `/admin/globalSettings/localeSettings`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/globalSettings/localeSettings`

Table Function Columns

The columns of the table function `LocaleSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isRTL	boolean	Is RTL	☐	
locale_$type	string		☐	
locale_community	boolean		☐	
locale_id	string		☐	
locale_language	string		☐	
locale_locale	string		☐	
locale_name	string		☐	

4.1.12 NotificationSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/notificationSettings`

Insert YouTrack API URL: `/admin/globalSettings/notificationSettings`

Update YouTrack API URL: `/admin/globalSettings/notificationSettings`

Delete YouTrack API URL: `/admin/globalSettings/notificationSettings`

Field Selection Method: NotRequired

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation:
`get /admin/globalSettings/notificationSettings`

Table Function Columns

The columns of the table function `NotificationSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
emailSettings_$type	string		☐	
emailSettings_anonymous	boolean		☐	
emailSettings_from	string		☐	
emailSettings_host	string		☐	
emailSettings_id	string		☐	
emailSettings_isEnabled	boolean		☐	
emailSettings_login	string		☐	
emailSettings_mailProtocol	string		☐	
emailSettings_port	int32		☐	
emailSettings_replyTo	string		☐	
emailSettings_sslKey_$type	string		☐	
emailSettings_sslKey_id	string		☐	
emailSettings_sslKey_name	string		☐	
id	string	ID	☐	
jabberSettings_$type	string		☐	
jabberSettings_host	string		☐	
jabberSettings_id	string		☐	
jabberSettings_isEnabled	boolean		☐	
jabberSettings_login	string		☐	
jabberSettings_port	int32		☐	
jabberSettings_serviceName	string		☐	

4.1.13 RestSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/restSettings`

Insert YouTrack API URL: `/admin/globalSettings/restSettings`

Update YouTrack API URL: `/admin/globalSettings/restSettings`

Delete YouTrack API URL: `/admin/globalSettings/restSettings`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/globalSettings/restSettings`

Table Function Columns

The columns of the table function `RestSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
allow AllOrigins	boolean	Allow All Origins	☐	
id	string	ID	☐	

4.1.14 SystemSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/globalSettings/systemSettings`

Insert YouTrack API URL: `/admin/globalSettings/systemSettings`

Update YouTrack API URL: `/admin/globalSettings/systemSettings`

Delete YouTrack API URL: `/admin/globalSettings/systemSettings`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/globalSettings/systemSettings`

Table Function Columns

The columns of the table function `SystemSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
administratorEmail	string	Administrator Email	☐	
allow StatisticsCollection	boolean	Allow Statistics Collection	☐	
baseUrl	string	Base URL	☐	
id	string	ID	☐	
isApplicationReadOnly	boolean	Is Application Read-only	☐	
maxExportItems	int32	Max Export Items	☐	
maxUploadFileSize	int64	Max Upload File Size	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

4.1.15 Telemetry

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/telemetry`

Insert YouTrack API URL: `/admin/telemetry`

Update YouTrack API URL: `/admin/telemetry`

Delete YouTrack API URL: `/admin/telemetry`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/telemetry`

Table Function Columns

The columns of the table function `Telemetry` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
allocatedMemory	string	Allocated Memory	☐	
availableMemory	string	Available Memory	☐	
availableProcessors	int32	Available Processors	☐	
blobStringsCacheHitRate	string	Blob String Cache Hit Rate	☐	
cachedResultsCountInDBQueriesCache	int32	Cached Results Count in DB Queries Cache	☐	
databaseBackgroundThreads	int32	Database Background Threads	☐	
databaseLocation	string	Database Location	☐	
databaseQueriesCacheHitRate	string	Database Queries Cache Hit Rate	☐	
databaseSize	string	Database Size	☐	
fullDatabaseSize	string	Full Database Size	☐	
id	string	ID	☐	
installationFolder	string	Installation Folder	☐	
logsLocation	string	Logs Location	☐	
notificationAnalyzerThreads	int32	Notification Analyzer Threads	☐	
onlineUsers_$type	string		☐	
onlineUsers_id	string		☐	
onlineUsers_users	int32		☐	
pendingAsyncJobs	int32	Pending Async Jobs	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reportCalculatorThreads	int32	Report Calculator Threads	☐	
requestsPerSecond	string	Requests per Second	☐	
startedTime	int64	Start Time	☐	
textIndexSize	string	Text Index Size	☐	
totalTransactions	int64	Total Transactions	☐	
transactionsPerSecond	string	Transactions per Second	☐	
uptime	string	Uptime	☐	
usedMemory	string	Used Memory	☐	

4.1.16 TimeTrackingSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings`

Insert YouTrack API URL: `/admin/timeTrackingSettings`

Update YouTrack API URL: `/admin/timeTrackingSettings`

Delete YouTrack API URL: `/admin/timeTrackingSettings`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/timeTrackingSettings`

Table Function Columns

The columns of the table function `TimeTrackingSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
workTimeSettings_$type	string		☐	
workTimeSettings_daysAWeek	int32		☐	
workTimeSettings_firstDayOfWeek	int32		☐	
workTimeSettings_id	string		☐	
workTimeSettings_minutesADay	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

4.1.17 TimeTrackingSettingWorkItemTypes

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes`

Insert YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes`

Update YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes`

Delete YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/timeTrackingSettings/workItemTypes`

Table Function Columns

The columns of the table function `TimeTrackingSettingWorkItemTypes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
autoAttached	boolean	Auto-attached	☐	
id	string	ID	☐	
name	string	Name	☐	

4.1.18 TimeTrackingSettingWorkItemTypesByWorkItemTypeId

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes/{workItemTypeId}`

Insert YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes/{workItemTypeId}`

Update YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes/{workItemTypeId}`

Delete YouTrack API URL: `/admin/timeTrackingSettings/workItemTypes/{workItemTypeId}`

Field Selection Method: NotRequired

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation:
`get /admin/timeTrackingSettings/workItemTypes/{workItemTypeId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TimeTrackingSettingWorkItemTypesByWorkItemTypeId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
workItemTypeId	string	☑		

Table Function Columns

The columns of the table function `TimeTrackingSettingWorkItemTypesByWorkItemTypeId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
autoAttached	boolean	Auto-attached	☐	
id	string	ID	☐	
name	string	Name	☐	

4.1.19 TimeTrackingWorkTimeSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings/workTimeSettings`

Insert YouTrack API URL: `/admin/timeTrackingSettings/workTimeSettings`

Update YouTrack API URL: `/admin/timeTrackingSettings/workTimeSettings`

Delete YouTrack API URL: `/admin/timeTrackingSettings/workTimeSettings`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/timeTrackingSettings/workTimeSettings`

Table Function Columns

The columns of the table function `TimeTrackingWorkTimeSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
daysAWeek	int32	Days a Week	☐	
firstDayOfWeek	int32	First Day of Week	☐	
id	string	ID	☐	
minutesADay	int32	Minutes a Day	☐	

4.1.20 WorkItemTypeTimeTrackingSettings

Catalog: YouTrack

Schema: Admin

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/timeTrackingSettings`

Insert YouTrack API URL: `/admin/timeTrackingSettings`

Update YouTrack API URL: `/admin/timeTrackingSettings`

Delete YouTrack API URL: `/admin/timeTrackingSettings`

Field Selection Method: NotRequired

Base Path: `workItemTypes[*]`

Select YouTrack API Operation: `get /admin/timeTrackingSettings`

Table Function Columns

The columns of the table function `WorkItemTypeTimeTrackingSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
autoAttached	boolean	Auto-attached	☐	
id_1	string		☐	
id	string	ID	☐	
name	string	Name	☐	
w orkTimeSettings_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
workTimeSettings_daysAWeek	int32		☐	
workTimeSettings_firstDayOfWeek	int32		☐	
workTimeSettings_id	string		☐	
workTimeSettings_minutesADay	int32		☐	

5 Schema: Agile

5.1 Tables

5.1.1 ProjectBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Base Path: `projects[*]`

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `ProjectBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_ringId	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
description	string	Description	☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
fromEmail	string	From Email	☐	
hideOrphansSwimlane	boolean		☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id	string	ID	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
replyToEmail	string	Reply-to Email	☐	
shortName	string	Short Name	☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
startingNumber	int64	Starting Number	☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

5.1.2 ProjectIssues

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: NotRequired

Base Path: `projects[*].issues[*]`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `ProjectIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
commentsCount	int32	Comments Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
created	int64	Created	☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_ringId	string		☐	
currentSprint_$type_1	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansSw imlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtThe Top	boolean		☐	
currentSprint_agile_updateableByP rojectBased	boolean		☐	
currentSprint_agile_visibleForProje ctBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_commentsCount	int32		☐	
currentSprint_created	int64		☐	
currentSprint_description	string		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id_1	string		☐	
currentSprint_id	string		☐	
currentSprint_idReadable	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_isDraft	boolean		☐	
currentSprint_name	string		☐	
currentSprint_numberInProject	int64		☐	
currentSprint_previousSprint_$typ e	string		☐	
currentSprint_previousSprint_archi ved	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_resolved	int64		☐	
currentSprint_start	int64		☐	
currentSprint_summary	string		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
currentSprint_updated	int64		☐	
currentSprint_usesMarkdown	boolean		☐	
currentSprint_votes	int32		☐	
currentSprint_wikifiedDescription	string		☐	
description_1	string		☐	
description	string	Description	☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
fromEmail	string	From Email	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
hideOrphansSwimlane	boolean		☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
replyToEmail	string	Reply-to Email	☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
startingNumber	int64	Starting Number	☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
summary	string	Summary	☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

5.1.3 ProjectIssuesBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Base Path: `projects[*].issues[*]`

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProjectIssuesBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `ProjectIssuesBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
archived	boolean	Archived	☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_ringId	string		☐	
currentSprint_$type_1	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_commentsCount	int32		☐	
currentSprint_created	int64		☐	
currentSprint_description	string		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id_1	string		☐	
currentSprint_id	string		☐	
currentSprint_idReadable	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_isDraft	boolean		☐	
currentSprint_name	string		☐	
currentSprint_numberInProject	int64		☐	
currentSprint_previousSprint_$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_resolved	int64		☐	
currentSprint_start	int64		☐	
currentSprint_summary	string		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
currentSprint_updated	int64		☐	
currentSprint_usesMarkdown	boolean		☐	
currentSprint_votes	int32		☐	
currentSprint_wikifiedDescription	string		☐	
description_1	string		☐	
description	string	Description	☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
fromEmail	string	From Email	☐	
hideOrphansSwimlane	boolean		☐	
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
originalEstimationField_fieldDefaults_$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
replyToEmail	string	Reply-to Email	☐	
resolved	int64	Resolved	☐	
shortName	string	Short Name	☐	
sprintsSettings_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
startingNumber	int64	Starting Number	☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
summary	string	Summary	☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.4 Projects

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: NotRequired

Base Path: `projects[*]`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `Projects` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
createdBy_$type	string		☐	
createdBy_avatarUrl	string		☐	
createdBy_banned	boolean		☐	
createdBy_email	string		☐	
createdBy_fullName	string		☐	
createdBy_guest	boolean		☐	
createdBy_id	string		☐	
createdBy_jabberAccountName	string		☐	
createdBy_login	string		☐	
createdBy_online	boolean		☐	
createdBy_ringId	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
description	string	Description	☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
fromEmail	string	From Email	☐	
hideOrphansSwimlane	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
iconUrl	string	Icon (URL)	☐	
id_1	string		☐	
id	string	ID	☐	
leader_$type	string		☐	
leader_avatarUrl	string		☐	
leader_banned	boolean		☐	
leader_email	string		☐	
leader_fullName	string		☐	
leader_guest	boolean		☐	
leader_id	string		☐	
leader_jabberAccountName	string		☐	
leader_login	string		☐	
leader_online	boolean		☐	
leader_ringId	string		☐	
name_1	string		☐	
name	string	Name	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
replyToEmail	string	Reply-to Email	☐	
shortName	string	Short Name	☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
startingNumber	int64	Starting Number	☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
team_$type	string		☐	
team_allUsersGroup	boolean		☐	
team_icon	string		☐	
team_id	string		☐	
team_name	string		☐	
team_ringId	string		☐	
team_usersCount	int64		☐	
template	boolean	Template	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.5 SprintById

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SprintById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
currentSprint_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansSw imlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtThe Top	boolean		☐	
currentSprint_agile_updateableByP rojectBased	boolean		☐	
currentSprint_agile_visibleForProje ctBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_$typ e	string		☐	
currentSprint_previousSprint_archi ved	boolean		☐	
currentSprint_previousSprint_finis h	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDef ault	boolean		☐	
currentSprint_previousSprint_nam e	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unre solvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCo unt	int32		☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	
estimationField_fieldDefaults_canB eEmpty	boolean		☐	
estimationField_fieldDefaults_empt yFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPubl ic	boolean		☐	
estimationField_fieldType_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssue List	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
hideOrphansSw imlane	boolean		☐	
id	string	ID	☐	
name	string	Name	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults _$type	string		☐	
originalEstimationField_fieldDefaults _canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults _emptyFieldText	string		☐	
originalEstimationField_fieldDefaults _id	string		☐	
originalEstimationField_fieldDefaults _isPublic	boolean		☐	
originalEstimationField_fieldType_$t ype	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunning Job	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttac hed	boolean		☐	
originalEstimationField_isDisplayedI nIssueList	boolean		☐	
originalEstimationField_isUpdateabl e	boolean		☐	
originalEstimationField_localizedNa me	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.6 SprintById1

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Base Path: `sprints[*]`

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintById1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SprintById1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_hideOrphansSw imlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_orphansAtTheTop	boolean		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJ ob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttach ed	boolean		☐	
columnSettings_field_isDisplayedInI ssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedNam e	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansS w imlane	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssue List	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
hideOrphansSw imlane	boolean		☐	
id_1	string		☐	
id	string	ID	☐	
isDefault	boolean	Is Default	☐	
name_1	string		☐	
name	string	Name	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults _$type	string		☐	
originalEstimationField_fieldDefaults _canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults _emptyFieldText	string		☐	
originalEstimationField_fieldDefaults _id	string		☐	
originalEstimationField_fieldDefaults _isPublic	boolean		☐	
originalEstimationField_fieldType_$t ype	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunning Job	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttac hed	boolean		☐	
originalEstimationField_isDisplayedI nIssueList	boolean		☐	
originalEstimationField_isUpdateabl e	boolean		☐	
originalEstimationField_localizedNa me	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
previousSprint_$type	string		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
start	int64	Start	☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.7 SprintById2

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintById2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SprintById2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
agile_$type	string		☐	
agile_colorCoding_$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id	string	ID	☐	
isDefault	boolean	Is Default	☐	
name	string	Name	☐	
previousSprint_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
previousSprint_agile_$type	string		☐	
previousSprint_agile_hideOrphansSwimlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
start	int64	Start	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	

5.1.8 SprintIssueAttachmentsBySprintId

Catalog: YouTrack

Schema: Agile

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintIssueAttachmentsBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SprintIssueAttachmentsBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_colorCoding_$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_$type	string		☐	
agile_columnSettings_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_currentSprint_$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_id	string		☐	
previousSprint_$type	string		☐	
previousSprint_agile_$type	string		☐	
previousSprint_agile_hideOrphansSw imlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
start	int64	Start	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.9 SprintIssueCommentsBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintIssueCommentsBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `SprintIssueCommentsBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_colorCoding_$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_$type	string		☐	
agile_originalEstimationField_aliases	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_$type	string		☐	
previousSprint_agile_$type	string		☐	
previousSprint_agile_hideOrphansSw imlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.10 SprintIssueCustomFieldsBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintIssueCustomFieldsBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SprintIssueCustomFieldsBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_colorCoding_$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSw imlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_$type	string		☐	
agile_originalEstimationField_aliase s	string		☐	
agile_originalEstimationField_hasRu nningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAuto Attached	boolean		☐	
agile_originalEstimationField_isDispl ayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpd ateable	boolean		☐	
agile_originalEstimationField_localiz edName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_ow ner_$type	string		☐	
agile_ow ner_avatarUrl	string		☐	
agile_ow ner_banned	boolean		☐	
agile_ow ner_email	string		☐	
agile_ow ner_fullName	string		☐	
agile_ow ner_guest	boolean		☐	
agile_ow ner_id	string		☐	
agile_ow ner_jabberAccountName	string		☐	
agile_ow ner_login	string		☐	
agile_ow ner_online	boolean		☐	
agile_ow ner_ringId	string		☐	
agile_sprintsSettings_$type	string		☐	
agile_sprintsSettings_cardOnSeve ralSprints	boolean		☐	
agile_sprintsSettings_disableSprint s	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtask sOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_sw imlaneSettings_$type	string		☐	
agile_sw imlaneSettings_enabled	boolean		☐	
agile_sw imlaneSettings_id	string		☐	
agile_updateableBy_$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOw ner_$type	string		☐	
draftOw ner_avatarUrl	string		☐	
draftOw ner_banned	boolean		☐	
draftOw ner_email	string		☐	
draftOw ner_fullName	string		☐	
draftOw ner_guest	boolean		☐	
draftOw ner_id	string		☐	
draftOw ner_jabberAccountName	string		☐	
draftOw ner_login	string		☐	
draftOw ner_online	boolean		☐	
draftOw ner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_$type	string		☐	
previousSprint_agile_$type	string		☐	
previousSprint_agile_hideOrphansSw imlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.11 SprintIssueLinksBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintIssueLinksBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SprintIssueLinksBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_colorCoding_$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSw imlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_$type	string		☐	
agile_originalEstimationField_aliase s	string		☐	
agile_originalEstimationField_hasRu nningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAuto Attached	boolean		☐	
agile_originalEstimationField_isDispl ayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpd ateable	boolean		☐	
agile_originalEstimationField_localiz edName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_ow ner_$type	string		☐	
agile_ow ner_avatarUrl	string		☐	
agile_ow ner_banned	boolean		☐	
agile_ow ner_email	string		☐	
agile_ow ner_fullName	string		☐	
agile_ow ner_guest	boolean		☐	
agile_ow ner_id	string		☐	
agile_ow ner_jabberAccountName	string		☐	
agile_ow ner_login	string		☐	
agile_ow ner_online	boolean		☐	
agile_ow ner_ringId	string		☐	
agile_sprintsSettings_$type	string		☐	
agile_sprintsSettings_cardOnSeve ralSprints	boolean		☐	
agile_sprintsSettings_disableSprint s	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtask sOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_sw imlaneSettings_$type	string		☐	
agile_sw imlaneSettings_enabled	boolean		☐	
agile_sw imlaneSettings_id	string		☐	
agile_updateableBy_$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOw ner_$type	string		☐	
draftOw ner_avatarUrl	string		☐	
draftOw ner_banned	boolean		☐	
draftOw ner_email	string		☐	
draftOw ner_fullName	string		☐	
draftOw ner_guest	boolean		☐	
draftOw ner_id	string		☐	
draftOw ner_jabberAccountName	string		☐	
draftOw ner_login	string		☐	
draftOw ner_online	boolean		☐	
draftOw ner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_$type	string		☐	
previousSprint_agile_$type	string		☐	
previousSprint_agile_hideOrphansSw imlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.12 SprintIssues

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: NotRequired

Base Path: `sprints[*].issues[*]`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `SprintIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_$type	string		☐	
agile_hideOrphansSw imlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_orphansAtTheTop	boolean		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJ ob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttach ed	boolean		☐	
columnSettings_field_isDisplayedInI ssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedNam e	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
currentSprint_$type_1	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansS w imlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtThe Top	boolean		☐	
currentSprint_agile_updateableByP rojectBased	boolean		☐	
currentSprint_agile_visibleForProje ctBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_commentsCount	int32		☐	
currentSprint_created	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_description	string		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id_1	string		☐	
currentSprint_id	string		☐	
currentSprint_idReadable	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_isDraft	boolean		☐	
currentSprint_name	string		☐	
currentSprint_numberInProject	int64		☐	
currentSprint_previousSprint_$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_resolved	int64		☐	
currentSprint_start	int64		☐	
currentSprint_summary	string		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
currentSprint_updated	int64		☐	
currentSprint_usesMarkdown	boolean		☐	
currentSprint_votes	int32		☐	
currentSprint_wikifiedDescription	string		☐	
description	string	Description	☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
hideOrphansSwimlane	boolean		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
previousSprint_$type	string		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
resolved	int64	Resolved	☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
start	int64	Start	☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
summary	string	Summary	☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updateableBy_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleForProjectBased	boolean		☐	
votes	int32	Votes	☐	
w ikifiedDescription	string	Wikified Description	☐	

5.1.13 SprintIssuesBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}`

Insert YouTrack API URL: `/agiles/{id}`

Update YouTrack API URL: `/agiles/{id}`

Delete YouTrack API URL: `/agiles/{id}`

Field Selection Method: NotRequired

Base Path: `sprints[*].issues[*]`

Select YouTrack API Operation: `get /agiles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintIssuesBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SprintIssuesBySprintId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_hideOrphansSw imlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_orphansAtTheTop	boolean		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJ ob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttach ed	boolean		☐	
columnSettings_field_isDisplayedInI ssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedNam e	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
currentSprint_$type_1	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansS w imlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtThe Top	boolean		☐	
currentSprint_agile_updateableByP rojectBased	boolean		☐	
currentSprint_agile_visibleForProje ctBased	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_archived	boolean		☐	
currentSprint_commentsCount	int32		☐	
currentSprint_created	int64		☐	
currentSprint_description	string		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id_1	string		☐	
currentSprint_id	string		☐	
currentSprint_idReadable	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_isDraft	boolean		☐	
currentSprint_name	string		☐	
currentSprint_numberInProject	int64		☐	
currentSprint_previousSprint_$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_resolved	int64		☐	
currentSprint_start	int64		☐	
currentSprint_summary	string		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
currentSprint_updated	int64		☐	
currentSprint_usesMarkdown	boolean		☐	
currentSprint_votes	int32		☐	
currentSprint_wikifiedDescription	string		☐	
description	string	Description	☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
hideOrphansSwimlane	boolean		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_$type	string		☐	
originalEstimationField_fieldType_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
previousSprint_$type	string		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
resolved	int64	Resolved	☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
start	int64	Start	☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
summary	string	Summary	☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
swimlaneSettings_id	string		☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_starting Number	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	
votes	int32	Votes	☐	
w ikifiedDescription	string	Wikified Description	☐	

5.1.14 SprintIssuesBySprintId1

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintIssuesBySprintId1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `SprintIssuesBySprintId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_colorCoding_$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_originalEstimationField_id	string		☐	
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_updateableBy_id	string		☐	
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_$type	string		☐	
previousSprint_agile_$type	string		☐	
previousSprint_agile_hideOrphansSw imlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.15 SprintIssueTagsBySprintId

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles/{id}/sprints`

Insert YouTrack API URL: `/agiles/{id}/sprints`

Update YouTrack API URL: `/agiles/{id}/sprints`

Delete YouTrack API URL: `/agiles/{id}/sprints`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /agiles/{id}/sprints`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SprintIssueTagsBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `SprintIssueTagsBySprintId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_colorCoding_$type	string		☐	
agile_colorCoding_id	string		☐	
agile_columnSettings_$type	string		☐	
agile_columnSettings_id	string		☐	
agile_currentSprint_$type	string		☐	
agile_currentSprint_archived	boolean		☐	
agile_currentSprint_finish	int64		☐	
agile_currentSprint_goal	string		☐	
agile_currentSprint_id	string		☐	
agile_currentSprint_isDefault	boolean		☐	
agile_currentSprint_name	string		☐	
agile_currentSprint_start	int64		☐	
agile_currentSprint_unresolvedIssuesCount	int32		☐	
agile_estimationField_$type	string		☐	
agile_estimationField_aliases	string		☐	
agile_estimationField_hasRunningJob	boolean		☐	
agile_estimationField_id	string		☐	
agile_estimationField_isAutoAttached	boolean		☐	
agile_estimationField_isDisplayedInIssueList	boolean		☐	
agile_estimationField_isUpdateable	boolean		☐	
agile_estimationField_localizedName	string		☐	
agile_estimationField_name	string		☐	
agile_estimationField_ordinal	int32		☐	
agile_hideOrphansSwimlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_originalEstimationField_$type	string		☐	
agile_originalEstimationField_aliases	string		☐	
agile_originalEstimationField_hasRunningJob	boolean		☐	
agile_originalEstimationField_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_originalEstimationField_isAutoAttached	boolean		☐	
agile_originalEstimationField_isDisplayedInIssueList	boolean		☐	
agile_originalEstimationField_isUpdateable	boolean		☐	
agile_originalEstimationField_localizedName	string		☐	
agile_originalEstimationField_name	string		☐	
agile_originalEstimationField_ordinal	int32		☐	
agile_orphansAtTheTop	boolean		☐	
agile_owner_$type	string		☐	
agile_owner_avatarUrl	string		☐	
agile_owner_banned	boolean		☐	
agile_owner_email	string		☐	
agile_owner_fullName	string		☐	
agile_owner_guest	boolean		☐	
agile_owner_id	string		☐	
agile_owner_jabberAccountName	string		☐	
agile_owner_login	string		☐	
agile_owner_online	boolean		☐	
agile_owner_ringId	string		☐	
agile_sprintsSettings_$type	string		☐	
agile_sprintsSettings_cardOnSeveralSprints	boolean		☐	
agile_sprintsSettings_disableSprints	boolean		☐	
agile_sprintsSettings_explicitQuery	string		☐	
agile_sprintsSettings_hideSubtasksOfCards	boolean		☐	
agile_sprintsSettings_id	string		☐	
agile_sprintsSettings_isExplicit	boolean		☐	
agile_status_$type	string		☐	
agile_status_hasJobs	boolean		☐	
agile_status_id	string		☐	
agile_status_valid	boolean		☐	
agile_swimlaneSettings_$type	string		☐	
agile_swimlaneSettings_enabled	boolean		☐	
agile_swimlaneSettings_id	string		☐	
agile_updateableBy_$type	string		☐	
agile_updateableBy_allUsersGroup	boolean		☐	
agile_updateableBy_icon	string		☐	
agile_updateableBy_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
agile_updateableBy_name	string		☐	
agile_updateableBy_ringId	string		☐	
agile_updateableBy_usersCount	int64		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleFor_$type	string		☐	
agile_visibleFor_allUsersGroup	boolean		☐	
agile_visibleFor_icon	string		☐	
agile_visibleFor_id	string		☐	
agile_visibleFor_name	string		☐	
agile_visibleFor_ringId	string		☐	
agile_visibleFor_usersCount	int64		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDefault	boolean	Is Default	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
previousSprint_$type	string		☐	
previousSprint_agile_$type	string		☐	
previousSprint_agile_hideOrphansSw imlane	boolean		☐	
previousSprint_agile_id	string		☐	
previousSprint_agile_name	string		☐	
previousSprint_agile_orphansAtTheTop	boolean		☐	
previousSprint_agile_updateableByProjectBased	boolean		☐	
previousSprint_agile_visibleForProjectBased	boolean		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_previousSprint_$type	string		☐	
previousSprint_previousSprint_archived	boolean		☐	
previousSprint_previousSprint_finish	int64		☐	
previousSprint_previousSprint_goal	string		☐	
previousSprint_previousSprint_id	string		☐	
previousSprint_previousSprint_isDefault	boolean		☐	
previousSprint_previousSprint_name	string		☐	
previousSprint_previousSprint_start	int64		☐	
previousSprint_previousSprint_unresolvedIssuesCount	int32		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
project_archived	boolean		☐	
project_description	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
start	int64	Start	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
untagOnResolve	boolean		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

5.1.16 Sprints

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /agiles`

Table Function Columns

The columns of the table function `Sprints` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttached	boolean		☐	
columnSettings_field_isDisplayedInIssueList	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedName	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansSwimlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtTheTop	boolean		☐	
currentSprint_agile_updateableByProjectBased	boolean		☐	
currentSprint_agile_visibleForProjectBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
hideOrphansSwimlane	boolean		☐	
id	string	ID	☐	
name	string	Name	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableByProjectBased	boolean		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

5.1.17 Sprints1

Catalog: YouTrack

Schema: Agile

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/agiles`

Insert YouTrack API URL: `/agiles`

Update YouTrack API URL: `/agiles`

Delete YouTrack API URL: `/agiles`

Field Selection Method: NotRequired

Base Path: `sprints[*]`

Select YouTrack API Operation: `get /agiles`

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `Sprints1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
agile_$type	string		☐	
agile_hideOrphansSw imlane	boolean		☐	
agile_id	string		☐	
agile_name	string		☐	
agile_orphansAtTheTop	boolean		☐	
agile_updateableByProjectBased	boolean		☐	
agile_visibleForProjectBased	boolean		☐	
archived	boolean	Archived	☐	
colorCoding_$type	string		☐	
colorCoding_id	string		☐	
columnSettings_$type	string		☐	
columnSettings_field_$type	string		☐	
columnSettings_field_aliases	string		☐	
columnSettings_field_hasRunningJ ob	boolean		☐	
columnSettings_field_id	string		☐	
columnSettings_field_isAutoAttach ed	boolean		☐	
columnSettings_field_isDisplayedInI ssueList	boolean		☐	
columnSettings_field_isUpdateable	boolean		☐	
columnSettings_field_localizedNam e	string		☐	
columnSettings_field_name	string		☐	
columnSettings_field_ordinal	int32		☐	
columnSettings_id	string		☐	
currentSprint_$type	string		☐	
currentSprint_agile_$type	string		☐	
currentSprint_agile_hideOrphansS w imlane	boolean		☐	
currentSprint_agile_id	string		☐	
currentSprint_agile_name	string		☐	
currentSprint_agile_orphansAtThe Top	boolean		☐	
currentSprint_agile_updateableByP rojectBased	boolean		☐	
currentSprint_agile_visibleForProje ctBased	boolean		☐	
currentSprint_archived	boolean		☐	
currentSprint_finish	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
currentSprint_goal	string		☐	
currentSprint_id	string		☐	
currentSprint_isDefault	boolean		☐	
currentSprint_name	string		☐	
currentSprint_previousSprint_$type	string		☐	
currentSprint_previousSprint_archived	boolean		☐	
currentSprint_previousSprint_finish	int64		☐	
currentSprint_previousSprint_goal	string		☐	
currentSprint_previousSprint_id	string		☐	
currentSprint_previousSprint_isDefault	boolean		☐	
currentSprint_previousSprint_name	string		☐	
currentSprint_previousSprint_start	int64		☐	
currentSprint_previousSprint_unresolvedIssuesCount	int32		☐	
currentSprint_start	int64		☐	
currentSprint_unresolvedIssuesCount	int32		☐	
estimationField_$type	string		☐	
estimationField_aliases	string		☐	
estimationField_fieldDefaults_$type	string		☐	
estimationField_fieldDefaults_canBeEmpty	boolean		☐	
estimationField_fieldDefaults_emptyFieldText	string		☐	
estimationField_fieldDefaults_id	string		☐	
estimationField_fieldDefaults_isPublic	boolean		☐	
estimationField_fieldType_$type	string		☐	
estimationField_fieldType_id	string		☐	
estimationField_hasRunningJob	boolean		☐	
estimationField_id	string		☐	
estimationField_isAutoAttached	boolean		☐	
estimationField_isDisplayedInIssueList	boolean		☐	
estimationField_isUpdateable	boolean		☐	
estimationField_localizedName	string		☐	
estimationField_name	string		☐	
estimationField_ordinal	int32		☐	
finish	int64	Finish	☐	
goal	string	Goal	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
hideOrphansSw imlane	boolean		☐	
id_1	string		☐	
id	string	ID	☐	
isDefault	boolean	Is Default	☐	
name_1	string		☐	
name	string	Name	☐	
originalEstimationField_$type	string		☐	
originalEstimationField_aliases	string		☐	
originalEstimationField_fieldDefaults_$type	string		☐	
originalEstimationField_fieldDefaults_canBeEmpty	boolean		☐	
originalEstimationField_fieldDefaults_emptyFieldText	string		☐	
originalEstimationField_fieldDefaults_id	string		☐	
originalEstimationField_fieldDefaults_isPublic	boolean		☐	
originalEstimationField_fieldType_$type	string		☐	
originalEstimationField_fieldType_id	string		☐	
originalEstimationField_hasRunningJob	boolean		☐	
originalEstimationField_id	string		☐	
originalEstimationField_isAutoAttached	boolean		☐	
originalEstimationField_isDisplayedInIssueList	boolean		☐	
originalEstimationField_isUpdateable	boolean		☐	
originalEstimationField_localizedName	string		☐	
originalEstimationField_name	string		☐	
originalEstimationField_ordinal	int32		☐	
orphansAtTheTop	boolean		☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	
ow ner_email	string		☐	
ow ner_fullName	string		☐	
ow ner_guest	boolean		☐	
ow ner_id	string		☐	
ow ner_jabberAccountName	string		☐	
ow ner_login	string		☐	
ow ner_online	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
previousSprint_$type	string		☐	
previousSprint_archived	boolean		☐	
previousSprint_finish	int64		☐	
previousSprint_goal	string		☐	
previousSprint_id	string		☐	
previousSprint_isDefault	boolean		☐	
previousSprint_name	string		☐	
previousSprint_start	int64		☐	
previousSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_$type	string		☐	
sprintsSettings_cardOnSeveralSprints	boolean		☐	
sprintsSettings_defaultSprint_$type	string		☐	
sprintsSettings_defaultSprint_archived	boolean		☐	
sprintsSettings_defaultSprint_finish	int64		☐	
sprintsSettings_defaultSprint_goal	string		☐	
sprintsSettings_defaultSprint_id	string		☐	
sprintsSettings_defaultSprint_isDefault	boolean		☐	
sprintsSettings_defaultSprint_name	string		☐	
sprintsSettings_defaultSprint_start	int64		☐	
sprintsSettings_defaultSprint_unresolvedIssuesCount	int32		☐	
sprintsSettings_disableSprints	boolean		☐	
sprintsSettings_explicitQuery	string		☐	
sprintsSettings_hideSubtasksOfCards	boolean		☐	
sprintsSettings_id	string		☐	
sprintsSettings_isExplicit	boolean		☐	
sprintsSettings_sprintSyncField_$type	string		☐	
sprintsSettings_sprintSyncField_aliases	string		☐	
sprintsSettings_sprintSyncField_hasRunningJob	boolean		☐	
sprintsSettings_sprintSyncField_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
sprintsSettings_sprintSyncField_isAutoAttached	boolean		☐	
sprintsSettings_sprintSyncField_isDisplayedInIssueList	boolean		☐	
sprintsSettings_sprintSyncField_isUpdateable	boolean		☐	
sprintsSettings_sprintSyncField_localizedName	string		☐	
sprintsSettings_sprintSyncField_name	string		☐	
sprintsSettings_sprintSyncField_ordinal	int32		☐	
start	int64	Start	☐	
status_$type	string		☐	
status_hasJobs	boolean		☐	
status_id	string		☐	
status_valid	boolean		☐	
swimlaneSettings_$type	string		☐	
swimlaneSettings_enabled	boolean		☐	
swimlaneSettings_id	string		☐	
unresolvedIssuesCount	int32	Unresolved Issue Count	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updateableByProjectBased	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
visibleForProjectBased	boolean		☐	

6 Schema: Articles

6.1 Tables

6.1.1 ArticleById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ArticleById. A value must be provided at all times for required parameters, but optional

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `ArticleById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
content_1	string		☐	
content	string	Content	☐	
created	int64	Created	☐	
externalArticle_$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	

6.1.2 Articles: YouTrack Articles

Catalog: YouTrack

Schema: Articles

Label: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `Articles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
content_1	string		☐	
content	string	Content	☐	
created	int64	Created	☐	
externalArticle_$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	

6.1.3 AttachmentById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function AttachmentById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `AttachmentById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
article_$type_1	string		☐	
article_$type	string		☐	
article_content_1	string		☐	
article_content	string		☐	
article_id_1	string		☐	
article_id	string		☐	
article_summary_1	string		☐	
article_summary	string		☐	
author_$type_1	string		☐	
author_$type	string		☐	
author_avatarUrl_1	string		☐	
author_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_banned_1	boolean		☐	
author_banned	boolean		☐	
author_email_1	string		☐	
author_email	string		☐	
author_fullName_1	string		☐	
author_fullName	string		☐	
author_guest_1	boolean		☐	
author_guest	boolean		☐	
author_id_1	string		☐	
author_id	string		☐	
author_jabberAccountName_1	string		☐	
author_jabberAccountName	string		☐	
author_login_1	string		☐	
author_login	string		☐	
author_online_1	boolean		☐	
author_online	boolean		☐	
author_ringId_1	string		☐	
author_ringId	string		☐	
base64Content_1	string		☐	
base64Content	string	Base64 Content	☐	
charset_1	string		☐	
charset	string	Charset	☐	
comment_$type_1	string		☐	
comment_$type	string		☐	
comment_created_1	int64		☐	
comment_created	int64		☐	
comment_id_1	string		☐	
comment_id	string		☐	
comment_text_1	string		☐	
comment_text	string		☐	
comment_updated_1	int64		☐	
comment_updated	int64		☐	
content_1	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
draft_1	boolean		☐	
draft	boolean	Draft	☐	
extension_1	string		☐	
extension	string	Extension	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalArticle_$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
metaData_1	string		☐	
metaData	string	Metadata	☐	
mimeType_1	string		☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed_1	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type_1	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
size_1	int64		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
url_1	string		☐	
url	string	URL	☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.4 Attachments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: NotRequired

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `Attachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
article_$type_1	string		☐	
article_$type	string		☐	
article_content_1	string		☐	
article_content	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
article_id_1	string		☐	
article_id	string		☐	
article_summary_1	string		☐	
article_summary	string		☐	
author_$type_1	string		☐	
author_$type	string		☐	
author_avatarUrl_1	string		☐	
author_avatarUrl	string		☐	
author_banned_1	boolean		☐	
author_banned	boolean		☐	
author_email_1	string		☐	
author_email	string		☐	
author_fullName_1	string		☐	
author_fullName	string		☐	
author_guest_1	boolean		☐	
author_guest	boolean		☐	
author_id_1	string		☐	
author_id	string		☐	
author_jabberAccountName_1	string		☐	
author_jabberAccountName	string		☐	
author_login_1	string		☐	
author_login	string		☐	
author_online_1	boolean		☐	
author_online	boolean		☐	
author_ringId_1	string		☐	
author_ringId	string		☐	
base64Content_1	string		☐	
base64Content	string	Base64 Content	☐	
charset_1	string		☐	
charset	string	Charset	☐	
comment_$type_1	string		☐	
comment_$type	string		☐	
comment_created_1	int64		☐	
comment_created	int64		☐	
comment_id_1	string		☐	
comment_id	string		☐	
comment_text_1	string		☐	
comment_text	string		☐	
comment_updated_1	int64		☐	
comment_updated	int64		☐	
content_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
draft_1	boolean		☐	
draft	boolean	Draft	☐	
extension_1	string		☐	
extension	string	Extension	☐	
externalArticle_$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
metaData_1	string		☐	
metaData	string	Metadata	☐	
mimeType_1	string		☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed_1	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type_1	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
size_1	int64		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
url_1	string		☐	
url	string	URL	☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.5 ChildArticleAttachments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: NotRequired

Base Path: `childArticles[*].attachments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `ChildArticleAttachments` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type_3	string		☐	
$type	string		☐	
base64Content_1	string		☐	
base64Content	string	Base64 Content	☐	
charset_1	string		☐	
charset	string	Charset	☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created_3	int64		☐	
created	int64	Created	☐	
draft_1	boolean		☐	
draft	boolean	Draft	☐	
extension_1	string		☐	
extension	string	Extension	☐	
externalArticle_$type_1	string		☐	
externalArticle_$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id_3	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
metaData_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
metaData	string	Metadata	☐	
mimeType_1	string		☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_$type	string		☐	
parentArticle_base64Content	string		☐	
parentArticle_charset	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_draft	boolean		☐	
parentArticle_extension	string		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_metaData	string		☐	
parentArticle_mimeType	string		☐	
parentArticle_name	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_removed	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_size	int64		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_url	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
removed_1	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type_1	string		☐	
reporter_$type_2	string		☐	
reporter_$type_3	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
size_1	int64		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated_3	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type_1	string		☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
url_1	string		☐	
url	string	URL	☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.6 ChildArticleAttachmentsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Base Path: `childArticles[*].attachments[*]`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChildArticleAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `ChildArticleAttachmentsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type_3	string		☐	
$type	string		☐	
base64Content_1	string		☐	
base64Content	string	Base64 Content	☐	
charset_1	string		☐	
charset	string	Charset	☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created_3	int64		☐	
created	int64	Created	☐	
draft_1	boolean		☐	
draft	boolean	Draft	☐	
extension_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
extension	string	Extension	☐	
externalArticle_$type_1	string		☐	
externalArticle_$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id_3	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
metaData_1	string		☐	
metaData	string	Metadata	☐	
mimeType_1	string		☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_$type	string		☐	
parentArticle_base64Content	string		☐	
parentArticle_charset	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_draft	boolean		☐	
parentArticle_extension	string		☐	
parentArticle_externalArticle_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_metaData	string		☐	
parentArticle_mimeType	string		☐	
parentArticle_name	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_removed	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_size	int64		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_url	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
removed_1	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type_1	string		☐	
reporter_$type_2	string		☐	
reporter_$type_3	string		☐	
reporter_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
size_1	int64		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated_3	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type_1	string		☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
url_1	string		☐	
url	string	URL	☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.7 ChildArticleComments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: NotRequired

Base Path: `childArticles[*].comments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `ChildArticleComments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
externalArticle_$type_1	string		☐	
externalArticle_$type	string		☐	
externalArticle_id_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_$type	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_text	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type_2	string		☐	
reporter_$type_3	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type_1	string		☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.8 ChildArticleCommentsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Base Path: `childArticles[*].comments[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function ChildArticleCommentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `ChildArticleCommentsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
externalArticle_$type_1	string		☐	
externalArticle_$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_$type	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_text	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type_2	string		☐	
reporter_$type_3	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type_1	string		☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.9 ChildArticles

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: NotRequired

Base Path: `childArticles[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `ChildArticles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
created_1	int64		☐	
created	int64	Created	☐	
externalArticle_$type_1	string		☐	
externalArticle_$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type_2	string		☐	
reporter_$type_3	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type_1	string		☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.10 ChildArticlesById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Base Path: `childArticles[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChildArticlesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `ChildArticlesById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created	int64	Created	☐	
externalArticle_$type_1	string		☐	
externalArticle_$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id	string	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_content_1	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type_2	string		☐	
reporter_$type_3	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type_1	string		☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibility_id	string		☐	

6.1.11 ChildChildArticles

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: NotRequired

Base Path: `childArticles[*].childArticles[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `ChildChildArticles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content_4	string		☐	
content_5	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
externalArticle_$type_1	string		☐	
externalArticle_$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren_2	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar_2	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable_2	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal_2	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_$type	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content_2	string		☐	
parentArticle_content_3	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren_2	boolean		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar_2	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_idReadable_2	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal_2	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary_2	string		☐	
parentArticle_summary_3	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type_2	string		☐	
reporter_$type_3	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary_4	string		☐	
summary_5	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.12 ChildChildArticlesById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Base Path: `childArticles[*].childArticles[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ChildChildArticlesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `ChildChildArticlesById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
content_1	string		☐	
content_2	string		☐	
content_3	string		☐	
content_4	string		☐	
content_5	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
externalArticle_$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalArticle_$type	string		☐	
externalArticle_id_1	string		☐	
externalArticle_id	string		☐	
externalArticle_key_1	string		☐	
externalArticle_key	string		☐	
externalArticle_name_1	string		☐	
externalArticle_name	string		☐	
externalArticle_url_1	string		☐	
externalArticle_url	string		☐	
hasChildren_1	boolean		☐	
hasChildren_2	boolean		☐	
hasChildren	boolean	Has Children	☐	
hasStar_1	boolean		☐	
hasStar_2	boolean		☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable_2	string		☐	
idReadable	string	Readable ID	☐	
ordinal_1	int64		☐	
ordinal_2	int64		☐	
ordinal	int64	Ordinal	☐	
parentArticle_$type	string		☐	
parentArticle_content_1	string		☐	
parentArticle_content_2	string		☐	
parentArticle_content_3	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created_2	int64		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren_1	boolean		☐	
parentArticle_hasChildren_2	boolean		☐	
parentArticle_hasChildren	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_hasStar_1	boolean		☐	
parentArticle_hasStar_2	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable_1	string		☐	
parentArticle_idReadable_2	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal_1	int64		☐	
parentArticle_ordinal_2	int64		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary_1	string		☐	
parentArticle_summary_2	string		☐	
parentArticle_summary_3	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated_2	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived_1	boolean		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail_1	string		☐	
project_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_iconUrl_1	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail_1	string		☐	
project_replyToEmail	string		☐	
project_shortName_1	string		☐	
project_shortName	string		☐	
project_startingNumber_1	int64		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template_1	boolean		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type_2	string		☐	
reporter_$type_3	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl_2	string		☐	
reporter_avatarUrl_3	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned_2	boolean		☐	
reporter_banned_3	boolean		☐	
reporter_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_email_1	string		☐	
reporter_email_2	string		☐	
reporter_email_3	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName_2	string		☐	
reporter_fullName_3	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest_2	boolean		☐	
reporter_guest_3	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id_2	string		☐	
reporter_id_3	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName_2	string		☐	
reporter_jabberAccountName_3	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login_2	string		☐	
reporter_login_3	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online_2	boolean		☐	
reporter_online_3	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId_2	string		☐	
reporter_ringId_3	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary_2	string		☐	
summary_3	string		☐	
summary_4	string		☐	
summary_5	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
summary	string	Summary	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type_1	string		☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl_1	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned_1	boolean		☐	
updatedBy_banned	boolean		☐	
updatedBy_email_1	string		☐	
updatedBy_email	string		☐	
updatedBy_fullName_1	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest_1	boolean		☐	
updatedBy_guest	boolean		☐	
updatedBy_id_1	string		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName_1	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login_1	string		☐	
updatedBy_login	string		☐	
updatedBy_online_1	boolean		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId_1	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type_3	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id_3	string		☐	
visibility_id	string		☐	

6.1.13 CommentAttachments

Catalog: YouTrack

Schema: Articles

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: NotRequired

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `CommentAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
article_content	string		☐	
article_created	int64		☐	
article_hasChildren	boolean		☐	
article_hasStar	boolean		☐	
article_idReadable	string		☐	
article_ordinal	int64		☐	
article_summary	string		☐	
article_updated	int64		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
content_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
draft	boolean	Draft	☐	
extension	string	Extension	☐	
externalArticle_$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
ordinal	int64	Ordinal	☐	
parentArticle_$type	string		☐	
parentArticle_base64Content	string		☐	
parentArticle_charset	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created	int64		☐	
parentArticle_draft	boolean		☐	
parentArticle_extension	string		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_metaData	string		☐	
parentArticle_mimeType	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_name	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_removed	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_size	int64		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_url	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type_1	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary	string	Summary	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
text	string	Text	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
url	string	URL	☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id	string		☐	

6.1.14 CommentAttachmentsByIssueId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /articles/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CommentAttachmentsByIssueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CommentAttachmentsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
article_content	string		☐	
article_created	int64		☐	
article_hasChildren	boolean		☐	
article_hasStar	boolean		☐	
article_idReadable	string		☐	
article_ordinal	int64		☐	
article_summary	string		☐	
article_updated	int64		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
content_1	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
draft	boolean	Draft	☐	
extension	string	Extension	☐	
externalArticle_$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
ordinal	int64	Ordinal	☐	
parentArticle_$type	string		☐	
parentArticle_base64Content	string		☐	
parentArticle_charset	string		☐	
parentArticle_content	string		☐	
parentArticle_created_1	int64		☐	
parentArticle_created	int64		☐	
parentArticle_draft	boolean		☐	
parentArticle_extension	string		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_hasStar	boolean		☐	
parentArticle_id	string		☐	
parentArticle_idReadable	string		☐	
parentArticle_metaData	string		☐	
parentArticle_mimeType	string		☐	
parentArticle_name	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_removed	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_size	int64		☐	
parentArticle_summary	string		☐	
parentArticle_updated_1	int64		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_url	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type_1	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
size	int64	Size	☐	
summary_1	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
url	string	URL	☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id	string		☐	

6.1.15 Comments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles`

Insert YouTrack API URL: `/articles`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Update YouTrack API URL: `/articles`

Delete YouTrack API URL: `/articles`

Field Selection Method: NotRequired

Base Path: `comments[*]`

Select YouTrack API Operation: `get /articles`

Table Function Columns

The columns of the table function `Comments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
article_content	string		☐	
article_created	int64		☐	
article_hasChildren	boolean		☐	
article_hasStar	boolean		☐	
article_idReadable	string		☐	
article_ordinal	int64		☐	
article_summary	string		☐	
article_updated	int64		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
content_1	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created	int64	Created	☐	
externalArticle_$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id	string		☐	

6.1.16 CommentsByIssueId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/articles/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Insert YouTrack API URL: `/articles/{id}`

Update YouTrack API URL: `/articles/{id}`

Delete YouTrack API URL: `/articles/{id}`

Field Selection Method: NotRequired

Base Path: `comments[*]`

Select YouTrack API Operation: `get /articles/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CommentsByIssueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CommentsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
article_content	string		☐	
article_created	int64		☐	
article_hasChildren	boolean		☐	
article_hasStar	boolean		☐	
article_idReadable	string		☐	
article_ordinal	int64		☐	
article_summary	string		☐	
article_updated	int64		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
content_1	string		☐	
content	string	Content	☐	
created_1	int64		☐	
created	int64	Created	☐	
externalArticle_$type	string		☐	
externalArticle_id	string		☐	
externalArticle_key	string		☐	
externalArticle_name	string		☐	
externalArticle_url	string		☐	
hasChildren	boolean	Has Children	☐	
hasStar	boolean	Has Star	☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
ordinal	int64	Ordinal	☐	
parentArticle_content	string		☐	
parentArticle_created	int64		☐	
parentArticle_externalArticle_$type	string		☐	
parentArticle_externalArticle_id	string		☐	
parentArticle_externalArticle_key	string		☐	
parentArticle_externalArticle_name	string		☐	
parentArticle_externalArticle_url	string		☐	
parentArticle_hasChildren	boolean		☐	
parentArticle_hasStar	boolean		☐	
parentArticle_idReadable	string		☐	
parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_content	string		☐	
parentArticle_parentArticle_created	int64		☐	
parentArticle_parentArticle_hasChildren	boolean		☐	
parentArticle_parentArticle_hasStar	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_parentArticle_idReadable	string		☐	
parentArticle_parentArticle_ordinal	int64		☐	
parentArticle_parentArticle_summary	string		☐	
parentArticle_parentArticle_updated	int64		☐	
parentArticle_project_archived	boolean		☐	
parentArticle_project_description	string		☐	
parentArticle_project_fromEmail	string		☐	
parentArticle_project_iconUrl	string		☐	
parentArticle_project_replyToEmail	string		☐	
parentArticle_project_shortName	string		☐	
parentArticle_project_startingNumber	int64		☐	
parentArticle_project_template	boolean		☐	
parentArticle_reporter_$type	string		☐	
parentArticle_reporter_avatarUrl	string		☐	
parentArticle_reporter_banned	boolean		☐	
parentArticle_reporter_email	string		☐	
parentArticle_reporter_fullName	string		☐	
parentArticle_reporter_guest	boolean		☐	
parentArticle_reporter_id	string		☐	
parentArticle_reporter_jabberAccountName	string		☐	
parentArticle_reporter_login	string		☐	
parentArticle_reporter_online	boolean		☐	
parentArticle_reporter_ringId	string		☐	
parentArticle_summary	string		☐	
parentArticle_updated	int64		☐	
parentArticle_updatedBy_$type	string		☐	
parentArticle_updatedBy_avatarUrl	string		☐	
parentArticle_updatedBy_banned	boolean		☐	
parentArticle_updatedBy_email	string		☐	
parentArticle_updatedBy_fullName	string		☐	
parentArticle_updatedBy_guest	boolean		☐	
parentArticle_updatedBy_id	string		☐	
parentArticle_updatedBy_jabberAccountName	string		☐	
parentArticle_updatedBy_login	string		☐	
parentArticle_updatedBy_online	boolean		☐	
parentArticle_updatedBy_ringId	string		☐	
parentArticle_visibility_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parentArticle_visibility_id	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_$type	string		☐	
reporter_avatarUrl_1	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned_1	boolean		☐	
reporter_banned	boolean		☐	
reporter_email_1	string		☐	
reporter_email	string		☐	
reporter_fullName_1	string		☐	
reporter_fullName	string		☐	
reporter_guest_1	boolean		☐	
reporter_guest	boolean		☐	
reporter_id_1	string		☐	
reporter_id	string		☐	
reporter_jabberAccountName_1	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login_1	string		☐	
reporter_login	string		☐	
reporter_online_1	boolean		☐	
reporter_online	boolean		☐	
reporter_profiles_$type_1	string		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id_1	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId_1	string		☐	
reporter_ringId	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updatedBy_$type	string		☐	
updatedBy_avatarUrl	string		☐	
updatedBy_banned	boolean		☐	
updatedBy_email	string		☐	
updatedBy_fullName	string		☐	
updatedBy_guest	boolean		☐	
updatedBy_id	string		☐	
updatedBy_jabberAccountName	string		☐	
updatedBy_login	string		☐	
updatedBy_online	boolean		☐	
updatedBy_profiles_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updatedBy_profiles_id	string		☐	
updatedBy_ringId	string		☐	
visibility_$type_1	string		☐	
visibility_$type_2	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id_2	string		☐	
visibility_id	string		☐	

6.1.17 GroupById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/groups/{id}`

Insert YouTrack API URL: `/groups/{id}`

Update YouTrack API URL: `/groups/{id}`

Delete YouTrack API URL: `/groups/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /groups/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function GroupById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `GroupById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id	string	ID	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_createdBy_$type	string		☐	
teamForProject_createdBy_avatarUrl	string		☐	
teamForProject_createdBy_banned	boolean		☐	
teamForProject_createdBy_email	string		☐	
teamForProject_createdBy_fullName	string		☐	
teamForProject_createdBy_guest	boolean		☐	
teamForProject_createdBy_id	string		☐	
teamForProject_createdBy_jabberAccountName	string		☐	
teamForProject_createdBy_login	string		☐	
teamForProject_createdBy_online	boolean		☐	
teamForProject_createdBy_ringId	string		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_leader_$type	string		☐	
teamForProject_leader_avatarUrl	string		☐	
teamForProject_leader_banned	boolean		☐	
teamForProject_leader_email	string		☐	
teamForProject_leader_fullName	string		☐	
teamForProject_leader_guest	boolean		☐	
teamForProject_leader_id	string		☐	
teamForProject_leader_jabberAccountName	string		☐	
teamForProject_leader_login	string		☐	
teamForProject_leader_online	boolean		☐	
teamForProject_leader_ringId	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
teamForProject_startingNumber	int64		☐	
teamForProject_team_$type	string		☐	
teamForProject_team_allUsersGroup	boolean		☐	
teamForProject_team_icon	string		☐	
teamForProject_team_id	string		☐	
teamForProject_team_name	string		☐	
teamForProject_team_ringId	string		☐	
teamForProject_team_usersCount	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

6.1.18 Groups

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/groups`

Insert YouTrack API URL: `/groups`

Update YouTrack API URL: `/groups`

Delete YouTrack API URL: `/groups`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /groups`

Table Function Columns

The columns of the table function `Groups` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id	string	ID	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_createdBy_$type	string		☐	
teamForProject_createdBy_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
teamForProject_createdBy_banned	boolean		☐	
teamForProject_createdBy_email	string		☐	
teamForProject_createdBy_fullName	string		☐	
teamForProject_createdBy_guest	boolean		☐	
teamForProject_createdBy_id	string		☐	
teamForProject_createdBy_jabberAccountName	string		☐	
teamForProject_createdBy_login	string		☐	
teamForProject_createdBy_online	boolean		☐	
teamForProject_createdBy_ringId	string		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_leader_$type	string		☐	
teamForProject_leader_avatarUrl	string		☐	
teamForProject_leader_banned	boolean		☐	
teamForProject_leader_email	string		☐	
teamForProject_leader_fullName	string		☐	
teamForProject_leader_guest	boolean		☐	
teamForProject_leader_id	string		☐	
teamForProject_leader_jabberAccountName	string		☐	
teamForProject_leader_login	string		☐	
teamForProject_leader_online	boolean		☐	
teamForProject_leader_ringId	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_team_$type	string		☐	
teamForProject_team_allUsersGroup	boolean		☐	
teamForProject_team_icon	string		☐	
teamForProject_team_id	string		☐	
teamForProject_team_name	string		☐	
teamForProject_team_ringId	string		☐	
teamForProject_team_usersCount	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

6.1.19 IssueLinkTypes

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueLinkTypes`

Insert YouTrack API URL: `/issueLinkTypes`

Update YouTrack API URL: `/issueLinkTypes`

Delete YouTrack API URL: `/issueLinkTypes`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueLinkTypes`

Table Function Columns

The columns of the table function `IssueLinkTypes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
aggregation	boolean	Aggregation	☐	
directed	boolean	Directed	☐	
id	string	ID	☐	
localizedName	string	Localized Name	☐	
localizedSourceToTarget	string	Localized Source to Target	☐	
localizedTargetToSource	string	Localized Target to Source	☐	
name	string	Name	☐	
readOnly	boolean	Read-only	☐	
sourceToTarget	string	Source to Target	☐	
targetToSource	string	Target to Source	☐	

6.1.20 IssueLinkTypesById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueLinkTypes/{id}`

Insert YouTrack API URL: `/issueLinkTypes/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Update YouTrack API URL: `/issueLinkTypes/{id}`

Delete YouTrack API URL: `/issueLinkTypes/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueLinkTypes/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueLinkTypesById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueLinkTypesById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
aggregation	boolean	Aggregation	☐	
directed	boolean	Directed	☐	
id	string	ID	☐	
localizedName	string	Localized Name	☐	
localizedSourceToTarget	string	Localized Source to Target	☐	
localizedTargetToSource	string	Localized Target to Source	☐	
name	string	Name	☐	
readOnly	boolean	Read-only	☐	
sourceToTarget	string	Source to Target	☐	
targetToSource	string	Target to Source	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

6.1.21 IssueTagAttachmentIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagAttachmentIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagAttachmentIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
comment_$type	string		☐	
comment_created	int64		☐	
comment_deleted	boolean		☐	
comment_id	string		☐	
comment_text	string		☐	
comment_textPreview	string		☐	
comment_updated	int64		☐	
comment_usesMarkdown	boolean		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.22 IssueTagById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

6.1.23 IssueTagById2

Catalog: YouTrack

Schema: Articles

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagById2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagById2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountNam e	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.24 IssueTagCommentAttachmentIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagCommentAttachmentIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagCommentAttachmentIssuesByTagId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.25 IssueTagCommentIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `comments[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagCommentIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagCommentIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updated_1	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.26 IssueTagCustomFieldIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Base Path: `customFields[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagCustomFieldIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagCustomFieldIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
projectCustomField_$type	string		☐	
projectCustomField_canBeEmpty	boolean		☐	
projectCustomField_emptyFieldText	string		☐	
projectCustomField_hasRunningJob	boolean		☐	
projectCustomField_id	string		☐	
projectCustomField_isPublic	boolean		☐	
projectCustomField_ordinal	int32		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.27 IssueTagIssueAttachments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssueAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.28 IssueTagIssueAttachmentsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagIssueAttachmentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagIssueAttachmentsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

6.1.29 IssueTagIssueById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagIssueById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagIssueById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.30 IssueTagIssueComments

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssueComments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.31 IssueTagIssueCommentsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagIssueCommentsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `IssueTagIssueCommentsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
untagOnResolve	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.32 IssueTagIssueCustomFields

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `IssueTagIssueCustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.33 IssueTagIssueLinks

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssueLinks` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOw ner_$type	string		☐	
draftOw ner_avatarUrl	string		☐	
draftOw ner_banned	boolean		☐	
draftOw ner_email	string		☐	
draftOw ner_fullName	string		☐	
draftOw ner_guest	boolean		☐	
draftOw ner_id	string		☐	
draftOw ner_jabberAccountName	string		☐	
draftOw ner_login	string		☐	
draftOw ner_online	boolean		☐	
draftOw ner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	
ow ner_email	string		☐	
ow ner_fullName	string		☐	
ow ner_guest	boolean		☐	
ow ner_id	string		☐	
ow ner_jabberAccountName	string		☐	
ow ner_login	string		☐	
ow ner_online	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_starting Number	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
w atchers_$type	string		☐	
w atchers_hasStar	boolean		☐	
w atchers_id	string		☐	
w ikifiedDescription	string	Wikified Description	☐	

6.1.34 IssueTagIssueLinksById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagIssueLinksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagIssueLinksById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.35 IssueTagIssues

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /issueTags`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `IssueTagIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOw ner_$type	string		☐	
draftOw ner_avatarUrl	string		☐	
draftOw ner_banned	boolean		☐	
draftOw ner_email	string		☐	
draftOw ner_fullName	string		☐	
draftOw ner_guest	boolean		☐	
draftOw ner_id	string		☐	
draftOw ner_jabberAccountName	string		☐	
draftOw ner_login	string		☐	
draftOw ner_online	boolean		☐	
draftOw ner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	
ow ner_email	string		☐	
ow ner_fullName	string		☐	
ow ner_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_replyTo Email	string		☐	
visibleFor_teamForProject_shortNa me	string		☐	
visibleFor_teamForProject_starting Number	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
w atchers_$type	string		☐	
w atchers_hasStar	boolean		☐	
w atchers_id	string		☐	
w ikifiedDescription	string	Wikified Description	☐	

6.1.36 IssueTagIssuesCustomFieldsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagIssuesCustomFieldsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagIssuesCustomFieldsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.37 IssueTagIssuesTags

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTagIssuesTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type_1	string		☐	
owner_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
summary	string	Summary	☐	
untagOnResolve_1	boolean		☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.38 IssueTagIssueTagsById

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}`

Insert YouTrack API URL: `/issueTags/{id}`

Update YouTrack API URL: `/issueTags/{id}`

Delete YouTrack API URL: `/issueTags/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /issueTags/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagIssueTagsById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagIssueTagsById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type_1	string		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve_1	boolean		☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

6.1.39 IssueTagLinkIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `links[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagLinkIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagLinkIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.40 IssueTagLinkIssuesByTagId1

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `links[*].issues[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function IssueTagLinkIssuesByTagId1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagLinkIssuesByTagId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_$type_1	string		☐	
parent_$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountNam e	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdow n	boolean		☐	
project_votes	int32		☐	
project_w ikifiedDescription	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.41 IssueTagLinkTrimmedIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `links[*].trimmedIssues[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagLinkTrimmedIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagLinkTrimmedIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_$type_1	string		☐	
parent_$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.42 IssueTags: YouTrack Issue Tags

Catalog: YouTrack

Schema: Articles

Label: Issue Tags

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags`

Insert YouTrack API URL: `/issueTags`

Update YouTrack API URL: `/issueTags`

Delete YouTrack API URL: `/issueTags`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issueTags`

Table Function Columns

The columns of the table function `IssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

6.1.43 TagIssuesByTagId

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `TagIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountNam e	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

6.1.44 TagIssuesByTagId2

Catalog: YouTrack

Schema: Articles

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issueTags/{id}/issues`

Insert YouTrack API URL: `/issueTags/{id}/issues`

Update YouTrack API URL: `/issueTags/{id}/issues`

Delete YouTrack API URL: `/issueTags/{id}/issues`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /issueTags/{id}/issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagIssuesByTagId2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `TagIssuesByTagId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_$type_1	string		☐	
parent_$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdow n	boolean		☐	
project_votes	int32		☐	
project_w ikifiedDescription	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

7 Schema: Backups

7.1 Tables

7.1.1 DatabaseBackupById

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/backups/{id}`

Insert YouTrack API URL: `/admin/databaseBackup/backups/{id}`

Update YouTrack API URL: `/admin/databaseBackup/backups/{id}`

Delete YouTrack API URL: `/admin/databaseBackup/backups/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/databaseBackup/backups/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function DatabaseBackupById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `DatabaseBackupById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
creationDate	int64	Creation Date	☐	
id	string	ID	☐	
link	string	Link	☐	
name	string	Name	☐	
size	int64	Size	☐	

7.1.2 DatabaseBackups

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/backups`

Insert YouTrack API URL: `/admin/databaseBackup/backups`

Update YouTrack API URL: `/admin/databaseBackup/backups`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Delete YouTrack API URL: `/admin/databaseBackup/backups`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/databaseBackup/backups`

Table Function Columns

The columns of the table function `DatabaseBackups` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
creationDate	int64	Creation Date	☐	
id	string	ID	☐	
link	string	Link	☐	
name	string	Name	☐	
size	int64	Size	☐	

7.1.3 DatabaseBackupSettingBackupStatuses

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings/backupStatus`

Insert YouTrack API URL: `/admin/databaseBackup/settings/backupStatus`

Update YouTrack API URL: `/admin/databaseBackup/settings/backupStatus`

Delete YouTrack API URL: `/admin/databaseBackup/settings/backupStatus`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/databaseBackup/settings/backupStatus`

Table Function Columns

The columns of the table function `DatabaseBackupSettingBackupStatuses` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
backupCancelled	boolean	Backup Cancelled	☐	
backupError_$type	string		☐	
backupError_date	int64		☐	
backupError_errorMessage	string		☐	
backupError_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
backupInProgress	boolean	Backup in Progress	☐	
id	string	ID	☐	

7.1.4 DatabaseBackupSettings

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings`

Insert YouTrack API URL: `/admin/databaseBackup/settings`

Update YouTrack API URL: `/admin/databaseBackup/settings`

Delete YouTrack API URL: `/admin/databaseBackup/settings`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/databaseBackup/settings`

Table Function Columns

The columns of the table function `DatabaseBackupSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
archiveFormat	string	Archive Format	☐	
availableDiskSpace	int64	Available Disk Space	☐	
backupStatus_$type	string		☐	
backupStatus_backupCancelled	boolean		☐	
backupStatus_backupError_$type	string		☐	
backupStatus_backupError_date	int64		☐	
backupStatus_backupError_errorMessage	string		☐	
backupStatus_backupError_id	string		☐	
backupStatus_backupInProgress	boolean		☐	
backupStatus_id	string		☐	
cronExpression	string	Cron Expression	☐	
filesToKeep	int32	Files to Keep	☐	
id	string	ID	☐	
isOn	boolean	Is On	☐	
location	string	Location	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

7.1.5 NotifiedUserSavedQuerySettings

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings`

Insert YouTrack API URL: `/admin/databaseBackup/settings`

Update YouTrack API URL: `/admin/databaseBackup/settings`

Delete YouTrack API URL: `/admin/databaseBackup/settings`

Field Selection Method: NotRequired

Base Path: `notifiedUsers[*].savedQueries[*]`

Select YouTrack API Operation: `get /admin/databaseBackup/settings`

Table Function Columns

The columns of the table function `NotifiedUserSavedQuerySettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archiveFormat	string	Archive Format	☐	
availableDiskSpace	int64	Available Disk Space	☐	
avatarUrl	string	Avatar (URL)	☐	
backupStatus_$type	string		☐	
backupStatus_backupCancelled	boolean		☐	
backupStatus_backupError_$type	string		☐	
backupStatus_backupError_date	int64		☐	
backupStatus_backupError_errorMessage	string		☐	
backupStatus_backupError_id	string		☐	
backupStatus_backupInProgress	boolean		☐	
backupStatus_id	string		☐	
banned	boolean	Banned	☐	
cronExpression	string	Cron Expression	☐	
email	string	Email	☐	
filesToKeep	int32	Files to Keep	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id_2	string		☐	
id	string	ID	☐	
isOn	boolean	Is On	☐	
jabberAccountName	string	Jabber Account Name	☐	
location	string	Location	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

7.1.6 NotifiedUserSettings

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings`

Insert YouTrack API URL: `/admin/databaseBackup/settings`

Update YouTrack API URL: `/admin/databaseBackup/settings`

Delete YouTrack API URL: `/admin/databaseBackup/settings`

Field Selection Method: NotRequired

Base Path: `notifiedUsers[*]`

Select YouTrack API Operation: `get /admin/databaseBackup/settings`

Table Function Columns

The columns of the table function `NotifiedUserSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
archiveFormat	string	Archive Format	☐	
availableDiskSpace	int64	Available Disk Space	☐	
avatarUrl	string	Avatar (URL)	☐	
backupStatus_$type	string		☐	
backupStatus_backupCancelled	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
backupStatus_backupError_$type	string		☐	
backupStatus_backupError_date	int64		☐	
backupStatus_backupError_errorMessage	string		☐	
backupStatus_backupError_id	string		☐	
backupStatus_backupInProgress	boolean		☐	
backupStatus_id	string		☐	
banned	boolean	Banned	☐	
cronExpression	string	Cron Expression	☐	
email	string	Email	☐	
filesToKeep	int32	Files to Keep	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isOn	boolean	Is On	☐	
jabberAccountName	string	Jabber Account Name	☐	
location	string	Location	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

7.1.7 NotifiedUserTagSettings

Catalog: YouTrack

Schema: Backups

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/databaseBackup/settings`

Insert YouTrack API URL: `/admin/databaseBackup/settings`

Update YouTrack API URL: `/admin/databaseBackup/settings`

Delete YouTrack API URL: `/admin/databaseBackup/settings`

Field Selection Method: NotRequired

Base Path: `notifiedUsers[*].tags[*]`

Select YouTrack API Operation: `get /admin/databaseBackup/settings`

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `NotifiedUserTagSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archiveFormat	string	Archive Format	☐	
availableDiskSpace	int64	Available Disk Space	☐	
avatarUrl	string	Avatar (URL)	☐	
backupStatus_$type	string		☐	
backupStatus_backupCancelled	boolean		☐	
backupStatus_backupError_$type	string		☐	
backupStatus_backupError_date	int64		☐	
backupStatus_backupError_errorMessage	string		☐	
backupStatus_backupError_id	string		☐	
backupStatus_backupInProgress	boolean		☐	
backupStatus_id	string		☐	
banned	boolean	Banned	☐	
cronExpression	string	Cron Expression	☐	
email	string	Email	☐	
filesToKeep	int32	Files to Keep	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isOn	boolean	Is On	☐	
jabberAccountName	string	Jabber Account Name	☐	
location	string	Location	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

8 Schema: CustomFields

8.1 Tables

8.1.1 CustomFieldAggregatedUserSavedQueriesByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*].savedQueries[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldAggregatedUserSavedQueriesByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldAggregatedUserSavedQueriesByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

8.1.2 CustomFieldAggregatedUsersByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldAggregatedUsersByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldAggregatedUsersByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

8.1.3 CustomFieldAggregatedUserTagsByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*].tags[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldAggregatedUserTagsByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldAggregatedUserTagsByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

8.1.4 CustomFieldBuildBundles

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/build`

Table Function Columns

The columns of the table function `CustomFieldBuildBundles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.5 CustomFieldBuildByBuildBundleId

Catalog: YouTrack

Schema: CustomFields

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/build/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldBuildByBuildBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldBuildByBuildBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.6 CustomFieldBuildByBuildBundleIdAndElementId

Catalog: YouTrack

Schema: CustomFields

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/build/{id}/values/{buildBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldBuildByBuildBundleIdAndElementId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
buildBundleElementId	string	☑		
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldBuildByBuildBundleIdAndElementId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
assembleDate	int64	Assembly Date	☐	
bundle_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.7 CustomFieldBuildValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/build`

Table Function Columns

The columns of the table function `CustomFieldBuildValues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
assembleDate	int64	Assembly Date	☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.8 CustomFieldBuildValuesByBuildBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/build/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldBuildValuesByBuildBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldBuildValuesByBuildBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
assembleDate	int64	Assembly Date	☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.9 CustomFieldBuildValuesByBuildBundleId1

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/build/{id}/values`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/build/{id}/values`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldBuildValuesByBuildBundleId1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldBuildValuesByBuildBundleId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
assembleDate	int64	Assembly Date	☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.10 CustomFieldEnumBundleByEnumFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/enum/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldEnumBundleByEnumFieldBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldEnumBundleByEnumFieldBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.11 CustomFieldEnumBundles

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/enum`

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `CustomFieldEnumBundles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.12 CustomFieldEnumBundleValuesByEnumFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/enum/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldEnumBundleValuesByEnumFieldBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `CustomFieldEnumBundleValuesByEnumFieldBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.13 CustomFieldEnumByEnumFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/enum/{id}/values`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldEnumByEnumFieldBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldEnumByEnumFieldBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.14 CustomFieldEnumByEnumFieldBundleIdAndElementId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/enum/{id}/values/{enumBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldEnumByEnumFieldBundleIdAndElementId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
enumBundleElementId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldEnumByEnumFieldBundleIdAndElementId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.15 CustomFieldEnumValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/enum`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/enum`

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `CustomFieldEnumValues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.16 CustomFieldIndividualUsers

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `individuals[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldIndividualUsers` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

8.1.17 CustomFieldIndividualUserSavedQueries

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Base Path: `individuals[*].savedQueries[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldIndividualUserSavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

8.1.18 CustomFieldIndividualUserSavedQueriesByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Base Path: `individuals[*].savedQueries[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldIndividualUserSavedQueriesByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldIndividualUserSavedQueriesByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

8.1.19 CustomFieldIndividualUsersByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `individuals[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldIndividualUsersByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `CustomFieldIndividualUsersByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

8.1.20 CustomFieldIndividualUserTags

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `individuals[*].tags[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldIndividualUserTags` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

8.1.21 CustomFieldIndividualUserTagsByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `individuals[*].tags[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldIndividualUserTagsByUserBundleId. A value must be provided at all times for

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldIndividualUserTagsByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

8.1.22 CustomFieldInstancesByCustomFieldPrototypeId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Field Selection Method: NotRequired

Base Path: `instances[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/customFields/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldInstancesByCustomFieldPrototypeId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldInstancesByCustomFieldPrototypeId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
aliases	string	Aliases	☐	
canBeEmpty	boolean	Nullable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
condition_$type	string		☐	
condition_id	string		☐	
emptyFieldText	string	Empty Field Text	☐	
field_$type	string		☐	
field_aliases	string		☐	
field_hasRunningJob	boolean		☐	
field_id	string		☐	
field_isAutoAttached	boolean		☐	
field_isDisplayedInIssueList	boolean		☐	
field_isUpdateable	boolean		☐	
field_localizedName	string		☐	
field_name	string		☐	
field_ordinal	int32		☐	
fieldDefaults_$type	string		☐	
fieldDefaults_canBeEmpty	boolean		☐	
fieldDefaults_emptyFieldText	string		☐	
fieldDefaults_id	string		☐	
fieldDefaults_isPublic	boolean		☐	
fieldDefaults_parent_$type	string		☐	
fieldDefaults_parent_aliases	string		☐	
fieldDefaults_parent_hasRunningJob	boolean		☐	
fieldDefaults_parent_id	string		☐	
fieldDefaults_parent_isAutoAttached	boolean		☐	
fieldDefaults_parent_isDisplayedInIssueList	boolean		☐	
fieldDefaults_parent_isUpdateable	boolean		☐	
fieldDefaults_parent_localizedName	string		☐	
fieldDefaults_parent_name	string		☐	
fieldDefaults_parent_ordinal	int32		☐	
fieldType_$type	string		☐	
fieldType_id	string		☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id	string	ID	☐	
isAutoAttached	boolean	Is Auto-attached	☐	
isDisplayedInIssueList	boolean	Is Displayed in Issue List	☐	
isPublic	boolean	Is Public	☐	
isUpdateable	boolean	Is Updateable	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	

8.1.23 CustomFieldOwnedFieldByOwnedFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/ownedField/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldOwnedFieldByOwnedFieldBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldOwnedFieldByOwnedFieldBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.24 CustomFieldOwnedFieldByOwnedFieldBundleIdAndElementId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/ownedField/{id}/values/{ownedBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldOwnedFieldByOwnedFieldBundleIdAndElementId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
ownedBundleElementId	string	☑		

Table Function Columns

The columns of the table function `CustomFieldOwnedFieldByOwnedFieldBundleIdAndElementId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_profiles_id	string		☐	
owner_ringId	string		☐	

8.1.25 CustomFieldOwnedFieldByValueId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}/values`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/ownedField/{id}/values`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldOwnedFieldByValueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `CustomFieldOwnedFieldByValueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	

8.1.26 CustomFieldOwnedFields

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/ownedField`

Table Function Columns

The columns of the table function `CustomFieldOwnedFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.27 CustomFieldOwnedFieldValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/ownedField`

Table Function Columns

The columns of the table function `CustomFieldOwnedFieldValues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	

8.1.28 CustomFieldOwnedFieldValuesByOwnedFieldBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/ownedField/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/ownedField/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldOwnedFieldValuesByOwnedFieldBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldOwnedFieldValuesByOwnedFieldBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	

8.1.29 CustomFields

Catalog: YouTrack

Schema: CustomFields

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields`

Update YouTrack API URL: `/admin/customFieldSettings/customFields`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/customFieldSettings/customFields`

Table Function Columns

The columns of the table function `CustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
aliases	string	Aliases	☐	
fieldDefaults_$type	string		☐	
fieldDefaults_canBeEmpty	boolean		☐	
fieldDefaults_emptyFieldText	string		☐	
fieldDefaults_id	string		☐	
fieldDefaults_isPublic	boolean		☐	
fieldDefaults_parent_$type	string		☐	
fieldDefaults_parent_aliases	string		☐	
fieldDefaults_parent_hasRunningJob	boolean		☐	
fieldDefaults_parent_id	string		☐	
fieldDefaults_parent_isAutoAttached	boolean		☐	
fieldDefaults_parent_isDisplayedInIssueList	boolean		☐	
fieldDefaults_parent_isUpdateable	boolean		☐	
fieldDefaults_parent_localizedName	string		☐	
fieldDefaults_parent_name	string		☐	
fieldDefaults_parent_ordinal	int32		☐	
fieldType_$type	string		☐	
fieldType_id	string		☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
isAutoAttached	boolean	Is Auto-attached	☐	
isDisplayedInIssueList	boolean	Is Displayed in Issue List	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.30 CustomFieldsByCustomFieldPrototypeId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/customFields/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldsByCustomFieldPrototypeId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldsByCustomFieldPrototypeId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
aliases	string	Aliases	☐	
fieldDefaults_$type	string		☐	
fieldDefaults_canBeEmpty	boolean		☐	
fieldDefaults_emptyFieldText	string		☐	
fieldDefaults_id	string		☐	
fieldDefaults_isPublic	boolean		☐	
fieldDefaults_parent_$type	string		☐	
fieldDefaults_parent_aliases	string		☐	
fieldDefaults_parent_hasRunningJob	boolean		☐	
fieldDefaults_parent_id	string		☐	
fieldDefaults_parent_isAutoAttached	boolean		☐	
fieldDefaults_parent_isDisplayedInIssueList	boolean		☐	
fieldDefaults_parent_isUpdateable	boolean		☐	
fieldDefaults_parent_localizedName	string		☐	
fieldDefaults_parent_name	string		☐	
fieldDefaults_parent_ordinal	int32		☐	
fieldType_$type	string		☐	
fieldType_id	string		☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
isAutoAttached	boolean	Is Auto-attached	☐	
isDisplayedInIssueList	boolean	Is Displayed in Issue List	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.31 CustomFieldsByCustomFieldPrototypeId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/fieldDefaults`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Insert YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/fieldDefaults`

Update YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/fieldDefaults`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/fieldDefaults`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/customFields/{id}/fieldDefaults`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldsByCustomFieldPrototypeId2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldsByCustomFieldPrototypeId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
canBeEmpty	boolean	Nullable	☐	
emptyFieldText	string	Empty Field Text	☐	
id	string	ID	☐	
isPublic	boolean	Is Public	☐	
parent_$type	string		☐	
parent_aliases	string		☐	
parent_fieldDefaults_$type	string		☐	
parent_fieldDefaults_canBeEmpty	boolean		☐	
parent_fieldDefaults_emptyFieldText	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_fieldDefaults_id	string		☐	
parent_fieldDefaults_isPublic	boolean		☐	
parent_fieldType_$type	string		☐	
parent_fieldType_id	string		☐	
parent_hasRunningJob	boolean		☐	
parent_id	string		☐	
parent_isAutoAttached	boolean		☐	
parent_isDisplayedInIssueList	boolean		☐	
parent_isUpdateable	boolean		☐	
parent_localizedName	string		☐	
parent_name	string		☐	
parent_ordinal	int32		☐	

8.1.32 CustomFieldsByCustomFieldPrototypeId3

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/instances`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/instances`

Update YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/instances`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields/{id}/instances`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/customFields/{id}/instances`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldsByCustomFieldPrototypeId3. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldsByCustomFieldPrototypeId3` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
canBeEmpty	boolean	Nullable	☐	
condition_$type	string		☐	
condition_id	string		☐	
condition_parent_$type	string		☐	
condition_parent_canBeEmpty	boolean		☐	
condition_parent_emptyFieldText	string		☐	
condition_parent_hasRunningJob	boolean		☐	
condition_parent_id	string		☐	
condition_parent_isPublic	boolean		☐	
condition_parent_ordinal	int32		☐	
emptyFieldText	string	Empty Field Text	☐	
field_$type	string		☐	
field_aliases	string		☐	
field_fieldDefaults_$type	string		☐	
field_fieldDefaults_canBeEmpty	boolean		☐	
field_fieldDefaults_emptyFieldText	string		☐	
field_fieldDefaults_id	string		☐	
field_fieldDefaults_isPublic	boolean		☐	
field_fieldType_$type	string		☐	
field_fieldType_id	string		☐	
field_hasRunningJob	boolean		☐	
field_id	string		☐	
field_isAutoAttached	boolean		☐	
field_isDisplayedInIssueList	boolean		☐	
field_isUpdateable	boolean		☐	
field_localizedName	string		☐	
field_name	string		☐	
field_ordinal	int32		☐	
hasRunningJob	boolean	Has Running Job	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	string	ID	☐	
isPublic	boolean	Is Public	☐	
ordinal	int32	Ordinal	☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_template	boolean		☐	

8.1.33 CustomFieldStateBundleById

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/state/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldStateBundleById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldStateBundleById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isUpdateable	boolean	Is Updateable	☐	

8.1.34 CustomFieldStateBundles

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/state`

Table Function Columns

The columns of the table function `CustomFieldStateBundles` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.35 CustomFieldStateBundleValues2ByStateBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/state/{id}/values`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldStateBundleValues2ByStateBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldStateBundleValues2ByStateBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
isResolved	boolean	Is Resolved	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
ordinal	int32	Ordinal	☐	

8.1.36 CustomFieldStateBundleValuesByStateBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/state/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldStateBundleValuesByStateBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldStateBundleValuesByStateBundleId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isResolved	boolean	Is Resolved	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.37 CustomFieldStateByStateBundleIdAndElementId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/state/{id}/values/{stateBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldStateByStateBundleIdAndElementId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
stateBundleElementId	string	☑		

Table Function Columns

The columns of the table function `CustomFieldStateByStateBundleIdAndElementId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
isResolved	boolean	Is Resolved	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	

8.1.38 CustomFieldStateValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/state`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/state`

Table Function Columns

The columns of the table function `CustomFieldStateValues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isResolved	boolean	Is Resolved	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	

8.1.39 CustomFieldUserBundles

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `groups[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUserBundles` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

8.1.40 CustomFieldUserBundleUsers

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUserBundleUsers` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	

8.1.41 CustomFieldUserBundleUserSavedQueries

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*].savedQueries[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUserBundleUserSavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	

8.1.42 CustomFieldUserBundleUserTags

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Base Path: `aggregatedUsers[*].tags[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUserBundleUserTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	

8.1.43 CustomFieldUserByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUserByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.44 CustomFieldUserByUserBundleId1

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserByUserBundleId1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUserByUserBundleId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.45 CustomFieldUserByUserBundleId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserByUserBundleId2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUserByUserBundleId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.46 CustomFieldUserGroupsByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}`

Field Selection Method: NotRequired

Base Path: `groups[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserGroupsByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUserGroupsByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id_1	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

8.1.47 CustomFieldUserGroupsByUserBundleId1

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/groups`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserGroupsByUserBundleId1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUserGroupsByUserBundleId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id	string	ID	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	
teamForProject_createdBy_$type	string		☐	
teamForProject_createdBy_avatarUrl	string		☐	
teamForProject_createdBy_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
teamForProject_createdBy_email	string		☐	
teamForProject_createdBy_fullName	string		☐	
teamForProject_createdBy_guest	boolean		☐	
teamForProject_createdBy_id	string		☐	
teamForProject_createdBy_jabberAccountName	string		☐	
teamForProject_createdBy_login	string		☐	
teamForProject_createdBy_online	boolean		☐	
teamForProject_createdBy_ringId	string		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_leader_$type	string		☐	
teamForProject_leader_avatarUrl	string		☐	
teamForProject_leader_banned	boolean		☐	
teamForProject_leader_email	string		☐	
teamForProject_leader_fullName	string		☐	
teamForProject_leader_guest	boolean		☐	
teamForProject_leader_id	string		☐	
teamForProject_leader_jabberAccountName	string		☐	
teamForProject_leader_login	string		☐	
teamForProject_leader_online	boolean		☐	
teamForProject_leader_ringId	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_team_$type	string		☐	
teamForProject_team_allUsersGroup	boolean		☐	
teamForProject_team_icon	string		☐	
teamForProject_team_id	string		☐	
teamForProject_team_name	string		☐	
teamForProject_team_ringId	string		☐	
teamForProject_team_usersCount	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

8.1.48 CustomFieldUsers

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user`

Table Function Columns

The columns of the table function `CustomFieldUsers` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.49 CustomFieldUsersByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.50 CustomFieldUsersByUserBundleId1

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: NotRequired

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Base Path: `savedQueries[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.51 CustomFieldUsersByUserBundleId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

8.1.52 CustomFieldUsersByUserBundleId3

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId3. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId3` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

8.1.53 CustomFieldUsersByUserBundleId4

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId4. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId4` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

8.1.54 CustomFieldUsersByUserBundleId5

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId5. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
userId	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId5` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
w ikifiedDescription	string	Wikified Description	☐	

8.1.55 CustomFieldUsersByUserBundleId6

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId6. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
userId	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId6` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	
ow ner_email	string		☐	
ow ner_fullName	string		☐	
ow ner_guest	boolean		☐	
ow ner_id	string		☐	
ow ner_jabberAccountName	string		☐	
ow ner_login	string		☐	
ow ner_online	boolean		☐	
ow ner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.56 CustomFieldUsersByUserBundleId7

Catalog: YouTrack

Schema: CustomFields

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId7. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
userId	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId7` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
wikifiedDescription	string	Wikified Description	☐	

8.1.57 CustomFieldUsersByUserBundleId8

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId8. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
userId	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId8` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	
ow ner_email	string		☐	
ow ner_fullName	string		☐	
ow ner_guest	boolean		☐	
ow ner_id	string		☐	
ow ner_jabberAccountName	string		☐	
ow ner_login	string		☐	
ow ner_online	boolean		☐	
ow ner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.58 CustomFieldUsersByUserBundleId9

Catalog: YouTrack

Schema: CustomFields

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals/{userId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleId9. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
userId	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleId9` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

8.1.59 CustomFieldUsersByUserBundleIdAndGroupId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/groups/{userGroupId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserBundleIdAndGroupId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
userGroupId	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserBundleIdAndGroupId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
allUsersGroup	boolean	All Users Group	☐	
icon	string	Icon	☐	
id	string	ID	☐	
name	string	Name	☐	
ringId	string	Ring ID	☐	
teamForProject_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
teamForProject_createdBy_$type	string		☐	
teamForProject_createdBy_avatarUrl	string		☐	
teamForProject_createdBy_banned	boolean		☐	
teamForProject_createdBy_email	string		☐	
teamForProject_createdBy_fullName	string		☐	
teamForProject_createdBy_guest	boolean		☐	
teamForProject_createdBy_id	string		☐	
teamForProject_createdBy_jabberAccountName	string		☐	
teamForProject_createdBy_login	string		☐	
teamForProject_createdBy_online	boolean		☐	
teamForProject_createdBy_ringId	string		☐	
teamForProject_description	string		☐	
teamForProject_fromEmail	string		☐	
teamForProject_iconUrl	string		☐	
teamForProject_leader_$type	string		☐	
teamForProject_leader_avatarUrl	string		☐	
teamForProject_leader_banned	boolean		☐	
teamForProject_leader_email	string		☐	
teamForProject_leader_fullName	string		☐	
teamForProject_leader_guest	boolean		☐	
teamForProject_leader_id	string		☐	
teamForProject_leader_jabberAccountName	string		☐	
teamForProject_leader_login	string		☐	
teamForProject_leader_online	boolean		☐	
teamForProject_leader_ringId	string		☐	
teamForProject_replyToEmail	string		☐	
teamForProject_shortName	string		☐	
teamForProject_startingNumber	int64		☐	
teamForProject_team_$type	string		☐	
teamForProject_team_allUsersGroup	boolean		☐	
teamForProject_team_icon	string		☐	
teamForProject_team_id	string		☐	
teamForProject_team_name	string		☐	
teamForProject_team_ringId	string		☐	
teamForProject_team_usersCount	int64		☐	
teamForProject_template	boolean		☐	
usersCount	int64	Users Count	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

8.1.60 CustomFieldUsersByUserId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUsersByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUsersByUserId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.61 CustomFieldUserTagsByUserBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/aggregatedUsers`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserTagsByUserBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUserTagsByUserBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	
ow ner_email	string		☐	
ow ner_fullName	string		☐	
ow ner_guest	boolean		☐	
ow ner_id	string		☐	
ow ner_jabberAccountName	string		☐	
ow ner_login	string		☐	
ow ner_online	boolean		☐	
ow ner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.62 CustomFieldUserTagsByUserBundleId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/user/{id}/individuals`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/user/{id}/individuals`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldUserTagsByUserBundleId2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldUserTagsByUserBundleId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	
ow ner_email	string		☐	
ow ner_fullName	string		☐	
ow ner_guest	boolean		☐	
ow ner_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

8.1.63 CustomFieldVersionByProjectVersionBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/version/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldVersionByProjectVersionBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `CustomFieldVersionByProjectVersionBundleId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.64 CustomFieldVersions

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/version`

Table Function Columns

The columns of the table function `CustomFieldVersions` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	

8.1.65 CustomFieldVersionValues

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/version`

Table Function Columns

The columns of the table function `CustomFieldVersionValues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
released	boolean	Released	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
releaseDate	int64	Release Date	☐	

8.1.66 CustomFieldVersionValuesByProjectVersionBundleId

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}`

Field Selection Method: NotRequired

Base Path: `values[*]`

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/version/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldVersionValuesByProjectVersionBundleId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldVersionValuesByProjectVersionBundleId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
archived	boolean	Archived	☐	
bundle_$type_1	string		☐	
bundle_$type	string		☐	
bundle_id_1	string		☐	
bundle_id	string		☐	
bundle_isUpdateable_1	boolean		☐	
bundle_isUpdateable	boolean		☐	
color_$type_1	string		☐	
color_$type	string		☐	
color_background_1	string		☐	
color_background	string		☐	
color_foreground_1	string		☐	
color_foreground	string		☐	
color_id_1	string		☐	
color_id	string		☐	
description_1	string		☐	
description	string	Description	☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
isUpdateable	boolean	Is Updateable	☐	
name_1	string		☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
released	boolean	Released	☐	
releaseDate	int64	Release Date	☐	

8.1.67 CustomFieldVersionValuesByProjectVersionBundleId2

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/version/{id}/values`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldVersionValuesByProjectVersionBundleId2. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldVersionValuesByProjectVersionBundleId2` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
archived	boolean	Archived	☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	
released	boolean	Released	☐	
releaseDate	int64	Release Date	☐	

8.1.68 CustomFieldVersionValuesByProjectVersionBundleId3

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Insert YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Update YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Delete YouTrack API URL: `/admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Field Selection Method: NotRequired

Select YouTrack API Operation:
`get /admin/customFieldSettings/bundles/version/{id}/values/{versionBundleElementId}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldVersionValuesByProjectVersionBundleId3. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		
versionBundleElementId	string	☑		

Table Function Columns

The columns of the table function `CustomFieldVersionValuesByProjectVersionBundleId3` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
archived	boolean	Archived	☐	
bundle_$type	string		☐	
bundle_id	string		☐	
bundle_isUpdateable	boolean		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
description	string	Description	☐	
hasRunningJob	boolean	Has Running Job	☐	
id	string	ID	☐	
name	string	Name	☐	
ordinal	int32	Ordinal	☐	
released	boolean	Released	☐	
releaseDate	int64	Release Date	☐	

8.1.69 InstanceCustomFields

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/customFields`

Insert YouTrack API URL: `/admin/customFieldSettings/customFields`

Update YouTrack API URL: `/admin/customFieldSettings/customFields`

Delete YouTrack API URL: `/admin/customFieldSettings/customFields`

Field Selection Method: NotRequired

Base Path: `instances[*]`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation: `get /admin/customFieldSettings/customFields`

Table Function Columns

The columns of the table function `InstanceCustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
aliases	string	Aliases	☐	
canBeEmpty	boolean	Nullable	☐	
condition_$type	string		☐	
condition_id	string		☐	
emptyFieldText	string	Empty Field Text	☐	
field_$type	string		☐	
field_aliases	string		☐	
field_hasRunningJob	boolean		☐	
field_id	string		☐	
field_isAutoAttached	boolean		☐	
field_isDisplayedInIssueList	boolean		☐	
field_isUpdateable	boolean		☐	
field_localizedName	string		☐	
field_name	string		☐	
field_ordinal	int32		☐	
fieldDefaults_$type	string		☐	
fieldDefaults_canBeEmpty	boolean		☐	
fieldDefaults_emptyFieldText	string		☐	
fieldDefaults_id	string		☐	
fieldDefaults_isPublic	boolean		☐	
fieldDefaults_parent_$type	string		☐	
fieldDefaults_parent_aliases	string		☐	
fieldDefaults_parent_hasRunningJob	boolean		☐	
fieldDefaults_parent_id	string		☐	
fieldDefaults_parent_isAutoAttached	boolean		☐	
fieldDefaults_parent_isDisplayedInIssueList	boolean		☐	
fieldDefaults_parent_isUpdateable	boolean		☐	
fieldDefaults_parent_localizedName	string		☐	
fieldDefaults_parent_name	string		☐	
fieldDefaults_parent_ordinal	int32		☐	
fieldType_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
fieldType_id	string		☐	
hasRunningJob_1	boolean		☐	
hasRunningJob	boolean	Has Running Job	☐	
id_1	string		☐	
id	string	ID	☐	
isAutoAttached	boolean	Is Auto-attached	☐	
isDisplayedInIssueList	boolean	Is Displayed in Issue List	☐	
isPublic	boolean	Is Public	☐	
isUpdateable	boolean	Is Updateable	☐	
localizedName	string	Localized Name	☐	
name	string	Name	☐	
ordinal_1	int32		☐	
ordinal	int32	Ordinal	☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	

8.1.70 Types

Catalog: YouTrack

Schema: CustomFields

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/admin/customFieldSettings/types`

Insert YouTrack API URL: `/admin/customFieldSettings/types`

Update YouTrack API URL: `/admin/customFieldSettings/types`

Delete YouTrack API URL: `/admin/customFieldSettings/types`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /admin/customFieldSettings/types`

Table Function Columns

The columns of the table function `Types` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	

9 Schema: Issues

9.1 Tables

9.1.1 AttachmentById

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `attachments[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function AttachmentById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `AttachmentById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
comment_$type	string		☐	
comment_created	int64		☐	
comment_deleted	boolean		☐	
comment_id	string		☐	
comment_text	string		☐	
comment_textPreview	string		☐	
comment_updated	int64		☐	
comment_usesMarkdown	boolean		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.2 Attachments

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `attachments[*]`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function Attachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `Attachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
comment_$type	string		☐	
comment_created	int64		☐	
comment_deleted	boolean		☐	
comment_id	string		☐	
comment_text	string		☐	
comment_textPreview	string		☐	
comment_updated	int64		☐	
comment_usesMarkdow n	boolean		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOw ner_$type	string		☐	
draftOw ner_avatarUrl	string		☐	
draftOw ner_banned	boolean		☐	
draftOw ner_email	string		☐	
draftOw ner_fullName	string		☐	
draftOw ner_guest	boolean		☐	
draftOw ner_id	string		☐	
draftOw ner_jabberAccountName	string		☐	
draftOw ner_login	string		☐	
draftOw ner_online	boolean		☐	
draftOw ner_profiles_$type	string		☐	
draftOw ner_profiles_id	string		☐	
draftOw ner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.3 CommentAttachments

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CommentAttachments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `CommentAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountNam e	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.4 CommentAttachmentsByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `comments[*].attachments[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CommentAttachmentsByIssueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `CommentAttachmentsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created_2	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updated_1	int64		☐	
updated_2	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.5 Comments

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `comments[*]`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function Comments. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `Comments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountNam e	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

9.1.6 CommentsByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `comments[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CommentsByIssueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CommentsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
author_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_ringId	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_resolved	int64		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_usesMarkdown	boolean		☐	
issue_votes	int32		☐	
issue_wikifiedDescription	string		☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type_1	string		☐	
visibility_$type	string		☐	
visibility_id_1	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.7 CustomFields

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `customFields[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFields. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
				one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `CustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
projectCustomField_$type	string		☐	
projectCustomField_canBeEmpty	boolean		☐	
projectCustomField_emptyFieldText	string		☐	
projectCustomField_hasRunningJob	boolean		☐	
projectCustomField_id	string		☐	
projectCustomField_isPublic	boolean		☐	
projectCustomField_ordinal	int32		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

9.1.8 CustomFieldsByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `customFields[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function CustomFieldsByIssueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `CustomFieldsByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
projectCustomField_$type	string		☐	
projectCustomField_canBeEmpty	boolean		☐	
projectCustomField_emptyFieldText	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
projectCustomField_hasRunningJob	boolean		☐	
projectCustomField_id	string		☐	
projectCustomField_isPublic	boolean		☐	
projectCustomField_ordinal	int32		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.9 IssueById

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.10 IssueLinksByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}/links`

Insert YouTrack API URL: `/issues/{id}/links`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Update YouTrack API URL: `/issues/{id}/links`

Delete YouTrack API URL: `/issues/{id}/links`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issues/{id}/links`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueLinksByIssueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueLinksByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
direction	string	Direction	☐	
id	string	ID	☐	
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

9.1.11 Issues

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function Issues. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `Issues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.12 IssueTags: YouTrack Issue Tags

Catalog: YouTrack

Schema: Issues

Label: Issue Tags

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTags. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `IssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_$type_1	string		☐	
parent_$type	string		☐	
parent_commentsCount	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.13 LinkById

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `links[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function LinkById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `LinkById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.14 LinkIssues

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `links[*].issues[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function LinkIssues. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `LinkIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_$type_1	string		☐	
parent_$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
w ikifiedDescription	string	Wikified Description	☐	

9.1.15 LinkIssuesByIssueId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `links[*].issues[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function LinkIssuesByIssueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `LinkIssuesByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_2	string		☐	
$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_$type_1	string		☐	
parent_$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.16 Links

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `links[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function Links. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
				times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

Table Function Columns

The columns of the table function `Links` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOw ner_$type	string		☐	
draftOw ner_avatarUrl	string		☐	
draftOw ner_banned	boolean		☐	
draftOw ner_email	string		☐	
draftOw ner_fullName	string		☐	
draftOw ner_guest	boolean		☐	
draftOw ner_id	string		☐	
draftOw ner_jabberAccountName	string		☐	
draftOw ner_login	string		☐	
draftOw ner_online	boolean		☐	
draftOw ner_profiles_$type	string		☐	
draftOw ner_profiles_id	string		☐	
draftOw ner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject	int64	Number in Project	☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

9.1.17 LinkTrimmedIssues

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `links[*].trimmedIssues[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function LinkTrimmedIssues. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `LinkTrimmedIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_$type_1	string		☐	
parent_$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_wikifiedDescription	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.18 LinkTrimmedIssuesByIssueId

Catalog: YouTrack

Schema: Issues

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `links[*].trimmedIssues[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function LinkTrimmedIssuesByIssueId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `LinkTrimmedIssuesByIssueId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
linkType_$type	string		☐	
linkType_aggregation	boolean		☐	
linkType_directed	boolean		☐	
linkType_id	string		☐	
linkType_localizedName	string		☐	
linkType_localizedSourceToTarget	string		☐	
linkType_localizedTargetToSource	string		☐	
linkType_name	string		☐	
linkType_readOnly	boolean		☐	
linkType_sourceToTarget	string		☐	
linkType_targetToSource	string		☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
parent_$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.19 TagById

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation: `get /issues/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `TagById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

9.1.20 TagIssuesByTagId

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues/{id}`

Insert YouTrack API URL: `/issues/{id}`

Update YouTrack API URL: `/issues/{id}`

Delete YouTrack API URL: `/issues/{id}`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /issues/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `TagIssuesByTagId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount_1	int32		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description_1	string		☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable_1	string		☐	
idReadable	string	Readable ID	☐	
isDraft_1	boolean		☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject_1	int64		☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_$type_1	string		☐	
parent_$type	string		☐	
parent_commentsCount	int32		☐	
parent_created	int64		☐	
parent_description	string		☐	
parent_direction	string		☐	
parent_id_1	string		☐	
parent_id	string		☐	
parent_idReadable	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_isDraft	boolean		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
parent_numberInProject	int64		☐	
parent_resolved	int64		☐	
parent_summary	string		☐	
parent_updated	int64		☐	
parent_usesMarkdown	boolean		☐	
parent_votes	int32		☐	
parent_wikifiedDescription	string		☐	
project_$type	string		☐	
project_archived	boolean		☐	
project_commentsCount	int32		☐	
project_created	int64		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description_1	string		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_idReadable	string		☐	
project_isDraft	boolean		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_numberInProject	int64		☐	
project_replyToEmail	string		☐	
project_resolved	int64		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_summary	string		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
project_updated	int64		☐	
project_usesMarkdown	boolean		☐	
project_votes	int32		☐	
project_wikifiedDescription	string		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved_1	int64		☐	
resolved	int64	Resolved	☐	
subtasks_$type_1	string		☐	
subtasks_$type	string		☐	
subtasks_commentsCount	int32		☐	
subtasks_created	int64		☐	
subtasks_description	string		☐	
subtasks_direction	string		☐	
subtasks_id_1	string		☐	
subtasks_id	string		☐	
subtasks_idReadable	string		☐	
subtasks_isDraft	boolean		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
subtasks_numberInProject	int64		☐	
subtasks_resolved	int64		☐	
subtasks_summary	string		☐	
subtasks_updated	int64		☐	
subtasks_usesMarkdown	boolean		☐	
subtasks_votes	int32		☐	
subtasks_wikifiedDescription	string		☐	
summary_1	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes_1	int32		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription_1	string		☐	
wikifiedDescription	string	Wikified Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

9.1.21 Tags

Catalog: YouTrack

Schema: Issues

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/issues`

Insert YouTrack API URL: `/issues`

Update YouTrack API URL: `/issues`

Delete YouTrack API URL: `/issues`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation: `get /issues`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function Tags. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
customFields	string	☐		The name of the custom field to show in the response. When you use this parameter and request the custom field data in the request URL, the response only shows the requested custom fields instead of all of them. To show more than one custom field, use this parameter several times. See Sample 2 for reference.
query	string	☐		Issues search query. Read more about search syntax here: <a href="https://www.jetbrains.com/help/youtrack/incloud/?Search-

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
				and-Command-Attributes">Search Query Reference

Table Function Columns

The columns of the table function `Tags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_profiles_$type	string		☐	
draftOwner_profiles_id	string		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
parent_linkType_$type	string		☐	
parent_linkType_aggregation	boolean		☐	
parent_linkType_directed	boolean		☐	
parent_linkType_id	string		☐	
parent_linkType_localizedName	string		☐	
parent_linkType_localizedSourceToTarget	string		☐	
parent_linkType_localizedTargetToSource	string		☐	
parent_linkType_name	string		☐	
parent_linkType_readOnly	boolean		☐	
parent_linkType_sourceToTarget	string		☐	
parent_linkType_targetToSource	string		☐	
project_archived	boolean		☐	
project_createdBy_$type	string		☐	
project_createdBy_avatarUrl	string		☐	
project_createdBy_banned	boolean		☐	
project_createdBy_email	string		☐	
project_createdBy_fullName	string		☐	
project_createdBy_guest	boolean		☐	
project_createdBy_id	string		☐	
project_createdBy_jabberAccountName	string		☐	
project_createdBy_login	string		☐	
project_createdBy_online	boolean		☐	
project_createdBy_ringId	string		☐	
project_description	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_leader_$type	string		☐	
project_leader_avatarUrl	string		☐	
project_leader_banned	boolean		☐	
project_leader_email	string		☐	
project_leader_fullName	string		☐	
project_leader_guest	boolean		☐	
project_leader_id	string		☐	
project_leader_jabberAccountName	string		☐	
project_leader_login	string		☐	
project_leader_online	boolean		☐	
project_leader_ringId	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_team_$type	string		☐	
project_team_allUsersGroup	boolean		☐	
project_team_icon	string		☐	
project_team_id	string		☐	
project_team_name	string		☐	
project_team_ringId	string		☐	
project_team_usersCount	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_profiles_$type	string		☐	
reporter_profiles_id	string		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_id	string		☐	
subtasks_linkType_$type	string		☐	
subtasks_linkType_aggregation	boolean		☐	
subtasks_linkType_directed	boolean		☐	
subtasks_linkType_id	string		☐	
subtasks_linkType_localizedName	string		☐	
subtasks_linkType_localizedSourceToTarget	string		☐	
subtasks_linkType_localizedTargetToSource	string		☐	
subtasks_linkType_name	string		☐	
subtasks_linkType_readOnly	boolean		☐	
subtasks_linkType_sourceToTarget	string		☐	
subtasks_linkType_targetToSource	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_profiles_$type	string		☐	
updater_profiles_id	string		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

10 Schema: Native

10.1 Tables

10.1.1 NATIVEPLATFORMSCALARREQUESTS: YouTrack Native Platform Scalar Requests

Direct access to native API.

Catalog: YouTrack

Schema: Native

Alias: `npt`

Label: Native Platform Scalar Requests

Documentation:

The NativePlatformScalarRequests table provides direct access to the native API protocol over an established connection to the YouTrack API server. It will contain a new row for every row inserted with a native API request in PAYLOAD_TEXT with the results of unaltered forwarding of the payload to the YouTrack API server.

Retrieve: true

Insert: true

Update: false

Delete: false

View Columns

The columns of the view `NATIVEPLATFORMSCALARREQUESTS` are shown below. Each column has an SQL data type. A new non-null value must be provided for every required column at all times during insert.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
BLOB_PREFERRED	boolean	BLOB Preferred	☑	Indicator whether a BLOB result is preferred over text.
BOL_RESPONSE_CACHE_MAX_AGE_SEC	int32	Response Cache Maximum Age (sec)	☐	Maximum age in seconds of Bridge Online response cache entries to be used.
CONTENT_TYPE	string(240)	Content Type	☐	
DATE_ENDED	datetime	End Date	☑	
DATE_STARTED	datetime	Start Date	☑	
DRY_RUN	boolean	Run without Actions	☑	
DURATION_MS	int32	Duration (ms)	☑	
ERROR_MESSAGE_CODE	string(30)	Error Message Code	☐	
ERROR_MESSAGE_TEXT	string(32000)	Error Message Text	☐	
FAIL_ON_ERROR	boolean	Fail on Error	☑	Whether to raise an exception when processing the native request triggered an error from the provider.
HTTP_DISK_CACHE_MAX_AGE_SEC	int32	HTTP Disk Cache Maximum Age (sec)	☐	Maximum age in seconds of HTTP disk cache entries to be used.
HTTP_DISK_CACHE_SAVE	boolean	Save HTTP Disk Cache	☐	Whether results can be stored in HTTP disk cache.
HTTP_DISK_CACHE_USE	boolean	Use HTTP Disk Cache	☐	Whether results can be fetched from HTTP disk cache.
HTTP_MEMORY_CACHE_MAX_AGE_SEC	int32	HTTP Memory Cache Maximum Age (sec)	☐	Maximum age in seconds of HTTP memory cache entries to be used.
HTTP_MEMORY_CACHE_SAVE	boolean	Save HTTP Memory Cache	☐	Whether results can be stored in HTTP memory cache.
HTTP_MEMORY_CACHE_USE	boolean	Use HTTP Memory Cache	☐	Whether results can be fetched from HTTP memory cache.
HTTP_METHOD	string(30)	HTTP Method	☐	
HTTP_STATUS_CODE	int16	HTTP Status Code	☐	
ORIG_SYSTEM_GROUP	string(4000)	Original System Group	☐	
ORIG_SYSTEM_REFERENCE	string(4000)	Original System Reference	☐	
PAYLOAD_TEXT	string	Payload	☐	
RESULT_BLOB	byte[]	Result BLOB	☐	
RESULT_DATE_TIME_UTC	datetime		☐	
RESULT_NUMBER	decimal		☐	
RESULT_TEXT	string	Result Text	☐	
SUCCESSFUL	boolean	Succesful	☑	
TIMEOUT_SEC	int32	Timeout (sec)	☐	Timeout in seconds.
TRANSACTION_ID	int32	Transaction ID	☑	Incrementing ID of the transaction.
URL	string(4000)	URL	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

11 Schema: SavedQueries

11.1 Tables

11.1.1 IssueAttachmentsBySavedQueryId

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueAttachmentsBySavedQueryId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueAttachmentsBySavedQueryId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.2 IssueById

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.3 IssueCommentsBySavedQueryId

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueCommentsBySavedQueryId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueCommentsBySavedQueryId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.4 IssueCustomFieldsBySavedQueryId

Catalog: YouTrack

Schema: SavedQueries

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueCustomFieldsBySavedQueryId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueCustomFieldsBySavedQueryId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.5 Issues

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `Issues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.6 IssuesAttachments

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesAttachments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.7 IssuesComments

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesComments` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.8 IssuesCustomFields

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: NotRequired

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesCustomFields` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.9 IssuesLinks

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesLinks` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.10 IssuesLinksById

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssuesLinksById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssuesLinksById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.11 IssuesTags

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `IssuesTags` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type_1	string		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.12 IssueTagsBySavedQueryId

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function IssueTagsBySavedQueryId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `IssueTagsBySavedQueryId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_$type_1	string		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

11.1.13 SavedQueries: YouTrack Saved Queries

Catalog: YouTrack

Schema: SavedQueries

Label: Saved Queries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries`

Insert YouTrack API URL: `/savedQueries`

Update YouTrack API URL: `/savedQueries`

Delete YouTrack API URL: `/savedQueries`

Field Selection Method: NotRequired

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation: `get /savedQueries`

Table Function Columns

The columns of the table function `SavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
query	string	Query	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

11.1.14 SavedQueryById

Catalog: YouTrack

Schema: SavedQueries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/savedQueries/{id}`

Insert YouTrack API URL: `/savedQueries/{id}`

Update YouTrack API URL: `/savedQueries/{id}`

Delete YouTrack API URL: `/savedQueries/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /savedQueries/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SavedQueryById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SavedQueryById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
query	string	Query	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

12 Schema: Users

12.1 Tables

12.1.1 IssueTags: YouTrack Issue Tags

Catalog: YouTrack

Schema: Users

Label: Issue Tags

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `IssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.2 Me

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `Me` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

12.1.3 MyIssueTags

Catalog: YouTrack

Schema: Users

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `MyIssueTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.4 MySavedQueries

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `MySavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.5 MySavedQueriessues

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation: `get /users/me`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `MySavedQueriessues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
votes	int32	Votes	☐	
w ikifiedDescription	string	Wikified Description	☐	

12.1.6 MyTags

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/me`

Insert YouTrack API URL: `/users/me`

Update YouTrack API URL: `/users/me`

Delete YouTrack API URL: `/users/me`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation: `get /users/me`

Table Function Columns

The columns of the table function `MyTags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.7 ProfileTimeTrackingsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/profiles/timetracking`

Insert YouTrack API URL: `/users/{id}/profiles/timetracking`

Update YouTrack API URL: `/users/{id}/profiles/timetracking`

Delete YouTrack API URL: `/users/{id}/profiles/timetracking`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/profiles/timetracking`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ProfileTimeTrackingsByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `ProfileTimeTrackingsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
periodFormat_$type	string		☐	
periodFormat_id	string		☐	

12.1.8 SavedQueries: YouTrack Saved Queries

Catalog: YouTrack

Schema: Users

Label: Saved Queries

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `SavedQueries` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.9 SavedQueryById

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: NotRequired

Base Path: `savedQueries[*]`

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SavedQueryById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SavedQueryById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
ringId	string	Ring ID	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_usersCount	int64		☐	

12.1.10 SavedQueryIssues

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `SavedQueryIssues` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.11 SavedQueryIssuesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: NotRequired

Base Path: `savedQueries[*].issues[*]`

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The following parameters can be used to control the behaviour of the table function SavedQueryIssuesByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `SavedQueryIssuesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
query	string	Query	☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	
votes	int32	Votes	☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.12 TagById

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `TagById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	
ow ner_$type	string		☐	
ow ner_avatarUrl	string		☐	
ow ner_banned	boolean		☐	
ow ner_email	string		☐	
ow ner_fullName	string		☐	
ow ner_guest	boolean		☐	
ow ner_id	string		☐	
ow ner_jabberAccountName	string		☐	
ow ner_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.13 TagIssuesByTagId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: NotRequired

Base Path: `tags[*].issues[*]`

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function TagIssuesByTagId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `TagIssuesByTagId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
online	boolean	Online	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
resolved	int64	Resolved	☐	
ringId	string	Ring ID	☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
votes	int32	Votes	☐	
w ikifiedDescription	string	Wikified Description	☐	

12.1.14 Tags

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: NotRequired

Base Path: `tags[*]`

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `Tags` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id_1	string		☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
name	string	Name	☐	
online	boolean	Online	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_ringId	string		☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_usersCount	int64		☐	

12.1.15 UserById

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}`

Insert YouTrack API URL: `/users/{id}`

Update YouTrack API URL: `/users/{id}`

Delete YouTrack API URL: `/users/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserById. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

12.1.16 UserGeneralProfilesBySprintId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/profiles/general`

Insert YouTrack API URL: `/users/{id}/profiles/general`

Update YouTrack API URL: `/users/{id}/profiles/general`

Delete YouTrack API URL: `/users/{id}/profiles/general`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/profiles/general`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserGeneralProfilesBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserGeneralProfilesBySprintId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
dateFieldFormat_$type	string		☐	
dateFieldFormat_datePattern	string		☐	
dateFieldFormat_id	string		☐	
dateFieldFormat_pattern	string		☐	
dateFieldFormat_presentation	string		☐	
id	string	ID	☐	
locale_$type	string		☐	
locale_community	boolean		☐	
locale_id	string		☐	
locale_language	string		☐	
locale_locale	string		☐	
locale_name	string		☐	
timezone_$type	string		☐	
timezone_id	string		☐	
timezone_offset	int32		☐	
timezone_presentation	string		☐	

12.1.17 UserIssueAttachmentSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueAttachmentSavedQueriesByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueAttachmentSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

12.1.18 UserIssueAttachmentTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Base Path: `issues[*].attachments[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueAttachmentTagsByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueAttachmentTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
base64Content	string	Base64 Content	☐	
charset	string	Charset	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
description	string	Description	☐	
draft	boolean	Draft	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
extension	string	Extension	☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
metaData	string	Metadata	☐	
mimeType	string	MIME-type	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
removed	boolean	Removed	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
size	int64	Size	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
thumbnailURL	string	Thumbnail (URL)	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
url	string	URL	☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.19 UserIssueCommentSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueCommentSavedQueriesByUserId. A value must be provided at all times for

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueCommentSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.20 UserIssueCommentTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Base Path: `issues[*].comments[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueCommentTagsByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueCommentTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created_1	int64		☐	
created	int64	Created	☐	
deleted	boolean	Deleted	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated_1	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown_1	boolean		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.21 UserIssueCustomFieldSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueCustomFieldSavedQueriesByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `UserIssueCustomFieldSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.22 UserIssueCustomFieldTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Base Path: `issues[*].customFields[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueCustomFieldTagsByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueCustomFieldTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.23 UserIssueLinkSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueLinkSavedQueriesByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueLinkSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.24 UserIssueLinkSavedQueryTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Base Path: `issues[*].links[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueLinkSavedQueryTagsByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueLinkSavedQueryTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
direction	string	Direction	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
w ikifiedDescription	string	Wikified Description	☐	

12.1.25 UserIssueSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueSavedQueriesByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.26 UserIssueTagSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueTagSavedQueriesByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Table Function Columns

The columns of the table function `UserIssueTagSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type_1	string		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
query	string	Query	☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.27 UserIssueTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Base Path: `issues[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueTagsByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
externalIssue_url	string		☐	
id_1	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.28 UserIssueTagsByUserId1

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Field Selection Method: NotRequired

Base Path: `issues[*].tags[*]`

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserIssueTagsByUserId1. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserIssueTagsByUserId1` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type_1	string		☐	
$type_2	string		☐	
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
commentsCount	int32	Comments Count	☐	
created	int64	Created	☐	
description	string	Description	☐	
draftOwner_$type	string		☐	
draftOwner_avatarUrl	string		☐	
draftOwner_banned	boolean		☐	
draftOwner_email	string		☐	
draftOwner_fullName	string		☐	
draftOwner_guest	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
draftOwner_id	string		☐	
draftOwner_jabberAccountName	string		☐	
draftOwner_login	string		☐	
draftOwner_online	boolean		☐	
draftOwner_ringId	string		☐	
externalIssue_$type	string		☐	
externalIssue_id	string		☐	
externalIssue_key	string		☐	
externalIssue_name	string		☐	
externalIssue_url	string		☐	
id_1	string		☐	
id_2	string		☐	
id	string	ID	☐	
idReadable	string	Readable ID	☐	
isDraft	boolean	Is Draft	☐	
name_1	string		☐	
name	string	Name	☐	
numberInProject	int64	Number in Project	☐	
owner_$type_1	string		☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id_1	string		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_name	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
owner_untagOnResolve	boolean		☐	
parent_$type	string		☐	
parent_direction	string		☐	
parent_id	string		☐	
project_archived	boolean		☐	
project_description	string		☐	
project_fromEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
project_iconUrl	string		☐	
project_replyToEmail	string		☐	
project_shortName	string		☐	
project_startingNumber	int64		☐	
project_template	boolean		☐	
reporter_$type	string		☐	
reporter_avatarUrl	string		☐	
reporter_banned	boolean		☐	
reporter_email	string		☐	
reporter_fullName	string		☐	
reporter_guest	boolean		☐	
reporter_id	string		☐	
reporter_jabberAccountName	string		☐	
reporter_login	string		☐	
reporter_online	boolean		☐	
reporter_ringId	string		☐	
resolved	int64	Resolved	☐	
subtasks_$type	string		☐	
subtasks_direction	string		☐	
subtasks_id	string		☐	
summary	string	Summary	☐	
untagOnResolve_1	boolean		☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
updated	int64	Updated	☐	
updater_$type	string		☐	
updater_avatarUrl	string		☐	
updater_banned	boolean		☐	
updater_email	string		☐	
updater_fullName	string		☐	
updater_guest	boolean		☐	
updater_id	string		☐	
updater_jabberAccountName	string		☐	
updater_login	string		☐	
updater_online	boolean		☐	
updater_ringId	string		☐	
usesMarkdown	boolean	Uses Mark Down	☐	
visibility_$type	string		☐	
visibility_id	string		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	
voters_$type	string		☐	
voters_hasVote	boolean		☐	
voters_id	string		☐	
votes	int32	Votes	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
watchers_$type	string		☐	
watchers_hasStar	boolean		☐	
watchers_id	string		☐	
wikifiedDescription	string	Wikified Description	☐	

12.1.29 UserNotificationProfilesBySprintId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/profiles/notifications`

Insert YouTrack API URL: `/users/{id}/profiles/notifications`

Update YouTrack API URL: `/users/{id}/profiles/notifications`

Delete YouTrack API URL: `/users/{id}/profiles/notifications`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/profiles/notifications`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserNotificationProfilesBySprintId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserNotificationProfilesBySprintId` are shown below. Each column has an SQL data type.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
autoWatchOnComment	boolean	Auto-watch on Comment	☐	
autoWatchOnCreate	boolean	Auto-watch on Create	☐	
autoWatchOnUpdate	boolean	Auto-watch on Update	☐	
autoWatchOnVote	boolean	Auto-watch on Vote	☐	
duplicateClusterNotificationsEnabled	boolean		☐	
emailNotificationsEnabled	boolean	Email Notifications Enabled	☐	
id	string	ID	☐	
jabberNotificationsEnabled	boolean	Jabber Notifications Enabled	☐	
mailboxIntegrationNotificationsEnabled	boolean		☐	
mentionNotificationsEnabled	boolean		☐	
notifyOnOwnChanges	boolean	Notify on Own Changes	☐	
usePlainTextEmails	boolean	Use Plain-text Emails	☐	

12.1.30 Users: YouTrack Users

Catalog: YouTrack

Schema: Users

Label: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users`

Insert YouTrack API URL: `/users`

Update YouTrack API URL: `/users`

Delete YouTrack API URL: `/users`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users`

Table Function Columns

The columns of the table function `Users` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
avatarUrl	string	Avatar (URL)	☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
banned	boolean	Banned	☐	
email	string	Email	☐	
fullName	string	Full Name	☐	
guest	boolean	Guest	☐	
id	string	ID	☐	
jabberAccountName	string	Jabber Account Name	☐	
login	string	Login	☐	
online	boolean	Online	☐	
profiles_$type	string		☐	
profiles_general_$type	string		☐	
profiles_general_id	string		☐	
profiles_id	string		☐	
profiles_notifications_$type	string		☐	
profiles_notifications_autoWatchOnComment	boolean		☐	
profiles_notifications_autoWatchOnCreate	boolean		☐	
profiles_notifications_autoWatchOnUpdate	boolean		☐	
profiles_notifications_autoWatchOnVote	boolean		☐	
profiles_notifications_duplicateClusterNotificationsEnabled	boolean		☐	
profiles_notifications_emailNotificationsEnabled	boolean		☐	
profiles_notifications_id	string		☐	
profiles_notifications_jabberNotificationsEnabled	boolean		☐	
profiles_notifications_mailboxIntegrationNotificationsEnabled	boolean		☐	
profiles_notifications_mentionNotificationsEnabled	boolean		☐	
profiles_notifications_notifyOnOwnChanges	boolean		☐	
profiles_notifications_usePlainTextEmails	boolean		☐	
profiles_timetracking_$type	string		☐	
profiles_timetracking_id	string		☐	
ringId	string	Ring ID	☐	

12.1.31 UserSavedQueriesByUserId

Catalog: YouTrack

Schema: Users

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/savedQueries`

Insert YouTrack API URL: `/users/{id}/savedQueries`

Update YouTrack API URL: `/users/{id}/savedQueries`

Delete YouTrack API URL: `/users/{id}/savedQueries`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/savedQueries`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserSavedQueriesByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `UserSavedQueriesByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
query	string	Query	☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

12.1.32 UserTagsByUserId

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/users/{id}/tags`

Insert YouTrack API URL: `/users/{id}/tags`

Update YouTrack API URL: `/users/{id}/tags`

Delete YouTrack API URL: `/users/{id}/tags`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /users/{id}/tags`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function UserTagsByUserId. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

The columns of the table function `UserTagsByUserId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
color_$type	string		☐	
color_background	string		☐	
color_foreground	string		☐	
color_id	string		☐	
id	string	ID	☐	
name	string	Name	☐	
owner_$type	string		☐	
owner_avatarUrl	string		☐	
owner_banned	boolean		☐	
owner_email	string		☐	
owner_fullName	string		☐	
owner_guest	boolean		☐	
owner_id	string		☐	
owner_jabberAccountName	string		☐	
owner_login	string		☐	
owner_online	boolean		☐	
owner_profiles_$type	string		☐	
owner_profiles_id	string		☐	
owner_ringId	string		☐	
untagOnResolve	boolean		☐	
updateableBy_$type	string		☐	
updateableBy_allUsersGroup	boolean		☐	
updateableBy_icon	string		☐	
updateableBy_id	string		☐	
updateableBy_name	string		☐	
updateableBy_ringId	string		☐	
updateableBy_teamForProject_archived	boolean		☐	
updateableBy_teamForProject_description	string		☐	
updateableBy_teamForProject_fromEmail	string		☐	
updateableBy_teamForProject_iconUrl	string		☐	
updateableBy_teamForProject_replyToEmail	string		☐	
updateableBy_teamForProject_shortName	string		☐	
updateableBy_teamForProject_startingNumber	int64		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
updateableBy_teamForProject_template	boolean		☐	
updateableBy_usersCount	int64		☐	
visibleFor_$type	string		☐	
visibleFor_allUsersGroup	boolean		☐	
visibleFor_icon	string		☐	
visibleFor_id	string		☐	
visibleFor_name	string		☐	
visibleFor_ringId	string		☐	
visibleFor_teamForProject_archived	boolean		☐	
visibleFor_teamForProject_description	string		☐	
visibleFor_teamForProject_fromEmail	string		☐	
visibleFor_teamForProject_iconUrl	string		☐	
visibleFor_teamForProject_replyToEmail	string		☐	
visibleFor_teamForProject_shortName	string		☐	
visibleFor_teamForProject_startingNumber	int64		☐	
visibleFor_teamForProject_template	boolean		☐	
visibleFor_usersCount	int64		☐	

12.1.33 WorkItemById

Catalog: YouTrack

Schema: Users

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/workItems/{id}`

Insert YouTrack API URL: `/workItems/{id}`

Update YouTrack API URL: `/workItems/{id}`

Delete YouTrack API URL: `/workItems/{id}`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /workItems/{id}`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function WorkItemById. A value must be provided at all times for required parameters, but optional

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
id	string	☑		

Table Function Columns

The columns of the table function `WorkItemById` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_profiles_$type	string		☐	
author_profiles_id	string		☐	
author_ringId	string		☐	
created	int64	Created	☐	
creator_$type	string		☐	
creator_avatarUrl	string		☐	
creator_banned	boolean		☐	
creator_email	string		☐	
creator_fullName	string		☐	
creator_guest	boolean		☐	
creator_id	string		☐	
creator_jabberAccountName	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
creator_login	string		☐	
creator_online	boolean		☐	
creator_profiles_$type	string		☐	
creator_profiles_id	string		☐	
creator_ringId	string		☐	
date	int64	Date	☐	
duration_$type	string		☐	
duration_id	string		☐	
duration_minutes	int32		☐	
duration_presentation	string		☐	
id	string	ID	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_draftOwner_$type	string		☐	
issue_draftOwner_avatarUrl	string		☐	
issue_draftOwner_banned	boolean		☐	
issue_draftOwner_email	string		☐	
issue_draftOwner_fullName	string		☐	
issue_draftOwner_guest	boolean		☐	
issue_draftOwner_id	string		☐	
issue_draftOwner_jabberAccountName	string		☐	
issue_draftOwner_login	string		☐	
issue_draftOwner_online	boolean		☐	
issue_draftOwner_ringId	string		☐	
issue_externalIssue_$type	string		☐	
issue_externalIssue_id	string		☐	
issue_externalIssue_key	string		☐	
issue_externalIssue_name	string		☐	
issue_externalIssue_url	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_parent_$type	string		☐	
issue_parent_direction	string		☐	
issue_parent_id	string		☐	
issue_project_archived	boolean		☐	
issue_project_description	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
issue_project_fromEmail	string		☐	
issue_project_iconUrl	string		☐	
issue_project_replyToEmail	string		☐	
issue_project_shortName	string		☐	
issue_project_startingNumber	int64		☐	
issue_project_template	boolean		☐	
issue_reporter_$type	string		☐	
issue_reporter_avatarUrl	string		☐	
issue_reporter_banned	boolean		☐	
issue_reporter_email	string		☐	
issue_reporter_fullName	string		☐	
issue_reporter_guest	boolean		☐	
issue_reporter_id	string		☐	
issue_reporter_jabberAccountName	string		☐	
issue_reporter_login	string		☐	
issue_reporter_online	boolean		☐	
issue_reporter_ringId	string		☐	
issue_resolved	int64		☐	
issue_subtasks_$type	string		☐	
issue_subtasks_direction	string		☐	
issue_subtasks_id	string		☐	
issue_summary	string		☐	
issue_updated	int64		☐	
issue_updater_$type	string		☐	
issue_updater_avatarUrl	string		☐	
issue_updater_banned	boolean		☐	
issue_updater_email	string		☐	
issue_updater_fullName	string		☐	
issue_updater_guest	boolean		☐	
issue_updater_id	string		☐	
issue_updater_jabberAccountName	string		☐	
issue_updater_login	string		☐	
issue_updater_online	boolean		☐	
issue_updater_ringId	string		☐	
issue_usesMarkdown	boolean		☐	
issue_visibility_$type	string		☐	
issue_visibility_id	string		☐	
issue_voters_$type	string		☐	
issue_voters_hasVote	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
issue_voters_id	string		☐	
issue_votes	int32		☐	
issue_watchers_$type	string		☐	
issue_watchers_hasStar	boolean		☐	
issue_watchers_id	string		☐	
issue_wikifiedDescription	string		☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
type_$type	string		☐	
type_autoAttached	boolean		☐	
type_id	string		☐	
type_name	string		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	

12.1.34 WorkItems: YouTrack Work Items

Catalog: YouTrack

Schema: Users

Label: Work Items

This is a read-only table function. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

Select YouTrack API URL: `/workItems`

Insert YouTrack API URL: `/workItems`

Update YouTrack API URL: `/workItems`

Delete YouTrack API URL: `/workItems`

Field Selection Method: NotRequired

Select YouTrack API Operation: `get /workItems`

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function WorkItems. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
author	string	☐		Parameter to filter work items by there author. Could specify few values of database id or login or Hub id or 'me' for current logged in user
createdEnd	int32	☐		The end timestamp of the interval for work items created date.
createdStart	int32	☐		The start timestamp of the interval for work items created date.
creator	string	☐		Parameter to filter work items by there creator. Could specify few values of database id or login or Hub id or 'me' for current logged in user
end	int32	☐		The end timestamp of the interval for work items date.
endDate	datetime	☐		The end date of the interval for work items date.
query	string	☐		Issues search query. Read more about search syntax here: Search Query Reference
start	int32	☐		The start timestamp of the interval for work items date.
startDate	datetime	☐		The start date of the interval for work items date.
updatedEnd	int32	☐		The end timestamp of the interval for work items updated date.
updatedStart	int32	☐		The start timestamp of the interval for work items updated date.

Table Function Columns

The columns of the table function `WorkItems` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
$type	string		☐	
author_$type	string		☐	
author_avatarUrl	string		☐	
author_banned	boolean		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
author_email	string		☐	
author_fullName	string		☐	
author_guest	boolean		☐	
author_id	string		☐	
author_jabberAccountName	string		☐	
author_login	string		☐	
author_online	boolean		☐	
author_profiles_$type	string		☐	
author_profiles_id	string		☐	
author_ringId	string		☐	
created	int64	Created	☐	
creator_$type	string		☐	
creator_avatarUrl	string		☐	
creator_banned	boolean		☐	
creator_email	string		☐	
creator_fullName	string		☐	
creator_guest	boolean		☐	
creator_id	string		☐	
creator_jabberAccountName	string		☐	
creator_login	string		☐	
creator_online	boolean		☐	
creator_profiles_$type	string		☐	
creator_profiles_id	string		☐	
creator_ringId	string		☐	
date	int64	Date	☐	
duration_$type	string		☐	
duration_id	string		☐	
duration_minutes	int32		☐	
duration_presentation	string		☐	
id	string	ID	☐	
issue_$type	string		☐	
issue_commentsCount	int32		☐	
issue_created	int64		☐	
issue_description	string		☐	
issue_draftOwner_$type	string		☐	
issue_draftOwner_avatarUrl	string		☐	
issue_draftOwner_banned	boolean		☐	
issue_draftOwner_email	string		☐	
issue_draftOwner_fullName	string		☐	
issue_draftOwner_guest	boolean		☐	
issue_draftOwner_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
issue_draftOwner_jabberAccountName	string		☐	
issue_draftOwner_login	string		☐	
issue_draftOwner_online	boolean		☐	
issue_draftOwner_ringId	string		☐	
issue_externalIssue_$type	string		☐	
issue_externalIssue_id	string		☐	
issue_externalIssue_key	string		☐	
issue_externalIssue_name	string		☐	
issue_externalIssue_url	string		☐	
issue_id	string		☐	
issue_idReadable	string		☐	
issue_isDraft	boolean		☐	
issue_numberInProject	int64		☐	
issue_parent_$type	string		☐	
issue_parent_direction	string		☐	
issue_parent_id	string		☐	
issue_project_archived	boolean		☐	
issue_project_description	string		☐	
issue_project_fromEmail	string		☐	
issue_project_iconUrl	string		☐	
issue_project_replyToEmail	string		☐	
issue_project_shortName	string		☐	
issue_project_startingNumber	int64		☐	
issue_project_template	boolean		☐	
issue_reporter_$type	string		☐	
issue_reporter_avatarUrl	string		☐	
issue_reporter_banned	boolean		☐	
issue_reporter_email	string		☐	
issue_reporter_fullName	string		☐	
issue_reporter_guest	boolean		☐	
issue_reporter_id	string		☐	
issue_reporter_jabberAccountName	string		☐	
issue_reporter_login	string		☐	
issue_reporter_online	boolean		☐	
issue_reporter_ringId	string		☐	
issue_resolved	int64		☐	
issue_subtasks_$type	string		☐	
issue_subtasks_direction	string		☐	
issue_subtasks_id	string		☐	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Name	Data Type	Label	Required	Documentation
issue_summary	string		☐	
issue_updated	int64		☐	
issue_updater_$type	string		☐	
issue_updater_avatarUrl	string		☐	
issue_updater_banned	boolean		☐	
issue_updater_email	string		☐	
issue_updater_fullName	string		☐	
issue_updater_guest	boolean		☐	
issue_updater_id	string		☐	
issue_updater_jabberAccountName	string		☐	
issue_updater_login	string		☐	
issue_updater_online	boolean		☐	
issue_updater_ringId	string		☐	
issue_usesMarkdown	boolean		☐	
issue_visibility_$type	string		☐	
issue_visibility_id	string		☐	
issue_voters_$type	string		☐	
issue_voters_hasVote	boolean		☐	
issue_voters_id	string		☐	
issue_votes	int32		☐	
issue_watchers_$type	string		☐	
issue_watchers_hasStar	boolean		☐	
issue_watchers_id	string		☐	
issue_wikifiedDescription	string		☐	
text	string	Text	☐	
textPreview	string	Text Preview	☐	
type_$type	string		☐	
type_autoAttached	boolean		☐	
type_id	string		☐	
type_name	string		☐	
updated	int64	Updated	☐	
usesMarkdown	boolean	Uses Mark Down	☐	

13 Schema: Views

13.1 Views

13.1.1 IDTypes

Each YouTrack ID consists of an entity ID, a dash as separator and a sequence number. IDTypes maps the entity ID of YouTrack IDs to an entity name.

Catalog: YouTrack

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Schema: Views

This is a read-only view. The YouTrack API may not support changing the data or the Invantive SQL driver for YouTrack does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the YouTrack API.

View Columns

The columns of the view `IDTypes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
DESCRIPTION	string(80)	Description	☑	
ID	int16	ID	☑	

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Index

- $ -

$type 15, 17, 18, 20, 22, 23, 24, 26, 30, 34, 38, 41, 45, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 65, 72, 79, 85, 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 152, 157, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 262, 264, 266, 268, 273, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 361, 363, 368, 374, 375, 376, 377, 378, 379, 380, 382, 383, 384, 386, 387, 389, 390, 392, 393, 394, 395, 396, 398, 399, 400, 401, 402, 404, 405, 406, 408, 410, 411, 413, 414, 415, 416, 418, 420, 421, 423, 426, 427, 429, 430, 432, 433, 434, 435, 436, 437, 438, 441, 444, 445, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 474, 477, 479, 482, 485, 486, 488, 489, 491, 492, 494, 495, 500, 506, 512, 517, 523, 528, 533, 537, 541, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 661, 662, 665, 667, 670, 672, 673, 675, 678, 680, 683, 686, 689, 691, 693, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 746, 747, 748, 751, 753, 757

$type_1 20, 26, 30, 34, 38, 41, 45, 57, 58, 65, 72, 79, 91, 101, 108, 114, 120, 126, 133, 140, 146, 157, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 378, 379, 380, 382, 383, 384, 389, 390, 395, 399, 400, 401, 402, 404, 405, 406, 408, 415, 416, 429, 432, 433, 434, 435, 436, 438, 441, 444, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 486, 488, 492, 495, 500, 506, 512, 517, 523, 528, 533, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

$type_2 26, 30, 34, 38, 45, 65, 72, 101, 108, 114, 120, 126, 133, 146, 172, 179, 185, 192, 200, 206, 226, 232, 239, 245, 280, 295, 299, 308, 312, 316, 320, 324, 332, 336, 340, 349, 355, 368, 378, 380, 382, 384, 389, 390, 395, 399, 401, 402, 405, 406, 415, 416, 429, 432, 435, 436, 438, 441, 448, 454, 461, 466, 486, 488, 506, 512, 547, 558, 565, 576, 581, 592, 606, 614, 618, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 733, 741

$type_3 185, 192

- A -

Activities 15
ActivityById 17
activityId 18, 20
ActivityPages 18
add-odata-mandatory-filters 2
Administrator Email 52
administratorEmail 52
After Cursor 18, 20
afterCursor 18, 20
Aggregation 266
agile_$type 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
agile_colorCoding_$type 97, 101, 108, 114, 120, 140, 146
agile_colorCoding_id 97, 101, 108, 114, 120, 140, 146
agile_columnSettings_$type 97, 101, 108, 114, 120, 140, 146
agile_columnSettings_id 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_$type 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_archived 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_finish 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_goal 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_id 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_isDefault 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_name 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_start 97, 101, 108, 114, 120, 140, 146
agile_currentSprint_unresolvedIssuesCount 97, 101, 108, 114, 120, 140, 146
agile_estimationField_$type 97, 101, 108, 114, 120, 140, 146
agile_estimationField_aliases 97, 101, 108, 114, 120, 140, 146
agile_estimationField_hasRunningJob 97, 101, 108, 114, 120, 140, 146
agile_estimationField_id 97, 101, 108, 114, 120, 140, 146
agile_estimationField_isAutoAttached 97, 101, 108, 114, 120, 140, 146
agile_estimationField_isDisplayedInIssueList 97, 101, 108, 114, 120, 140, 146
agile_estimationField_isUpdateable 97, 101, 108, 114, 120, 140, 146
agile_estimationField_localizedName 97, 101, 108, 114, 120, 140, 146
agile_estimationField_name 97, 101, 108, 114, 120, 140, 146

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

agile_estimationField_ordinal 97, 101, 108, 114, 120, 140, 146
agile_hideOrphansSwimlane 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
agile_id 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
agile_name 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
agile_originalEstimationField_$type 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_aliases 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_hasRunningJob 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_id 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_isAutoAttached 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_isDisplayedInIssueList 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_isUpdateable 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_localizedName 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_name 97, 101, 108, 114, 120, 140, 146
agile_originalEstimationField_ordinal 97, 101, 108, 114, 120, 140, 146
agile_orphansAtTheTop 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
agile_owner_$type 97, 101, 108, 114, 120, 140, 146
agile_owner_avatarUrl 97, 101, 108, 114, 120, 140, 146
agile_owner_banned 97, 101, 108, 114, 120, 140, 146
agile_owner_email 97, 101, 108, 114, 120, 140, 146
agile_owner_fullName 97, 101, 108, 114, 120, 140, 146
agile_owner_guest 97, 101, 108, 114, 120, 140, 146
agile_owner_id 97, 101, 108, 114, 120, 140, 146
agile_owner_jabberAccountName 97, 101, 108, 114, 120, 140, 146
agile_owner_login 97, 101, 108, 114, 120, 140, 146
agile_owner_online 97, 101, 108, 114, 120, 140, 146
agile_owner_ringId 97, 101, 108, 114, 120, 140, 146
agile_sprintsSettings_$type 97, 101, 108, 114, 120, 140, 146
agile_sprintsSettings_cardOnSeveralSprints 97, 101, 108, 114, 120, 140, 146
agile_sprintsSettings_disableSprints 97, 101, 108, 114, 120, 140, 146
agile_sprintsSettings_explicitQuery 97, 101, 108, 114, 120, 140, 146
agile_sprintsSettings_hideSubtasksOfCards 97, 101, 108, 114, 120, 140, 146
agile_sprintsSettings_id 97, 101, 108, 114, 120, 140, 146
agile_sprintsSettings_isExplicit 97, 101, 108, 114, 120, 140, 146
agile_status_$type 97, 101, 108, 114, 120, 140, 146
agile_status_hasJobs 97, 101, 108, 114, 120, 140, 146
agile_status_id 97, 101, 108, 114, 120, 140, 146
agile_status_valid 97, 101, 108, 114, 120, 140, 146
agile_swimlaneSettings_$type 97, 101, 108, 114, 120, 140, 146
agile_swimlaneSettings_enabled 97, 101, 108, 114, 120, 140, 146
agile_swimlaneSettings_id 97, 101, 108, 114, 120, 140, 146
agile_updateableBy_$type 97, 101, 108, 114, 120, 140, 146
agile_updateableBy_allUsersGroup 97, 101, 108, 114, 120, 140, 146
agile_updateableBy_icon 97, 101, 108, 114, 120, 140, 146
agile_updateableBy_id 97, 101, 108, 114, 120, 140, 146
agile_updateableBy_name 97, 101, 108, 114, 120, 140, 146
agile_updateableBy_ringId 97, 101, 108, 114, 120, 140, 146
agile_updateableBy_usersCount 97, 101, 108, 114, 120, 140, 146
agile_updateableByProjectBased 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
agile_visibleFor_$type 97, 101, 108, 114, 120, 140, 146
agile_visibleFor_allUsersGroup 97, 101, 108, 114, 120, 140, 146
agile_visibleFor_icon 97, 101, 108, 114, 120, 140, 146
agile_visibleFor_id 97, 101, 108, 114, 120, 140, 146
agile_visibleFor_name 97, 101, 108, 114, 120, 140, 146
agile_visibleFor_ringId 97, 101, 108, 114, 120, 140, 146
agile_visibleFor_usersCount 97, 101, 108, 114, 120, 140, 146
agile_visibleForProjectBased 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
Aliases 408, 418, 420, 492
All Users Group 262, 264, 433, 444, 445, 474
Allocated Memory 53
allocatedMemory 53
Allow All Origins 22, 51

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Allow Statistics Collection 52
allowAllOrigins 22, 51
AllowedOriginRestSettings 22
allowStatisticsCollection 52
allUsersGroup 262, 264, 433, 444, 445, 474
analysis-enforce-row-uniqueness 2
api-access-token 2
api-client-id 2
api-client-secret 2
api-pre-expiry-refresh-sec 2
api-redirect-url 2
api-refresh-token 2
api-scope 2
api-token-url 2
api-url 2
AppearanceSettings 23
appearanceSettings_$type 24
appearanceSettings_dateFieldFormat_$type 24
appearanceSettings_dateFieldFormat_datePattern 24
appearanceSettings_dateFieldFormat_id 24
appearanceSettings_dateFieldFormat_pattern 24
appearanceSettings_dateFieldFormat_presentation 24
appearanceSettings_id 24
appearanceSettings_logo_$type 24
appearanceSettings_logo_id 24
appearanceSettings_logo_url 24
appearanceSettings_timeZone_$type 24
appearanceSettings_timeZone_id 24
appearanceSettings_timeZone_offset 24
appearanceSettings_timeZone_presentation 24
Archive Format 377, 378, 379, 380
Archived 26, 30, 34, 38, 41, 45, 58, 65, 72, 79, 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157, 486, 488, 489, 491
archiveFormat 377, 378, 379, 380
article_$type 172, 179
article_$type_1 172, 179
article_content 172, 179, 239, 245, 251, 256
article_content_1 172, 179
article_created 239, 245, 251, 256
article_hasChildren 239, 245, 251, 256
article_hasStar 239, 245, 251, 256
article_id 172, 179
article_id_1 172, 179
article_idReadable 239, 245, 251, 256
article_ordinal 239, 245, 251, 256
article_summary 172, 179, 239, 245, 251, 256
article_summary_1 172, 179
article_updated 239, 245, 251, 256
ArticleById 163
Articles 168
assembleDate 387, 389, 390, 392
Assembly Date 387, 389, 390, 392
AttachmentById 172, 495
Attachments 179, 500
author 15, 18, 20, 757
author_$type 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_$type_1 172, 179
author_avatarUrl 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_avatarUrl_1 172, 179
author_banned 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_banned_1 172, 179
author_email 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_email_1 172, 179
author_fullName 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_fullName_1 172, 179
author_guest 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_guest_1 172, 179
author_id 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_id_1 172, 179
author_jabberAccountName 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_jabberAccountName_1 172, 179
author_login 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_login_1 172, 179
author_online 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_online_1 172, 179
author_profiles_$type 15, 17, 753, 757
author_profiles_id 15, 17, 753, 757
author_ringId 15, 17, 20, 172, 179, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
author_ringId_1 172, 179
autoAttached 55, 57
Auto-attached 55, 57
Auto-watch on Comment 746

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Auto-watch on Create 746
Auto-watch on Update 746
Auto-watch on Vote 746
autoWatchOnComment 746
autoWatchOnCreate 746
autoWatchOnUpdate 746
autoWatchOnVote 746
Available Disk Space 377, 378, 379, 380
Available Memory 53
Available Processors 53
availableDiskSpace 377, 378, 379, 380
availableMemory 53
availableProcessors 53
Avatar (URL) 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
avatarUrl 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747

- B -

Backup Cancelled 376
Backup in Progress 376
backupCancelled 376
backupError_$type 376
backupError_date 376
backupError_errorMessage 376
backupError_id 376
backupInProgress 376
backupStatus_$type 377, 378, 379, 380
backupStatus_backupCancelled 377, 378, 379, 380
backupStatus_backupError_$type 377, 378, 379, 380
backupStatus_backupError_date 377, 378, 379, 380
backupStatus_backupError_errorMessage 377, 378, 379, 380
backupStatus_backupError_id 377, 378, 379, 380
backupStatus_backupInProgress 377, 378, 379, 380
backupStatus_id 377, 378, 379, 380
Banned 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
Base URL 52
Base64 Content 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
base64Content 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
base64Content_1 172, 179, 185, 192
baseUrl 52
Before Cursor 18, 20
beforeCursor 18, 20
BLOB Preferred 604
Blob String Cache Hit Rate 53
BLOB_PREFERRED 604
blobStringsCacheHitRate 53
BOL_RESPONSE_CACHE_MAX_AGE_SEC 604
buildBundleElementId 387
bulk-delete-page-size-rows 2
bulk-insert-page-size-bytes 2
bulk-insert-page-size-rows 2
bundle_$type 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 486, 488, 489, 491
bundle_$type_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488
bundle_id 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 486, 488, 489, 491
bundle_id_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488
bundle_isUpdateable 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 486, 488, 489, 491
bundle_isUpdateable_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488

- C -

Cached Results Count in DB Queries Cache 53
cachedResultsCountInDBQueriesCache 53
canBeEmpty 408, 421, 423, 492
categories 15, 18, 20
category_$type 15, 17, 20
category_id 15, 17, 20
Charset 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
charset_1 172, 179, 185, 192
ChildArticleAttachments 185
ChildArticleAttachmentsById 192
ChildArticleComments 200
ChildArticleCommentsById 206
ChildArticles 213
ChildArticlesById 219
ChildChildArticles 226

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ChildChildArticlesById 232
color_$type 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 448, 454, 466, 470, 479, 482, 486, 488, 489, 491, 547, 587, 592, 599, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 737, 741, 751
color_$type_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488
color_background 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 448, 454, 466, 470, 479, 482, 486, 488, 489, 491, 547, 587, 592, 599, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 737, 741, 751
color_background_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488
color_foreground 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 448, 454, 466, 470, 479, 482, 486, 488, 489, 491, 547, 587, 592, 599, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 737, 741, 751
color_foreground_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488
color_id 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 387, 389, 390, 392, 395, 396, 398, 399, 411, 413, 415, 416, 427, 429, 430, 432, 448, 454, 466, 470, 479, 482, 486, 488, 489, 491, 547, 587, 592, 599, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 737, 741, 751
color_id_1 389, 390, 395, 399, 415, 416, 429, 432, 486, 488
colorCoding_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
colorCoding_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_aliases 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_hasRunningJob 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_isAutoAttached 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_isDisplayedInIssueList 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_isUpdateable 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_localizedName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_field_ordinal 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
columnSettings_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
comment_$type 172, 179, 268, 495, 500
comment_$type_1 172, 179
comment_created 172, 179, 268, 495, 500
comment_created_1 172, 179
comment_deleted 268, 495, 500
comment_id 172, 179, 268, 495, 500
comment_id_1 172, 179
comment_text 172, 179, 268, 495, 500
comment_text_1 172, 179
comment_textPreview 268, 495, 500
comment_updated 172, 179, 268, 495, 500
comment_updated_1 172, 179
comment_usesMarkdown 268, 495, 500
CommentAttachments 239, 506
CommentAttachmentsByIssueId 245, 512
Comments 251, 517
Comments Count 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
CommentsByIssueId 256, 523
commentsCount 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
commentsCount_1 349, 355, 368, 547, 558, 565, 576, 581, 592
condition_$type 408, 423, 492
condition_id 408, 423, 492
condition_parent_$type 423
condition_parent_canBeEmpty 423
condition_parent_emptyFieldText 423
condition_parent_hasRunningJob 423
condition_parent_id 423
condition_parent_isPublic 423
condition_parent_ordinal 423
Content 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Content Type 604
content_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
content_2 185, 192, 200, 206, 213, 219, 226, 232
content_3 185, 192, 200, 206, 213, 219, 226, 232
content_4 226, 232
content_5 226, 232
CONTENT_TYPE 604
created 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 753, 757
created_1 26, 30, 101, 108, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 295, 299, 308, 312, 349, 355, 368, 495, 500, 506, 512, 517, 523, 547, 558, 565, 576, 581, 592, 606, 614, 626, 630, 694, 699, 703, 707
created_2 172, 179, 185, 192, 200, 206, 226, 232, 239, 245, 280, 506, 512
created_3 185, 192
createdBy_$type 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_$type_1 45
createdBy_avatarUrl 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_banned 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_email 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_fullName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_guest 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_id 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_id_1 45
createdBy_jabberAccountName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_login 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_name 45
createdBy_online 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_profiles_$type 26, 30, 34, 38, 41, 45
createdBy_profiles_id 26, 30, 34, 38, 41, 45
createdBy_ringId 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
createdBy_untagOnResolve 45
createdEnd 757
createdStart 757
Creation Date 374, 375
creationDate 374, 375
creator 757
creator_$type 753, 757
creator_avatarUrl 753, 757
creator_banned 753, 757
creator_email 753, 757
creator_fullName 753, 757
creator_guest 753, 757
creator_id 753, 757
creator_jabberAccountName 753, 757
creator_login 753, 757
creator_online 753, 757
creator_profiles_$type 753, 757
creator_profiles_id 753, 757
creator_ringId 753, 757
Cron Expression 377, 378, 379, 380
cronExpression 377, 378, 379, 380
currentSprint_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_$type_1 65, 72, 126, 133
currentSprint_agile_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_agile_hideOrphansSwimlane 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_agile_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_agile_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_agile_orphansAtTheTop 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_agile_updateableByProjectBased 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_agile_visibleForProjectBased 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_archived 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_commentsCount 65, 72, 126, 133
currentSprint_created 65, 72, 126, 133
currentSprint_description 65, 72, 126, 133
currentSprint_finish 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_goal 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_id_1 65, 72, 126, 133
currentSprint_idReadable 65, 72, 126, 133
currentSprint_isDefault 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_isDraft 65, 72, 126, 133

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

currentSprint_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_numberInProject 65, 72, 126, 133
currentSprint_previousSprint_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_previousSprint_archived 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_previousSprint_finish 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_previousSprint_goal 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_previousSprint_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_previousSprint_isDefault 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_previousSprint_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_previousSprint_start 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_previousSprint_unresolvedIssuesCount 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_resolved 65, 72, 126, 133
currentSprint_start 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_summary 65, 72, 126, 133
currentSprint_unresolvedIssuesCount 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
currentSprint_updated 65, 72, 126, 133
currentSprint_usesMarkdown 65, 72, 126, 133
currentSprint_votes 65, 72, 126, 133
currentSprint_wikifiedDescription 65, 72, 126, 133
cursor 18, 20
CustomFieldAggregatedUserSavedQueriesByUserBundleId 382
CustomFieldAggregatedUsersByUserBundleId 383
CustomFieldAggregatedUserTagsByUserBundleId 384
CustomFieldBuildBundles 386
CustomFieldBuildByBuildBundleId 386
CustomFieldBuildByBuildBundleIdAndElementId 387
CustomFieldBuildValues 389
CustomFieldBuildValuesByBuildBundleId 390
CustomFieldBuildValuesByBuildBundleId1 392
CustomFieldEnumBundleByEnumFieldBundleId 393
CustomFieldEnumBundles 394
CustomFieldEnumBundleValuesByEnumFieldBundleId 395
CustomFieldEnumByEnumFieldBundleId 396
CustomFieldEnumByEnumFieldBundleIdAndElementId 398
CustomFieldEnumValues 399
CustomFieldIndividualUsers 400
CustomFieldIndividualUserSavedQueries 401
CustomFieldIndividualUserSavedQueriesByUserBundleId 402
CustomFieldIndividualUsersByUserBundleId 404
CustomFieldIndividualUserTags 405
CustomFieldIndividualUserTagsByUserBundleId 406
CustomFieldInstancesByCustomFieldPrototypeId 408
CustomFieldOwnedFieldByOwnedFieldBundleId 410
CustomFieldOwnedFieldByOwnedFieldBundleIdAndElementId 411
CustomFieldOwnedFieldByValueId 413
CustomFieldOwnedFields 414
CustomFieldOwnedFieldValues 415
CustomFieldOwnedFieldValuesByOwnedFieldBundleId 416
customFields 418, 500, 506, 517, 528, 543, 547, 558, 571, 576, 599
CustomFieldsByCustomFieldPrototypeId 420
CustomFieldsByCustomFieldPrototypeId2 421
CustomFieldsByCustomFieldPrototypeId3 423
CustomFieldsByIssueId 533
CustomFieldStateBundleById 426
CustomFieldStateBundles 427
CustomFieldStateBundleValues2ByStateBundleId 427
CustomFieldStateBundleValuesByStateBundleId 429
CustomFieldStateByStateBundleIdAndElementId 430
CustomFieldStateValues 432
CustomFieldUserBundles 433
CustomFieldUserBundleUsers 434
CustomFieldUserBundleUserSavedQueries 435
CustomFieldUserBundleUserTags 436
CustomFieldUserByUserBundleId 437
CustomFieldUserByUserBundleId1 438
CustomFieldUserByUserBundleId2 441
CustomFieldUserGroupsByUserBundleId 444
CustomFieldUserGroupsByUserBundleId1 445
CustomFieldUsers 448
CustomFieldUsersByUserBundleId 448
CustomFieldUsersByUserBundleId1 451
CustomFieldUsersByUserBundleId2 454
CustomFieldUsersByUserBundleId3 457
CustomFieldUsersByUserBundleId4 459
CustomFieldUsersByUserBundleId5 461
CustomFieldUsersByUserBundleId6 464
CustomFieldUsersByUserBundleId7 466
CustomFieldUsersByUserBundleId8 470
CustomFieldUsersByUserBundleId9 472
CustomFieldUsersByUserBundleIdAndGroupId 474

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

CustomFieldUsersByUserId 477
CustomFieldUserTagsByUserBundleId 479
CustomFieldUserTagsByUserBundleId2 482
CustomFieldVersionByProjectVersionBundleId 486
CustomFieldVersions 486
CustomFieldVersionValues 486
CustomFieldVersionValuesByProjectVersionBundleId 488
CustomFieldVersionValuesByProjectVersionBundleId2 489
CustomFieldVersionValuesByProjectVersionBundleId3 491

- D -

Database Background Threads 53
Database Location 53
Database Queries Cache Hit Rate 53
Database Size 53
databaseBackgroundThreads 53
DatabaseBackupById 374
DatabaseBackups 375
DatabaseBackupSettingBackupStatuses 376
DatabaseBackupSettings 377
databaseLocation 53
databaseQueriesCacheHitRate 53
databaseSize 53
Date 753, 757
DATE_ENDED 604
DATE_STARTED 604
dateFieldFormat_$type 23, 693
dateFieldFormat_datePattern 23, 693
dateFieldFormat_id 23, 693
dateFieldFormat_pattern 23, 693
dateFieldFormat_presentation 23, 693
Days a Week 56
daysAWeek 56
Deleted 30, 108, 280, 285, 308, 312, 506, 512, 517, 523, 614, 630, 703, 707
DESCRIPTION 761
description_1 26, 30, 34, 38, 41, 45, 65, 72, 349, 355, 368, 389, 390, 395, 399, 415, 416, 429, 432, 486, 488, 547, 558, 565, 576, 581, 592
Directed 266
Direction 38, 120, 320, 324, 345, 349, 355, 541, 554, 558, 565, 571, 576, 581, 638, 642, 720, 724
download-error-400-bad-request-max-tries 2
download-error-400-bad-request-sleep-initial-ms 2
download-error-400-bad-request-sleep-max-ms 2
download-error-400-bad-request-sleep-multiplicator 2
download-error-408-request-timeout-max-tries 2
download-error-408-request-timeout-sleep-initial-ms 2
download-error-408-request-timeout-sleep-max-ms 2
download-error-408-request-timeout-sleep-multiplicator 2
download-error-422-bad-request-max-tries 2
download-error-422-bad-request-sleep-initial-ms 2
download-error-422-bad-request-sleep-max-ms 2
download-error-422-bad-request-sleep-multiplicator 2
download-error-429-too-many-requests-max-tries 2
download-error-429-too-many-requests-sleep-initial-ms 2
download-error-429-too-many-requests-sleep-max-ms 2
download-error-429-too-many-requests-sleep-multiplicator 2
download-error-502-server-unavailable-max-tries 2
download-error-502-server-unavailable-sleep-initial-ms 2
download-error-502-server-unavailable-sleep-max-ms 2
download-error-502-server-unavailable-sleep-multiplicator 2
download-error-503-server-unavailable-max-tries 2
download-error-503-server-unavailable-sleep-initial-ms 2
download-error-503-server-unavailable-sleep-max-ms 2
download-error-503-server-unavailable-sleep-multiplicator 2
download-error-504-gateway-timeout-max-tries 2
download-error-504-gateway-timeout-sleep-initial-ms 2
download-error-504-gateway-timeout-sleep-max-ms 2
download-error-504-gateway-timeout-sleep-multiplicator 2
download-error-590-network-connect-timeout-max-tries 2
download-error-590-network-connect-timeout-sleep-initial-ms 2
download-error-590-network-connect-timeout-sleep-max-ms 2
download-error-590-network-connect-timeout-sleep-multiplicator 2
download-error-599-network-connect-timeout-max-tries 2
download-error-599-network-connect-timeout-sleep-initial-ms 2
download-error-599-network-connect-timeout-sleep-max-ms 2
download-error-599-network-connect-timeout-sleep-multiplicator 2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

download-error-argument-exception-max-tries 2
download-error-argument-exception-sleep-initial-ms 2
download-error-argument-exception-sleep-max-ms 2
download-error-argument-exception-sleep-multiplicator 2
download-error-internet-down-max-tries 2
download-error-internet-down-sleep-initial-ms 2
download-error-internet-down-sleep-max-ms 2
download-error-internet-down-sleep-multiplicator 2
download-error-io-exception-max-tries 2
download-error-io-exception-sleep-initial-ms 2
download-error-io-exception-sleep-max-ms 2
download-error-io-exception-sleep-multiplicator 2
download-error-json-exception-max-tries 2
download-error-json-exception-sleep-initial-ms 2
download-error-json-exception-sleep-max-ms 2
download-error-json-exception-sleep-multiplicator 2
download-error-other-exception-max-tries 2
download-error-other-exception-sleep-initial-ms 2
download-error-other-exception-sleep-max-ms 2
download-error-other-exception-sleep-multiplicator 2
download-error-socket-exception-max-tries 2
download-error-socket-exception-sleep-initial-ms 2
download-error-socket-exception-sleep-max-ms 2
download-error-socket-exception-sleep-multiplicator 2
download-error-web-exception-max-tries 2
download-error-web-exception-sleep-initial-ms 2
download-error-web-exception-sleep-max-ms 2
download-error-web-exception-sleep-multiplicator 2
download-error-web-not-implemented-max-tries 2
download-error-web-not-implemented-sleep-initial-ms 2
download-error-web-not-implemented-sleep-max-ms 2
download-error-web-not-implemented-sleep-multiplicator 2
download-error-web-timeout-max-tries 2
download-error-web-timeout-sleep-initial-ms 2
download-error-web-timeout-sleep-max-ms 2
download-error-web-timeout-sleep-multiplicator 2
download-error-web-unauthorized-max-tries 2
download-error-web-unauthorized-sleep-initial-ms 2
download-error-web-unauthorized-sleep-max-ms 2
download-error-web-unauthorized-sleep-multiplicator 2
Draft 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
draft_1 172, 179, 185, 192
draftOwner_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_avatarUrl 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_banned 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_email 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_fullName 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_guest 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

draftOwner_jabberAccountName 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_login 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_online 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
draftOwner_profiles_$type 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
draftOwner_profiles_id 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
draftOwner_ringId 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
Driver 1
DRY_RUN 604
duplicateClusterNotificationsEnabled 746
Duration (ms) 604
duration_$type 753, 757
duration_id 753, 757
duration_minutes 753, 757
DURATION_MS 604
duration_presentation 753, 757

- E -

Email 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
Email Notifications Enabled 746
emailNotificationsEnabled 746
emailSettings_$type 50
emailSettings_anonymous 50
emailSettings_from 50
emailSettings_host 50
emailSettings_id 50
emailSettings_isEnabled 50
emailSettings_login 50
emailSettings_mailProtocol 50
emailSettings_port 50
emailSettings_replyTo 50
emailSettings_sslKey_$type 50
emailSettings_sslKey_id 50
emailSettings_sslKey_name 50
Empty Field Text 408, 421, 423, 492
emptyFieldText 408, 421, 423, 492
end 15, 18, 20, 757
End Date 604
endDate 757
enumBundleElementId 398
Error 49
Error Message Code 604
Error Message Text 604
ERROR_MESSAGE_CODE 604
ERROR_MESSAGE_TEXT 604
estimationField_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_aliases 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_fieldDefaults_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_fieldDefaults_canBeEmpty 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_fieldDefaults_emptyFieldText 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_fieldDefaults_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_fieldDefaults_isPublic 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_fieldType_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_fieldType_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

estimationField_hasRunningJob 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_isAutoAttached 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_isDisplayedInIssueList 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_isUpdateable 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_localizedName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
estimationField_ordinal 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
Extension 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
extension_1 172, 179, 185, 192
externalArticle_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
externalArticle_$type_1 185, 192, 200, 206, 213, 219, 226, 232
externalArticle_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
externalArticle_id_1 185, 192, 200, 206, 213, 219, 226, 232
externalArticle_key 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
externalArticle_key_1 185, 192, 200, 206, 213, 219, 226, 232
externalArticle_name 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
externalArticle_name_1 185, 192, 200, 206, 213, 219, 226, 232
externalArticle_url 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
externalArticle_url_1 185, 192, 200, 206, 213, 219, 226, 232
externalIssue_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
externalIssue_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
externalIssue_key 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
externalIssue_name 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
externalIssue_url 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

- F -

Fail on Error 604
FAIL_ON_ERROR 604
field_$type 15, 17, 20, 408, 423, 492
field_aliases 408, 423, 492
field_fieldDefaults_$type 423
field_fieldDefaults_canBeEmpty 423
field_fieldDefaults_emptyFieldText 423
field_fieldDefaults_id 423
field_fieldDefaults_isPublic 423
field_fieldType_$type 423
field_fieldType_id 423
field_hasRunningJob 408, 423, 492
field_id 15, 17, 20, 408, 423, 492
field_isAutoAttached 408, 423, 492
field_isDisplayedInIssueList 408, 423, 492
field_isUpdateable 408, 423, 492
field_localizedName 408, 423, 492
field_name 15, 17, 20, 408, 423, 492
field_ordinal 408, 423, 492

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

field_presentation 15, 17, 20
fieldDefaults_$type 408, 418, 420, 492
fieldDefaults_canBeEmpty 408, 418, 420, 492
fieldDefaults_emptyFieldText 408, 418, 420, 492
fieldDefaults_id 408, 418, 420, 492
fieldDefaults_isPublic 408, 418, 420, 492
fieldDefaults_parent_$type 408, 418, 420, 492
fieldDefaults_parent_aliases 408, 418, 420, 492
fieldDefaults_parent_hasRunningJob 408, 418, 420, 492
fieldDefaults_parent_id 408, 418, 420, 492
fieldDefaults_parent_isAutoAttached 408, 418, 420, 492
fieldDefaults_parent_isDisplayedInIssueList 408, 418, 420, 492
fieldDefaults_parent_isUpdateable 408, 418, 420, 492
fieldDefaults_parent_localizedName 408, 418, 420, 492
fieldDefaults_parent_name 408, 418, 420, 492
fieldDefaults_parent_ordinal 408, 418, 420, 492
fieldType_$type 408, 418, 420, 492
fieldType_id 408, 418, 420, 492
Files to Keep 377, 378, 379, 380
filesToKeep 377, 378, 379, 380
Finish 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
First Day of Week 56
firstDayOfWeek 56
force-case-sensitive-identifiers 2
forced-casing-identifiers 2
From Email 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
fromEmail 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
Full Database Size 53
Full Name 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
fullDatabaseSize 53
fullName 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747

- G -

GlobalSettings 24
Goal 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
GroupById 262
Groups 264
Guest 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747

- H -

Has After 18, 20
Has Before 18, 20
Has Children 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
Has Running Job 387, 389, 390, 392, 395, 396, 398, 399, 408, 411, 413, 415, 416, 418, 420, 423, 427, 429, 430, 432, 486, 488, 489, 491, 492
Has Star 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
hasAfter 18, 20
hasBefore 18, 20
hasChildren 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
hasChildren_1 185, 192, 200, 206, 213, 219, 226, 232
hasChildren_2 226, 232
hasRunningJob 387, 389, 390, 392, 395, 396, 398, 399, 408, 411, 413, 415, 416, 418, 420, 423, 427, 429, 430, 432, 486, 488, 489, 491, 492
hasRunningJob_1 389, 390, 395, 399, 408, 415, 416, 429, 432, 486, 488, 492
hasStar 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
hasStar_1 185, 192, 200, 206, 213, 219, 226, 232
hasStar_2 226, 232
hideOrphansSwimlane 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
HTTP Disk Cache Maximum Age (sec) 604
HTTP Memory Cache Maximum Age (sec) 604
HTTP Method 604
HTTP Status Code 604
HTTP_DISK_CACHE_MAX_AGE_SEC 604
HTTP_DISK_CACHE_SAVE 604
HTTP_DISK_CACHE_USE 604
HTTP_MEMORY_CACHE_MAX_AGE_SEC 604
HTTP_MEMORY_CACHE_SAVE 604
HTTP_MEMORY_CACHE_USE 604
HTTP_METHOD 604
HTTP_STATUS_CODE 604
http-disk-cache-compression-level 2
http-disk-cache-directory 2
http-disk-cache-ignore-write-errors 2
http-disk-cache-max-age-sec 2
http-get-timeout-max-ms 2
http-get-timeout-ms 2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

http-memory-cache-compression-level 2
http-memory-cache-max-age-sec 2
http-post-timeout-max-ms 2
http-post-timeout-ms 2

- I -

Icon 262, 264, 433, 444, 445, 474
Icon (URL) 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
iconUrl 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
id 17, 58, 72, 85, 91, 97, 101, 108, 114, 120, 133, 140, 146, 163, 172, 192, 206, 219, 232, 245, 256, 262, 266, 268, 273, 275, 280, 285, 290, 299, 304, 312, 324, 332, 340, 345, 349, 355, 363, 368, 374, 382, 383, 384, 386, 387, 390, 392, 393, 395, 396, 398, 402, 404, 406, 408, 410, 411, 413, 416, 420, 421, 423, 426, 427, 429, 430, 437, 438, 441, 444, 445, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 474, 477, 479, 482, 485, 488, 489, 491, 495, 512, 523, 533, 537, 541, 554, 565, 581, 587, 592, 606, 610, 614, 618, 642, 650, 656, 672, 675, 680, 683, 686, 691, 693, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 746, 748, 751, 753
id_1 20, 26, 30, 34, 38, 41, 45, 57, 58, 65, 72, 79, 91, 101, 108, 114, 120, 126, 133, 140, 146, 157, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 378, 379, 380, 382, 383, 384, 389, 390, 395, 399, 400, 401, 402, 404, 405, 406, 408, 415, 416, 429, 432, 433, 434, 435, 436, 438, 441, 444, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 486, 488, 492, 495, 500, 506, 512, 517, 523, 528, 533, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
id_2 26, 30, 34, 38, 45, 65, 72, 101, 108, 114, 120, 126, 133, 146, 172, 179, 185, 192, 200, 206, 226, 232, 239, 245, 280, 295, 299, 308, 312, 316, 320, 324, 332, 336, 340, 349, 355, 368, 378, 380, 382, 384, 389, 390, 395, 399, 401, 402, 405, 406, 415, 416, 429, 432, 435, 436, 438, 441, 448, 454, 461, 466, 486, 488, 506, 512, 547, 558, 565, 576, 581, 592, 606, 614, 618, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 733, 741
id_3 185, 192
idReadable 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
idReadable_1 185, 192, 200, 206, 213, 219, 226, 232, 349, 355, 368, 547, 558, 565, 576, 581, 592
idReadable_2 226, 232
IDTypes 761
ignore-http-400-errors 2
ignore-http-401-errors 2
ignore-http-402-errors 2
ignore-http-403-errors 2
ignore-http-404-errors 2
ignore-http-422-errors 2
ignore-http-429-errors 2
ignore-http-500-errors 2
ignore-http-502-errors 2
ignore-http-503-errors 2
ignore-unknown-path-type 2
ignore-values-unknown-path 2
Installation Folder 53
installationFolder 53
InstanceCustomFields 492
invalid-json-on-get-max-tries 2
invalid-json-on-get-sleep-initial-ms 2
invalid-json-on-get-sleep-max-ms 2
invalid-json-on-get-sleep-multiplicator 2
invalid-json-on-post-max-tries 2
invalid-json-on-post-sleep-initial-ms 2
invalid-json-on-post-sleep-max-ms 2
invalid-json-on-post-sleep-multiplicator 2
invantive-sql-compress-sparse-arrays 2
invantive-sql-correct-invalid-date 2
invantive-sql-forward-filters-to-data-containers 2
invantive-sql-share-byte-arrays 2
invantive-sql-share-strings 2
invantive-sql-shuffle-fetch-results-data-containers 2
invantive-use-cache 2
Is Application Read-only 52
Is Auto-attached 408, 418, 420, 492
Is Default 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
Is Displayed in Issue List 408, 418, 420, 492

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Is Draft 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
Is On 377, 378, 379, 380
Is Public 408, 421, 423, 492
Is Resolved 427, 429, 430, 432
Is RTL 50
Is Updateable 382, 383, 384, 386, 389, 390, 393, 394, 395, 399, 400, 401, 402, 404, 405, 406, 408, 410, 414, 415, 416, 418, 420, 426, 427, 429, 432, 433, 434, 435, 436, 437, 444, 448, 485, 486, 488, 492
isApplicationReadOnly 52
isAutoAttached 408, 418, 420, 492
isDefault 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
isDisplayedInIssueList 408, 418, 420, 492
isDraft 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
isDraft_1 349, 355, 368, 547, 558, 565, 576, 581, 592
isOn 377, 378, 379, 380
isPublic 408, 421, 423, 492
isResolved 427, 429, 430, 432
isRTL 50
Issue Tags 45, 361, 547, 658
issue_$type 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_commentsCount 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_created 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_description 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_draftOwner_$type 753, 757
issue_draftOwner_avatarUrl 753, 757
issue_draftOwner_banned 753, 757
issue_draftOwner_email 753, 757
issue_draftOwner_fullName 753, 757
issue_draftOwner_guest 753, 757
issue_draftOwner_id 753, 757
issue_draftOwner_jabberAccountName 753, 757
issue_draftOwner_login 753, 757
issue_draftOwner_online 753, 757
issue_draftOwner_ringId 753, 757
issue_externalIssue_$type 753, 757
issue_externalIssue_id 753, 757
issue_externalIssue_key 753, 757
issue_externalIssue_name 753, 757
issue_externalIssue_url 753, 757
issue_id 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_idReadable 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_isDraft 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_numberInProject 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_parent_$type 753, 757
issue_parent_direction 753, 757
issue_parent_id 753, 757
issue_project_archived 753, 757
issue_project_description 753, 757
issue_project_fromEmail 753, 757
issue_project_iconUrl 753, 757
issue_project_replyToEmail 753, 757
issue_project_shortName 753, 757
issue_project_startingNumber 753, 757
issue_project_template 753, 757
issue_reporter_$type 753, 757
issue_reporter_avatarUrl 753, 757
issue_reporter_banned 753, 757
issue_reporter_email 753, 757
issue_reporter_fullName 753, 757
issue_reporter_guest 753, 757
issue_reporter_id 753, 757
issue_reporter_jabberAccountName 753, 757
issue_reporter_login 753, 757
issue_reporter_online 753, 757
issue_reporter_ringId 753, 757
issue_resolved 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_subtasks_$type 753, 757
issue_subtasks_direction 753, 757
issue_subtasks_id 753, 757
issue_summary 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_updated 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_updater_$type 753, 757
issue_updater_avatarUrl 753, 757
issue_updater_banned 753, 757
issue_updater_email 753, 757
issue_updater_fullName 753, 757

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

issue_updater_guest 753, 757
issue_updater_id 753, 757
issue_updater_jabberAccountName 753, 757
issue_updater_login 753, 757
issue_updater_online 753, 757
issue_updater_ringId 753, 757
issue_usesMarkdown 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_visibility_$type 753, 757
issue_visibility_id 753, 757
issue_voters_$type 753, 757
issue_voters_hasVote 753, 757
issue_voters_id 753, 757
issue_votes 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
issue_watchers_$type 753, 757
issue_watchers_hasStar 753, 757
issue_watchers_id 753, 757
issue_wikifiedDescription 268, 280, 285, 495, 500, 506, 512, 517, 523, 753, 757
IssueAttachments 26
IssueAttachmentsBySavedQueryId 606
IssueById 537, 610
IssueComments 30
IssueCommentsBySavedQueryId 614
IssueCustomFields 34
IssueCustomFieldsBySavedQueryId 618
IssueLinks 38
IssueLinksByIssueId 541
IssueLinkTypes 266
IssueLinkTypesById 266
issueQuery 15, 18, 20
Issues 41, 543, 623
IssuesAttachments 626
IssuesComments 630
IssuesCustomFields 634
IssuesLinks 638
IssuesLinksById 642
IssuesTags 646
IssueTagAttachmentIssuesByTagId 268
IssueTagById 273
IssueTagById2 275
IssueTagCommentAttachmentIssuesByTagId 280
IssueTagCommentIssuesByTagId 285
IssueTagCustomFieldIssuesByTagId 290
IssueTagIssueAttachments 295
IssueTagIssueAttachmentsById 299
IssueTagIssueById 304
IssueTagIssueComments 308
IssueTagIssueCommentsById 312
IssueTagIssueCustomFields 316
IssueTagIssueLinks 320
IssueTagIssueLinksById 324
IssueTagIssues 328
IssueTagIssuesCustomFieldsById 332
IssueTagIssuesTags 336
IssueTagIssueTagsById 340
IssueTagLinkIssuesByTagId 345
IssueTagLinkIssuesByTagId1 349
IssueTagLinkTrimmedIssuesByTagId 355
IssueTags 45, 361, 547, 658
IssueTagsBySavedQueryId 650
isUpdateable 382, 383, 384, 386, 389, 390, 393, 394, 395, 399, 400, 401, 402, 404, 405, 406, 408, 410, 414, 415, 416, 418, 420, 426, 427, 429, 432, 433, 434, 435, 436, 437, 444, 448, 485, 486, 488, 492

- J -

Jabber Account Name 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
Jabber Notifications Enabled 746
jabberAccountName 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
jabberNotificationsEnabled 746
jabberSettings_$type 50
jabberSettings_host 50
jabberSettings_id 50
jabberSettings_isEnabled 50
jabberSettings_login 50
jabberSettings_port 50
jabberSettings_serviceName 50
join-set-points-per-request 2

- L -

leader_$type 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_$type_1 45
leader_avatarUrl 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_banned 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_email 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_fullName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_guest 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_id 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_id_1 45

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

leader_jabberAccountName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_login 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_name 45
leader_online 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_profiles_$type 26, 30, 34, 38, 41, 45
leader_profiles_id 26, 30, 34, 38, 41, 45
leader_ringId 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
leader_untagOnResolve 45
License 49
license_$type 24
license_error 24
license_id 24
license_license 24
license_username 24
Licenses 49
limit-partition-calls-left 2
Link 374, 375
LinkById 554
LinkIssues 558
LinkIssuesByIssueId 565
Links 571
LinkTrimmedIssues 576
LinkTrimmedIssuesByIssueId 581
linkType_$type 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_aggregation 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_directed 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_id 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_localizedName 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_localizedSourceToTarget 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_localizedTargetToSource 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_name 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_readOnly 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_sourceToTarget 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
linkType_targetToSource 345, 349, 355, 541, 554, 558, 565, 571, 576, 581
locale_$type 50, 693
locale_community 50, 693
locale_id 50, 693
locale_language 50, 693
locale_locale 50, 693
locale_name 50, 693
LocaleSettings 50
localeSettings_$type 24
localeSettings_id 24
localeSettings_isRTL 24
localeSettings_locale_$type 24
localeSettings_locale_community 24
localeSettings_locale_id 24
localeSettings_locale_language 24
localeSettings_locale_locale 24
localeSettings_locale_name 24
Localized Name 266, 395, 396, 398, 399, 408, 418, 420, 427, 429, 430, 432, 492
Localized Source to Target 266
Localized Target to Source 266
localizedName 266, 395, 396, 398, 399, 408, 418, 420, 427, 429, 430, 432, 492
localizedSourceToTarget 266
localizedTargetToSource 266
Location 377, 378, 379, 380
Login 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
log-native-calls-to-disk-max-events 2
log-native-calls-to-disk-max-seconds 2
log-native-calls-to-disk-on-error 2
log-native-calls-to-disk-on-success 2
log-native-calls-to-trace 2
logo_$type 23
logo_id 23
logo_url 23
Logs Location 53
logsLocation 53

- M -

mailboxIntegrationNotificationsEnabled 746
Max Export Items 52
Max Upload File Size 52
maxExportItems 52
maximum-discovered-column-count 2
maximum-length-identifiers 2
max-odata-filters 2
maxUploadFileSize 52
max-url-length-accepted 2
max-url-length-desired 2
Me 661
mentionNotificationsEnabled 746
Metadata 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
metaData_1 172, 179, 185, 192

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

metadata-cache-max-age-sec 2
mimeType 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
MIME-type 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
mimeType_1 172, 179, 185, 192
Minutes a Day 56
minutesADay 56
MyIssueTags 662
MySavedQueries 665
MySavedQueriessues 667
MyTags 670

- N -

Name 26, 30, 34, 38, 41, 45, 55, 57, 58, 65, 72, 79, 85, 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 152, 157, 172, 179, 185, 192, 239, 245, 262, 264, 266, 268, 273, 280, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 374, 375, 378, 380, 382, 384, 387, 389, 390, 392, 395, 396, 398, 399, 401, 402, 405, 406, 408, 411, 413, 415, 416, 418, 420, 427, 429, 430, 432, 433, 435, 436, 438, 441, 444, 445, 448, 451, 454, 461, 464, 466, 470, 474, 477, 479, 482, 486, 488, 489, 491, 492, 495, 500, 506, 512, 528, 533, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
name_1 26, 34, 45, 58, 65, 72, 79, 91, 101, 114, 126, 133, 146, 157, 172, 179, 185, 192, 295, 299, 316, 332, 336, 340, 389, 390, 395, 399, 415, 416, 429, 432, 486, 488, 606, 618, 626, 634, 646, 650, 694, 699, 712, 716, 733, 741
Native Platform Scalar Requests 604
NATIVEPLATFORMSCALARREQUESTS 604
Notification Analyzer Threads 53
notificationAnalyzerThreads 53
NotificationSettings 50
notificationSettings_$type 24
notificationSettings_emailSettings_$type 24
notificationSettings_emailSettings_anonymous 24
notificationSettings_emailSettings_from 24
notificationSettings_emailSettings_host 24
notificationSettings_emailSettings_id 24
notificationSettings_emailSettings_isEnabled 24
notificationSettings_emailSettings_login 24
notificationSettings_emailSettings_mailProtocol 24
notificationSettings_emailSettings_port 24
notificationSettings_emailSettings_replyTo 24
notificationSettings_id 24
notificationSettings_jabberSettings_$type 24
notificationSettings_jabberSettings_host 24
notificationSettings_jabberSettings_id 24
notificationSettings_jabberSettings_isEnabled 24
notificationSettings_jabberSettings_login 24
notificationSettings_jabberSettings_port 24
notificationSettings_jabberSettings_serviceName 24
NotifiedUserSavedQuerySettings 378
NotifiedUserSettings 379
NotifiedUserTagSettings 380
Notify on Own Changes 746
notifyOnOwnChanges 746
npt 604
Nullable 408, 421, 423, 492
Number in Project 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
numberInProject 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
numberInProject_1 349, 355, 368, 547, 558, 565, 576, 581, 592

- O -

oauth-unauthorized-max-tries 2
oauth-unauthorized-sleep-initial-ms 2
oauth-unauthorized-sleep-max-ms 2
oauth-unauthorized-sleep-multiplicator 2
Online 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
onlineUsers_$type 53
onlineUsers_id 53
onlineUsers_users 53
Ordinal 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 387, 389, 390, 392, 395, 396, 398, 399, 408, 411, 413, 415, 416, 418, 420, 423, 427, 429, 430, 432, 486, 488, 489, 491, 492

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

ordinal_1 185, 192, 200, 206, 213, 219, 226, 232, 389, 390, 395, 399, 408, 415, 416, 429, 432, 486, 488, 492
ordinal_2 226, 232
ORIG_SYSTEM_GROUP 604
ORIG_SYSTEM_REFERENCE 604
Original System Group 604
Original System Reference 604
originalEstimationField_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_aliases 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_fieldDefaults_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_fieldDefaults_canBeEmpty 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_fieldDefaults_emptyFieldText 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_fieldDefaults_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_fieldDefaults_isPublic 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_fieldType_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_fieldType_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_hasRunningJob 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_isAutoAttached 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_isDisplayedInIssueList 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_isUpdateable 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_localizedName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
originalEstimationField_ordinal 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
orphansAtTheTop 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
ownedBundleElementId 411
owner_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_$type_1 336, 340, 646, 650, 733, 741
owner_avatarUrl 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_banned 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_email 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_fullName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_guest 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_id_1 336, 340, 646, 650, 733, 741

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

owner_jabberAccountName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_login 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_name 336, 340, 646, 650, 733, 741
owner_online 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_profiles_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 411, 413, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_profiles_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 411, 413, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_ringId 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 411, 413, 415, 416, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
owner_untagOnResolve 336, 340, 646, 650, 733, 741

- P -

parent_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 421, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
parent_$type_1 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_aliases 421
parent_commentsCount 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_created 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_description 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_direction 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
parent_fieldDefaults_$type 421
parent_fieldDefaults_canBeEmpty 421
parent_fieldDefaults_emptyFieldText 421
parent_fieldDefaults_id 421
parent_fieldDefaults_isPublic 421
parent_fieldType_$type 421
parent_fieldType_id 421
parent_hasRunningJob 421
parent_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 421, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
parent_id_1 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_idReadable 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_isAutoAttached 421
parent_isDisplayedInIssueList 421
parent_isDraft 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_isUpdateable 421

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parent_linkType_$type 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_aggregation 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_directed 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_id 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_localizedName 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_localizedSourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_localizedTargetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_name 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_readOnly 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_sourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_linkType_targetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
parent_localizedName 421
parent_name 421
parent_numberInProject 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_ordinal 421
parent_resolved 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_summary 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_updated 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_usesMarkdown 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_votes 349, 355, 368, 547, 558, 565, 576, 581, 592
parent_wikifiedDescription 349, 355, 368, 547, 558, 565, 576, 581, 592
parentArticle_$type 185, 192, 200, 206, 226, 232, 239, 245
parentArticle_base64Content 185, 192, 239, 245
parentArticle_charset 185, 192, 239, 245
parentArticle_content 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_content_1 185, 192, 200, 206, 213, 219, 226, 232
parentArticle_content_2 226, 232
parentArticle_content_3 226, 232
parentArticle_created 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_created_1 185, 192, 200, 206, 213, 219, 226, 232, 239, 245
parentArticle_created_2 185, 192, 200, 206, 226, 232
parentArticle_draft 185, 192, 239, 245
parentArticle_extension 185, 192, 239, 245
parentArticle_externalArticle_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_externalArticle_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_externalArticle_key 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_externalArticle_name 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_externalArticle_url 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_hasChildren 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_hasChildren_1 185, 192, 200, 206, 213, 219, 226, 232
parentArticle_hasChildren_2 226, 232
parentArticle_hasStar 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_hasStar_1 185, 192, 200, 206, 213, 219, 226, 232
parentArticle_hasStar_2 226, 232
parentArticle_id 185, 192, 200, 206, 226, 232, 239, 245
parentArticle_idReadable 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parentArticle_idReadable_1 185, 192, 200, 206, 213, 219, 226, 232
parentArticle_idReadable_2 226, 232
parentArticle_metaData 185, 192, 239, 245
parentArticle_mimeType 185, 192, 239, 245
parentArticle_name 185, 192, 239, 245
parentArticle_ordinal 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_ordinal_1 185, 192, 200, 206, 213, 219, 226, 232
parentArticle_ordinal_2 226, 232
parentArticle_parentArticle_content 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_parentArticle_created 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_parentArticle_hasChildren 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_parentArticle_hasStar 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_parentArticle_idReadable 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_parentArticle_ordinal 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_parentArticle_summary 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_parentArticle_updated 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_project_archived 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_project_description 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_project_fromEmail 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_project_iconUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_project_replyToEmail 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_project_shortName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_project_startingNumber 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_project_template 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_removed 185, 192, 239, 245
parentArticle_reporter_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_reporter_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_size 185, 192, 239, 245
parentArticle_summary 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_summary_1 185, 192, 200, 206, 213, 219, 226, 232
parentArticle_summary_2 226, 232
parentArticle_summary_3 226, 232
parentArticle_text 200, 206
parentArticle_updated 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updated_1 185, 192, 200, 206, 213, 219, 226, 232, 239, 245
parentArticle_updated_2 185, 192, 200, 206, 226, 232

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

parentArticle_updatedBy_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_updatedBy_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_url 185, 192, 239, 245
parentArticle_visibility_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
parentArticle_visibility_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
partition-slot-based-rate-limit-length-ms 2
partition-slot-based-rate-limit-slots 2
Payload 604
PAYLOAD_TEXT 604
Pending Async Jobs 53
pendingAsyncJobs 53
periodFormat_$type 672
periodFormat_id 672
pre-request-delay-ms 2
previousSprint_$type 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
previousSprint_agile_$type 97, 101, 108, 114, 120, 140, 146
previousSprint_agile_hideOrphansSwimlane 97, 101, 108, 114, 120, 140, 146
previousSprint_agile_id 97, 101, 108, 114, 120, 140, 146
previousSprint_agile_name 97, 101, 108, 114, 120, 140, 146
previousSprint_agile_orphansAtTheTop 97, 101, 108, 114, 120, 140, 146
previousSprint_agile_updateableByProjectBased 97, 101, 108, 114, 120, 140, 146
previousSprint_agile_visibleForProjectBased 97, 101, 108, 114, 120, 140, 146
previousSprint_archived 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
previousSprint_finish 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
previousSprint_goal 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
previousSprint_id 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
previousSprint_isDefault 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
previousSprint_name 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
previousSprint_previousSprint_$type 97, 101, 108, 114, 120, 140, 146
previousSprint_previousSprint_archived 97, 101, 108, 114, 120, 140, 146
previousSprint_previousSprint_finish 97, 101, 108, 114, 120, 140, 146
previousSprint_previousSprint_goal 97, 101, 108, 114, 120, 140, 146
previousSprint_previousSprint_id 97, 101, 108, 114, 120, 140, 146
previousSprint_previousSprint_isDefault 97, 101, 108, 114, 120, 140, 146
previousSprint_previousSprint_name 97, 101, 108, 114, 120, 140, 146
previousSprint_previousSprint_start 97, 101, 108, 114, 120, 140, 146
previousSprint_previousSprint_unresolvedIssuesCount 97, 101, 108, 114, 120, 140, 146
previousSprint_start 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
previousSprint_unresolvedIssuesCount 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
profiles_$type 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_general_$type 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

profiles_general_id 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_id 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 434, 435, 436, 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_$type 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_autoWatchOnComment 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_autoWatchOnCreate 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_autoWatchOnUpdate 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_autoWatchOnVote 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_duplicateClusterNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_emailNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_id 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_jabberNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_mailboxIntegrationNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_mentionNotificationsEnabled 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_notifyOnOwnChanges 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_notifications_usePlainTextEmails 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_timetracking_$type 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
profiles_timetracking_id 438, 441, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
ProfileTimeTrackingsByUserId 672
project_$type 349, 368, 547, 558, 565, 592
project_archived 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
project_archived_1 185, 192, 200, 206, 213, 219, 226, 232
project_commentsCount 349, 368, 547, 558, 565, 592
project_created 349, 368, 547, 558, 565, 592
project_createdBy_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

project_createdBy_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_createdBy_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_description 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
project_description_1 185, 192, 200, 206, 213, 219, 226, 232, 349, 368, 547, 558, 565, 592
project_fromEmail 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
project_fromEmail_1 185, 192, 200, 206, 213, 219, 226, 232
project_iconUrl 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
project_iconUrl_1 185, 192, 200, 206, 213, 219, 226, 232
project_id 349, 368, 547, 558, 565, 592
project_idReadable 349, 368, 547, 558, 565, 592
project_isDraft 349, 368, 547, 558, 565, 592
project_leader_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

project_leader_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_leader_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_numberInProject 349, 368, 547, 558, 565, 592
project_replyToEmail 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
project_replyToEmail_1 185, 192, 200, 206, 213, 219, 226, 232
project_resolved 349, 368, 547, 558, 565, 592
project_shortName 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
project_shortName_1 185, 192, 200, 206, 213, 219, 226, 232
project_startingNumber 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
project_startingNumber_1 185, 192, 200, 206, 213, 219, 226, 232
project_summary 349, 368, 547, 558, 565, 592
project_team_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_team_allUsersGroup 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_team_icon 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_team_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_team_name 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_team_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
project_team_usersCount 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 423, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

project_template 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 408, 423, 492, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
project_template_1 185, 192, 200, 206, 213, 219, 226, 232
project_updated 349, 368, 547, 558, 565, 592
project_usesMarkdown 349, 368, 547, 558, 565, 592
project_votes 349, 368, 547, 558, 565, 592
project_wikifiedDescription 349, 368, 547, 558, 565, 592
ProjectActivityPages 20
ProjectBySprintId 58
projectCustomField_$type 290, 528, 533
projectCustomField_canBeEmpty 290, 528, 533
projectCustomField_emptyFieldText 290, 528, 533
projectCustomField_hasRunningJob 290, 528, 533
projectCustomField_id 290, 528, 533
projectCustomField_isPublic 290, 528, 533
projectCustomField_ordinal 290, 528, 533
ProjectIssues 65
ProjectIssuesBySprintId 72
Projects 79

- Q -

query 378, 382, 401, 402, 435, 438, 441, 451, 461, 464, 477, 500, 506, 517, 528, 543, 547, 558, 571, 576, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 665, 667, 673, 675, 678, 680, 694, 703, 712, 720, 729, 733, 748, 757

- R -

Readable ID 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
readOnly 266
Read-only 266
Release Date 486, 488, 489, 491
Released 486, 488, 489, 491
releaseDate 486, 488, 489, 491
Removed 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
removed_1 172, 179, 185, 192
Reply-to Email 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
replyToEmail 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
Report Calculator Threads 53
reportCalculatorThreads 53
reporter_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_$type_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_$type_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_$type_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_avatarUrl 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_avatarUrl_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_avatarUrl_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_avatarUrl_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_banned 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_banned_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

reporter_banned_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_banned_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_email 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_email_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_email_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_email_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_fullName 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_fullName_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_fullName_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_fullName_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_guest 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_guest_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_guest_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_guest_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_id_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_id_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_id_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_jabberAccountName 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_jabberAccountName_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_jabberAccountName_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_jabberAccountName_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_login 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_login_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_login_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_login_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_online 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

reporter_online_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_online_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_online_3 185, 192, 200, 206, 213, 219, 226, 232
reporter_profiles_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
reporter_profiles_$type_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_profiles_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
reporter_profiles_id_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_ringId 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
reporter_ringId_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
reporter_ringId_2 185, 192, 200, 206, 213, 219, 226, 232
reporter_ringId_3 185, 192, 200, 206, 213, 219, 226, 232
requested-page-size 2
Requests per Second 53
requests-parallel-max 2
requestsPerSecond 53
Resolved 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
resolved_1 349, 355, 368, 547, 558, 565, 576, 581, 592
Response Cache Maximum Age (sec) 604
RestSettings 51
restSettings_$type 24
restSettings_allowAllOrigins 24
restSettings_id 24
Result BLOB 604
Result Text 604
RESULT_BLOB 604
RESULT_DATE_TIME_UTC 604
RESULT_NUMBER 604
RESULT_TEXT 604
Reverse 15, 18, 20
Ring ID 262, 264, 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 433, 434, 435, 436, 438, 441, 444, 445, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 474, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
ringId 262, 264, 378, 379, 380, 382, 383, 384, 400, 401, 402, 404, 405, 406, 433, 434, 435, 436, 438, 441, 444, 445, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 474, 477, 479, 482, 658, 661, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 691, 747
Run without Actions 604

- S -

Save HTTP Disk Cache 604
Save HTTP Memory Cache 604
Saved Queries 654, 673
SavedQueries 654, 673
SavedQueryById 656, 675
SavedQueryIssues 678
SavedQueryIssuesByUserId 680
service-url 2
Short Name 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
shortName 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
simulate-http-400-errors 2
simulate-http-400-errors-percentage 2
simulate-http-401-errors 2
simulate-http-401-errors-percentage 2
simulate-http-403-errors 2
simulate-http-403-errors-percentage 2
simulate-http-408-errors 2
simulate-http-408-errors-percentage 2
simulate-http-429-errors 2
simulate-http-429-errors-percentage 2
simulate-http-500-errors 2
simulate-http-500-errors-percentage 2
simulate-http-502-errors 2
simulate-http-502-errors-percentage 2
simulate-http-503-errors 2
simulate-http-503-errors-percentage 2
simulate-http-protocol-errors 2
simulate-http-protocol-errors-percentage 2
simulate-http-timeout-errors 2
simulate-http-timeout-errors-percentage 2

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Size 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 374, 375, 495, 500, 506, 512, 606, 627, 694, 699
size_1 172, 179, 185, 192
slot-based-rate-limit-length-ms 2
slot-based-rate-limit-slots 2
Source to Target 266
sourceToTarget 266
SprintById 85
SprintById1 91
SprintById2 97
SprintIssueAttachmentsBySprintId 101
SprintIssueCommentsBySprintId 108
SprintIssueCustomFieldsBySprintId 114
SprintIssueLinksBySprintId 120
SprintIssues 126
SprintIssuesBySprintId 133
SprintIssuesBySprintId1 140
SprintIssueTagsBySprintId 146
Sprints 152
Sprints1 157
sprintsSettings_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_cardOnSeveralSprints 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_archived 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_finish 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_goal 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_isDefault 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_start 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_defaultSprint_unresolvedIssuesCount 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_disableSprints 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_explicitQuery 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_hideSubtasksOfCards 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_isExplicit 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_aliases 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_hasRunningJob 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_isAutoAttached 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_isDisplayedInIssueList 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_isUpdateable 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_localizedName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
sprintsSettings_sprintSyncField_ordinal 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
standardize-identifiers 2
standardize-identifiers-casing 2
start 15, 18, 20, 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157, 757
Start Date 604
Start Time 53
startDate 757
startedTime 53
Starting Number 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
startingNumber 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
stateBundleElementId 430
status_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
status_hasJobs 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
status_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
status_valid 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
subtasks_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
subtasks_$type_1 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_commentsCount 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_created 349, 355, 368, 547, 558, 565, 576, 581, 592

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

subtasks_description 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_direction 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
subtasks_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
subtasks_id_1 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_idReadable 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_isDraft 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_linkType_$type 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_aggregation 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_directed 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_id 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_localizedName 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_localizedSourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_localizedTargetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_name 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_readOnly 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_sourceToTarget 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_linkType_targetToSource 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
subtasks_numberInProject 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_resolved 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_summary 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_updated 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_usesMarkdown 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_votes 349, 355, 368, 547, 558, 565, 576, 581, 592
subtasks_wikifiedDescription 349, 355, 368, 547, 558, 565, 576, 581, 592
Succesful 604
SUCCESSFUL 604
Summary 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
summary_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 349, 355, 368, 547, 558, 565, 576, 581, 592
summary_2 185, 192, 200, 206, 213, 219, 226, 232
summary_3 185, 192, 200, 206, 213, 219, 226, 232
summary_4 226, 232
summary_5 226, 232
swagger-specification-file 2
swagger-specification-http-disk-cache-max-age-sec 2
swagger-specification-url 2
swimlaneSettings_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
swimlaneSettings_enabled 58, 65, 72, 79, 85, 91, 126, 133, 152, 157

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

swimlaneSettings_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
SystemSettings 52
systemSettings_$type 24
systemSettings_administratorEmail 24
systemSettings_allowStatisticsCollection 24
systemSettings_baseUrl 24
systemSettings_id 24
systemSettings_isApplicationReadOnly 24
systemSettings_maxExportItems 24
systemSettings_maxUploadFileSize 24

- T -

TagById 587, 683
TagIssuesByTagId 363, 592, 686
TagIssuesByTagId2 368
Tags 599, 689
Target member 15, 17, 20
Target to Source 266
targetMember 15, 17, 20
targetToSource 266
team_$type 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
team_allUsersGroup 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
team_icon 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
team_id 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
team_name 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
team_ringId 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
team_teamForProject_archived 26, 30, 34, 38, 41, 45
team_teamForProject_description 26, 30, 34, 38, 41, 45
team_teamForProject_fromEmail 26, 30, 34, 38, 41, 45
team_teamForProject_iconUrl 26, 30, 34, 38, 41, 45
team_teamForProject_replyToEmail 26, 30, 34, 38, 41, 45
team_teamForProject_shortName 26, 30, 34, 38, 41, 45
team_teamForProject_startingNumber 26, 30, 34, 38, 41, 45
team_teamForProject_template 26, 30, 34, 38, 41, 45
team_usersCount 26, 30, 34, 38, 41, 45, 58, 65, 72, 79
teamForProject_archived 262, 264, 433, 444, 445, 474
teamForProject_createdBy_$type 262, 264, 445, 474
teamForProject_createdBy_avatarUrl 262, 264, 445, 474
teamForProject_createdBy_banned 262, 264, 445, 474
teamForProject_createdBy_email 262, 264, 445, 474
teamForProject_createdBy_fullName 262, 264, 445, 474
teamForProject_createdBy_guest 262, 264, 445, 474
teamForProject_createdBy_id 262, 264, 445, 474
teamForProject_createdBy_jabberAccountName 262, 264, 445, 474
teamForProject_createdBy_login 262, 264, 445, 474
teamForProject_createdBy_online 262, 264, 445, 474
teamForProject_createdBy_ringId 262, 264, 445, 474
teamForProject_description 262, 264, 433, 444, 445, 474
teamForProject_fromEmail 262, 264, 433, 444, 445, 474
teamForProject_iconUrl 262, 264, 433, 444, 445, 474
teamForProject_leader_$type 262, 264, 445, 474
teamForProject_leader_avatarUrl 262, 264, 445, 474
teamForProject_leader_banned 262, 264, 445, 474
teamForProject_leader_email 262, 264, 445, 474
teamForProject_leader_fullName 262, 264, 445, 474
teamForProject_leader_guest 262, 264, 445, 474
teamForProject_leader_id 262, 264, 445, 474
teamForProject_leader_jabberAccountName 262, 264, 445, 474
teamForProject_leader_login 262, 264, 445, 474
teamForProject_leader_online 262, 264, 445, 474
teamForProject_leader_ringId 262, 264, 445, 474
teamForProject_replyToEmail 262, 264, 433, 444, 445, 474
teamForProject_shortName 262, 264, 433, 444, 445, 474
teamForProject_startingNumber 262, 264, 433, 444, 445, 474
teamForProject_team_$type 262, 264, 445, 474
teamForProject_team_allUsersGroup 262, 264, 445, 474
teamForProject_team_icon 262, 264, 445, 474
teamForProject_team_id 262, 264, 445, 474
teamForProject_team_name 262, 264, 445, 474
teamForProject_team_ringId 262, 264, 445, 474
teamForProject_team_usersCount 262, 264, 445, 474
teamForProject_template 262, 264, 433, 444, 445, 474
Telemetry 53
Template 26, 30, 34, 38, 41, 45, 58, 65, 72, 79

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

Text 22, 30, 108, 200, 206, 239, 245, 251, 256, 280, 285, 308, 312, 506, 512, 517, 523, 614, 630, 703, 707, 753, 757
Text Index Size 53
Text Preview 30, 108, 280, 285, 308, 312, 506, 512, 517, 523, 614, 630, 703, 707, 753, 757
textIndexSize 53
textPreview 30, 108, 280, 285, 308, 312, 506, 512, 517, 523, 614, 630, 703, 707, 753, 757
Thumbnail (URL) 26, 101, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
thumbnailURL 26, 101, 268, 280, 295, 299, 495, 500, 506, 512, 606, 626, 694, 699
Timeout (sec) 604
TIMEOUT_SEC 604
Timestamp 15, 17, 20
TimeTrackingSettings 54
TimeTrackingSettingWorkItemTypes 55
TimeTrackingSettingWorkItemTypesByWorkItemTypeId 55
TimeTrackingWorkTimeSettings 56
timezone_$type 23, 693
timezone_id 23, 693
timezone_offset 23, 693
timezone_presentation 23, 693
Total Transactions 53
totalTransactions 53
Transaction ID 604
TRANSACTION_ID 604
Transactions per Second 53
transactionsPerSecond 53
type_$type 753, 757
type_autoAttached 753, 757
type_id 753, 757
type_name 753, 757
Types 494

- U -

Unresolved Issue Count 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
unresolvedIssuesCount 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 157
untagOnResolve 45, 146, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 380, 384, 405, 406, 436, 448, 454, 466, 470, 479, 482, 547, 587, 592, 599, 646, 650, 658, 662, 670, 683, 686, 689, 699, 707, 716, 724, 733, 737, 741, 751
untagOnResolve_1 336, 340, 741
updateableBy_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_allUsersGroup 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_icon 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_ringId 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_teamForProject_archived 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

updateableBy_teamForProject_description 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_teamForProject_fromEmail 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_teamForProject_iconUrl 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_teamForProject_replyToEmail 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_teamForProject_shortName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_teamForProject_startingNumber 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_teamForProject_template 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableBy_usersCount 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 672, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
updateableByProjectBased 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
Updated 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 753, 757
updated_1 26, 30, 101, 108, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 295, 299, 308, 312, 349, 355, 368, 495, 500, 506, 512, 517, 523, 547, 558, 565, 576, 581, 592, 606, 614, 626, 630, 694, 699, 703, 707
updated_2 172, 179, 185, 192, 200, 206, 226, 232, 239, 245, 280, 506, 512
updated_3 185, 192
updatedBy_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_$type_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_avatarUrl 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_avatarUrl_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_banned 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_banned_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_email 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_email_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_fullName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_fullName_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_guest 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_guest_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_id_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_jabberAccountName 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_jabberAccountName_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_login 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

updatedBy_login_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_online 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_online_1 185, 192, 200, 206, 213, 219, 226, 232
updatedBy_profiles_$type 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_profiles_id 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_ringId 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
updatedBy_ringId_1 185, 192, 200, 206, 213, 219, 226, 232
updatedEnd 757
updatedStart 757
updater_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_avatarUrl 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_banned 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_email 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_fullName 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_guest 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_jabberAccountName 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_login 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_online 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
updater_profiles_$type 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
updater_profiles_id 268, 275, 280, 285, 290, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599
updater_ringId 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
Uptime 53

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

URL 26, 101, 172, 179, 185, 192, 239, 245, 268, 280, 295, 299, 495, 500, 506, 512, 604, 606, 626, 694, 699
url_1 172, 179, 185, 192
Use HTTP Disk Cache 604
Use HTTP Memory Cache 604
Use Plain-text Emails 746
use-batch-insert 2
Used Memory 53
usedMemory 53
use-http-disk-cache-read 2
use-http-disk-cache-write 2
use-http-memory-cache-read 2
use-http-memory-cache-write 2
usePlainTextEmails 746
User Name 49
UserById 691
UserGeneralProfilesBySprintId 693
userGroupId 474
userId 461, 464, 466, 470, 472
UserIssueAttachmentSavedQueriesByUserId 694
UserIssueAttachmentTagsByUserId 699
UserIssueCommentSavedQueriesByUserId 703
UserIssueCommentTagsByUserId 707
UserIssueCustomFieldSavedQueriesByUserId 712
UserIssueCustomFieldTagsByUserId 716
UserIssueLinkSavedQueriesByUserId 720
UserIssueLinkSavedQueryTagsByUserId 724
UserIssueSavedQueriesByUserId 729
UserIssueTagSavedQueriesByUserId 733
UserIssueTagsByUserId 737
UserIssueTagsByUserId1 741
username 49
UserNotificationProfilesBySprintId 746
Users 747
Users Count 262, 264, 433, 444, 445, 474
UserSavedQueriesByUserId 748
usersCount 262, 264, 433, 444, 445, 474
UserTagsByUserId 751
Uses Mark Down 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 753, 757
usesMarkdown 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 753, 757
usesMarkdown_1 30, 108, 280, 285, 308, 312, 349, 355, 368, 506, 512, 517, 523, 547, 558, 565, 576, 581, 592, 614, 630, 703, 707

- V -

versionBundleElementId 491
visibility_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
visibility_$type_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523
visibility_$type_2 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
visibility_$type_3 172, 179, 185, 192, 200, 206, 213, 219, 226, 232
visibility_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
visibility_id_1 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 268, 280, 285, 495, 500, 506, 512, 517, 523
visibility_id_2 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256
visibility_id_3 172, 179, 185, 192, 200, 206, 213, 219, 226, 232
visibleFor_$type 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

visibleFor_allUsersGroup 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_icon 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_id 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_name 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_ringId 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_teamForProject_archived 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_teamForProject_description 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_teamForProject_fromEmail 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_teamForProject_iconUrl 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_teamForProject_replyToEmail 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_teamForProject_shortName 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_teamForProject_startingNumber 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_teamForProject_template 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleFor_usersCount 58, 65, 72, 79, 85, 91, 126, 133, 152, 157, 273, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 361, 363, 368, 438, 441, 448, 451, 454, 461, 464, 466, 470, 477, 479, 482, 547, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 662, 665, 667, 670, 673, 675, 678, 680, 683, 686, 689, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 748, 751
visibleForProjectBased 58, 65, 72, 79, 85, 91, 126, 133, 152, 157
voters_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.

voters_hasVote 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
voters_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
Votes 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
votes_1 349, 355, 368, 547, 558, 565, 576, 581, 592

- W -

watchers_$type 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
watchers_hasStar 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
watchers_id 26, 30, 34, 38, 41, 45, 101, 108, 114, 120, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
Wikified Description 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
WikifiedDescription 26, 30, 34, 38, 41, 45, 65, 72, 101, 108, 114, 120, 126, 133, 140, 146, 268, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 363, 368, 438, 441, 448, 454, 461, 466, 495, 500, 506, 512, 517, 523, 528, 533, 537, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 658, 662, 667, 678, 680, 686, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741
WikifiedDescription_1 349, 355, 368, 547, 558, 565, 576, 581, 592
Work Items 757
WorkItemById 753
WorkItems 757
workItemTypeId 55
WorkItemTypeTimeTrackingSettings 57
workTimeSettings_$type 54, 57
workTimeSettings_daysAWeek 54, 57
workTimeSettings_firstDayOfWeek 54, 57
workTimeSettings_id 54, 57
workTimeSettings_minutesADay 54, 57

- Y -

YouTrack 1, 15, 17, 18, 20, 22, 23, 24, 26, 30, 34, 38, 41, 45, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 65, 72, 79, 85, 91, 97, 101, 108, 114, 120, 126, 133, 140, 146, 152, 157, 163, 168, 172, 179, 185, 192, 200, 206, 213, 219, 226, 232, 239, 245, 251, 256, 262, 264, 266, 268, 273, 275, 280, 285, 290, 295, 299, 304, 308, 312, 316, 320, 324, 328, 332, 336, 340, 345, 349, 355, 361, 363, 368, 374, 375, 376, 377, 378, 379, 380, 382, 383, 384, 386, 387, 389, 390, 392, 393, 394, 395, 396, 398, 399, 400, 401, 402, 404, 405, 406, 408, 410, 411, 413, 414, 415, 416, 418, 420, 421, 423, 426, 427, 429, 430, 432, 433, 434, 435, 436, 437, 438, 441, 444, 445, 448, 451, 454, 457, 459, 461, 464, 466, 470, 472, 474, 477, 479, 482, 485, 486, 488, 489, 491, 492, 494, 495, 500, 506, 512, 517, 523, 528, 533, 537, 541, 543, 547, 554, 558, 565, 571, 576, 581, 587, 592, 599, 604, 606, 610, 614, 618, 623, 626, 630, 634, 638, 642, 646, 650, 654, 656, 658, 661, 662, 665, 667, 670, 672, 673, 675, 678, 680, 683, 686, 689, 691, 693, 694, 699, 703, 707, 712, 716, 720, 724, 729, 733, 737, 741, 746, 747, 748, 751, 753, 757, 761

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.



Invantive B.V.
Biesteweg 11
3849 RD Hierden
the Netherlands

Tel: +31 88 00 26 500
Fax: +31 84 22 58 178
info@invantive.com
invantive.com

IBAN NL25 BUNQ 2098 2586 07
Chamber of Industry and Commerce
13031406
VAT NL812602377B01
RSIN 8122602377
Managing Director: Guido Leenders
Registered office: Roermond

(C) Copyright 2004-2025 Invantive Software B.V., the Netherlands. All rights reserved.
24.0.92
29/06/2026, 20:11
ISBN 978-94-6302-000-8: